



Appendix for Test report



Appendix A: DTS (6 dB) Bandwidth

In this document, the "DTS6dBBW" refers to the measured "DTS (6 dB) Bandwidth" value. In this Appendix, the "fc(DTS6dBBW)" refers to the centre of the measured "DTS6dBBW". The introduction of the "fc(DTS6dBBW)" is due to that other measurements use it as the spectrum analyzer setting.

For measurements on smart antenna systems (devices with multiple transmit chains), the test is performed at each chain, and used as respective results for each chain.


Part I - Test Results

Test Mode	Test Channel	Frequency[MHz]	DTS6dBBW[MHz]	Verdict
TM1_Ch0	L	2402	0.67	pass
TM1_Ch19	M	2440	0.68	pass
TM1_Ch39	H	2480	0.67	pass



Part II - Test Plots

2.1 TM1_Ch0_L






2.2 TM1_Ch19_M





2.3 TM1_Ch39_H





Appendix B: Occupied Bandwidth

For measurements on smart antenna systems (devices with multiple transmit chains), the test is performed at each chain, and used as respective results for each chain.


Part I - Test Results

Test Mode	Test Channel	Frequency[MHz]	Occupied Bandwidth [MHz]	Verdict
TM1 _Ch0	L	2402	1.07	pass
TM1 _Ch19	M	2440	1.07	pass
TM1 _Ch39	H	2480	1.07	pass




Part II - Test Plots

2.1 TM1_Ch0_L






2.2 TM1_Ch19_M





2.3 TM1_Ch39_H






Appendix C: Duty Cycle

Part I - Test Results

Test Mode	TX Freq. [MHz]	Duty cycle [%]
TM1	CH0,CH19,CH39	62

Part II - Test Plots





Appendix D: Maximum Conducted Average Output Power

Part I - Test Results

Test Mode	Test Channel	Frequency[MHz]	Duty Cycle [%]	Power[dBm]	Verdict
TM1_Ch0	L	2402	62	0.17	pass
TM1_Ch19	M	2440	62	0.68	pass
TM1_Ch39	H	2480	62	-0.66	pass



Part II - Test Plots

2.1 TM1 _Ch0_L





2.2 TM1 _Ch19_M





2.3 TM1 _Ch39_H





Appendix E: Maximum Power Spectral Density Level

Part I - Test Results

Test Mode	Test Channel	Frequency[MHz]	Duty Cycle [%]	PSD[dBm/10 kHz]	Verdict
TM1_Ch0	L	2402	62	-13.70	pass
TM1_Ch19	M	2440	62	-13.42	pass
TM1_Ch39	H	2480	62	-13.98	pass



Part II - Test Plots

2.1 TM1 _Ch0_L





2.2 TM1 _Ch0_M





2.3 TM1 _Ch39_H





Appendix F: Band Edges Compliance


Part I - Test Results

Test Mode	Test Channel	Frequency[MHz]	Carrier Power[dBm]	Max.Spurious Level[dBm]	Verdict
TM1 _Ch0	L	2402	0.14	-48.63	pass
TM1 _Ch39	H	2480	-0.60	-48.77	pass




Part II - Test Plots

2.1 TM1 _Ch0_L





2.2 TM1 _Ch39_H



Appendix G: Unwanted Emissions into Non-Restricted Frequency

Bands

In this Appendix, the "Pref", which is used as the reference level, refers to the peak power level in any 100 kHz bandwidth within the fundamental emission, the "Puw" refers to the maximum emission power in 100 kHz band segments outside of the authorized frequency band.

Considering that the higher ratio of RBW to the span for the frequency ranges below 30 MHz makes the results determination be complicated, a narrower RBW other than 100 kHz is used for these ranges. The measured value should add a RBW correction factor (RBWCF) where $RBWCF [dB] = 10 \times \lg(100 [kHz]/\text{narrower RBW [kHz]})$. As to this Appendix, the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

For measurements on smart antenna systems (devices with multiple transmit chains), the test is performed at each chain and used as respective results for each chain, due to the relative-limit requirement.

In the result table, the "< Limit" denotes that "The Puw [dBm] is less than Pref[dBm]-30[dBm], see test plots for detailed".

Part I - Test Results

Test Mode	Test Channel	Frequency[MHz]	Pref[dBm]	Puw[dBm]	Verdict
TM1 _Ch0	L	2402	0.27	<limit	pass
TM1 _Ch19	M	2440	0.79	<limit	pass
TM1 _Ch39	H	2480	-0.46	<limit	pass



Part II - Test Plots


2.1 TM1 _Ch0_L


Pref:








Puw:

















2.2 TM1 _Ch19_M


Pref:








P_{uw}:


















2.3 TM1 _Ch39_H


Pref:








P_uw:














Appendix H: Radiated Spurious Emission & Spurious in Restricted Band

Note: We tested all modes, but the data presented below is the worst case.

Below 1GHz, RBW = 100 kHz, VBW = 300 kHz.

Above 1GHz, RBW = 1 MHz, VBW = 3 MHz.

The simultaneous transmission has been considered


1.1 Part 1: Testing Range of “9 kHz to 30MHz”

NOTE1: No peak found in the Test Range of “9 kHz to 30MHz”

1.2 Part 2: Testing Range of “30 MHz to 1 GHz”

Note 1: The test results and plot for testing range of “30 MHz to 1 GHz” showed as below is the WORST case for all Test Modes and Channels. This range will not be presented for each Test Mode and each Channel.

Note 2: The emissions in this range are mainly from the Platform Device (Notepad PC and its ancillary components).



Frequency (MHz)	QuasiPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
46.31176	26.18	40	13.82	100	V	105	16.1
137.59976	28.35	43.5	15.15	142	V	290	13.5
166.60224	26.91	43.5	16.59	144	H	135	11.8
232.37488	29.66	46	16.34	100	H	109	14.2
299.84958	31.5	46	14.5	100	H	156	15.6
332.3097	28.12	46	17.88	123	H	278	16.6

Note:

- 1, Level =Reading level by receiver + Transd (Antenna factor + cable loss – preamplifier gain)
The reading level is calculated by software which is not shown in the sheet.
- 2, Margin=Limit - Level

1.3 Part 3: Testing Range of “1GHz to 3GHz”


Note 1: The testing range of “1GHz to 3 GHz” is for checking radiated emissions located in restricted bands near the EUT operating bands.

Note 2: Two limits are required in the testing range above 1 GHz, that is Peak limit (74 dB μ V/m) and Average Limit (54 dB μ V/m).


Note 3: The peak spike exceeds the limit line is EUT’s operating frequency.

Test Mode:

1.3.1 Test Mode: TM1



1.3.1.1 Channel 0



MEASUREMENT RESULT: AV Detector

Frequency (MHz)	Level (dBμ V/m)	Limit (dBμ V/m)	Margin (dB)	Height (cm)	Pol	Azimuth h	Transd. (dB)
2390.0000	28.26	54.00	25.74	150.0	V	135	-10.2

MEASUREMENT RESULT: PK Detector

Frequency (MHz)	Level (dBμ V/m)	Limit (dBμ V/m)	Margin (dB)	Height (cm)	Pol	Azimuth h	Transd. (dB)
2390.0000	51.66	74.00	22.34	150.0	V	135	-10.2


Note:

1, Level =Reading level by receiver + Transd (Antenna factor + cable loss – preamplifier gain)

The reading level is calculated by software which is not shown in the sheet.

2, Margin=Limit - Level

1.3.1.2 Channel 39



MEASUREMENT RESULT: AV Detector

Frequency (MHz)	Level (dBμ V/m)	Limit (dBμ V/m)	Margin (dB)	Height (cm)	Pol	Azimuth g	Transd. (dB)
2483.5000	28.73	54.00	25.27	150.0	V	131	-6.8

MEASUREMENT RESULT: PK Detector

Frequency (MHz)	Level (dBμ V/m)	Limit (dBμ V/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Transd. (dB)
2483.5000	47.55	74.00	26.45	150.0	V	225	-6.8

Note:

1, Level =Reading level by receiver + Transd (Antenna factor + cable loss – preamplifier gain)

The reading level is calculated by software which is not shown in the sheet.


2, Margin=Limit - Level

1.4 Part 4: Testing Range of “3 GHz to 18 GHz”

Note 1: The test results and plot for testing range of “3 GHz to 18 GHz” showed as below is the WORST case for all Test Modes and Channels. This range will not be presented for each Test Mode and each Channel.

Note 2: The testing range of “3 GHz to 18 GHz” is for checking radiated emissions located in restricted bands faraway from the EUT operating bands.

Note 3: Two limits are required in the testing range above 3 GHz, that is Peak limit (74 dB μ V/m) and Average Limit (54 dB μ V/m).




1.5 Part 5: Testing Range of “18 GHz to 26.5 GHz”

NOTE: No peak found in the Test Range of “18 GHz to 26.5GHz”

Appendix I: Conducted Emission at Power Port

Note: RBW =9 kHz, VBW = 30 kHz

Channel 39



MEASUREMENT RESULT: AV Detector

Frequency (MHz)	Level (dBμV)	Limit (dBμV)	Transd. (dB)	Margin (dB)	Line	PE
0.174766	26.61	54.73	9.7	28.12	N	FLO
0.231486	23.26	52.4	9.7	29.14	N	FLO
0.370374	25.64	48.49	9.7	22.85	N	FLO
1.339938	28.37	46	9.7	17.63	N	FLO
4.879979	25.57	46	9.8	20.43	N	FLO
21.588194	27.07	50	10.2	22.93	N	FLO

**MEASUREMENT RESULT: PK Detector**

Frequency (MHz)	Level (dB μ V)	Limit (dB μ V)	Transd. (dB)	Margin (dB)	Line	PE
0.173811	49.64	64.78	9.7	15.14	N	FLO
0.231204	44.56	62.41	9.7	17.85	N	FLO
0.370637	36.59	58.49	9.7	21.9	N	FLO
1.282269	38.29	56	9.7	17.71	N	FLO
4.831897	34.63	56	9.8	21.37	N	FLO
21.409015	36.93	60	10.2	23.07	N	FLO

Note:

1, Level =Reading level by receiver + Transd (Antenna factor + cable loss – preamplifier gain)

The reading level is calculated by software which is not shown in the sheet.

2, Margin=Limit - Level

END