



中国认可
国际互认
检测
TESTING
CNAS L0310



FCC Maximum Permissible Exposure(MPE) Estimation Report

Product Name: LTE CPE

Model: B525s-65a

Report No.: SYBH(Z-SAR)20190705010001-2

FCC ID: QISB525S-65A2

	APPROVED (Lab Manager)	PREPARED (Test Engineer)
BY	<i>Wei Huaobin</i>	<i>Zhang Zufu</i>
DATE	2019-07-23	2019-07-23

Reliability Laboratory of Huawei Technologies Co., Ltd.

(Global Compliance and Testing Center of Huawei Technologies Co., Ltd)

No.2, New City Avenue, Songshan Lake Sci. & Tech. Industry Park,
Dongguan,Guangdong, 523808, P.R.C

Tel: +86 769 23830808 Fax: +86 769 23837628

※ ※ **Notice** ※ ※

1. The laboratory has passed the accreditation by China National Accreditation Service for Conformity Assessment (CNAS). The accreditation number is L0310.
2. The laboratory has passed the accreditation by The American Association for Laboratory Accreditation (A2LA). The accreditation number is 2174.01 & 2174.02 & 2174.03
3. The laboratory (Reliability Lab of Huawei Technologies Co., Ltd) is also named as “Global Compliance and Testing Center of Huawei Technologies Co., Ltd”, the both names have coexisted since 2009.
4. The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
5. The test report is invalid if there is any evidence of erasure and/or falsification.
6. The test report is only valid for the test samples.
7. Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
8. If any question about this report, please contact the laboratory (PublicGCTC@huawei.com).

※ ※ **Modified History** ※ ※

REV.	DESCRIPTION	ISSUED DATE	REMARK
Rev.1.0	Initial Test Report Release	2019-07-23	Zhang Zufu

Table of Contents

1	EUT Description.....	5
1.1	General Description.....	6
2	Test specification(s).....	7
3	Testing laboratory.....	7
4	Applicant and Manufacturer.....	7
5	Application details.....	7
6	Ambient Condition.....	7
7	RF Exposure Requirements.....	8
7.1	FCC MPE Limits.....	9
8	RF Exposure Evaluation.....	10
8.1	Calculation of Power Density for Single Chain Transmitters.....	10
9	Exposure calculations for multiple sources.....	12
9.1	Calculation of WiFi MIMO Transmitters.....	13
9.2	Estimation of Co-located Transmitters.....	14

1 EUT Description

Device Information:			
Product Name :	LTE CPE		
Model :	B525s-65a		
FCC ID:	QISB525S-65A2		
Device Type :	Mobile Device		
Device Phase:	Identical Prototype		
Exposure Category:	Uncontrolled environment/ general population		
Hardware Version :	WL1B525I		
Software Version :	81.191.21.00.00		
Antenna Type :	Internal Antenna		
Device Operating Configurations:			
Supporting Mode(s)	GSM850/1900,UMTS Band II/V, LTE Band 2/4/5/7/26/38/41, WiFi 2.4G/5G		
Test Modulation	GSM(GMSK/8PSK),UMTS(QPSK),LTE(QPSK/16QAM), WiFi(DSSS/OFDM)		
Operating Frequency Range(s)	Band	Tx (MHz)	Rx (MHz)
	GSM850	824-849	869-894
	GSM1900	1850-1910	1930-1990
	UMTS Band II	1850-1910	1930-1990
	UMTS Band V	824-849	869-894
	LTE Band 2	1850-1910	1930-1990
	LTE Band 4	1710-1755	2110-2155
	LTE Band 5	824-849	869-894
	LTE Band 7	2500-2570	2620-2690
	LTE Band 26	814-849	859-894
	LTE Band 38	2570-2620	2570-2620
	LTE Band 41	2496-2690	2496-2690
	WiFi 2.4G	2432-2462	2432-2462
	WiFi 5G	5150-5250	5150-5250

1.1 General Description

The HUAWEI B525s-65a LTE CPE (B525s-65a for short) is a wireless gateway that integrates LTE and high-speed Ethernet uplink access, which provides users with flexible and diversified data access and voice services. The B525s-65a supports wired and wireless network access, and provides data routing service.

2 Test specification(s)

ANSI Std C95.1-1992	Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz – 300 GHz.(IEEE Std C95.1-1991)
KDB 447498 D01	General RF Exposure Guidance v06

3 Testing laboratory

Test Site	Reliability Laboratory of Huawei Technologies Co., Ltd.
Test Location	NO.2 New City Avenue Songshan Lake Sci. & Tech. Industry Park, Dongguan, Guangdong, P.R.C
Telephone	+86 769 23830808
Fax	+86 769 23837628
State of accreditation	The Test laboratory (area of testing) is accredited according to ISO/IEC 17025. CNAS Registration number: L0310 A2LA TESTING CERT #2174.01 & 2174.02 & 2174.03

4 Applicant and Manufacturer

Company Name	HUAWEI TECHNOLOGIES CO., LTD
Address	Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C

5 Application details

Start Date of test	2019-07-23
End Date of test	2019-07-23

6 Ambient Condition

Ambient temperature	18°C – 25°C
Relative Humidity	30% – 70%

7 RF Exposure Requirements

An estimation of MPE in this application for product is used to ensure if it complies with the rules of the standard in the regulation list above.

Maximum permissible exposure (MPE) refers to the RF energy that is acceptable for human exposure. It is broken down into two categories, Occupational/controlled and General population/uncontrolled.

Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

A rough estimation of the expected exposure in power flux density on a given point can be made with the following equation:

$$S = \frac{P \times G}{4 \times \pi \times R^2}$$

Where:

S = power density

P = power input to the antenna

G = numeric gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the centre of radiation of the antenna

EIRP = P*G

The antenna of the product, under normal use condition is at least 20 cm away from the

body of the user. Warning statement to the user for keeping at least 20cm separation distance and the prohibition of operating to a person has been printed on the user's manual. Therefore, the S of the device is calculated with R=20cm, and if it is below the limit S, then we can conclude the device complies with the rules.

7.1 FCC MPE Limits

We analysis if it comply with the limits for General population/uncontrolled exposure. The FCC MPE limits for field strength and power density are given in 47CFR 1.1310(Table below).These limits are generally based on recommended exposure guidelines published by the National Council on Radiation Protection and Measurements (NCRP), and also partly based on guidelines recommended by the American National Standards Institute (ANSI) in Section 4.1 of ANSI/IEEE C95.1.

Table: Limits for Maximum Permissible Exposure (MPE)

(A) Limits for Occupational/controlled Exposure				
Frequency Range(MHz)	Electric Field Strength(E)(V/m)	Magnetic Field Strength(H)(A/m)	Power Density (S)(mW/cm ²)	Averaging Time (minute) E ² , H ² or S
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f ²)*	6
30-300	61.4	0.163	1.0	6
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/uncontrolled Exposure				
Frequency Range(MHz)	Electric Field Strength(E)(V/m)	Magnetic Field Strength(H)(A/m)	Power Density (S)(mW/cm ²)	Averaging Time (minute) E ² , H ² or S
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30
f=frequency in MHz			*Plane-wave equivalent power density	

8 RF Exposure Evaluation

8.1 Calculation of Power Density for Single Chain Transmitters

Band	Antenna	Tune-up Power* (dBm)	Gain (dBi)	EIRP (dBm)	EIRP (mW)	R (cm)	S (mW/cm ²)	Limit (mW/cm ²)	% of limit
GSM850 (CS)	Internal Antenna 1	35.00	1.50	36.50	558.35	20.00	0.11	0.55	20.24%
GSM850 1slot	Internal Antenna 1	35.00	1.50	36.50	558.35	20.00	0.11	0.55	20.24%
GSM850 2slot	Internal Antenna 1	33.00	1.50	34.50	704.60	20.00	0.14	0.55	25.53%
GSM850 3slot	Internal Antenna 1	31.00	1.50	32.50	666.85	20.00	0.13	0.55	24.18%
GSM850 4slot	Internal Antenna 1	29.00	1.50	30.50	561.01	20.00	0.11	0.55	20.33%
GSM1900 (CS)	Internal Antenna 1	32.00	2.00	34.00	313.99	20.00	0.06	1.00	6.25%
GSM1900 1slot	Internal Antenna 1	32.00	2.00	34.00	313.99	20.00	0.06	1.00	6.25%
GSM1900 2slot	Internal Antenna 1	30.00	2.00	32.00	396.22	20.00	0.08	1.00	7.89%
GSM1900 3slot	Internal Antenna 1	28.00	2.00	30.00	375.00	20.00	0.07	1.00	7.46%
GSM1900 4slot	Internal Antenna 1	26.00	2.00	28.00	315.48	20.00	0.06	1.00	6.28%
UMTS Band II	Internal Antenna 1	25.70	1.50	27.20	524.81	20.00	0.10	1.00	10.45%
UTMS Band V	Internal Antenna 1	25.70	1.50	27.20	524.81	20.00	0.10	0.55	19.03%
LTE Band 2	Internal Antenna 1	25.70	1.50	27.20	524.81	20.00	0.10	1.00	10.45%
LTE Band 4	Internal Antenna 1	25.70	1.50	27.20	524.81	20.00	0.10	1.00	10.45%
LTE Band 5	Internal Antenna 1	25.70	1.50	27.20	524.81	20.00	0.10	0.55	19.03%
LTE Band 7	Internal Antenna 1	25.70	2.00	27.70	588.84	20.00	0.12	1.00	11.72%
LTE Band 26	Internal Antenna 1	25.70	1.50	27.20	524.81	20.00	0.10	0.54	19.34%
LTE Band 38	Internal Antenna 1	25.70	2.00	27.70	588.84	20.00	0.12	1.00	11.72%
LTE Band 41	Internal Antenna 1	25.70	2.00	27.70	588.84	20.00	0.12	1.00	11.72%
WiFi 2.4G	Internal Antenna 2	20.00	1.00	21.00	125.89	20.00	0.03	1.00	2.51%
WiFi 2.4G	Internal Antenna 3	20.00	1.00	21.00	125.89	20.00	0.03	1.00	2.51%
WiFi 5G	Internal Antenna 2	24.00	1.00	25.00	316.23	20.00	0.06	1.00	6.29%
WiFi 5G	Internal Antenna 3	24.00	1.00	25.00	316.23	20.00	0.06	1.00	6.29%



HUAWEI

WiFi 5G	Internal Antenna 4	24.00	1.00	25.00	316.23	20.00	0.06	1.00	6.29%
---------	--------------------	-------	------	-------	--------	-------	------	------	--------------

Note:*- based on the maximum tune-up tolerance limit declared by manufacturer

For GSM bands, the time-based average power considering the duty cycle should be used in MPE evaluation. To average the power, the division factor is as follows:

1Tx slot = 1 transmit time slot out of 8 time slots => power divided by (1/8) = > - 9.03dB

2Tx slots = 2 transmit time slot out of 8 time slots=> power divided by (2/8) = > - 6.02dB

3Tx slots = 3 transmit time slot out of 8 time slots=> power divided by (3/8) = > - 4.26dB

4Tx slots = 4 transmit time slot out of 8 time slots=> power divided by (4/8) = > - 3.01dB

According to the power density calculations with a distance from the point to the antenna 20cm above, all values meet the limit specified in section 7, so it is into compliance.

9 Exposure calculations for multiple sources

When a number of sources at different frequencies, and/or broadband sources, contribute to the total exposure, it becomes necessary to weigh each contribution relative to the MPE in accordance with the provisions of Table (A) and Table (B). To comply with the MPE, the fraction of the MPE in terms of E^2 , H^2 (or power density) incurred within each frequency interval should be determined and the sum of all such fractions should not exceed unity.

In order to ensure compliance with the MPE for a controlled environment, the sum of the ratios of the power density to the corresponding MPE should not exceed unity. That is

$$\sum_{i=1}^n \frac{S_i}{MPE_i} \leq 1$$

The product also has multiple transmitters. The Simultaneous Transmission Possibilities are as below:

Simultaneous Tx Combination	Configuration
1	WiFi 2.4G MIMO
2	WiFi 5G MIMO
3	WiFi 2.4G+WiFi 5G
4	GSM/UMTS/LTE +WiFi 2.4G
5	GSM/UMTS/LTE +WiFi 5G
6	GSM/UMTS/LTE +WiFi 2.4G+WiFi 5G

Note: There are three WiFi internal antennas. Ant2 and Ant3 support WiFi 2.4G and WiFi 5G. Ant4 support WiFi 5G only. Ant2 and Ant3 can support WiFi 2.4G and WiFi 5G at the same time.

9.1 Calculation of WiFi MIMO Transmitters

Mode	Antenna	Tune-up Power (dBm)	Gain (dBi)	EIRP (dBm)	EIRP (mW)	R (cm)	S (mW/cm ²)	Limit (mW/cm ²)	% of limit	Total exposure ratio (<1)
WiFi 2.4G 2*2 MIMO	Internal Antenna 2	17.00	1.00	18.00	63.10	20.00	0.01	1.00	1.26%	2.52%
	Internal Antenna 3	17.00	1.00	18.00	63.10	20.00	0.01	1.00	1.26%	
WiFi 5G 2*2 MIMO	Internal Antenna 2	24.00	1.00	25.00	316.23	20.00	0.06	1.00	6.29%	12.58%
	Internal Antenna 3	24.00	1.00	25.00	316.23	20.00	0.06	1.00	6.29%	
WiFi 5G 2*2 MIMO	Internal Antenna 2	24.00	1.00	25.00	316.23	20.00	0.06	1.00	6.29%	12.58%
	Internal Antenna 4	24.00	1.00	25.00	316.23	20.00	0.06	1.00	6.29%	
WiFi 5G 2*2 MIMO	Internal Antenna 3	24.00	1.00	25.00	316.23	20.00	0.06	1.00	6.29%	12.58%
	Internal Antenna 4	24.00	1.00	25.00	316.23	20.00	0.06	1.00	6.29%	
WiFi 5G 3*3 MIMO	Internal Antenna 2	24.00	1.00	25.00	316.23	20.00	0.06	1.00	6.29%	18.87%
	Internal Antenna 3	24.00	1.00	25.00	316.23	20.00	0.06	1.00	6.29%	
	Internal Antenna 4	24.00	1.00	25.00	316.23	20.00	0.06	1.00	6.29%	

9.2 Estimation of Co-located Transmitters

NO.	Simultaneous Conditions	Max. PD Mode/Band	% of limit	Total exposure ratio (<1)
1	WiFi 2.4G+WiFi 5G	WiFi 2.4G 2*2 MIMO	2.52%	21.39%
		WiFi 5G 3*3 MIMO	18.87%	
2	GSM/UMTS/LTE +WiFi 2.4G	GSM850 2slot	25.53%	28.05%
		WiFi 2.4G 2*2 MIMO	2.52%	
3	GSM/UMTS/LTE +WiFi 5G	GSM850 2slot	25.53%	44.40%
		WiFi 5G 3*3 MIMO	18.87%	
4	GSM/UMTS/LTE +WiFi 2.4G+ WiFi 5G	GSM850 2slot	25.53%	46.92%
		WiFi 2.4G 2*2 MIMO	2.52%	
		WiFi 5G 3*3 MIMO	18.87%	

According to the Table above, we can conclude that the calculation results of all simultaneous transmission possibilities are less than 100%, so it is into compliance. Therefore the product also meets the requirements under multiple sources condition.

END