


2.3.6.2 Channel 11 @Ant 2



MEASUREMENT RESULT: AV Detector

| Frequency (MHz) | Level (dBμ V/m) | Limit (dBμ V/m) | Margin (dB) | Height (cm) | Pol | Azimuth h | Transd. (dB) |
|-----------------|-----------------|-----------------|-------------|-------------|-----|-----------|--------------|
| 2483.5 | 31.17 | 54.00 | 22.83 | 150.0 | H | 190.0 | -6.4 |

MEASUREMENT RESULT: PK Detector

| Frequency (MHz) | Level (dBμ V/m) | Limit (dBμ V/m) | Margin (dB) | Height (cm) | Pol | Azimuth h (deg) | Transd. (dB) |
|-----------------|-----------------|-----------------|-------------|-------------|-----|-----------------|--------------|
| 2483.5 | 50.15 | 74.00 | 23.85 | 150.0 | H | 190.0 | -6.4 |

Note:

1, Level =Reading level by receiver + Transd (Antenna factor + cable loss – preamplifier gain)


The reading level is calculated by software which is not shown in the sheet.

2, Margin=Limit – Level

2.3.7 Test Mode: 11G CDD

2.3.7.1 Channel 1 CDD

Full Spectrum



MEASUREMENT RESULT: AV Detector

| Frequency (MHz) | Level (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) | Height (cm) | Pol | Azimuth h | Transd. (dB) |
|-----------------|----------------------|----------------------|-------------|-------------|-----|-----------|--------------|
| 2390 | 44.95 | 54.00 | 9.05 | 150.0 | H | 112.0 | -8.6 |

MEASUREMENT RESULT: PK Detector

| Frequency (MHz) | Level (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) | Height (cm) | Pol | Azimuth h (deg) | Transd. (dB) |
|-----------------|----------------------|----------------------|-------------|-------------|-----|-----------------|--------------|
| 2390 | 66.28 | 74.00 | 7.72 | 150.0 | V | 318.0 | -8.6 |


Note:

1, Level = Reading level by receiver + Transd (Antenna factor + cable loss – preamplifier gain)

The reading level is calculated by software which is not shown in the sheet.

2, Margin = Limit – Level

2.3.7.2 Channel 11 CDD



MEASUREMENT RESULT: AV Detector

| Frequency (MHz) | Level (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) | Height (cm) | Pol | Azimuth h | Transd. (dB) |
|-----------------|----------------------|----------------------|-------------|-------------|-----|-----------|--------------|
| 2483.5 | 42.08 | 54.00 | 11.92 | 150 | V | 36.0 | -6.6 |

MEASUREMENT RESULT: PK Detector

| Frequency (MHz) | Level (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) | Height (cm) | Pol | Azimuth h (deg) | Transd. (dB) |
|-----------------|----------------------|----------------------|-------------|-------------|-----|-----------------|--------------|
| 2483.5 | 64.82 | 74.00 | 9.18 | 150 | H | 33.0 | -6.6 |

Note:


1, Level = Reading level by receiver + Transd (Antenna factor + cable loss – preamplifier gain)

The reading level is calculated by software which is not shown in the sheet.

2, Margin = Limit – Level

2.3.8 Test Mode: 11N MIMO

2.3.8.1 Channel 1 MIMO



MEASUREMENT RESULT: AV Detector

| Frequency (MHz) | Level (dBμ V/m) | Limit (dBμ V/m) | Margin (dB) | Height (cm) | Pol | Azimuth h | Transd. (dB) |
|-----------------|-----------------|-----------------|-------------|-------------|-----|-----------|--------------|
| 2390 | 38.25 | 54.00 | 15.75 | 100.0 | H | 195.0 | -8.6 |


MEASUREMENT RESULT: PK Detector

| Frequency (MHz) | Level (dBμ V/m) | Limit (dBμ V/m) | Margin (dB) | Height (cm) | Pol | Azimuth h (deg) | Transd. (dB) |
|-----------------|-----------------|-----------------|-------------|-------------|-----|-----------------|--------------|
| 2390 | 60.42 | 74.00 | 13.58 | 150.0 | H | 226.0 | -8.6 |

Note:

- 1, Level = Reading level by receiver + Transd (Antenna factor + cable loss – preamplifier gain)
The reading level is calculated by software which is not shown in the sheet.
- 2, Margin = Limit – Level

2.3.8.2 Channel 11 @MIMO



MEASUREMENT RESULT: AV Detector

| Frequency (MHz) | Level (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) | Height (cm) | Pol | Azimuth h | Transd. (dB) |
|-----------------|----------------------|----------------------|-------------|-------------|-----|-----------|--------------|
| 2483.5 | 44.45 | 54.00 | 9.55 | 100.0 | H | 93.0 | -8.6 |

MEASUREMENT RESULT: PK Detector

| Frequency (MHz) | Level (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) | Height (cm) | Pol | Azimuth h (deg) | Transd. (dB) |
|-----------------|----------------------|----------------------|-------------|-------------|-----|-----------------|--------------|
| 2483.5 | 63.39 | 74.00 | 10.61 | 150.0 | H | 87.0 | -8.6 |

Note:


1, Level =Reading level by receiver + Transd (Antenna factor + cable loss – preamplifier gain)

The reading level is calculated by software which is not shown in the sheet.

2, Margin=Limit – Level

2.4 Part 4: Testing Range of “3 GHz to 18 GHz”

- Note 1: The test results and plot for testing range of “3 GHz to 18 GHz” showed as below is the WORST case for all Test Modes and Channels. This range will not be presented for each Test Mode and each Channel.
- Note 2: The testing range of “3 GHz to 18 GHz” is for checking radiated emissions located in restricted bands faraway from the EUT operating bands.
- Note 3: Two limits are required in the testing range above 1 GHz, that is Peak limit (74 dB μ V/m) and Average Limit (54 dB μ V/m).






2.5Part 5: Testing Range of “18 GHz to 26.5 GHz”

NOTE: No peak found in the Test Range of “18 GHz to 26.5GHz”

Appendix I: Conducted Emission at Power Port

Note: RBW =9 kHz, VBW = 30 kHz



MEASUREMENT RESULT: PK Detector

| Frequency (MHz) | Level (dB μ V) | Limit (dB μ V) | Transd. (dB) | Margin (dB) | Line | PE |
|-----------------|--------------------|--------------------|--------------|-------------|------|-----|
| 0.159551 | 54.35 | 65.49 | 9.7 | 11.14 | L1 | FLO |
| 0.159914 | 54.27 | 65.47 | 9.7 | 11.20 | L1 | FLO |
| 0.257426 | 48.10 | 61.51 | 9.7 | 13.41 | N | FLO |
| 1.224344 | 46.78 | 56.00 | 9.7 | 9.22 | N | FLO |
| 1.236038 | 46.57 | 56.00 | 9.7 | 9.43 | L1 | FLO |
| 2.215012 | 46.37 | 56.00 | 9.7 | 9.63 | N | FLO |

MEASUREMENT RESULT: AV Detector

| Frequency (MHz) | Level (dB μ V) | Limit (dB μ V) | Transd. (dB) | Margin (dB) | Line | PE |
|-----------------|--------------------|--------------------|--------------|-------------|------|-----|
| 0.162748 | 38.18 | 55.32 | 9.7 | 17.14 | N | FLO |
| 0.164022 | 38.61 | 55.25 | 9.7 | 16.64 | L1 | FLO |
| 0.261585 | 34.17 | 51.38 | 9.7 | 17.21 | N | FLO |
| 0.701190 | 27.43 | 46.00 | 9.7 | 18.57 | N | FLO |
| 1.224344 | 26.89 | 46.00 | 9.7 | 19.11 | L1 | FLO |
| 1.582871 | 29.03 | 46.00 | 9.7 | 16.97 | L1 | FLO |

Note:

1, Level =Reading level by receiver + Transd (Antenna factor + cable loss – preamplifier gain)

The reading level is calculated by software which is not shown in the sheet.

2, Margin=Limit - Level

END