



No. DAT-P-114/01-01



No. L0442

TEST REPORT

No. 2006E01013

| | |
|---------------------|--|
| FCC ID | QISC506 |
| Test Name | Electromagnetic Field (Specific Absorption Rate) |
| Product | CDMA 1X Digital Mobile Phone |
| Model | HUAWEI C506 |
| Client | HUAWEI Technologies Co., Ltd. |
| Type of test | Non Type Approval |

Telecommunication Metrology Center
of Ministry of Information Industry



Notes

1. . The test report shall be invalid if there is no “specified stamp for the test report” or the stamp of the test organization on it.
2. Copies of the test report shall be invalid if there is no “specified stamp for the test report” or the stamp of the test organization on it.
3. The test report shall be invalid if there are no signatures of the testing person, reviewing person and approving person on it.
4. The test report shall be invalid if it is altered.
5. Any demurral about the test shall be put forward to the testing organization within 15 days after the receiving of the test report.
6. This test report standalone dose not constitute or imply by its own an approval of the product by any Certification Authorities or Competent Bodies.
7. This report is only valid if complete, and test report shall not be reproduced except in full, without written approval of the laboratory.
8. This report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of Telecommunication Metrology Center of MII and the Accreditation Bodies, if it applies.

Address: No. 52, Huayuan Bei Road, Haidian District, Beijing, P. R. China
(Telecommunication Metrology Center of MII)

Post code: 100083

Telephone: +86 10 62302041

Fax: +86 10 62304793

Web site: <http://www.emcite.com>

E-mail: welcome@emcite.com

TABLE OF CONTENT

| | |
|---|-----------|
| 1 COMPETENCE AND WARRANTIES | 5 |
| 2 GENERAL CONDITIONS..... | 5 |
| 3 DESCRIPTION OF EUT..... | 5 |
| 3.1 ADDRESSING INFORMATION RELATED TO EUT..... | 5 |
| 3.2 CONSTITUENTS OF EUT | 6 |
| 3.3 GENERAL DESCRIPTION..... | 6 |
| 4 OPERATIONAL CONDITIONS DURING TEST | 6 |
| 4.1 SCHEMATIC TEST CONFIGURATION..... | 6 |
| 4.2 SAR MEASUREMENT SET-UP..... | 7 |
| 4.3 DASY4 E-FIELD PROBE SYSTEM..... | 8 |
| 4.4 E-FIELD PROBE CALIBRATION | 9 |
| 4.5 OTHER TEST EQUIPMENT | 10 |
| 4.6 EQUIVALENT TISSUES..... | 10 |
| 4.7 SYSTEM SPECIFICATIONS..... | 11 |
| 5 CHARACTERISTICS OF THE TEST | 11 |
| 5.1 APPLICABLE LIMIT REGULATIONS | 11 |
| 5.2 APPLICABLE MEASUREMENT STANDARDS..... | 12 |
| 6 LABORATORY ENVIRONMENT | 12 |
| 7 CONDUCTED OUTPUT POWER MEASUREMENT..... | 12 |
| 7.1 SUMMARY | 12 |
| 7.2 CONDUCTED POWER | 12 |
| 8 TEST RESULTS | 13 |
| 8.1 DIELECTRIC PERFORMANCE | 13 |
| 8.2 SYSTEM VALIDATION..... | 13 |
| 8.3 SUMMARY OF MEASUREMENT RESULTS | 14 |
| 8.4 CONCLUSION..... | 15 |
| 9 MEASUREMENT UNCERTAINTY | 15 |
| 10 MAIN TEST INSTRUMENTS..... | 16 |
| 11 TEST PERIOD..... | 16 |
| 12 TEST LOCATION..... | 16 |
| ANNEX A MEASUREMENT PROCESS | 17 |
| ANNEX B TEST LAYOUT | 18 |
| ANNEX C GRAPH RESULTS..... | 22 |
| ANNEX D SYSTEM VALIDATION RESULTS..... | 52 |
| ANNEX E PROBE CALIBRATION CERTIFICATE..... | 53 |


**Telecommunication Metrology Center
of Ministry of Information Industry**

No. 2006E01013

Page 4 of 62


| | | | |
|-----------------------------|---|-----------------------|------------------------------|
| Product Name | CDMA 1X Digital Mobile Phone | Sample Model | HUAWEI C506 |
| Client | HUAWEI Technologies Co., Ltd. | Type of test | Non Type Approval |
| Factory | HUAWEI Technologies Co., Ltd. | Sampling arrival date | June 19 th , 2006 |
| Manufacturer | HUAWEI Technologies Co., Ltd. | | |
| Sampling/ Sending sample | Sending sample | Sample sent by | Fan Yong |
| Sampling location | / | Sampling person | / |
| Sample quantity | 1 | Sample matrix | / |
| Series number of the Sample | 0756F2F3 | | |
| Test basis | <p>EN 50360-2001: Product standard for the measurement of Specific Absorption Rate related to human exposure to electromagnetic fields from mobile phones.</p> <p>EN 50361-2001: Basic standard for the measurement of Specific Absorption Rate related to human exposure to electromagnetic fields from mobile phones.</p> <p>ANSI C95.1-1999: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.</p> <p>IEEE 1528-2003: Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques.</p> <p>IEC 62209-1: Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Human models, instrumentation, and procedures –Part 1: Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)</p> <p>OET Bulletin 65 (Edition 97-01) and Supplement C(Edition 01-01): Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits.</p> | | |
| Test conclusion | <p>Localized Specific Absorption Rate (SAR) of this portable wireless equipment has been measured in all cases requested by the relevant standards cited in Clause 5.2 of this test report. Maximum localized SAR is below exposure limits specified in the relevant standards cited in Clause 5.1 of this test report.</p> <p>General Judgment: Pass</p> <p align="right">(Stamp)</p> <p align="right">Date of issue: July 5th, 2006</p> | | |
| Note | <p>TX Freq. Band: 824-849 MHz (CDMA)</p> <p>Max. Power: 0.25 Watt (CDMA)</p> <p>Antenna Character: 21mm</p> <p>The test results relate only to the items tested of the sample(s).</p> | | |

Approved by



(Lu Bingsong)


Deputy Director of the laboratory

Reviewed by


(Chu Wenhua)

Tested by


(Sun Qian)



1 COMPETENCE AND WARRANTIES

Telecommunication Metrology Center of Ministry of Information Industry is a test laboratory accredited by DAR (DATech) – Deutschen Akkreditierungs Rat (Deutsche Akkreditierungsstelle Technik) for the tests indicated in the Certificate No. **DAT-P-114/01-10**.

Telecommunication Metrology Center of Ministry of Information Industry is a test laboratory competent to carry out the tests described in this test report.

Telecommunication Metrology Center of Ministry of Information Industry guarantees the reliability of the data presented in this test report, which is the results of measurements and tests performed for the items under test on the date and under the conditions stated in this test report and is based on the knowledge and technical facilities available at **Telecommunication Metrology Center of Ministry of Information Industry** at the time of execution of the test.

Telecommunication Metrology Center of Ministry of Information Industry is liable to the client for the maintenance by its personnel of the confidentiality of all information related to the items under test and the results of the test.

2 GENERAL CONDITIONS

- 2.1 This report only refers to the item that has undergone the test.
- 2.2 This report standalone dose not constitute or imply by its own an approval of the product by the certification Bodies or competent Authorities.
- 2.3 This document is only valid if complete; no partial reproduction can be made without written approval of Telecommunication Metrology Center of Ministry of Information Industry.
- 2.4 This report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of Telecommunication Metrology Center of Ministry of Information Industry and the Accreditation Bodies, if it applies.

3 DESCRIPTION OF EUT

3.1 Addressing Information Related to EUT

Table 1: Applicant (The Client)

| | |
|-----------------|---|
| Name or Company | HUAWEI Technologies Co., Ltd. |
| Address/Post | Bantian, Longgang District, Shenzhen, Guangdong |
| City | Shenzhen |
| Postal Code | 518129 |
| Country | China |
| Telephone | 0755-28780808 |
| Fax | 0755-28780808 |

**Telecommunication Metrology Center
of Ministry of Information Industry**

No. 2006E01013

Page 6 of 61

Table 2: Manufacturer

| | |
|-----------------|---|
| Name or Company | HUAWEI Technologies Co., Ltd. |
| Address/Post | Bantian, Longgang District, Shenzhen, Guangdong |
| City | Shenzhen |
| Postal Code | 518129 |
| Country | China |
| Telephone | 0755-28780808 |
| Fax | 0755-28780808 |

3.2 Constituents of EUT

Table 3: Constituents of Samples

| Description | Model | Serial Number | Manufacturer |
|-----------------|--------------|---------------|---|
| Handset | HUAWEI C506 | 0756F2F3 | HUAWEI Technologies Co., Ltd. |
| Lithium Battery | HBC506 | EVE622810157 | XIANYANG VOLTIX ENERGY CO., LTD |
| AC/DC Adapter | TPCA-050040U | TPI632106182 | TECH-POWER Electronics (Shenzhen) Co., Ltd. |



Picture 1: Constituents of the sample (Lithium Battery is in the Handset)

3.3 General Description

Equipment Under Test (EUT) is a model of CDMA 1X portable Mobile Station (MS) with integrated antenna. It consists of Handset and normal options: Lithium Battery and AC/DC Adapter as Table 3 and Picture 1. With the request of the client, SAR is tested for CDMA 835MHz.

The sample undergoing test was selected by the Client.

Components list please refer to documents of the manufacturer

4 OPERATIONAL CONDITIONS DURING TEST

4.1 Schematic Test Configuration

During SAR test, EUT is in its Traffic Mode (Channel Allocated) at Normal Voltage Condition. A communication is set up in the test mode of EUT, and a call is established. The Absolute Radio Frequency Channel Number (ARFCN) is allocated to 1013, 384 and 777 respectively in the case of CDMA 835 MHz. The EUT is commanded to operate at maximum transmitting power.

**Telecommunication Metrology Center
of Ministry of Information Industry**

No. 2006E01013

Page 7 of 61

The EUT shall use its internal transmitter. The antenna(s), battery and accessories shall be those specified by the manufacturer. The EUT battery must be fully charged and checked periodically during the test to ascertain uniform power output. If a wireless link is used, the antenna connected to the output of the base station simulator shall be placed at least 50 cm away from the handset. The signal transmitted by the simulator to the antenna feeding point shall be lower than the output power level of the handset by at least 30 dB.

Test communication setup meet as followings:

| | |
|--|---|
| Communication standard between mobile station and base station simulator | 3GPP2 C.S0011-B |
| Radio configuration | RC3 (Supporting CDMA 1X) |
| Spreading Rate | SR1 |
| Data Rate | 9600bps |
| Service Options | SO55 (loop back mode) |
| Service Options | SO3 (voice mode) |
| Multiplex Options | The mobile station does not support this service. |

Base station Simulator: CMU200

Test Parameter setup for maximum RF output power according to section 4.4.5 of 3GPP2 C.S0011-B:

| Parameter | Units | Value |
|-----------------------------|-------------|-------|
| I_{or} | dBm/1.23MHz | -104 |
| $\frac{PilotE_c}{I_{or}}$ | dB | -7 |
| $\frac{TrafficE_c}{I_{or}}$ | dB | -7.4 |

For SAR test, the maximum power output is very important and essential; it is identical under the measurement uncertainty. It is proper to use typical Test Mode 3 (FW RC3, RVS RC3, SO55) as the worst case for SAR test.


Under the loop back mode between mobile station and CMU200, the transmitter continuously emits with maximum power more strong than voice mode, so the SAR test was done with loop back mode. To make the mobile emits maximum power; the output power of CMU200 would be adjusted to minimum power with the sensitivity of the mobile station to build steady connection with mobile station. The power level control parameter in the CMU200 is "0", it means "all up" and requires mobile station to emit with maximum power.

4.2 SAR Measurement Set-up

These measurements were performed with the automated near-field scanning system DASY4 Professional from Schmid & Partner Engineering AG (SPEAG). The system is based on a high precision robot (working range greater than 0.9m) which positions the probes with a positional repeatability of better than ± 0.02 mm. Special E- and H-field probes have been developed for

measurements close to material discontinuity, the sensors of which are directly loaded with a Schottky diode and connected via highly resistive lines (length =300mm) to the data acquisition unit.

A cell controller system contains the power supply, robot controller, teaches pendant (Joystick), and remote control, is used to drive the robot motors. The PC consists of the Micron Pentium III 800 MHz computer with Windows 2000 system and SAR Measurement Software DASY4, A/D interface card, monitor, mouse, and keyboard. The Stäubli Robot is connected to the cell controller to allow software manipulation of the robot. A data acquisition electronic (DAE) circuit performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC plug-in card.



Picture 2: SAR Lab Test Measurement Set-up


The DAE consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the PC-card is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe mounting device includes two different sensor systems for frontal and sidewise probe contacts. They are also used for mechanical surface detection and probe collision detection. The robot uses its own controller with a built in VME-bus computer.

4.3 Dasy4 E-field Probe System

The SAR measurements were conducted with the dosimetric probe ET3DV6 (manufactured by SPEAG), designed in the classical triangular configuration and optimized for dosimetric evaluation. The probe has been calibrated according to the standard procedure with an accuracy of better than $\pm 10\%$. The spherical isotropy was evaluated and found to be better than $\pm 0.25\text{dB}$.

ET3DV6 Probe Specification

| | |
|--------------|--|
| Construction | Symmetrical design with triangular core |
| | Built-in optical fiber for surface detection |
| | System(ET3DV6 only) |
| | Built-in shielding against static charges |
| | PEEK enclosure material(resistant to organic solvents, e.q., glycol) |



Picture 3: ET3DV6 E-field Probe

| | |
|-------------------|--|
| Calibration | In air from 10 MHz to 2.5 GHz In brain and muscle simulating tissue at frequencies of 450MHz, 900MHz and 1.8GHz (accuracy±8%) Calibration for other liquids and frequencies upon request |
| Frequency | 10 MHz to > 6 GHz; Linearity: ±0.2 dB (30 MHz to 3 GHz) |
| Directivity | ±0.2 dB in brain tissue (rotation around probe axis) ±0.4 dB in brain tissue (rotation normal probe axis) |
| Dynamic Range | 5u W/g to > 100mW/g; Linearity: ±0.2dB |
| Surface Detection | ±0.2 mm repeatability in air and clear liquids over diffuse reflecting surface(ET3DV6 only) |
| Dimensions | Overall length: 330mm Tip length: 16mm Body diameter: 12mm Tip diameter: 6.8mm Distance from probe tip to dipole centers: 2.7mm |
| Application | General dosimetry up to 3GHz Compliance tests of mobile phones Fast automatic scanning in arbitrary phantoms |



Picture4:ET3DV6 E-field probe

4.4 E-field Probe Calibration

Each probe is calibrated according to a dosimetric assessment procedure with accuracy better than ± 10%. The spherical isotropy was evaluated and found to be better than ± 0.25dB. The sensitivity parameters (NormX, NormY, NormZ), the diode compression parameter (DCP) and the conversion factor (ConvF) of the probe are tested.

The free space E-field from amplified probe outputs is determined in a test chamber. This is performed in a TEM cell for frequencies below 1 GHz, and in a wave guide above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is then rotated 360 degrees.

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated brain tissue. The measured free space E-field in the medium correlates to temperature rise in a dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

$$SAR = C \frac{\Delta T}{\Delta t}$$

Where:

Δt = Exposure time (30 seconds),

C = Heat capacity of tissue (brain or muscle),

ΔT = Temperature increase due to RF exposure.

Or

$$\text{SAR} = \frac{|E|^2 \sigma}{\rho}$$

Where:

σ = Simulated tissue conductivity,

ρ = Tissue density (kg/m³).

Note: Please see Annex E to check the probe calibration certificate.



Picture 5: Device Holder

4.5 Other Test Equipment

4.5.1 Device Holder for Transmitters

In combination with the Generic Twin Phantom V3.0, the Mounting Device (POM) enables the rotation of the mounted transmitter in spherical coordinates whereby the rotation points is the ear opening. The devices can be easily, accurately, and repeat ably positioned according to the FCC and CENELEC specifications. The device holder can be locked at different phantom locations (left head, right head, flat phantom).

4.5.2 Phantom

The Generic Twin Phantom is constructed of a fiberglass shell integrated in a wooden table. The shape of the shell is based on data from an anatomical study designed to determine the maximum exposure in at least 90% of all users. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents the evaporation of the liquid. Reference markings on the Phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot.

| | |
|-----------------|---------------------------------|
| Shell Thickness | 2±0.1 mm |
| Filling Volume | Approx. 20 liters |
| Dimensions | 810 x 1000 x 500 mm (H x L x W) |
| Available | Special |



Picture6: Generic Twin Phantom

4.6 Equivalent Tissues

The liquid used for the frequency range of 800-2000 MHz consisted of water, sugar, salt and Cellulose. The liquid has previously been proven to be suited for worst-case. The Table 4 shows the detail solution. It's satisfying the latest tissue dielectric parameters requirements proposed by the IEEE 1528.

Table 4. Composition of the Head Tissue Equivalent Matter

| MIXTURE % | FREQUENCY 835MHz |
|---------------------------------------|--|
| Water | 41.45 |
| Sugar | 56.0 |
| Salt | 1.45 |
| Preventol | 0.1 |
| Cellulose | 1.0 |
| Dielectric Parameters Target Value | f=835MHz $\epsilon=41.5$ $\sigma=0.90$ |

Table 5. Composition of the Body Tissue Equivalent Matter

| MIXTURE % | FREQUENCY 835MHz |
|------------------------------------|--|
| Water | 52.5 |
| Sugar | 45.0 |
| Salt | 1.4 |
| Preventol | 0.1 |
| Cellulose | 1.0 |
| Dielectric Parameters Target Value | f=835MHz $\epsilon=55.2$ $\sigma=0.97$ |

4.7 System Specifications

4.7.1 Robotic System Specifications

Specifications

Positioner: Stäubli Unimation Corp. Robot Model: RX90L

Repeatability: ± 0.02 mm

No. of Axis: 6

Data Acquisition Electronic (DAE) System

Cell Controller

Processor: Pentium III

Clock Speed: 800 MHz

Operating System: Windows 2000

Data Converter

Features: Signal Amplifier, multiplexer, A/D converter, and control logic

Software: DASY4 software

Connecting Lines: Optical downlink for data and status info.

Optical uplink for commands and clock

5 CHARACTERISTICS OF THE TEST

5.1 Applicable Limit Regulations

EN 50360–2001: Product standard for the measurement of Specific Absorption Rate related to human exposure to electromagnetic fields from mobile phones.

It specifies the maximum exposure limit of **2.0 W/kg** as averaged over any 10 gram of tissue for portable devices being used within 20 mm of the user in the uncontrolled environment.

ANSI C95.1-1999: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

It specifies the maximum exposure limit of **1.6 W/kg** as averaged over any 1 gram of tissue for portable devices being used within 20 mm of the user in the uncontrolled environment.

5.2 Applicable Measurement Standards

EN 50361-2001: Basic standard for the measurement of Specific Absorption Rate related to human exposure to electromagnetic fields from mobile phones.

IEEE 1528-2003: Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques.

IEC 62209-1: Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Human models, instrumentation, and procedures –Part 1: Procedure to determine the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)

OET Bulletin 65 (Edition 97-01) and Supplement C(Edition 01-01): Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits.

They specify the measurement method for demonstration of compliance with the SAR limits for such equipments.

6 LABORATORY ENVIRONMENT

Table 6: The Ambient Conditions during EMF Test

| | |
|---|----------------------------|
| Temperature | Min. = 15 °C, Max. = 30 °C |
| Relative humidity | Min. = 30%, Max. = 70% |
| Ground system resistance | < 0.5 Ω |
| Ambient noise is checked and found very low and in compliance with requirement of standards. Reflection of surrounding objects is minimized and in compliance with requirement of standards. | |

7 CONDUCTED OUTPUT POWER MEASUREMENT

7.1 Summary

During the process of testing, the EUT was controlled via Rhode & Schwarz Digital Radio Communication tester (CMU-200) to ensure the maximum power transmission and proper modulation. This result contains conducted output power and ERP for the EUT. In all cases, the measured peak output power should be greater and within 5% than EMI measurement.

7.2 Conducted Power

7.2.1 Measurement Methods

The EUT was set up for the maximum output power. The channel power was measured with Agilent

**Telecommunication Metrology Center
of Ministry of Information Industry**

No. 2006E01013

Page 13 of 61

Spectrum Analyzer E4440A. These measurements were done at 3 channels, 1013, 384 and 777 before SAR test and after SAR test.

7.2.2 Measurement result

Table 7: Conducted Power Measurement Results

| | Conducted Power | | |
|----------------------|------------------------|------------------------|------------------------|
| | Channel 1013(824.7MHz) | Channel 384(836.52MHz) | Channel 777(848.31MHz) |
| Before Test (dBm) | 23.8 | 24.2 | 23.9 |
| After Test (dBm) | 23.6 | 24.3 | 23.7 |

7.2.3 Power Drift

To control the output power stability during the SAR test, DASY4 system calculates the power drift by measuring the E-field at the same location at the beginning and at the end of the measurement for each test position. These drift values can be found in Table 11 and Table 12 labeled as: (Power Drift [dB]). This ensures that the power drift during one measurement is within 5%.

8 TEST RESULTS

8.1 Dielectric Performance

Table 8: Dielectric Performance of Head Tissue Simulating Liquid

| Measurement is made at temperature 22.5 °C and relative humidity 49%. Liquid temperature during the test: 21.4°C | | | |
|---|-----------|-------------------------|-----------------------------|
| / | Frequency | Permittivity ϵ | Conductivity σ (S/m) |
| Target value | 835 MHz | 41.5 | 0.90 |
| Measurement value (Average of 10 tests) | 835 MHz | 41.7 | 0.88 |

Table 9: Dielectric Performance of Body Tissue Simulating Liquid

| Measurement is made at temperature 22.5 °C and relative humidity 49%. Liquid temperature during the test: 21.4°C | | | |
|---|-----------|-------------------------|-----------------------------|
| / | Frequency | Permittivity ϵ | Conductivity σ (S/m) |
| Target value | 835 MHz | 55.2 | 0.97 |
| Measurement value (Average of 10 tests) | 835 MHz | 54.6 | 0.95 |

8.2 System Validation

Table 10: System Validation

| Measurement is made at temperature 23.3 °C, relative humidity 47%, input power 250 mW. Liquid temperature during the test: 22.5°C | | | | | |
|--|-----------|---------------------|-------------------------|-----------------------------|-------------|
| Liquid parameters | | Frequency | Permittivity ϵ | Conductivity σ (S/m) | |
| | | 835 MHz | 41.7 | 0.88 | |
| Verification results | Frequency | Target value (W/kg) | | Measurement value (W/kg) | |
| | | 10 g Average | 1 g Average | 10 g Average | 1 g Average |
| | 835 MHz | 1.55 | 2.375 | 1.62 | 2.48 |

**Telecommunication Metrology Center
of Ministry of Information Industry**

No. 2006E01013

Page 14 of 61

Note: Target Values used are one fourth of those in IEEE Std 1528-2003 (feeding power is normalized to 1 Watt), i.e. 250 mW is used as feeding power to the validation dipole (SPEAG using).

8.3 Summary of Measurement Results

Table 11: SAR Values (Head, 835 MHz Band)

| Limit of SAR (W/kg) | 10 g Average | 1 g Average | Power Drift (dB) |
|--|---------------------------|-------------|------------------|
| | 2.0 | 1.6 | |
| Test Case | Measurement Result (W/kg) | | |
| | 10 g Average | 1 g Average | |
| Left hand, Touch cheek, Top frequency(See Fig.1) | 0.826 | 1.25 | -0.200 |
| Left hand, Touch cheek, Mid frequency(See Fig.3) | 0.406 | 0.610 | -0.200 |
| Left hand, Touch cheek, Bottom frequency(See Fig.5) | 0.484 | 0.734 | -0.059 |
| Left hand, Tilt 15 Degree, Top frequency(See Fig.7) | 0.225 | 0.303 | 0.186 |
| Left hand, Tilt 15 Degree, Mid frequency(See Fig.9) | 0.105 | 0.140 | 0.154 |
| Left hand, Tilt 15 Degree, Bottom frequency(See Fig.11) | 0.117 | 0.156 | -0.200 |
| Right hand, Touch cheek, Top frequency(See Fig.13) | 0.757 | 1.14 | -0.200 |
| Right hand, Touch cheek, Mid frequency(See Fig.15) | 0.361 | 0.542 | 0.183 |
| Right hand, Touch cheek, Bottom frequency(See Fig.17) | 0.412 | 0.620 | -0.125 |
| Right hand, Tilt 15 Degree, Top frequency(See Fig.19) | 0.250 | 0.341 | 0.103 |
| Right hand, Tilt 15 Degree, Mid frequency(See Fig.21) | 0.124 | 0.170 | 0.074 |
| Right hand, Tilt 15 Degree, Bottom frequency(See Fig.23) | 0.156 | 0.214 | -0.200 |

**Telecommunication Metrology Center
of Ministry of Information Industry**

No. 2006E01013

Page 15 of 61

Table 12: SAR Values (Body, 835 MHz Band)

| Limit of SAR (W/kg) | 10 g Average | 1 g Average | Power Drift (dB) |
|--|---------------------------|-------------|------------------|
| | 2.0 | 1.6 | |
| Test Case | Measurement Result (W/kg) | | |
| | 10 g Average | 1 g Average | |
| Body, Towards Ground, Top frequency(See Fig.25) | 0.528 | 0.764 | -0.200 |
| Body, Towards Ground, Mid frequency(See Fig.27) | 0.254 | 0.367 | -0.200 |
| Body, Towards Ground, Bottom frequency(See Fig.29) | 0.264 | 0.382 | 0.030 |

8.4 Conclusion

Localized Specific Absorption Rate (SAR) of this portable wireless device has been measured in all cases requested by the relevant standards cited in Clause 5.2 of this report. Maximum localized SAR is below exposure limits specified in the relevant standards cited in Clause 5.1 of this test report.

9 Measurement Uncertainty

| SN | a | Type | c | d | e = f(d,k) | f | h = c x f / e | k |
|----|---|------|------------|-------------|------------|--------------------------|-------------------------|----------------|
| | Uncertainty Component | | Tol. (± %) | Prob. Dist. | Div. | c _i (1 g) | 1 g u _i (±%) | v _i |
| 1 | System repetivity | A | 0.5 | N | 1 | 1 | 0.5 | 9 |
| | Measurement System | | | | | | | |
| 2 | Probe Calibration | B | 5 | N | 2 | 1 | 2.5 | ∞ |
| 3 | Axial Isotropy | B | 4.7 | R | √3 | $\frac{(1-cp)^{1/2}}{2}$ | 4.3 | ∞ |
| 4 | Hemispherical Isotropy | B | 9.4 | R | √3 | √c _p | | ∞ |
| 5 | Boundary Effect | B | 0.4 | R | √3 | 1 | 0.23 | ∞ |
| 6 | Linearity | B | 4.7 | R | √3 | 1 | 2.7 | ∞ |
| 7 | System Detection Limits | B | 1.0 | R | √3 | 1 | 0.6 | ∞ |
| 8 | Readout Electronics | B | 1.0 | N | 1 | 1 | 1.0 | ∞ |
| 9 | RF Ambient Conditions | B | 3.0 | R | √3 | 1 | 1.73 | ∞ |
| 10 | Probe Positioner Mechanical Tolerance | B | 0.4 | R | √3 | 1 | 0.2 | ∞ |
| 11 | Probe Positioning with respect to Phantom Shell | B | 2.9 | R | √3 | 1 | 1.7 | ∞ |
| 12 | Extrapolation, interpolation and Integration Algorithms for Max. SAR Evaluation | B | 3.9 | R | √3 | 1 | 2.3 | ∞ |
| | Test sample Related | | | | | | | |

**Telecommunication Metrology Center
of Ministry of Information Industry**

No. 2006E01013

Page 16 of 61

| | | | | | | | | |
|--|--|---|-----|---|------------|------|-------|----------|
| 13 | Test Sample Positioning | A | 4.9 | N | 1 | 1 | 4.9 | N-1 |
| 14 | Device Holder Uncertainty | A | 6.1 | N | 1 | 1 | 6.1 | N-1 |
| 15 | Output Power Variation - SAR drift measurement | B | 5.0 | R | $\sqrt{3}$ | 1 | 2.9 | ∞ |
| Phantom and Tissue Parameters | | | | | | | | |
| 16 | Phantom Uncertainty (shape and thickness tolerances) | B | 1.0 | R | $\sqrt{3}$ | 1 | 0.6 | ∞ |
| 17 | Liquid Conductivity - deviation from target values | B | 5.0 | R | $\sqrt{3}$ | 0.64 | 1.7 | ∞ |
| 18 | Liquid Conductivity - measurement uncertainty | B | 5.0 | N | 1 | 0.64 | 1.7 | M |
| 19 | Liquid Permittivity - deviation from target values | B | 5.0 | R | $\sqrt{3}$ | 0.6 | 1.7 | ∞ |
| 20 | Liquid Permittivity - measurement uncertainty | B | 5.0 | N | 1 | 0.6 | 1.7 | M |
| Combined Standard Uncertainty | | | | | | | 11.25 | |
| Expanded Uncertainty (95% CONFIDENCE INTERVAL) | | | | | K=2 | | 22.5 | |

10 MAIN TEST INSTRUMENTS

Table13: List of Main Instruments

| No. | Name | Type | Serial Number | Calibration Date | Valid Period |
|-----|------------------|--------------|---------------|--------------------------|--------------|
| 01 | Network analyzer | HP 8753E | US38433212 | August 29,2005 | One year |
| 02 | Power meter | NRVD | 101253 | June 20, 2006 | One year |
| 03 | Power sensor | NRV-Z5 | 100333 | | |
| 04 | Power sensor | NRV-Z6 | 100011 | September 3, 2005 | One year |
| 05 | Signal Generator | E4433B | US37230472 | September 5, 2005 | One Year |
| 06 | Amplifier | VTL5400 | 0505 | No Calibration Requested | |
| 07 | BTS | CMU 200 | 105948 | August 15, 2005 | One year |
| 08 | E-field Probe | SPEAG ET3DV6 | 1736 | November 25, 2005 | One year |
| 09 | DAE | SPEAG DAE3 | 536 | July 11, 2005 | One year |

11 TEST PERIOD

The test is performed from May 13th to May 15th, 2006.

12 TEST LOCATION

The test is performed at Radio Communication & Electromagnetic Compatibility Laboratory of Telecommunication Metrology Center

END OF REPORT BODY

ANNEX A MEASUREMENT PROCESS

The evaluation was performed with the following procedure:

Step 1: Measurement of the SAR value at a fixed location above the reference point was measured and was used as a reference value for assessing the power drop.

Step 2: The SAR distribution at the exposed side of the phantom was measured at a distance of 3.9 mm from the inner surface of the shell. The area covered the entire dimension of the flat phantom and the horizontal grid spacing was 10 mm x 10 mm. Based on this data, the area of the maximum absorption was determined by spline interpolation.


Step 3: Around this point, a volume of 30 mm x 30 mm x 30 mm was assessed by measuring 7 x 7 x 7 points. On this basis of this data set, the spatial peak SAR value was evaluated with the following procedure:

a. The data at the surface were extrapolated, since the center of the dipoles is 2.7 mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.2 mm. The extrapolation was based on a least square algorithm. A polynomial of the fourth order was calculated through the points in z-axes. This polynomial was then used to evaluate the points between the surface and the probe tip.

b. The maximum interpolated value was searched with a straightforward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1g or 10g) were computed using the 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the "Not a knot"-condition (in x ~ y and z-directions). The volume was integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were interpolated to calculate the average.

c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.

Step 4: Re-measurement the SAR value at the same location as in Step 1. If the value changed by more than 5%, the evaluation is repeated.




Picture A: SAR Measurement Points in Area Scan

ANNEX B TEST LAYOUT



Picture B1: Specific Absorption Rate Test Layout



Picture B2: Liquid depth in the Flat Phantom (CDMA 835 MHz)



Picture B3: Left Hand Touch Cheek Position




Picture B4: Left Hand Tilt 15° Position



Picture B5: Right Hand Touch Cheek Position



Picture B6: Right Hand Tilt 15° Position



Picture B7: Body-worn Position (toward ground, the distance from handset to the bottom of the Phantom is 1.5cm)

ANNEX C GRAPH RESULTS

CDMA 1X Left Cheek High

Electronics: DAE3 Sn536

Communication System: CDMA 1X-new Frequency: 848.31 MHz Duty Cycle: 1:1

Probe: ET3DV6 - SN1736 ConvF(6.51, 6.51, 6.51)

Cheek High/Area Scan (51x111x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (interpolated) = 1.40 mW/g


Cheek High/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm,
dz=5mm

Reference Value = 8.31 V/m; Power Drift = -0.200 dB

Peak SAR (extrapolated) = 1.73 W/kg

SAR(1 g) = 1.25 mW/g; SAR(10 g) = 0.826 mW/g

Maximum value of SAR (measured) = 1.33 mW/g



0 dB = 1.33mW/g

Fig. 1 Left Hand Touch Cheek CDMA 835MHz CH777




Fig. 2 Z-Scan at power reference point (CDMA 835MHz CH777)

CDMA 1X Left Cheek Middle

Electronics: DAE3 Sn536

Communication System: CDMA 1X-new Frequency: 836.52 MHz Duty Cycle: 1:1

Probe: ET3DV6 - SN1736 ConvF(6.51, 6.51, 6.51)

Cheek Middle/Area Scan (51x111x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (interpolated) = 0.691 mW/g


Cheek Middle/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm,
dz=5mm

Reference Value = 5.97 V/m; Power Drift = -0.200 dB

Peak SAR (extrapolated) = 0.838 W/kg

SAR(1 g) = 0.610 mW/g; SAR(10 g) = 0.406 mW/g

Maximum value of SAR (measured) = 0.653 mW/g



0 dB = 0.653mW/g

Fig. 3 Left Hand Touch Cheek CDMA 835MHz CH384




Fig. 4 Z-Scan at power reference point (CDMA 835MHz CH384)

CDMA 1X Left Cheek Low

Electronics: DAE3 Sn536

Communication System: CDMA 1X-new Frequency: 824.7 MHz Duty Cycle: 1:1

Probe: ET3DV6 - SN1736 ConvF(6.51, 6.51, 6.51)

Cheek Low/Area Scan (51x111x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (interpolated) = 0.810 mW/g


Cheek Low/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm,
dz=5mm

Reference Value = 6.34 V/m; Power Drift = -0.059 dB

Peak SAR (extrapolated) = 1.02 W/kg

SAR(1 g) = 0.734 mW/g; SAR(10 g) = 0.484 mW/g

Maximum value of SAR (measured) = 0.788 mW/g



0 dB = 0.788mW/g

Fig. 5 Left Hand Touch Cheek CDMA 835MHz CH1013




Fig. 6 Z-Scan at power reference point (CDMA 835MHz CH1013)

CDMA 1X Left Tilt High

Electronics: DAE3 Sn536

Communication System: CDMA 1X-new Frequency: 848.31 MHz Duty Cycle: 1:1

Probe: ET3DV6 - SN1736 ConvF(6.51, 6.51, 6.51)

Tilt High/Area Scan (51x111x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.319 mW/g

Tilt High/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.4 V/m; Power Drift = 0.186 dB

Peak SAR (extrapolated) = 0.381 W/kg

SAR(1 g) = 0.303 mW/g; SAR(10 g) = 0.225 mW/g

Maximum value of SAR (measured) = 0.317 mW/g




Fig. 7 Left Hand Tilt 15°CDMA 835MHz CH777




Fig. 8 Z-Scan at power reference point (CDMA 835MHz CH777)

CDMA 1X Left Tilt Middle

Electronics: DAE3 Sn536

Communication System: CDMA 1X-new Frequency: 836.52 MHz Duty Cycle: 1:1

Probe: ET3DV6 - SN1736 ConvF(6.51, 6.51, 6.51)

Tilt Middle/Area Scan (51x111x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (interpolated) = 0.143 mW/g


Tilt Middle/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm,
dz=5mm

Reference Value = 7.21 V/m; Power Drift = 0.154 dB

Peak SAR (extrapolated) = 0.176 W/kg

SAR(1 g) = 0.140 mW/g; SAR(10 g) = 0.105 mW/g

Maximum value of SAR (measured) = 0.146 mW/g



0 dB = 0.146mW/g

Fig. 9 Left Hand Tilt 15°CDMA 835MHz CH384