



EMC Test Report

Product Name:
HUAWEI IDEOS SERIES; cdma2000 Digital Mobile Phone;
IDEOS

Model Number:HUAWEI C8150-1

Report No: SYBHZ(R)E071092010EB-1
FCC ID:QISC8150-1

Reliability Laboratory of Huawei Technologies Co., Ltd.

Huawei Base, Bantian, Longgang District, Shenzhen 518129, P.R. China

Tel: +86 755 28780808 Fax: +86 755 89652518

Notice 1

1. The laboratory has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS), and accreditation number: L0310.
2. The laboratory has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements. The site recognition number is 97456.
3. The laboratory has been listed by industry Canada to perform electromagnetic emission measurement. The site recognition number is 6369A-1.
4. The test report is invalid if not marked with "exclusive stamp for the test report".
5. The test report is invalid if not marked with the stamps or the signatures of the persons responsible for performing, revising and approving the test report.
6. The test report is invalid if there is any evidence of erasure and/or falsification.
7. If there is any dissidence for the test report, please file objection to the test centre within 15 days from the date of receiving the test report.
8. Normally, the test report is only responsible for the samples that have undergone the test.
9. Context of the test report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of the laboratory.

Notice 2

Modification Information:

Modification Information


Modification Information	1	
	2	
	3	<i>Not Applicable!</i>
	4	
	5	
	6	
	7	

REPORT ON	EMC Test of C8150-1
	M/N: HUAWEI C8150-1
REGULATION	FCC CFR47 Part 15: Subpart B;
	FCC CFR47 Part 22: Subpart H;
START OF TEST	Sep. 29, 2010
END OF TEST	Oct. 12, 2010
Final Judgement:	Pass

Approved By

2010-10-12
Date

Liuchunlin
Name



Signature

Reviewed By

2010-10-12
Date

Dailinjun
Name



Signature

Operator

2010-10-12
Date

Wenjianfeng
Name



Signature

REPORT BODY CONTENT

1	Status.....	6
1.1	Product Information.....	6
1.2	Test Site.....	6
1.3	Test environment condition.....	6
2	Summary of Results.....	7
3	Equipment Specification	8
3.1	General Description	8
3.2	Sub-Assembly Identity	8
4	System Configuration during EMC Test.....	9
4.1	Cables Used during Test	9
4.2	Associated Equipment Used during Test.....	9
4.3	Test Configurations and Test Mode.....	9
4.4	Test conditions and test connections.....	10
5	Electromagnetic Interference (EMI)	11
5.1	Radiated Disturbance 30MHz to 18GHz	11
5.2	Conducted Disturbance 0.15 MHz to 30MHz	12
5.3	Radiated Spurious Emissions	13
6	Main Test Instruments	15
7	System Measurement Uncertainty	16
8	Graph and Data of Emission Test.....	17
8.1	Radiated Disturbance	17
8.2	Conducted Disturbance	19
8.3	Radiated Spurious Emission.....	20

1 Status

1.1 Product Information

CLIENT:	Huawei Technologies Co., Ltd.
ADDRESS:	Bantian Longgang District Shenzhen, P.R. China
MANUFACTURING DESCRIPTION	HUAWEI IDEOS SERIES; cdma2000 Digital Mobile Phone; IDEOS
MANUFACTURERS MODEL NUMBER	C8150-1

1.2 Test Site

Site 1:

EMC LABORATORY OF RELIABILITY LABORATORY OF HUAWEI TECHNOLOGIES CO., LTD

1.3 Test environment condition

Ambient temperature	20~25°C
Relative humidity	40%~52%
Atmospheric pressure	101kPa

2 Summary of Results

Table 2 below shows a brief summary of the results obtained.

Summary of results

EUT Classification: Wireless Terminal				
Test Items	Test Configuration & Test Mode	Required Performance Criteria	Result	Site
<u>Radiated Emissions</u> Enclosure Port	TC1/TC2 (TM6-TM10)	N/A	Pass	Site1
<u>Conducted Emissions</u>	TC1 (TM1- TM10)	N/A	Pass	Site1
<u>Radiated Spurious Emissions</u> Enclosure Port	TC1 (TM1- TM3)	N/A	Pass	Site1

Note:
1, Measurement taken is within the measurement uncertainty of measurement system.
2, TC = Test configuration

3 Equipment Specification

3.1 General Description

HUAWEI IDEOS SERIES; cdma2000 Digital Mobile Phone; IDEOS — HUAWEI C8150-1 is subscriber equipment in the CDMA/EVDO system. The frequency band is US Cellular, it can be included in this report. The Mobile Phone implements such functions as RF signal receiving/transmitting, CDMA2000 1x and 1XEV-DO protocol processing, voice, MMS service, GPS, AGPS and WIFI etc. Externally it provides micro SD card interface, earphone port(to provide voice service) .

3.1.1 Main Equipment Technical Data

Description:	HUAWEI IDEOS SERIES; cdma2000 Digital Mobile Phone; IDEOS
Models:	C8150-1
Input Rated Voltage	\equiv 3.7V
Extreme Voltage	3.6V and 4.2V
Rated Power	Normal 3W ,Max 8 W
Dimensions	103mm (L)×55mm (W)×14mm (H)
Weight	<110g (with battery)

Mode		Work Frequency	
		Transmitt Frequency (MHz)	Receive Frequency (MHz)
CDMA2000 1x and 1XEV-DO	CDMA/EVDO800	824-849	869-894
Bluetooth		2400-2483.5	
WIFI		2400-2483.5	

3.2 Sub-Assembly Identity

Board				
Model Name	Qty.	Serial	Description	
HC1C815M	1	1M2AA11060503491	Main board of Mobile Phone	
Accessory				
Name	Qty.	Manufacturer	Serials number	Description
Adapter	1	Huawei Technologies Co.	HKAA74963016	Model:HW-050100U1W Input voltage: ~100-240V ;50/60Hz Output voltage: \equiv +5.0V, 1A Rate power: 5W
Adapter	1	Huawei Technologies Co.	HKAA74963018	Model:HW-050100B1W Input voltage: ~100-240V ;50/60Hz Output voltage: \equiv +5.0V, 1A Rate power: 5W
Adapter	1	Huawei Technologies Co.	HKAA74963017	Model:HW-050100E1W Input voltage: ~100-240V ;50/60Hz Output voltage: \equiv +5.0V, 1A Rate power: 5W
Rechargeable Li-ion	1	Huawei Technologies Co., Ltd.	UNHA325V11300324	Battery Model: HB4J1H Rated capacity: 1200mAh Nominal Voltage: \equiv +3.7V Charging Voltage: \equiv +4.2V

4 System Configuration during EMC Test

The Equipment under Test (EUT) was functioning correctly during all tests. The EUT was installed within the test site and was configured to simulate a typical user installation.

4.1 Cables Used during Test

Cable Used during Test

Cable	Quantity	Type of Cable
AC Power Port	1	Unshielded
USB	1	shielded
Earphone	1	Unshielded

4.2 Associated Equipment Used during Test

Associated Equipment Used during Test

Name	Model	Manufacturer	S/N	Cal Date	Cal Interval (month)
Radio Communication Tester	CMU200	R&S	3607033573	2010-03-12	12
Notebook	D810	DELL	3105083303	NA	NA

4.3 Test Configurations and Test Mode

4.3.1 Test Configuration.

The EUT will be connected to test system (Base Station Simulator) in order to simulate normal operating conditions (with reference to the guidance given in the standard for this type of equipment).

TC1:EUT powered with an adapter and connected to the test system (Base Station Simulator).

TC2:EUT connected to the notebook by USB port.

Configuration table

TC1/TC2	TM1~TM10
---------	----------

4.3.2 Test Mode

There were 10 test Modes. TM1 and TM10 were shown in the diagrams below:

TM1	operate in traffic mode CDMA800;
TM2	operate in traffic mode EVDO800.0;
TM3	operate in traffic mode EVDO800.A;
TM4	operate in traffic mode Bluetooth;
TM5	operate in traffic mode WIFI;
TM6	operate in idle mode CDMA800;
TM7	operate in idle mode EVDO800.0;
TM8	operate in idle mode EVDO800.A;
TM9	operate in idle mode Bluetooth;
TM10	operate in idle mode WIFI;

4.4 Test conditions and test connections

4.4.1 Test Conditions

The EUT will be connected to test system (Base Station Simulator) in order to simulate normal operating conditions (with reference to the guidance given in the standard for this type of equipment).


4.4.2 Test connections

Traffic Mode:

The EUT is required to be in the traffic mode, a call is set up according to the generic call set up procedure and enter the EUT into loop back test mode.

For CDMA, the following conditions shall also be met:

- The EUT shall be commanded to operate at maximum transmit power;



: Test Configuration

Idle Mode:

The EUT will be connected to test system (Base Station Simulator) in order to simulate normal operating conditions (with reference to the guidance given in the standard for this type of equipment).

The EUT is required to be in the idle mode.

For CDMA, the following conditions shall be met:

- UE shall be camped on a cell;
- UE shall perform Location Registration (LR) before the test, but not during the test;
- UE's neighbour cell list shall be empty;

For Cellular, the following conditions shall be met:

When the EUT is required to be in the idle mode, the test system shall simulate a Base Station (BS) with Broadcast Control Channel/Common Control Channel (BCCH/CCCH) on one carrier. The EUT shall be synchronized to the BCCH, listening to the CCCH and able to respond to paging messages. Periodic Location Updating shall be disabled.

5 Electromagnetic Interference (EMI)

5.1 Radiated Disturbance 30MHz to 18GHz

5.1.1 Test Procedure

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4dB according to the standards: ANSI C63.4. The test distance was 3m. The set-up and test methods were according to ANSI 63.4 and CAN/CSA-CEI/IEC CISPR 22


A preliminary scan and a final scan of the emissions were made from 30 MHz to 18 GHz by using test script of software; the emissions were measured using Quasi-Peak Detector (30MHz~1GHz) and AV detector (above 1GHz). The maximal emission value was acquired by adjusting the antenna height, polarisation and turntable azimuth in accordance with the software setup. Normally, the height range of antenna was 1m to 4m, the azimuth range of turntable was 0° to 360°, The receive antenna has two polarizations V and H.

EUT was configured in idle mode and the test performed at worst emission state.

Measurement bandwidth: 30 MHz – 1000 MHz: 120 k Hz

Measurement bandwidth: 1GHz – 18GHz: 1MHz

Test set up figure:



Test set up

5.1.2 Test Results

The EUT has met the requirements for Radiated Emission of enclosure port.

The test data is shown in section 8.1 of the report.

Test Limits

Frequency of Emission (MHz)	Radiated Limit	
	Unit($\mu\text{V}/\text{m}$)	Unit($\text{dB}\mu\text{V}/\text{m}$)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

5.2 Conducted Disturbance 0.15 MHz to 30MHz

5.2.1 Test Procedure

The Table-top EUT was placed upon a non-metallic table 0.8 m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.4: 2003.


Conducted Disturbance at AC Port measurements were undertaken on the L and N Lines. The emissions were measured using a Quasi-Peak Detector and Average Detector.

Huawei Mobile Station was communicated with the BTS simulator through Air interface, the BTS simulator controls the Mobile Station to transmitter the maximum power which defined in specification of product. The Mobile Station operated on the typical channel.

Measurement bandwidth (RBW) for 150kHz to 30 MHz: 9 kHz;

Test Set-up figure:

The Mobile Station was setup in the screened chamber and operated under nominal conditions.



Test Set-up

5.2.2 Test Results

The EUT has met requirements for Conducted disturbance of signal lines. The test data is shown in section 8.2 of the report.

Test Limit of DC&AC Power Port

Frequency range	150kHz~ 30MHz	
Classification	Class B	
Limit(Class B)	Voltage limits	
	QP	AV
0.15MHz~0.5MHz	66~56 dB μ V	56~46 dB μ V
0.5MHz~5MHz	56 dB μ V	46 dB μ V
5MHz~30MHz	60 dB μ V	50 dB μ V

5.3 Radiated Spurious Emissions


5.3.1 Test Procedure

A test site fulfilling the requirements of ITU-R Recommendation SM329-10 was used. The EUT was placed on a non-conducting support in the anechoic chamber and was operated from a power source via an RF filter to avoid radiation from the power leads.

Step 1:


For transmitters other than single sideband, independent sideband and controlled carrier radiotelephone, ERP shall be measured when the transmitter is adjusted in accordance with the tune-up procedure to give the values of current and voltage on the circuit elements specified in 2.1033(c)(8). Connect the EUT to the BTS simulator via the air interface.

Test the Radiated maximum output power by the Rohde and Schwarz ESIB26 Test Receiver from test antenna.



Step 2:

Use substitution method to verify the maximum output power. The EUT is substituted by a dipole antenna. The dipole is connected to a signal generator. And then adjust the output level of the signal generator to get the same received power recorded in step1 on ESIB26 Test Receiver, and record the power level of Signal Generator. Of course, the cable loss at the test frequency should be compensated.



Test should be performed in normal voltage condition.

According to part 22.917, the defined measurement bandwidth as following:

22.917(b) Measurement procedure: Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater.

Measurement bandwidth (RBW) for 9 kHz up to 150 kHz: 1 kHz;
Measurement bandwidth (RBW) for 150 kHz up to 30 MHz: 10 kHz;
Measurement bandwidth (RBW) for 30MHz up to 1 GHz: 100 kHz;
Measurement bandwidth (RBW) for 1GHz up to 18GHz: 1MHz;

Radiated Spurious Emissions Limits

Frequency band	Minimum requirement (E.R.P) traffic mode
9KHz~18GHz	-13dBm

No peak found in pre- test. All frequency points' margin is bigger than 20dB, so the substitution method isn't used.

Calculation Sample:

Substitution Results

Freq. [MHz]	Measurement Value [dBm]	Substitution Antenna Type	Gain [dBd]	Cable Loss [dB]	Signal Generator Level [dBm]	Substitution Level [dBm]	FCC limit [dBm]	Result

Note: For get the E.R.P. (Efficient Radiated Power) in substitution method, the following formula should take to calculate it,

$$E.R.P. [dBm] = SGP [dBm] - Cable Loss [dB] + Gain [dBd]$$

NOTE: SGP- Signal Generator Level

5.3.2 Test Results

The EUT has met the requirements of FCC Part22 requirement.

6 Main Test Instruments

Main Test Equipments

Test item	Test Instrument	Model	Manufacturer	Cal-Date	Cal Interval (month)
RE&CE	EMI Test receiver	ESU26	R&S	Jun.25, 2010	12
	Broadband Antenna	VULB 9163	SCHWARZBECK	May.15, 2010	12
	Horn Antenna	HF906	R&S	May.15, 2010	12
	LISN	ENV216	R&S	Jul.25, 2010	12
RSE	EMI Test receiver	ESIB26	R&S	April.22, 2010	12
	Broadband Antenna	CBL6112B	SCHAFFNER	Nov.30.2009	12
	Horn Antenna	3117	ETS-Lindgren	Oct.28.2009	12
	Horn Antenna	3160	ETS-Lindgren	Oct.28.2009	12
Software Information					
Test Item	Software Name	Manufacturer	Version		
RE/CE	ES-K1	R&S	1.7.1		
RSE	EMC32	R&S	V5.10.99		

7 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

System Measurement Uncertainty


Items		Extended Uncertainty
RE	Field strength (dB μ V/m)	U=4.1dB; k=2(30MHz-1GHz) U=4.1dB; k=2(1GHz-18GHz)
RSE	ERP (dBm)	U=2.2dB; k=2
CE	Disturbance Voltage (dB μ V)	U=3.4dB; k=2

8 Graph and Data of Emission Test

8.1 Radiated Disturbance

This test was carried out in all the test modes, Here only the worst test result was shown.


30MHz-1GHz



MEASUREMENT RESULT: QP Detector

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Height cm	Azimuth deg	Polarisation
32.340000	23.10	11.7	40.0	16.9	107.0	140.00	VERTICAL
94.560000	23.50	12.7	43.5	20.0	200.0	95.00	HORIZONTAL
203.340000	23.20	12.2	43.5	20.3	143.0	121.00	HORIZONTAL
310.200000	27.50	15.8	46.0	18.5	101.0	162.00	HORIZONTAL
472.380000	26.80	19.4	46.0	19.2	200.0	352.00	HORIZONTAL
838.140000	33.00	25.4	46.0	13.0	160.0	110.00	VERTICAL

1GHz-18GHz




MEASUREMENT RESULT: AV Detector

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Height cm	Azimuth deg	Polarisation
2202.500000	20.70	-11.8	54.0	33.3	100.0	1.00	HORIZONTAL
3350.500000	23.10	-7.9	54.0	30.9	100.0	359.00	VERTICAL
3501.000000	24.00	-7.4	54.0	30.0	100.0	144.00	HORIZONTAL
7534.500000	28.10	1.5	54.0	25.9	100.0	286.00	HORIZONTAL
10994.000000	30.70	6.7	54.0	23.3	100.0	353.00	HORIZONTAL
17952.000000	36.10	17.0	54.0	17.9	100.0	306.00	VERTICAL

8.2 Conducted Disturbance

8.2.1 AC Port Test Data

This test was carried out in all the test modes, Here only the worst test result was shown.



MEASUREMENT RESULT: QP Detector

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Line	PE
0.186000	38.90	10.1	64	25.1	N	FLO
0.312000	34.00	10.0	60	26.0	N	FLO
0.562000	32.20	10.1	56	23.8	N	FLO
0.638000	34.30	10.1	56	21.7	N	FLO
2.076000	31.00	10.1	56	25.0	N	FLO
6.110000	26.80	10.2	60	33.2	N	FLO

MEASUREMENT RESULT: AV Detector


Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Line	PE
0.206000	25.40	10.0	53	27.6	N	FLO
0.310000	27.20	10.0	50	22.8	N	FLO
0.390000	29.00	10.0	48	18.0	N	FLO
0.486000	21.60	10.1	46	24.4	N	FLO
1.124000	24.60	10.1	46	21.4	N	FLO
2.476000	23.00	10.1	46	23.0	N	FLO

8.3 Radiated Spurious Emission


This test results are the maximum level of radiated spurious emissions in vertical and horizontal polarity. The highest peak exceeds the limit line is carrier frequency.

8.3.1 For CDMA800


Traffic Mode (9kHz-30MHz)



Traffic Mode (30MHz-2GHz)




Traffic Mode (2GHz-18GHz)




8.3.2 For EVDO800.0


Traffic Mode (9kHz-30MHz)




Traffic Mode (30MHz-2GHz)




Traffic Mode (2GHz-18GHz)




8.3.3 For EVDO800.A Traffic Mode (9kHz-30MHz)



Traffic Mode (30MHz-2GHz)



Traffic Mode (2GHz-18GHz)



END