

FCC - TEST REPORT

Report Number : **68.950.18.0336.01** Date of Issue: **August 7, 2018**

Model : **CP60**

Product Type : HUAWEI WIRELESS CHARGER

Applicant : Huawei Technologies Co., Ltd.

Address : Administration Building, Headquarters of Huawei Technologies Co.,
: Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C

Manufacturer : Huawei Technologies Co., Ltd.

Address : Administration Building, Headquarters of Huawei Technologies Co.,
: Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C

Test Result : Positive Negative

Total pages including Appendices : **19**

TÜV SÜD Certification and Testing (China) Co., Ltd. – Shenzhen Branch is a subcontractor to TÜV SÜD Product Service GmbH according to the principles outlined in ISO 17025.

TÜV SÜD Certification and Testing (China) Co., Ltd. – Shenzhen Branch reports apply only to the specific samples tested under stated test conditions. Construction of the actual test samples has been documented. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. The manufacturer/importer is responsible to the Competent Authorities in Europe for any modifications made to the production units which result in non-compliance to the relevant regulations. TÜV SÜD Certification and Testing (China) Co., Ltd. – Shenzhen Branch shall have no liability for any deductions, inferences or generalizations drawn by the client or others from TÜV SÜD Certification and Testing (China) Co., Ltd. – Shenzhen Branch issued reports.

This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval



1 Table of Contents

| | | |
|-----|--|----|
| 1 | Table of Contents | 2 |
| 2 | Details about the Test Laboratory | 3 |
| 3 | Description of the Equipment Under Test | 4 |
| 4 | Summary of Test Standards | 5 |
| 5 | Summary of Test Results..... | 6 |
| 6 | General Remarks | 7 |
| 7 | Test Setups | 8 |
| 8 | Systems test configuration..... | 9 |
| 9 | Technical Requirement..... | 10 |
| 9.1 | Conducted Emission Test | 10 |
| 9.2 | 20 dB Bandwidth and 99% Occupied Bandwidth | 13 |
| 9.3 | Radiated Emission Test | 14 |
| 10 | Test Equipment List..... | 18 |
| 11 | System Measurement Uncertainty..... | 19 |



2 Details about the Test Laboratory

Details about the Test Laboratory

Test Site 1

Company name: TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch
Building 12 & 13, Zhiheng Wisdomland Business Park, Nantou Checkpoint
Road 2, Nanshan District
Shenzhen 518052
P.R. China

Telephone: 86 755 8828 6998

Fax: 86 755 828 5299

FCC Registration 514049

No.:

IC Registration 10320A

No.:



3 Description of the Equipment Under Test

Product: HUAWEI WIRELESS CHARGER

Model no.: CP60

FCC ID: QISCP60

Options and accessories: Adapter and USB Cable

Rating: 5-12Vdc 2A Max supplied by an external adapter

Adapter information: Manufacturer: Huawei Technologies Co.,Ltd.
Model: HW-100400U00
Input voltage:100-240V 50/60Hz 1.2A
Output voltage:5V \equiv 2A or 9V \equiv 2A or 10V \equiv 4A Max

RF Transmission Frequency: 111-148KHz

Antenna Type: Integrated coil antenna

Description of the EUT: The Equipment Under Test (EUT) is a wireless charger which operated at 111-148kHz.



4 Summary of Test Standards

| Test Standards | |
|--|--|
| FCC Part 15 Subpart C 10-1-2017 Edition | PART 15 - RADIO FREQUENCY DEVICES Subpart C - Intentional Radiators |

All the test methods were according to ANSI C63.10 (2013).

5 Summary of Test Results

| Technical Requirements | | | | | | |
|------------------------|----------------------------------|------------|-----------|-------------------------------------|--------------------------|--------------------------|
| FCC Part 15 Subpart C | | | | | | |
| Test Condition | | Pages | Test Site | Test Result | | |
| | | | | Pass | Fail | N/A |
| §15.207 | Conducted emission AC power port | 10 | Site 1 | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| -- | 20dB bandwidth | 13 | Site 1 | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| §15.205 | Restricted bands of operation | 13 | Site 1 | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| §15.209 | Radiated emission | 14 | Site 1 | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| §15.203 | Antenna requirement | See note 1 | | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |

Note 1: The EUT uses an Integrated coil antenna, which gain is 0dBi. In accordance to §15.203, it is considered sufficiently to comply with the provisions of this section.



6 General Remarks

Remarks

This submittal(s) (test report) is intended for FCC ID: QISCP60, complies with Section 15.207, 15.209, 15.205 of the FCC Part 15, Subpart C rules.

SUMMARY:

All tests according to the regulations cited on page 5 were

- Performed

- **Not** Performed

The Equipment under Test

- **Fulfills** the general approval requirements.

- **Does not** fulfill the general approval requirements.

Sample Received Date: July 30, 2018

Testing Start Date: August 1, 2018

Testing End Date: August 2, 2018

- TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch -

Reviewed by:

John Zhi
Project Manager

Prepared by:

Alan Xiong
Project Engineer


Tested by:

Tree Zhan
Test Engineer


7 Test Setups

7.1 Radiated test setups


Below 30MHz



30MHz-1GHz



7.2 Conducted RF test setups





8 Systems test configuration

Auxiliary Equipment Used during Test:

| Description | Manufacturer | Model NO. | S/N |
|--------------|--------------|-----------|-----|
| Mobile Phone | HUAWEI | --- | --- |

| Description | Length | Shielded/unshielded | With / without ferrite |
|-------------|--------|---------------------|------------------------|
| USB Cable | 1.0m | Shielded | Without ferrite |

9 Technical Requirement

9.1 Conducted Emission Test

Test Method

1. The EUT was placed on a table, which is 0.8m above ground plane
2. The power line of the EUT is connected to the AC mains through an Artificial Mains Network (A.M.N.).
3. Maximum procedure was performed to ensure EUT compliance
4. A EMI test receiver is used to test the emissions from both sides of AC line

Limit


According to §15.207, conducted emissions limit as below:

| Frequency MHz | QP Limit dB μ V | AV Limit dB μ V |
|------------------|------------------------|------------------------|
| 0.150-0.500 | 66-56* | 56-46* |
| 0.500-5 | 56 | 46 |
| 5-30 | 60 | 50 |

*Decreasing linearly with logarithm of the frequency

Conducted Emission

Product Type : HUAWEI WIRELESS CHARGER
 M/N : CP60
 Operating Condition : Charging Mode
 Test Specification : Line
 Comment : AC 120V/60Hz




| Frequency (MHz) | MaxPeak (dBµV) | Average (dBµV) | Limit (dBµV) | Margin (dB) | Line | Corr. (dB) |
|-----------------|----------------|----------------|--------------|-------------|------|------------|
| 0.166000 | 53.33 | --- | 65.16 | 11.83 | L1 | 10.2 |
| 0.282000 | 47.65 | --- | 60.76 | 13.11 | L1 | 10.2 |
| 0.678500 | --- | 26.98 | 46.00 | 19.02 | L1 | 10.2 |
| 0.678500 | 38.86 | --- | 56.00 | 17.14 | L1 | 10.2 |
| 0.730500 | --- | 24.30 | 46.00 | 21.70 | L1 | 10.2 |
| 0.730500 | 34.18 | --- | 56.00 | 21.82 | L1 | 10.2 |
| 1.290000 | 44.14 | --- | 56.00 | 11.86 | L1 | 10.2 |
| 5.510000 | 42.28 | --- | 60.00 | 17.72 | L1 | 10.4 |

*Correct factor=cable loss + LISN factor

Conducted Emission

Product Type : HUAWEI WIRELESS CHARGER
 M/N : CP60
 Operating Condition : Charging Mode
 Test Specification : Neutral
 Comment : AC 120V/60Hz



| Frequency (MHz) | QuasiPeak (dBµV) | Average (dBµV) | Limit (dBµV) | Margin (dB) | Line | Corr. (dB) |
|-----------------|------------------|----------------|--------------|-------------|------|------------|
| 0.169500 | --- | 40.43 | 54.98 | 14.55 | N | 10.3 |
| 0.169500 | 53.48 | --- | 64.98 | 11.50 | N | 10.3 |
| 0.229500 | --- | 34.72 | 52.47 | 17.75 | N | 10.3 |
| 0.229500 | 50.31 | --- | 62.47 | 12.16 | N | 10.3 |
| 0.281500 | --- | 34.73 | 50.77 | 16.04 | N | 10.3 |
| 0.281500 | 48.09 | --- | 60.77 | 12.68 | N | 10.3 |
| 0.329500 | --- | 24.92 | 49.46 | 24.54 | N | 10.3 |
| 0.329500 | 45.13 | --- | 59.46 | 14.33 | N | 10.3 |
| 0.658500 | --- | 25.58 | 46.00 | 20.42 | N | 10.4 |
| 0.658500 | 43.23 | --- | 56.00 | 12.77 | N | 10.4 |
| 0.729500 | --- | 32.79 | 46.00 | 13.21 | N | 10.4 |
| 0.729500 | 43.15 | --- | 56.00 | 12.85 | N | 10.4 |

*Correct factor=cable loss + LISN factor



9.2 20 dB Bandwidth and 99% Occupied Bandwidth

Test Method

1. Use the following spectrum analyzer settings:
RBW=200Hz, VBW≥3RBW, Sweep = auto, Detector function = peak, Trace = max hold
2. Use the automatic bandwidth measurement capability of an instrument, may be employed using the X dB bandwidth mode with X set to 20 dB, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 20 dB.
3. Allow the trace to stabilize, record the X dB Bandwidth value.

Limit

Limit [kHz]

No Limit

Test result

| Frequency KHz | 20dB bandwidth Hz | 99% bandwidth Hz | Result | | Result |
|------------------|-------------------------|------------------------|----------------------|----------------------|--------|
| | | | F _L (KHz) | F _H (KHz) | |
| 111KHz | 419.7 | 448.6 | 110.9 | -- | Pass |
| 148KHz | 538.1 | 543.2 | -- | 148.4 | Pass |

The fundamental frequency is outside the restricted bands of 15.205 section.

9.3 Radiated Emission Test

Test Method

- 1: The EUT was placed on a turn table which is 0.8m above ground for below 1GHz at 3 meters chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- 2: The EUT was set 3 meters away from the interference – receiving antenna, which was mounted on the top of a variable – height antenna tower.
- 3: The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- 4: For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- 5: Use the following spectrum analyzer settings According to C63.10:

Limit

the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

| Frequency MHz | Field Strength μ V/m | Field Strength dB μ V/m | Detector | Measurement distance meters |
|------------------|-----------------------------|--------------------------------|----------|--------------------------------|
| 0.009-0.490 | 2400/F(kHz) | 48.5-13.8 | QP | 300 |
| 0.490-1.705 | 24000/F(kHz) | 33.8-23.0 | QP | 30 |
| 1.705-30 | 30 | 29.5 | QP | 30 |
| 30-88 | 100 | 40 | QP | 3 |
| 88-216 | 150 | 43.5 | QP | 3 |
| 216-960 | 200 | 46 | QP | 3 |
| 960-1000 | 500 | 54 | QP | 3 |
| Above 1000 | 500 | 54 | AV | 3 |
| Above 1000 | 5000 | 74 | PK | 3 |

Note 1: Limit 3m(dB μ V/m)=Limit 300m(dB μ V/m)+40Log(300m/3m) (Below 30MHz)

Note 2: Limit 3m(dB μ V/m)=Limit 30m(dB μ V/m)+40Log(30m/3m) (Below 30MHz)

Radiated emissions test (9KHz-30MHz)


| Frequency Band | Frequency | Emission Level | Polarization | Limit | Detector | Margin | Correct factor | Result |
|-----------------|-----------------|----------------|--------------|--------------|----------|--------------|----------------|--------|
| | MHz | dB μ V/m | | dB μ V/m | | dB μ V/m | (dB) | |
| 9KHz-30MHz | 0.149 | 56.47 | H | 93.8 | QP | 37.33 | 19.7 | Pass |
| | 0.150 | 66.02 | H | 93.8 | QP | 27.78 | 19.7 | Pass |
| | 0.195 | 55.21 | H | 93.8 | QP | 38.59 | 19.7 | Pass |
| | 0.245 | 53.48 | H | 93.8 | QP | 40.32 | 19.7 | Pass |
| | Other frequency | -- | H | 93.8 | QP | -- | -- | Pass |
| | 0.00900 | 54.62 | V | 93.8 | QP | 39.18 | 20.8 | Pass |
| | 0.149 | 57.41 | V | 93.8 | QP | 36.39 | 19.7 | Pass |
| | 0.150 | 62.10 | V | 93.8 | QP | 31.7 | 19.7 | Pass |
| | 0.0240 | 52.04 | V | 93.8 | QP | 41.76 | 20.0 | Pass |
| Other frequency | -- | V | 93.8 | QP | -- | -- | Pass | |

Remark:

- (1) “*” means the emission(s) appear within the restrict bands shall follow the requirement of section 15.205.
- (2) Data of measurement within this frequency range shown “--” in the table above means the reading of emissions are the noise floor or attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (3) Above 1GHz: Corrector factor = Antenna Factor + Cable Loss- Amplifier Gain
Below 1GHz: Corrector factor = Antenna Factor + Cable Loss
- (4) All tested frequencies comply for the strictest limit (93.8dB μ V/m). so the test result can considered as Pass.

Radiated emissions test (30MHz-1000MHz)

Product Type : HUAWEI WIRELESS CHARGER
 M/N : CP60
 Operating Condition : Quick Charging Mode
 Test Specification : Horizontal
 Comment : 30MHz-1000MHz




| Frequency (MHz) | MaxPeak (dBµV/m) | Limit (dBµV/m) | Margin (dB) | Height (cm) | Pol | Azimuth (deg) | Corr. (dB) |
|-----------------|------------------|----------------|-------------|-------------|-----|---------------|------------|
| 50.006250 | 19.28 | 40.00 | 20.72 | 100.0 | H | 9.0 | 17.7 |
| 62.919375 | 17.51 | 40.00 | 22.49 | 100.0 | H | 9.0 | 15.8 |
| 102.810625 | 20.36 | 43.50 | 23.14 | 200.0 | H | 0.0 | 16.1 |
| 199.750000 | 25.62 | 43.50 | 17.88 | 200.0 | H | 69.0 | 16.2 |
| 436.430000 | 32.41 | 46.00 | 13.59 | 100.0 | H | 195.0 | 22.5 |
| 950.045000 | 35.36 | 46.00 | 10.64 | 100.0 | H | 61.0 | 31.0 |

Corrector factor = Antenna Factor + Cable Loss



Product Type : HUAWEI WIRELESS CHARGER
 M/N : CP60
 Operating Condition : Quick Charging Mode
 Test Specification : Vertical
 Comment : 30MHZ-1000MHZ



| Frequency (MHz) | MaxPeak (dBµV/m) | Limit (dBµV/m) | Margin (dB) | Height (cm) | PoI | Azimuth (deg) | Corr. (dB) |
|-----------------|------------------|----------------|-------------|-------------|-----|---------------|------------|
| 46.853750 | 28.58 | 40.00 | 11.42 | 100.0 | V | 38.0 | 18.0 |
| 80.500625 | 24.42 | 40.00 | 15.58 | 200.0 | V | 227.0 | 11.9 |
| 99.961250 | 26.29 | 43.50 | 17.21 | 100.0 | V | 218.0 | 16.4 |
| 120.998125 | 25.26 | 43.50 | 18.24 | 100.0 | V | 124.0 | 14.5 |
| 170.710625 | 31.13 | 43.50 | 12.37 | 100.0 | V | 109.0 | 13.9 |
| 196.900625 | 35.09 | 43.50 | 8.41 | 100.0 | V | 148.0 | 16.2 |

Corrector factor = Antenna Factor + Cable Loss

10 Test Equipment List

List of Test Instruments

Radiated Emission Test

| DESCRIPTION | MANUFACTURER | MODEL NO. | SERIAL NO. | CAL. DUE DATE |
|---|-----------------|-----------|-----------------|---------------|
| EMI Test Receiver | Rohde & Schwarz | ESR 26 | 101269 | 2019-7-6 |
| Trilog Super Broadband Test Antenna | Schwarzbeck | VULB 9163 | 707 | 2019-7-6 |
| Horn Antenna | Rohde & Schwarz | HF907 | 102294 | 2019-7-6 |
| Loop Antenna | Rohde & Schwarz | HFH2-Z2 | 100398 | 2019-7-6 |
| Pre-amplifier | Rohde & Schwarz | SCU 18 | 102230 | 2019-7-6 |
| Signal Generator | Rohde & Schwarz | SMY01 | 839369/005 | 2019-7-6 |
| Attenuator | Agilent | 8491A | MY39264334 | 2019-7-6 |
| 3m Semi-anechoic chamber | TDK | 9X6X6 | ---- | 2020-7-7 |
| Test software | Rohde & Schwarz | EMC32 | Version 9.15.00 | N/A |

Conducted Emission Test

| DESCRIPTION | MANUFACTURER | MODEL NO. | SERIAL NO. | CAL. DUE DATE |
|--------------------|-------------------|----------------|----------------|---------------|
| EMI Test Receiver | Rohde & Schwarz | ESR 3 | 101782 | 2019-7-6 |
| LISN | Rohde & Schwarz | ENV4200 | 100249 | 2019-7-6 |
| LISN | Rohde & Schwarz | ENV432 | 101318 | 2019-7-6 |
| LISN | Rohde & Schwarz | ENV216 | 100326 | 2019-7-6 |
| ISN | Rohde & Schwarz | ENY81 | 100177 | 2019-7-6 |
| ISN | Rohde & Schwarz | ENY81-CA6 | 101664 | 2019-7-6 |
| High Voltage Probe | Rohde & Schwarz | TK9420(VT9420) | 9420-584 | 2019-6-30 |
| RF Current Probe | Rohde & Schwarz | EZ-17 | 100816 | 2019-6-30 |
| Attenuator | Shanghai Huaxiang | TS2-26-3 | 080928189 | 2019-7-6 |
| Test software | Rohde & Schwarz | EMC32 | Version9.15.00 | N/A |



11 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

| System Measurement Uncertainty | |
|---|--|
| Test Items | Extended Uncertainty |
| Uncertainty for Conducted Emission 9kHz-150KHz | 3.62dB |
| Uncertainty for Radiated Emission in 3m chamber 9KHz-30MHz | 4.46dB |
| Uncertainty for Radiated Emission in 3m chamber 30MHz-1000MHz | Horizontal: 4.91dB; Vertical: 4.89dB; |