



EMC Test Report

Product Name: CDMA 1X USB Stick

Model Number: EC121

Report No: SYBH (R) 002122007EB-1

Reliability Laboratory of Huawei Technologies Co., Ltd.

Huawei Base, Bantian, Longgang District, Shenzhen 518129, P.R. China

Tel: +86 755 28780808 Fax: +86 755 89652518

Notice 1

1. The laboratory has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS), and accreditation number: L0310.
2. The laboratory has obtained the accreditation of THE AMERICAN ASSOCIATION FOR LABORATORY ACCREDITATION (A2LA), and Accreditation Council Certificate Number: 2174.01.
3. The laboratory has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements. The site recognition number is 97456.
4. The laboratory has been listed by industry Canada to perform electromagnetic emission measurement. The site recognition number is 6369A-1.
5. The laboratory also has been listed by the VCCI to perform EMC measurements. The accreditation number is R2364, C2583, and T256.
6. The test report is invalid if not marked with "exclusive stamp for the test report".
7. The test report is invalid if not marked with the stamps or the signatures of the persons responsible for performing, revising and approving the test report.
8. The test report is invalid if there is any evidence of erasure and/or falsification.
9. If there is any dissidence for the test report, please file objection to the test centre within 15 days from the date of receiving the test report.
10. Normally, the test report is only responsible for the samples that have undergone the test.
11. Context of the test report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of the laboratory.

Notice 2

Modification Information:

Table 1 Modification Information

Modification Information	1	
	2	
	3	<i>Not Applicable!</i>
	4	
	5	
	6	
	7	

REPORT ON EMC Test of CDMA 1X USB Stick
M/N: EC121
REGULATION FCC CFR47 Part 15: Subpart B;
FCC CFR47 Part 22 Subpart H; :
START OF TEST Jan.10, 2008
END OF TEST Jan.20, 2008
Final Judgement: Pass

Approver	<u>2008-01-24</u> Date	<u>张兴海</u> Name	 Signature
Reviewer	<u>2008-01-22</u> Date	<u>余 辉</u> Name	 Signature
Operator	<u>2008-01-22</u> Date	<u>胡 俊</u> Name	 Signature

REPORT BODY CONTENT

1	Status.....	6
1.1	Product Information.....	6
1.2	Applied Standard.....	6
1.3	Test Site.....	7
1.4	Test environment condition.....	7
2	Summary of Results.....	8
3	Equipment Specification.....	9
3.1	General Description.....	9
3.2	Technical Data.....	9
3.3	Sub-Assembly Identity.....	9
4	System Configuration during EMC Test.....	10
4.1	Cables Used during Test.....	10
4.2	Associated Equipment Used during Test.....	10
4.3	Test Configurations and Test Mode.....	10
4.4	Test conditions and test Connections.....	10
5	Electromagnetic Interference (EMI).....	12
5.1	Radiated Disturbance 30MHz to 1000MHz.....	12
5.2	Conducted Disturbance 0.15 MHz to 30MHz.....	13
5.3	Radiated Spurious Emissions.....	14
6	Main Test Instruments.....	16
7	System Measurement Uncertainty.....	17
8	Graph and Data of Emission Test.....	18
8.1	Radiated Disturbance.....	18
8.2	Conducted Disturbance.....	19
8.3	Radiated Spurious Emission.....	20

1 Status

1.1 Product Information

CLIENT: Huawei Technologies Co., Ltd.
ADDRESS: Bantian Longgang District Shenzhen, P.R. China
MANUFACTURING DESCRIPTION HUAWEI Wireless USB Stick
MANUFACTURERS MODEL NUMBER EC121

1.2 Applied Standard

FCC Measurement Specification	FCC Limits Part(s)	Description	Result
-	15.107	Conducted Emission at Power Port	PASS
-	15.109	Radiated Emission of Enclosure in Idle Mode	PASS
2.1051	22.917	Spurious Emission at Antenna Terminals	PASS

1.3 Test Site

Site 1:

EMC LABORATORY OF RELIABILITY LABORATORY OF HUAWEI TECHNOLOGIES CO., LTD

Site 2:

EMC LABORATORY OF AUDIX LABORATORY

Site 3:

EMC LABORATORY OF HUATONGWEI INTERNATIONAL INSPECTION CO, Ltd.

1.4 Test environment condition

Ambient temperature	20~25°C
Relative humidity	40%~52%
Atmospheric pressure	101kPa

2 Summary of Results

Table 2 below shows a brief summary of the results obtained.

Table 2 Summary of results

EUT Classification : Wireless Terminal				
Test Items	Test Configuration & Test Mode	Required Performance Criteria	Result	Site
<u>Radiated Emissions</u> Enclosure Port	TC1,TC2 (TM3~TM4)	N/A	Pass	Site1
<u>Conducted Emissions</u>	TC1,TC2 (TM1~TM4)	N/A	Pass	Site1
<u>Radiated Spurious Emissions</u> Enclosure Port 30MHz ~26.5GHz	TC1,TC2 (TM1~TM4)	N/A	Pass	Site1
Note: 1, Measurement taken is within the measurement uncertainty of measurement system. 2, TC = Test configuration 3, NT=no test. Because of not containing devices susceptible to magnetic fields, the EUT has been exempt from immunity test of power frequency magnetic field.				

3 Equipment Specification

3.1 General Description

HUAWEI EC121 is wireless USB Stick, support CDMA 1X 800MHz. For CDMA 1X 800MHz, the TX frequency is 824MHz-849MHz and the RX frequency is 869MHz-894MHz. The product should be used by USB interface. The major business is internet connection, also include short message, Voice call etc. UIM card interface and antenna interface. EC121 has an internal antenna as default.

3.2 Technical Data

3.2.1 Main Equipment Technical Data

Name	USB STICK
Model	EC121
Input Rated Voltage	 5V
Rated Power	2.4 W
Dimensions	106.7(depth) × 44.3(width) × 14.5(height) (mm ³)
Weight	19g

Table 3 Sub-Assembly Identity

Mode		Work Frequency	
		Transmitt Frequency (MHz)	Receive Frequency (MHz)
CDMA	CDMA 1X 800	824-849	869-894

3.3 Sub-Assembly Identity

Table 4 Sub-Assembly Identity

Model Name	Qty.	Serial Number	Description
Huawei EC121	1	020HK107C000129	Main board of data card
Name	Qty.	Serials number	Description

4 System Configuration during EMC Test

The Equipment under Test (EUT) was functioning correctly during all tests. The EUT was installed within the test site and was configured to simulate a typical user installation.

4.1 Cables Used during Test

Table 5 Cable Used during Test

Port	Connector	Type of Cable
USB	USB	Non-shielding

4.2 Associated Equipment Used during Test

Table 6 Associated Equipment Used during Test

Name	Model	Manufacturer	S/N	Cal Date
Radio Communication Tester	CMU200	R&S	3604091211	2007-10-12
Notebook	T43	IBM	3106093834	N/A

4.3 Test Configurations and Test Mode

4.3.1 Test Configuration.

The EUT will be connected to test system (Base Station Simulator) in order to simulate normal operating conditions (with reference to the guidance given in the standard for this type of equipment).

Table 7 Configuration table

Test configuration	Test mode
TC1~TC2	TM1~TM4

TC1: EUT was powered by USB port connected to the notebook directly.

TC2: EUT was powered by USB cable connected to the notebook.

4.3.2 Test Mode

There was 8 test Modes. TM1 to TM4 were shown below:

TM1: operate in traffic mode CDMA800;

TM2: operate in traffic mode CDMA800;

TM3: operate in idle mode CDMA800;

TM4: operate in idle mode CDMA800;

4.4 Test conditions and test Connections

4.4.1 Test Conditions

The EUT will be connected to test system (Base Station Simulator) in order to simulate normal operating conditions (with reference to the guidance given in the standard for this type of equipment).

4.4.2 Test Connections

Traffic Mode:

The EUT is required to be in the traffic mode, a call is set up according to the generic call set up procedure and enter the EUT into loop back test mode.(CDMA see 3GPP2 C.S0011-B).

For CDMA, the following conditions shall also be met:

Logical Test Interface for details regarding generic call set-up procedure

- set and send continuously up power control commands to the UE;

- The EUT shall be commanded to operate at maximum transmit power;

Assign channel frequency to an appropriate channel number. Set the ARFCN channel number to 283 (833.49MHz) for CDMA.




Figure 1. Test Configuration

Idle Mode :

The EUT is required to be in the idle mode.

For CDMA, the following conditions shall be met:

- UE shall be camped on a cell;
- UE shall perform Location Registration (LR) before the test, but not during the test;
- UE's neighbour cell list shall be empty;
- Paging repetition period and DRX cycle shall be set to minimum (shortest possible time interval).




Figure 2. Test Configuration

5 Electromagnetic Interference (EMI)

5.1 Radiated Disturbance 30MHz to 1000MHz

5.1.1 Test Procedure

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4dB according to the standards: ANSI C63.4 (2003). The test distance was 3m. The EUT was set-up on insulator 80cm above the Ground Plane. The set-up and test methods were according to ANSI C63.4. The Radiated Disturbance measurements were made using a Rohde and Schwarz ESMI Test Receiver and control software ES-K1.

A preliminary scan and a final scan of the emissions were made from 30 MHz to 1GHz by using test script of software; the emissions were measured using a Quasi-Peak Detector. The maximal emission value was acquired by adjusting the antenna height, polarisation and turntable azimuth in accordance with the software setup. Normally, the height range of antenna was 1m to 4m, the azimuth range of turntable was 0° to 360°, The receive antenna has two polarizations V and H.

Huawei Mobile Station was communicated with the BTS simulator through Air interface. The Mobile Station operated on the typical channel and the Mobile Station worked in idle mode, transmitter was not work in this test.

EUT was configured to idle mode according to TC1 and the test performed at worst emission state.

Measurement bandwidth: 30 MHz – 1000 MHz: 120 k Hz

Test set up figure:




Figure 3. Test set up

5.1.2 Test Results

The EUT has met the requirements for Radiated Emission of enclosure port. The test data is shown in section 8.1 of the report.

Table 8 Test Limits

Frequency of Emission (MHz)	Radiated Limit	
	Unit(μV/m)	Unit(dBμV/m)
30-88	100	40
88-216	150	43.5
216-960	200	46
960-1000	500	54

5.2 Conducted Disturbance 0.15 MHz to 30MHz

5.2.1 Test Procedure

The Table-top EUT was placed upon a non-metallic table 0.8 m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.4: 2003.

Conducted Disturbance at AC Port measurements were undertaken on the L and N Lines. The emissions were measured using a Quasi-Peak Detector and Average Detector.

Huawei Mobile Station was communicated with the BTS simulator through Air interface, the BTS simulator controls the Mobile Station to transmitter the maximum power which defined in specification of product. The Mobile Station operated on the typical channel.

Measurement bandwidth (RBW) for 150kHz to 30 MHz: 9 kHz;

Test Set-up figure:

The Mobile Station was setup in the screened chamber and operated under nominal conditions.




Figure 4. Test Set-up

5.2.2 Test Results

The EUT has met requirements for Conducted disturbance of power lines. The test data is shown in section 8.2 of the report.

Table 9 Test Limit of DC&AC Power Port

Frequency range	150kHz~ 30MHz	
Classification	Class B	
Limit(Class B)	Voltage limits	
	QP	AV
0.15MHz~0.5MHz	66~56 dB μ V	56~46 dB μ V
0.5MHz~5MHz	56 dB μ V	46 dB μ V
5MHz~30MHz	60 dB μ V	50 dB μ V


5.3 Radiated Spurious Emissions
5.3.1 Test Procedure

A test site fulfilling the requirements of ITU-R Recommendation SM329-10 was used. The EUT was placed on a non-conducting support in the anechoic chamber and was operated from a power source via an RF filter to avoid radiation from the power leads.

Step 1:


For transmitters other than single sideband, independent sideband and controlled carrier radiotelephone, EIRP shall be measured when the transmitter is adjusted in accordance with the tune-up procedure to give the values of current and voltage on the circuit elements specified in 2.1033(c)(8). Connect the EUT to the BTS simulator via the air interface.

Test the Radiated maximum output power by the Rohde and Schwarz ESIB26 Test Receiver from test antenna.



Step 2:

Use substitution method to verify the maximum output power. The EUT is substituted by a dipole antenna. The dipole is connected to a signal generator. And then adjust the output level of the signal generator to get the same received power recorded in step1 on ESIB26 Test Receiver, and record the power level of Signal Generator. Of course, the cable loss at the test frequency should be compensated.



According to part 22.917, the defined measurement bandwidth as following:

22.917(b) Measurement procedure:

- Measurement bandwidth (RBW) for 9 kHz up to 150 kHz: 1 kHz;
- Measurement bandwidth (RBW) for 150 kHz up to 30 MHz: 10 kHz;
- Measurement bandwidth (RBW) for 30 MHz up to 1 GHz: 100 kHz;
- Measurement bandwidth (RBW) for 1GHz up to 18 GHz: 1MHz;

Table 10 Radiated Spurious Emissions Limits

Frequency band	Minimum requirement (E.R.P) traffic mode
30MHz~18GHz	-13dBm

5.3.2 Test Results

The EUT has met the requirements of FCC Part22 requirement.

6 Main Test Instruments

Table 11 Main Test Equipments

Test item	Test Instrument	Model	Manufacturer	Cal-Date	Cal Interval (month)
RE	EMI Test receiver	ESMI	R&S	April.23, 2007	12
	Broadband Antenna	CBL 6112B (2941)	SCHAFFNER	Feb.26, 2007	12
CE	EMI Test receiver	ESCS30	R&S	May.29, 2007	12
	Artificial Mains Network	ENV4200	R&S	May.21, 2007	12
RSE	EMI Test receiver	ESIB26	R&S	May.30.2007	12
	Horn Antenna	3117	EMCO	May.20.2007	12
	Broadband Antenna	CBL6112B /2941	SCHAFFNER	Feb.16.2007	12
	Horn Antenna	3160	EMCO	May.20.2007	12
Software Information					
Test Item	Software Name	Manufacturer	Version		
RE/CE	ES-K1	R&S	1.7.1		
RSE	EMC32	R&S	V5.0		

7 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

Table 12 System Measurement Uncertainty


	Items	Extended Uncertainty
RE	Field strength (dB μ V/m)	U=4.6dB; k=2(30MHz-1GHz)
RSE	ERP (dBm)	U = 2.2dB ; k = 2
CE	Disturbance Voltage (dB μ V)	U=3.3dB; k=2

8 Graph and Data of Emission Test

8.1 Radiated Disturbance

This test was carried out in all the test modes, Here only the worst test result was shown.

8.1.1 Radiated Disturbance




MEASUREMENT RESULT: QP Detector

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Height cm	Azimuth deg	Polarisation
32.980000	26.50	-5.8	40.0	13.5	115.0	120.00	HORIZONTAL
72.750000	24.20	-16.1	40.0	15.8	136.0	254.00	VERTICAL
160.900000	20.50	-11.6	43.5	23.0	287.0	68.00	HORIZONTAL
221.040000	26.70	-11.2	46.0	19.3	182.0	772.00	HORIZONTAL
367.040000	35.60	-5.3	46.0	10.4	150.0	214.00	HORIZONTAL
903.500000	39.80	1.4	46.0	6.20	115.0	73.00	HORIZONTAL

8.2 Conducted Disturbance

8.2.1 AC Power Port Test Data



MEASUREMENT RESULT: QP Detector

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.158000	50.70	10.9	66	15.3	QP	N	FLO
0.353500	34.70	10.2	59	24.3	QP	N	FLO
1.784500	30.20	9.9	56	25.8	QP	N	FLO
3.542000	37.20	10.1	56	18.8	QP	L3	FLO
10.935500	35.40	11.6	60	24.6	QP	L3	FLO
29.154500	17.20	13.7	60	42.8	QP	L3	FLO


MEASUREMENT RESULT: AV Detector

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.162500	30.10	10.8	55	24.9	AV	L3	FLO
0.795000	16.30	9.9	46	29.7	AV	N	FLO
1.725500	22.20	10.0	46	23.8	AV	N	FLO
3.652000	21.50	10.1	46	24.5	AV	L3	FLO
10.832500	27.10	11.6	50	22.9	AV	L3	FLO
12.256500	19.20	11.7	50	30.8	AV	L3	FLO


8.3 Radiated Spurious Emission

8.3.1 For CDMA 800(TC1)


Traffic Mode (9kHz-30MHz)



Traffic Mode (30MHz-2GHz)




Traffic Mode (2GHz-18GHz)




8.3.2 For CDMA 800 (TC2)


Traffic Mode (9kHz-30MHz)



Traffic Mode (30MHz-2GHz)



Traffic Mode (2GHz-18GHz)



END