

FCC RF EXPOSURE REPORT

For

GPON Terminal

MODEL NUMBER: EchoLife EG8247Q

FCC ID: QISEG8247Q

REPORT NUMBER: 4788418338.1-4

ISSUE DATE: November 07, 2018

Prepared for

HUAWEI TECHNOLOGIES CO., LTD.

Administration Building, Huawei Technologies Co., Ltd. Bantian, Longgang
District, Shenzhen, P.R. China, 518129

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, People's Republic of China

Tel: +86 769 22038881 Fax: +86 769 33244054 Website: www.ul.com



REPORT NO.: 4788418338.1-4 Page 2 of 11

Revision History

Rev.	Issue Date	Revisions	Revised By
VO	07/30/2018	Initial Issue	Miller Ma
V1	11/07/2018	Updated the 4.0 chapter of the report.	Miller Ma






TABLE OF CONTENTS

1.	ATTESTATION OF TEST RESULTS	4
2	TEST METHODOLOGY	5
3.	FACILITIES AND ACCREDITATION	5
4	REQUIREMENT	6



REPORT NO.: 4788418338.1-4

Page 4 of 11

1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: HUAWEI TECHNOLOGIES CO., LTD.

Address: Administration Building, Huawei Technologies Co., Ltd. Bantian,

Longgang District, Shenzhen, P.R. China, 518129

Manufacturer Information

Company Name: HUAWEI TECHNOLOGIES CO., LTD.

Address: Administration Building, Huawei Technologies Co., Ltd. Bantian,

Longgang District, Shenzhen, P.R. China, 518129

EUT Description

EUT Name: GPON Terminal

Model: EchoLife EG8247Q; EchoLife EG8245Q; EchoLife HG8247Q5;

EchoLife HG8245Q5.

Brand Name: HUAWEI
Sample Status: Normal
Sample ID: 1607492
Sample Received Date: May 22, 2018

Date of Tested: May 22, 2018~ June 22, 2018

APPLICABLE STANDARDS

STANDARD

TEST RESULTS

FCC 47CFR§2.1091

Complies

Tested By: Checked By:

Miller Ma

Engineer Project Associate

Sephenbuo

Shann les

Shawn Wen Laboratory Leader

Approved By:

Miller Ma

Stephen Guo

Laboratory Manager



REPORT NO.: 4788418338.1-4 Page 5 of 11

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091.

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	A2LA (Certificate No.: 4102.01) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA. FCC (FCC Designation No.: CN1187) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Delcaration of Conformity (DoC) and Certification rules IC(Company No.: 21320) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with Industry Canada. The Company Number is 21320. VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the
	UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch.
	Facility Name: Chamber D, the VCCI registration No. is G-20019 and R-20004
	Shielding Room B, the VCCI registration No. is C-20012 and T-20011

Note 1: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China



REPORT NO.: 4788418338.1-4 Page 6 of 11

4. REQUIREMENT

LIMIT AND CALCULATION METHOD

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with. Limits for General Population/Uncontrolled Exposure

RF EXPOSURE LIMIT

Frequency Range (MHz)	E-field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm²)	Averaging Time E ², H ² or S (Minutes)
0.3 1.34	614	1.63	(100)*	30
1.34 30	824/f	2.19/f	(180/f ²)*	30
30 300	27.5	0.073	0.2	30
300 1500			f/1500	30
1500 100,000			1.0	30

CALCULATION METHOD

S=PG/4πR²

Where:

S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator R=distance to the center of radiation of the antenna

REPORT NO.: 4788418338.1-4 Page 7 of 11

CALCULATED RESULTS

For SISO Mode

2.4GHz WIFI							
Frequency	Max Tune Up Power		Power Density	Power Density Limit	Test Result		
MHz	dBm	mW	mW/cm ²	mW/cm ²			
2412~2462	23	199.53	0.0629	1.0	Complies		

5GHzWIFI (UNII-1)							
Frequency	Max Tune Up Power		Power Density	Power Density Limit	Test Result		
MHz	dBm	mW	mW/cm ²	mW/cm ²	-		
5180~5240	26	398.11	0.1255	1.0	Complies		

5GHzWIFI (UNII-2)							
Frequency	Max Tune Up Power		Power Density	Power Density Limit	Test Result		
MHz	dBm	mW	mW/cm ²	mW/cm ²			
5260~5320	24	251.19	0.0792	1.0	Complies		

5GHzWIFI (UNII-2)							
Frequency	Max Tune Up Power		Power Density	Power Density Limit	Test Result		
MHz	dBm	mW	mW/cm ²	mW/cm ²			
5500~5720	24	251.19	0.0792	1.0	Complies		



REPORT NO.: 4788418338.1-4 Page 8 of 11

5GHzWIFI (UNII-3)							
Frequency	Max Tui	ne Up Power	Power Density	Power Density Limit	Test Result		
MHz	dBm	mW	mW/cm ²	mW/cm ²			
5725~5825	26	398.11	0.1255	1.0	Complies		

For MIMO Mode

2.4GHz WIFI							
Frequency	Max Tune Up Power		Power Density	Power Density Limit	Test Result		
MHz	dBm	mW	mW/cm ²	mW/cm ²			
2412~2462	23.77	238.23	0.2254	1.0	Complies		

5GHzWIFI (UNII-1)							
Frequency	Max Tune Up Power		Power Density	Power Density Limit	Test Result		
MHz	dBm	mW	mW/cm ²	mW/cm ²			
5180~5240	29	794.33	0.7515	1.0	Complies		

5GHzWIFI (UNII-2)							
Frequency	Max Tune Up Power		Power Density	Power Density Limit	Test Result		
MHz	dBm	mW	mW/cm ²	mW/cm ²			
5260~5320	24	251.19	0.2376	1.0	Complies		

5GHzWIFI (UNII-2)							
Frequency	Max Tune Up Power		Power Density	Power Density Limit	Test Result		
MHz	dBm	mW	mW/cm ²	mW/cm ²			
5500~5720	24	251.19	0.2376	1.0	Complies		



REPORT NO.: 4788418338.1-4 Page 10 of 11

5GHzWIFI (UNII-3)							
Frequency	Max Tune Up Power		Power Power Density Limit		Test Result		
MHz	dBm	mW	mW/cm ²	mW/cm ²			
5725~5825	29	794.33	0.7515	1.0	Complies		



REPORT NO.: 4788418338.1-4 Page 11 of 11

For 2.4GHz and 5GHz WIFI can be transmitted simultaneously

2.4GHz+5GHzWIFI (UNII-3)							
Frequency	Max Tune Up Power		Power Density	Power Density (Sum)	Power Density Limit	Test Result	
MHz	dBm	mW	mW/cm ²	mW/cm ²	mW/cm ²		
2412~2462	23.77	238.23	0.2254	0.9769	1.0	Complies	
5725~5825	29	794.33	0.7515			Complies	

Note: 1. direction =Antenna Gain+10 log(Nant) where Nant is the number of outputs, Gant is the Antenna gain. π =3.141, Antenna Gain=2.0dBi, Nant=1 for 1TX Mode, Nant=2 for 2TX Mode, Nant=3 for 3TX.

- 2. The minimum separation distance of the device is greater than 20cm.
- 3. Calculate by WORST-CASE mode.
- 4. Owing to the maximum Calculated Result is below the limit, so it deemed to comply with the basic restrictions.
- 5. Max Tune Up Power by manufacturer's declaration
- 6. 2.4GHz and 5GHz WIFI can be transmitted simultaneously.

END OF REPORT