

HUAWEI Technologies Co., Ltd.

RF TEST REPORT

Report Type:

FCC Part 15.247 & ISED RSS-247 RF report

Model:

eM300-8a V2R1

REPORT NUMBER:

181101512SHA-003

ISSUE DATE:

February 4, 2019

DOCUMENT CONTROL NUMBER:

TTRF15.247-01_V1 © 2018 Intertek



Applicant: HUAWEI Technologies Co., Ltd.
Administration Building, Headquarters of Huawei Technologies Co.,
Ltd., Bantian, Longgang District, 518129

Manufacturer: HUAWEI Technologies Co., Ltd.
Administration Building, Headquarters of Huawei Technologies Co.,
Ltd., Bantian, Longgang District, 518129

FCC ID: QISEM300-8AMC

SUMMARY:

The equipment complies with the requirements according to the following standard(s) or Specification:

47CFR Part 15 (2017): Radio Frequency Devices (Subpart C)

ANSI C63.10 (2013): American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

RSS-247 Issue 2 (February 2017): Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices

RSS-Gen Issue 5 (April 2018): General Requirements for Compliance of Radio Apparatus

PREPARED BY:



Project Engineer
Erick Liu

REVIEWED BY:



Reviewer
Daniel Zhao

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

TEST REPORT

Content

REVISION HISTORY.....	5
MEASUREMENT RESULT SUMMARY.....	6
1 GENERAL INFORMATION	7
1.1 DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	7
1.2 TECHNICAL SPECIFICATION	7
1.3 DESCRIPTION OF TEST FACILITY	8
2 TEST SPECIFICATIONS.....	9
2.1 STANDARDS OR SPECIFICATION	9
2.2 MODE OF OPERATION DURING THE TEST.....	9
2.3 TEST SOFTWARE LIST	10
2.4 TEST PERIPHERALS LIST	10
2.5 TEST ENVIRONMENT CONDITION:.....	10
2.6 INSTRUMENT LIST	11
2.7 MEASUREMENT UNCERTAINTY	13
3 20DB BANDWIDTH	14
3.1 LIMIT	14
3.2 MEASUREMENT PROCEDURE	14
3.3 TEST CONFIGURATION	15
3.4 TEST RESULTS OF 20dB BANDWIDTH.....	15
4 CARRIER FREQUENCY SEPARATION.....	16
4.1 LIMIT	16
4.2 TEST CONFIGURATION	16
4.3 TEST PROCEDURE AND TEST SETUP.....	16
4.4 TEST RESULTS OF CARRIER FREQUENCY SEPARATION.....	16
5 OUTPUT POWER.....	17
5.1 LIMIT	17
5.2 TEST CONFIGURATION	17
5.3 MEASUREMENT PROCEDURE	17
5.4 TEST RESULTS OF OUTPUT POWER.....	17
6 RADIATED EMISSIONS	18
6.1 LIMIT	18
6.2 MEASUREMENT PROCEDURE	18
6.3 TEST CONFIGURATION	20
6.4 TEST RESULTS OF RADIATED EMISSIONS	23
7 CONDUCTED SPURIOUS EMISSIONS & BAND EDGE	25
7.1 LIMIT	25
7.2 TEST CONFIGURATION	25
7.3 MEASUREMENT PROCEDURE	25
7.4 TEST RESULTS OF CONDUCTED SPURIOUS EMISSIONS & BAND EDGE	26
8 POWER LINE CONDUCTED EMISSION.....	27
8.1 LIMIT	27
8.2 TEST CONFIGURATION	27
8.3 MEASUREMENT PROCEDURE	28

TEST REPORT

- 8.4 TEST RESULTS OF POWER LINE CONDUCTED EMISSION..... 29
- 9 NUMBER OF HOPPING FREQUENCIES 31**
 - 9.1 LIMIT 31
 - 9.2 TEST CONFIGURATION 31
 - 9.3 TEST PROCEDURE AND TEST SETUP 31
 - 9.4 TEST RESULTS OF NUMBER OF HOPPING FREQUENCIES 31
- 10 DWELL TIME 32**
 - 10.1 LIMIT 32
 - 10.2 TEST CONFIGURATION 32
 - 10.3 TEST PROCEDURE AND TEST SETUP 32
 - 10.4 TEST RESULTS OF DWELL TIME 33
- 11 OCCUPIED BANDWIDTH..... 34**
 - 11.1 LIMIT 34
 - 11.2 MEASUREMENT PROCEDURE 34
 - 11.3 TEST CONFIGURATION 34
 - 11.4 THE RESULTS OF OCCUPIED BANDWIDTH 34
- 12 ANTENNA REQUIREMENT 35**
- APPENDIX A: TEST RESULTS 36**
 - 1.1 RF OUTPUT POWER 36
 - 1.1.1 *Test Result and Data* 36
 - 1.2 20dB DOWN BANDWIDTH..... 37
 - 1.2.1 *Test Result and Data* 37
 - 1.3 TRANSMITTER SPURIOUS EMISSION 38
 - 1.3.1 *Test Result and Data* 38
 - 1.4 FREQUENCY BAND EDGE..... 40
 - 1.4.1 *Test Result and Data* 40
 - 1.5 DWELL TIME 41
 - 1.5.1 *Test Result and Data* 41
 - 1.6 CARRIER FREQUENCY SEPARATION 43
 - 1.6.1 *Test Result and Data* 43
 - 1.7 HOPPING CHANNEL NUMBERS..... 44
 - 1.7.1 *Test Result and Data* 44

Revision History

Report No.	Version	Description	Issued Date
181101512SHA-003	Rev. 01	Initial issue of report	February 4, 2019

Measurement result summary

TEST ITEM	FCC REFERANCE	IC REFERANCE	RESULT
20 dB Bandwidth	15.247(a)(1)	RSS-247 Issue 2 Clause 5.1	Pass
Carrier Frequency Separation	15.247(a)(1)	RSS-247 Issue 2 Clause 5.1	Pass
Output power	15.247(b)(1)	RSS-247 Issue 2 Clause 5.4	Pass
Radiated Emissions	15.205 & 15.209	RSS-Gen Issue 5 Clause 8.9&8.10	Pass
Conducted Spurious Emissions & Band Edge	15.247(d)	RSS-247 Issue 2 Clause 5.5	Pass
Power line conducted emission	15.207	RSS-Gen Issue 5 Clause 8.8	Pass
Number of Hopping Frequencies	15.247(a)(1)(iii)	RSS-247 Issue 2 Clause 5.1	
Dwell time	15.247(a)(1)(iii)	RSS-247 Issue 2 Clause 5.1	
Occupied bandwidth	-	RSS-Gen Issue 5 Clause 6.6	Tested
Antenna requirement	15.203	-	Pass

Notes: 1: NA =Not Applicable

1 GENERAL INFORMATION

1.1 Description of Equipment Under Test (EUT)

Product name:	eLTE-IoT Module
Type/Model:	eM300-8a V2R1
Description of EUT:	Huawei eLTE-IoT module series are the wireless modules designed for the Internet of Things (IoT) industry, providing narrowband and low-power-consumption radio data bearer for interconnection with the network. Huawei eLTE-IoT module series also provide a UART port for integration into various industrial devices.
Rating:	DC 3.8V
Category of EUT:	Class B
EUT type:	<input checked="" type="checkbox"/> Table top <input type="checkbox"/> Floor standing
Software Version:	/
Hardware Version:	/
Sample received date:	December 6, 2018
Date of test:	December 11, 2018 – January 12, 2019

1.2 Technical Specification

Frequency Band:	902MHz ~ 928MHz
Support Standards:	IEEE 802.15.4
Modulation Technique:	Frequency Hopping Spread Spectrum (FHSS)
Type of Modulation:	QPSK
Channel Number:	756
Antenna:	External Antenna, 2.5dBi

1.3 Description of Test Facility

Name:	Intertek Testing Services Shanghai
Address:	Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China
Telephone:	86 21 61278200
Telefax:	86 21 54262353

The test facility is recognized, certified, or accredited by these organizations:	CNAS Accreditation Lab Registration No. CNAS L0139
	FCC Accredited Lab Designation Number: CN1175
	IC Registration Lab Registration code No.: 2042B-1
	VCCI Registration Lab Registration No.: R-4243, G-845, C-4723, T-2252
	A2LA Accreditation Lab Certificate Number: 3309.02

2 TEST SPECIFICATIONS

2.1 Standards or specification

47CFR Part 15 (2017)
 ANSI C63.10 (2013)
 RSS-247 Issue 2 (February 2017)
 RSS-Gen Issue 5 (April 2018)

2.2 Mode of operation during the test

While testing the transmitter mode of the EUT, the internal modulation is applied.
 All the functions of the host device except the BT module were set on stand-by mode.

The power setting parameter:

The worst-case power setting parameter			
Test software Version	CMD Command		
Modulation Mode	902.5MHz	915.1MHz	927.5MHz
QPSK	0	0	0

Radiated test mode: EUT transmitted signal with antenna;
 Conducted test mode: EUT transmitted signal from RF port connected to SPA directly;

2.3 Test software list

Test Items	Software	Manufacturer	Version
Conducted emission	ESxS-K1	R&S	V2.1.0
Radiated emission	ES-K1	R&S	V1.71

2.4 Test peripherals list

Item No.	Name	Band and Model	Description
1	Laptop computer	HP	-

2.5 Test environment condition:

Test items	Temperature	Humidity
20 dB Bandwidth	24°C	51% RH
Output power		
Carrier Frequency Separation		
Number of Hopping Frequencies		
Dwell time		
Occupied bandwidth		
Conducted Spurious Emissions & Band Edge	23°C	53% RH
Power line conducted emission		
Radiated Emissions	24°C	54% RH

2.6 Instrument list

Conducted Emission/Disturbance Power/Tri-loop Test/CDN method					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
<input checked="" type="checkbox"/>	Test Receiver	R&S	ESCS 30	EC 2107	2019-07-15
<input checked="" type="checkbox"/>	A.M.N.	R&S	ESH2-Z5	EC 3119	2019-11-30
<input checked="" type="checkbox"/>	A.M.N.	R&S	ENV 216	EC 3393	2019-07-04
<input checked="" type="checkbox"/>	A.M.N.	R&S	ENV4200	EC 3558	2019-06-10
<input type="checkbox"/>	Absorbing clamp	R&S	MDS 21	EC 2108	2019-06-19
<input type="checkbox"/>	CDN	Frankonia	CDN M2M316	EC 5969	2020-03-15
<input type="checkbox"/>	CDN	Schaffner	CDN M316	EC 2113-1	2019-07-16
<input type="checkbox"/>	Attenuator	Weinschel	68-6-44	EC 3043-9	2020-02-05
<input checked="" type="checkbox"/>	Tri-loop	Schwarzbeck	HXYZ 9170	EC 3384	2019-10-10
<input checked="" type="checkbox"/>	Voltage Probe	Schwarzbeck	TK9420	EC 4888	2019-09-12
<input type="checkbox"/>	Current probe	R&S	EZ-17	EC 3221	2020-03-15
<input type="checkbox"/>	I.S.N.	FCC	FCC-TLISN -T2-02	EC 3754	2020-02-05
<input type="checkbox"/>	I.S.N.	FCC	FCC-TLISN -T4-02	EC 3755	2020-02-05
<input type="checkbox"/>	I.S.N.	FCC	FCC-TLISN -T8-02	EC 3756	2020-02-05
Radiated Emission					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
<input checked="" type="checkbox"/>	Test Receiver	R&S	ESIB 26	EC 3045	2019-09-12
<input checked="" type="checkbox"/>	Bilog Antenna	TESEQ	CBL 6112D	EC 4206	2019-06-10
<input checked="" type="checkbox"/>	Pre-amplifier	R&S	AFS42- 00101800-25-S- 42	EC5262	2019-06-10
<input checked="" type="checkbox"/>	Horn antenna	R&S	HF 906	EC 3049	2020-11-17
<input checked="" type="checkbox"/>	Horn antenna	ETS	3117	EC 4792-1	2020-01-09
<input type="checkbox"/>	Horn antenna	TOYO	HAP18-26W	EC 4792-3	2020-07-09
<input checked="" type="checkbox"/>	Active loop antenna	Schwarzbeck	FMZB1519	EC 5345	2020-03-07

TEST REPORT

RF test					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
<input checked="" type="checkbox"/>	PXA Signal Analyzer	Keysight	N9030A	EC 5338	2020-03-05
<input checked="" type="checkbox"/>	Power sensor	Agilent	U2021XA	EC 5338-1	2020-03-05
<input checked="" type="checkbox"/>	Vector Signal Generator	Agilent	N5182B	EC 5175	2020-03-05
<input checked="" type="checkbox"/>	Spectrum analyzer	R&S	CMW500	EC5944	2019-12-23
<input checked="" type="checkbox"/>	MXG Analog Signal Generator	Agilent	N5181A	EC 5338-2	2020-03-05
<input type="checkbox"/>	Mobile Test System	Litepoint	lqxel	EC 5176	2020-01-09
<input type="checkbox"/>	Test Receiver	R&S	ESCI 7	EC 4501	2019-09-12
Tet Site					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
<input checked="" type="checkbox"/>	Shielded room	Zhongyu	-	EC 2838	2020-01-07
<input type="checkbox"/>	Shielded room	Zhongyu	-	EC 2839	2020-01-14
<input checked="" type="checkbox"/>	Semi-anechoic chamber	Albatross project	-	EC 3048	2019-07-31
<input type="checkbox"/>	Fully-anechoic chamber	Albatross project	-	EC 3047	2019-07-31
Additional instrument					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
<input checked="" type="checkbox"/>	Spectrum analyzer	Agilent	E7402A	EC 2254	2019-07-15
<input checked="" type="checkbox"/>	Therom-Hygrograph	ZJ1-2A	S.M.I.F.	EC 3783	2020-02-28
<input type="checkbox"/>	Therom-Hygrograph	ZJ1-2A	S.M.I.F.	EC 2122	2020-03-11
<input checked="" type="checkbox"/>	Therom-Hygrograph	ZJ1-2A	S.M.I.F.	EC 5198	2020-01-18
<input type="checkbox"/>	Therom-Hygrograph	ZJ1-2A	S.M.I.F.	EC 3326	2020-03-28
<input type="checkbox"/>	Pressure meter	YM3	Shanghai Mengde	EC 3320	2019-07-01

TEST REPORT**2.7 Measurement uncertainty**

The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Test item	Measurement uncertainty
Maximum peak output power	$\pm 0.74\text{dB}$
Radiated Emissions in restricted frequency bands below 1GHz	$\pm 4.90\text{dB}$
Radiated Emissions in restricted frequency bands above 1GHz	$\pm 5.02\text{dB}$
Emission outside the frequency band	$\pm 2.89\text{dB}$
Power line conducted emission	$\pm 3.19\text{dB}$

3 20dB bandwidth

Test result: Pass


3.1 Limit

Reporting only.

3.2 Measurement Procedure

- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the EMI receiver or spectrum analyzer shall be between two times and five times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level.
- d) Steps a) through c) might require iteration to adjust within the specified tolerances.
- e) The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target “-xx dB down” requirement; that is, if the requirement calls for measuring the -20 dB OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value.
- f) Set detection mode to peak and trace mode to max hold.
- g) Determine the reference value: Set the EUT to transmit an unmodulated carrier or modulated signal, as applicable. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value).
- h) Determine the “-xx dB down amplitude” using $[(\text{reference value}) - xx]$. Alternatively, this calculation may be made by using the marker-delta function of the instrument.
- i) If the reference value is determined by an unmodulated carrier, then turn the EUT modulation ON, and either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise, the trace from step g) shall be used for step j).
- j) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-xx dB down amplitude” determined in step h). If a marker is below this “-xx dB down amplitude” value, then it shall be as close as possible to this value. The occupied bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the “-xx dB down amplitude” determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth.
- k) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

3.3 Test Configuration



3.4 Test Results of 20dB bandwidth

Please refer to Appendix A.


4 Carrier Frequency Separation

Test result: Pass

4.1 Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

4.2 Test Configuration



4.3 Test Procedure and test setup

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a) Span: Wide enough to capture the peaks of two adjacent channels.
- b) RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
- c) Video (or average) bandwidth (VBW) \geq RBW.
- d) Sweep: Auto.
- e) Detector function: Peak.
- f) Trace: Max hold.
- g) Allow the trace to stabilize.

Use the marker-delta function to determine the separation between the peaks of the adjacent channels. Compliance of an EUT with the appropriate regulatory limit shall be determined. A plot of the data shall be included in the test report.

4.4 Test Results of Carrier Frequency Separation

Please refer to Appendix A.


5 Output power

Test result: Pass

5.1 Limit

For frequency hopping systems operating in the 902-928 MHz band: 1 watt for systems employing at least 50 hopping channels; and, 0.25 watts for systems employing less than 50 hopping channels, but at least 25 hopping channels, as permitted under paragraph (a)(1)(i) of this section.

5.2 Test Configuration



5.3 Measurement Procedure

This is an RF-conducted test to evaluate maximum peak output power. Use a direct connection between the antenna port of the unlicensed wireless device and the spectrum analyzer, through suitable attenuation. The hopping shall be disabled for this test:

- a) Use the following spectrum analyzer settings:
 - 1) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
 - 2) RBW > 20 dB bandwidth of the emission being measured.
 - 3) VBW \geq RBW.
 - 4) Sweep: Auto.
 - 5) Detector function: Peak.
 - 6) Trace: Max hold.
- b) Allow trace to stabilize.
- c) Use the marker-to-peak function to set the marker to the peak of the emission.
- d) The indicated level is the peak output power, after any corrections for external attenuators and cables.
- e) A plot of the test results and setup description shall be included in the test report.

5.4 Test Results of Output Power

Please refer to Appendix A.

6 Radiated Emissions

Test result: Pass

6.1 Limit

The radiated emissions which fall in the restricted bands, must also comply with the radiated emission limits specified showed as below:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

6.2 Measurement Procedure

For Radiated emission below 30MHz:

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- Both X and Y axes of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

NOTE:

- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

TEST REPORT**For Radiated emission above 30MHz:**


- a) The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c) The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e) The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f) The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 3 x RBW (Duty cycle \geq 98%) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported

6.3 Test Configuration


For Radiated emission below 30MHz:



For Radiated emission 30MHz to 1GHz:



For Radiated emission above 1GHz:



TEST REPORT

6.4 Test Results of Radiated Emissions

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

The worst data was listed in the report.

Test data:

CH	Antenna	Frequency (MHz)	Corrected Reading (dBuV/m)	Correct Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector
L	H	30.00	26.10	18.60	40.00	13.90	PK
	H	154.41	33.50	11.40	43.50	10.00	PK
	H	902.50	91.30	23.50	Fundamental	/	PK
	H	1987.98	36.30	-6.90	74.00	37.70	PK
	H	3861.72	36.90	-1.20	74.00	37.10	PK
	V	30.00	27.20	18.60	40.00	12.80	PK
	V	154.41	37.30	11.40	43.50	6.20	PK
	V	902.50	88.30	23.50	Fundamental	/	PK
	V	1306.61	29.50	-11.60	74.00	44.50	PK
	V	2124.25	35.00	-6.40	74.00	39.00	PK
M	H	61.10	28.70	6.90	40.00	11.30	PK
	H	915.10	88.30	23.50	Fundamental	/	PK
	H	1306.61	28.90	-11.60	74.00	45.10	PK
	H	2362.73	33.80	-5.70	74.00	40.20	PK
	V	61.10	31.30	6.90	40.00	8.70	PK
	V	915.10	88.80	23.50	Fundamental	/	PK
	V	1238.48	28.80	-12.00	74.00	45.20	PK
H	V	1987.98	33.40	-6.90	74.00	40.60	PK
	H	239.94	40.20	12.80	46.00	5.80	PK
	H	362.40	31.70	16.60	46.00	14.30	PK
	H	927.50	88.30	23.50	Fundamental	/	PK
	H	1238.48	29.70	-12.00	74.00	44.30	PK
	H	2260.52	33.90	-6.00	74.00	40.10	PK
	V	239.94	38.90	12.80	46.00	7.10	PK
	V	362.40	31.90	16.60	46.00	14.10	PK
	V	927.50	88.50	23.50	Fundamental	/	PK
	V	1715.43	36.90	-8.70	74.00	37.10	PK
V	2771.54	34.10	-5.20	74.00	39.90	PK	

TEST REPORT

- Remark: 1. Correct Factor = Antenna Factor + Cable Loss (+ Amplifier, for higher than 1GHz), the value was added to Original Receiver Reading by the software automatically.
2. Corrected Reading = Original Receiver Reading + Correct Factor
3. Margin = Limit - Corrected Reading
4. If the PK Corrected Reading is lower than AV limit, the AV test can be elided.

Example: Assuming Antenna Factor = 30.20dB/m, Cable Loss = 2.00dB,
Gain of Preamplifier = 32.00dB, Original Receiver Reading = 10.00dBuV,
Limit = 40.00dBuV/m.
Then Correct Factor = $30.20 + 2.00 - 32.00 = 0.20\text{dB/m}$;
Corrected Reading = $10\text{dBuV} + 0.20\text{dB/m} = 10.20\text{dBuV/m}$;
Margin = $40.00\text{dBuV/m} - 10.20\text{dBuV/m} = 29.80\text{dB}$.


7 Conducted Spurious Emissions & Band Edge

Test result: Pass

7.1 Limit

In any 100kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

7.2 Test Configuration



7.3 Measurement Procedure

- a) Connect the EMI receiver or spectrum analyzer to the EUT using an appropriate RF cable connected to the EUT output. Configure the spectrum analyzer settings as described in step e)
- b) Set the EUT to the lowest frequency channel (for the hopping on test, the hopping sequence shall include the lowest frequency channel).
- c) Set the EUT to operate at maximum output power and 100% duty cycle, or equivalent “normal mode of operation” as specified in 6.10.3. of ANSI C63.10.
- d) If using the radiated method, then use the applicable procedure(s) of 6.4, 6.5, or 6.6 of ANSI C63.10, and orient the EUT and measurement antenna positions to produce the highest emission level.
- e) Perform the test as follows:
 - 1) Span: Wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products that fall outside of the authorized band of operation.
 - 2) Reference level: As required to keep the signal from exceeding the maximum instrument input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level.
 - 3) Attenuation: Auto (at least 10 dB preferred).
 - 4) Sweep time: Coupled.
 - 5) Resolution bandwidth: 100 kHz
 - 6) Video bandwidth: 300 kHz
 - 7) Detector: Peak
 - 8) Trace: Max hold

TEST REPORT

- f) Allow the trace to stabilize. For the test with the hopping function turned ON, this can take several minutes to achieve a reasonable probability of intercepting any emissions due to oscillator overshoot.
- g) Set the marker on the emission at the band edge, or on the highest modulation product outside of the band, if this level is greater than that at the band edge. Enable the marker-delta function, and then use the marker-to-peak function to move the marker to the peak of the in-band emission.
- h) Repeat step c) through step e) for every applicable modulation.
- i) Set the EUT to the highest frequency channel (for the hopping on test, the hopping sequence shall include the highest frequency channel) and repeat step c) through step d).
- j) The band-edge measurement shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

7.4 Test Results of Conducted Spurious Emissions & Band Edge

Please refer to Appendix A

8 Power line conducted emission


Test result: Pass

8.1 Limit

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	QP	AV
0.15-0.5	66 to 56*	56 to 46 *
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

8.2 Test Configuration



8.3 Measurement Procedure


Measured levels of ac power-line conducted emission shall be the emission voltages from the voltage probe, where permitted, or across the 50 Ω LISN port (to which the EUT is connected), where permitted, terminated into a 50 Ω measuring instrument. All emission voltage and current measurements shall be made on each current-carrying conductor at the plug end of the EUT power cord by the use of mating plugs and receptacles on the LISN, if used. Equipment shall be tested with power cords that are normally supplied or recommended by the manufacturer and that have electrical and shielding characteristics that are the same as those cords normally supplied or recommended by the manufacturer. For those measurements using a LISN, the 50 Ω measuring port is terminated by a measuring instrument having 50 Ω input impedance. All other ports are terminated in 50 Ω loads.

Tabletop devices shall be placed on a platform of nominal size 1 m by 1.5 m, raised 80 cm above the reference ground plane. The vertical conducting plane or wall of an RF-shielded (screened) room shall be located 40 cm to the rear of the EUT. Floor-standing devices shall be placed either directly on the reference ground-plane or on insulating material as described in ANSI C63.4. All other surfaces of tabletop or floor-standing EUTs shall be at least 80 cm from any other grounded conducting surface, including the case or cases of one or more LISNs.

The bandwidth of the test receiver is set at 9 kHz.


8.4 Test Results of Power line conducted emission

Test Curve:



Test Data:

Frequency (MHz)	Quasi-peak			Average		
	level dB(µV)	Limit dB(µV)	Margin (dB)	level dB(µV)	limit dB(µV)	Margin (dB)
0.39	47.25	57.98	10.73	39.57	47.98	8.41
0.59	35.48	56.00	20.52	28.19	46.00	17.81
0.78	34.54	56.00	21.46	27.50	46.00	18.50
1.36	32.96	56.00	23.04	24.59	46.00	21.41
2.04	32.89	56.00	23.11	25.10	46.00	20.90
2.79	31.35	56.00	24.65	22.95	46.00	23.05



Test Data:

Frequency (MHz)	Quasi-peak			Average		
	level dB(µV)	Limit dB(µV)	Margin (dB)	level dB(µV)	limit dB(µV)	Margin (dB)
0.39	43.56	58.08	14.52	36.47	48.08	11.61
0.61	39.50	56.00	16.50	32.04	46.00	13.96
0.77	39.52	56.00	16.48	30.79	46.00	15.21
1.48	36.46	56.00	19.54	28.18	46.00	17.82
2.20	35.28	56.00	20.72	27.48	46.00	18.52
2.91	33.65	56.00	22.35	25.56	46.00	20.44

Remark: 1. Correct Factor = LISN Factor + Cable Loss, the value was added to Original Receiver Reading by the software automatically.

2. Corrected Reading = Original Receiver Reading + Correct Factor

3. Margin = Limit - Corrected Reading

4. If the PK Corrected Reading is lower than AV limit, the AV test can be elided.


9 Number of Hopping Frequencies

Test result:Pass

9.1 Limit

Number of Hopping Frequencies in the 902-928 MHz band shall use at least 50 channels.

9.2 Test Configuration



9.3 Test procedure and test setup

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a) Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
- b) RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- c) VBW \geq RBW.
- d) Sweep: Auto.
- e) Detector function: Peak.
- f) Trace: Max hold.
- g) Allow the trace to stabilize.

9.4 Test Results of Number of Hopping Frequencies

Please refer to Appendix A


10 Dwell Time

Test result:Pass

10.1 Limit

The dwell time on any channel shall not be greater than 0.4 seconds within a 20 seconds period.

10.2 Test Configuration



10.3 Test procedure and test setup

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a) Span: Zero span, centered on a hopping channel.
- b) RBW shall be \leq channel spacing and where possible RBW should be set $\gg 1 / T$, where T is the expected dwell time per channel.
- c) Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.
- d) Detector function: Peak.
- e) Trace: Max hold.

Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time.

Repeat the measurement using a longer sweep time to determine the number of hops over the period specified in the requirements. The sweep time shall be equal to, or less than, the period specified in the requirements. Determine the number of hops over the sweep time and calculate the total number of hops in the period specified in the requirements, using the following equation:

$$\text{(Number of hops in the period specified in the requirements)} = \text{(number of hops on spectrum analyzer)} \times \text{(period specified in the requirements / analyzer sweep time)}$$

The average time of occupancy is calculated from the transmit time per hop multiplied by the number of hops in the period specified in the requirements. If the number of hops in a specific time varies with

TEST REPORT

different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation.

The measured transmit time and time between hops shall be consistent with the values described in the operational description for the EUT.

10.4 Test Results of Dwell Time

Please refer to Appendix A

11 Occupied Bandwidth

Test result: **Tested**

11.1 Limit


None

11.2 Measurement Procedure

The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts.

The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the occupied bandwidth (OBW) and video bandwidth (VBW) shall be approximately 3x RBW.

11.3 Test Configuration



11.4 The results of Occupied Bandwidth

Please refer to Appendix A

12 Antenna requirement

Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

Result:


EUT uses permanently attached antenna to the intentional radiator, so it can comply with the provisions of this section.

Appendix A: Test results

1.1 RF Output Power

1.1.1 Test Result and Data

Maximum Output Power					
Mode	Test Frequency (MHz)	Power (dBm)	Antenna Gain (dBi)	e.i.r.p (dBm)	Result
QPSK	902.5	23.624	2.50	26.124	Pass
QPSK	915.2	23.718	2.50	26.218	Pass
QPSK	927.5	23.694	2.50	26.194	Pass




TEST REPORT

1.2 20dB Down Bandwidth

1.2.1 Test Result and Data

Occupied 20dB Bandwidth		
Mode	Test Frequency (MHz)	20dB Bandwidth (kHz)
GFSK	902.5	28.912
GFSK	915.1	29.716
GFSK	927.5	30.886





TEST REPORT

1.3 Transmitter Spurious Emission

1.3.1 Test Result and Data

Transmitter Spurious Emission				
Mode	Test Frequency (MHz)	Frequency Range	Power (dBm)	Result
QPSK	902.5	30MHz~1000MHz	-46.484	Pass
QPSK	902.5	1000MHz~10000MHz	-32.946	Pass
QPSK	902.5	Band Edge	-38.160	Pass
QPSK	915.1	30MHz~1000MHz	-45.360	Pass
QPSK	915.1	1000MHz~10000MHz	-33.351	Pass
QPSK	927.5	30MHz~1000MHz	-45.960	Pass
QPSK	927.5	1000MHz~10000MHz	-34.485	Pass
QPSK	927.5	Band Edge	-32.152	Pass






TEST REPORT

1.4 Frequency Band Edge

1.4.1 Test Result and Data


Frequency Band Edges-Conducted					
Mode	Test Range (MHz)	Hopping Mode	Band Edge (dBm)	Limit (dBm)	Result
QPSK	895.0~905.0	Hopping On	-30.374	3.52	Pass
QPSK	924.3~932.3	Hopping On	-23.493	3.57	Pass




1.5 Dwell Time

1.5.1 Test Result and Data

Dwell Time					
Mode	Test Frequency (MHz)	Transmission Time (ms)	Number	Dwell Time (ms)	Result
QPSK	902.5	39.90	3	119.70	Pass
QPSK	915.1	40.00	4	160.00	Pass
QPSK	927.5	40.00	4	160.00	Pass





TEST REPORT

1.6 Carrier Frequency Separation

1.6.1 Test Result and Data


Carrier Frequency Separation				
Mode	Frequency (MHz)	Frequency Separation (MHz)	(20dB BW) Limits(kHz)	Result
QPSK	902.5	30.0	25	Pass
QPSK	915.1	30.6	25	Pass
QPSK	927.5	31.6	25	Pass



1.7 Hopping Channel Numbers

1.7.1 Test Result and Data

Number Of Hopping Channels				
Mode	Test Frequency (MHz)	Number of Hopping channel	Limit	Result
QPSK	902~904.5	54	>50	Pass
QPSK	914.5~917	54	>50	Pass
QPSK	925.5~928	54	>50	Pass



***** END *****