



TEST REPORT

No.I16N00380-EMC

for

Huawei Technologies Co., Ltd.

Fixed Wireless Terminal

Model Name: F617-50

FCC ID: QISF617-50

with

Hardware Version: WL1F617I

Software Version: V100R001

Issued Date: 2016-04-28

Test Laboratory:

FCC 2.948 Listed: No.342690

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

Test Laboratory:

CTTL, Telecommunication Technology Labs, Academy of Telecommunication Research, MIIT

No.52, HuayuanNorth Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633, Fax:+86(0)10-62304633Email:cttl@chinattl.com, website:www.chinattl.com



REPORT HISTORY

Report Number	Revision	Description	Issue Date
I16N00380-EMC	Rev.0	1st edition	2016-04-28



CONTENTS

1. TEST LABORATORY	4
1.1. TESTING LOCATION	4
1.2. TESTING ENVIRONMENT	4
1.3. PROJECT DATA	4
1.4. SIGNATURE	4
2. CLIENT INFORMATION	5
2.1. APPLICANT INFORMATION	5
2.2. MANUFACTURER INFORMATION	5
3. EQUIPMENT UNDERTEST (EUT) AND ANCILLARY EQUIPMENT (AE)	6
3.1. ABOUT EUT	6
3.2. INTERNAL IDENTIFICATION OF EUT	6
3.3. INTERNAL IDENTIFICATION OF AE	6
3.4. EUT SET-UPS	7
4. REFERENCE DOCUMENTS	8
4.1. REFERENCE DOCUMENTS FOR TESTING	8
5. LABORATORY ENVIRONMENT	9
6. SUMMARY OF TEST RESULTS	10
7. TEST FACILITIES UTILIZED	11
ANNEX A: MEASUREMENT RESULTS.....	12

1. Test Laboratory

1.1. Testing Location

Address: TCL International E city No. 1001 Zhongshanyuan Road, Nanshan District, Shenzhen, Guangdong, China
Postal Code: 518048
Telephone: +86(755)33322000
Fax: +86(755)33322000

1.2. Testing Environment

Normal Temperature: 15-35°C
Relative Humidity: 20-75%

1.3. Project data


Testing Start Date: 2016-04-14
Testing End Date: 2016-04-22

1.4. Signature




Liang Yong

(Prepared this test report)



Du Zhaoxuan

(Reviewed this test report)



Cao Junfei

Director of the laboratory
(Approved this test report)



2. Client Information

2.1. Applicant Information

Company Name: Huawei Technologies Co., Ltd.
Address: Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C

2.2. Manufacturer Information

Company Name: Huawei Technologies Co., Ltd.
Address: Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	Fixed Wireless Terminal
Model Name	F617-50
Marketing Name	HUAWEI F617-50, F617-50
FCC ID	QISF617-50
TX Band	GSM1900,WCDMA Band II
RX Band	GSM1900, WCDMA Band II

The Equipment Under Test(EUT)are a model of Fixed Wireless Terminal with integrated antenna. The EUT supports GPRS service and EGPRS service.

Remark: The above EUT's information is declared by manufacturer. Please refer to the specifications or user's manual for more detailed information.

3.2. Internal Identification of EUT

EUT ID*	SN or IMEI
N0.1	861140030000808

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE

AE ID*	Description	SN
AE1	Battery	/
AE2	Travel charger	/

AE1-1

Model	HGB-2A10×3
Manufacturer	Huawei Technologies Co., Ltd.
Capacitance	1000mAh
Nominal voltage	3.6V
SN	GRPG10600993

AE1-2

Model	HGB-2A10×3
Manufacturer	Huawei Technologies Co., Ltd.
Capacitance	1000mAh
Nominal voltage	3.6V
SN	HGYF42014546

AE2-1

Model	HW-050100E6W
Manufacturer	SHENZHEN HUNTKEY ELECTRIC CO., LTD
Length of cable	145cm
SN	XQHFB1301081



AE2-2

Model HW-050100E6W
Manufacturer Shenzhen OCT Xinqiao Technology Co.,ltd
Length of cable 145cm
SN HKAG12549992

AE2-3

Model HW-050100U6W
Manufacturer SHENZHEN HUNTKEY ELECTRIC CO., LTD
Length of cable 145cm
SN /

AE2-4

Model HW-050100U6W
Manufacturer Shenzhen OCT Xinqiao Technology Co.,ltd
Length of cable 145cm
SN /

*AE ID: is used to identify the test sample in the lab internally.

3.4. EUT set-ups

EUT set-up No.	Combination of EUT and AE	Remarks
Set.1	EUT1+ AE1-1 + AE2-1	Charging mode
Set.2	EUT1+ AE1-2 + AE2-2	Charging mode
Set.3	EUT1+AE1-1+PC	USB mode
Set.4	EUT1+AE1-2+PC	USB mode

4. Reference Documents

4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 15, Subpart B	Radio frequency devices	10-1-2015 Edition
ANSI C63.4	Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2014

5. LABORATORY ENVIRONMENT

Semi-anechoic chamber did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	0.014MHz-1MHz,>60dB; 1MHz-18000MHz,>90dB
Electrical insulation	> 2MΩ
Ground system resistance	< 4 Ω
Normalised site attenuation (NSA)	< ±4 dB, 3 m distance, from 30 to 1000 MHz

Shield room did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. =35 %, Max. = 60 %
Shielding effectiveness	0.014MHz-1MHz,>60dB; 1MHz-10000MHz,>90dB
Electrical insulation	> 2MΩ
Ground system resistance	< 4 Ω

Fully-anechoic chamber did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	0.014MHz-1MHz,>60dB; 1MHz-18000MHz,>90dB
Electrical insulation	> 2MΩ
Ground system resistance	< 4 Ω
Voltage Standing Wave Ratio (VSWR)	≤ 6 dB, from 1 to 18 GHz, 3 m distance
Uniformity of field strength	Between 0 and 6 dB, from 80 to 3000 MHz



6. SUMMARY OF TEST RESULTS

Abbreviations used in this clause:	
P	Pass
NA	Not applicable
F	Fail

Items	Test Name	Clause in FCC rules	Section in this report	Verdict
1	Radiated Emission	15.109(a)	A.1	P
2	Conducted Emission	15.107(a)	A.2	P



7. Test Facilities Utilized

NO.	NAME	TYPE	SERIES NUMBER	PRODUCER	CALDUE DATE	CAL PERIOD
1.	Test Receiver	ESCI	100701	R&S	2016.08.10	1 year
2.	Test Receiver	ESCI	100702	R&S	2016.05.30	1 year
3.	Spectrum Analyzer	FSP 40	100378	R&S	2016.12.18	1 year
4.	BiLog Antenna	VULB9163	9163 329	Schwarzbeck	2017.01.20	3 years
5.	LISN	ESH2-Z5	100196	R&S	2017.01.12	1 year
6.	Horn Antenna	3117	00066585	ETS-Lindgren	2019.03.05	3 years
7.	Universal Radio Communication Tester	E5515C	GB44051324	Agilent	2016.05.19	1 year
8.	PC	M4099t	SA08850737	Lenovo	/	/
9.	Monitor	L1710d	0M04340B10 01010	Lenovo	/	/
10.	Printer	P1008	VNF6C12491	HP	/	/
11.	Keyboard	KB-0225	0723779	Lenovo	/	/
12.	Mouse	MO28UOL	44B39412	Lenovo	/	/

ANNEX A: MEASUREMENT RESULTS

A.1 Radiated Emission (§15.109(a))

Reference

FCC: CFR Part 15.109(a)

A.1.1 Method of measurement

The field strength of radiated emissions from the unintentional radiator (USB mode of MS and charging mode of MS) at a distance of 3 meters is tested. Tested in accordance with the procedures of ANSI C63.4 - 2014, section 8.3.

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

A.1.2 EUT Operating Mode:

The MS is operating in the USB mode and charging mode. During the test MS is connected to a PC via a USB cable in the case of USB mode and is connected to a charger in the case of charging mode. The model of the PC is Lenovo Thinkcentre M4099t, and the serial number of the PC is SA08850737. PC go to network via MS.

A.1.3 Measurement Limit

Limit from CFR Part 15.109(a)

Frequency range (MHz)	Field strength limit ($\mu\text{V}/\text{m}$)		
	Quasi-peak	Average	Peak
30-88	100		
88-216	150		
216-960	200		
960-1000	500		
>1000		500	5000

*Note: The original limit is defined at 10m test distance. This limit is calculated according to CISPR requirements.

A.1.4 Test Condition

Frequency of emission (MHz)	RBW/VBW	Sweep Time(s)
30-1000	120kHz (IF bandwidth)	5
Above 1000	1MHz/3MHz	15

A.1.5 Measurement Results

A "reference path loss" is established and the A_{Rpl} is the attenuation of "reference path loss". It includes the antenna factor of receive antenna and the path loss.

The measurement results are obtained as described below:

$$\text{Result} = P_{\text{Mea}} + A_{\text{Rpl}} = P_{\text{Mea}} + G_A + G_{\text{PL}}$$

Where

G_A : Antenna factor of receive antenna

G_{PL} : Path Loss

P_{Mea} : Measurement result on receiver.

Note: the result contains vertical part and Horizontal part

RE Measurement uncertainty: 30M-1GHz: 5.08dB (k=2);
1GHz-18GHz: 4.56 dB (k=2)

Set.1 Charging mode / Peak detector

Frequency(MHz)	Result(dBuV/m)	Polarity	A_{Rpl} (dB)	Margin(dB)	Limit (dB μ V/m)
14547.000000	58.3	H	13.7	15.7	74.0
15143.000000	59.1	H	14.3	14.9	74.0
15781.000000	59.7	V	14.5	14.3	74.0
16224.500000	59.9	V	14.9	14.1	74.0
16802.500000	60.8	V	15.8	13.2	74.0
17351.500000	60.2	H	15.9	13.8	74.0

Set.1 Charging mode / Average detector

Frequency(MHz)	Result(dBuV/m)	Polarity	A_{Rpl} (dB)	Margin(dB)	Limit (dB μ V/m)
14527.500000	46.3	H	13.7	7.7	54.0
15169.000000	47.4	V	14.3	6.6	54.0
15744.000000	48.0	V	14.4	6.0	54.0
16204.000000	48.3	H	14.9	5.7	54.0
16859.000000	48.8	V	16.1	5.2	54.0
17403.000000	48.4	H	16.2	5.6	54.0

Set.2 Charging mode / Peak detector

Frequency(MHz)	Result(dBuV/m)	Polarity	A _{Rpl} (dB)	Margin(dB)	Limit (dBμV/m)
14131.500000	58.1	V	13.3	15.9	74.0
15151.000000	59.0	V	14.3	15.0	74.0
15671.500000	59.7	H	14.4	14.3	74.0
16317.000000	60.4	H	15.3	13.6	74.0
16745.500000	60.6	H	15.4	13.4	74.0
17369.000000	60.7	H	16.0	13.3	74.0

Set.2 Charging mode / Average detector

Frequency(MHz)	Result(dBuV/m)	Polarity	A _{Rpl} (dB)	Margin(dB)	Limit (dBμV/m)
14539.500000	46.4	V	13.7	7.6	54.0
15142.500000	47.4	V	14.3	6.6	54.0
15752.500000	48.2	H	14.4	5.8	54.0
16224.500000	48.6	H	14.9	5.4	54.0
16789.500000	49.2	H	15.7	4.8	54.0
17415.500000	48.7	H	16.2	5.3	54.0

Set.3 USB mode / Peak detector

Frequency(MHz)	Result(dBuV/m)	Polarity	A _{Rpl} (dB)	Margin(dB)	Limit (dBμV/m)
14538.000000	56.2	H	11.9	17.8	74.0
14885.500000	57.0	H	11.9	17.0	74.0
15675.500000	59.3	V	12.6	14.7	74.0
16216.000000	59.8	H	13.1	14.2	74.0
16804.500000	61.2	H	13.9	12.8	74.0
17715.500000	59.6	V	13.9	14.4	74.0

Set.3 USB mode / Average detector

Frequency(MHz)	Result(dBuV/m)	Polarity	A _{Rpl} (dB)	Margin(dB)	Limit (dBμV/m)
13999.500000	44.7	H	10.8	9.3	54.0
15167.500000	45.3	H	12.1	8.7	54.0
15688.000000	47.4	H	12.7	6.6	54.0
16226.000000	47.8	H	13.1	6.2	54.0
16769.500000	48.5	H	13.9	5.5	54.0
17386.000000	47.9	V	14.0	6.1	54.0

Set.4 USB mode / Peak detector

Frequency(MHz)	Result(dBuV/m)	Polarity	A _{Rpl} (dB)	Margin(dB)	Limit (dB μ V/m)
14143.000000	57.4	H	11.2	16.6	74.0
15152.000000	58.0	H	12.1	16.0	74.0
15668.500000	58.8	V	12.6	15.2	74.0
16239.500000	59.7	V	13.2	14.3	74.0
16782.000000	60.1	H	13.9	13.9	74.0
17269.000000	60.5	V	13.9	13.5	74.0

Set.4 USB mode / Average detector

Frequency(MHz)	Result(dBuV/m)	Polarity	A _{Rpl} (dB)	Margin(dB)	Limit (dB μ V/m)
14153.000000	44.7	V	11.2	9.3	54.0
15149.500000	45.6	H	12.1	8.4	54.0
15768.500000	47.2	V	12.8	6.8	54.0
16231.500000	47.8	V	13.1	6.2	54.0
16783.000000	48.3	H	13.9	5.7	54.0
17347.500000	47.9	V	14.0	6.1	54.0

Note: The measurement result of Set.1 Set.2 Set.3and Set.4 showed here are worst cases of combinations of different batteries and USB cables.

Charging mode: Set 1




Figure A.1 Radiated Emission from 30MHz to 1GHz




Figure A.2 Radiated Emission from 1GHz to 18GHz

Charging mode: Set 2




Figure A.3 Radiated Emission from 30MHz to 1GHz




Figure A.4 Radiated Emission from 1GHz to 18GHz

USB mode: Set 3




Figure A.5 Radiated Emission from 30MHz to 1GHz




Figure A.6 Radiated Emission from 1GHz to 18GHz

Note: the spike over the limit is coming from the traffic carrier.

USB mode: Set 4




Figure A.7 Radiated Emission from 30MHz to 1GHz




Figure A.8 Radiated Emission from 1GHz to 18GHz

Note: the spike over the limit is coming from the traffic carrier.

A.2 Conducted Emission (§15.107(a))

Reference

FCC: CFR Part 15.107(a)

A.2.1 Method of measurement

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits. Tested in accordance with the procedures of ANSI C63.4 - 2014, section 7.3.

A.2.2 EUT Operating Mode:

The MS is operating in the USB mode and charging mode. During the test MS is connected to a PC via a USB cable in the case of USB mode and is connected to a charger in the case of charging mode. The model of the PC is Lenovo Thinkcentre M4099t, and the serial number of the PC is SA08850737. PC go to network via MS.

A.2.3 Measurement Limit

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency

A.2.4 Test Condition in charging mode

Voltage (V)	Frequency (Hz)
120	60

RBW	Sweep Time(s)
9kHz	1

CE Measurement uncertainty: 2.7 dB (k=2)

A.2.5 Measurement Results
Charging mode:Set.1




Figure A.9 Conducted Emission

Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.162000	41.0	GND	L1	10.0	24.4	65.4
0.446000	40.4	GND	L1	10.0	16.6	56.9
0.478000	41.6	GND	L1	10.0	14.8	56.4
0.642000	38.4	GND	L1	10.0	17.6	56.0
0.710000	38.4	GND	L1	10.0	17.6	56.0
16.546000	41.8	GND	N	10.5	18.2	60.0

Final Measurement Detector 2

Frequency (MHz)	Average (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.394000	34.7	GND	L1	10.0	13.3	48.0
0.442000	29.3	GND	L1	10.0	17.7	47.0
0.482000	27.7	GND	N	10.1	18.6	46.3
0.710000	28.1	GND	L1	10.0	17.9	46.0
2.238000	26.0	GND	L1	10.1	20.0	46.0
16.054000	33.6	GND	L1	10.4	16.4	50.0

Charging mode:Set.2

ESH2-Z5 Scan-FCC




Figure A.10 Conducted Emission

Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.166000	37.9	GND	L1	10.0	27.3	65.2
0.266000	38.3	GND	L1	10.0	22.9	61.2
0.298000	38.0	GND	L1	10.0	22.3	60.3
0.330000	38.2	GND	N	10.0	21.3	59.5
0.930000	33.0	GND	L1	10.1	23.0	56.0
21.894000	34.0	GND	L1	10.6	26.0	60.0

Final Measurement Detector 2

Frequency (MHz)	Average (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.266000	33.5	GND	N	10.1	17.8	51.2
0.298000	32.9	GND	N	10.1	17.4	50.3
0.330000	35.9	GND	N	10.0	13.6	49.5
0.362000	33.7	GND	N	10.1	14.9	48.7
1.358000	26.9	GND	N	10.1	19.1	46.0
1.390000	26.7	GND	N	10.1	19.3	46.0

USB mode:Set.3

ESH2-Z5 Scan-FCC




Figure A.11 Conducted Emission

Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.202000	45.7	GND	N	10.1	17.8	63.5
0.306000	43.8	GND	N	10.1	16.2	60.1
0.506000	34.9	GND	N	10.1	21.1	56.0
0.606000	35.4	GND	N	10.1	20.6	56.0
0.706000	31.1	GND	N	10.0	24.9	56.0
7.462000	35.4	GND	L1	10.3	24.6	60.0

Final Measurement Detector 2

Frequency (MHz)	Average (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.202000	45.3	GND	N	10.1	8.2	53.5
0.306000	43.3	GND	N	10.1	6.8	50.1
0.606000	33.5	GND	N	10.1	12.5	46.0
0.710000	35.3	GND	N	10.0	10.7	46.0
1.114000	31.1	GND	N	10.1	14.9	46.0
1.518000	26.9	GND	N	10.1	19.1	46.0

USB mode:Set.4

ESH2-Z5 Scan-FCC




Figure A.12 Conducted Emission

Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.202000	44.9	GND	N	10.1	18.6	63.5
0.306000	44.7	GND	N	10.1	15.4	60.1
0.510000	35.5	GND	N	10.1	20.5	56.0
0.610000	37.0	GND	N	10.0	19.0	56.0
4.982000	27.5	GND	L1	10.2	28.5	56.0
7.298000	35.7	GND	L1	10.3	24.3	60.0

Final Measurement Detector 2

Frequency (MHz)	Average (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.202000	44.5	GND	N	10.1	9.0	53.5
0.306000	44.2	GND	N	10.1	5.9	50.1
0.610000	35.0	GND	N	10.0	11.0	46.0
0.714000	35.4	GND	N	10.0	10.6	46.0
1.018000	32.8	GND	L1	10.0	13.2	46.0
1.526000	29.7	GND	N	10.1	16.3	46.0

END OF REPORT