



FCC Part15.247 Test Report

Product Name : GSM Mobile Phone
Model No. : HUAWEI G6310
FCC ID : QISG6310

Applicant : Huawei Technologies Co., Ltd.
Address : Bantian, Longgang District, Shenzhen, 518129
Guangdong, P. R. China

Date of Receipt : 22/05/2012
Test Date : 26/05/2012~11/06/2012
Issued Date : 14/06/2012
Report No. : 125S062R-RF-US-P06V02
Report Version : V1.2

The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF, CNAS or any agency of the Government.
The test report shall not be reproduced except in full without the written approval of QuieTek Corporation.

Test Report Certification

Issued Date : 14/06/2012

Report No. : 125S062R-RF-US-P06V02



Product Name : GSM Mobile Phone
 Applicant : Huawei Technologies Co., Ltd.
 Address : Bantian, Longgang District, Shenzhen, 518129 Guangdong, P.
 R. China
 Manufacturer : Huawei Technologies Co., Ltd.
 Address : Bantian, Longgang District, Shenzhen, 518129 Guangdong, P.
 R. China
 Model No. : HUAWEI G6310
 FCC ID : QISG6310
 EUT Voltage : DC 3.7V
 Trade Name : HUAWEI
 Applicable Standard : FCC CFR Title 47 Part 15 Subpart C: 2011;
 ANSI C63.4: 2009; ANSI C63.10: 2009
 Test Result : Complied
 Performed Location : Suzhou EMC Laboratory
 No.99 Hongye Rd., Suzhou Industrial Park Loufeng Hi-Tech
 Development Zone., Suzhou, China
 TEL: +86-512-6251-5088 / FAX: +86-512-6251-5098
 FCC Registration Number: 800392

Documented By : Alice Ni
 (Engineering ADM: Alice Ni)
 Reviewed By : Robin Wu
 (Engineering Supervisor: Robin Wu)
 Approved By : Marlin Chen
 (Engineering Manager: Marlin Chen)

Laboratory Information

We, **Quietek Corporation**, are an independent EMC and safety consultancy that was established the whole facility in our laboratories. The test facility has been accredited/accepted(audited or listed) by the following related bodies in compliance with ISO 17025, EN 45001 and specified testing scope:

| | | |
|----------------------|----------|-----------------------|
| Taiwan R.O.C. | : | BSMI, NCC, TAF |
| Germany | : | TUV Rheinland |
| Norway | : | Nemko, DNV |
| USA | : | FCC, NVLAP |
| Japan | : | VCCI |
| China | : | CNAS |

The related certificate for our laboratories about the test site and management system can be downloaded from Quietek Corporation's Web Site :<http://www.quietek.com/tw/ctg/cts/accreditations.htm>
The address and introduction of Quietek Corporation's laboratories can be founded in our Web site :
<http://www.quietek.com/>

If you have any comments, Please don't hesitate to contact us. Our contact information is as below:

HsinChu Testing Laboratory :

No.75-2, 3rd Lin, Wangye Keng, Yongxing Tsuen, Qionglin Shiang, Hsinchu County 307, Taiwan, R.O.C.
TEL:+886-3-592-8858 / FAX:+886-3-592-8859 E-Mail : service@quietek.com

Linkou Testing Laboratory :

No.5-22, Ruishukeng, Linkou Dist., New Taipei City 24451, Taiwan, R.O.C.
TEL : 886-2-8601-3788 / FAX : 886-2-8601-3789 E-Mail : service@quietek.com

Suzhou Testing Laboratory :

No.99 Hongye Rd., Suzhou Industrial Park Loufeng Hi-Tech Development Zone., SuZhou, China
TEL : +86-512-6251-5088 / FAX : 86-512-6251-5098 E-Mail : service@quietek.com

TABLE OF CONTENTS

| Description | Page |
|---|------|
| 1. General Information | 6 |
| 1.1. EUT Description | 6 |
| 1.2. Mode of Operation | 9 |
| 1.3. Tested System Details | 10 |
| 1.4. Configuration of Tested System | 11 |
| 1.5. EUT Exercise Software | 12 |
| 2. Technical Test | 13 |
| 2.1. Summary of Test Result | 13 |
| 2.2. Test Environment | 14 |
| 3. Conducted Emission | 15 |
| 3.1. Test Equipment | 15 |
| 3.2. Test Setup | 15 |
| 3.3. Limit..... | 16 |
| 3.4. Test Procedure | 16 |
| 3.5. Uncertainty | 16 |
| 3.6. Test Result | 17 |
| 4. Radiated Emission | 19 |
| 4.1. Test Equipment | 19 |
| 4.2. Test Setup | 20 |
| 4.3. Limit..... | 21 |
| 4.4. Test Procedure | 21 |
| 4.5. Uncertainty | 21 |
| 4.6. Test Result | 22 |
| 5. RF Antenna Conducted Spurious..... | 26 |
| 5.1. Test Equipment | 26 |
| 5.2. Test Setup | 26 |
| 5.3. Limit..... | 26 |
| 5.4. Test Procedure | 27 |
| 5.5. Uncertainty | 27 |
| 5.6. Test Result | 28 |
| 6. Radiated Emission Band Edge | 36 |
| 6.1. Test Equipment | 36 |
| 6.2. Test Setup | 37 |
| 6.3. Limit..... | 37 |
| 6.4. Test Procedure | 37 |
| 6.5. Uncertainty | 37 |
| 6.6. Test Result | 38 |

| | | |
|-------|--|----|
| 7. | Operation Frequency Range of 20dB Bandwidth..... | 38 |
| 7.1. | Test Equipment | 70 |
| 7.2. | Test Setup | 70 |
| 7.3. | Limit..... | 70 |
| 7.4. | Test Procedure | 70 |
| 7.5. | Uncertainty | 70 |
| 7.6. | Test Result | 71 |
| 8. | Occupied Bandwidth | 75 |
| 8.1. | Test Equipment | 75 |
| 8.2. | Test Setup | 75 |
| 8.3. | Limit..... | 75 |
| 8.4. | Test Procedure | 75 |
| 8.5. | Uncertainty | 75 |
| 8.6. | Test Result | 76 |
| 9. | Power Output..... | 84 |
| 9.1. | Test Equipment | 84 |
| 9.2. | Test Setup | 84 |
| 9.3. | Limit..... | 84 |
| 9.4. | Test Procedure | 85 |
| 9.5. | Uncertainty | 85 |
| 9.6. | Test Result | 86 |
| 10. | Power Spectral Density | 90 |
| 10.1. | Test Equipment..... | 90 |
| 10.2. | Test Setup | 90 |
| 10.3. | Limit..... | 90 |
| 10.4. | Test Procedure | 91 |
| 10.5. | Uncertainty | 91 |
| 10.6. | Test Result..... | 92 |

1. General Information

1.1. EUT Description

| | |
|-------------------------|--|
| Product Name | GSM Mobile Phone |
| Model No. | HUAWEI G6310 |
| Hardware Version | LUCKY-V1.0 |
| Software Version | G6310V100R001C00B202SP05DW |
| Device Category | Portable |
| RF Exposure Environment | Uncontrolled |
| Antenna Type | Internal |
| 2G | |
| Support Band | GSM850/GSM900/DCS1800/PCS1900 |
| GPRS Type | Class B |
| GPRS Class | Class 12 |
| Uplink | GSM 850: 824~849MHz PCS 1900: 1850~1910MHz |
| Downlink | GSM 850: 869~894MHz PCS 1900: 1930~1990MHz |
| Release Version | R99 |
| Type of modulation | GMSK |
| Antenna Gain | -1.5dBi for GSM 850 0dBi for PCS 1900 |
| Bluetooth | |
| Bluetooth Frequency | 2402~2480MHz |
| Bluetooth Version | V2.1 + EDR |
| Type of modulation | FHSS |
| Data Rate | 1Mbps(GFSK), 2Mbps(Pi/4 DQPSK), 3Mbps (8DPSK) |
| Antenna Gain | -2dBi |
| Wi-Fi | |
| Wi-Fi Frequency | 802.11b/g/n(20MHz): 2412 ~ 2462 MHz 802.11n(40MHz): 2422 ~ 2452 MHz |
| Type of modulation | 802.11b: DSSS; 802.11g/n: OFDM |
| Data Rate | 802.11b: 1/2/5.5/11 Mbps 802.11g: 6/9/12/18/24/36/48/54 Mbps 802.11n: up to 150 Mbps |
| Antenna Gain | -2dBi |

| Components | |
|-------------------------|--|
| Headset Model Number #1 | HUAWEI/ HT-1350002-24K001 |
| Headset Model Number #2 | HUAWEI/ 150C-333E-3.5MM-2 |
| Battery #1 | Brand Name: HUAWEI M/N: HB4H1 Rated Voltage and Capacitance: 3.7V/1000mAh S/N: XD1111010424074 |
| Battery #2 | Brand Name: HUAWEI M/N: HB4H1 Rated Voltage and Capacitance: 3.7V/1000mAh S/N: GAGC322XC1201996 |
| Adapter #1 | Brand Name: HUAWEI M/N: HS-050040U6 Input: 100-240V~50/60Hz 0.2A Output: 5Vdc, 400mA S/N: HKABC1868436 |
| Adapter #2 | Brand Name: HUAWEI M/N: HS-050040U6 Input: 100-240V~50/60Hz 0.2A Output: 5Vdc, 400Ma S/N: BYABC2708623 |

Note : Adapter #1 is used for RF test.

For 2.4GHz Band

| 802.11b/g Working Frequency of Each Channel: | | | | | | | |
|--|-----------|---------|-----------|---------|-----------|---------|-----------|
| Channel | Frequency | Channel | Frequency | Channel | Frequency | Channel | Frequency |
| 01 | 2412 MHz | 02 | 2417 MHz | 03 | 2422 MHz | 04 | 2427 MHz |
| 05 | 2432 MHz | 06 | 2437 MHz | 07 | 2442 MHz | 08 | 2447 MHz |
| 09 | 2452 MHz | 10 | 2457 MHz | 11 | 2462 MHz | N/A | N/A |

| 802.11n(40MHz) Working Frequency of Each Channel: | | | | | | | |
|---|-----------|---------|-----------|---------|-----------|---------|-----------|
| Channel | Frequency | Channel | Frequency | Channel | Frequency | Channel | Frequency |
| 03 | 2422 MHz | 04 | 2427 MHz | 05 | 2432 MHz | 06 | 2437 MHz |
| 07 | 2442 MHz | 08 | 2447 MHz | 09 | 2452 MHz | N/A | N/A |

1.2. Mode of Operation

Quietek has verified the construction and function in typical operation. All the test modes were carried out with the EUT in normal operation, which was shown in this test report and defined as:

| |
|------------------------------------|
| Test Mode |
| Mode 1: Transmit by 802.11b |
| Mode 2: Transmit by 802.11g |
| Mode 3: Transmit by 802.11n(20MHz) |
| Mode 4: Transmit by 802.11n(40MHz) |

Note:


1. Regards to the frequency band operation: the lowest, middle and highest frequency of channel were selected to perform the test, then shown on this report.
2. For portable device, radiated spurious emission was verified over X, Y, Z axis, and shown the worst case on this report.
3. This device is a composite device in accordance with Part 15 Subpart B regulations. The function for the receiver was measured and made a test report that the report number is 125388R-ITUSP01V02.

1.3. Tested System Details

The types for all equipments, plus descriptions of all cables used in the tested system (including inserted cards) are:

| Product | | Manufacturer | Model No. | Serial No. | Power Cord |
|---------|-----|--------------|-----------|------------|------------|
| 1 | N/A | N/A | N/A | N/A | N/A |

1.4. Configuration of Tested System



1.5. EUT Exercise Software

| | |
|---|--|
| 1 | Setup the EUT and simulators as shown on above. |
| 2 | Turn on the power of equipment. |
| 3 | Execute the software provided by applicant on the phone. |
| 4 | Select test channel and test mode to test. |

2. Technical Test

2.1. Summary of Test Result

- No deviations from the test standards
- Deviations from the test standards as below description:

| Performed Test Item | Normative References | Test Performed | Deviation |
|--|--|----------------|-----------|
| Conducted Emission | FCC CFR Title 47 Part 15 Subpart C: 2011 Section 15.207 | Yes | No |
| Radiated Emission | FCC CFR Title 47 Part 15 Subpart C: 2011 Section 15.209 | Yes | No |
| RF Antenna Conducted Spurious | FCC CFR Title 47 Part 15 Subpart C: 2011 Section 15.247(d) | Yes | No |
| Radiated Emission Band Edge | FCC CFR Title 47 Part 15 Subpart C: 2011 15.247(d) | Yes | No |
| Operation Frequency Range of 20dB Bandwidth | FCC CFR Title 47 Part 15 Subpart C: 2011 15.215(c) | Yes | No |
| Occupied Bandwidth | FCC CFR Title 47 Part 15 Subpart C: 2011 Section 15.247(a)(2) | Yes | No |
| Power Output | FCC CFR Title 47 Part 15 Subpart C: 2011 Section 15.247(b)(3) | Yes | No |
| Power Spectral Density | FCC CFR Title 47 Part 15 Subpart C: 2011 Section 15.247(e) | Yes | No |

2.2. Test Environment

| Items | Required (IEC 68-1) | Actual |
|----------------------------|---------------------|----------|
| Temperature (°C) | 15-35 | 21 |
| Humidity (%RH) | 25-75 | 50 |
| Barometric pressure (mbar) | 860-1060 | 950-1000 |

3. Conducted Emission


3.1. Test Equipment

Conducted Emission / TR-1

| Instrument | Manufacturer | Type No. | Serial No. | Cali. Due Date |
|----------------------------|--------------|----------|------------|----------------|
| EMI Test Receiver | R&S | ESCI | 100726 | 2013.04.18 |
| Two-Line V-Network | R&S | ENV216 | 100043 | 2013.04.18 |
| Two-Line V-Network | R&S | ENV216 | 100044 | 2012.09.07 |
| 50ohm Coaxial Switch | Anritsu | MP59B | 6200464462 | 2013.05.04 |
| 50ohm Termination | SHX | TF2 | 07081401 | 2012.09.22 |
| Temperature/Humidity Meter | zhicheng | ZC1-2 | TR1-TH | 2013.01.10 |

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

3.2. Test Setup



3.3. Limit

| FCC Part 15 Subpart C Paragraph 15.207 Limits | | |
|---|-----------|-----------|
| Frequency (MHz) | QP (dBuV) | AV (dBuV) |
| 0.15 - 0.50 | 66 - 56 | 56 - 46 |
| 0.50 - 5.0 | 56 | 46 |
| 5.0 - 30 | 60 | 50 |

Note 1: The lower limit shall apply at the transition frequencies.

Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

3.4. Test Procedure

The EUT was setup according to ANSI C63.4: 2009 and tested according to ANSI C63.10: 2009 for compliance to FCC 47CFR 15.247 requirements.

The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface. The EUT and simulators are connected to the main power through a line impedance stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)

Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.

The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.


Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.

3.5. Uncertainty

The measurement uncertainty is defined as ± 2.02 dB


3.6. Test Result

| | |
|--|--------------------------|
| Site: TR1 | Time: 2012/05/31 - 20:31 |
| Limit: FCC_Part15.207_CE_AC Power_ClassB | Margin: 0 |
| Probe: ENV216_101044(0.009-30MHz) | Polarity: Line |
| EUT: GSM Mobile Phone | Power: AC 120V/60Hz |
| Note: Mode 1 | |



| No | Mark | Frequency (MHz) | Measure Level (dBuV) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV) | Factor (dB) | Type |
|----|------|-----------------|----------------------|----------------------|-----------------|--------------|-------------|------|
| 1 | * | 0.158 | 44.869 | 35.024 | -20.699 | 65.568 | 9.846 | QP |
| 2 | | 0.158 | 33.642 | 23.797 | -21.927 | 55.568 | 9.846 | AV |
| 3 | | 0.450 | 26.156 | 16.253 | -30.719 | 56.875 | 9.904 | QP |
| 4 | | 0.450 | 1.442 | -8.462 | -45.433 | 46.875 | 9.904 | AV |
| 5 | | 3.934 | 35.126 | 25.290 | -20.874 | 56.000 | 9.836 | QP |
| 6 | | 3.934 | 20.179 | 10.343 | -25.821 | 46.000 | 9.836 | AV |
| 7 | | 4.710 | 31.470 | 21.621 | -24.530 | 56.000 | 9.849 | QP |
| 8 | | 4.710 | 13.951 | 4.102 | -32.049 | 46.000 | 9.849 | AV |
| 9 | | 5.306 | 36.033 | 26.159 | -23.967 | 60.000 | 9.875 | QP |
| 10 | | 5.306 | 19.031 | 9.156 | -30.969 | 50.000 | 9.875 | AV |
| 11 | | 6.846 | 36.626 | 26.698 | -23.374 | 60.000 | 9.928 | QP |
| 12 | | 6.846 | 20.343 | 10.415 | -29.657 | 50.000 | 9.928 | AV |

| | |
|--|--------------------------|
| Site: TR1 | Time: 2012/05/31 - 20:34 |
| Limit: FCC_Part15.207_CE_AC Power_ClassB | Margin: 0 |
| Probe: ENV216_101044(0.009-30MHz) | Polarity: Neutral |
| EUT: GSM Mobile Phone | Power: AC 120V/60Hz |
| Note: Mode 1 | |



| No | Mark | Frequency (MHz) | Measure Level (dBuV) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV) | Factor (dB) | Type |
|----|------|-----------------|----------------------|----------------------|-----------------|--------------|-------------|------|
| 1 | | 0.170 | 36.585 | 26.616 | -28.375 | 64.960 | 9.969 | QP |
| 2 | | 0.170 | 19.525 | 9.556 | -35.435 | 54.960 | 9.969 | AV |
| 3 | | 0.330 | 25.076 | 15.111 | -34.376 | 59.451 | 9.965 | QP |
| 4 | | 0.330 | 2.525 | -7.440 | -46.926 | 49.451 | 9.965 | AV |
| 5 | | 0.494 | 22.305 | 12.253 | -33.795 | 56.100 | 10.052 | QP |
| 6 | | 0.494 | -0.451 | -10.503 | -46.551 | 46.100 | 10.052 | AV |
| 7 | * | 4.138 | 33.592 | 23.538 | -22.408 | 56.000 | 10.054 | QP |
| 8 | | 4.138 | 17.509 | 7.455 | -28.491 | 46.000 | 10.054 | AV |
| 9 | | 6.470 | 31.682 | 21.486 | -28.318 | 60.000 | 10.196 | QP |
| 10 | | 6.470 | 15.307 | 5.111 | -34.693 | 50.000 | 10.196 | AV |
| 11 | | 23.098 | 29.876 | 19.461 | -30.124 | 60.000 | 10.415 | QP |
| 12 | | 23.098 | 12.891 | 2.476 | -37.109 | 50.000 | 10.415 | AV |

4. Radiated Emission

4.1. Test Equipment

Radiated Emission / AC-2

| Instrument | Manufacturer | Type No. | Serial No. | Cal. Date |
|----------------------------|--------------|--------------|------------|------------|
| EMI Test Receiver | R&S | ESCI | 100573 | 2013.04.18 |
| Loop Antenna | R&S | HFH2-Z2 | 833799/003 | 2012.11.22 |
| Bilog Antenna | Teseq GmbH | CBL6112D | 27611 | 2012.10.18 |
| Coaxial Cable | Huber+Suhner | SUCOFLEX 106 | AC2-C | 2013.03.02 |
| Temperature/Humidity Meter | Zhicheng | ZC1-2 | AC2-TH | 2013.05.07 |


Radiated Emission / AC-5

| Instrument | Manufacturer | Type No. | Serial No. | Cal. Date |
|----------------------------|--------------|--------------|-------------|------------|
| Spectrum Analyzer | Agilent | N9010A | MY48030494 | 2013.04.18 |
| Preamplifier | Miteq | NSP1800-25 | 1364185 | 2013.05.04 |
| Preamplifier | Quietek | AP-040G | CHM-0906001 | 2013.05.04 |
| Bilog Antenna | Teseq GmbH | CBL6112D | 27612 | 2012.10.18 |
| Broad-Band Horn Antenna | Schwarzbeck | BBHA9120D | 499 | 2013.06.11 |
| Broad-Band Horn Antenna | Schwarzbeck | BBHA9170 | 294 | 2013.11.24 |
| Coaxial Cable | Huber+Suhner | SUCOFLEX 106 | AC5-C1 | 2013.03.02 |
| Coaxial Cable | Huber+Suhner | SUCOFLEX 106 | AC5-C2 | 2013.03.02 |
| Coaxial Cable | Huber+Suhner | SUCOFLEX 102 | AC5-C3 | 2013.03.02 |
| Temperature/Humidity Meter | Zhicheng | ZC1-2 | AC5-TH | 2013.01.10 |


Note 1: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

4.2. Test Setup

Under 1GHz Test Setup:



Above 1GHz Test Setup:



4.3. Limit

| FCC Part 15 Subpart C Paragraph 15.209 | | |
|--|--------------|----------------|
| Frequency (MHz) | Distance (m) | Level (dBuV/m) |
| 30 - 88 | 3 | 40 |
| 88 - 216 | 3 | 43.5 |
| 216 - 960 | 3 | 46 |
| Above 960 | 3 | 54 |

Note 1: The lower limit shall apply at the transition frequency.

Note 2: Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

Note 3: E field strength (dBuV/m) = 20 log E field strength (uV/m)

4.4. Test Procedure

The EUT was setup according to ANSI C63.4: 2009 and tested according to ANSI C63.10: 2009 for compliance to FCC 47CFR 15.247 requirements.

The EUT is placed on a turn table which is 0.8 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.4: 2009 on radiated measurement.

The resolution bandwidth below 1GHz setting on the field strength meter is 120 kHz and above 1GHz is 1MHz.

The frequency range from 30MHz to 10th harmonic is checked.

Note: When doing emission measurement above 1GHz, the horn antenna will be bended down a little (as horn antenna has the narrow beamwidth) in order to keeping the antenna in the “cone of radiation” of EUT. The 3dB beamwidth is 60 degrees for H-plane and 90 degrees for E-plane.

4.5. Uncertainty

The measurement uncertainty above 1G is defined as ± 3.9 dB
 below 1G is defined as ± 3.8 dB

4.6. Test Result

All of the test result shown indicates the worst case, and spectrum analyzer parameters setting as shown below:

Peak detector: RBW = 1MHz, VBW = 3MHz, sweep time = 200ms;

Average detector: RBW = 1MHz, VBW = 10Hz, sweep time = auto.

Mode 1: Transmit by 802.11b

| CH | Antenna | Frequency (MHz) | Reading Level (dBuV/m) | Factor (dB) | Measure Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|----|---------|-----------------|------------------------|-------------|------------------------|----------------|-------------|----------|
| 1 | V | 2413.2 | 69.2 | 31.2 | 100.4 | Fundamental | / | PK |
| | H | 158.0 | -0.7 | 10.0 | 9.3 | 43.5 | -34.2 | PK |
| | V | 542.0 | -0.6 | 19.4 | 18.8 | 46 | -27.2 | PK |
| | V | 3125.0 | 35.0 | 0.0 | 35.0 | 54(Note) | -19.0 | PK |
| | V | 4825.0 | 57.5 | -11.9 | 45.6 | 54(Note) | -8.4 | PK |
| | V | 7236.0 | 48.4 | -3.3 | 45.1 | 54(Note) | -8.9 | PK |
| | H | 24000.0 | 59.1 | -8.9 | 50.2 | 54(Note) | -3.8 | PK |
| 6 | V | 2438.5 | 68.4 | 31.2 | 99.6 | Fundamental | / | PK |
| | H | 225.9 | -0.2 | 10.3 | 10.1 | 46 | -35.9 | QP |
| | H | 451.5 | -0.2 | 17.3 | 17.1 | 46 | -28.9 | PK |
| | H | 3280.0 | 34.4 | 0.0 | 34.4 | 54(Note) | -19.6 | PK |
| | V | 4876.0 | 57.8 | -11.7 | 46.1 | 54(Note) | -7.9 | PK |
| | V | 7311.0 | 48.7 | -3.0 | 45.7 | 54(Note) | -8.3 | PK |
| | H | 24000.0 | 59.1 | -8.9 | 50.2 | 54(Note) | -3.8 | PK |
| 11 | V | 2462.2 | 66.6 | 31.2 | 97.8 | Fundamental | / | PK |
| | V | 225.9 | 0.4 | 10.3 | 10.7 | 46 | -35.3 | PK |
| | V | 542.0 | -0.4 | 19.4 | 19.0 | 46 | -27.0 | PK |
| | H | 3184.5 | 35.4 | 0.0 | 35.4 | 54(Note) | -18.6 | PK |
| | H | 4927.0 | 56.3 | -11.5 | 44.8 | 54(Note) | -9.2 | PK |
| | V | 7386.0 | 48.4 | -2.8 | 45.6 | 54(Note) | -8.4 | PK |
| | V | 24000.0 | 59.1 | -8.9 | 50.2 | 54(Note) | -3.8 | PK |

Note : This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.

Mode 2: Transmit by 802.11g

| CH | Antenna | Frequency (MHz) | Reading Level (dBuV/m) | Factor (dB) | Measure Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|----|---------|-----------------|------------------------|-------------|------------------------|----------------|-------------|----------|
| 1 | H | 2409.6 | 66.3 | 31.2 | 97.5 | Fundamental | / | PK |
| | H | 451.5 | -0.6 | 17.3 | 16.7 | 46 | -29.3 | PK |
| | V | 542.0 | 0.0 | 19.4 | 19.4 | 46 | -26.6 | PK |
| | H | 3125.0 | 35.2 | 0.0 | 35.2 | 54(Note) | -18.8 | PK |
| | V | 4824.0 | 52.2 | -11.9 | 40.3 | 54(Note) | -13.7 | PK |
| | H | 7236.0 | 47.7 | -3.3 | 44.4 | 54(Note) | -9.6 | PK |
| | H | 24000.0 | 59.1 | -8.9 | 50.2 | 54(Note) | -3.8 | PK |
| 6 | H | 2438.5 | 64.8 | 31.2 | 96.0 | Fundamental | / | PK |
| | V | 158.0 | 0.6 | 10.0 | 10.6 | 43.5 | -32.9 | PK |
| | V | 451.5 | 0.0 | 17.3 | 17.3 | 46 | -28.7 | PK |
| | V | 3280.0 | 34.2 | 0.0 | 34.2 | 54(Note) | -19.8 | PK |
| | V | 4874.0 | 52.9 | -11.7 | 41.2 | 54(Note) | -12.8 | PK |
| | H | 7311.0 | 47.2 | -3.0 | 44.2 | 54(Note) | -9.8 | PK |
| | H | 24000.0 | 59.1 | -8.9 | 50.2 | 54(Note) | -3.8 | PK |
| 11 | V | 2462.4 | 63.1 | 31.2 | 94.3 | Fundamental | / | PK |
| | V | 542.0 | -0.7 | 19.4 | 18.7 | 46 | -27.3 | PK |
| | H | 542.0 | 0.0 | 19.4 | 19.4 | 46 | -26.6 | PK |
| | V | 3184.5 | 34.8 | 0.0 | 34.8 | 54(Note) | -19.2 | PK |
| | V | 4927.0 | 54.9 | -11.5 | 43.4 | 54(Note) | -10.6 | PK |
| | V | 7386.0 | 48.3 | -2.8 | 45.5 | 54(Note) | -8.5 | PK |
| | H | 24000.0 | 59.1 | -8.9 | 50.2 | 54(Note) | -3.8 | PK |

Note : This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.

Mode 3: Transmit by 802.11n(20MHz)

| CH | Antenna | Frequency (MHz) | Reading Level (dBuV/m) | Factor (dB) | Measure Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|----|---------|-----------------|------------------------|-------------|------------------------|----------------|-------------|----------|
| 1 | H | 2408.8 | 65.5 | 31.2 | 96.7 | Fundamental | / | PK |
| | V | 298.4 | -0.8 | 13.5 | 12.7 | 46 | -33.3 | PK |
| | V | 542.0 | -1.2 | 19.4 | 18.2 | 46 | -27.8 | PK |
| | V | 3125.0 | 51.7 | -15.7 | 36.0 | 54(Note) | -18.0 | PK |
| | H | 4824.0 | 52.0 | -11.9 | 40.1 | 54(Note) | -13.9 | PK |
| | H | 7236.0 | 47.8 | -3.3 | 44.5 | 54(Note) | -9.5 | PK |
| | H | 24000.0 | 59.1 | -8.9 | 50.2 | 54(Note) | -3.8 | PK |
| 6 | H | 2438.5 | 63.7 | 31.2 | 94.9 | Fundamental | / | PK |
| | H | 225.9 | -0.6 | 10.3 | 9.7 | 46 | -36.3 | PK |
| | V | 542.0 | -0.3 | 19.4 | 19.1 | 46 | -26.9 | PK |
| | V | 3280.0 | 50.8 | -16.2 | 34.6 | 54(Note) | -19.4 | PK |
| | V | 4874.0 | 53.1 | -11.7 | 41.4 | 54(Note) | -12.6 | PK |
| | V | 7311.0 | 48.3 | -3.0 | 45.3 | 54(Note) | -8.7 | PK |
| | H | 24000.0 | 59.1 | -8.9 | 50.2 | 54(Note) | -3.8 | PK |
| 11 | V | 2461.5 | 62.7 | 31.2 | 93.9 | Fundamental | / | PK |
| | H | 298.4 | -0.8 | 13.5 | 12.7 | 46 | -33.3 | PK |
| | V | 542.0 | -0.3 | 19.4 | 19.1 | 46 | -26.9 | PK |
| | V | 3184.5 | 51.4 | -15.9 | 35.5 | 54(Note) | -18.5 | PK |
| | V | 4927.0 | 54.0 | -11.5 | 42.5 | 54(Note) | -11.5 | PK |
| | V | 7386.0 | 48.3 | -2.8 | 45.5 | 54(Note) | -8.5 | PK |
| | H | 24000.0 | 59.1 | -8.9 | 50.2 | 54(Note) | -3.8 | PK |

Note : This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.

Mode 4: Transmit by 802.11n(40MHz)

| CH | Antenna | Frequency (MHz) | Reading Level (dBuV/m) | Factor (dB) | Measure Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|----|---------|-----------------|------------------------|-------------|------------------------|----------------|-------------|----------|
| 3 | H | 2412.8 | 59.7 | 31.2 | 90.9 | Fundamental | / | PK |
| | H | 225.9 | -0.2 | 10.3 | 10.1 | 46 | -35.9 | PK |
| | H | 451.5 | -1.1 | 17.3 | 16.2 | 46 | -29.8 | PK |
| | V | 3184.5 | 51.5 | -15.9 | 35.6 | 54(Note) | -18.4 | PK |
| | V | 4844.0 | 51.6 | -11.8 | 39.8 | 54(Note) | -14.2 | PK |
| | H | 7266.0 | 46.8 | -3.2 | 43.6 | 54(Note) | -10.4 | PK |
| | H | 24000.0 | 59.1 | -8.9 | 50.2 | 54(Note) | -3.8 | PK |
| 6 | H | 2438.5 | 59.2 | 31.2 | 90.4 | Fundamental | / | PK |
| | V | 225.9 | -0.3 | 10.3 | 10.0 | 46 | -36.0 | PK |
| | V | 451.5 | -1.1 | 17.3 | 16.2 | 46 | -29.8 | PK |
| | H | 3125.0 | 50.6 | -15.7 | 34.9 | 54(Note) | -19.1 | PK |
| | V | 4874.0 | 51.4 | -11.7 | 39.7 | 54(Note) | -14.3 | PK |
| | H | 7311.0 | 47.5 | -3.0 | 44.5 | 54(Note) | -9.5 | PK |
| | H | 24000.0 | 59.1 | -8.9 | 50.2 | 54(Note) | -3.8 | PK |
| 9 | V | 2459.1 | 58.8 | 31.2 | 90.0 | Fundamental | / | PK |
| | H | 542.0 | -1.2 | 19.4 | 18.2 | 46 | -27.8 | PK |
| | V | 225.9 | -1.2 | 10.3 | 9.1 | 46 | -36.9 | PK |
| | H | 3280.0 | 51.0 | -16.2 | 34.8 | 54(Note) | -19.2 | PK |
| | V | 4904.0 | 51.1 | -11.6 | 39.5 | 54(Note) | -14.5 | PK |
| | H | 7356.0 | 47.3 | -2.8 | 44.5 | 54(Note) | -9.5 | PK |
| | H | 24000.0 | 59.1 | -8.9 | 50.2 | 54(Note) | -3.8 | PK |

Note : This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.

5. RF Antenna Conducted Spurious


5.1. Test Equipment

RF Antenna Conducted Spurious / TR-8

| Instrument | Manufacturer | Type No. | Serial No. | Cali. Due Date |
|----------------------------|--------------|----------|------------|----------------|
| Spectrum Analyzer | Agilent | E4446A | MY45300103 | 2013.04.18 |
| Temperature/Humidity Meter | zhicheng | ZC1-2 | TR8-TH | 2013.05.07 |

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

5.2. Test Setup



5.3. Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.4. Test Procedure

The EUT was tested according to KDB 558074 for compliance to FCC 47CFR 15.247 requirements.

Set RBW = 100 kHz, Set VBW > RBW, scan up through 10th harmonic.


5.5. Uncertainty

The measurement uncertainty is defined as ± 1.27 dB


5.6. Test Result

| | | |
|-----------|---|-------------------------------|
| Product | : | GSM Mobile Phone |
| Test Item | : | RF Antenna Conducted Spurious |
| Test Site | : | TR-8 |
| Test Mode | : | Mode 1: Transmit by 802.11b |


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




| | |
|-----------|---------------------------------|
| Product | : GSM Mobile Phone |
| Test Item | : RF Antenna Conducted Spurious |
| Test Site | : TR-8 |
| Test Mode | : Mode 2: Transmit by 802.11g |


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




| | |
|-----------|--------------------------------------|
| Product | : GSM Mobile Phone |
| Test Item | : RF Antenna Conducted Spurious |
| Test Site | : TR-8 |
| Test Mode | : Mode 3: Transmit by 802.11n(20MHz) |


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




| | |
|-----------|--------------------------------------|
| Product | : GSM Mobile Phone |
| Test Item | : RF Antenna Conducted Spurious |
| Test Site | : TR-8 |
| Test Mode | : Mode 4: Transmit by 802.11n(40MHz) |


Channel 03 (2422MHz)



Channel 06 (2437MHz)



Channel 09 (2452MHz)



6. Radiated Emission Band Edge

6.1. Test Equipment


Radiated Emission Band Edge / AC-5

| Instrument | Manufacturer | Type No. | Serial No. | Cal. Due Date |
|----------------------------|--------------|------------|-------------|---------------|
| Spectrum Analyzer | Agilent | N9010A | MY48030494 | 2013.04.18 |
| EMI Test Receiver | R&S | ESCI | 100573 | 2013.04.18 |
| Preamplifier | Miteq | NSP1800-25 | 1364185 | 2013.05.04 |
| Preamplifier | Quietek | AP-040G | CHM-0906001 | 2013.05.04 |
| Bilog Antenna | Teseq GmbH | CBL6112D | 27612 | 2012.10.18 |
| Broad-Band Horn Antenna | Schwarzbeck | BBHA9120D | 499 | 2013.06.11 |
| 50ohm Coaxial Switch | Anritsu | MP59B | 6200464462 | 2013.03.02 |
| Temperature/Humidity Meter | zhicheng | ZC1-2 | AC5-TH | 2013.01.10 |

Note 1: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

Note 2: The test instruments marked with "X" are used to measure the final test results.

6.2. Test Setup



6.3. Limit

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a) of FCC part 15, must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

6.4. Test Procedure

The EUT was setup according to ANSI C63.4: 2009 and tested according to ANSI C63.10: 2009 for compliance to FCC 47CFR 15.247 requirements.

The EUT is placed on a turn table which is 0.8 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.4: 2009 on radiated measurement.

6.5. Uncertainty


The measurement uncertainty above 1G is defined as ± 3.9 dB

6.6. Test Result

Peak detector: RBW = 1MHz, VBW = 3MHz, sweep time = 200ms;


Average detector: RBW = 1MHz, VBW = 10Hz, sweep time = auto.

| | |
|--|--------------------------|
| Engineer: Nancy | |
| Site: AC5 | Time: 2012/06/01 - 09:41 |
| Limit: FCC_Part15.209_RE(3m) | Margin: 0 |
| Probe: BBHA 9120D_499(1-18GHz) | Polarity: Horizontal |
| EUT: GSM Mobile Phone | Power: By Battery |
| Note: Mode 1: Transmit at channel 2412MHz by 802.11b | |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|--------|------|
| 1 | | | 2390.000 | 61.341 | 30.156 | -12.659 | 74.000 | 31.185 | PK |
| 2 | | * | 2411.365 | 96.248 | 65.072 | N/A | N/A | 31.176 | PK |

| | |
|--|--------------------------|
| Engineer: Nancy | |
| Site: AC5 | Time: 2012/06/01 - 09:46 |
| Limit: FCC_Part15.209_RE(3m) | Margin: 0 |
| Probe: BBHA 9120D_499(1-18GHz) | Polarity: Horizontal |
| EUT: GSM Mobile Phone | Power: By Battery |
| Note: Mode 1: Transmit at channel 2412MHz by 802.11b | |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|--------|------|
| 1 | | | 2390.000 | 48.009 | 16.824 | -5.991 | 54.000 | 31.185 | AV |
| 2 | | * | 2411.585 | 86.330 | 55.154 | N/A | N/A | 31.177 | AV |

| | |
|--|--------------------------|
| Engineer: Nancy | |
| Site: AC5 | Time: 2012/06/01 - 09:52 |
| Limit: FCC_Part15.209_RE(3m) | Margin: 0 |
| Probe: BBHA 9120D_499(1-18GHz) | Polarity: Vertical |
| EUT: GSM Mobile Phone | Power: By Battery |
| Note: Mode 1: Transmit at channel 2412MHz by 802.11b | |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|--------|------|
| 1 | | | 2390.000 | 61.451 | 30.266 | -12.549 | 74.000 | 31.185 | PK |
| 2 | | * | 2413.235 | 100.396 | 69.219 | N/A | N/A | 31.177 | PK |

| | |
|--|--------------------------|
| Engineer: Nancy | |
| Site: AC5 | Time: 2012/06/01 - 09:55 |
| Limit: FCC_Part15.209_RE(3m) | Margin: 0 |
| Probe: BBHA 9120D_499(1-18GHz) | Polarity: Vertical |
| EUT: GSM Mobile Phone | Power: By Battery |
| Note: Mode 1: Transmit at channel 2412MHz by 802.11b | |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|--------|------|
| 1 | | | 2390.000 | 48.021 | 16.836 | -5.979 | 54.000 | 31.185 | AV |
| 2 | | * | 2411.585 | 90.176 | 59.000 | N/A | N/A | 31.177 | AV |

| | |
|--|--------------------------|
| Engineer: Nancy | |
| Site: AC5 | Time: 2012/06/01 - 09:59 |
| Limit: FCC_Part15.209_RE(3m) | Margin: 0 |
| Probe: BBHA 9120D_499(1-18GHz) | Polarity: Horizontal |
| EUT: GSM Mobile Phone | Power: By Battery |
| Note: Mode 1: Transmit at channel 2462MHz by 802.11b | |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|--------|------|
| 1 | | * | 2461.825 | 94.390 | 63.192 | N/A | N/A | 31.198 | PK |
| 2 | | | 2483.500 | 61.269 | 30.061 | -12.731 | 74.000 | 31.208 | PK |

| | |
|--|--------------------------|
| Engineer: Nancy | |
| Site: AC5 | Time: 2012/06/01 - 10:02 |
| Limit: FCC_Part15.209_RE(3m) | Margin: 0 |
| Probe: BBHA 9120D_499(1-18GHz) | Polarity: Horizontal |
| EUT: GSM Mobile Phone | Power: By Battery |
| Note: Mode 1: Transmit at channel 2462MHz by 802.11b | |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|--------|------|
| 1 | | * | 2462.025 | 85.088 | 53.890 | N/A | N/A | 31.198 | AV |
| 2 | | | 2483.500 | 48.124 | 16.916 | -5.876 | 54.000 | 31.208 | AV |

| | |
|--|--------------------------|
| Engineer: Nancy | |
| Site: AC5 | Time: 2012/06/01 - 10:03 |
| Limit: FCC_Part15.209_RE(3m) | Margin: 0 |
| Probe: BBHA 9120D_499(1-18GHz) | Polarity: Vertical |
| EUT: GSM Mobile Phone | Power: By Battery |
| Note: Mode 1: Transmit at channel 2462MHz by 802.11b | |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|--------|------|
| 1 | | * | 2462.225 | 97.807 | 66.609 | N/A | N/A | 31.198 | PK |
| 2 | | | 2483.500 | 61.019 | 29.811 | -12.981 | 74.000 | 31.208 | PK |

| | |
|--|--------------------------|
| Engineer: Nancy | |
| Site: AC5 | Time: 2012/06/01 - 10:06 |
| Limit: FCC_Part15.209_RE(3m) | Margin: 0 |
| Probe: BBHA 9120D_499(1-18GHz) | Polarity: Vertical |
| EUT: GSM Mobile Phone | Power: By Battery |
| Note: Mode 1: Transmit at channel 2462MHz by 802.11b | |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|--------|------|
| 1 | | * | 2462.100 | 88.872 | 57.674 | N/A | N/A | 31.198 | AV |
| 2 | | | 2483.500 | 48.224 | 17.016 | -5.776 | 54.000 | 31.208 | AV |

| | |
|--|--------------------------|
| Engineer: Nancy | |
| Site: AC5 | Time: 2012/06/01 - 10:07 |
| Limit: FCC_Part15.209_RE(3m) | Margin: 0 |
| Probe: BBHA 9120D_499(1-18GHz) | Polarity: Horizontal |
| EUT: GSM Mobile Phone | Power: By Battery |
| Note: Mode 2: Transmit at channel 2412MHz by 802.11g | |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|--------|------|
| 1 | | | 2390.000 | 63.210 | 32.025 | -10.790 | 74.000 | 31.185 | PK |
| 2 | | * | 2408.120 | 92.611 | 61.434 | N/A | N/A | 31.177 | PK |

| | |
|--|--------------------------|
| Engineer: Nancy | |
| Site: AC5 | Time: 2012/06/01 - 10:17 |
| Limit: FCC_Part15.209_RE(3m) | Margin: 0 |
| Probe: BBHA 9120D_499(1-18GHz) | Polarity: Horizontal |
| EUT: GSM Mobile Phone | Power: By Battery |
| Note: Mode 2: Transmit at channel 2412MHz by 802.11g | |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|--------|------|
| 1 | | | 2390.000 | 48.489 | 17.304 | -5.511 | 54.000 | 31.185 | AV |
| 2 | | * | 2409.385 | 81.044 | 49.867 | N/A | N/A | 31.176 | AV |

| | |
|--|--------------------------|
| Engineer: Nancy | |
| Site: AC5 | Time: 2012/06/01 - 10:21 |
| Limit: FCC_Part15.209_RE(3m) | Margin: 0 |
| Probe: BBHA 9120D_499(1-18GHz) | Polarity: Vertical |
| EUT: GSM Mobile Phone | Power: By Battery |
| Note: Mode 2: Transmit at channel 2412MHz by 802.11g | |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|--------|------|
| 1 | | | 2390.000 | 65.493 | 34.308 | -8.507 | 74.000 | 31.185 | PK |
| 2 | | * | 2409.605 | 97.497 | 66.320 | N/A | N/A | 31.176 | PK |

| | |
|--|--------------------------|
| Engineer: Nancy | |
| Site: AC5 | Time: 2012/06/01 - 10:23 |
| Limit: FCC_Part15.209_RE(3m) | Margin: 0 |
| Probe: BBHA 9120D_499(1-18GHz) | Polarity: Vertical |
| EUT: GSM Mobile Phone | Power: By Battery |
| Note: Mode 2: Transmit at channel 2412MHz by 802.11g | |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|--------|------|
| 1 | | | 2390.000 | 49.205 | 18.020 | -4.795 | 54.000 | 31.185 | AV |
| 2 | | * | 2406.580 | 85.172 | 53.994 | N/A | N/A | 31.178 | AV |

| | |
|--|--------------------------|
| Engineer: Nancy | |
| Site: AC5 | Time: 2012/06/01 - 10:28 |
| Limit: FCC_Part15.209_RE(3m) | Margin: 0 |
| Probe: BBHA 9120D_499(1-18GHz) | Polarity: Horizontal |
| EUT: GSM Mobile Phone | Power: By Battery |
| Note: Mode 2: Transmit at channel 2462MHz by 802.11g | |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|--------|------|
| 1 | | * | 2462.575 | 89.623 | 58.425 | N/A | N/A | 31.198 | PK |
| 2 | | | 2483.500 | 62.929 | 31.721 | -11.071 | 74.000 | 31.208 | PK |

| | |
|--|--------------------------|
| Engineer: Nancy | |
| Site: AC5 | Time: 2012/06/01 - 10:33 |
| Limit: FCC_Part15.209_RE(3m) | Margin: 0 |
| Probe: BBHA 9120D_499(1-18GHz) | Polarity: Horizontal |
| EUT: GSM Mobile Phone | Power: By Battery |
| Note: Mode 2: Transmit at channel 2462MHz by 802.11g | |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|--------|------|
| 1 | | * | 2461.175 | 79.093 | 47.896 | N/A | N/A | 31.197 | AV |
| 2 | | | 2483.500 | 48.710 | 17.502 | -5.290 | 54.000 | 31.208 | AV |

| | |
|--|--------------------------|
| Engineer: Nancy | |
| Site: AC5 | Time: 2012/06/01 - 10:36 |
| Limit: FCC_Part15.209_RE(3m) | Margin: 0 |
| Probe: BBHA 9120D_499(1-18GHz) | Polarity: Vertical |
| EUT: GSM Mobile Phone | Power: By Battery |
| Note: Mode 2: Transmit at channel 2462MHz by 802.11g | |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|--------|------|
| 1 | | * | 2462.425 | 94.249 | 63.051 | N/A | N/A | 31.198 | PK |
| 2 | | | 2483.500 | 64.849 | 33.641 | -9.151 | 74.000 | 31.208 | PK |

| | |
|--|--------------------------|
| Engineer: Nancy | |
| Site: AC5 | Time: 2012/06/01 - 10:40 |
| Limit: FCC_Part15.209_RE(3m) | Margin: 0 |
| Probe: BBHA 9120D_499(1-18GHz) | Polarity: Vertical |
| EUT: GSM Mobile Phone | Power: By Battery |
| Note: Mode 2: Transmit at channel 2462MHz by 802.11g | |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|--------|------|
| 1 | | * | 2461.025 | 83.496 | 52.299 | N/A | N/A | 31.197 | AV |
| 2 | | | 2483.500 | 49.897 | 18.689 | -4.103 | 54.000 | 31.208 | AV |

| | |
|---|--------------------------|
| Engineer: Nancy | |
| Site: AC5 | Time: 2012/06/01 - 10:41 |
| Limit: FCC_Part15.209_RE(3m) | Margin: 0 |
| Probe: BBHA 9120D_499(1-18GHz) | Polarity: Horizontal |
| EUT: GSM Mobile Phone | Power: By Battery |
| Note: Mode 3: Transmit at channel 2412MHz by 802.11n(20MHz) | |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|--------|------|
| 1 | | | 2390.000 | 62.883 | 31.698 | -11.117 | 74.000 | 31.185 | PK |
| 2 | | * | 2407.405 | 92.762 | 61.585 | N/A | N/A | 31.178 | PK |

| | |
|---|--------------------------|
| Engineer: Nancy | |
| Site: AC5 | Time: 2012/06/01 - 10:44 |
| Limit: FCC_Part15.209_RE(3m) | Margin: 0 |
| Probe: BBHA 9120D_499(1-18GHz) | Polarity: Horizontal |
| EUT: GSM Mobile Phone | Power: By Battery |
| Note: Mode 3: Transmit at channel 2412MHz by 802.11n(20MHz) | |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|--------|------|
| 1 | | | 2390.000 | 48.579 | 17.394 | -5.421 | 54.000 | 31.185 | AV |
| 2 | | * | 2405.205 | 80.489 | 49.311 | N/A | N/A | 31.179 | AV |

| | |
|---|--------------------------|
| Engineer: Nancy | |
| Site: AC5 | Time: 2012/06/01 - 10:46 |
| Limit: FCC_Part15.209_RE(3m) | Margin: 0 |
| Probe: BBHA 9120D_499(1-18GHz) | Polarity: Vertical |
| EUT: GSM Mobile Phone | Power: By Battery |
| Note: Mode 3: Transmit at channel 2412MHz by 802.11n(20MHz) | |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|--------|------|
| 1 | | | 2390.000 | 62.841 | 31.656 | -11.159 | 74.000 | 31.185 | PK |
| 2 | | * | 2408.835 | 96.701 | 65.524 | N/A | N/A | 31.177 | PK |

| | |
|---|--------------------------|
| Engineer: Nancy | |
| Site: AC5 | Time: 2012/06/01 - 10:50 |
| Limit: FCC_Part15.209_RE(3m) | Margin: 0 |
| Probe: BBHA 9120D_499(1-18GHz) | Polarity: Vertical |
| EUT: GSM Mobile Phone | Power: By Battery |
| Note: Mode 3: Transmit at channel 2412MHz by 802.11n(20MHz) | |



| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|--------|------|
| 1 | | | 2390.000 | 49.558 | 18.373 | -4.442 | 54.000 | 31.185 | AV |
| 2 | | * | 2407.955 | 83.646 | 52.469 | N/A | N/A | 31.178 | AV |

| | |
|---|--------------------------|
| Engineer: Nancy | |
| Site: AC5 | Time: 2012/06/01 - 10:52 |
| Limit: FCC_Part15.209_RE(3m) | Margin: 0 |
| Probe: BBHA 9120D_499(1-18GHz) | Polarity: Horizontal |
| EUT: GSM Mobile Phone | Power: By Battery |
| Note: Mode 3: Transmit at channel 2462MHz by 802.11n(20MHz) | |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|--------|------|
| 1 | | * | 2461.525 | 89.461 | 58.263 | N/A | N/A | 31.197 | PK |
| 2 | | | 2483.500 | 61.534 | 30.326 | -12.466 | 74.000 | 31.208 | PK |

| | |
|---|--------------------------|
| Engineer: Nancy | |
| Site: AC5 | Time: 2012/06/01 - 10:55 |
| Limit: FCC_Part15.209_RE(3m) | Margin: 0 |
| Probe: BBHA 9120D_499(1-18GHz) | Polarity: Horizontal |
| EUT: GSM Mobile Phone | Power: By Battery |
| Note: Mode 3: Transmit at channel 2462MHz by 802.11n(20MHz) | |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|--------|------|
| 1 | | * | 2460.625 | 76.146 | 44.949 | N/A | N/A | 31.198 | AV |
| 2 | | | 2483.500 | 48.548 | 17.340 | -5.452 | 54.000 | 31.208 | AV |

| | |
|---|--------------------------|
| Engineer: Nancy | |
| Site: AC5 | Time: 2012/06/01 - 10:55 |
| Limit: FCC_Part15.209_RE(3m) | Margin: 0 |
| Probe: BBHA 9120D_499(1-18GHz) | Polarity: Vertical |
| EUT: GSM Mobile Phone | Power: By Battery |
| Note: Mode 3: Transmit at channel 2462MHz by 802.11n(20MHz) | |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|--------|------|
| 1 | | * | 2461.475 | 93.852 | 62.654 | N/A | N/A | 31.197 | PK |
| 2 | | | 2483.500 | 64.683 | 33.475 | -9.317 | 74.000 | 31.208 | PK |

| | |
|---|--------------------------|
| Engineer: Nancy | |
| Site: AC5 | Time: 2012/06/01 - 10:58 |
| Limit: FCC_Part15.209_RE(3m) | Margin: 0 |
| Probe: BBHA 9120D_499(1-18GHz) | Polarity: Vertical |
| EUT: GSM Mobile Phone | Power: By Battery |
| Note: Mode 3: Transmit at channel 2462MHz by 802.11n(20MHz) | |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|--------|------|
| 1 | | * | 2461.100 | 81.681 | 50.484 | N/A | N/A | 31.197 | AV |
| 2 | | | 2483.500 | 49.157 | 17.949 | -4.843 | 54.000 | 31.208 | AV |

| | |
|---|--------------------------|
| Engineer: Nancy | |
| Site: AC5 | Time: 2012/06/01 - 10:59 |
| Limit: FCC_Part15.209_RE(3m) | Margin: 0 |
| Probe: BBHA 9120D_499(1-18GHz) | Polarity: Horizontal |
| EUT: GSM Mobile Phone | Power: By Battery |
| Note: Mode 4: Transmit at channel 2422MHz by 802.11n(40MHz) | |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|--------|------|
| 1 | | | 2390.000 | 62.239 | 31.054 | -11.761 | 74.000 | 31.185 | PK |
| 2 | | * | 2412.960 | 87.319 | 56.142 | N/A | N/A | 31.177 | PK |

| | |
|---|--------------------------|
| Engineer: Nancy | |
| Site: AC5 | Time: 2012/06/01 - 11:03 |
| Limit: FCC_Part15.209_RE(3m) | Margin: 0 |
| Probe: BBHA 9120D_499(1-18GHz) | Polarity: Horizontal |
| EUT: GSM Mobile Phone | Power: By Battery |
| Note: Mode 4: Transmit at channel 2422MHz by 802.11n(40MHz) | |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|--------|------|
| 1 | | | 2390.000 | 48.642 | 17.457 | -5.358 | 54.000 | 31.185 | AV |
| 2 | | * | 2411.970 | 75.646 | 44.469 | N/A | N/A | 31.177 | AV |

| | |
|---|--------------------------|
| Engineer: Nancy | |
| Site: AC5 | Time: 2012/06/01 - 11:04 |
| Limit: FCC_Part15.209_RE(3m) | Margin: 0 |
| Probe: BBHA 9120D_499(1-18GHz) | Polarity: Vertical |
| EUT: GSM Mobile Phone | Power: By Battery |
| Note: Mode 4: Transmit at channel 2422MHz by 802.11n(40MHz) | |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|--------|------|
| 1 | | | 2390.000 | 61.866 | 30.681 | -12.134 | 74.000 | 31.185 | PK |
| 2 | | * | 2412.762 | 90.916 | 59.739 | N/A | N/A | 31.177 | PK |

| | |
|---|--------------------------|
| Engineer: Nancy | |
| Site: AC5 | Time: 2012/06/01 - 11:07 |
| Limit: FCC_Part15.209_RE(3m) | Margin: 0 |
| Probe: BBHA 9120D_499(1-18GHz) | Polarity: Vertical |
| EUT: GSM Mobile Phone | Power: By Battery |
| Note: Mode 4: Transmit at channel 2422MHz by 802.11n(40MHz) | |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|--------|------|
| 1 | | | 2390.000 | 48.793 | 17.608 | -5.207 | 54.000 | 31.185 | AV |
| 2 | | * | 2411.772 | 79.597 | 48.421 | N/A | N/A | 31.177 | AV |

| | |
|---|--------------------------|
| Engineer: Nancy | |
| Site: AC5 | Time: 2012/06/01 - 11:08 |
| Limit: FCC_Part15.209_RE(3m) | Margin: 0 |
| Probe: BBHA 9120D_499(1-18GHz) | Polarity: Horizontal |
| EUT: GSM Mobile Phone | Power: By Battery |
| Note: Mode 4: Transmit at channel 2452MHz by 802.11n(40MHz) | |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|--------|------|
| 1 | | * | 2448.830 | 84.141 | 52.952 | N/A | N/A | 31.189 | PK |
| 2 | | | 2483.500 | 61.934 | 30.726 | -12.066 | 74.000 | 31.208 | PK |

| | |
|---|--------------------------|
| Engineer: Nancy | |
| Site: AC5 | Time: 2012/06/01 - 11:12 |
| Limit: FCC_Part15.209_RE(3m) | Margin: 0 |
| Probe: BBHA 9120D_499(1-18GHz) | Polarity: Horizontal |
| EUT: GSM Mobile Phone | Power: By Battery |
| Note: Mode 4: Transmit at channel 2452MHz by 802.11n(40MHz) | |




| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|--------|------|
| 1 | | * | 2459.030 | 73.367 | 42.171 | N/A | N/A | 31.196 | AV |
| 2 | | | 2483.500 | 48.284 | 17.076 | -5.716 | 54.000 | 31.208 | AV |

| | |
|---|--------------------------|
| Engineer: Nancy | |
| Site: AC5 | Time: 2012/06/01 - 11:13 |
| Limit: FCC_Part15.209_RE(3m) | Margin: 0 |
| Probe: BBHA 9120D_499(1-18GHz) | Polarity: Vertical |
| EUT: GSM Mobile Phone | Power: By Battery |
| Note: Mode 4: Transmit at channel 2452MHz by 802.11n(40MHz) | |



| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|--------|------|
| 1 | | * | 2459.132 | 90.020 | 58.824 | N/A | N/A | 31.196 | PK |
| 2 | | | 2483.500 | 60.918 | 29.710 | -13.082 | 74.000 | 31.208 | PK |

| | |
|---|--------------------------|
| Engineer: Nancy | |
| Site: AC5 | Time: 2012/06/01 - 11:15 |
| Limit: FCC_Part15.209_RE(3m) | Margin: 0 |
| Probe: BBHA 9120D_499(1-18GHz) | Polarity: Vertical |
| EUT: GSM Mobile Phone | Power: By Battery |
| Note: Mode 4: Transmit at channel 2452MHz by 802.11n(40MHz) | |



| No | Flag | Mark | Frequency (MHz) | Measure Level (dBuV/m) | Reading Level (dBuV) | Over Limit (dB) | Limit (dBuV/m) | Factor | Type |
|----|------|------|-----------------|------------------------|----------------------|-----------------|----------------|--------|------|
| 1 | | * | 2449.102 | 77.300 | 46.110 | N/A | N/A | 31.189 | AV |
| 2 | | | 2483.500 | 48.515 | 17.307 | -5.485 | 54.000 | 31.208 | AV |

7. Operation Frequency Range of 20dB Bandwidth


7.1. Test Equipment

Operation Frequency Range of 20dB Bandwidth / TR-8

| Instrument | Manufacturer | Type No. | Serial No. | Cali. Due Date |
|----------------------------|--------------|----------|------------|----------------|
| Spectrum Analyzer | Agilent | E4446A | MY45300103 | 2013.04.18 |
| Temperature/Humidity Meter | zhicheng | ZC1-2 | TR8-TH | 2013.05.07 |

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

7.2. Test Setup



7.3. Limit

20 dB bandwidth of the emission is contained within the operation frequency band.

7.4. Test Procedure

The EUT was tested according to KDB 558074 for compliance to FCC 47CFR 15.247 requirements.

Set RBW = 100 kHz, Span greater than RBW.


7.5. Uncertainty

The measurement uncertainty is defined as ± 1 kHz


7.6. Test Result

| | | |
|-----------|---|---|
| Product | : | GSM Mobile Phone |
| Test Item | : | Operation Frequency Range of 20dB Bandwidth |
| Test Site | : | TR-8 |
| Test Mode | : | Mode 1: Transmit by 802.11b |

Channel 01 (2412MHz)




Channel 11 (2462MHz)




| | |
|-----------|---|
| Product | : GSM Mobile Phone |
| Test Item | : Operation Frequency Range of 20dB Bandwidth |
| Test Site | : TR-8 |
| Test Mode | : Mode 2: Transmit by 802.11g |

Channel 01 (2412MHz)




Channel 11 (2462MHz)




| | |
|-----------|---|
| Product | : GSM Mobile Phone |
| Test Item | : Operation Frequency Range of 20dB Bandwidth |
| Test Site | : TR-8 |
| Test Mode | : Mode 3: Transmit by 802.11n(20MHz) |

Channel 01 (2412MHz)




Channel 11 (2462MHz)




| | |
|-----------|---|
| Product | : GSM Mobile Phone |
| Test Item | : Operation Frequency Range of 20dB Bandwidth |
| Test Site | : TR-8 |
| Test Mode | : Mode 4: Transmit by 802.11n(40MHz) |

Channel 03 (2422MHz)



Channel 09 (2452MHz)



8. Occupied Bandwidth


8.1. Test Equipment

Occupied Bandwidth / TR-8

| Instrument | Manufacturer | Type No. | Serial No. | Cali. Due Date |
|----------------------------|--------------|----------|------------|----------------|
| Spectrum Analyzer | Agilent | E4446A | MY45300103 | 2013.04.18 |
| Temperature/Humidity Meter | zhicheng | ZC1-2 | TR8-TH | 2013.05.07 |

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

8.2. Test Setup



8.3. Limit

The minimum 6 dB bandwidth shall be at least 500 kHz.

8.4. Test Procedure

The EUT was tested according to KDB 558074 for compliance to FCC 47CFR 15.247 requirements.

Set RBW = 100 kHz, Span greater than RBW.

8.5. Uncertainty


The measurement uncertainty is defined as ± 1 kHz

8.6. Test Result


| | | |
|-----------|---|-----------------------------|
| Product | : | GSM Mobile Phone |
| Test Item | : | 6dB Occupied Bandwidth |
| Test Site | : | TR-8 |
| Test Mode | : | Mode 1: Transmit by 802.11b |

| Channel No. | Frequency (MHz) | Occupied Bandwidth (kHz) | Limit (kHz) | Result |
|-------------|-----------------|--------------------------|-------------|--------|
| 01 | 2412 | 9450 | 500 | Pass |
| 06 | 2437 | 9180 | 500 | Pass |
| 11 | 2462 | 9150 | 500 | Pass |


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




| | |
|-----------|-------------------------------|
| Product | : GSM Mobile Phone |
| Test Item | : 6dB Occupied Bandwidth |
| Test Site | : TR-8 |
| Test Mode | : Mode 2: Transmit by 802.11g |

| Channel No. | Frequency (MHz) | Occupied Bandwidth (kHz) | Limit (kHz) | Result |
|-------------|-----------------|--------------------------|-------------|--------|
| 01 | 2412 | 16580 | 500 | Pass |
| 06 | 2437 | 16580 | 500 | Pass |
| 11 | 2462 | 16560 | 500 | Pass |


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




| | |
|-----------|--------------------------------------|
| Product | : GSM Mobile Phone |
| Test Item | : 6dB Occupied Bandwidth |
| Test Site | : TR-8 |
| Test Mode | : Mode 3: Transmit by 802.11n(20MHz) |

| Channel No. | Frequency (MHz) | Occupied Bandwidth (kHz) | Limit (kHz) | Result |
|-------------|-----------------|--------------------------|-------------|--------|
| 01 | 2412 | 17860 | 500 | Pass |
| 06 | 2437 | 17830 | 500 | Pass |
| 11 | 2462 | 17830 | 500 | Pass |


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




| | |
|-----------|--------------------------------------|
| Product | : GSM Mobile Phone |
| Test Item | : 6dB Occupied Bandwidth |
| Test Site | : TR-8 |
| Test Mode | : Mode 4: Transmit by 802.11n(40MHz) |

| Channel No. | Frequency (MHz) | Occupied Bandwidth (kHz) | Limit (kHz) | Result |
|-------------|-----------------|--------------------------|-------------|--------|
| 03 | 2422 | 36560 | 500 | Pass |
| 06 | 2437 | 36470 | 500 | Pass |
| 09 | 2452 | 36470 | 500 | Pass |


Channel 03 (2422MHz)



Channel 06 (2437MHz)



Channel 09 (2452MHz)



9. Power Output


9.1. Test Equipment

Power Output / TR-8

| Instrument | Manufacturer | Type No. | Serial No. | Cali. Due Date |
|----------------------------|--------------|----------|------------|----------------|
| Wideband Peak Power Meter | Anritsu | ML2495A | 0905006 | 2013.01.12 |
| Power Sensor | Anritsu | MA2411B | 0846014 | 2013.01.12 |
| Temperature/Humidity Meter | zhicheng | ZC1-2 | TR8-TH | 2013.05.07 |

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

9.2. Test Setup



9.3. Limit

The maximum peak power shall be less 1 Watt (30dBm).

Note: the conducted output power limit specified above is based on the use the antennas with directional gains that do not exceed 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values above, as appropriate, by the amount in dB that the directional gain of antenna exceeds 6 dBi.

9.4. Test Procedure

The EUT was tested according to KDB 558074 for compliance to FCC 47CFR 15.247 requirements.

Use the wideband power meter to test peak power and record the result.

9.5. Uncertainty

The measurement uncertainty is defined as ± 1.27 dB

9.6. Test Result

Power output test was verified over all data rates of each mode shown as below, and then choose the maximum power output (blue marker) for final test of each channel.

| MCS Index for 802.11n | Spatial Streams | Data Rate (Mbps) | | | | | |
|--------------------------|--------------------|------------------|---------|-----------------|----------|-----------------|----------|
| | | 802.11b | 802.11g | 20MHz Bandwidth | | 40MHz Bandwidth | |
| | | | | 800ns GI | 400ns GI | 800ns GI | 400ns GI |
| 0 | 1 | 1 | 6 | 6.5 | 7.2 | 13.5 | 15.0 |
| 1 | 1 | 2 | 9 | 13.0 | 14.4 | 27.0 | 30.0 |
| 2 | 1 | 5.5 | 12 | 19.5 | 21.7 | 40.5 | 45.0 |
| 3 | 1 | 11 | 18 | 26.0 | 28.9 | 54.0 | 60.0 |
| 4 | 1 | --- | 24 | 39.0 | 43.3 | 81.0 | 90.0 |
| 5 | 1 | --- | 36 | 52.0 | 57.8 | 108.0 | 120.0 |
| 6 | 1 | --- | 48 | 58.5 | 65.0 | 121.5 | 135.0 |
| 7 | 1 | --- | 54 | 65.0 | 72.2 | 135.0 | 150.0 |
| 8 | 2 | --- | --- | 13.0 | 14.4 | 27.0 | 30.0 |
| 9 | 2 | --- | --- | 26.0 | 28.9 | 54.0 | 60.0 |
| 10 | 2 | --- | --- | 39.0 | 43.3 | 81.0 | 90.0 |
| 11 | 2 | --- | --- | 52.0 | 57.8 | 108.0 | 120.0 |
| 12 | 2 | --- | --- | 78.0 | 86.7 | 162.0 | 180.0 |
| 13 | 2 | --- | --- | 104.0 | 115.6 | 216.0 | 240.0 |
| 14 | 2 | --- | --- | 117.0 | 130.0 | 243.0 | 270.0 |
| 15 | 2 | --- | --- | 130.0 | 144.0 | 270.0 | 300.0 |

Power output at various data rates:

| Test Mode | Bandwidth | Frequency (MHz) | Channel | Data Rate | Peak Power (dBm) |
|----------------|-----------|-----------------|---------|-----------|------------------|
| 802.11b | 20 | 2437 | 6 | 1 | 14.90 |
| | | | | 5.5 | 16.79 |
| | | | | 11 | 17.79 |
| 802.11g | 20 | 2437 | 6 | 6 | 15.63 |
| | | | | 24 | 15.98 |
| | | | | 54 | 16.16 |
| 802.11n(20MHz) | 20 | 2437 | 6 | 6.5 | 15.95 |
| | | | | 39 | 15.94 |
| | | | | 65 | 15.96 |
| 802.11n(40MHz) | 40 | 2437 | 6 | 13.5 | 14.21 |
| | | | | 81 | 14.55 |
| | | | | 135 | 14.58 |

| | | |
|-----------|---|-----------------------------|
| Product | : | GSM Mobile Phone |
| Test Item | : | Power Output |
| Test Site | : | TR8 |
| Test Mode | : | Mode 1: Transmit by 802.11b |

| Channel No. | Frequency (MHz) | Measurement Power Output (dBm) | Limit (dBm) | Result |
|-------------|-----------------|--------------------------------|-------------|--------|
| 01 | 2412 | 17.78 | 30.00 | Pass |
| 06 | 2437 | 17.79 | 30.00 | Pass |
| 11 | 2462 | 19.08 | 30.00 | Pass |

| | | |
|-----------|---|-----------------------------|
| Product | : | GSM Mobile Phone |
| Test Item | : | Power Output |
| Test Site | : | TR8 |
| Test Mode | : | Mode 2: Transmit by 802.11g |

| Channel No. | Frequency (MHz) | Measurement Power Output (dBm) | Limit (dBm) | Result |
|-------------|-----------------|--------------------------------|-------------|--------|
| 01 | 2412 | 16.09 | 30.00 | Pass |
| 06 | 2437 | 16.16 | 30.00 | Pass |
| 11 | 2462 | 17.53 | 30.00 | Pass |

| | | |
|-----------|---|------------------------------------|
| Product | : | GSM Mobile Phone |
| Test Item | : | Power Output |
| Test Site | : | TR8 |
| Test Mode | : | Mode 3: Transmit by 802.11n(20MHz) |

| Channel No. | Frequency (MHz) | Measurement Power Output (dBm) | Limit (dBm) | Result |
|-------------|-----------------|--------------------------------|-------------|--------|
| 01 | 2412 | 15.69 | 30.00 | Pass |
| 06 | 2437 | 15.96 | 30.00 | Pass |
| 11 | 2462 | 17.08 | 30.00 | Pass |

| | | |
|-----------|---|------------------------------------|
| Product | : | GSM Mobile Phone |
| Test Item | : | Power Output |
| Test Site | : | TR8 |
| Test Mode | : | Mode 4: Transmit by 802.11n(40MHz) |

| Channel No. | Frequency (MHz) | Measurement Power Output (dBm) | Limit (dBm) | Result |
|-------------|-----------------|--------------------------------|-------------|--------|
| 03 | 2422 | 14.05 | 30.00 | Pass |
| 06 | 2437 | 14.58 | 30.00 | Pass |
| 09 | 2452 | 15.10 | 30.00 | Pass |

10. Power Spectral Density


10.1. Test Equipment

Power Spectral Density / TR-8

| Instrument | Manufacturer | Type No. | Serial No. | Cali. Due Date |
|----------------------------|--------------|----------|------------|----------------|
| Spectrum Analyzer | Agilent | E4446A | MY45300103 | 2013.04.18 |
| Temperature/Humidity Meter | zhicheng | ZC1-2 | TR8-TH | 2013.05.07 |

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

10.2. Test Setup



10.3. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiated to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

10.4. Test Procedure

The EUT was tested according to KDB 558074 for compliance to FCC 47CFR 15.247 requirements.

Set RBW= 100 kHz, VBW \geq 300KHz, SPAN to 5-30 % greater than the EBW, Scale the observed power level to an equivalent value in 3 kHz by adjusting (reducing) the measured power by a bandwidth correction factor (BWCF) where $BWCF = 10\log(3\text{ kHz}/100\text{kHz} = -15.2\text{ dB})$.

10.5. Uncertainty


The measurement uncertainty is defined as $\pm 1.27\text{ dB}$

10.6. Test Result


| | | |
|-----------|---|-----------------------------|
| Product | : | GSM Mobile Phone |
| Test Item | : | Power Spectral Density |
| Test Site | : | TR-8 |
| Test Mode | : | Mode 1: Transmit by 802.11b |

| Channel No. | Frequency (MHz) | Reading Value (dBm) | BWCF (dB) | PSD (dBm) | Limit (dBm) | Result |
|-------------|-----------------|---------------------|-----------|-----------|-------------|--------|
| 01 | 2412 | 2.13 | -15.2 | -13.07 | 8 | Pass |
| 06 | 2437 | 3.31 | -15.2 | -11.89 | 8 | Pass |
| 11 | 2462 | 4.48 | -15.2 | -10.72 | 8 | Pass |


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




| | | |
|-----------|---|-----------------------------|
| Product | : | GSM Mobile Phone |
| Test Item | : | Power Spectral Density |
| Test Site | : | TR-8 |
| Test Mode | : | Mode 2: Transmit by 802.11g |

| Channel No. | Frequency (MHz) | Reading Value (dBm) | BWCF (dB) | PSD (dBm) | Limit (dBm) | Result |
|-------------|-----------------|---------------------|-----------|-----------|-------------|--------|
| 01 | 2412 | -2.41 | -15.2 | -17.61 | 8 | Pass |
| 06 | 2437 | -3.94 | -15.2 | -19.14 | 8 | Pass |
| 11 | 2462 | -2.43 | -15.2 | -17.63 | 8 | Pass |


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




| | |
|-----------|--------------------------------------|
| Product | : GSM Mobile Phone |
| Test Item | : Power Spectral Density |
| Test Site | : TR-8 |
| Test Mode | : Mode 3: Transmit by 802.11n(20MHz) |

| Channel No. | Frequency (MHz) | Reading Value (dBm) | BWCF (dB) | PSD (dBm) | Limit (dBm) | Result |
|-------------|-----------------|---------------------|-----------|-----------|-------------|--------|
| 01 | 2412 | -5.28 | -15.2 | -20.48 | 8 | Pass |
| 06 | 2437 | -3.93 | -15.2 | -19.13 | 8 | Pass |
| 11 | 2462 | -2.43 | -15.2 | -17.63 | 8 | Pass |


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




| | |
|-----------|--------------------------------------|
| Product | : GSM Mobile Phone |
| Test Item | : Power Spectral Density |
| Test Site | : TR-8 |
| Test Mode | : Mode 4: Transmit by 802.11n(40MHz) |

| Channel No. | Frequency (MHz) | Reading Value (dBm) | BWCF (dB) | PSD (dBm) | Limit (dBm) | Result |
|-------------|-----------------|---------------------|-----------|-----------|-------------|--------|
| 03 | 2422 | -9.18 | -15.2 | -24.38 | 8 | Pass |
| 06 | 2437 | -8.40 | -15.2 | -23.60 | 8 | Pass |
| 09 | 2452 | -7.47 | -15.2 | -22.67 | 8 | Pass |

Channel 03 (2422MHz)



Channel 06 (2437MHz)



Channel 09 (2452MHz)

