



**SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch**

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
Email: ee.shenzhen@sgs.com

Report No.: SZEM180700654901
Page: 1 of 36

FCC TEST REPORT

Application No: SZEM1807006549RG
Applicant: Huawei Technologies Co., Ltd.
Address of Applicant: Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C
Manufacturer: Huawei Technologies Co., Ltd.
Address of Manufacturer: Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C
Product Name: Smart Phone
Model No.(EUT): HMA-L29, HMA-L09
Trade Mark: HUAWEI
FCC ID: QISHMA-LX9
Standards: 47 CFR Part 2
 47 CFR Part 22 subpart H
 47 CFR Part 24 subpart E
 47 CFR Part 27 subpart C
 47 CFR Part 90 subpart R
Test Method: FCC KDB 971168 D01 Power Meas License Digital Systems V03r01
 TIA-603-E 2016
Date of Receipt: 2018-07-10
Date of Test: 2018-07-11 to 2018-08-20
Date of Issue: 2018-09-03

| | |
|---------------------|---------------|
| Test Result: | PASS * |
|---------------------|---------------|

* In the configuration tested, the EUT detailed in this report complied with the standards specified above.

Authorized Signature:

Derek Yang
Wireless Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, -available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



1 Version

| Revision Record | | | | |
|-----------------|---------|------------|----------|----------|
| Version | Chapter | Date | Modifier | Remark |
| 01 | | 2018-09-03 | | Original |
| | | | | |
| | | | | |

| | | | |
|---------------------------------|--|--|---------------------------------|
| Authorized for issue by: | | | |
| Tested By | |  <hr/> (Mike Hu) /Project Engineer | 2018-09-03 <hr/> Date |
| Checked By | |  <hr/> (David Chen) /Reviewer | 2018-09-03 <hr/> Date |



Content

| | Page |
|---|-----------|
| 1 VERSION | 2 |
| 2 TEST SUMMARY | 5 |
| 2.1 GSM850/UMTS BAND 5<E BAND 5 / 26 | 5 |
| 2.2 GSM1900/UMTS BAND 2 /LTE BAND 2 | 5 |
| 2.3 UMTS BAND 4 /LTE BAND 4 | 6 |
| 2.4 LTE BAND 7/38/41 | 6 |
| 2.5 LTE BAND 12/17 | 7 |
| 2.6 LTE BAND 26 | 7 |
| 3 GENERAL INFORMATION | 9 |
| 3.1 CLIENT INFORMATION | 9 |
| 3.2 GENERAL DESCRIPTION OF EUT | 9 |
| 3.3 TEST MODE | 10 |
| 3.4 TEST ENVIRONMENT | 11 |
| 3.5 TEST FREQUENCIES | 11 |
| 3.6 TEST LOCATION | 20 |
| 3.7 TEST FACILITY | 20 |
| 3.8 DEVIATION FROM STANDARDS | 20 |
| 3.9 ABNORMALITIES FROM STANDARD CONDITIONS | 20 |
| 3.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER | 21 |
| 3.11 TECHNICAL SPECIFICATION | 21 |
| 4 DESCRIPTION OF TESTS | 24 |
| 4.1 CONDUCTED OUTPUT POWER | 24 |
| 4.2 EFFECTIVE (ISOTROPIC) RADIATED POWER OF TRANSMITTER | 24 |
| 4.3 OCCUPIED BANDWIDTH | 25 |
| 4.4 BAND EDGE AT ANTENNA TERMINALS | 26 |
| 4.5 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL | 26 |
| 4.6 PEAK-AVERAGE RATIO | 27 |
| 4.7 FIELD STRENGTH OF SPURIOUS RADIATION | 27 |
| 4.8 FREQUENCY STABILITY / TEMPERATURE VARIATION | 28 |
| 4.9 TEST SETUPS | 30 |
| <i>Test Setup 1</i> | <i>30</i> |



| | |
|---|-----------|
| <i>Test Setup 2</i> | 30 |
| <i>Test Setup 3</i> | 31 |
| <i>Test Setup 4</i> | 31 |
| 4.10 TEST CONDITIONS | 32 |
| 5 MAIN TEST INSTRUMENTS | 34 |
| 6 MEASUREMENT UNCERTAINTY | 36 |
| 7 PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS | 36 |



2 Test Summary

2.1 GSM850/UMTS BAND 5<E BAND 5 / 26

| Test Item | FCC Rule No. | Requirements | Test Result | Verdict |
|--|------------------|---|-------------------------|---------|
| Effective (Isotropic) Radiated Power Output Data | §2.1046, §22.913 | FCC: ERP ≤ 7 W | Section 1 of Appendix B | Pass |
| Peak-Average Ratio | --- | Limit≤13 dB | Section 2 of Appendix B | Pass |
| Modulation Characteristics | §2.1047 | Digital modulation | Section 3 of Appendix B | Pass |
| Bandwidth | §2.1049 | OBW: No limit. EBW: No limit. | Section 4 of Appendix B | Pass |
| Band Edges Compliance | §2.1051, §2.917 | ≤ -13 dBm/1%*EBW, in 1 MHz bands immediately outside and adjacent to the frequency block. | Section 5 of Appendix B | Pass |
| Spurious Emission at Antenna Terminals | §2.1051, §2.917 | FCC: ≤ -13 dBm/100 kHz, from 9 kHz to 10 th harmonics but outside authorized operating frequency ranges. | Section 6 of Appendix B | Pass |
| Field Strength of Spurious Radiation | §2.1053, §22.917 | FCC: ≤ -13 dBm/100 kHz. | Section 7 of Appendix B | Pass |
| Frequency Stability | §2.1055, §22.355 | ≤ ±2.5ppm. | Section 8 of Appendix B | Pass |

NOTE: For the verdict, the "N/A" denotes "not applicable", the "N/T" denotes "not tested".

2.2 GSM1900/UMTS BAND 2 /LTE BAND 2

| Test Item | FCC Rule No. | Requirements | Test Result | Verdict |
|--|------------------|--|-------------------------|---------|
| Effective (Isotropic) Radiated Power Output Data | §2.1046, §24.232 | EIRP ≤ 2 W | Section 1 of Appendix B | Pass |
| Peak-Average Ratio | §2.1046, §24.232 | Limit≤13 dB | Section 2 of Appendix B | Pass |
| Modulation Characteristics | §2.1047 | Digital modulation | Section 3 of Appendix B | Pass |
| Bandwidth | §2.1049 | OBW: No limit. EBW: No limit. | Section 4 of Appendix B | Pass |
| Band Edges Compliance | §2.1051, §24.238 | ≤ -13 dBm/1%*EBW, in 1 MHz bands immediately outside and adjacent to the frequency block. | Section 5 of Appendix B | Pass |
| Spurious Emission at Antenna Terminals | §2.1051, §24.238 | ≤ -13 dBm/1 MHz, from 9 kHz to 10 th harmonics but outside authorized operating frequency ranges. | Section 6 of Appendix B | Pass |
| Field Strength of Spurious Radiation | §2.1053, §24.238 | ≤ -13 dBm/1 MHz. | Section 7 of Appendix B | Pass |
| Frequency Stability | §2.1055, §24.235 | ≤ ±2.5 ppm. | Section 8 of Appendix B | Pass |



| Test Item | FCC Rule No. | Requirements | Test Result | Verdict |
|--|--------------|--------------|-------------|---------|
| NOTE: For the verdict, the "N/A" denotes "not applicable", the "N/T" denotes "not tested". | | | | |

2.3 UMTS BAND 4 /LTE BAND 4

| Test Item | FCC Rule No. | Requirements | Test Result | Verdict |
|--|--------------------|--|-------------------------|---------|
| Effective (Isotropic) Radiated Power Output Data | §2.1046, §27.50(d) | EIRP ≤ 1 W | Section 1 of Appendix B | Pass |
| Peak-Average Ratio | §2.1046, §27.50(d) | Limit≤13 dB | Section 2 of Appendix B | Pass |
| Modulation Characteristics | §2.1047 | Digital modulation | Section 3 of Appendix B | Pass |
| Bandwidth | §2.1049 | OBW: No limit. EBW: No limit. | Section 4 of Appendix B | Pass |
| Band Edges Compliance | §2.1051, §27.53(h) | ≤ -13 dBm/1%*EBW, in 1 MHz bands immediately outside and adjacent to the frequency block. | Section 5 of Appendix B | Pass |
| Spurious Emission at Antenna Terminals | §2.1051, §27.53(h) | ≤ -13 dBm/1 MHz, from 9 kHz to 10 th harmonics but outside authorized operating frequency ranges. | Section 6 of Appendix B | Pass |
| Field Strength of Spurious Radiation | §2.1053, §27.53(h) | ≤ -13 dBm/1 MHz. | Section 7 of Appendix B | Pass |
| Frequency Stability | §2.1055, §27.54 | ≤ ±2.5 ppm. | Section 8 of Appendix B | Pass |
| NOTE: For the verdict, the "N/A" denotes "not applicable", the "N/T" denotes "not tested". | | | | |

2.4 LTE BAND 7/38/41

| Test Item | FCC Rule No. | Requirements | Test Result | Verdict |
|--|---------------------|---|-------------------------|---------|
| Effective (Isotropic) Radiated Power Output Data | §2.1046, §27.50(h) | EIRP ≤ 2W | Section 1 of Appendix B | Pass |
| Peak-Average Ratio | §27.50(a) | ≤13 dB | Section 2 of Appendix B | Pass |
| Modulation Characteristics | §2.1047 | Digital modulation | Section 3 of Appendix B | Pass |
| Bandwidth | §2.1049 | OBW: No limit. EBW: No limit. | Section 4 of Appendix B | Pass |
| Band Edges Compliance | §2.1051, §27.53(m4) | For mobile digital stations, the attenuation factor shall be not less than 40 + 10 log (P) dB on all frequencies between the channel edge and 5 megahertz from the channel edge, 43 + 10 log (P) dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and 55 + 10 log (P) dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. | Section 5 of Appendix B | Pass |



| Test Item | FCC Rule No. | Requirements | Test Result | Verdict |
|--|--------------------|--|-------------------------|---------|
| Spurious Emission at Antenna Terminals | §2.1051, §27.53(m) | <p>Channel Edge $-25 \text{ dBm}/1 \text{ MHz}$ $-25 \text{ dBm}/1 \text{ MHz}$ 9 kHz 9.5 MHz $X \text{ MHz}$ 10^{th} harmonics $X = \text{Max} [6 \text{ MHz}, \text{EBW}]$</p> | Section 6 of Appendix B | Pass |
| Field Strength of Spurious Radiation | §2.1053, §27.53(m) | <p>Channel Edge $-25 \text{ dBm}/1 \text{ MHz}$ $-25 \text{ dBm}/1 \text{ MHz}$ 9 kHz 9.5 MHz $X \text{ MHz}$ 10^{th} harmonics $X = \text{Max} [6 \text{ MHz}, \text{EBW}]$</p> | Section 7 of Appendix B | Pass |
| Frequency Stability | §2.1055, §27.54 | Within authorized bands of operation/frequency block. | Section 8 of Appendix B | Pass |

NOTE: For the verdict, the "N/A" denotes "not applicable", the "N/T" denotes "not tested".

2.5 LTE BAND 12/17

| Test Item | FCC Rule No. | Requirements | Test Result | Verdict |
|--|--------------------|---|-------------------------|---------|
| Effective (Isotropic) Radiated Power Output Data | §27.50(c) | FCC: ERP $\leq 3 \text{ W}$. | Section 1 of Appendix B | Pass |
| Peak-Average Ratio | §2.1046, §27.50(c) | Limit $\leq 13 \text{ dB}$ | Section 2 of Appendix B | Pass |
| Modulation Characteristics | §2.1047 | Digital modulation | Section 3 of Appendix B | Pass |
| Bandwidth | §2.1049 | OBW: No limit. EBW: No limit. | Section 4 of Appendix B | Pass |
| Band Edges Compliance | §2.1051, §27.53(g) | $\leq -13 \text{ dBm}/1\% \cdot \text{EBW}$, in 1 MHz bands immediately outside and adjacent to the frequency block. | Section 5 of Appendix B | Pass |
| Spurious Emission at Antenna Terminals | §2.1051, §27.53(g) | FCC: $\leq -13 \text{ dBm}/100 \text{ kHz}$, from 9 kHz to 10 th harmonics but outside authorized operating frequency ranges. | Section 6 of Appendix B | Pass |
| Field Strength of Spurious Radiation | §2.1053, §27.53(g) | FCC: $\leq -13 \text{ dBm}/100 \text{ kHz}$. | Section 7 of Appendix B | Pass |
| Frequency Stability | §2.1055, §27.54 | $\leq \pm 2.5 \text{ ppm}$. | Section 8 of Appendix B | Pass |

NOTE: For the verdict, the "N/A" denotes "not applicable", the "N/T" denotes "not tested".

2.6 LTE BAND 26

| Test Item | FCC Rule No. | Requirements | Test Result | Verdict |
|------------------------------------|------------------|---------------------------------|-------------------------|---------|
| Transmitter Conducted Power Output | §2.1046, §90.635 | $< 100 \text{ W}$. | Section 1 of Appendix B | PASS |
| Peak-Average Ratio | --- | FCC: Limit $\leq 13 \text{ dB}$ | Section 2 of Appendix B | N/T |
| Modulation | §2.1047 | Digital modulation | Section 3 of Appendix B | PASS |



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM180700654901

Page: 8 of 36

| Test Item | FCC Rule No. | Requirements | Test Result | Verdict |
|--|---------------------|--|-------------------------|---------|
| Characteristics | | | Appendix B | |
| Bandwidth | §2.1049 | OBW: No limit. EBW: No limit. | Section 4 of Appendix B | PASS |
| Emission Mask | §2.1051 § 90.210 | For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $116 \text{ Log}_{10}(f/6.1)$ decibels or $50+10\text{Log}_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz. | Section 5 of Appendix B | PASS |
| Spurious Emission at Antenna Terminals | §2.1051, §90.691 | $< 43 + 10\text{Log}_{10}(P[\text{Watts}])$ for all out-of-band emissions | Section 6 of Appendix B | PASS |
| Field Strength of Spurious Radiation | §2.1053, §90.691 | $< 43 + 10\text{Log}_{10}(P[\text{Watts}])$ for all out-of-band emissions | Section 7 of Appendix B | PASS |
| Frequency Stability | §2.1055, §90.213 | $< \pm 2.5\text{ppm}$. | Section 8 of Appendix B | PASS |
| NOTE: For the verdict, the "N/A" denotes "not applicable", the "N/T" denotes "not tested". | | | | |

Remark:

According to the declaration from the applicant, the differences between HMA-L29 and HMA-L09 are identical except for HMA-L09 support single SIM card which deleted by software. Therefore we only test HMA-L29 in this report





3 General Information

3.1 Client Information

| | |
|--------------------------|---|
| Applicant: | Huawei Technologies Co., Ltd. |
| Address of Applicant: | Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C |
| Manufacturer: | Huawei Technologies Co., Ltd. |
| Address of Manufacturer: | Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C |

3.2 General Description of EUT

| | |
|-------------------|--|
| Product Name: | Smart Phone |
| Model No.: | HMA-L29, HMA-L09 |
| Trade Mark: | HUAWEI |
| Hardware Version: | HL1HIMAM |
| Software Version: | 9.0.0.46(C432E55R1P7log) |
| Sample Type: | Portable Device |
| Antenna Type: | PIFA |
| Antenna Gain: | GSM850: -2.76dBi(Main Antenna); -11.05dBi (Second Antenna); GSM1900:-1.43dBi(Main Antenna); -4.93dBi (Second Antenna); WCDMA BAND II:-2.61dBi(Main Antenna); -3.51dBi (Second Antenna); WCDMA BAND VI:-0.284dBi(Main Antenna); -7.92dBi (Second Antenna); WCDMA BAND V:-3.41dBi(Main Antenna); -7.24dBi (Second Antenna); LTE BAND 2:-2.05dBi(Main Antenna); -3.42dBi (Second Antenna); LTE BAND 4:0.21dBi(Main Antenna); -8.12dBi (Second Antenna); LTE BAND 5:-2.66dBi(Main Antenna); -7.35dBi (Second Antenna); LTE BAND 7: 1.01dBi(Main Antenna); -3.36dBi (Second Antenna); LTE BAND12:-4.73dBi(Main Antenna); -7.43dBi (Second Antenna); LTE BAND17: -4.37dBi(Main Antenna); -7.57dBi (Second Antenna); LTE BAND26:-2.95dBi(Main Antenna); -7.04dBi (Second Antenna); LTE BAND38: 0.63dBi(Main Antenna); -2.81dBi (Second Antenna); LTE BAND41: 0.89dBi(Main Antenna); -3.61dBi (Second Antenna); |
| Power Supply | Battery Model: HB436486ECW Rated capacity: 3900mAh Nominal Voltage:  +3.82V Charging Voltage:  +4.40V |
| AC adaptor: | Model: HW-050450B00 Manufacturer: Huawei Technologies Co., Ltd. Input: 100V-240V~50/60Hz, 0.75A |



| | |
|--|---|
| | <p>Output: 5V ===== 2A OR 4.5V ===== 5A OR 5V ===== 4.5A Model: HW-050450E00 Manufacturer: Huawei Technologies Co., Ltd. Input: 100V-240V~50/60Hz, 0.75A</p> <p>Output: 5V ===== 2A OR 4.5V ===== 5A OR 5V ===== 4.5A Model: HW-050450U00 Manufacturer: Huawei Technologies Co., Ltd. Input: 100V-240V~50/60Hz, 0.75A</p> <p>Output: 5V ===== 2A OR 4.5V ===== 5A OR 5V ===== 4.5A Model: HW-050450A00 Manufacturer: Huawei Technologies Co., Ltd. Input: 100V-240V~50/60Hz, 0.75A</p> <p>Output: 5V ===== 2A OR 4.5V ===== 5A OR 5V ===== 4.5A Model: HW-050450E01 Manufacturer: Huawei Technologies Co., Ltd. Input: 100V-240V~50/60Hz, 0.75A</p> <p>Output: 5V ===== 2A OR 9V ===== 2A</p> |
|--|---|

3.3 Test Mode

| Test Mode | Test Modes Description |
|-----------|---------------------------------------|
| GSM/TM1 | GSM system, GSM/GPRS, GMSK modulation |
| GSM/TM2 | GSM system, EGPRS, 8PSK modulation |
| UMTS/TM1 | UMTS system, WCDMA, QPSK modulation |
| UMTS/TM2 | UMTS system, WCDMA, 16QAM modulation |
| LTE/TM1 | LTE system, QPSK modulation |
| LTE/TM2 | LTE system, 16QAM modulation |
| LTE/TM3 | LTE system, 64QAM modulation |

NOTE: The test mode(s) are selected according to relevant radio technology specifications.



3.4 Test Environment

| Environment Parameter | Selected Values During Tests | |
|-----------------------|------------------------------|-------|
| Relative Humidity | 52% | |
| Atmospheric Pressure: | 101.32 KPa | |
| Temperature | NT | 25 °C |
| Voltage: | LV | 3.6V |
| | NV | 3.82V |
| | HV | 4.35V |

NOTE: LV= lower extreme test voltage; NV= nominal voltage
 HV= upper extreme test voltage; NT= normal temperature

3.5 Test Frequencies

| Test Mode | TX / RX | RF Channel | | |
|-----------|---------|-------------|-------------|-------------|
| | | Low (L) | Middle (M) | High (H) |
| GSM850 | TX | Channel 128 | Channel 190 | Channel 251 |
| | | 824.2MHz | 836.6 MHz | 848.8 MHz |
| | RX | Channel 128 | Channel 190 | Channel 251 |
| | | 869.2 MHz | 881.6 MHz | 893.8 MHz |

| Test Mode | TX / RX | RF Channel | | |
|-----------|---------|-------------|-------------|-------------|
| | | Low (L) | Middle (M) | High (H) |
| GSM1900 | TX | Channel 512 | Channel 661 | Channel 810 |
| | | 1850.2MHz | 1880.0 MHz | 1909.8 MHz |
| | RX | Channel 512 | Channel 661 | Channel 810 |
| | | 1930.2 MHz | 1960.0 MHz | 1989.8 MHz |

| Test Mode | TX / RX | RF Channel | | |
|-----------------|---------|--------------|--------------|--------------|
| | | Low (L) | Middle (M) | High (H) |
| WCDMA BAND V | TX | Channel 4132 | Channel 4182 | Channel 4233 |
| | | 826.4MHz | 836.4 MHz | 846.6 MHz |
| | RX | Channel 4357 | Channel 4407 | Channel 4458 |
| | | 871.4 MHz | 881.4 MHz | 891.6 MHz |

| Test Mode | TX / RX | RF Channel | | |
|------------------|---------|--------------|--------------|--------------|
| | | Low (L) | Middle (M) | High (H) |
| WCDMA BAND IV | TX | Channel 1312 | Channel 1413 | Channel 1513 |
| | | 1712.4MHz | 1732.6 MHz | 1752.6 MHz |



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM180700654901

Page: 12 of 36

| | | | | |
|--|----|--------------|--------------|--------------|
| | RX | Channel 1537 | Channel 1638 | Channel 1738 |
| | | 2112.4 MHz | 2132.6 MHz | 2152.6 MHz |

| Test Mode | TX / RX | RF Channel | | |
|------------------|---------|--------------|--------------|--------------|
| | | Low (L) | Middle (M) | High (H) |
| WCDMA BAND II | TX | Channel 9262 | Channel 9400 | Channel 9538 |
| | | 1852.4 MHz | 1880.0 MHz | 1907.6 MHz |
| | RX | Channel 9662 | Channel 9800 | Channel 9938 |
| | | 1932.4 MHz | 1960.0 MHz | 1987.6 MHz |

| Test Mode | Bandwidth | TX / RX | RF Channel | | |
|------------|-----------|---------|---------------|---------------|---------------|
| | | | Low (L) | Middle (M) | High (H) |
| LTE BAND 2 | 1.4MHz | TX | Channel 18607 | Channel 18900 | Channel 19193 |
| | | | 1850.7 MHz | 1880 MHz | 1909.3 MHz |
| | | RX | Channel 607 | Channel 900 | Channel 1193 |
| | | | 1930.7 MHz | 1960 MHz | 1989.3 MHz |
| | 3MHz | TX | Channel 18615 | Channel 18900 | Channel 19185 |
| | | | 1851.5 MHz | 1880 MHz | 1908.5 MHz |
| | | RX | Channel 615 | Channel 900 | Channel 1185 |
| | | | 1931.5 MHz | 1960 MHz | 1988.5 MHz |
| | 5MHz | TX | Channel 18625 | Channel 18900 | Channel 19175 |
| | | | 1852.5 MHz | 1880 MHz | 1907.5 MHz |
| | | RX | Channel 625 | Channel 900 | Channel 1175 |
| | | | 1932.5 MHz | 1960 MHz | 1987.5 MHz |
| | 10MHz | TX | Channel 18650 | Channel 18900 | Channel 19150 |
| | | | 1855 MHz | 1880 MHz | 1905 MHz |
| | | RX | Channel 650 | Channel 900 | Channel 1150 |
| | | | 1935 MHz | 1960 MHz | 1985 MHz |
| | 15MHz | TX | Channel 18675 | Channel 18900 | Channel 19125 |
| | | | 1857.5 MHz | 1880 MHz | 1902.5 MHz |
| | | RX | Channel 675 | Channel 900 | Channel 1125 |
| | | | 1937.5 MHz | 1960 MHz | 1982.5 MHz |
| | 20MHz | TX | Channel 18700 | Channel 18900 | Channel 19100 |
| | | | 1860 MHz | 1880 MHz | 1900 MHz |
| | | RX | Channel 700 | Channel 900 | Channel 1100 |
| | | | 1940 MHz | 1960 MHz | 1980 MHz |



**SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch**

Report No.: SZEM180700654901

Page: 13 of 36

| Test Mode | Bandwidth | TX / RX | RF Channel | | |
|------------|-----------|---------|---------------|---------------|---------------|
| | | | Low (L) | Middle (M) | High (H) |
| LTE BAND 4 | 1.4MHz | TX | Channel 19957 | Channel 20175 | Channel 20393 |
| | | | 1710.7 MHz | 1732.5 MHz | 1754.3 MHz |
| | | RX | Channel 1975 | Channel 2175 | Channel 2375 |
| | | | 2112.5 MHz | 2132.5MHz | 2152.5 MHz |
| | 3MHz | TX | Channel 19965 | Channel 20175 | Channel 20385 |
| | | | 1711.5 MHz | 1732.5 MHz | 1753.5 MHz |
| | | RX | Channel 2000 | Channel 2175 | Channel 2350 |
| | | | 2115 MHz | 2132.5MHz | 2150 MHz |
| | 5MHz | TX | Channel 19975 | Channel 20175 | Channel 20375 |
| | | | 1712.5 MHz | 1732.5 MHz | 1752.5 MHz |
| | | RX | Channel 1975 | Channel 2175 | Channel 2375 |
| | | | 2112.5 MHz | 2132.5MHz | 2152.5 MHz |
| | 10MHz | TX | Channel 20000 | Channel 20175 | Channel 20350 |
| | | | 1715 MHz | 1732.5 MHz | 1750 MHz |
| | | RX | Channel 2000 | Channel 2175 | Channel 2350 |
| | | | 2115 MHz | 2132.5MHz | 2150 MHz |
| | 15MHz | TX | Channel 20025 | Channel 20175 | Channel 20325 |
| | | | 1717.5 MHz | 1732.5 MHz | 1747.5 MHz |
| | | RX | Channel 2025 | Channel 2175 | Channel 2325 |
| | | | 2117.5 MHz | 2132.5MHz | 2147.5 MHz |
| | 20MHz | TX | Channel 20050 | Channel 20175 | Channel 20300 |
| | | | 1720 MHz | 1732.5 MHz | 1745 MHz |
| | | RX | Channel 2050 | Channel 2175 | Channel 2300 |
| | | | 2120 MHz | 2132.5MHz | 2145 MHz |

| Test Mode | Bandwidth | TX / RX | RF Channel | | |
|------------|--------------|---------------|---------------|---------------|---------------|
| | | | Low (L) | Middle (M) | High (H) |
| LTE BAND 5 | 1.4MHz | TX | Channel 20407 | Channel 20525 | Channel 20643 |
| | | | 824.7 MHz | 836.5 MHz | 848.3 MHz |
| | | RX | Channel 2407 | Channel 20525 | Channel 2643 |
| | | | 869.7 MHz | 881.5 MHz | 893.3 MHz |
| | 3MHz | TX | Channel 20415 | Channel 20525 | Channel 20635 |
| | | | 825.5 MHz | 836.5 MHz | 847.5 MHz |
| RX | Channel 2415 | Channel 20525 | Channel 2635 | | |

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM180700654901

Page: 14 of 36

| | | | | | |
|--|-------|----|---------------|---------------|---------------|
| | 5MHz | TX | 870.5 MHz | 881.5 MHz | 892.5 MHz |
| | | | Channel 20425 | Channel 20525 | Channel 20625 |
| | | RX | 826.5 MHz | 836.5 MHz | 846.5 MHz |
| | | | Channel 2425 | Channel 20525 | Channel 2625 |
| | 10MHz | TX | 871.5 MHz | 881.5 MHz | 891.5 MHz |
| | | | Channel 20450 | Channel 20525 | Channel 20600 |
| | | RX | 829 MHz | 836.5 MHz | 844 MHz |
| | | | Channel 2450 | Channel 2525 | Channel 2600 |
| | | | 874 MHz | 881.5 MHz | 889 MHz |

| Test Mode | Bandwidth | TX / RX | RF Channel | | |
|------------|-----------|---------|---------------|---------------|---------------|
| | | | Low (L) | Middle (M) | High (H) |
| LTE BAND 7 | 5MHz | TX | Channel 20775 | Channel 21100 | Channel 21425 |
| | | | 2502.5 MHz | 2535 MHz | 2567.5 MHz |
| | | RX | Channel 2775 | Channel 3100 | Channel 5825 |
| | | | 2622.5 MHz | 2655 MHz | 2687.5 MHz |
| | 10MHz | TX | Channel 20800 | Channel 21100 | Channel 21400 |
| | | | 2505 MHz | 2535 MHz | 2565 MHz |
| | | RX | Channel 2800 | Channel 3100 | Channel 3400 |
| | | | 2625 MHz | 2655 MHz | 2685 MHz |
| | 15MHz | TX | Channel 20825 | Channel 21100 | Channel 21375 |
| | | | 2507.5 MHz | 2535 MHz | 2562.5 MHz |
| | | RX | Channel 2825 | Channel 3100 | Channel 3375 |
| | | | 2627.5 MHz | 2655 MHz | 2682.5 MHz |
| | 20MHz | TX | Channel 20850 | Channel 21100 | Channel 21350 |
| | | | 2510 MHz | 2535 MHz | 2560 MHz |
| | | RX | Channel 2850 | Channel 3100 | Channel 3350 |
| | | | 2630 MHz | 2655 MHz | 2680 MHz |

| Test Mode | Bandwidth | TX / RX | RF Channel | | |
|------------|-----------|---------|---------------|---------------|---------------|
| | | | Low (L) | Middle (M) | High (H) |
| LTE BAND12 | 1.4MHz | TX | Channel 23017 | Channel 23095 | Channel 23173 |
| | | | 699.7 MHz | 707.5 MHz | 715.3 MHz |
| | | RX | Channel 5017 | Channel 5095 | Channel 5173 |
| | | | 729.7 MHz | 737.5 MHz | 745.3 MHz |
| | 3MHz | TX | Channel 23025 | Channel 23095 | Channel 23165 |
| | | | 700.5 MHz | 707.5 MHz | 714.5 MHz |
| | | RX | Channel 5025 | Channel 5095 | Channel 5165 |
| | | | 730.5 MHz | 737.5 MHz | 744.5 MHz |
| | 5MHz | TX | Channel 23035 | Channel 23095 | Channel 23155 |
| | | | 701.5 MHz | 707.5 MHz | 713.5 MHz |

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



| | | | | | |
|--|-------|----|---------------|---------------|---------------|
| | | RX | Channel 5035 | Channel 5095 | Channel 5155 |
| | | | 731.5 MHz | 737.5 MHz | 743.5 MHz |
| | 10MHz | TX | Channel 23060 | Channel 23095 | Channel 23130 |
| | | | 704 MHz | 707.5 MHz | 711 MHz |
| | | RX | Channel 5060 | Channel 5095 | Channel 5130 |
| | | | 734 MHz | 737.5 MHz | 741 MHz |

| Test Mode | Bandwidth | TX / RX | RF Channel | | |
|-------------|-----------|---------|---------------|---------------|---------------|
| | | | Low (L) | Middle (M) | High (H) |
| LTE BAND 17 | 5MHz | TX | Channel 23755 | Channel 23790 | Channel 23825 |
| | | | 706.5 MHz | 710 MHz | 713.5 MHz |
| | | RX | Channel 5755 | Channel 5790 | Channel 5825 |
| | | | 736.5 MHz | 740 MHz | 743.5 MHz |
| | 10MHz | TX | Channel 23780 | Channel 23790 | Channel 23800 |
| | | | 709 MHz | 710 MHz | 711 MHz |
| | | RX | Channel 5780 | Channel 5790 | Channel 5800 |
| | | | 739 MHz | 740 MHz | 741 MHz |

| Test Mode | Bandwidth | TX / RX | RF Channel | | |
|-------------------------|-----------|---------|---------------|---------------|---------------|
| | | | Low (L) | Middle (M) | High (H) |
| LTE BAND26 (814-824) | 1.4MHz | TX | Channel 26697 | Channel 26740 | Channel 26783 |
| | | | 814.7 MHz | 819 MHz | 823.3 MHz |
| | | RX | Channel 8697 | Channel 8740 | Channel 8783 |
| | | | 859.7 MHz | 864MHz | 868.3 MHz |
| | 3MHz | TX | Channel 26705 | Channel 26740 | Channel 26775 |
| | | | 815.5 MHz | 819 MHz | 822.5 MHz |
| | | RX | Channel 8705 | Channel 8740 | Channel 8775 |
| | | | 860.5 MHz | 864MHz | 867.5 MHz |
| | 5MHz | TX | Channel 26715 | Channel 26740 | Channel 26765 |
| | | | 816.5 MHz | 819 MHz | 821.5 MHz |
| | | RX | Channel 8715 | Channel 8740 | Channel 8755 |
| | | | 861.5 MHz | 864MHz | 866.5 MHz |
| | 10MHz | TX | Channel 26740 | Channel 26740 | Channel 26740 |
| | | | 819 MHz | 819 MHz | 819 MHz |
| | | RX | Channel 8740 | Channel 8740 | Channel 8740 |
| | | | 864MHz | 864MHz | 864MHz |



| Test Mode | Bandwidth | TX / RX | RF Channel | | |
|-------------------------|-----------|---------------|---------------|---------------|---------------|
| | | | Low (L) | Middle (M) | High (H) |
| LTE BAND26 (824-849) | 1.4MHz | TX | Channel 26797 | Channel 26915 | Channel 27033 |
| | | | 824.7 MHz | 836.5 MHz | 848.3 MHz |
| | | RX | Channel 8697 | Channel 8915 | Channel 9033 |
| | | | 859.7 MHz | 881.5 MHz | 893.3 MHz |
| | 3MHz | TX | Channel 26805 | Channel 26915 | Channel 27025 |
| | | | 825.5 MHz | 836.5 MHz | 847.5 MHz |
| | | RX | Channel 8805 | Channel 8915 | Channel 9025 |
| | | | 860.5 MHz | 881.5 MHz | 892.5 MHz |
| | 5MHz | TX | Channel 26815 | Channel 26915 | Channel 27015 |
| | | | 826.5 MHz | 836.5 MHz | 846.5 MHz |
| | | RX | Channel 8815 | Channel 8915 | Channel 9015 |
| | | | 871.5 MHz | 881.5 MHz | 891.5 MHz |
| | 10MHz | TX | Channel 26840 | Channel 26915 | Channel 26990 |
| | | | 829 MHz | 836.5 MHz | 844 MHz |
| | | RX | Channel 8840 | Channel 8915 | Channel 8990 |
| | | | 874 MHz | 881.5 MHz | 889 MHz |
| 15MHz | TX | Channel 26865 | Channel 26915 | Channel 26965 | |
| | | 831.5 MHz | 836.5 MHz | 841.5 MHz | |
| | RX | Channel 8865 | Channel 8915 | Channel 8965 | |
| | | 876.5 MHz | 881.5 MHz | 886.5 MHz | |

| Test Mode | Bandwidth | TX / RX | RF Channel | | |
|-------------|-----------|---------|---------------|--------------|---------------|
| | | | Low (L) | Middle (M) | High (H) |
| LTE BAND 38 | 5MHz | TX/RX | Channel 37775 | Channel38000 | Channel 38225 |
| | | | 2572.5 MHz | 2595 MHz | 2617.5 MHz |
| | 10MHz | TX/RX | Channel 37800 | Channel38000 | Channel 38200 |
| | | | 2575 MHz | 2595 MHz | 2615 MHz |
| | 15MHz | TX/RX | Channel 37825 | Channel38000 | Channel 38175 |
| | | | 2577.5 MHz | 2595 MHz | 2612.5 MHz |
| | 20MHz | TX/RX | Channel 37850 | Channel38000 | Channel 38150 |
| | | | 2580 MHz | 2595 MHz | 2610 MHz |



| Test Mode | Bandwidth | TX / RX | RF Channel | | |
|-------------|-----------|---------|---------------|--------------|---------------|
| | | | Low (L) | Middle (M) | High (H) |
| LTE BAND 41 | 5MHz | TX/RX | Channel 39675 | Channel40620 | Channel 41565 |
| | | | 2498.5 MHz | 2593 MHz | 2687.5 MHz |
| | 10MHz | TX/RX | Channel 39700 | Channel40620 | Channel 41540 |
| | | | 2501 MHz | 2593 MHz | 2685 MHz |
| | 15MHz | TX/RX | Channel 39725 | Channel40620 | Channel 41515 |
| | | | 2503.5 MHz | 2593 MHz | 2682.5 MHz |
| | 20MHz | TX/RX | Channel 39750 | Channel40620 | Channel 41490 |
| | | | 2506 MHz | 2593 MHz | 2680 MHz |

Test frequencies for CA_5B

Table 4.3.1.1.5A-1: Test frequencies for CA_5B

| Range | CC-Combo / N _{RB,agg} [RB] | CC1 Note1 | | | | | CC2 Note1 | | | | |
|-------|---|--------------|-----------------|--------------------------|-----------------|--------------------------|--------------|-----------------|--------------------------|-----------------|--------------------------|
| | | BW [RB] | N _{UL} | f _{UL} [MHz] | N _{DL} | f _{DL} [MHz] | BW [RB] | N _{UL} | f _{UL} [MHz] | N _{DL} | f _{DL} [MHz] |
| Low | 15+25 | 15 | 20416 | 825.6 | 2416 | 870.6 | 25 | 20455 | 829.5 | 2455 | 874.5 |
| | | 25 | 20425 | 826.5 | 2425 | 871.5 | 15 | 20464 | 830.4 | 2464 | 875.4 |
| | 25+50 | 25 | 20428 | 826.8 | 2428 | 871.8 | 50 | 20500 | 834 | 2500 | 879 |
| | 50+25 | 50 | 20450 | 829 | 2450 | 874 | 25 | 20522 | 836.2 | 2522 | 881.2 |
| Mid | 15+25 | 50 | 20450 | 829 | 2450 | 874 | 50 | 20549 | 838.9 | 2549 | 883.9 |
| | | 15 | 20501 | 834.1 | 2501 | 879.1 | 25 | 20540 | 838.0 | 2540 | 883.0 |
| High | 25+50 | 25 | 20510 | 835.0 | 2510 | 880.0 | 15 | 20549 | 838.9 | 2549 | 883.9 |
| | | 25 | 20478 | 831.8 | 2478 | 876.8 | 50 | 20550 | 839 | 2550 | 884 |
| | 50+25 | 50 | 20500 | 834 | 2500 | 879 | 25 | 20572 | 841.2 | 2572 | 886.2 |
| | 50+50 | 50 | 20476 | 831.6 | 2476 | 876.6 | 50 | 20575 | 841.5 | 2575 | 886.5 |
| High | 15+25 | 15 | 20586 | 842.6 | 2586 | 887.6 | 25 | 20625 | 846.5 | 2625 | 891.5 |
| | | 25 | 20595 | 843.5 | 2595 | 888.5 | 15 | 20634 | 847.4 | 2634 | 892.4 |
| High | 25+50 | 25 | 20528 | 836.8 | 2528 | 881.8 | 50 | 20600 | 844 | 2600 | 889 |
| | 50+25 | 50 | 20550 | 839 | 2550 | 884 | 25 | 20622 | 846.2 | 2622 | 891.2 |
| | 50+50 | 50 | 20501 | 834.1 | 2501 | 879.1 | 50 | 20600 | 844 | 2600 | 889 |

Note 1: Carriers in increasing frequency order.



Test frequencies for CA_7C

Table 4.3.1.1.7A-1: Test frequencies for CA_7C

| Range | CC-Combo / N _{RB_agg} [RB] | CC1 Note1 | | | | | CC2 Note1 | | | | |
|---------|---|--------------|-----------------|--------------------------|-----------------|--------------------------|--------------|-----------------|--------------------------|-----------------|--------------------------|
| | | BW [RB] | N _{UL} | f _{UL} [MHz] | N _{DL} | f _{DL} [MHz] | BW [RB] | N _{UL} | f _{UL} [MHz] | N _{DL} | f _{DL} [MHz] |
| Low | 50+100 | 50 | 20805 | 2505.5 | 2805 | 2625.5 | 100 | 20949 | 2519.9 | 2949 | 2639.9 |
| | | 100 | 20850 | 2510 | 2850 | 2630 | 50 | 20994 | 2524.4 | 2994 | 2644.4 |
| | 75+50 | 75 | 20825 | 2507.5 | 2825 | 2627.5 | 50 | 20945 | 2519.5 | 2945 | 2639.5 |
| | 75+75 | 75 | 20825 | 2507.5 | 2825 | 2627.5 | 75 | 20975 | 2522.5 | 2975 | 2642.5 |
| | 75+100 | 75 | 20828 | 2507.8 | 2828 | 2627.8 | 100 | 20999 | 2524.9 | 2999 | 2644.9 |
| | | 100 | 20850 | 2510 | 2850 | 2630 | 75 | 21021 | 2527.1 | 3021 | 2647.1 |
| 100+100 | 100 | 20850 | 2510 | 2850 | 2630 | 100 | 21048 | 2529.8 | 3048 | 2649.8 | |
| Mid | 50+100 | 50 | 21006 | 2525.6 | 3006 | 2645.6 | 100 | 21150 | 2540 | 3150 | 2660 |
| | | 100 | 21051 | 2530.1 | 3051 | 2650.1 | 50 | 21195 | 2544.5 | 3195 | 2664.5 |
| | 75+50 | 75 | 21051 | 2530.1 | 3051 | 2650.1 | 50 | 21171 | 2542.1 | 3171 | 2662.1 |
| | 75+75 | 75 | 21025 | 2527.5 | 3025 | 2647.5 | 75 | 21175 | 2542.5 | 3175 | 2662.5 |
| | 75+100 | 75 | 21003 | 2525.3 | 3003 | 2645.3 | 100 | 21174 | 2542.4 | 3174 | 2662.4 |
| | | 100 | 21026 | 2527.6 | 3026 | 2647.6 | 75 | 21197 | 2544.7 | 3197 | 2664.7 |
| 100+100 | 100 | 21001 | 2525.1 | 3001 | 2645.1 | 100 | 21199 | 2544.9 | 3199 | 2664.9 | |
| High | 50+100 | 50 | 21206 | 2545.6 | 3206 | 2665.6 | 100 | 21350 | 2560 | 3350 | 2680 |
| | | 100 | 21251 | 2550.1 | 3251 | 2670.1 | 50 | 21395 | 2564.5 | 3395 | 2684.5 |
| | 75+50 | 75 | 21277 | 2552.7 | 3277 | 2672.7 | 50 | 21397 | 2564.7 | 3397 | 2684.7 |
| | 75+75 | 75 | 21225 | 2547.5 | 3225 | 2667.5 | 75 | 21375 | 2562.5 | 3375 | 2682.5 |
| | 75+100 | 75 | 21179 | 2542.9 | 3179 | 2662.9 | 100 | 21350 | 2560 | 3350 | 2680 |
| | | 100 | 21201 | 2545.1 | 3201 | 2665.1 | 75 | 21372 | 2562.2 | 3372 | 2682.2 |
| 100+100 | 100 | 21152 | 2540.2 | 3152 | 2660.2 | 100 | 21350 | 2560 | 3350 | 2680 | |

Note 1: Carriers in increasing frequency order.

Test frequencies for CA_38C

Table 4.3.1.2.6A-1: Test frequencies for CA_38C

| Range | CC-Combo / N _{RB_agg} [RB] | CC1 Note1 | | | CC2 Note1 | | |
|-------|---|--------------|--------------------|-----------------------------|--------------|--------------------|-----------------------------|
| | | BW [RB] | N _{UL/DL} | f _{UL/DL} [MHz] | BW [RB] | N _{UL/DL} | f _{UL/DL} [MHz] |
| Low | 75+75 | 75 | 37825 | 2577.5 | 75 | 37975 | 2592.5 |
| | 100+100 | 100 | 37850 | 2580 | 100 | 38048 | 2599.8 |
| Mid | 75+75 | 75 | 37925 | 2587.5 | 75 | 38075 | 2602.5 |
| | 100+100 | 100 | 37901 | 2585.1 | 100 | 38099 | 2604.9 |
| High | 75+75 | 75 | 38025 | 2597.5 | 75 | 38175 | 2612.5 |
| | 100+100 | 100 | 37952 | 2590.2 | 100 | 38150 | 2610 |

Note 1: Carriers in increasing frequency order.



Test frequencies for CA_41C

Table 4.3.1.2.9A-1: Test frequencies for CA_41C

| Range | CC-Combo / N _{RB_agg} [RB] | CC1 Note1 | | | CC2 Note1 | | |
|-------|---|--------------|--------------------|-----------------------------|--------------|--------------------|-----------------------------|
| | | BW [RB] | N _{UL/DL} | f _{UL/DL} [MHz] | BW [RB] | N _{UL/DL} | f _{UL/DL} [MHz] |
| Low | 25+100 | 25 | 39683 | 2499.3 | 100 | 39800 | 2511 |
| | | 100 | 39750 | 2506 | 25 | 39867 | 2517.7 |
| | 50+75 | 50 | 39703 | 2501.3 | 75 | 39823 | 2513.3 |
| | | 75 | 39725 | 2503.5 | 50 | 39845 | 2515.5 |
| | 50+100 | 50 | 39705 | 2501.5 | 100 | 39849 | 2515.9 |
| | | 100 | 39750 | 2506 | 50 | 39894 | 2520.4 |
| | 75+75 | 75 | 39725 | 2503.5 | 75 | 39875 | 2518.5 |
| | | 75 | 39728 | 2503.8 | 100 | 39899 | 2520.9 |
| | 75+100 | 100 | 39750 | 2506 | 75 | 39921 | 2523.1 |
| | | 100 | 39750 | 2506 | 100 | 39948 | 2525.8 |
| Mid | 25+100 | 25 | 40528 | 2583.8 | 100 | 40645 | 2595.5 |
| | | 100 | 40595 | 2590.5 | 25 | 40712 | 2602.2 |
| | 50+75 | 50 | 40549 | 2585.9 | 75 | 40669 | 2597.9 |
| | | 75 | 40571 | 2588.1 | 50 | 40691 | 2600.1 |
| | 50+100 | 50 | 40526 | 2583.6 | 100 | 40670 | 2598.0 |
| | | 100 | 40571 | 2588.1 | 50 | 40715 | 2602.5 |
| | 75+75 | 75 | 40545 | 2585.5 | 75 | 40695 | 2600.5 |
| | | 75 | 40523 | 2583.3 | 100 | 40694 | 2600.4 |
| | 75+100 | 100 | 40546 | 2585.6 | 75 | 40717 | 2602.7 |
| | | 100 | 40521 | 2583.1 | 100 | 40719 | 2602.9 |
| High | 25+100 | 25 | 41373 | 2668.3 | 100 | 41490 | 2680 |
| | | 100 | 41440 | 2675 | 25 | 41557 | 2686.7 |
| | 50+75 | 50 | 41395 | 2670.5 | 75 | 41515 | 2682.5 |
| | | 75 | 41417 | 2672.7 | 50 | 41537 | 2684.7 |
| | 50+100 | 50 | 41346 | 2665.6 | 100 | 41490 | 2680 |
| | | 100 | 41391 | 2670.1 | 50 | 41535 | 2684.5 |
| | 75+75 | 75 | 41365 | 2667.5 | 75 | 41515 | 2682.5 |
| | | 75 | 41319 | 2662.9 | 100 | 41490 | 2680 |
| | 75+100 | 100 | 41341 | 2665.1 | 75 | 41512 | 2682.2 |
| | | 100 | 41292 | 2660.2 | 100 | 41490 | 2680 |

Note 1: Carriers in increasing frequency order.



3.6 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China.
518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

3.7 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

• **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

• **VCCI**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

• **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

• **Industry Canada (IC)**

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

3.8 Deviation from Standards

None.

3.9 Abnormalities from Standard Conditions

None.



3.10 Other Information Requested by the Customer

None.

3.11 Technical Specification

| Characteristics | Description | |
|---------------------------|-------------------------------------|-------------------------------------|
| Radio System Type | <input checked="" type="checkbox"/> | GSM |
| | <input checked="" type="checkbox"/> | UMTS |
| | <input checked="" type="checkbox"/> | LTE |
| Supported Frequency Range | GSM850 | Transmission (TX):824 to 849 MHz |
| | | Receiving (RX):869 to 894 MHz |
| | GSM1900 | Transmission (TX):1850 to 1910 MHz |
| | | Receiving (RX): 1930 to 1990 MHz |
| | UMTS BAND II | Transmission (TX):1850 to 1910 MHz |
| | | Receiving (RX):1930 to 1990 MHz |
| | UMTS BAND IV | Transmission (TX):1710 to 1755 MHz |
| | | Receiving (RX): 2110 to 2155 MHz |
| | UMTS BAND V | Transmission (TX):824 to 849 MHz |
| | | Receiving (RX):869 to 894 MHz |
| | LTE BAND 2 | Transmission (TX):1850 to 1910 MHz |
| | | Receiving (RX):1930 to 1990 MHz |
| | LTE BAND 4 | Transmission (TX):1710 to 1755 MHz |
| | | Receiving (RX): 2110 to 2155 MHz |
| | LTE BAND 5 | Transmission (TX): 824 to 849 MHz |
| | | Receiving (RX): 869 to 894 MHz |
| | LTE BAND 7 | Transmission (TX): 2500 to 2570 MHz |
| | | Receiving (RX): 2620 to 2690 MHz |
| | LTE BAND 12 | Transmission (TX):699 to 716 MHz |
| | | Receiving (RX): 729 to 746 MHz |
| | LTE BAND 17 | Transmission (TX):704 to 716 MHz |
| | | Receiving (RX): 734 to 746 MHz |
| | LTE BAND 26 (814 to 824 MHz) | Transmission (TX): 814 to 824MHz |
| | | Receiving (RX): 859 to 869 MHz |
| | LTE BAND 26 (824 to 849 MHz) | Transmission (TX):824 to 849 MHz |
| | | Receiving (RX):869 to 894 MHz |
| | LTE BAND 38 | Transmission (TX):2570 to 2620 MHz |
| | | Receiving (RX): 2570 to 2620 MHz |
| LTE BAND 41 | Transmission (TX):2496 to 2690MHz | |
| | Receiving (RX): 2496 to 2690MHz | |
| LTE CA_5B | Transmission (TX): 824 to 849 MHz | |
| | Receiving (RX): 869 to 894 MHz | |



| | | |
|------------------------|--|--|
| | LTE CA_7C | Transmission (TX): 2500 to 2570 MHz |
| | | Receiving (RX):2620 to 2690 MHz |
| | LTE CA_38C | Transmission (TX): 2570 to 2620 MHz |
| | | Receiving (RX): 2570 to 2620 MHz |
| | LTE CA_41C | Transmission (TX):2496 to 2690MHz |
| | | Receiving (RX): 2496 to 2690MHz |
| Target TX Output Power | GSM850:33 dBm GSM1900: 30dBm UMTS BAND II: 23dBm UMTS BAND IV: 23dBm UMTS BAND V: 23dBm LTE BAND 2: 25dBm LTE BAND 4: 25.2dBm LTE BAND 5: 25.5dBm LTE BAND 7: 24.7dBm LTE BAND12: 25.5dBm LTE BAND17: 25.5dBm LTE BAND26: 25.5dBm LTE BAND38: 25.2dBm LTE BAND41: 25.2dBm LTE BAND CA_5B: 25.5dBm LTE BAND CA_7C: 24.7dBm LTE BAND CA_38C: 25.2dBm LTE BAND CA_41C: 25.2dBm | |
| Supported Bandwidth | Channel | GSM system: <input checked="" type="checkbox"/> 0.2 MHz |
| | | UMTS system: <input checked="" type="checkbox"/> 5 MHz |
| | | LTE BAND 2 <input checked="" type="checkbox"/> 1.4 MHz; <input checked="" type="checkbox"/> 3 MHz; <input checked="" type="checkbox"/> 5 MHz; <input checked="" type="checkbox"/> 10 MHz; <input checked="" type="checkbox"/> 15 MHz, <input checked="" type="checkbox"/> 20 MHz |
| | | LTE BAND 4 <input checked="" type="checkbox"/> 1.4 MHz; <input checked="" type="checkbox"/> 3 MHz; <input checked="" type="checkbox"/> 5 MHz; <input checked="" type="checkbox"/> 10 MHz; <input checked="" type="checkbox"/> 15 MHz, <input checked="" type="checkbox"/> 20 MHz |
| | | LTE BAND 5 <input checked="" type="checkbox"/> 1.4 MHz; <input checked="" type="checkbox"/> 3 MHz; <input checked="" type="checkbox"/> 5 MHz; <input checked="" type="checkbox"/> 10 MHz |
| | | LTE BAND 7 <input checked="" type="checkbox"/> 5 MHz; <input checked="" type="checkbox"/> 10 MHz; <input checked="" type="checkbox"/> 15 MHz, <input checked="" type="checkbox"/> 20 MHz |
| | | LTE BAND 12 <input checked="" type="checkbox"/> 1.4 MHz; <input checked="" type="checkbox"/> 3 MHz; <input checked="" type="checkbox"/> 5 MHz; <input checked="" type="checkbox"/> 10 MHz |
| | | LTE BAND 17 <input checked="" type="checkbox"/> 5 MHz; <input checked="" type="checkbox"/> 10 MHz |
| | | LTE BAND 26 (814-824) <input checked="" type="checkbox"/> 1.4 MHz; <input checked="" type="checkbox"/> 3 MHz; <input checked="" type="checkbox"/> 5 MHz; <input checked="" type="checkbox"/> 10 MHz; |
| | | LTE BAND 26 (824-849) <input checked="" type="checkbox"/> 1.4 MHz; <input checked="" type="checkbox"/> 3 MHz; <input checked="" type="checkbox"/> 5 MHz; <input checked="" type="checkbox"/> 10 MHz; <input checked="" type="checkbox"/> 15 MHz |
| | | LTE BAND38 <input checked="" type="checkbox"/> 5 MHz; <input checked="" type="checkbox"/> 10 MHz; <input checked="" type="checkbox"/> 15 MHz, <input checked="" type="checkbox"/> 20 MHz |
| | | LTE BAND41 <input checked="" type="checkbox"/> 5 MHz; <input checked="" type="checkbox"/> 10 MHz; <input checked="" type="checkbox"/> 15 MHz, <input checked="" type="checkbox"/> 20 MHz |
| | | LTE BAND CA_5B <input checked="" type="checkbox"/> 25+50; <input checked="" type="checkbox"/> 50+25; <input checked="" type="checkbox"/> 50+50 |
| | | LTE BAND CA_7C <input checked="" type="checkbox"/> 50+100; <input checked="" type="checkbox"/> 75+50; <input checked="" type="checkbox"/> 75+75, <input checked="" type="checkbox"/> 75+100 |



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM180700654901

Page: 23 of 36

| | | |
|---|--------------------------|---|
| | | <input checked="" type="checkbox"/> 100+100 |
| | LTE BAND CA_38C | <input checked="" type="checkbox"/> 75+75; <input checked="" type="checkbox"/> 100+100; |
| | LTE BAND CA_41C | <input checked="" type="checkbox"/> 25+100; <input checked="" type="checkbox"/> 50+75; <input checked="" type="checkbox"/> 50+100; <input checked="" type="checkbox"/> 75+75; <input checked="" type="checkbox"/> 75+100, <input checked="" type="checkbox"/> 100+100 |
| Characteristics | Description | |
| Designation of Emissions (Note: the necessary bandwidth of which is the worst value from the measured occupied bandwidths for each type of channel bandwidth configuration.) | GSM850 | 246KGXW,256KG7W |
| | GSM1900 | 243KGXW,253KG7W |
| | UMTS BAND II | 4M17F9W |
| | UMTS BAND IV | 4M17F9W |
| | UMTS BAND V | 4M17F9W |
| | LTE BAND 2 | 1M10G7D;1M10W7D; 1M10W7D 2M70G7D;2M70W7D; 2M70W7D 4M48G7D;4M48W7D; 4M48W7D 8M93G7D;8M95W7D; 8M93W7D 13M5G7D;13M5W7D; 13M5W7D 17M9G7D;18M0W7D; 17M9W7D |
| | LTE BAND 4 | 1M10G7D;1M09W7D; 1M10W7D 2M70G7D;2M70W7D; 2M70W7D 4M48G7D;4M49W7D; 4M49W7D 8M95G7D;8M95W7D; 8M97W7D 13M5G7D;13M5W7D; 13M5W7D 17M9G7D;17M9W7D; 17M9W7D |
| | LTE BAND 5 | 1M10G7D;1M09W7D; 1M09W7D 2M70G7D;2M70W7D; 2M70W7D 4M48G7D;4M49W7D; 4M48W7D 8M95G7D;8M95W7D; 8M95W7D |
| | LTE BAND 7 | 4M48G7D;4M48W7D; 4M48W7D 8M95G7D;8M95W7D; 8M95W7D 13M5G7D;13M5W7D; 13M5W7D 17M9G7D;17M9W7D; 18M0W7D |
| | LTE BAND 12 | 1M10G7D;1M09W7D; 1M09W7D 2M70G7D;2M70W7D; 2M70W7D 4M49G7D;4M48W7D; 4M48W7D 8M95G7D;8M95W7D; 8M95W7D |
| | LTE BAND 17 | 4M50G7D;4M49W7D; 4M48W7D 8M95G7D;8M95W7D; 8M93W7D |
| | LTE BAND 26 (814-824) | 1M10G7D;1M10W7D; 1M10W7D 2M70G7D;2M70W7D; 2M70W7D 4M48G7D;4M49W7D; 4M48W7D 8M95G7D;8M95W7D; 8M95W7D |
| | LTE BAND 26 (824-849) | 1M10G7D;1M10W7D; 1M09W7D 2M69G7D;2M70W7D; 2M70W7D |

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



| | | |
|--|-----------------|--|
| | | 4M49G7D;4M48W7D; 4M48W7D 8M95G7D;8M95W7D; 8M95W7D 13M5G7D;13M5W7D; 13M5W7D |
| | LTE BAND 38 | 4M49G7D;4M48W7D; 4M48W7D 8M95G7D;8M95W7D; 8M95W7D 13M5G7D;13M5W7D; 13M5W7D 18M0G7D;17M9W7D; 17M9W7D |
| | LTE BAND 41 | 4M48G7D;4M47W7D; 4M48W7D 8M91G7D;8M95W7D; 8M95W7D 13M5G7D;13M5W7D; 13M5W7D 17M9G7D;18M0W7D; 17M9W7D |
| | LTE BAND CA_5B | 14M0G7D;14M0W7D; 13M9W7D 18M8G7D;18M8W7D; 18M9W7D |
| | LTE BAND CA_7C | 28M4G7D;28M3W7D; 28M3W7D 37M6G7D;37M6W7D; 37M6W7D |
| | LTE BAND CA_38C | 28M3G7D;28M4W7D; 28M4W7D 37M5G7D;37M6W7D; 37M6W7D |
| | LTE BAND CA_41C | 22M9G7D;22M9W7D; 22M9W7D 37M6G7D;37M6W7D; 37M6W7D |

4 Description of Tests

4.1 Conducted Output Power

Measurement Procedure: FCC KDB 971168 D01 V03r01

The transmitter output was connected to a calibrated coaxial cable, attenuator and power meter, the other end of which was connected to a Base Station Simulator. The Base Station Simulator was set to force the EUT to its maximum power setting. The power output at the transmitter antenna port was determined by adding the value of the cable insertion loss to the power reading. The tests were performed at three frequencies (low channel, middle channel and high channel) and on the highest power levels, which can be setup on the transmitters.

Note: Reference test setup 1

4.2 Effective (Isotropic) Radiated Power of Transmitter

Measurement Procedure: FCC KDB 971168 D01 V03r01 ; ANSI/TIA-603-E-2016-Section 2.2.17

Below 1GHz test procedure as below:

- 1). The EUT was powered ON and placed on a 0.8m high table in the chamber. The antenna of the transmitter was extended to its maximum length.
- 2). The disturbance of the transmitter was maximized on the test receiver display by raising and lowering from 1m to 4m the receive antenna and by rotating through 360° the turntable. After the fundamental emission was maximized, a field strength measurement was made.



- 3). Steps 1) and 2) were performed with the EUT and the receive antenna in both vertical and horizontal polarization.
- 4). The transmitter was then removed and replaced with another antenna. The center of the antenna was approximately at the same location as the center of the transmitter.
- 5). A signal at the disturbance was fed to the substitution antenna by means of a non-radiating cable. With both the substitution and the receive antennas horizontally polarized, the receive antenna was raised and lowered to obtain a maximum reading at the test receiver. The level of the signal generator was adjusted until the measured field strength level in step 2) is obtained for this set of conditions.
- 6). The output power into the substitution antenna was then measured.
- 7). Steps 5) and 6) were repeated with both antennas polarized.
- 8). Calculate power in dBm by the following formula:

$$\text{ERP (dBm)} = \text{Pg(dBm)} - \text{cable loss (dB)} + \text{antenna gain (dBd)}$$

Where:

Pg is the generator output power into the substitution antenna.

Above 1GHz test procedure as below:

- 1). Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber
- 2). Calculate power in dBm by the following formula:
$$\text{EIRP(dBm)} = \text{Pg(dBm)} - \text{cable loss (dB)} + \text{antenna gain (dBi)}$$
$$\text{EIRP} = \text{ERP} + 2.15\text{dB}$$
- Where:
Pg is the generator output power into the substitution antenna.
- 3). Test the EUT in the lowest channel, the middle channel the Highest channel
- 4). The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, Only the test worst case mode is recorded in the report.
- 5). Repeat above procedures until all frequencies measured was complete.

Note: Reference test setup 2

4.3 Occupied Bandwidth

Measurement Procedure: FCC KDB 971168 D01 V03r01 Section 4.2

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. The transmitter output was connected to a calibrated coaxial cable, attenuator and Spectrum analyser, the other end of which was connected to a Base Station Simulator. The Base Station Simulator was set to force the EUT to its maximum power setting. The tests were performed at three frequencies (low channel, middle channel and high channel). The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts. The resolution bandwidth shall be set to as close to 1 percent of the selected span as is possible without being below 1 percent. The video bandwidth shall be set to 3 times the resolution bandwidth. Video averaging is not permitted. Where practical, a sampling detector shall be used since a peak or, peak hold, may produce a wider bandwidth than actual. The trace data points are recovered and are directly summed in linear terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 percent of the total is reached and that frequency recorded. The process is repeated for the highest frequency data points. This frequency is recorded. The span between the two recorded frequencies is the occupied bandwidth.



Note: Reference test setup 1

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW \geq 3 x RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

4.4 Band Edge at Antenna Terminals

Measurement Procedure: FCC KDB 971168 D01 V03r01 Section 6.0

The transmitter output was connected to a calibrated coaxial cable, attenuator and Spectrum analyser, the other end of which was connected to a Base Station Simulator. The Base Station Simulator was set to force the EUT to its maximum power setting. The tests were performed at three frequencies (low channel and high channel).in the 1MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of 100kHz or 1% of the emission bandwidth of the fundamental emission of the transmitter may be employed. The EUT emission bandwidth is measured as the width of the signal between two points, outside of which all emission are attenuated at least 26dB below the transmitter power. The video bandwidth of the spectrum analyzer was set at thrice the resolution bandwidth. Detector Mode was set to peak or peak hold power.

Note: Reference test setup 1

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW \geq 1% of the emission bandwidth
4. VBW \geq 3 x RBW
5. Detector = RMS
6. Number of sweep points \geq 2 x Span/RBW
7. Trace mode = trace average for continuous emissions, max hold for pulse emissions
8. Sweep time = auto couple
9. The trace was allowed to stabilize

4.5 Spurious And Harmonic Emissions at Antenna Terminal

Measurement Procedure: FCC KDB 971168 D01 V03r01

The transmitter output was connected to a calibrated coaxial cable, attenuator and Spectrum analyzer, the other end of which was connected to a Base Station Simulator. The Base Station Simulator was set to force the EUT to its maximum power setting. The tests were performed at three frequencies (low channel



and high channel). The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB. Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

Note: Reference test setup 1

Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to at least $10 \times$ the fundamental frequency (separated into at least two plots per channel)
2. Detector = RMS
3. Trace mode = trace average for continuous emissions, max hold for pulse emissions
4. Sweep time = auto couple
5. The trace was allowed to stabilize
6. Please see test notes below for RBW and VBW settings

4.6 Peak-Average Ratio

Measurement Procedure: FCC KDB 971168 D01 V03r01 Section 5.7.1

A peak to average ratio measurement is performed at the conducted port of the EUT. For WCDMA signals, the spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level. For GSM signals, an average and a peak trace are used on a spectrum analyzer to determine the largest deviation between the average and the peak power of the EUT in a bandwidth greater than the emission bandwidth. The traces are generated with the spectrum analyzer set to zero span mode.

Note: Reference test setup 1

Test Settings

1. The signal analyzer's CCDF measurement profile is enabled
2. Frequency = carrier center frequency
3. Measurement BW > Emission bandwidth of signal
4. The signal analyzer was set to collect one million samples to generate the CCDF curve
5. The measurement interval was set depending on the type of signal analyzed. For continuous signals (>98% duty cycle), the measurement interval was set to 1ms. For burst transmissions, the spectrum analyzer is set to use an internal "RF Burst" trigger that is synced with an incoming pulse and the measurement interval is set to less than the duration of the "on time" of one burst to ensure that energy is only captured during a time in which the transmitter is operating at maximum power

4.7 Field Strength of Spurious Radiation

Measurement Procedure: FCC KDB 971168 D01 V03r01

Below 1GHz test procedure as below:



- 1). The EUT was powered ON and placed on a 80cm high table in the chamber. The antenna of the transmitter was extended to its maximum length.
- 2). The disturbance of the transmitter was maximized on the test receiver display by raising and lowering from 1m to 4m (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) the receive antenna and by rotating through 360° the turntable. After the fundamental emission was maximized, a field strength measurement was made.
- 3). Steps 1) and 2) were performed with the EUT and the receive antenna in both vertical and horizontal polarization.
- 4). The transmitter was then removed and replaced with another antenna. The center of the antenna was approximately at the same location as the center of the transmitter.
- 5). A signal at the disturbance was fed to the substitution antenna by means of a non-radiating cable. With both the substitution and the receive antennas horizontally polarized, the receive antenna was raised and lowered to obtain a maximum reading at the test receiver. The level of the signal generator was adjusted until the measured field strength level in step 2) is obtained for this set of conditions.
- 6). The output power into the substitution antenna was then measured.
- 7). Steps 5) and 6) were repeated with both antennas polarized.
- 8) Calculate power in dBm by the following formula:

$$\text{ERP(dBm)} = \text{Pg(dBm)} - \text{cable loss (dB)} + \text{antenna gain (dBd)}$$

Where:

Pd is the dipole equivalent power, Pg is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to Pg [dBm] – cable loss [dB]. The calculated Pd levels are then compared to the absolute spurious emission limit of -13dBm which is equivalent to the required minimum attenuation of $43 + 10\log_{10}(\text{Power [Watts]})$.

Above 1GHz test procedure as below:

- 1) Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber
- 2) Calculate power in dBm by the following formula:

$$\text{EIRP(dBm)} = \text{Pg(dBm)} - \text{cable loss (dB)} + \text{antenna gain (dBi)}$$

$$\text{EIRP} = \text{ERP} + 2.15\text{dB}$$

Where:

Pg is the generator output power into the substitution antenna.

3. Test the EUT in the lowest channel, the middle channel the Highest channel
4. The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, Only the test worst case mode is recorded in the report.
5. Repeat above procedures until all frequencies measured was complete

Note: Reference test setup 3

4.8 Frequency Stability / Temperature Variation

Measurement Procedure:

Frequency stability testing is performed in accordance with the guidelines of FCC KDB 971168 D01 V03r01; ANSI/TIA-603-E-2016

. The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment,

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

Specification – The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ (± 2.5 ppm) of the center frequency.


Time Period and Procedure:

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

Note: Reference test setup 4

4.9 Test Setups

Test Setup 1



Test Setup 2




Figure 1. 30MHz to 1GHz




Figure 2. above 1GHz

Test Setup 3




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz





Figure 3. above 1GHz

Test Setup 4





4.10 Test Conditions

| Test Case | | Test Conditions | |
|-------------------------------------|---|--|--|
| Transmit Output Power Data | Average Power, Total | Test Environment | Ambient Climate & Rated Voltage |
| | | Test Setup | Test Setup 1 |
| | | RF Channels (TX) | L, M, H (L= low channel, M= middle channel, H= high channel) |
| | | Test Mode | GSM/TM1;GSM/TM2;UMTS/TM1; UMTS/TM2; LTE/TM1;LTE/TM2; LTE/TM3 |
| | Average Power, Spectral Density (if required) | Test Environment | Ambient Climate & Rated Voltage |
| | | Test Setup | Test Setup 1 |
| | | RF Channels (TX) | L, M, H (L= low channel, M= middle channel, H= high channel) |
| | | Test Mode | GSM/TM1;GSM/TM2;UMTS/TM1; UMTS/TM2; TM1;LTE/TM1;LTE/TM2; LTE/TM3 |
| Peak-to-Average Ratio (if required) | Test Environment | Ambient Climate & Rated Voltage | |
| | Test Setup | Test Setup 1 | |
| | RF Channels (TX) | L, M, H (L= low channel, M= middle channel, H= high channel) | |
| | Test Mode | GSM/TM1;GSM/TM2;UMTS/TM1; UMTS/TM2; TM1;LTE/TM1;LTE/TM2; LTE/TM3 | |
| Modulation Characteristics | Test Environment | Ambient Climate & Rated Voltage | |
| | Test Setup | Test Setup 1 | |
| | RF Channels (TX) | M (M= middle channel) | |
| | Test Mode | GSM/TM1;GSM/TM2;UMTS/TM1; UMTS/TM2; LTE/TM1;LTE/TM2; LTE/TM3 | |
| Bandwidth | Occupied Bandwidth | Test Environment | Ambient Climate & Rated Voltage |
| | | Test Setup | Test Setup 1 |
| | | RF Channels (TX) | L, M, H (L= low channel, M= middle channel, H= high channel) |
| | | Test Mode | GSM/TM1;GSM/TM2;UMTS/TM1; UMTS/TM2; LTE/TM1;LTE/TM2; LTE/TM3 |
| | Emission Bandwidth (if required) | Test Environment | Ambient Climate & Rated Voltage |
| | | Test Setup | Test Setup 1 |
| | | RF Channels (TX) | L, M, H (L= low channel, M= middle channel, H= high channel) |
| | | Test Mode | GSM/TM1;GSM/TM2;UMTS/TM1; UMTS/TM2; LTE/TM1;LTE/TM2; LTE/TM3 |
| Band Edges Compliance | Test Environment | Ambient Climate & Rated Voltage | |
| | Test Setup | Test Setup 1 | |
| | RF Channels (TX) | L, H (L= low channel, H= high channel) | |



**SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch**

Report No.: SZEM180700654901

Page: 33 of 36

| | | |
|--|------------------|--|
| | Test Mode | GSM/TM1;GSM/TM2;UMTS/TM1; UMTS/TM2; LTE/TM1;LTE/TM2 ; LTE/TM3 |
| Spurious Emission at Antenna Terminals | Test Environment | Ambient Climate & Rated Voltage |
| | Test Setup | Test Setup 1 |
| | RF Channels (TX) | L,M, H (L= low channel, M= middle channel, H= high channel) |
| | Test Mode | GSM/TM1;UMTS/TM1; LTE/TM1 |
| Field Strength of Spurious Radiation | Test Environment | Ambient Climate & Rated Voltage |
| | Test Setup | Test Setup 2 |
| | Test Mode | GSM/TM1;GSM/TM2;UMTS/TM1;UMTS/TM2; LTE/TM1;LTE/TM2; LTE/TM3 NOTE: If applicable, the EUT conf. that has maximum power density (based on the equivalent power level) is selected. |
| | RF Channels (TX) | L, M, H (L= low channel, M= middle channel, H= high channel) |
| Frequency Stability | Test Environment | (1) -30 °C to +50 °C with step 10 °C at Rated Voltage; (2) VL, VN and VH of Rated Voltage at Ambient Climate. |
| | Test Setup | Test Setup 4 |
| | RF Channels (TX) | L, M, H (L= low channel, M= middle channel, H= high channel) |
| | Test Mode | GSM/TM1;GSM/TM2;UMTS/TM1; UMTS/TM2; LTE/TM1;LTE/TM2; LTE/TM3 |



5 Main Test Instruments

| RE in Chamber | | | | | | |
|---------------|--------------------------------------|------------------------------------|-------------------|---------------|---------------------------|------------------------------|
| Item | Test Equipment | Manufacturer | Model No. | Inventory No. | Cal. date (yyyy-mm-dd) | Cal.Due date (yyyy-mm-dd) |
| 1 | 3m Semi-Anechoic Chamber | ETS-LINDGREN | N/A | SEM001-01 | 2018/03/13 | 2021/03/12 |
| 2 | 3m Semi-Anechoic Chamber | AUDIX | N/A | SEM001-02 | 2018/03/13 | 2021/03/12 |
| 3 | EMI Test Receiver | Agilent Technologies | N9038A | SEM004-05 | 2017/10/09 | 2018/10/09 |
| 4 | EXA Signal Analyzer (10Hz-26.5GHz) | Agilent Technologies Inc | N9010A | SEM004-09 | 2018/04/13 | 2019/04/12 |
| 5 | BiConiLog Antenna (26-3000MHz) | ETS-LINDGREN | 3142C | SEM003-02 | 2017/11/15 | 2020/11/15 |
| 6 | Double-ridged horn (1-18GHz) | ETS-LINDGREN | 3117 | SEM003-11 | 2015/10/17 | 2018/10/17 |
| 7 | Horn Antenna (18-26GHz) | ETS-LINDGREN | 3160 | SEM003-12 | 2017/11/24 | 2020/11/24 |
| 8 | Horn Antenna (15GHz-40GHz) | Schwarzbeck | BBHA 9170 | SEM003-15 | 2017/10/17 | 2020/10/17 |
| 9 | Low Noise Amplifier (100MHz-18GHz) | Black Diamond Series | BDLNA-0118-352810 | SEM005-05 | 2017/09/27 | 2018/09/26 |
| 10 | Band filter | N/A | N/A | N/A | N/A | N/A |
| 11 | Pre-amplifier (0.1-1300MHz) | Agilent Technologies | 8447D | SEM005-01 | 2018/03/13 | 2019/03/12 |
| 12 | Pre-Amplifier (0.1-26.5GHz) | Compliance Directions Systems Inc. | PAP-0126 | SEM004-10 | 2017/10/17 | 2018/10/17 |
| 13 | Pre-amplifier (26GHz-40GHz) | Compliance Directions Systems Inc. | PAP-2640-50 | SEM005-08 | 2018/03/14 | 2019/03/14 |
| 14 | Band filter | Amindeon | 82346 | SEM023-01 | N/A | N/A |
| 15 | Universal radio communication tester | Rohde & Schwarz | CMU200 | SEM010-01 | 2017/10/09 | 2018/10/09 |
| 16 | Universal radio communication tester | Rohde & Schwarz | CMW500 | SEM010-03 | 2017/10/23 | 2018/10/23 |
| 17 | DC Power Supply | Zhao Xin | RXN-305D | SEM011-02 | 2017/10/09 | 2018/10/09 |
| 18 | BiConiLog Antenna (30MHz-3GHz) | Schwarzbeck | VULB9163 | SEM003-05 | 2015/10/17 | 2018/10/17 |
| 19 | Horn Antenna (800MHz-18GHz) | Rohde & Schwarz | HF907 | SEM003-06 | 2018/06/06 | 2021/06/06 |



| RE in Chamber | | | | | | |
|---------------|------------------------------------|----------------------|-----------|---------------|------------------------|----------------------------|
| Item | Test Equipment | Manufacturer | Model No. | Inventory No. | Cal. Date (yyyy mm-dd) | Cal. Due date (yyyy-mm-dd) |
| 1 | 10m Semi-Anechoic Chamber | SAEMC | FSAC1018 | SEM001-03 | 2018/03/10 | 2019/03/09 |
| 2 | EMI Test Receiver (9k-7GHz) | Rohde & Schwarz | ESR | SEM004-03 | 2018/02/14 | 2019/02/14 |
| 3 | Trilog-Broadband Antenna(30M-1GHz) | Schwarzbeck | VULB9168 | SEM003-18 | 2016/06/29 | 2019/06/29 |
| 4 | Pre-amplifier | Sonoma Instrument Co | 310N | SEM005-03 | 2018/06/06 | 2019/06/05 |
| 5 | .Loop Antenna | ETS-Lindgren | 6502 | SEM003-08 | 2018/07/14 | 2021/07/13 |

| RF connected test | | | | | | |
|-------------------|--|--------------------------|------------------|---------------|------------------------|---------------------------|
| Item | Test Equipment | Manufacturer | Model No. | Inventory No. | Cal. date (yyyy-mm-dd) | Cal.Due date (yyyy-mm-dd) |
| 1 | Humi/ Temp Indicator | MingGao | TH101B | W006-09 | 2018/03/13 | 2019/03/12 |
| 2 | Signal Analyzer | Rohde Schwarz | FSV | W025-02 | 2018/03/13 | 2019/03/12 |
| 3 | Spectrum Analyzer (20Hz-43GHz) | Rohde & Schwarz | FSU43 | SEM004-08 | 2018/04/14 | 2019/04/13 |
| 4 | Barometer | ChangChun | DYM3 | SEL0088 | 2018/05/24 | 2019/05/24 |
| 5 | Dual Output Mobile Communication DC Source | Agilent Technologies Inc | 66311B | W009-09 | 2018/04/28 | 2019/04/28 |
| 6 | Digital Multimeter | Fluke | 15B+ | W055-01 | 2018/03/13 | 2019/03/12 |
| 7 | Wideband Radio Communication Tester | Rohde & Schwarz | CMW500 | W005-02 | 2018/03/13 | 2019/03/12 |
| 8 | Temperature Chamber | GIANT FORCE | ICT-150-40-CP-AR | W027-04 | 2017/12/04 | 2018/12/04 |
| 9 | Wideband Radio Communication Teste | Anristu | MT8821C | 6201462742 | 2018/05/02 | 2019/05/01 |



6 Measurement Uncertainty

For a 95% confidence level ($k = 2$), the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 as following:

| Test Item | Extended Uncertainty | Data |
|--------------------------------------|--------------------------|---|
| Transmit Output Power Data | Power [dBm] | $U = \pm 0.37$ dB |
| Bandwidth | Magnitude [%] | $U = \pm 0.2\%$ |
| Band Edge Compliance | Disturbance Power [dBm] | $U = \pm 2.0$ dB |
| Spurious Emissions, Conducted | Disturbance Power [dBm] | $U = \pm 2.0$ dB |
| Field Strength of Spurious Radiation | ERP[dBm]/EIRP [dBm] | For 3 m Chamber: $U = \pm 4.5$ dB (30 MHz to 1GHz) $U = \pm 3.3$ dB (above 1 GHz) For 10 m Chamber: $U = \pm 4.5$ dB (30 MHz to 1GHz) $U = \pm 3.2$ dB (above 1 GHz) |
| Frequency Stability | Frequency Accuracy [ppm] | $U = \pm 0.24$ ppm |

7 Photographs - EUT Constructional Details

Refer to Appendix A - Photographs of EUT Constructional Details for SZEM1807006549RG.

The End