

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053
 Fax: +86 (0) 755 2671 0594
 Email: ee.shenzhen@sgs.com

Report No.: HR/2018/B000302
 Page: 1 of 47


FCC TEST REPORT

Application No: HR/2018/B0003
Applicant: Huawei Technologies Co.,Ltd
Address of Applicant: Administration Buliding Headquarters of Huawei Technologies Co.,Ltd.Bantian,longgang District 518129 Shenzhen PEOPLE'S REPUBLIC OF CHINA
Manufacturer: Huawei Technologies Co.,Ltd
Address of Manufacturer: Administration Buliding Headquarters of Huawei Technologies Co.,Ltd.Bantian,longgang District 518129 Shenzhen PEOPLE'S REPUBLIC OF CHINA
EUT Description: Mobile WiFi
Model No.: HW-01L
Trade Mark: HUAWEI
FCC ID: QISHW-01L
Standards: 47 CFR FCC Part 2, Subpart J
 47 CFR Part 15, Subpart C
 KDB558074 D01 15.247 Meas Guidance v05
Test Method: ANSI C63.4(2014)
 ANSI C63.10 (2013)
Date of Receipt: 2018/11/8
Date of Test: 2018/11/8 to 2018/11/30
Date of Issue: 2018/12/11

Test Result:	PASS *
---------------------	---------------

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Derek Yang
 Wireless Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.



1 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
00		2018/12/11		Original

Authorized for issue by:				
Tested By		 <hr/> (Mike Hu) /Project Engineer		2018/12/11
				Date
Checked By		 <hr/> (David Chen) /Reviewer		2018/12/11
				Date



2 Test Summary

Test Item	Test Requirement	Test method	Test Result	Result
AC Power Line Conducted Emission	15.207	ANSI C63.10 2013	Clause 4.3	PASS
Conducted Output Power	15.247 (b)(3)	ANSI C63.10 2013	Clause 4.4	PASS
DTS (6 dB) Bandwidth & 99% Occupied Bandwidth	15.247 (a)(2)	ANSI C63.10 2013	Clause 4.5	PASS
Power Spectral Density	15.247 (e)	ANSI C63.10 2013	Clause 4.6	PASS
Band-edge for RF Conducted Emissions	15.247(d)	ANSI C63.10 2013	Clause 4.7	PASS
RF Conducted Spurious Emissions	15.247(d)	ANSI C63.10 2013	Clause 4.8	PASS
Radiated Spurious Emissions	15.205/15.209	ANSI C63.10 2013	Clause 4.9	PASS
Restricted bands around fundamental frequency (Radiated Emission)	15.205/15.209	ANSI C63.10 2013	Clause 4.10	PASS



Contents

1	VERSION	2
2	TEST SUMMARY	3
3	GENERAL INFORMATION	5
3.1	CLIENT INFORMATION	5
3.2	TEST LOCATION	5
3.3	TEST FACILITY.....	5
3.4	GENERAL DESCRIPTION OF EUT.....	6
3.5	TEST ENVIRONMENT.....	7
3.6	DESCRIPTION OF SUPPORT UNITS	7
4	TEST RESULTS AND MEASUREMENT DATA	8
4.1	ANTENNA REQUIREMENT	8
4.2	DUTY CYCLE	9
4.2.1	<i>Test Results</i>	9
4.2.1	<i>Test Plots</i>	9
4.3	AC POWER LINE CONDUCTED EMISSIONS	10
4.4	CONDUCTED OUTPUT POWER	13
4.4.1	<i>Test Results</i>	13
4.4.2	<i>Test plots</i> :.....	14
4.5	DTS (6 dB) BANDWIDTH & 99% OCCUPIED BANDWIDTH.....	16
4.5.1	<i>Test Results</i>	16
4.5.2	<i>Test plots</i>	17
4.6	POWER SPECTRAL DENSITY.....	20
4.6.1	<i>Test Results</i>	20
4.6.2	<i>Test plots</i>	21
4.7	BAND-EDGE FOR RF CONDUCTED EMISSIONS	23
4.7.1	<i>Test plots</i>	24
4.8	SPURIOUS RF CONDUCTED EMISSIONS	25
4.8.1	<i>Test plots</i> :.....	26
4.9	RADIATED SPURIOUS EMISSION.....	28
4.9.1	<i>Radiated Emission below 1GHz</i>	31
4.9.2	<i>Transmitter Emission above 1GHz</i>	33
4.10	RESTRICTED BANDS AROUND FUNDAMENTAL FREQUENCY.....	40
4.10.1	<i>Test plots</i>	41
5	MEASUREMENT UNCERTAINTY (95% CONFIDENCE LEVELS, K=2)	45
6	EQUIPMENT LIST	46
7	PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS	47

3 General Information

3.1 Client Information

Applicant:	Huawei Technologies Co.,Ltd
Address of Applicant:	Administration Buliding Headquarters of Huawei Technologies Co.,Ltd.Bantian,longgang District 518129 Shenzhen PEOPLE'S REPUBLIC OF CHINA
Manufacturer:	Huawei Technologies Co.,Ltd
Address of Manufacturer:	Administration Buliding Headquarters of Huawei Technologies Co.,Ltd.Bantian,longgang District 518129 Shenzhen PEOPLE'S REPUBLIC OF CHINA

3.2 Test Location

Company:	SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch
Address:	No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China
Post code:	518057
Telephone:	+86 (0) 755 2601 2053
Fax:	+86 (0) 755 2671 0594
E-mail:	ee.shenzhen@sgs.com

3.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

• **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

• **VCCI**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

• **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

• **Industry Canada (IC)**

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.



3.4 General Description of EUT

EUT Description::	Mobile WiFi
Model No.:	HW-01L
Trade Mark:	HUAWEI
Hardware Version:	CL1SB08M01
Software Version:	8.0.1.31 (H60SP11C736)
Operation Frequency:	2400MHz~2483.5MHz $f_c = 2402 \text{ MHz} + N * 2 \text{ MHz}$, where: - f_c = "Operating Frequency" in MHz, - N = "Channel Number" with the range from 0 to 39.
Bluetooth Version:	Bluetooth V5.0 (Only supported 1Mbs)
Modulation Type:	GFSK
Number of Channel:	40
Sample Type:	<input checked="" type="checkbox"/> Portable Device, <input type="checkbox"/> Module
Antenna Type:	<input type="checkbox"/> External, <input checked="" type="checkbox"/> Integrated
Antenna Gain:	3. 2dBi
Power Supply	<input type="checkbox"/> AC/DC Adapter; <input checked="" type="checkbox"/> Battery; <input type="checkbox"/> PoE;; <input type="checkbox"/> Other:

Operation Frequency of each channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	10	2422MHz	20	2442MHz	30	2462MHz
1	2404MHz	11	2424MHz	21	2444MHz	31	2464MHz
2	2406MHz	12	2426MHz	22	2446MHz	32	2466MHz
3	2408MHz	13	2428MHz	23	2448MHz	33	2468MHz
4	2410MHz	14	2430MHz	24	2450MHz	34	2470MHz
5	2412MHz	15	2432MHz	25	2452MHz	35	2472MHz
6	2414MHz	16	2434MHz	26	2454MHz	36	2474MHz
7	2416MHz	17	2436MHz	27	2456MHz	37	2476MHz
8	2418MHz	18	2438MHz	28	2458MHz	38	2478MHz
9	2420MHz	19	2440MHz	29	2460MHz	39	2480MHz

Remark:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel (CH0)	2402MHz
The middle channel (CH19)	2440MHz
The highest channel (CH39)	2480MHz



3.5 Test Environment

Operating Environment	
Temperature:	25.0 °C
Humidity:	50 % RH
Atmospheric Pressure:	101.32 KPa

3.6 Description of Support Units

The EUT has been tested independent unit.



4 Test results and Measurement Data

4.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203 /247(c)
<p>15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p>15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.</p>	
<p>The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 3.2dBi.</p>	


4.2 Duty Cycle

4.2.1 Test Results

Test Mode	TX Freq. [MHz]	Duty cycle [%]
BLE	CH0,CH19,CH39	62.30


4.2.1 Test Plots

4.2.1.1 BLE



Date: 21.NOV.2018 07:05:03

4.3 AC Power Line Conducted Emissions


Test Requirement:	47 CFR Part 15C Section 15.207		
Test Method:	ANSI C63.10: 2013		
Test Frequency Range:	150kHz to 30MHz		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
	* Decreases with the logarithm of the frequency.		
Test Procedure:	<p>1) The mains terminal disturbance voltage test was conducted in a shielded room.</p> <p>2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.</p> <p>3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane.</p> <p>4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.</p> <p>5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.</p>		
Test Setup:			
Test Mode:	Transmitting with GFSK modulation. Charge +Transmitting mode.		
Instruments Used:	Refer to section 5.10 for details.		
Test Results:	Pass		

Measurement Data

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.


Live line:



Site : Shielding Room
 Condition: Line
 Job No. : B0003
 Test mode: d

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.20	0.02	9.66	35.57	45.25	53.62	-8.37	Peak
2	0.27	0.03	9.67	32.87	42.57	51.16	-8.59	Peak
3	0.33	0.04	9.67	32.51	42.22	49.44	-7.22	Peak
4	0.46	0.06	9.67	32.36	42.09	46.63	-4.54	Peak
5	0.61	0.07	9.67	32.25	41.99	46.00	-4.01	Peak
6	1.80	0.15	9.72	28.02	37.89	46.00	-8.11	Peak

Neutral line:



Site : Shielding Room
 Condition: Neutral
 Job No. : B0003
 Test mode: d

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.19	0.02	9.64	33.76	43.42	53.84	-10.42	Peak
2	0.27	0.03	9.64	32.63	42.30	51.20	-8.90	Peak
3	0.33	0.04	9.64	31.24	40.92	49.44	-8.52	Peak
4	0.46	0.06	9.64	30.41	40.11	46.63	-6.52	Peak
5	0.59	0.07	9.64	32.12	41.83	46.00	-4.17	Peak
6	2.17	0.16	9.69	30.24	40.09	46.00	-5.91	Peak

Remarks:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.

4.4 Conducted Output Power

Test Requirement:	47 CFR Part 15C Section 15.247 (b)(3)
Test Method:	ANSI C63.10 :2013 Section 11.9.1.1
Test Setup:	
Limit:	30dBm
Test Mode:	Transmitting with GFSK modulation.
Instruments Used:	Refer to section 5.10 for details.
Test Results:	Pass

4.4.1 Test Results

Measurement Data of Average Power


GFSK mode		
Test channel	Average Output Power (dBm)	Result
Lowest	-2.21	Report purpose only
Middle	-0.71	Report purpose only
Highest	-2.15	Report purpose only

Measurement Data of Peak Power :

GFSK mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	-2.10	30.00	Pass
Middle	-0.62	30.00	Pass
Highest	-1.95	30.00	Pass


4.4.2 Test plots:

4.4.2.1 GFSK _Lowest Channel



Date: 28.NOV.2018 09:54:34

4.4.2.2 GFSK _Middle Channel




Date: 28.NOV.2018 09:54:15



4.4.2.3

GFSK_Highest Channel



Date: 28.NOV.2018 09:53:51

4.5 DTS (6 dB) Bandwidth & 99% Occupied Bandwidth


Test Requirement:	47 CFR Part 15C Section 15.247 (a)(2)
Test Method:	ANSI C63.10: 2013 Section 11.8 Option 2
Test Setup:	<p>The diagram illustrates the test setup. A Spectrum Analyzer is connected via a red cable to an E.U.T. (Equipment Under Test). Both are placed on a Non-Conducted Table. Below the table is a Ground Reference Plane.</p>
Limit:	≥ 500 kHz
Test Mode:	Transmitting with GFSK modulation.
Instruments Used:	Refer to section 5.10 for details.
Test Results:	Pass

4.5.1 Test Results


Mode	Test Channel	99% Occupied Bandwidth (MHz)	6dB Emission Bandwidth (MHz)	Limit (kHz)	Result
GFSK	Lowest	1.07	0.71	≥500	Pass
	Middle	1.08	0.71	≥500	Pass
	Highest	1.07	0.72	≥500	Pass

4.5.2 Test plots

4.5.2.1 GFSK _Lowest Channel




Date: 28.NOV.2018 09:59:46




Date: 28.NOV.2018 09:59:10

4.5.2.2 GFSK_Middle Channel




Date: 28.NOV.2018 10:00:18




Date: 28.NOV.2018 09:58:51

4.5.2.3 GFSK_Highest Channel



Date: 28.NOV.2018 10:00:36



Date: 28.NOV.2018 09:58:24

4.6 Power Spectral Density


Test Requirement:	47 CFR Part 15C Section 15.247 (e)
Test Method:	ANSI C63.10 :2013 Section 11.10.2
Test Setup:	<p>The diagram shows a Spectrum Analyzer on the left and an E.U.T. on the right, connected by a red cable. They are both on a table labeled 'Non-Conducted Table'. Below the table is a 'Ground Reference Plane'.</p>
Limit:	≤8.00dBm/3kHz
Test Mode:	Transmitting with GFSK modulation.
Instruments Used:	Refer to section 5.10 for details.
Test Results:	Pass

4.6.1 Test Results

Mode	Test Channel	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
GFSK	Lowest	-17.53	≤8.00	Pass
	Middle	-16.07	≤8.00	Pass
	Highest	-17.42	≤8.00	Pass


4.6.2 Test plots

4.6.2.1 GFSK _Lowest Channel



Date: 28.NOV.2018 10:01:48


4.6.2.2 GFSK _Middle Channel



Date: 28.NOV.2018 10:01:33

4.6.2.3

GFSK_Highest Channel




Date: 28.NOV.2018 10:01:13

4.7 Band-edge for RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10: 2013 Section 11.13
Test Setup:	<p>The diagram shows a Spectrum Analyzer on the left and an E.U.T. on the right, connected by a red cable. They are both placed on a table labeled 'Non-Conducted Table'. Below the table is a thick grey bar labeled 'Ground Reference Plane'.</p>
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Mode:	Transmitting with GFSK modulation.
Instruments Used:	Refer to section 5.10 for details.
Test Results:	Pass


4.7.1 Test plots

4.7.1.1 GFSK _Lowest Channel



Date: 28.NOV.2018 10:02:25

4.7.1.2 GFSK _Highest Channel




Date: 28.NOV.2018 10:03:09

4.8 Spurious RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10: 2013 Section 11.11
Test Setup:	<p>The diagram shows a Spectrum Analyzer on the left and an E.U.T. on the right, connected by a red cable. They are both on a table labeled 'Non-Conducted Table'. Below the table is a 'Ground Reference Plane'.</p>
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Mode:	Transmitting with GFSK modulation.
Instruments Used:	Refer to section 5.10 for details.
Test Results:	Pass


4.8.1 Test plots:

4.8.1.1 GFSK _Lowest Channel




Date: 28.NOV.2018 10:06:55

4.8.1.2 GFSK _Middle Channel



Date: 28.NOV.2018 10:05:20

4.8.1.3 GFSK_Highest Channel



Date: 28.NOV.2018 10:04:36

Remark:

Scan from 9kHz to 25GHz, the disturbance between 9KHz to 30MHz was very low, and the above harmonics were the highest point could be found when testing, The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

4.9 Radiated Spurious Emission

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205				
Test Method:	ANSI C63.10 :2013 Section 11.12				
Test Site:	Measurement Distance: 3m or 10m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak	
	Peak	1MHz	10Hz	Average	
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
Above 1GHz	500	54.0	Average	3	
Remark: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.					

Test Setup:




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

Test Procedure:


- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or



	<p>average method as specified and then reported in a data sheet.</p> <p>h. Test the EUT in the lowest channel (2402MHz), the middle channel (2440MHz), the highest channel (2480MHz)</p> <p>i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.</p> <p>j. Repeat above procedures until all frequencies measured was complete.</p>
Exploratory Test Mode:	Transmitting with GFSK modulation. Charge + Transmitting mode.
Final Test Mode:	Transmitting with GFSK modulation. Pretest the EUT at Charge + Transmitting mode, For below 1GHz part, through pre-scan, the worst case is the lowest channel. Only the worst case is recorded in the report.
Instruments Used:	Refer to section 5.10 for details.
Test Results:	Pass

4.9.1 Radiated Emission below 1GHz

4.9.1.1 Charge + Transmitting, Vertical




Condition: 3m VERTICAL

Job No. : B0003

Test mode: d

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dB
1 pp	55.22	0.80	13.66	27.58	33.43	40.00	-19.69
2	92.14	1.12	13.30	27.51	29.67	43.50	-26.92
3	144.33	1.31	14.11	27.52	34.56	43.50	-21.04
4	167.82	1.35	15.66	27.52	30.41	43.50	-23.60
5	294.11	1.87	19.37	27.54	24.38	46.00	-27.92
6	463.97	2.47	23.86	27.83	26.29	46.00	-21.21

4.9.1.2 Charge + Transmitting, Horizontal



Condition: 3m HORIZONTAL


Job No. : B0003

Test mode: d

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	30.96	0.60	21.95	27.67	25.87	20.75	40.00	-19.25
2	90.22	1.10	13.12	27.51	29.86	16.57	43.50	-26.93
3	193.09	1.39	16.30	27.53	25.52	15.68	43.50	-27.82
4	247.68	1.66	18.92	27.53	24.99	18.04	46.00	-27.96
5	495.93	2.59	24.52	27.87	25.23	24.47	46.00	-21.53
6 pp	768.75	3.11	28.32	27.46	26.54	30.51	46.00	-15.49

4.9.2 Transmitter Emission above 1GHz


4.9.2.1 GFSK _Lowest Channel_ Vertical



Site : chamber
 Condition: 3m VERTICAL
 Job No : B0003
 Mode : 2402 TX RSE
 Note : BLE

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	1390.276	5.12	25.39	40.63	39.69	29.57	74.00	-44.43 peak
2	4482.150	7.54	33.57	43.29	38.77	36.59	74.00	-37.41 peak
3	4804.000	7.89	33.97	43.61	37.29	35.54	74.00	-38.46 peak
4	6583.209	11.30	35.65	42.34	37.86	42.47	74.00	-31.53 peak
5	7206.000	10.08	36.07	41.86	38.08	42.37	74.00	-31.63 peak
6	9608.000	10.75	37.67	38.43	23.60	33.59	54.00	-20.41 Average
7	9608.000	10.75	37.67	38.43	31.68	41.67	74.00	-32.33 peak


4.9.2.2 GFSK _Middle Channel_ Vertical



Site : chamber
 Condition: 3m VERTICAL
 Job No : B0003
 Mode : 2440 TX RSE
 Note : BLE

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	1426.916	5.24	25.53	40.66	38.92	29.03	74.00	-44.97 peak
2	4495.125	7.55	33.59	43.30	37.46	35.30	74.00	-38.70 peak
3	4880.000	7.97	34.06	43.69	37.24	35.58	74.00	-38.42 peak
4	6621.375	11.19	35.67	42.31	37.53	42.08	74.00	-31.92 peak
5	7320.000	10.05	36.16	41.77	36.10	40.54	74.00	-33.46 peak
6	9760.000	10.82	37.76	38.18	25.38	35.78	54.00	-18.22 Average
7	9760.000	10.82	37.76	38.18	31.44	41.84	74.00	-32.16 peak


4.9.2.3 GFSK _High Channel_ Vertical



Site : chamber
 Condition: 3m VERTICAL
 Job No : B0003
 Mode : 2480 TX RSE
 Note : BLE

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1331.288	4.91	25.15	40.59	40.85	30.32	74.00	-43.68	peak
2	3992.781	6.97	32.69	42.74	38.69	35.61	74.00	-38.39	peak
3	4960.000	8.05	34.15	43.76	38.10	36.54	74.00	-37.46	peak
4	6545.263	11.41	35.63	42.37	38.92	43.59	74.00	-30.41	peak
5	7440.000	10.02	36.25	41.69	37.11	41.69	74.00	-32.31	peak
6	9920.000	10.90	37.85	37.93	24.19	35.01	54.00	-18.99	Average
7	9920.000	10.90	37.85	37.93	31.83	42.65	74.00	-31.35	peak


4.9.2.4 GFSK _Lowest Channel_ Horizontal



Site : chamber
 Condition: 3m HORIZONTAL
 Job No : B0003
 Mode : 2402 TX RSE
 Note : BLE

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1516.210	5.46	25.87	40.72	39.31	29.92	74.00	-44.08	peak
2	3879.027	6.86	32.47	42.61	39.23	35.95	74.00	-38.05	peak
3	4804.000	7.89	33.97	43.61	38.00	36.25	74.00	-37.75	peak
4	6621.375	11.19	35.67	42.31	37.50	42.05	74.00	-31.95	peak
5	7206.000	10.08	36.07	41.86	35.25	39.54	74.00	-34.46	peak
6	9608.000	10.75	37.67	38.43	23.56	33.55	54.00	-20.45	Average
7	9608.000	10.75	37.67	38.43	32.38	42.37	74.00	-31.63	peak


4.9.2.5 GFSK _Middle Channel_ Horizontal



Site : chamber
 Condition: 3m HORIZONTAL
 Job No : B0003
 Mode : 2440 TX RSE
 Note : BLE

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1533.841	5.44	25.96	40.73	39.95	30.62	74.00	-43.38	peak
2	4430.628	7.48	33.48	43.23	39.00	36.73	74.00	-37.27	peak
3	4880.000	7.97	34.06	43.69	38.60	36.94	74.00	-37.06	peak
4	6088.991	10.75	35.19	42.75	39.11	42.30	74.00	-31.70	peak
5	7320.000	10.05	36.16	41.77	37.00	41.44	74.00	-32.56	peak
6	9760.000	10.82	37.76	38.18	24.16	34.56	54.00	-19.44	Average
7	9760.000	10.82	37.76	38.18	32.77	43.17	74.00	-30.83	peak

4.9.2.6 GFSK _High Channel_ Horizontal



Site : chamber
 Condition: 3m HORIZONTAL
 Job No : B0003
 Mode : 2480 TX RSE
 Note : BLE

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	1533.841	5.44	25.96	40.73	38.49	29.16	74.00	-44.84 peak
2	4443.453	7.50	33.50	43.25	37.74	35.49	74.00	-38.51 peak
3	4960.000	8.05	34.15	43.76	39.68	38.12	74.00	-35.88 peak
4	6815.551	10.64	35.79	42.15	38.34	42.62	74.00	-31.38 peak
5	7440.000	10.02	36.25	41.69	36.93	41.51	74.00	-32.49 peak
6	9920.000	10.90	37.85	37.93	24.53	35.35	54.00	-18.65 Average
7	9920.000	10.90	37.85	37.93	32.29	43.11	74.00	-30.89 peak

Remark:

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 2) Scan from 9kHz to 25GHz, the disturbance between 9KHz to 30MHz was very low, and the above harmonics were the highest point could be found when testing, The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 3) As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.
- 4) All Modes have been tested, but only the worst case data displayed in this report.

4.10 Restricted bands around fundamental frequency

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205		
Test Method:	ANSI C63.10: 2013 Section 11.12		
Test Site:	Measurement Distance: 3m or 10m (Semi-Anechoic Chamber)		
Limit:	Frequency	Limit (dBuV/m @3m)	Remark
	30MHz-88MHz	40.0	Quasi-peak Value
	88MHz-216MHz	43.5	Quasi-peak Value
	216MHz-960MHz	46.0	Quasi-peak Value
	Above 1GHz	54.0	Average Value
		74.0	Peak Value




Figure 1. 30MHz to 1GHz

Figure 2. Above 1 GHz


Test Procedure:	<ol style="list-style-type: none"> For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel Test the EUT in the lowest channel, the Highest channel The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Transmitting with GFSK modulation.



	Charge + Transmitting mode.
Final Test Mode:	Transmitting with GFSK modulation. Pretest the EUT at Charge + Transmitting mode. Only the worst case is recorded in the report.
Instruments Used:	Refer to section 5.10 for details.
Test Results:	Pass

4.10.1 Test plots


4.10.1.1 Worst Case Mode(GFSK) Lowest Channel_ Peak_ Vertical



Site : chamber
 Condition: 3m VERTICAL
 Job No : B0003
 Mode : 2402 Band edge

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2326.672	5.39	28.41	41.15	58.17	50.82	74.00	-23.18 peak
2	2390.000	5.47	28.52	41.17	55.97	48.79	74.00	-25.21 peak
3 *	2402.000	5.49	28.54	41.18	88.59	81.44	74.00	7.44 peak


4.10.1.2 Worst Case Mode(GFSK) Highest Channel_ Peak_ Vertical



Site : chamber
 Condition: 3m VERTICAL
 Job No : B0003
 Mode : 2480 Band edge

	Cable	Ant	Preamp	Read	Limit	Over		
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 *	2480.000	5.59	28.67	41.21	86.44	79.49	74.00	5.49 peak
2	2483.500	5.60	28.67	41.21	56.72	49.78	74.00	-24.22 peak
3	2499.246	5.62	28.70	41.22	58.78	51.88	74.00	-22.12 peak


4.10.1.3 Worst Case Mode(GFSK) Lowest Channel_ Peak_ Horizontal



Site : chamber
 Condition: 3m HORIZONTAL
 Job No : B0003
 Mode : 2402 Band edge

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2380.908	5.46	28.50	41.17	57.70	50.49	74.00	-23.51 peak
2	2390.000	5.47	28.52	41.17	55.13	47.95	74.00	-26.05 peak
3 *	2402.000	5.49	28.54	41.18	97.76	90.61	74.00	16.61 peak

4.10.1.4 Worst Case Mode(GFSK) Highest Channel_ Peak_ Horizontal



Site : chamber
 Condition: 3m HORIZONTAL
 Job No : B0003
 Mode : 2480 Band edge

	Cable	Ant	Preamp	Read	Limit	Over		
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 * 2480.000	5.59	28.67	41.21	94.60	87.65	74.00	13.65	peak
2 2483.500	5.60	28.67	41.21	58.27	51.33	74.00	-22.67	peak
3 2493.576	5.61	28.69	41.21	59.41	52.50	74.00	-21.50	peak

Remark:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

$$\text{Final Test Level} = \text{Receiver Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Preamplifier Factor}$$

All Modes have been tested, but only the worst case data displayed in this report.

5 Measurement Uncertainty (95% confidence levels, k=2)

No.	Item	Measurement Uncertainty
1	Total RF power, conducted	±0.75dB
2	RF power density, conducted	±2.84dB
3	Spurious emissions, conducted	±0.75dB
4	Radiated Spurious emission test	±4.5dB (30MHz-1GHz)
		±4.8dB (1GHz-25GHz)
5	Conduct emission test	±3.12 dB(9KHz- 30MHz)
6	Temperature test	±1°C
7	Humidity test	±3%
8	DC and low frequency voltages	±0.5%



6 Equipment List

Conducted Emission					
Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date	Cal. Due date
				(yyyy-mm-dd)	(yyyy-mm-dd)
Shielding Room	ZhongYu Electron	GB-88	SEM001-06	2017/5/10	2020/5/9
LISN	Rohde & Schwarz	ENV216	SEM007-01	2018/9/2	2019/9/2
LISN	ETS-LINDGREN	Feb-16	SEM007-02	2018/4/2	2019/4/1
Measurement Software	AUDIX	e3 V5.4.1221d	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM024-01	2018/7/12	2019/7/11
2 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T2-02	EMC0122	2018/2/14	2019/2/13
EMI Test Receiver	Rohde & Schwarz	ESCI	SEM004-02	2018/4/2	2019/4/1

RF conducted test					
Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date	Cal. Due date
				(yyyy-mm-dd)	(yyyy-mm-dd)
DC Power Supply	Agilent Technologies Inc	66311B	W009-09	2018/9/15	2019/9/15
Signal Analyzer	Rohde & Schwarz	FSV	W025-05	2018/3/13	2019/3/12
Coaxial Cable	SGS	N/A	SEM031-01	2018/7/13	2019/7/12
Attenuator	Weinschel Associates	WA41	SEM021-09	N/A	N/A
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2018/9/2	2019/9/2
Temperature Chamber	GIANT FORCE	ICT-150-40-CP-AR	W027-03	2018/11/27	2019/11/27
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2018/9/2	2019/9/2

RE in Chamber					
Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date	Cal. Due date
				(yyyy-mm-dd)	(yyyy-mm-dd)
3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEM001-01	2017/8/5	2020/8/4
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM025-01	2018/7/12	2019/7/11
MXE EMI Receiver (20Hz-8.4GHz)	Agilent Technologies	N9038A	SEM004-05	2018/9/2	2019/9/2
BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEM003-01	2017/6/27	2020/6/26
Pre-amplifier (0.1-1.3GHz)	Agilent Technologies	8447D	SEM005-01	2018/4/2	2019/4/1



RE in Chamber					
Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (yyyy-mm-dd)	Cal. Due date (yyyy-mm-dd)
10m Semi-Anechoic Chamber	SAEMC	FSAC1018	SEM001-03	2018/3/31	2021/3/30
EMI Test Receiver (9k-7GHz)	Rohde & Schwarz	ESR	SEM004-03	2018/4/2	2019/4/1
Trilog-Broadband Antenna(25M-2GHz)	Schwarzbeck	VULB9168	SEM003-18	2016/6/29	2019/6/28
Pre-amplifier (9k-1GHz)	Sonoma	310N	SEM005-03	2018/4/13	2019/4/12
Loop Antenna (9kHz-30MHz)	ETS-Lindgren	6502	SEM003-08	2017/8/22	2020/8/21
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM029-01	2018/7/12	2019/7/11

RE in Chamber					
Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date	Cal. Due date
				(yyyy-mm-dd)	(yyyy-mm-dd)
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2018/3/13	2021/3/12
Measurement Software	AUDIX	e3V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2018/7/12	2019/7/11
EXA Signal Analyzer (10Hz-26.5GHz)	Agilent Technologies Inc	N9010A	SEM004-09	2018/4/13	2019/4/12
BiConiLog Antenna (26-3000MHz)	ETS-Lindgren	3142C	SEM003-01	2017/6/27	2020/6/26
Horn Antenna (0.8-18GHz)	Rohde & Schwarz	HF907	SEM003-07	2018/4/13	2021/4/12
Pre-amplifier(0.1-1.3GHz)	HP	8447D	SEM005-02	2018/9/2	2019/9/2
Low Noise Amplifier(100MHz-18GHz)	Black Diamond Series	BDLNA-0118-352810	SEM005-05	2018/9/27	2019/9/27
Pre-amplifier(18-26GHz)	Rohde & Schwarz	CH14-H052	SEM005-17	2018/4/2	2019/4/1
Band filter	N/A	N/A	SEM023-01	N/A	N/A

7 Photographs - EUT Constructional Details

Refer to Appendix A - Photographs of EUT Constructional Details for HR/2018/B0003.

The End