



FCC Test Report

APPLICANT : Huawei Technologies Co.,Ltd.
EQUIPMENT : Smart Phone
BRAND NAME : honor
MODEL NAME : JAT-L41
FCC ID : QISJAT-L41
STANDARD : 47 CFR Part 15 Subpart B
CLASSIFICATION : Certification

The product was received on Jan. 14, 2019 and testing was completed on Jan. 25, 2019. We, Sporton International (Shenzhen) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI C63.4-2014 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Shenzhen) Inc., the test report shall not be reproduced except in full.



Approved by: Eric Shih / Manager

Sporton International (Shenzhen) Inc.

**1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen City,
Guangdong Province 518055, China**



TABLE OF CONTENTS

REVISION HISTORY..... 3

SUMMARY OF TEST RESULT 4

1. GENERAL DESCRIPTION 5

 1.1. Applicant..... 5

 1.2. Manufacturer 5

 1.3. Product Feature of Equipment Under Test 5

 1.4. Product Specification of Equipment Under Test 6

 1.5. Accessories List 7

 1.6. Modification of EUT 8

 1.7. Test Location 9

 1.8. Applicable Standards 9

2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST 10

 2.1. Test Mode 10

 2.2. Connection Diagram of Test System 12

 2.3. Support Unit used in test configuration and system 12

 2.4. EUT Operation Test Setup 13

3. TEST RESULT 14

 3.1. Test of AC Conducted Emission Measurement 14

 3.2. Test of Radiated Emission Measurement 18

4. LIST OF MEASURING EQUIPMENT 22

5. UNCERTAINTY OF EVALUATION 23

APPENDIX A. SETUP PHOTOGRAPHS



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FC911406	Rev. 01	Initial issue of report	Jan. 31, 2019



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.107	AC Conducted Emission	< 15.107 limits	PASS	Under limit 6.34 dB at 0.20 MHz
3.2	15.109	Radiated Emission	< 15.109 limits	PASS	Under limit 6.22 dB at 30.00 MHz



1. General Description

1.1. Applicant

Huawei Technologies Co.,Ltd.

Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C

1.2. Manufacturer

Huawei Technologies Co.,Ltd.

Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C

1.3. Product Feature of Equipment Under Test

Product Feature	
Equipment	Smart Phone
Brand Name	honor
Model Name	JAT-L41
FCC ID	QISJAT-L41
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/HSPA+/DC-HSDPA/LTE WLAN 2.4GHz 802.11b/g/n (HT20/HT40) Bluetooth BR/EDR/LE
IMEI Code	867638040015223/867638040016809 for Sample 1 867638040015637/867638040017211 for Sample 2 867638040015165/867638040016742 for Sample 3
HW Version	HL1JATM
SW Version	9.0.1.108(C900E70R1P8)
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



1.4. Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz LTE Band 5 : 824.7 MHz ~ 848.3 MHz LTE Band 7 : 2502.5 MHz ~ 2567.5 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz
Rx Frequency	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band II: 1932.4 MHz ~ 1987.6 MHz LTE Band 5 : 869.7 MHz ~ 893.3 MHz LTE Band 7 : 2622.5 MHz ~ 2687.5 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz GNSS : 1559 MHz ~ 1610 MHz
Antenna Type	WWAN: Fixed Internal Antenna WLAN : Internal Antenna Bluetooth: Internal Antenna GNSS: Internal Antenna
Type of Modulation	GSM: GMSK GPRS: GMSK EDGE(MCS 0-4): GMSK / (MCS 5-9): 8PSK WCDMA : BPSK (Uplink) HSPA : QPSK (Uplink) HSPA+ : 16QAM DC-HSDPA : 64QAM LTE: QPSK / 16QAM 802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) Bluetooth LE : GFSK Bluetooth (1Mbps) : GFSK Bluetooth (2Mbps) : $\pi/4$ -DQPSK Bluetooth (3Mbps) : 8-DPSK GNSS : BPSK

1.5. Accessories List

Specification of Accessory				
AC Adapter 1	Brand Name	Huawei Technologies Co., Ltd.	Model Name	HW-050100B01
	Power Rating	I/P: 100 - 240 Vac; O/P: 5Vdc, 1.0A		
	Manufacturer	Dongguan Phitek Electronics Co., Ltd		
AC Adapter 2	Brand Name	Huawei Technologies Co., Ltd.	Model Name	HW-050100B01
	Power Rating	I/P: 100 - 240 Vac; O/P: 5Vdc, 1.0A		
	Manufacturer	HUIZHOU BYD ELECTRONIC CO., LTD		
AC Adapter 3	Brand Name	Huawei Technologies Co., Ltd.	Model Name	HW-050100B01
	Power Rating	I/P: 100 - 240 Vac; O/P: 5Vdc, 1.0A		
	Manufacturer	SHENZHEN HUNTKEY ELECTRIC CO., LTD.		
AC Adapter 4	Brand Name	Huawei Technologies Co., Ltd.	Model Name	HW-050100E01
	Power Rating	I/P: 100 - 240 Vac; O/P: 5Vdc, 1.0A		
	Manufacturer	Dongguan Phitek Electronics Co., Ltd.		
AC Adapter 5	Brand Name	Huawei Technologies Co., Ltd.	Model Name	HW-050100E01
	Power Rating	I/P: 100 - 240 Vac; O/P: 5Vdc, 1.0A		
	Manufacturer	HUIZHOU BYD ELECTRONIC CO., LTD		
AC Adapter 6	Brand Name	Huawei Technologies Co., Ltd.	Model Name	HW-050100E01
	Power Rating	I/P: 100 - 240 Vac; O/P: 5Vdc, 1.0A		
	Manufacturer	SHENZHEN HUNTKEY ELECTRIC CO., LTD.		
AC Adapter 7	Brand Name	Huawei Technologies Co., Ltd.	Model Name	HW-050100A01
	Power Rating	I/P: 100 - 240 Vac; O/P: 5Vdc, 1.0A		
	Manufacturer	Dongguan Phitek Electronics Co., Ltd.		
AC Adapter 8	Brand Name	Huawei Technologies Co., Ltd.	Model Name	HW-050100A01
	Power Rating	I/P: 100 - 240 Vac; O/P: 5Vdc, 1.0A		
	Manufacturer	HUIZHOU BYD ELECTRONIC CO., LTD		
AC Adapter 9	Brand Name	Huawei Technologies Co., Ltd.	Model Name	HW-050100A01
	Power Rating	I/P: 100 - 240 Vac; O/P: 5Vdc, 1.0A		
	Manufacturer	SHENZHEN HUNTKEY ELECTRIC CO., LTD.		
AC Adapter 10	Brand Name	Huawei Technologies Co., Ltd.	Model Name	HW-050100U01
	Power Rating	I/P: 100 - 240 Vac; O/P: 5Vdc, 1.0A		
	Manufacturer	Dongguan Phitek Electronics Co., Ltd.		
AC Adapter 11	Brand Name	Huawei Technologies Co., Ltd.	Model Name	HW-050100U01
	Power Rating	I/P: 100 - 240 Vac; O/P: 5Vdc, 1.0A		
	Manufacturer	HUIZHOU BYD ELECTRONIC CO., LTD		
AC Adapter 12	Brand Name	Huawei Technologies Co., Ltd.	Model Name	HW-050100U01
	Power Rating	I/P: 100 - 240 Vac; O/P: 5Vdc, 1.0A		
	Manufacturer	SHENZHEN HUNTKEY ELECTRIC CO., LTD.		

Battery 1	Brand Name	Huawei Technologies Co., Ltd.	Model Name	HB405979ECW
	Power Rating	3.82Vdc, 2920mAh	Manufacturer	Sunwoda
Battery 2	Brand Name	Huawei Technologies Co., Ltd.	Model Name	HB405979ECW
	Power Rating	3.82Vdc, 2920mAh	Manufacturer	SCUD
Battery 3	Brand Name	Huawei Technologies Co., Ltd.	Model Name	HB405979ECW
	Power Rating	3.82Vdc, 2920mAh	Manufacturer	Desay
USB Cable 1	Brand Name	Huawei Technologies Co., Ltd.	Model Name	L99U2013-CS-H
	Signal Line	1.0 meter, non-shielded cable, without ferrite core		
USB Cable 2	Brand Name	Huawei Technologies Co., Ltd.	Model Name	203-0786-0
	Signal Line	1.0 meter, non-shielded cable, without ferrite core		
USB Cable 3	Brand Name	Huawei Technologies Co., Ltd.	Model Name	130-26654
	Signal Line	1.0 meter, non-shielded cable, without ferrite core		
USB Cable 4	Brand Name	Huawei Technologies Co., Ltd.	Model Name	WA0007
	Signal Line	1.0 meter, non-shielded cable, without ferrite core		
USB Cable 5	Brand Name	Huawei Technologies Co., Ltd.	Model Name	L99U2017-CS-H
	Signal Line	1.0 meter, non-shielded cable, without ferrite core		
USB Cable 6	Brand Name	Huawei Technologies Co., Ltd.	Model Name	203-1583-0
	Signal Line	1.0 meter, non-shielded cable, without ferrite core		
USB Cable 7	Brand Name	Huawei Technologies Co., Ltd.	Model Name	130-26669
	Signal Line	1.0 meter, non-shielded cable, without ferrite core		
USB Cable 8	Brand Name	Huawei Technologies Co., Ltd.	Model Name	WA0001
	Signal Line	1.0 meter, non-shielded cable, without ferrite core		
USB Cable 9	Brand Name	Huawei Technologies Co., Ltd.	Model Name	CUBB01M-HC304-DH
	Signal Line	1.0 meter, non-shielded cable, without ferrite core		

1.6. Modification of EUT

No modifications are made to the EUT during all test items.



1.7. Test Location

Sporton International (Shenzhen) Inc. is accredited to ISO 17025 by National Voluntary Laboratory Accreditation Program (NVLAP code: 600156-0).

Test Site	Sporton International (Shenzhen) Inc.		
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen City, Guangdong Province 518055, China TEL: +86-755-8637-9589 FAX: +86-755-8637-9595		
Test Site No.	Sporton Site No.	FCC designation No.	FCC Test Firm Registration No.
	CO01-SZ	CN5018	337463

Test Site	Sporton International (Shenzhen) Inc.		
Test Site Location	No. 3 Bldg the third floor of south, Shahe River west, Fengzeyuan Warehouse, Nanshan District, Shenzhen City, Guangdong Province 518055, China TEL: +86-755- 3320-2398		
Test Site No.	Sporton Site No.	FCC designation No.	FCC Test Firm Registration No.
	03CH01-SZ	CN5019	577730

1.8. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart B
- ANSI C63.4-2014

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.



2. Test Configuration of Equipment Under Test

2.1. Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.


Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (30MHz to the 5th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

Test Items	Function Type
AC Conducted Emission	Mode 1: GSM850 Idle + Earphone + Bluetooth Idle + WLAN (2.4G) Idle + Camera(Rear) + USB Cable 1(Charging from Adapter 1) + Battery 1 + SIM 1 for Sample 1
	Mode 2: GSM1900 Idle + Earphone + Bluetooth Idle + WLAN (2.4G) Idle + Camera(Front) + USB Cable 2(Charging from Adapter 2) + Battery 2 + SIM 2 for Sample 2
	Mode 3: WCDMA Band V Idle + Earphone + Bluetooth Idle + WLAN (2.4G) Idle + Color Bar(MPEG4) + USB Cable 3(Charging from Adapter 3) + Battery 3 + SIM 1 for Sample 3
	Mode 4: WCDMA Band II Idle + Earphone + Bluetooth Idle + WLAN (2.4G) Idle + H-ptten + USB Cable 4(Charging from Adapter 4) + Battery 1 + SIM 1 for Sample 1
	Mode 5: LTE Band 5 Idle + Earphone + Bluetooth Idle + WLAN (2.4G) Idle + GNSS Rx + USB Cable 5(Charging from Adapter 5) + Battery 1 + SIM 1 for Sample 1
	Mode 6: LTE Band 7 Idle + Earphone + Bluetooth Idle + WLAN (2.4G) Idle + Camera(Rear) + USB Cable 6(Charging from Adapter 6) + Battery 1 + SIM 1 for Sample 1
	Mode 7: GSM850 Idle + Earphone + Bluetooth Idle + WLAN (2.4G) Idle + Camera(Rear) + USB Cable 7(Charging from Adapter 1) + Battery 1 + SIM 1 for Sample 1
	Mode 8: GSM850 Idle + Earphone + Bluetooth Idle + WLAN (2.4G) Idle + Camera(Rear) + USB Cable 8(Charging from Adapter 1) + Battery 1 + SIM 1 for Sample 1
	Mode 9: GSM850 Idle + Earphone + Bluetooth Idle + WLAN (2.4G) Idle + Camera(Rear) + USB Cable 9(Charging from Adapter 1) + Battery 1 + SIM 1 for Sample 1
	Mode 10: GSM850 Idle + Earphone + Bluetooth Idle + WLAN (2.4G) Idle + Camera(Rear) + USB Cable 9(Data Link with Notebook) + Battery 1 + SIM 1 for Sample 1



Radiated Emission	<p>Mode 1: GSM850 Idle + Earphone + Bluetooth Idle + WLAN (2.4G) Idle + Camera(Rear) + USB Cable 1(Charging from Adapter 1) + Battery 1 + SIM 1 for Sample 1</p> <p>Mode 2: GSM1900 Idle + Earphone + Bluetooth Idle + WLAN (2.4G) Idle + Camera(Front) + USB Cable 2(Charging from Adapter 2) + Battery 2 + SIM 2 for Sample 2</p> <p>Mode 3: WCDMA Band V Idle + Earphone + Bluetooth Idle + WLAN (2.4G) Idle + Color Bar(MPEG4) + USB Cable 3(Charging from Adapter 3) + Battery 3 + SIM 1 for Sample 3</p> <p>Mode 4: WCDMA Band II Idle + Earphone + Bluetooth Idle + WLAN (2.4G) Idle + H-ptten + USB Cable 4(Charging from Adapter 4) + Battery 1 + SIM 1 for Sample 1</p> <p>Mode 5: LTE Band 5 Idle + Earphone + Bluetooth Idle + WLAN (2.4G) Idle + GNSS Rx + USB Cable 5(Charging from Adapter 5) + Battery 1 + SIM 1 for Sample 1</p> <p>Mode 6: LTE Band 7 Idle + Earphone + Bluetooth Idle + WLAN (2.4G) Idle + H-ptten + USB Cable 6(Charging from Adapter 6) + Battery 1 + SIM 1 for Sample 1</p> <p>Mode 7: WCDMA Band II Idle + Earphone + Bluetooth Idle + WLAN (2.4G) Idle + H-ptten + USB Cable 7(Charging from Adapter 4) + Battery 1 + SIM 1 for Sample 1</p> <p>Mode 8: WCDMA Band II Idle + Earphone + Bluetooth Idle + WLAN (2.4G) Idle + H-ptten + USB Cable 8(Charging from Adapter 4) + Battery 1 + SIM 1 for Sample 1</p> <p>Mode 9: WCDMA Band II Idle + Earphone + Bluetooth Idle + WLAN (2.4G) Idle + H-ptten + USB Cable 9(Charging from Adapter 4) + Battery 1 + SIM 1 for Sample 1</p> <p>Mode 10 : WCDMA Band II Idle + Earphone + Bluetooth Idle + WLAN (2.4G) Idle + H-ptten + USB Cable 9(Data Link with Notebook) + Battery 1 + SIM 1 for Sample 1</p>
<p>Remark:</p> <ol style="list-style-type: none"> 1. The worst case of AC is mode 1; only the test data of this mode is reported. 2. The worst case of RE is mode 9; only the test data of this mode is reported. 3. Data Link with Notebook means data application transferred mode between EUT and Notebook. 	

2.2. Connection Diagram of Test System



2.3. Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	LTE Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded,1.8m
3.	WLAN AP	Dlink	DIR-820L	KA2IR820LA1	N/A	Unshielded,1.8m
4.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded,1.8m
5.	Notebook	Lenovo	E540	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
6.	Bluetooth Earphone	Samsung	HS3000	A3LHS3000	N/A	N/A
7.	Bluetooth Earphone	Samsung	EO-MG900	PYAHS-107W	N/A	N/A
8.	SD Card	Kingston	MicroSD HC	Fcc DoC	N/A	N/A
9.	Earphone	Apple	MC690ZP/A	N/A	Shielded, 1.0m	N/A
10.	Earphone	APPLE	DCAY1V-A9007ZJW3-000	N/A	N/A	N/A
11.	iPod	Apple	MC525 ZP/A	Fcc DoC	Shielded, 1.0m	N/A
12.	iPod	Apple	MC69029/A	N/A	N/A	N/A



2.4. EUT Operation Test Setup

The EUT was in GSM or WCDMA or LTE idle mode during the testing. The EUT was synchronized to the BCCH, and is in continuous receiving mode by setting system simulator's paging reorganization.

At the same time, the EUT was attached to the Bluetooth earphone or WLAN AP, and the following programs installed in the EUT were programmed during the test.

1. Data application is transferred between Notebook and EUT via USB cable.
2. Turn on GNSS function to make the EUT receive continuous signals from GNSS station.
3. Turn on camera to capture images.
4. Turn on MPEG4 function.
5. Execute "H Pattern" to show H Pattern on the Display Screen.

3. Test Result

3.1. Test of AC Conducted Emission Measurement

3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

<Class B Limit>

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedure

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.1.4 Test Setup





3.1.5 Test Result of AC Conducted Emission

Test Engineer :	Zhang Xu	Temperature :	22~25°C
Test Voltage :	120Vac / 60Hz	Relative Humidity :	50~55%
		Phase :	Line

Date: 2019-01-25 Time: 21:22:27


Site : CO01-SZ
Condition: FCC 15B_QP LISN_20180719_L LINE

IMEI : 867638040015223/867638040016809

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.15	40.09	-15.87	55.96	30.00	0.03	10.06	Average
2	0.15	57.89	-8.07	65.96	47.80	0.03	10.06	QP
3	0.20	38.30	-15.24	53.54	28.20	0.03	10.07	Average
4 *	0.20	57.20	-6.34	63.54	47.10	0.03	10.07	QP
5	0.27	30.11	-21.01	51.12	20.00	0.03	10.08	Average
6	0.27	48.01	-13.11	61.12	37.90	0.03	10.08	QP
7	0.34	28.31	-20.96	49.27	18.20	0.03	10.08	Average
8	0.34	43.31	-15.96	59.27	33.20	0.03	10.08	QP
9	0.42	28.21	-19.25	47.46	18.10	0.03	10.08	Average
10	0.42	41.61	-15.85	57.46	31.50	0.03	10.08	QP
11	0.60	31.40	-14.60	46.00	21.30	0.02	10.08	Average
12	0.60	44.30	-11.70	56.00	34.20	0.02	10.08	QP
13	0.74	30.61	-15.39	46.00	20.50	0.03	10.08	Average
14	0.74	41.71	-14.29	56.00	31.60	0.03	10.08	QP
15	0.96	31.05	-14.95	46.00	20.90	0.06	10.09	Average
16	0.96	41.75	-14.25	56.00	31.60	0.06	10.09	QP
17	1.12	30.37	-15.63	46.00	20.20	0.08	10.09	Average
18	1.12	42.07	-13.93	56.00	31.90	0.08	10.09	QP
19	1.49	28.59	-17.41	46.00	18.40	0.09	10.10	Average
20	1.49	40.79	-15.21	56.00	30.60	0.09	10.10	QP
21	11.74	36.38	-13.62	50.00	25.60	0.42	10.36	Average
22	11.74	46.68	-13.32	60.00	35.90	0.42	10.36	QP



Test Engineer :	Zhang Xu	Temperature :	22~25°C
		Relative Humidity :	50~55%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral



Site : CO01-SZ
 Condition: FCC 15B_QP LISN_20180719_N NEUTRAL

IMEI : 867638040015223/867638040016809

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.15	35.19	-20.81	56.00	25.10	0.03	10.06	Average
2 *	0.15	53.59	-12.41	66.00	43.50	0.03	10.06	QP
3	0.22	27.90	-24.80	52.70	17.80	0.03	10.07	Average
4	0.22	47.80	-14.90	62.70	37.70	0.03	10.07	QP
5	0.27	29.81	-21.26	51.07	19.70	0.03	10.08	Average
6	0.27	44.21	-16.86	61.07	34.10	0.03	10.08	QP
7	0.41	24.50	-23.18	47.68	14.40	0.02	10.08	Average
8	0.41	39.50	-18.18	57.68	29.40	0.02	10.08	QP
9	0.60	32.50	-13.50	46.00	22.40	0.02	10.08	Average
10	0.60	41.60	-14.40	56.00	31.50	0.02	10.08	QP
11	0.73	25.90	-20.10	46.00	15.80	0.02	10.08	Average
12	0.73	35.40	-20.60	56.00	25.30	0.02	10.08	QP
13	11.20	31.06	-18.94	50.00	20.49	0.21	10.36	Average
14	11.20	38.86	-21.14	60.00	28.29	0.21	10.36	QP

3.2. Test of Radiated Emission Measurement

3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the the following table:

<Class B Limit>

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.2.2. Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.2.3. Test Procedures


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak), RBW=1MHz/VBW=10Hz (Average) for frequency above 1GHz).
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dB μ V/m) = 20 log Emission level (μ V/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz





3.2.5. Test Result of Radiated Emission

Test Engineer :	Xiangxiong Liang	Temperature :	24~25°C
		Relative Humidity :	48~49%
Test Distance :	3m	Polarization :	Horizontal
Remark :	#7 is system simulator signal which can be ignored.		




Site : 03CH01-SZ
 Condition : FCC CLASS-B 3m LF_ANT(35408)_6 HORIZONTAL

IMEI : 867638040015223/867638040016809

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	30.00	24.59	-15.41	40.00	31.26	24.40	0.23	31.30	---	---	Peak
2	100.81	24.78	-18.72	43.50	38.76	16.76	0.86	31.60	---	---	Peak
3	151.25	25.57	-17.93	43.50	39.05	16.60	1.31	31.39	---	---	Peak
4	192.96	27.41	-16.09	43.50	41.69	15.46	1.57	31.31	---	---	Peak
5	581.93	29.56	-16.44	46.00	33.80	24.30	2.95	31.49	---	---	Peak
6	891.36	31.65	-14.35	46.00	32.86	26.47	3.80	31.48	178	156	Peak
7	1960.00	50.37			71.46	30.87	6.03	57.99	---	---	Peak
8	2992.00	45.97	-28.03	74.00	61.73	32.64	8.91	57.31	---	---	Peak
9	4648.00	46.87	-27.13	74.00	59.66	33.84	10.73	57.36	---	---	Peak
10	6716.00	47.55	-26.45	74.00	55.27	34.99	15.74	58.45	---	---	Peak
11	7076.00	47.68	-26.32	74.00	57.33	35.02	14.16	58.83	100	52	Peak
12	10364.00	47.49	-26.51	74.00	54.85	37.02	14.61	58.99	---	---	Peak
13	12184.00	47.29	-26.71	74.00	51.05	38.54	15.03	57.33	---	---	Peak



Test Engineer :	Xiangxiong Liang	Temperature :	24~25°C
		Relative Humidity :	48~49%
Test Distance :	3m	Polarization :	Vertical
Remark :	#7 is system simulator signal which can be ignored.		



Site : 03CH01-SZ
 Condition : FCC CLASS-B 3m LF_ANT(35408)_6 VERTICAL

IMEI : 867638040015223/867638040016809

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	30.00	33.78	-6.22	40.00	40.45	24.40	0.23	31.30	152	135 Peak	
2	58.13	27.00	-13.00	40.00	45.29	12.82	0.49	31.60	---	---	Peak
3	156.10	26.74	-16.76	43.50	40.51	16.27	1.35	31.39	---	---	Peak
4	191.02	30.23	-13.27	43.50	44.57	15.42	1.56	31.32	---	---	Peak
5	607.15	29.25	-16.75	46.00	33.27	24.53	3.03	31.58	---	---	Peak
6	844.80	31.15	-14.85	46.00	32.53	26.33	3.68	31.39	---	---	Peak
7	1960.00	50.34			71.43	30.87	6.03	57.99	---	---	Peak
8	2882.00	44.72	-29.28	74.00	61.76	32.29	8.05	57.38	---	---	Peak
9	4758.00	45.66	-28.34	74.00	58.47	33.80	10.82	57.43	---	---	Peak
10	6640.00	46.84	-27.16	74.00	54.62	34.96	15.63	58.37	---	---	Peak
11	7274.00	45.42	-28.58	74.00	55.55	35.40	13.38	58.91	---	---	Peak
12	10962.00	46.48	-27.52	74.00	52.69	37.38	14.75	58.34	---	---	Peak
13	12180.00	46.95	-27.05	74.00	50.71	38.54	15.03	57.33	156	258 Peak	



4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Receiver	R&S	ESR7	101630	9kHz~7GHz;	Dec. 23, 2018	Jan. 25, 2019	Dec. 22, 2019	Conduction (CO01-SZ)
AC LISN	EMCO	3816/2SH	00103912	9kHz~30MHz	Oct. 18, 2018	Jan. 25, 2019	Oct. 17, 2019	Conduction (CO01-SZ)
AC LISN (for auxiliary equipment)	EMCO	3816/2SH	00103892	9kHz~30MHz	Dec. 23, 2018	Jan. 25, 2019	Dec. 22, 2019	Conduction (CO01-SZ)
AC Power Source	Chroma	61602	616020000891	100Vac~250Vac	Jul. 18, 2018	Jan. 25, 2019	Jul. 17, 2019	Conduction (CO01-SZ)
EMI Test Receiver&SA	Agilent	N9038A	MY52260185	20Hz~26.5GHz	Aug. 30, 2018	Jan. 21, 2019	Aug. 29, 2019	Radiation (03CH01-SZ)
Bilog Antenna	TeseQ	CBL6112D	35407	30MHz~2GHz	Jun. 05, 2018	Jan. 21, 2019	Jun. 04, 2019	Radiation (03CH01-SZ)
Double Ridge Horn Antenna	ETS Lindgren	3117	119436	1GHz~18GHz	Jun. 28, 2018	Jan. 21, 2019	Jun. 27, 2019	Radiation (03CH01-SZ)
LF Amplifier	Burgeon	BPA-530	102209	0.01~3000Mhz	Apr. 20, 2018	Jan. 21, 2019	Apr. 19, 2019	Radiation (03CH01-SZ)
HF Amplifier	MITEQ	AMF-7D-0010 1800-30-10P-R	1707137	1GHz~18GHz	Oct. 19, 2018	Jan. 21, 2019	Oct. 18, 2019	Radiation (03CH01-SZ)
AC Power Source	Chroma	61601	616010001985	N/A	NCR	Jan. 21, 2019	NCR	Radiation (03CH01-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Jan. 21, 2019	NCR	Radiation (03CH01-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Jan. 21, 2019	NCR	Radiation (03CH01-SZ)

NCR: No Calibration Required



5. Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.6dB
---	-------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.8dB
---	-------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0dB
---	-------