



# SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen,  
Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053  
Fax: +86 (0) 755 2671 0594  
Email: ee.shenzhen@sgs.com

Report No.: SZEM180600503301  
Page : 1 of 56

## FCC SAR TEST REPORT

**Application No:** SZEM1806005033RG  
**Applicant:** Huawei Technologies Co.,Ltd.  
**Manufacturer:** Huawei Technologies Co.,Ltd.  
**Factory:** Huawei Technologies Co.,Ltd.  
    **Product Name:** HUAWEI MediaPad T3  
    **Model No.(EUT):** KOB-W09  
    **Trade Mark:** HUAWEI  
**FCC ID:** QISKOB-W09  
**Standards:** FCC 47CFR §2.1093  
**Date of Receipt:** 2018-06-12  
**Date of Test:** 2018-06-12 to 2018-06-13  
**Date of Issue:** 2018-06-17  
**Test Result :** **PASS \***

\* In the configuration tested, the EUT detailed in this report complied with the standards specified above.

Authorized Signature:

Derek Yang

Wireless Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only

## REVISION HISTORY

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2018-06-17		Original

## TEST SUMMARY

Frequency Band	Test position	Test mode	Max Report SAR1-g (W/kg)	SAR limit (W/kg)	Verdict
WI-FI (2.4GHz)	Head	802.11b	0.49	1.6	PASS
WI-FI (2.4GHz)	Body	802.11b	<b>1.19</b>	1.6	PASS
WI-FI (5GHz)	Head	802.11n HT40	<b>0.72</b>	1.6	PASS
WI-FI (5GHz)	Body	802.11a	0.80	1.6	PASS


Approved & Released by



Simon Ling

SAR Manager

Tested by



Mark Liu

SAR Engineer

# CONTENTS

<b>1</b>	<b>GENERAL INFORMATION</b>	<b>6</b>
1.1	DETAILS OF CLIENT	6
1.2	TEST LOCATION	6
1.3	TEST FACILITY	7
1.4	GENERAL DESCRIPTION OF EUT	8
1.5	TEST SPECIFICATION	10
1.6	RF EXPOSURE LIMITS	10
<b>2</b>	<b>SAR MEASUREMENTS SYSTEM CONFIGURATION</b>	<b>11</b>
2.1	THE SAR MEASUREMENT SYSTEM	11
2.2	ISOTROPIC E-FIELD PROBE EX3DV4	12
2.3	DATA ACQUISITION ELECTRONICS (DAE)	13
2.4	SAM TWIN PHANTOM	13
2.5	ELI PHANTOM	14
2.6	DEVICE HOLDER FOR TRANSMITTERS	15
2.7	MEASUREMENT PROCEDURE	16
2.7.1	Scanning procedure	16
2.7.2	Data Storage	18
2.7.3	Data Evaluation by SEMCAD	18
<b>3</b>	<b>DESCRIPTION OF TEST POSITION</b>	<b>20</b>
3.1	THE HEAD TEST POSITION	20
3.1.1	SAM Phantom Shape	20
3.1.2	EUT constructions	20
3.1.3	Definition of the "cheek" position	21
3.1.4	Definition of the "tilted" position	22
3.1.5	Proximity Sensor Triggering Test for Head	23
3.2	THE BODY TEST POSITION	24
3.2.1	Proximity Sensor Triggering Test for body	24
<b>4</b>	<b>SAR SYSTEM VERIFICATION PROCEDURE</b>	<b>28</b>
4.1	TISSUE SIMULATE LIQUID	28
4.1.1	Recipes for Tissue Simulate Liquid	28
4.1.2	Measurement for Tissue Simulate Liquid	29
4.2	SAR SYSTEM VALIDATION	30
4.2.1	Justification for Extended SAR Dipole Calibrations	31
4.2.2	Summary System Validation Result(s)	32
4.2.3	Detailed System Validation Results	32

<b>5</b>	<b>TEST RESULTS AND MEASUREMENT DATA .....</b>	<b>33</b>
<b>5.1</b>	<b>OPERATION CONFIGURATIONS .....</b>	<b>33</b>
5.1.1	<i>WiFi Test Configuration .....</i>	<i>33</i>
5.1.2	<i>DUT Antenna Locations .....</i>	<i>39</i>
5.1.3	<i>Stand-alone SAR test evaluation .....</i>	<i>40</i>
<b>5.2</b>	<b>MEASUREMENT OF RF CONDUCTED POWER.....</b>	<b>41</b>
5.2.1	<i>Conducted Power Of WIFI and BT .....</i>	<i>41</i>
<b>5.3</b>	<b>MEASUREMENT OF SAR DATA.....</b>	<b>46</b>
5.3.1	<i>SAR Result Of 2.4GHz WIFI.....</i>	<i>46</i>
5.3.2	<i>SAR Result Of 5GHz WIFI(U-NII-2A).....</i>	<i>48</i>
5.3.3	<i>SAR Result Of 5GHz WIFI(U-NII-2C).....</i>	<i>49</i>
5.3.4	<i>SAR Result Of 5GHz WIFI(U-NII-3).....</i>	<i>50</i>
<b>5.4</b>	<b>MULTIPLE TRANSMITTER EVALUATION.....</b>	<b>52</b>
5.4.1	<i>Simultaneous SAR SAR test evaluation .....</i>	<i>52</i>
<b>6</b>	<b>EQUIPMENT LIST .....</b>	<b>53</b>
<b>7</b>	<b>MEASUREMENT UNCERTAINTY .....</b>	<b>54</b>
<b>8</b>	<b>CALIBRATION CERTIFICATE .....</b>	<b>55</b>
<b>9</b>	<b>PHOTOGRAPHS.....</b>	<b>55</b>
	<b>APPENDIX A: DETAILED SYSTEM VALIDATION RESULTS .....</b>	<b>56</b>
	<b>APPENDIX B: DETAILED TEST RESULTS .....</b>	<b>56</b>
	<b>APPENDIX C: CALIBRATION CERTIFICATE.....</b>	<b>56</b>
	<b>APPENDIX D: PHOTOGRAPHS .....</b>	<b>56</b>

# 1 General Information

## 1.1 Details of Client

Applicant:	Huawei Technologies Co.,Ltd.
Address:	Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C
Manufacturer:	Huawei Technologies Co.,Ltd.
Address:	Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C
Factory:	Huawei Technologies Co.,Ltd.
Address:	Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C

## 1.2 Test Location

Company: SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch E&E Lab  
Address: No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China  
Post code: 518057  
Telephone: +86 (0) 755 2601 2053  
Fax: +86 (0) 755 2671 0594  
E-mail: ee.shenzhen@sgs.com

### 1.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation (A2LA). Certificate No. 3816.01.

- **VCCI**

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

- **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

## 1.4 General Description of EUT

Product Name:	HUAWEI MediaPad T3		
Model No.(EUT):	KOB-W09		
Trade Mark:	HUAWEI		
Product Phase:	production unit		
Device Type :	portable device		
Exposure Category:	uncontrolled environment / general population		
FCC ID:	QISKOB-W09		
SN:	GQE4T17602000815		
Hardware Version:	HL1TRTM		
Software Version:	KOB-W09C100B007		
Antenna Type:	Inner Antenna		
<b>Device Operating Configurations :</b>			
Modulation Mode:	<b>WIFI:</b> DSSS,OFDM; <b>BT:</b> GFSK, π/4DQPSK,8DPSK		
Frequency Bands:	Band	Tx (MHz)	Rx (MHz)
	WIFI(2.4GHz)	2412-2462	2412-2462
	WIFI(5GHz)	5150-5250	5150-5250
		5250-5350	5250-5350
		5470-5725	5470-5725
BT	2402-2480	2402-2480	
Battery Information 1#:	Model No.:	HB3080G1EBW	
	Normal Voltage :	3.8V	
	Rated capacity :	4650mAh	
	Manufacturer:	Huawei Technologies Co.,Ltd.	
Battery Information 2#:	Model No.:	HB3080G1EBC	
	Normal Voltage :	3.8V	
	Rated capacity :	4650mAh	
	Manufacturer:	Huawei Technologies Co.,Ltd.	



The difference between model KOW-W09(new) and model KOB-W09(old) is show in the below table:

	KOB-W09(old)	KOB-W09(new)
CE bands	N/a	N/a
SIM card	N/a	N/a
NFC	N/a	N/a
FM	N/a	N/a
External camera	the same	the same
internal camera	the same	the same
FLASH	the same	the same
Mainboard	the same	the same
PCB layout	the same	the same
Appearance	the same	the same
Bluetooth mode	the same	the same
WLAN mode	the same	the same
BT/ WLAN antenna	the same	the same
GSM/ WCDMA /LTE antenna	N/a	N/a
Adapter	the same	the same
Battery	the same	the same
Chipset	the same	the same
Memory	the same	the same
Dimension	the same	the same
RF Parameter	the same	the same
Main Frequency NV	the same	the same
other		<ol style="list-style-type: none"> <li>1. Remove 3 grounding shrapnel of the main board;</li> <li>2. Remove 5 Common mode Choke and replace them with 0 ohm resistance;</li> <li>3. Replace one high Q inductor with a laminated inductor;</li> <li>4. Remove 4 TVS</li> </ol>

Note: According to the difference above, the KOB-W09(new) is test at the worst case of original test report SZEM170600606901 for WiFi 2.4G/5G&BT.

## 1.5 Test Specification

Identity	Document Title
FCC 47CFR §2.1093	Radiofrequency Radiation Exposure Evaluation: Portable Devices
ANSI/IEEE Std C95.1 – 1992	IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz – 300 GHz.
IEEE 1528-2013	Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
KDB 248227 D01 v02r02	802.11 Wi-Fi SAR
KDB 616217 D04 v01r02	SAR for laptop and tablets
KDB447498 D01 v06	General RF Exposure Guidance
KDB447498 D03 v01	Supplement C Cross-Reference
KDB 865664 D01 v01r04	SAR Measurement 100 MHz to 6 GHz
KDB 865664 D02 v01r02	RF Exposure Reporting

## 1.6 RF exposure limits

Human Exposure	Uncontrolled Environment General Population	Controlled Environment Occupational
<b>Spatial Peak SAR*</b> (Brain*Trunk)	<b>1.60 mW/g</b>	8.00 mW/g
<b>Spatial Average SAR**</b> (Whole Body)	0.08 mW/g	0.40 mW/g
<b>Spatial Peak SAR***</b> (Hands/Feet/Ankle/Wrist)	4.00 mW/g	20.00 mW/g

### Notes:

\* The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time

\*\* The Spatial Average value of the SAR averaged over the whole body.

\*\*\* The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

**Uncontrolled Environments** are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

**Controlled Environments** are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation.)

## 2 SAR Measurements System Configuration

### 2.1 The SAR Measurement System

This SAR Measurement System uses a Computer-controlled 3-D stepper motor system (SPEAG DASY5 professional system). A E-field probe is used to determine the internal electric fields. The SAR can be obtained from the equation  $SAR = \sigma (|E|^2) / \rho$  where  $\sigma$  and  $\rho$  are the conductivity and mass density of the tissue-Simulate.


The DASY5 system for performing compliance tests consists of the following items:

A standard high precision 6-axis robot (Stabile RX family) with controller, teach pendant and software .An arm extension for accommodation the data acquisition electronics (DAE).

A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.

A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.


The Electro-optical converter (EOC) performs the conversion between optical and electrical of the signals for the digital communication to DAE and for the analog signal from the optical surface detection. The EOC is connected to the measurement server.




F-1. SAR Measurement System Configuration

- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- A probe alignment unit which improves the (absolute) accuracy of the probe positioning.
- A computer operating Windows 7.
- DASY5 software.
- Remote control with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
- The SAM twin phantom enabling testing left-hand, right-hand and Body Worn usage.
- The device holder for handheld mobile phones.
- Tissue simulating liquid mixed according to the given recipes.
- Validation dipole kits allowing to validating the proper functioning of the system.


## 2.2 Isotropic E-field Probe EX3DV4

	<p>Symmetrical design with triangular core          Built-in shielding against static charges          PEEK enclosure material (resistant to organic solvents, e.g., DGBE)</p>
<b>Calibration</b>	ISO/IEC 17025 <a href="#">calibration service</a> available.
<b>Frequency</b>	10 MHz to > 6 GHz Linearity: $\pm 0.2$ dB (30 MHz to 6 GHz)
<b>Directivity</b>	$\pm 0.3$ dB in TSL (rotation around probe axis) $\pm 0.5$ dB in TSL (rotation normal to probe axis)
<b>Dynamic Range</b>	10 $\mu$ W/g to > 100 mW/g Linearity: $\pm 0.2$ dB (noise: typically < 1 $\mu$ W/g)
<b>Dimensions</b>	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm
<b>Application</b>	High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields); the only probe that enables compliance testing for frequencies up to 6 GHz with precision of better 30%.
<b>Compatibility</b>	DASY3, DASY4, DASY52 SAR and higher, EASY4/MRI

## 2.3 Data Acquisition Electronics (DAE)

<b>Model</b>	DAE3,DAE4	
<b>Construction</b>	Signal amplifier, multiplexer, A/D converter and control logic. Serial optical link for communication with DASY4/5 embedded system (fully remote controlled). Two step probe touch detector for mechanical surface detection and emergency robot stop.	
<b>Measurement Range</b>	-100 to +300 mV (16 bit resolution and two range settings: 4mV,400mV)	
<b>Input Offset Voltage</b>	< 5µV (with auto zero)	
<b>Input Bias Current</b>	< 50 f A	
<b>Dimensions</b>	60 x 60 x 68 mm	


## 2.4 SAM Twin Phantom

<b>Material</b>	Vinylester, glass fiber reinforced (VE-GF)	
<b>Liquid Compatibility</b>	Compatible with all SPEAG tissue simulating liquids (incl. DGBE type)	
<b>Shell Thickness</b>	2 ± 0.2 mm (6 ± 0.2 mm at ear point)	
<b>Dimensions (incl. Wooden Support)</b>	Length: 1000 mm Width: 500 mm Height: adjustable feet	
<b>Filling Volume</b>	approx. 25 liters	
<b>Wooden Support</b>	SPEAG standard phantom table	

The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528 and IEC 62209-1. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot.

Twin SAM V5.0 has the same shell geometry and is manufactured from the same material as Twin SAM V4.0, but has reinforced top structure.

## 2.5 ELI Phantom

<b>Material</b>	Vinylester, glass fiber reinforced (VE-GF)	
<b>Liquid Compatibility</b>	Compatible with all SPEAG tissue simulating liquids (incl. DGBE type)	
<b>Shell Thickness</b>	2.0 ± 0.2 mm (bottom plate)	
<b>Dimensions</b>	Major axis: 600 mm Minor axis: 400 mm	
<b>Filling Volume</b>	approx. 30 liters	
<b>Wooden Support</b>	SPEAG standard phantom table	

Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI is fully compatible with the IEC 62209-2 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles.

ELI V5.0 has the same shell geometry and is manufactured from the same material as ELI4, but has reinforced top structure.

## 2.6 Device Holder for Transmitters



F-2. Device Holder for Transmitters

- The DASY device holder is designed to cope with different positions given in the standard. It has two scales for the device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear reference points). The rotation centres for both scales are the ear reference point (ERP). Thus the device needs no repositioning when changing the angles.
- The DASY device holder has been made out of low-loss POM material having the following dielectric parameters: relative permittivity  $\epsilon=3$  and loss tangent  $\delta=0.02$ . The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.

## 2.7 Measurement procedure

### 2.7.1 Scanning procedure

#### Step 1: Power reference measurement

The “reference” and “drift” measurements are located at the beginning and end of the batch process. They measure the field drift at one single point in the liquid over the complete procedure.

#### Step 2: Area scan

The SAR distribution at the exposed side of the head was measured at a distance of 4mm from the inner surface of the shell. The area covered the entire dimension of the head and the horizontal grid spacing was 15mm\*15mm or 12mm\*12mm or 10mm\*10mm. Based on the area scan data, the area of the maximum absorption was determined by spline interpolation.

#### Step 3: Zoom scan

Around this point, a volume of 30mm\*30mm\*30mm (fine resolution volume scan, zoom scan) was assessed by measuring 5x5x7 points ( $\leq 2\text{GHz}$ ) and 7x7x7 points ( $\geq 2\text{GHz}$ ). On this basis of this data set, the spatial peak SAR value was evaluated with the following procedure:

The data at the surface was extrapolated, since the centre of the dipoles is 2.0mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.2mm. (This can be variable. Refer to the probe specification). The extrapolation was based on a least square algorithm. A polynomial of the fourth order was calculated through the points in z-axes. This polynomial was then used to evaluate the points between the surface and the probe tip. The maximum interpolated value was searched with a straight-forward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1g or 10g) were computed using the 3D-Spline interpolation algorithm. The volume was integrated with the trapezoidal algorithm. One thousand points were interpolated to calculate the average. All neighbouring volumes were evaluated until no neighboring volume with a higher average value was found.

The area and zoom scan resolutions specified in the table below must be applied to the SAR measurements. Probe boundary effect error compensation is required for measurements with the probe tip closer than half a probe tip diameter to the phantom surface. Both the probe tip diameter and sensor offset distance must satisfy measurement protocols; to ensure probe boundary effect errors are minimized and the higher fields closest to the phantom surface can be correctly measured and extrapolated to the phantom surface for computing 1-g SAR. Tolerances of the post-processing algorithms must be verified by the test laboratory for the scan resolutions used in the SAR measurements, according to the reference distribution functions specified in IEEE Std. 1528-2013.



		$\leq 3$ GHz	$> 3$ GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface		$5 \pm 1$ mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location		$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: $\Delta x_{Area}$ , $\Delta y_{Area}$		$\leq 2$ GHz: $\leq 15$ mm 2 – 3 GHz: $\leq 12$ mm	3 – 4 GHz: $\leq 12$ mm 4 – 6 GHz: $\leq 10$ mm
		When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: $\Delta x_{Zoom}$ , $\Delta y_{Zoom}$		$\leq 2$ GHz: $\leq 8$ mm 2 – 3 GHz: $\leq 5$ mm*	3 – 4 GHz: $\leq 5$ mm* 4 – 6 GHz: $\leq 4$ mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{Zoom}(n)$	$\leq 5$ mm	3 – 4 GHz: $\leq 4$ mm 4 – 5 GHz: $\leq 3$ mm 5 – 6 GHz: $\leq 2$ mm
	graded grid	$\Delta z_{Zoom}(1)$ : between 1 <sup>st</sup> two points closest to phantom surface	$\leq 4$ mm
		$\Delta z_{Zoom}(n>1)$ : between subsequent points	$\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$
Minimum zoom scan volume	x, y, z	$\geq 30$ mm	3 – 4 GHz: $\geq 28$ mm 4 – 5 GHz: $\geq 25$ mm 5 – 6 GHz: $\geq 22$ mm
<p>Note: <math>\delta</math> is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.</p> <p>* When zoom scan is required and the <u>reported</u> SAR from the <u>area scan based 1-g SAR estimation</u> procedures of KDB 447498 is <math>\leq 1.4</math> W/kg, <math>\leq 8</math> mm, <math>\leq 7</math> mm and <math>\leq 5</math> mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.</p>			

#### Step 4: Power reference measurement (drift)

The Power Drift Measurement job measures the field at the same location as the most recent power reference measurement job within the same procedure, and with the same settings. The indicated drift is mainly the variation of the DUT's output power and should vary max.  $\pm 5\%$

## 2.7.2 Data Storage

The DASY software stores the acquired data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors), together with all necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files with the extension "DAE". The software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of incorrect parameter settings. For example, if a measurement has been performed with a wrong crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be re-evaluated. The measured data can be visualized or exported in different units or formats, depending on the selected probe type ([V/m], [A/m], [°C], [m W/g], [m W/cm<sup>2</sup>], [dBrel], etc.). Some of these units are not available in certain situations or show meaningless results, e.g., a SAR output in a lossless media will always be zero. Raw data can also be exported to perform the evaluation with other software packages.

## 2.7.3 Data Evaluation by SEMCAD

The SEMCAD software automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Probe parameters:	- Sensitivity	Normi, ai0, ai1, ai2
- Conversion factor	ConvFi	
- Diode compression point	Dcpi	
Device parameters:	- Frequency	f
- Crest factor	cf	
Media parameters:	- Conductivity	ε
- Density	ρ	

These parameters must be set correctly in the software. They can be found in the component documents or they can be imported into the software from the configuration files issued for the DASY components. In the direct measuring mode of the multimeter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics.

If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power.

The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot c f / d c p_i$$

With  $V_i$  = compensated signal of channel  $i$  ( $i = x, y, z$ )

$U_i$  = input signal of channel  $i$  ( $i = x, y, z$ )

cf = crest factor of exciting field (DASY parameter)

dcp  $i$  = diode compression point (DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

E-field probes:

$$E_i = (V_i / \text{Norm}_i \cdot \text{ConvF})^{1/2}$$

H-field probes:

$$H_i = (V_i)^{1/2} \cdot (a_{i0} + a_{i1}f + a_{i2}f^2) / f$$

With  $V_i$  = compensated signal of channel  $i$  ( $i = x, y, z$ )

$\text{Norm}_i$  = sensor sensitivity of channel  $i$  ( $i = x, y, z$ )

[mV/(V/m)<sup>2</sup>] for E-field Probes

ConvF = sensitivity enhancement in solution

$a_{ij}$  = sensor sensitivity factors for H-field probes

$f$  = carrier frequency [GHz]

$E_i$  = electric field strength of channel  $i$  in V/m

$H_i$  = magnetic field strength of channel  $i$  in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = (E_x^2 + E_y^2 + E_z^2)^{1/2}$$

The primary field data are used to calculate the derived field units.

$$SAR = (E_{tot}^2 \cdot \sigma) / (\epsilon \cdot 1000)$$

with SAR = local specific absorption rate in mW/g

$E_{tot}$  = total field strength in V/m

$\sigma$  = conductivity in [mho/m] or [Siemens/m]

$\epsilon$  = equivalent tissue density in g/cm<sup>3</sup>

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid. The power flow density is calculated assuming the excitation field to be a free space field.

$$P_{pwe} = E_{tot}^2 / 3770 \quad \text{or} \quad P_{pwe} = H_{tot}^2 \cdot 37.7$$

with  $P_{pwe}$  = equivalent power density of a plane wave in mW/cm<sup>2</sup>

$E_{tot}$  = total electric field strength in V/m

$H_{tot}$  = total magnetic field strength in A/m

### 3 Description of Test Position


#### 3.1 The Head Test Position

##### 3.1.1 SAM Phantom Shape




F-3. Front, back, and side views of SAM (model for the phantom shell). Full-head model is for illustration purposes only-procedures in this recommended practice are intended primarily for the phantom setup.


Note: The centre strip including the nose region has a different thickness tolerance.



F-4. Sagittally bisected phantom with extended perimeter (shown placed on its side as used for SAR measurements)




F-5. Close-up side view of phantom, showing the ear region, N-F and B-M lines, and seven cross-sectional plane locations




F-6. Side view of the phantom showing relevant markings and seven cross-sectional plane locations

##### 3.1.2 EUT constructions



F-7. Handset vertical and horizontal reference lines—"fixed case"




F-8. Handset vertical and horizontal reference lines—"clam-shell case"

### 3.1.3 Definition of the "cheek" position


- a) Position the device with the vertical centre line of the body of the device and the horizontal line crossing the centre of the ear piece in a plane parallel to the sagittal plane of the phantom ("initial position"). While maintaining the device in this plane, align the vertical centre line with the reference plane containing the three ear and mouth reference points (M, RE and LE) and align the centre of the ear piece with the line RE-LE.
- b) Translate the mobile phone box towards the phantom with the ear piece aligned with the line LE-RE until telephone touches the ear. While maintaining the device in the reference plane and maintaining the phone contact with the ear, move the bottom of the box until any point on the front side is in contact with the cheek of the phantom or until contact with the ear is lost.

### 3.1.4 Definition of the “tilted” position

- a) Position the device in the “cheek” position described above;
- b) While maintaining the device in the reference plane described above and pivoting against the ear, move it outward away from the mouth by an angle of 15 degrees or until contact with the ear is lost.




F-9. Definition of the reference lines and points, on the phone and on the phantom and initial position



F-10. “Cheek” and “tilt” positions of the mobile phone on the left side

### 3.1.5 Proximity Sensor Triggering Test for Head

For Head exposure condition, device tilt angle influences to proximity sensor triggering is determined as below:  
 Firstly, the DUT was positioned directly touch the SAM phantom (Left& Right hand touch cheek position) for each band. Rotate the DUT around the ear reference point of the phantom in 5° increments until the DUT is 15° or more away from the touch cheek position at 0°  
 Then the DUT is positioned at 15° or more away from the touch cheek position and moved towards the phantom in 5°increments until the DUT directly touch the SAM phantom at 0°(Left & Right hand touch cheek position).



The DUT is moved towards and away from SAM phantom.

angle between phantom to DUT in degree	0	5	10	15	20	25	30
Condition of Sensor	on	on	on	on	on	on	on

Based on the validation results above, angle tilt coverage can ensure that the proximity sensor is triggered for all the Head test positions(Left/Right Hand Touched cheek, Left/Right Hand tiled 15 °)


## 3.2 The Body Test Position

The overall diagonal dimension of the display section of a tablet is > 20 cm, Per FCC KDB 616217, the back surface and edges of the tablet should be tested for SAR compliance with the tablet touching the phantom. SAR evaluation for the front surface of tablet display screens are generally not necessary. The SAR Exclusion Threshold in KDB 447498 D01 can be applied to determine SAR test exclusion for adjacent edge configurations. The closest distance from the antenna to an adjacent tablet edge is used to determine if SAR testing is required for the adjacent edges, with the adjacent edge positioned against the phantom and the edge containing the antenna positioned perpendicular to the phantom.

### 3.2.1 Proximity Sensor Triggering Test for body

#### 1) Proximity sensor triggering distances

The Proximity sensor triggering was applied to WIFI. Proximity sensor triggering distance testing was performed according to the procedures outlined in KDB 616217 D04 section 6.2, and EUT moving further away from the flat phantom and EUT moving toward the flat phantom were both assessed.



Proximity Sensor Triggering Distance(mm)		
Position	Back	Top
Minimum	12	13
Required SAR Test	11	12




Antenna	Band	Trigger Condition	Body exposure condition
			Power reduction(dB)
WIFI Antenna	2.4GHz	Back side: Close to 12mm Top side: Close to 13mm	4.2
	5GHz	Back side: Close to 12mm Top side: Close to 13mm	7


Note: SAR tests with proximity sensor power reduction are only required for the sides of frequency bands in the table above. For the other sides or other frequency bands of the device, SAR is still tested at the maximum power level with sensor off.

Band/Mode	Ch#	Measured Power(dBm)		Reduction levels(dB)
		Max. Power	Power back-off	
WIFI 2.4GHz	6	16.45	12.52	3.93
WIFI 5GHz	120	15.44	8.61	6.83

● DUT Moving Toward (Trigger) the Phantom




Gap (mm)




Gap (mm)

- DUT Moving Away (Release) from the Phantom



Gap (mm)



Gap (mm)

## 2) Proximity sensor coverage


If a sensor is spatially offset from the antenna(s), it is necessary to verify sensor triggering for conditions where the antenna is next to the user but the sensor is laterally further away to ensure sensor coverage is sufficient for reducing the power to maintain compliance. For p-sensor coverage testing, the device is moved and “along the direction of maximum antenna and sensor offset”.

The proximity sensor and main antenna use same metallic electrode, so there is no spatial offset.

## 3) Device tilt angle influences to proximity sensor triggering

The influence of device tilt angles to proximity sensor triggering was determined by positioning each tablet edge that contains a transmitting antenna, perpendicular to the flat phantom, at 13 mm separation.

Rotating the tablet around the edge next to the phantom in  $\leq 10^\circ$  increments until the tablet is  $\pm 45^\circ$  from the vertical position at  $0^\circ$ , and the maximum output power remains in the reduced mode.



The Sensor Triggering Distance(mm)	
Position	Top
Minimum	13
Required SAR Test	12

Summary of Tablet Tilt Angle Influence to Proximity Sensor Triggering for Right Side													
Band(MHz)	Minimum trigger distance Per KDB616217§6.2	Minimum trigger distance at which power reduction was maintained over $\pm 45^\circ$	Power Reduction Status										
			$-45^\circ$	$-35^\circ$	$-25^\circ$	$-15^\circ$	$-5^\circ$	$0^\circ$	$5^\circ$	$15^\circ$	$25^\circ$	$35^\circ$	$45^\circ$
WIFI 2.4GHz	13mm	13mm	on	on	on	on	on	on	on	on	on	on	on
WIFI 5GHz	13mm	13mm	on	on	on	on	on	on	on	on	on	on	on

## 4 SAR System Verification Procedure

### 4.1 Tissue Simulate Liquid

#### 4.1.1 Recipes for Tissue Simulate Liquid

The following tables give the recipes for tissue simulating liquids to be used in different frequency bands:

Ingredients (% by weight)	Frequency (MHz)							
	450		700-950		1700-2000		2300-2700	
Tissue Type	Head	Body	Head	Body	Head	Body	Head	Body
Water	38.56	51.16	40.30	50.75	55.24	70.17	55.00	68.53
Salt (NaCl)	3.95	1.49	1.38	0.94	0.31	0.39	0.2	0.1
Sucrose	56.32	46.78	57.90	48.21	0	0	0	0
HEC	0.98	0.52	0.24	0	0	0	0	0
Bactericide	0.19	0.05	0.18	0.10	0	0	0	0
Tween	0	0	0	0	44.45	29.44	44.80	31.37
Salt: 99+% Pure Sodium Chloride				Sucrose: 98+% Pure Sucrose				
Water: De-ionized, 16 MΩ <sup>+</sup> resistivity				HEC: Hydroxyethyl Cellulose				
Tween: Polyoxyethylene (20) sorbitan monolaurate								
HSL5GHz is composed of the following ingredients:								
Water: 50-65%								
Mineral oil: 10-30%								
Emulsifiers: 8-25%								
Sodium salt: 0-1.5%								
MSL5GHz is composed of the following ingredients:								
Water: 64-78%								
Mineral oil: 11-18%								
Emulsifiers: 9-15%								
Sodium salt: 2-3%								

Table 1 : Recipe of Tissue Simulate Liquid

#### 4.1.2 Measurement for Tissue Simulate Liquid


The dielectric properties for this Tissue Simulate Liquids were measured by using the Agilent Model 85070E Dielectric Probe in conjunction with Agilent E5071C Network Analyzer (300 KHz-8500 MHz). The Conductivity ( $\sigma$ ) and Permittivity ( $\rho$ ) are listed in Table 2. For the SAR measurement given in this report. The temperature variation of the Tissue Simulate Liquids was  $22\pm 2^\circ\text{C}$ .

Measurement for Tissue Simulate Liquid							
Tissue Type	Measured Frequency (MHz)	Target Tissue ( $\pm 5\%$ )		Measured Tissue		Liquid Temp.	Measured Date
		$\epsilon_r$	$\sigma(\text{S/m})$	$\epsilon_r$	$\sigma(\text{S/m})$	( $^\circ\text{C}$ )	
2450 Head	2450	39.20 (37.24~41.16)	1.80 (1.71~1.89)	38.488	1.878	22	2018/6/12
2450 Body	2450	52.70 (50.07~55.34)	1.95 (1.85~2.05)	52.667	1.969	22	2018/6/12
5750 Head	5750	35.4 (33.63~37.17)	5.22 (4.96~5.48)	35.143	5.363	22.2	2018/6/12
5750 Body	5750	48.3 (45.89~50.72)	5.94 (5.64~6.24)	47.096	5.969	22.2	2018/6/12

Table 2 : Measurement result of Tissue electric parameters

## 4.2 SAR System Validation

The microwave circuit arrangement for system verification is sketched in F-3. The daily system accuracy verification occurs within the flat section of the SAM phantom. A SAR measurement was performed to see if the measured SAR was within +/- 10% from the target SAR values. The tests were conducted on the same days as the measurement of the EUT. The obtained results from the system accuracy verification are displayed in the table 3 (A power level of 250mw was input to the dipole antenna for below 3GHz, A power level of 100mw was input to the dipole antenna for 3–6GHz). During the tests, the ambient temperature of the laboratory was in the range  $22\pm 2^{\circ}\text{C}$ , the relative humidity was in the range 60% and the liquid depth above the ear reference points was above 15 cm in all the cases. It is seen that the system is operating within its specification, as the results are within acceptable tolerance of the reference values.



F-11. the microwave circuit arrangement used for SAR system verification

#### 4.2.1 Justification for Extended SAR Dipole Calibrations

1) Referring to KDB865664 D01 requirements for dipole calibration, instead of the typical annual calibration recommended by measurement standards, longer calibration intervals of up to three years may be considered when it is demonstrated that the SAR target, impedance and return loss of a dipole have remain stable according to the following requirements. Each measured dipole is expected to evaluate with the following criteria at least on annual interval in Appendix C.

- a) There is no physical damage on the dipole;
- b) System check with specific dipole is within 10% of calibrated value;
- c) Return-loss is within 10% of calibrated measurement;
- d) Impedance is within 5Ω from the previous measurement.

2) Network analyzer probe calibration against air, distilled water and a shorting block performed before measuring liquid parameters.

## 4.2.2 Summary System Validation Result(s)

Validation Kit		Measured SAR 250mW	Measured SAR 250mW	Measured SAR (normalized to 1w)	Measured SAR (normalized to 1w)	Target SAR (normalized to 1w) (±10%)	Target SAR (normalized to 1w) (±10%)	Liquid Temp. (°C)	Measured Date
		1g (W/kg)	10g (W/kg)	1g (W/kg)	10g (W/kg)	1-g(W/kg)	10-g(W/kg)		
D2450V2	Head	13.70	6.33	54.8	25.32	53.1 (47.79-58.41)	24.9 (22.41-27.39)	22	2018/6/12
	Body	12.60	5.93	50.4	23.72	51.0 (45.9-56.1)	23.5 (21.15-25.85)	22	2018/6/12
Validation Kit		Measured SAR 100mW	Measured SAR 100mW	Measured SAR (normalized to 1w)	Measured SAR (normalized to 1w)	Target SAR (normalized to 1w) (±10%)	Target SAR (normalized to 1w) (±10%)	Liquid Temp. (°C)	Measured Date
		1g (W/kg)	10g (W/kg)	1g (W/kg)	10g (W/kg)	1-g(W/kg)	10-g(W/kg)		
D5GHzV2	Head (5.75GHz)	8.52	2.42	85.2	24.2	80 (72-88)	22.7 (20.43-24.97)	22.2	2018/6/12
	Body (5.75GHz)	7.55	2.09	75.5	20.9	74.8 (67.32-82.28)	21 (18.9-23.1)	22.2	2018/6/12

Table 3 : SAR System Validation Result

## 4.2.3 Detailed System Validation Results

Please see the Appendix A



## 5 Test results and Measurement Data


### 5.1 Operation Configurations

#### 5.1.1 WiFi Test Configuration

A Wi-Fi device must be configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools for SAR measurement.


- 2.4G WIFI

Duty cycle= $\frac{632}{672}=94.05\%$




- 5G WIFI 802.11a

Duty cycle=632/672=94.05%



- 5G WIFI 802.11nHT40

Duty cycle=632/672=94.05%



#### 5.1.1.1 Initial Test Position SAR Test Reduction Procedure

DSSS and OFDM configurations are considered separately according to the required SAR procedures. SAR is measured in the initial test position using the 802.11 transmission mode configuration required by the DSSS procedure or initial test configuration and subsequent test configuration(s) according to the OFDM procedures. The initial test position procedure is described in the following:

- 1) . When the reported SAR of the initial test position is  $\leq 0.4$  W/kg, further SAR measurement is not required for the other (remaining) test positions in that exposure configuration and 802.11 transmission mode combinations within the frequency band or aggregated band. SAR is also not required for that exposure configuration in the subsequent test configuration(s).
- 2) . When the reported SAR of the initial test position is  $> 0.4$  W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position using subsequent highest extrapolated or estimated 1-g SAR conditions determined by area scans or next closest/smallest test separation distance and maximum RF coupling test positions based on manufacturer justification, on the highest maximum output power channel, until the reported SAR is  $\leq 0.8$  W/kg or all required test positions (left, right, touch, tilt or subsequent surfaces and edges) are tested.
- 3) . For all positions/configurations tested using the initial test position and subsequent test positions, when the reported SAR is  $> 0.8$  W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is  $\leq 1.2$  W/kg or all required channels are tested. a) Additional power measurements may be required for this step, which should be limited to those necessary for identifying the subsequent highest output power channels.

#### 5.1.1.2 Initial Test Configuration Procedures

An initial test configuration is determined for OFDM transmission modes according to the channel bandwidth, modulation and data rate combination(s) with the highest maximum output power specified for production units in each standalone and aggregated frequency band. SAR is measured using the highest measured maximum output power channel. For configurations with the same specified or measured maximum output power, additional transmission mode and test channel selection procedures are required. SAR test reduction for subsequent highest output test channels is determined according to *reported* SAR of the initial test configuration. For next to the ear, hotspot mode and UMC mini-tablet exposure configurations where multiple test positions are required, the initial test position procedure is applied to minimize the number of test positions required for SAR measurement using the initial test configuration transmission mode. For fixed exposure conditions that do not have multiple SAR test positions, SAR is measured in the transmission mode determined by the initial test configuration.

When the *reported* SAR of the initial test configuration is  $> 0.8$  W/kg, SAR measurement is required for subsequent next highest measured output power channel(s) in the initial test configuration until *reported* SAR is  $\leq 1.2$  W/kg or all required channels are tested.

#### 5.1.1.3 Subsequent Test Configuration Procedures

SAR measurement requirements for the remaining 802.11 transmission mode configurations that have not been tested in the initial test configuration are determined separately for each standalone and aggregated frequency band, in each exposure condition, according to the maximum output power specified for production units. The initial test position procedure is applied to next to the ear, UMPC mini-tablet and hotspot mode configurations. When the same maximum output power is specified for multiple transmission modes, additional power measurements may be required to determine if SAR measurements are required for subsequent highest output power channels in a subsequent test configuration. The subsequent test configuration and SAR measurement procedures are described in the following.

- 1) . When SAR test exclusion provisions of KDB Publication 447498 are applicable and SAR measurement is not required for the initial test configuration, SAR is also not required for the next highest maximum output power transmission mode subsequent test configuration(s) in that frequency band or aggregated band and exposure configuration.
- 2) . When the highest *reported* SAR for the initial test configuration (when applicable, include subsequent highest output channels), according to the initial test position or fixed exposure position requirements, is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is  $\leq 1.2$  W/kg, SAR is not required for that subsequent test configuration.

- 3) . The number of channels in the initial test configuration and subsequent test configuration can be different due to differences in channel bandwidth. When SAR measurement is required for a subsequent test configuration and the channel bandwidth is smaller than that in the initial test configuration, all channels in the subsequent test configuration that overlap with the larger bandwidth channel tested in the initial test configuration should be used to determine the highest maximum output power channel. This step requires additional power measurement to identify the highest maximum output power channel in the subsequent test configuration to determine SAR test reduction.
  - a) SAR should first be measured for the channel with highest measured output power in the subsequent test configuration.
  - b) SAR for subsequent highest measured maximum output power channels in the subsequent test configuration is required only when the *reported* SAR of the preceding higher maximum output power channel(s) in the subsequent test configuration is  $> 1.2$  W/kg or until all required channels are tested.
    - i) For channels with the same measured maximum output power, SAR should be measured using the channel closest to the center frequency of the larger channel bandwidth channel in the initial test configuration.
- 4) . SAR measurements for the remaining highest specified maximum output power OFDM transmission mode configurations that have not been tested in the initial test configuration (highest maximum output) or subsequent test configuration(s) (subsequent next highest maximum output power) is determined by recursively applying the subsequent test configuration procedures in this section to the remaining configurations according to the following:
  - a) replace “subsequent test configuration” with “next subsequent test configuration” (i.e., subsequent next highest specified maximum output power configuration)
  - b) replace “initial test configuration” with “all tested higher output power configurations”

#### 5.1.1.4 2.4 GHz SAR Procedures

Separate SAR procedures are applied to DSSS and OFDM configurations in the 2.4 GHz band to simplify DSSS test requirements. For 802.11b DSSS SAR measurements, DSSS SAR procedure applies to fixed exposure test position and initial test position procedure applies to multiple exposure test positions. When SAR measurement is required for an OFDM configuration, the initial test configuration, subsequent test configuration and initial test position procedures are applied. The SAR test exclusion requirements for 802.11g/n OFDM configurations are described in following.

- **802.11b DSSS SAR Test Requirements**

SAR is measured for 2.4 GHz 802.11b DSSS using either a fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

- 1) . When the reported SAR of the highest measured maximum output power channel for the exposure configuration is  $\leq 0.8$  W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.
- 2) . When the reported SAR is  $> 0.8$  W/kg, SAR is required for that exposure configuration using the next highest measured output power channel. When any reported SAR is  $> 1.2$  W/kg, SAR is required for the third channel; i.e., all channels require testing.

- **2.4 GHz 802.11g/n OFDM SAR Test Exclusion Requirements**

When SAR measurement is required for 2.4 GHz 802.11g/n OFDM configurations, the measurement and test reduction procedures for OFDM are applied (section 5.3, including sub-sections). SAR is not required for the following 2.4 GHz OFDM conditions.

- 1) . When KDB Publication 447498 SAR test exclusion applies to the OFDM configuration.
- 2) . When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is  $\leq 1.2$  W/kg.

### 5.1.1.5 WiFi 5G SAR Test Procedures

#### 5.1.1.5.1 U-NII-1 and U-NII-2A Bands

For devices that operate in only one of the U-NII-1 and U-NII-2A bands, the normally required SAR procedures for OFDM configurations are applied. For devices that operate in both U-NII bands using the same transmitter and antenna(s), SAR test reduction is determined according to the following:

- 1) When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest *reported* SAR for a test configuration is  $\leq 1.2$  W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition); otherwise, both bands are tested independently for SAR.
- 2) When different maximum output power is specified for the bands, begin SAR measurement in the band with higher specified maximum output power. The highest *reported* SAR for the tested configuration is adjusted by the ratio of lower to higher specified maximum output power for the two bands. When the adjusted SAR is  $\leq 1.2$  W/kg, SAR is not required for the band with lower maximum output power in that test configuration; otherwise, both bands are tested independently for SAR.
- 3) The two U-NII bands may be aggregated to support a 160 MHz channel on channel number 50. Without additional testing, the maximum output power for this is limited to the lower of the maximum output power certified for the two bands. When SAR measurement is required for at least one of the bands and the highest *reported* SAR adjusted by the ratio of specified maximum output power of aggregated to standalone band is  $> 1.2$  W/kg, SAR is required for the 160 MHz channel. This procedure does not apply to an aggregated band with maximum output higher than the standalone band(s); the aggregated band must be tested independently for SAR. SAR is not required when the 160 MHz channel is operating at a reduced maximum power and also qualifies for SAR test exclusion.

#### 5.1.1.5.2 U-NII-2C and U-NII-3 Bands

The frequency range covered by these bands is 380 MHz (5.47 – 5.85 GHz), which requires a minimum of at least two SAR probe calibration frequency points to support SAR measurements. When Terminal Doppler Weather Radar (TDWR) restriction applies, all channels that operate at 5.60 – 5.65 GHz must be included to apply the SAR test reduction and measurement procedures.

When the same transmitter and antenna(s) are used for U-NII-2C band and U-NII-3 band or 5.8 GHz band of §15.247, the bands may be aggregated to enable additional channels with 20, 40 or 80 MHz bandwidth to span across the band gap, as illustrated in Appendix B. The maximum output power for the additional band gap channels is limited to the lower of those certified for the bands. Unless band gap channels are permanently disabled, they must be considered for SAR testing. The frequency range covered by these bands is 380 MHz (5.47 – 5.85 GHz), which requires a minimum of at least two SAR probe calibration frequency points to support SAR measurements. To maintain SAR measurement accuracy and to facilitate test reduction, the channels in U-NII-2C band above 5.65 GHz may be grouped with the 5.8 GHz channels in U-NII-3 or §15.247 band to enable two SAR probe calibration frequency points to cover the bands, including the band gap channels. When band gap channels are supported and the bands are not aggregated for SAR testing, band gap channels must be considered independently in each band according to the normally required OFDM SAR measurement and probe calibration frequency points requirements.

#### **5.1.1.5.3 OFDM Transmission Mode SAR Test Configuration and Channel Selection Requirements**


The initial test configuration for 5 GHz OFDM transmission modes is determined by the 802.11 configuration with the highest maximum output power specified for production units, including tune-up tolerance, in each standalone and aggregated frequency band. SAR for the initial test configuration is measured using the highest maximum output power channel determined by the default power measurement procedures. When multiple configurations in a frequency band have the same specified maximum output power, the initial test configuration is determined according to the following steps applied sequentially.

- 1) The largest channel bandwidth configuration is selected among the multiple configurations with the same specified maximum output power.
- 2) If multiple configurations have the same specified maximum output power and largest channel bandwidth, the lowest order modulation among the largest channel bandwidth configurations is selected.
- 3) If multiple configurations have the same specified maximum output power, largest channel bandwidth and lowest order modulation, the lowest data rate configuration among these configurations is selected.
- 4) When multiple transmission modes (802.11a/g/n/ac) have the same specified maximum output power, largest channel bandwidth, lowest order modulation and lowest data rate, the lowest order 802.11 mode is selected; i.e., 802.11a is chosen over 802.11n then 802.11ac or 802.11g is chosen over 802.11n. After an initial test configuration is determined, if multiple test channels have the same measured maximum output power, the channel chosen for SAR measurement is determined according to the following. These channel selection procedures apply to both the initial test configuration and subsequent test configuration(s), with respect to the default power measurement procedures or additional power measurements required for further SAR test reduction. The same procedures also apply to subsequent highest output power channel(s) selection.
  - The channel closest to mid-band frequency is selected for SAR measurement.
  - For channels with equal separation from mid-band frequency; for example, high and low channels or two mid-band channels, the higher frequency (number) channel is selected for SAR measurement.

#### **5.1.1.5.4 SAR Test Requirements for OFDM configurations**

When SAR measurement is required for 802.11 a/n/ac OFDM configurations, each standalone and frequency aggregated band is considered separately for SAR test reduction. When the same transmitter and antenna(s) are used for U-NII-1 and U-NII-2A bands, additional SAR test reduction applies. When band gap channels between U-NII-2C band and 5.8 GHz U-NII-3 or §15.247 band are supported, the highest maximum output power transmission mode configuration and maximum output power channel across the bands must be used to determine SAR test reduction, according to the initial test configuration and subsequent test configuration requirements. In applying the initial test configuration and subsequent test configuration procedures, the 802.11 transmission configuration with the highest specified maximum output power and the channel within a test configuration with the highest measured maximum output power should be clearly distinguished to apply the procedures.

## 5.1.2 DUT Antenna Locations



Note: Per KDB 616217, the diagonal length is > 200mm, the device is considered a “tablet” device and needed to test 0mm 1-g body SAR.

### 5.1.3 Stand-alone SAR test evaluation

1) Per FCC KDB 447498D01, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where:

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

2) At 100 MHz to 6 GHz and for test separation distances  $> 50$  mm, the SAR test exclusion threshold is determined according to the following:

a) [Power allowed at numeric threshold for 50 mm in step 1) + (test separation distance - 50 mm) · (f(MHz)/150)] mW, at 100 MHz to 1500 MHz

b) [Power allowed at numeric threshold for 50 mm in step 1) + (test separation distance - 50 mm) · 10] mW at  $> 1500$  MHz and  $\leq 6$  GHz

1) Standalone SAR exclusion calculation (Antenna to adjacent sides  $< 50$  mm)

Bnad	Exposure Condition	f (GHz)	Pmax (dBm)	Pmax (mw)	separation distance(mm)					Calculated Value					SAR Test ( Yes or No )				
					Back side	Left side	Right side	Top side	Bottom side	Back side	Left side	Right side	Top side	Bottom side	Back side	Left side	Right side	Top side	Bottom side
WiFi 2.4G	Body 0mm	2.462	17.00	50.12	5	70	36	5	205.03	15.728	>50mm	2.184	15.728	>50mm	Yes	>50mm	No	Yes	>50mm
WiFi 5.2G	Body 0mm	5.200	16.00	39.81	5	70	36	5	205.03	18.156	>50mm	2.522	18.156	>50mm	Yes	>50mm	No	Yes	>50mm
WiFi 5.3G	Body 0mm	5.300	16.00	39.81	5	70	36	5	205.03	18.330	>50mm	2.546	18.330	>50mm	Yes	>50mm	No	Yes	>50mm
WiFi 5.5G	Body 0mm	5.500	16.00	39.81	5	70	36	5	205.03	18.673	>50mm	2.593	18.673	>50mm	Yes	>50mm	No	Yes	>50mm
WiFi 5.8G	Body 0mm	5.800	16.00	39.81	5	70	36	5	205.03	19.175	>50mm	2.663	19.175	>50mm	Yes	>50mm	No	Yes	>50mm
BT	Body 0mm	2.480	9.00	7.94	5	70	36	5	205.03	2.502	>50mm	0.347	2.502	>50mm	No	>50mm	No	No	>50mm

2) Standalone SAR exclusion calculation (Antenna to adjacent sides  $> 50$  mm)

Bnad	Exposure Condition	f (GHz)	Pmax (dBm)	Pmax (mw)	separation distance(mm)					Calculated Value					SAR Test ( Yes or No )				
					Back side	Left side	Right side	Top side	Bottom side	Back side	Left side	Right side	Top side	Bottom side	Back side	Left side	Right side	Top side	Bottom side
WiFi 2.4G	Body 0mm	2.462	17.00	50.12	5	70	36	5	205.03	<50mm	295.83	<50mm	<50mm	1646.30	<50mm	No	<50mm	<50mm	No
WiFi 5.2G	Body 0mm	5.200	16.00	39.81	5	70	36	5	205.03	<50mm	265.78	<50mm	<50mm	1616.30	<50mm	No	<50mm	<50mm	No
WiFi 5.3G	Body 0mm	5.300	16.00	39.81	5	70	36	5	205.03	<50mm	264.55	<50mm	<50mm	1616.30	<50mm	No	<50mm	<50mm	No
WiFi 5.5G	Body 0mm	5.500	16.00	39.81	5	70	36	5	205.03	<50mm	262.29	<50mm	<50mm	1616.30	<50mm	No	<50mm	<50mm	No
WiFi 5.8G	Body 0mm	5.800	16.00	39.81	5	70	36	5	205.03	<50mm	200.00	<50mm	<50mm	1616.30	<50mm	No	<50mm	<50mm	No
BT	Body 0mm	2.480	9.00	7.94	5	70	36	5	205.03	<50mm	296.00	<50mm	<50mm	1646.30	<50mm	No	<50mm	<50mm	No

According to the table above, the standalone test configurations required for this device are as below:

Test configurations	Front side	Back side	Left side	Right side	Top side	Bottom side
WiFi 2.4G	No	Yes	No	No	Yes	No
WiFi 5G	No	Yes	No	No	Yes	No
BT	No	Yes	No	No	Yes	No

When standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

1)  $(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm}) \cdot [\sqrt{f(\text{GHz})}/x] \text{ W/kg}$  for test separation distances  $\leq 50$  mm, where  $x = 7.5$  for 1-g SAR and  $x = 18.75$  for 10-g SAR.

When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion

2) 0.4 W/kg for 1-g SAR and 1.0 W/kg for 10-g SAR, when the test separation distance is  $> 50$  mm.

Mode	Position	Pmax (dBm)	Pmax (mw)	test separation distance(mm)					f(GHz)	X	Estimated SAR(W/Kg)				
				Back side	Left side	Right side	Top side	Bottom side			Back side	Left side	Right side	Top side	Bottom side
WiFi 2.4G	Body 0mm	17.00	50.12	5	70	36	5	205.03	2.462	7.5	measure	0.400	0.292	measure	0.400
WiFi 5G	Body 0mm	16.00	39.81	5	70	36	5	205.03	5.850	7.5	measure	0.400	0.232	measure	0.400
BT	Body 0mm	9.00	7.94	5	70	36	5	205.03	2.480	7.5	0.334	0.400	0.334	0.334	0.400

Table 4: Estimated SAR calculation for WiFi and BT

Note:

1) \* - maximum possible output power declared by manufacturer



## 5.2 Measurement of RF conducted Power

### 5.2.1 Conducted Power Of WIFI and BT

2450MHz Wi-Fi-sensor on						
Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	Tune up	Average Power (dBm)	SAR Test
802.11b	1	2412	1	12.8	12.55	NO
	6	2437		12.8	12.52	NO
	11	2462		12.8	12.57	Yes
802.11g	1	2412	6	12.8	12.40	NO
	6	2437		12.8	12.51	NO
	11	2462		12.8	12.45	NO
802.11n HT20	1	2412	6.5	12.8	12.48	NO
	6	2437		12.8	12.49	NO
	11	2462		12.8	12.47	NO
2450MHz Wi-Fi-sensor off						
Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	Tune up	Average Power (dBm)	SAR Test
802.11b	1	2412	1	12.8	12.39	NO
	6	2437		17.0	16.45	Yes
	11	2462		12.8	12.51	NO
802.11g	1	2412	6	12.8	12.05	NO
	6	2437		17.0	15.97	NO
	11	2462		12.8	12.06	NO
802.11n HT20	1	2412	6.5	12.8	12.11	NO
	6	2437		17.0	15.95	NO
	11	2462		12.8	12.16	NO

5GHz Wi-Fi-sensor on							
Band(GHz)	Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	Tune up	Average Power (dBm)	SAR Test
5.2	802.11a	36	5180	6	9	8.27	NO
		40	5200		9	8.18	NO
		44	5220		9	8.11	NO
		48	5240		9	8.09	NO
	802.11n HT20	36	5180	6.5	9	8.26	NO
		40	5200		9	8.12	NO
		44	5220		9	8.05	NO
		48	5240		9	8.14	NO
	802.11n HT40	38	5190	13.5	9	8.76	NO
		46	5230		9	8.71	NO

5GHz Wi-Fi-sensor on							
Band(GHz)	Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	Tune up	Average Power (dBm)	SAR Test
5.3	802.11a	52	5260	6	9	8.12	NO
		56	5280		9	8.08	NO
		60	5300		9	8.02	NO
		64	5320		9	8.15	NO
	802.11n HT20	52	5260	6.5	9	8.17	NO
		56	5280		9	8.14	NO
		60	5300		9	8.04	NO
		64	5320		9	8.01	NO
	802.11n HT40	54	5270	13.5	9	8.75	NO
		62	5310		9	8.78	Yes

5GHz Wi-Fi-sensor on							
Band(GHz)	Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	Tune up	Average Power (dBm)	SAR Test
5.5	802.11a	100	5500	6	9	8.91	NO
		104	5520		9	8.71	NO
		108	5540		9	8.41	NO
		112	5560		9	8.24	NO
		116	5580		9	8.12	NO
		120	5600		9	8.21	NO
		124	5620		9	8.41	NO
		128	5640		9	8.43	NO
		132	5660		9	8.48	NO
		136	5680		9	8.55	NO
	140	5700	9	8.42	NO		
	802.11n HT20	100	5500	6.5	9	8.84	NO
		104	5520		9	8.68	NO
		108	5540		9	8.41	NO
		112	5560		9	8.21	NO
		116	5580		9	8.18	NO
		120	5600		9	8.23	NO
		124	5620		9	8.38	NO
		128	5640		9	8.51	NO
		132	5660		9	8.43	NO
		136	5680		9	8.49	NO
	140	5700	9	8.36	NO		
	802.11n HT40	102	5510	13.5	9	8.96	Yes
		110	5550		9	8.84	NO
		118	5590		9	8.78	NO
		126	5630		9	8.91	NO
		134	5670		9	8.88	NO

5GHz Wi-Fi-sensor on							
Band(GHz)	Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	Tune up	Average Power (dBm)	SAR Test
5.8	802.11a	149	5745	6	9	8.31	NO
		153	5765		9	8.34	NO
		157	5785		9	8.21	NO
		161	5805		9	8.26	NO
		165	5825		9	8.43	NO
	802.11n HT20	149	5745	6.5	9	8.24	NO
		153	5765		9	8.22	NO
		157	5785		9	8.25	NO
		161	5805		9	8.26	NO
		165	5825		9	8.42	NO
	802.11n HT40	151	5755	13.5	9	8.83	Yes
		159	5795		9	8.71	NO

5GHz Wi-Fi-sensor off							
Band(GHz)	Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	Tune up	Average Power (dBm)	SAR Test
5.2	802.11a	36	5180	6	13	12.36	NO
		40	5200		16	15.08	NO
		44	5220		16	15.05	NO
		48	5240		16	14.91	NO
	802.11n HT20	36	5180	6.5	13	12.34	NO
		40	5200		16	15.07	NO
		44	5220		16	15.04	NO
		48	5240		16	14.94	NO
	802.11n HT40	38	5190	13.5	9	8.26	NO
		46	5230		15.5	13.92	NO

5GHz Wi-Fi-sensor off							
Band(GHz)	Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	Tune up	Average Power (dBm)	SAR Test
5.3	802.11a	52	5260	6	16	14.99	NO
		56	5280		16	15.00	Yes
		60	5300		16	14.94	NO
		64	5320		14	13.21	NO
	802.11n HT20	52	5260	6.5	16	14.98	NO
		56	5280		16	15.04	NO
		60	5300		16	14.97	NO
		64	5320		14	13.23	NO
	802.11n HT40	54	5270	13.5	15.5	14.01	NO
		62	5310		9	8.18	NO

5GHz Wi-Fi-sensor off							
Band(GHz)	Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	Tune up	Average Power (dBm)	SAR Test
5.5	802.11a	100	5500	6	16	15.57	Yes
		104	5520		16	15.45	NO
		108	5540		16	15.30	NO
		112	5560		16	15.18	NO
		116	5580		16	14.94	NO
		120	5600		16	15.04	NO
		124	5620		16	15.15	NO
		128	5640		16	15.21	NO
		132	5660		16	15.21	NO
		136	5680		16	15.15	NO
	140	5700	15	14.23	NO		
	802.11n HT20	100	5500	6.5	16	15.59	NO
		104	5520		16	15.43	NO
		108	5540		16	15.29	NO
		112	5560		16	15.23	NO
		116	5580		16	14.98	NO
		120	5600		16	15.15	NO
		124	5620		16	15.18	NO
		128	5640		16	15.29	NO
		132	5660		16	15.21	NO
		136	5680		16	15.19	NO
	140	5700	15	14.26	NO		
	802.11n HT40	102	5510	13.5	15	13.83	NO
		110	5550		15.5	14.24	NO
		118	5590		15.5	13.95	NO
		126	5630		15.5	14.05	NO
		134	5670		15.5	13.97	NO

5GHz Wi-Fi-sensor off							
Band(GHz)	Mode	Channel	Frequency( MHz)	Data Rate (Mbps)	Tune up	Average Power (dBm)	SAR Test
5.8	802.11a	149	5745	6	16	15.01	NO
		153	5765		16	14.97	NO
		157	5785		16	14.90	NO
		161	5805		16	14.98	NO
		165	5825		16	15.18	Yes
	802.11n HT20	149	5745	6.5	16	14.97	NO
		153	5765		16	14.92	NO
		157	5785		16	14.91	NO
		161	5805		16	15.02	NO
		165	5825		16	15.22	NO
	802.11n HT40	151	5755	13.5	15.5	13.68	NO
		159	5795		15.5	13.81	NO

Table 5 : Conducted Power Of WIFI.

BT		Average Conducted Power(dBm)			
Band	Channel	GFSK	$\pi/4$ DQPSK	8DPSK	Tune up
BT	0	7.01	7.00	7.26	9
	39	7.64	7.57	7.90	
	78	8.09	8.09	<b>8.38</b>	

Table 6 : Conducted Power Of BT.

## 5.3 Measurement of SAR Data

### 5.3.1 SAR Result Of 2.4GHz WIFI

Test position	Test mode	Test Ch./Frequency	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg) 1-g	Power drift (dB)	Conducted power (dBm)	Tune up Limit (dBm)	Scaled factor	Scaled SAR (W/kg)	Liquid Temp.	SAR limit (W/kg)
Head Test data with Sensor on												
Left touch cheek	802.11b	11/2462	94.05%	1.063	0.441	0.13	12.57	12.8	1.054	<b>0.494</b>	22	1.6
Left tilted 15 degree	802.11b	11/2462	94.05%	1.063	0.306	0.07	12.57	12.8	1.054	0.343	22	1.6
Right touch cheek	802.11b	11/2462	94.05%	1.063	0.225	0.03	12.57	12.8	1.054	0.252	22	1.6
Right tilted 15 degree	802.11b	11/2462	94.05%	1.063	0.200	-0.07	12.57	12.8	1.054	0.224	22	1.6
Head Test data with Battery 2# Sensor on												
Left touch cheek	802.11b	11/2462	94.05%	1.063	0.363	0.06	12.57	12.8	1.054	0.407	22	1.6
Body Test data with Sensor on(Separate 0mm)												
Back side	802.11b	11/2462	94.05%	1.063	1.060	0.11	12.57	12.8	1.054	<b>1.188</b>	22	1.6
Back side	802.11b	1/2412	94.05%	1.063	1.030	0.02	12.55	12.8	1.059	1.160	22	1.6
Top side	802.11b	11/2462	94.05%	1.063	0.258	0.116	12.57	12.8	1.054	0.289	22	1.6
Back side-repeated	802.11b	11/2462	94.05%	1.063	1.050	0.05	12.57	12.8	1.054	1.177	22	1.6
Body Test data at worst case with battery 2# Sensor on(Separate 0mm)												
Back side	802.11b	11/2462	94.05%	1.063	1.040	0.01	12.55	12.8	1.059	1.171	22	1.6
Body Test data with Sensor off												
Back side-11mm	802.11b	6/2437	94.05%	1.063	0.232	-0.01	16.45	17	1.135	0.280	22	1.6
Top side-12mm	802.11b	6/2437	94.05%	1.063	0.0997	-0.09	16.45	17	1.135	0.120	22	1.6
Body Test data at worst case with battery 2# Sensor off												
Back side-11mm	802.11b	6/2437	94.05%	1.063	0.251	0.16	16.45	17	1.135	<b>0.303</b>	22	1.6

Table 7: SAR of 2.4GHz WIFI (Original report SZEM170600606901).

Test position	Test mode	Test Ch./Frequency	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg) 1-g	Power drift (dB)	Conducted power (dBm)	Tune up Limit (dBm)	Scaled factor	Scaled SAR (W/kg)	Liquid Temp.	SAR limit (W/kg)
Head Test Data at the worst case												
Left touch cheek	802.11b	11/2462	94.05%	1.063	0.409	-0.13	12.57	12.8	1.054	<b>0.459</b>	22	1.6
Body Test data at the worst case with Sensor on (Separate 0mm)												
Back side	802.11b	11/2462	94.05%	1.063	1.030	-0.17	12.57	12.8	1.054	<b>1.155</b>	22	1.6

Table 8: SAR of 2.4GHz WIFI (Variant).

Note:

- 1) The maximum Scaled SAR value is marked in bold. Graph Results refer to Appendix B
- 2) If the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is  $\leq 0.8$  W/kg then testing at the other channels is not required for such test configuration(s).
- 3) Per KDB248227D01, for Body SAR test of WiFi 2.4G, SAR is measured for 2.4 GHz 802.11b DSSS using the initial test position procedure. The highest reported SAR for DSSS is adjusted by the ratio of OFDM 802.11g/n to DSSS specified maximum output power and the adjusted SAR is  $< 1.2$  W/kg, so SAR for 802.11g/n is not required.

Test Position	Channel/ Frequency	Measured SAR (1g)	1 <sup>st</sup> Repeated	Ratio	2 <sup>nd</sup> Repeated	3 <sup>rd</sup> Repeated
	(MHz)		SAR (1g)		SAR (1g)	SAR (1g)
Back side	11/2462	1.06	1.05	1.01	N/A	N/A
1) When the original highest measured SAR is $\geq 0.80$ W/kg, the measurement was repeated once.						
2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was $> 1.20$ or when the original or repeated measurement was $\geq 1.45$ W/kg (~ 10% from the 1-g SAR limit).						
3) A third repeated measurement was performed only if the original, first or second repeated measurement was $\geq 1.5$ W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is $> 1.20$ .						
4) Repeated measurements are not required when the original highest measured SAR is $< 0.80$ W/kg						

### 5.3.2 SAR Result Of 5GHz WIFI(U-NII-2A)

Test position	Test mode	Test Ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg)1-g	Power drift (dB)	Conducted power (dBm)	Tune up Limit (dBm)	Scaled factor	Scaled SAR (W/kg)	Liquid Temp.	SAR limit (W/kg)
Head Test data with Sensor on												
Left touch cheek	802.11n HT40	62/5310	94.05%	1.063	0.237	0.04	8.78	9	1.052	0.265	22.2	1.6
Left tilted 15 degree	802.11n HT40	62/5310	94.05%	1.063	0.254	-0.12	8.78	9	1.052	0.284	22.2	1.6
Right touch cheek	802.11n HT40	62/5310	94.05%	1.063	0.200	0.08	8.78	9	1.052	0.224	22.2	1.6
Right tilted 15 degree	802.11n HT40	62/5310	94.05%	1.063	0.219	-0.07	8.78	9	1.052	0.245	22.2	1.6
Head Test data with Battery 2# Sensor on												
Left tilted 15 degree	802.11n HT40	62/5310	94.05%	1.063	0.349	-0.02	8.78	9	1.052	<b>0.390</b>	22.2	1.6
Body Test data with Sensor on(Separate 0mm)												
Back side	802.11n HT40	62/5310	94.05%	1.063	0.383	0.12	8.78	9	1.052	0.428	22.2	1.6
Top side	802.11n HT40	62/5310	94.05%	1.063	0.401	-0.11	8.78	9	1.052	0.449	22.2	1.6
Body Test data at worst case with battery2# Sensor on(Separate 0mm)												
Top side	802.11n HT40	62/5310	94.05%	1.063	0.471	0.07	8.78	9	1.052	<b>0.527</b>	22.2	1.6
Body Test data with Sensor off												
Back side-11mm	802.11a	56/5280	94.05%	1.063	0.173	0.19	15	16	1.259	0.232	22.2	1.6
Top side-12mm	802.11a	56/5280	94.05%	1.063	0.371	-0.04	15	16	1.259	0.497	22.2	1.6
Body Test data at worst case with battery2# Sensor off												
Top side-12mm	802.11a	56/5280	94.05%	1.063	0.435	0.01	15	16	1.259	<b>0.582</b>	22.2	1.6

Table 9: SAR of 5GHz WIFI(U-NII-2A) (Original report SZEM170600606901).

Note:

- 1) The maximum Scaled SAR value is marked in bold. Graph Results refer to Appendix B
- 2) If the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is  $\leq 0.8$  W/kg then testing at the other channels is not required for such test configuration(s).
- 3) When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. As the highest *reported* SAR for a test configuration is  $\leq 1.2$  W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition);



### 5.3.3 SAR Result Of 5GHz WIFI(U-NII-2C)

Test position	Test mode	Test Ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg)1-g	Power drift (dB)	Conducted power (dBm)	Tune up Limit (dBm)	Scaled factor	Scaled SAR (W/kg)	Liquid Temp.	SAR limit (W/kg)
Head Test data with Sensor on												
Left touch cheek	802.11n HT40	102/5510	94.05%	1.063	0.303	0.08	8.96	9	1.009	0.325	22.2	1.6
Left tilted 15 degree	802.11n HT40	102/5510	94.05%	1.063	0.316	0.01	8.96	9	1.009	0.339	22.2	1.6
Right touch cheek	802.11n HT40	102/5510	94.05%	1.063	0.241	-0.02	8.96	9	1.009	0.259	22.2	1.6
Right tilted 15 degree	802.11n HT40	102/5510	94.05%	1.063	0.300	0.04	8.96	9	1.009	0.322	22.2	1.6
Head Test data with Battery 2# Sensor on												
Left tilted 15 degree	802.11n HT40	102/5510	94.05%	1.063	0.471	-0.12	8.96	9	1.009	<b>0.505</b>	22.2	1.6
Body Test data with Sensor on(Separate 0mm)												
Back side	802.11n HT40	102/5510	94.05%	1.063	0.314	-0.04	8.96	9	1.009	0.337	22.2	1.6
Top side	802.11n HT40	102/5510	94.05%	1.063	0.323	0.01	8.96	9	1.009	0.347	22.2	1.6
Body Test data with battery2# Sensor on(Separate 0mm)												
Top side	802.11n HT40	102/5510	94.05%	1.063	0.419	-0.19	8.96	9	1.009	<b>0.450</b>	22.2	1.6
Body Test data with Sensor off												
Back side-11mm	802.11a	100/5500	94.05%	1.063	0.129	-0.07	15.57	16	1.104	0.151	22.2	1.6
Top side-12mm	802.11a	100/5500	94.05%	1.063	0.316	-0.08	15.57	16	1.104	0.371	22.2	1.6
Body Test data with battery2# Sensor off												
Top side-12mm	802.11a	100/5500	94.05%	1.063	0.419	-0.01	15.57	16	1.104	<b>0.492</b>	22.2	1.6

Table 10: SAR of 5GHz WIFI(U-NII-2C) (Original report SZEM170600606901).

Note:

- 1) The maximum Scaled SAR value is marked in bold. Graph Results refer to Appendix B
- 2) If the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is  $\leq 0.8$  W/kg then testing at the other channels is not required for such test configuration(s).

### 5.3.4 SAR Result Of 5GHz WIFI(U-NII-3)

Test position	Test mode	Test Ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg )1-g	Power drift (dB)	Conducted power (dBm)	Tune up Limit (dBm)	Scaled factor	Scaled SAR (W/kg)	Liquid Temp.	SAR limit (W/kg)
Head Test data with Sensor on												
Left touch cheek	802.11n HT40	151/5755	94.05%	1.063	0.331	0.08	8.83	9	1.040	0.366	22.2	1.6
Left tilted 15 degree	802.11n HT40	151/5755	94.05%	1.063	0.336	0.08	8.83	9	1.040	0.372	22.2	1.6
Right touch cheek	802.11n HT40	151/5755	94.05%	1.063	0.277	0.09	8.83	9	1.040	0.306	22.2	1.6
Right tilted 15 degree	802.11n HT40	151/5755	94.05%	1.063	0.328	0.07	8.83	9	1.040	0.363	22.2	1.6
Head Test data with Battery 2# Sensor on												
Left tilted 15 degree	802.11n HT40	151/5755	94.05%	1.063	0.497	0.07	8.83	9	1.040	<b>0.550</b>	22.2	1.6
Body Test data with Sensor on(Separate 0mm)												
Back side	802.11n HT40	151/5755	94.05%	1.063	0.349	0.01	8.83	9	1.040	0.386	22.2	1.6
Top side	802.11n HT40	151/5755	94.05%	1.063	0.383	0.04	8.83	9	1.040	0.423	22.2	1.6
Body Test data with battery2# Sensor on(Separate 0mm)												
Top side	802.11n HT40	151/5755	94.05%	1.063	0.527	-0.03	8.83	9	1.040	<b>0.583</b>	22.2	1.6
Body Test data with Sensor off												
Back side-11mm	802.11a	165/5825	94.05%	1.063	0.178	-0.08	15.18	16	1.208	0.229	22.2	1.6
Top side-12mm	802.11a	165/5825	94.05%	1.063	0.452	0.03	15.18	16	1.208	0.580	22.2	1.6
Body Test data with battery2# Sensor off												
Top side-12mm	802.11a	165/5825	94.05%	1.063	0.591	-0.07	15.18	16	1.208	<b>0.759</b>	22.2	1.6

Table 11: SAR of 5GHz WIFI(U-NII-3) (Original report SZEM170600606901).

Test position	Test mode	Test Ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg) 1-g	Power drift (dB)	Conducted power (dBm)	Tune up Limit (dBm)	Scaled factor	Scaled SAR (W/kg)	Liquid Temp.	SAR limit (W/kg)
Head Test Data at the worst case												
Left tilted 15 degree	802.11n HT40	151/5755	94.05%	1.063	0.653	-0.07	8.83	9	1.040	<b>0.722</b>	22.2	1.6
Body Test data at the worst case with Sensor off												
Top side-12mm	802.11a	165/5825	94.05%	1.063	0.619	0.14	15.18	16	1.208	<b>0.795</b>	22.2	1.6

Table 12: SAR of 5GHz WIFI(U-NII-3) (Variant).

Note:

- 1) The maximum Scaled SAR value is marked in bold. Graph Results refer to Appendix B
- 2) If the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is  $\leq 0.8$  W/kg then testing at the other channels is not required for such test configuration(s).

## 5.4 Multiple Transmitter Evaluation

### 5.4.1 Simultaneous SAR SAR test evaluation

#### 1) Simultaneous Transmission

NO.	Simultaneous Transmission Configuration	Body
1	2.4GHz/5GHz WiFi +BT (They share the same antenna and cannot transmit at the same time by design.)	NO

## 6 Equipment list

Test Platform		SPEAG DASY5 Professional				
Location		SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch				
Description		SAR Test System (Frequency range 300MHz-6GHz)				
Software Reference		DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)				
<b>Hardware Reference</b>						
Equipment		Manufacturer	Model	Serial Number	Calibration Date	Due date of calibration
<input checked="" type="checkbox"/>	Robot	Staubli	RX90L	F03/5V32A1/A01	NCR	NCR
<input checked="" type="checkbox"/>	Twin Phantom	SPEAG	SAM 1	TP-1283	NCR	NCR
<input checked="" type="checkbox"/>	Twin Phantom	SPEAG	SAM 1	1912	NCR	NCR
<input checked="" type="checkbox"/>	Twin Phantom	SPEAG	SAM 2	1913	NCR	NCR
<input checked="" type="checkbox"/>	DAE	SPEAG	DAE4	1374	2017-08-31	2018-08-30
<input checked="" type="checkbox"/>	E-Field Probe	SPEAG	EX3DV4	3962	2018-01-11	2019-01-10
<input checked="" type="checkbox"/>	Validation Kits	SPEAG	D2450V2	733	2016-12-07	2019-12-06
<input checked="" type="checkbox"/>	Validation Kits	SPEAG	D5GHzV2	1165	2016-12-13	2019-12-12
<input checked="" type="checkbox"/>	Agilent Network Analyzer	Agilent	E5071C	MY46523590	2018-03-13	2019-03-12
<input checked="" type="checkbox"/>	Dielectric Probe Kit	Agilent	85070E	US01440210	NCR	NCR
<input checked="" type="checkbox"/>	RF Bi-Directional Coupler	Agilent	86205-60001	MY31400031	NCR	NCR
<input checked="" type="checkbox"/>	Signal Generator	Agilent	N5171B	MY53050736	2018-03-13	2019-03-12
<input checked="" type="checkbox"/>	Preamplifier	Mini-Circuits	ZHL-42W	15542	NCR	NCR
<input checked="" type="checkbox"/>	Power Meter	Agilent	E4416A	GB41292095	2018-03-13	2019-03-12
<input checked="" type="checkbox"/>	Power Sensor	Agilent	8481H	MY41091234	2018-03-13	2019-03-12
<input checked="" type="checkbox"/>	Power Sensor	R&S	NRP-Z92	100025	2018-03-13	2019-03-12
<input checked="" type="checkbox"/>	Attenuator	SHX	TS2-3dB	30704	NCR	NCR
<input checked="" type="checkbox"/>	Coaxial low pass filter	Mini-Circuits	VLF-2500(+)	NA	NCR	NCR
<input checked="" type="checkbox"/>	Coaxial low pass filter	Microlab Fxr	LA-F13	NA	NCR	NCR
<input checked="" type="checkbox"/>	50 Ω coaxial load	Mini-Circuits	KARN-50+	00850	NCR	NCR
<input checked="" type="checkbox"/>	DC POWER SUPPLY	SAKO	SK1730SL5A	NA	NCR	NCR
<input checked="" type="checkbox"/>	Speed reading thermometer	MingGao	T809	NA	2018-03-13	2019-03-12
<input checked="" type="checkbox"/>	Humidity and Temperature Indicator	KIMTOKA	KIMTOKA	NA	2018-03-13	2019-03-12

## 7 Measurement Uncertainty

Measurements and results are all in compliance with the standards listed in this report. All measurements and results are recorded and maintained at the laboratory performing the tests and measurement uncertainties are taken into account when comparing measurements to pass/ fail criteria. The Expanded uncertainty (95% CONFIDENCE INTERVAL) is 21.36%.

A	b1	c	d	e = f(d,k)	g	i = C*g/e	k
Uncertainty Component	Section in P1528	Tol (%)	Prob . Dist.	Div.	Ci (1g)	1g ui (%)	Vi (Veff)
Probe calibration	E.2.1	6.3	N	1	1	6.30	∞
Axial isotropy	E.2.2	0.5	R	$\sqrt{3}$	$(1 - C_p)^{1/2}$	0.20	∞
hemispherical isotropy	E.2.2	2.6	R	$\sqrt{3}$	$\sqrt{C_p}$	1.06	∞
Boundary effect	E.2.3	1.0	R	$\sqrt{3}$	1	0.58	∞
Linearity	E.2.4	0.6	R	$\sqrt{3}$	1	0.35	∞
System detection limit	E.2.5	0.25	R	$\sqrt{3}$	1	0.14	∞
Readout electronics	E.2.6	0.3	N	1	1	0.30	∞
Response time	E.2.7	0	R	$\sqrt{3}$	1	0.00	∞
Integration time	E.2.8	2.6	R	$\sqrt{3}$	1	1.50	∞
RF ambient Condition –Noise	E.6.1	3	R	$\sqrt{3}$	1	1.73	∞
RF ambient Condition- reflections	E.6.1	3	R	$\sqrt{3}$	1	1.73	∞
Probe positioning- mechanical tolerance	E.6.2	1.5	R	$\sqrt{3}$	1	0.87	∞
Probe positioning- with respect to phantom	E.6.3	2.9	R	$\sqrt{3}$	1	1.67	∞
Max. SAR evaluation	E.5.2	1	R	$\sqrt{3}$	1	0.58	∞
Test sample positioning	E.4.2	3.7	N	1	1	3.70	9
Device holder uncertainty	E.4.1	3.6	N	1	1	3.60	∞
Output power variation –SAR drift measurement	6.6.2	5	R	$\sqrt{3}$	1	2.89	∞
Phantom uncertainty (shape and thickness tolerances)	E.3.1	4	R	$\sqrt{3}$	1	2.31	∞
Liquid conductivity - deviation from target values	E.3.2	5	R	$\sqrt{3}$	0.64	1.85	∞
Liquid conductivity - measurement uncertainty	E.3.2	5.78	N	1	0.64	3.68	5

Liquid permittivity - deviation from target values	E.3.3	5	R	$\sqrt{3}$	0.6	1.73	$\infty$
Liquid permittivity - measurement uncertainty	E.3.3	0.62	N	1	0.6	0.372	5
Combined standard uncertainty				RSS		10.68	430
Expanded uncertainty (95% CONFIDENCE INTERVAL)				K=2		<b>21.36</b>	

Table 13 : Measurement Uncertainty

## 8 Calibration certificate

Please see the Appendix C

## 9 Photographs

Please see the Appendix D

## **Appendix A: Detailed System Validation Results**

## **Appendix B: Detailed Test Results**

## **Appendix C: Calibration certificate**

## **Appendix D: Photographs**

**---END---**

---