



**FCC PART 15C
TEST REPORT
No. B17N00263-WLAN**

for

HUAWEI Technologies Co., Ltd.

HUAWEI MediaPad T3

Model Name: KOB-W09

With

Hardware Version: REACHW-V1.0

Software Version: KOB-W09C331B002-log

FCC ID: QISKOB-W09

Issued Date: 2017-06-16

Test Laboratory:

FCC 2.948 Listed: No.342690

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

Test Laboratory:

CTTL, Telecommunication Technology Labs, Academy of Telecommunication Research, MIIT.

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel: +86(0)10-62304633-2512, Fax: +86(0)10-62304633-2504

Email: ctl_terminals@catr.cn, website: www.chinattl.com



REPORT HISTORY

Report Number	Revision	Description	Issue Date
B17N00263-WLAN	Rev.0	1st edition	2017-04-10
B17N00263-WLAN	Rev.1	2nd edition	2017-06-16



CONTENTS

1. TEST LABORATORY	6
1.1. TESTING LOCATION	6
1.2. TESTING ENVIRONMENT	6
1.3. PROJECT DATA	6
1.4. SIGNATURE	6
2. CLIENT INFORMATION	7
2.1. APPLICANT INFORMATION	7
2.2. MANUFACTURER INFORMATION	7
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	8
3.1. ABOUT EUT	8
3.2. INTERNAL IDENTIFICATION OF EUT	8
3.3. INTERNAL IDENTIFICATION OF AE	8
4. REFERENCE DOCUMENTS	9
4.1. DOCUMENTS SUPPLIED BY APPLICANT	9
4.2. REFERENCE DOCUMENTS FOR TESTING	9
5. TEST RESULTS	10
5.1. SUMMARY OF TEST RESULTS	10
5.2. STATEMENTS	10
5.3. TERMS USED IN THE RESULT TABLE	10
5.4. LABORATORY ENVIRONMENT	11
6. TEST FACILITIES UTILIZED	12
ANNEX A: MEASUREMENT RESULTS FOR RECEIVER	13
A.0 ANTENNA REQUIREMENT	13
A.1 MAXIMUM AVERAGE OUTPUT POWER	14
A.2 PEAK POWER SPECTRAL DENSITY	15
A.3 OCCUPIED 6dB BANDWIDTH	16
A.4 BAND EDGES COMPLIANCE	17
A.5 TRANSMITTER SPURIOUS EMISSION	18
A.5.1 TRANSMITTER SPURIOUS EMISSION - CONDUCTED	18
A.5.2 TRANSMITTER SPURIOUS EMISSION - RADIATED	19
A.6 AC POWERLINE CONDUCTED EMISSION	26
ANNEX B: TEST LAYOUTS	32
FIG.1 POWER SPECTRAL DENSITY (802.11B, CH 1)	32
FIG.2 POWER SPECTRAL DENSITY (802.11B, CH 6)	32
FIG.3 POWER SPECTRAL DENSITY (802.11B, CH 11)	33
FIG.4 POWER SPECTRAL DENSITY (802.11G, CH 1)	33
FIG.5 POWER SPECTRAL DENSITY (802.11G, CH 6)	34



FIG.6	POWER SPECTRAL DENSITY (802.11G, CH 11).....	34
FIG.7	POWER SPECTRAL DENSITY (802.11N-20MHZ, CH 1).....	35
FIG.8	POWER SPECTRAL DENSITY (802.11N-20MHZ, CH 6).....	35
FIG.9	POWER SPECTRAL DENSITY (802.11N-20MHZ, CH 11).....	36
FIG.10	OCCUPIED 6DB BANDWIDTH (802.11B, CH 1).....	36
FIG.11	OCCUPIED 6DB BANDWIDTH (802.11B, CH 6).....	37
FIG.12	OCCUPIED 6DB BANDWIDTH (802.11B, CH 11).....	37
FIG.13	OCCUPIED 6DB BANDWIDTH (802.11G, CH 1).....	38
FIG.14	OCCUPIED 6DB BANDWIDTH (802.11G, CH 6).....	38
FIG.15	OCCUPIED 6DB BANDWIDTH (802.11G, CH 11).....	39
FIG.16	OCCUPIED 6DB BANDWIDTH (802.11 N-20MHZ, CH 1).....	39
FIG.17	OCCUPIED 6DB BANDWIDTH (802.11 N-20MHZ, CH 6).....	40
FIG.18	OCCUPIED 6DB BANDWIDTH (802.11 N-20MHZ, CH 11).....	40
FIG.19	BAND EDGES (802.11B, CH 1).....	41
FIG.20	BAND EDGES (802.11B, CH 11).....	41
FIG.21	BAND EDGES (802.11G, CH 1).....	42
FIG.22	BAND EDGES (802.11G, CH 11).....	42
FIG.23	BAND EDGES (802.11 N-20MHZ, CH 1).....	43
FIG.24	BAND EDGES (802.11 N-20MHZ, CH 11).....	43
FIG.25	CONDUCTED SPURIOUS EMISSION (802.11B, CH1, CENTER FREQUENCY).....	44
FIG.26	CONDUCTED SPURIOUS EMISSION (802.11B, CH1, 30 MHZ-1 GHZ).....	44
FIG.27	CONDUCTED SPURIOUS EMISSION (802.11B, CH1, 1 GHZ-10 GHZ).....	45
FIG.28	CONDUCTED SPURIOUS EMISSION (802.11B, CH6, CENTER FREQUENCY).....	45
FIG.29	CONDUCTED SPURIOUS EMISSION (802.11B, CH6, 30 MHZ-1 GHZ).....	46
FIG.30	CONDUCTED SPURIOUS EMISSION (802.11B, CH6, 1 GHZ-10 GHZ).....	46
FIG.31	CONDUCTED SPURIOUS EMISSION (802.11B, CH11, CENTER FREQUENCY).....	47
FIG.32	CONDUCTED SPURIOUS EMISSION (802.11B, CH11, 30 MHZ-1 GHZ).....	47
FIG.33	CONDUCTED SPURIOUS EMISSION (802.11B, CH11, 1 GHZ-10 GHZ).....	48
FIG.34	CONDUCTED SPURIOUS EMISSION (802.11G, CH1, CENTER FREQUENCY).....	48
FIG.35	CONDUCTED SPURIOUS EMISSION (802.11G, CH1, 30 MHZ-1 GHZ).....	49
FIG.36	CONDUCTED SPURIOUS EMISSION (802.11G, CH1, 1 GHZ-10 GHZ).....	49
FIG.37	CONDUCTED SPURIOUS EMISSION (802.11G, CH6, CENTER FREQUENCY).....	50
FIG.38	CONDUCTED SPURIOUS EMISSION (802.11G, CH6, 30 MHZ-1 GHZ).....	50
FIG.39	CONDUCTED SPURIOUS EMISSION (802.11G, CH6, 1 GHZ-10 GHZ).....	51
FIG.40	CONDUCTED SPURIOUS EMISSION (802.11G, CH11, CENTER FREQUENCY).....	51
FIG.41	CONDUCTED SPURIOUS EMISSION (802.11G, CH11, 30 MHZ-1 GHZ).....	52
FIG.42	CONDUCTED SPURIOUS EMISSION (802.11G, CH11, 1 GHZ-10 GHZ).....	52
FIG.43	CONDUCTED SPURIOUS EMISSION (802.11N-20MHZ, CH1, CENTER FREQUENCY).....	53
FIG.44	CONDUCTED SPURIOUS EMISSION (802.11N-20MHZ, CH1, 30 MHZ-1 GHZ).....	53
FIG.45	CONDUCTED SPURIOUS EMISSION (802.11N-20MHZ, CH1, 1 GHZ-10 GHZ).....	54
FIG.46	CONDUCTED SPURIOUS EMISSION (802.11N-20MHZ, CH6, CENTER FREQUENCY).....	54
FIG.47	CONDUCTED SPURIOUS EMISSION (802.11N-20MHZ, CH6, 30 MHZ-1 GHZ).....	55
FIG.48	CONDUCTED SPURIOUS EMISSION (802.11N-20MHZ, CH6, 1 GHZ-10 GHZ).....	55
FIG.49	CONDUCTED SPURIOUS EMISSION (802.11N-20MHZ, CH11, CENTER FREQUENCY).....	56



FIG.50 CONDUCTED SPURIOUS EMISSION (802.11N-20MHz, Ch11, 30 MHz-1 GHz) 56
FIG.51 CONDUCTED SPURIOUS EMISSION (802.11N-20MHz, Ch11, 1 GHz-10 GHz)..... 57
FIG.52 CONDUCTED SPURIOUS EMISSION (ALL CHANNELS, 10 GHz-26 GHz) 57
FIG.53 RADIATED SPURIOUS EMISSION (802.11B, Ch1, 1 GHz-18GHz) 58
FIG.54 RADIATED SPURIOUS EMISSION (802.11B, Ch6, 9kHz-30MHz)..... 58
FIG.55 RADIATED SPURIOUS EMISSION (802.11B, Ch6, 30MHz-1 GHz) 59
FIG.56 RADIATED SPURIOUS EMISSION (802.11B, Ch6, 1 GHz-18GHz) 59
FIG.57 RADIATED SPURIOUS EMISSION (802.11B, Ch6, 18 GHz-26.5GHz) 60
FIG.58 RADIATED SPURIOUS EMISSION (802.11B, Ch11, 1 GHz-18GHz) 60
FIG.59 RADIATED EMISSION POWER (802.11B, Ch1, 2380GHz~2450GHz) 61
FIG.60 RADIATED EMISSION POWER (802.11B, Ch11, 2450GHz~2500GHz)..... 61
FIG.61 RADIATED SPURIOUS EMISSION (802.11G, Ch1, 1 GHz-18 GHz) 62
FIG.62 RADIATED SPURIOUS EMISSION (802.11G, Ch6, 9kHz-30MHz)..... 62
FIG.63 RADIATED SPURIOUS EMISSION (802.11G, Ch6, 30MHz-1 GHz)..... 63
FIG.64 RADIATED SPURIOUS EMISSION (802.11G, Ch6, 1 GHz-18 GHz) 63
FIG.65 RADIATED SPURIOUS EMISSION (802.11G, Ch6, 18 GHz-26.5 GHz) 64
FIG.66 RADIATED SPURIOUS EMISSION (802.11G, Ch11, 1 GHz-18 GHz)..... 64
FIG.67 RADIATED EMISSION POWER (802.11G, Ch1, 2380GHz~2450GHz)..... 65
FIG.68 RADIATED EMISSION POWER (802.11G, Ch11, 2450GHz~2500GHz)..... 65
FIG.69 RADIATED SPURIOUS EMISSION (802.11N-20MHz, Ch1, 1 GHz-18 GHz) 66
FIG.70 RADIATED SPURIOUS EMISSION (802.11N-20MHz, Ch6, 9kHz-30MHz)..... 66
FIG.71 RADIATED SPURIOUS EMISSION (802.11N-20MHz, Ch6, 30MHz-1 GHz)..... 67
FIG.72 RADIATED SPURIOUS EMISSION (802.11N-20MHz, Ch6, 1 GHz-18 GHz) 67
FIG.73 RADIATED SPURIOUS EMISSION (802.11N-20MHz, Ch6, 18 GHz-26.5 GHz) 68
FIG.74 RADIATED SPURIOUS EMISSION (802.11N-20MHz, Ch11, 1 GHz-18 GHz)..... 68
FIG.75 RADIATED EMISSION POWER (802.11N-20MHz, Ch1, 2380GHz~2450GHz)..... 69
FIG.76 RADIATED EMISSION POWER (802.11N-20MHz, Ch11, 2450GHz~2500GHz)..... 69
FIG.77 AC POWERLINE CONDUCTED EMISSION (TRAFFIC, AE1) 70
FIG.78 AC POWER LINE CONDUCTED EMISSION (IDLE, AE1)..... 71
FIG.79 AC POWERLINE CONDUCTED EMISSION (TRAFFIC, AE2) 72
FIG.80 AC POWER LINE CONDUCTED EMISSION (IDLE, AE2)..... 73
FIG.81 AC POWERLINE CONDUCTED EMISSION (TRAFFIC, AE3) 74
FIG.82 AC POWER LINE CONDUCTED EMISSION (IDLE, AE3)..... 75
FIG.83 AC POWERLINE CONDUCTED EMISSION (TRAFFIC, AE1) 76
FIG.84 AC POWER LINE CONDUCTED EMISSION (IDLE, AE1)..... 77
FIG.85 AC POWERLINE CONDUCTED EMISSION (TRAFFIC, AE2) 78
FIG.86 AC POWER LINE CONDUCTED EMISSION (IDLE, AE2)..... 79
FIG.87 AC POWERLINE CONDUCTED EMISSION (TRAFFIC, AE3) 80
FIG.88 AC POWER LINE CONDUCTED EMISSION (IDLE, AE3)..... 81

ANNEX C: PERSONS INVOLVED IN THIS TESTING 82

1. Test Laboratory

1.1. Testing Location

Location: CTTL(South Branch)

Address: TCL International E city, No. 1001, Zhongshanyuan Road, Nanshan
District, Shenzhen, Guangdong, China 518000

1.2. Testing Environment

Normal Temperature: 15-35°C


Relative Humidity: 20-75%

1.3. Project data

Testing Start Date: 2017-03-14

Testing End Date: 2017-06-13

1.4. Signature



Lin Kanfeng

(Prepared this test report)



Tang Weisheng

(Reviewed this test report)



Zhang Bojun

(Approved this test report)



2. Client Information

2.1. Applicant Information

Company Name: Huawei Technologies Co., Ltd
Address: Administration Building, Huawei Base, Bantian, Longgang District,
Shenzhen
City: Shenzhen
Postal Code: 518129
Country: China
Telephone: 15602311354
Fax: /

2.2. Manufacturer Information

Company Name: Huawei Technologies Co., Ltd
Address: Administration Building, Huawei Base, Bantian, Longgang District,
Shenzhen
City: Shenzhen
Postal Code: 518129
Country: China
Telephone: 15602311354
Fax: /



3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	HUAWEI MediaPad T3
Model Name	KOB-W09
Market Name	HUAWEI MediaPad T3
RF Protocol	IEEE 802.11b/g/n20
Operating Frequency	2412MHz~2462MHz
FCC ID	QISKOB-W09

3.2. Internal Identification of EUT

EUT ID*	IMEI	HW Version	SW Version	Receive Date
EUT1	/	REACHW-V1.0	KOB-W09C331B002-log	2017-03-14

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE

AE ID*	Description	SN
AE1	Charger	/
AE2	Charger	/
AE3	Charger	/

AE1

Model	HW-050100U01
Manufacturer	SHENZHEN HUNTKEY ELECTRONIC CO.,LTD.

AE2

Model	HW-050100U01
Manufacturer	HUIZHOU BYD ELECTRONIC CO., LTD.

AE3

Model	HW-050100U01
Manufacturer	DONGGUAN PHITEK ELECTRONICS CO.,LTD.

*AE ID: is used to identify the test sample in the lab internally.



4. Reference Documents

4.1. Documents supplied by applicant

EUT feature information is supplied by the applicant or manufacturer, which is the basis of testing.

4.2. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part15	FCC CFR 47, Part 15, Subpart C: 15.205 Restricted bands of operation; 15.209 Radiated emission limits, general requirements; 15.247 Operation within the bands 902–928MHz, 2400–2483.5 MHz, and 5725–5850 MHz	Nov,2015
ANSI C63.10	American National Standard for Testing Wireless Devices	Jun,2013

5. Test Results

5.1. Summary of Test Results

No	Test cases	Sub-clause of Part15C	Verdict
0.	Antenna Requirement	15.203	P
1.	Maximum Peak Output Power	15.247 (b)	P
2.	Peak Power Spectral Density	15.247 (e)	P
3.	Occupied 6dB Bandwidth	15.247 (a)	P
4.	Band Edges Compliance	15.247 (d)	P
5.	Transmitter Spurious Emission - Conducted	15.247 (d)	P
6.	Transmitter Spurious Emission - Radiated	15.247, 15.205, 15.209	P
7.	AC Powerline Conducted Emission	15.107, 15.207	P

See **ANNEX A** and **ANNEX B** for details.

5.2. Statements

CTTL has evaluated the test cases requested by the applicant/manufacturer as listed in section 5.1 of this report, for the EUT specified in section 3, according to the standards or reference documents listed in section 4.2.

5.3. Terms used in the result table

Terms used in Verdict column

P	Pass
NA	Not Available
F	Fail

Abbreviations

AC	Alternating Current
AFH	Adaptive Frequency Hopping
BW	Band Width
E.I.R.P.	equivalent isotropic radiated power
ISM	Industrial, Scientific and Medical
R&TTE	Radio and Telecommunications Terminal Equipment
RF	Radio Frequency
Tx	Transmitter

5.4. Laboratory Environment

Semi-anechoic chamber did not exceed following limits along the EMC testing

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	0.014MHz - 1MHz, >60dB; 1MHz - 1000MHz, >90dB.
Electrical insulation	> 2 MΩ
Ground system resistance	< 4Ω
Normalised site attenuation (NSA)	< ±4dB, 3m/10m distance, from 30 to 1000 MHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 3000 MHz

Shielded room did not exceed following limits along the EMC testing

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	0.014MHz - 1MHz, >60dB; 1MHz - 1000MHz, >90dB.
Electrical insulation	> 2 MΩ
Ground system resistance	< 4 Ω

Fully-anechoic chamber did not exceed following limits along the EMC testing

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	0.014MHz - 1MHz, >60dB; 1MHz - 1000MHz, >90dB.
Electrical insulation	> 2 MΩ
Ground system resistance	< 4Ω
Voltage Standing Wave Ratio (VSWR)	≤6dB, from 1 to 18 GHz, 3m distance

6. Test Facilities Utilized

Conducted test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Due date	Calibration Period
1	Vector Signal Analyzer	FSV40	100903	Rohde & Schwarz	2018-01-18	1 year
2	Data Acquisition Unit	U2531A	TW55443 507	Agilent	/	/
3	Power Sensor	U2021X A	MY55430 013	Agilent	2018-01-18	1 year

Radiated emission test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Due date	Calibration Period
1	Test Receiver	ESCI	100701	R&S	2017-08-09	1 year
2	Loop Antenna	HLA6120	35779	TESEQ	2019-05-02	3 years
3	BiLog Antenna	VULB9163	9163 329	Schwarzbeck	2020-02-17	3 years
4	Horn Antenna	3117	00066585	ETS-Lindgren	2019-03-05	3 years
5	Universal Radio Communication Tester	CMW270	100540	Rohde & Schwarz	2018-04-12	1 year
6	Spectrum Analyzer	FSP 40	100378	R&S	2017-12-15	1 year
7	Chamber	FACT5-2.0	4166	ETS-Lindgren	2018-05-13	3 years

Anechoic chamber

Fully anechoic chamber by ETS-Lindgren



ANNEX A: MEASUREMENT RESULTS FOR RECEIVER

A.0 Antenna requirement

Measurement Limit:

Standard	Requirement
FCC CRF Part 15.203	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

Conclusion: The Directional gains of antenna used for transmitting is 0dBi.

The RF transmitter uses an integrate antenna without connector.



A.1 Maximum Average Output Power

Measurement Limit:

Standard	Limit (dBm)
FCC CRF Part 15.247(b)(1)	< 30

Measurement Results:

802.11b/g mode

Mode	Data Rate (Mbps)	Test Result (dBm)		
		2412MHz (Ch1)	2437MHz (Ch6)	2462 MHz (Ch11)
802.11b	1	12.40	16.30	12.37
	2	12.45	16.37	12.40
	5.5	12.34	16.41	12.46
	11	12.44	16.42	12.53
802.11g	6	12.45	16.34	12.49
	9	12.37	16.34	12.53
	12	12.38	16.35	12.52
	18	12.49	16.35	12.54
	24	12.55	16.28	12.50
	36	12.51	16.32	12.51
	48	12.39	13.30	12.48
54	12.42	13.23	12.47	

802.11n-20MHz mode

Mode	Data Rate (MCS Index)	Test Result (dBm)		
		2412MHz (Ch1)	2437MHz (Ch6)	2462 MHz (Ch11)
802.11n (20MHz)	MCS0	12.53	16.39	12.57
	MCS1	12.48	16.36	12.68
	MCS2	12.56	16.42	12.65
	MCS3	12.57	16.38	12.67
	MCS4	12.54	16.35	12.66
	MCS5	12.57	16.36	12.65
	MCS6	12.45	13.25	12.54
	MCS7	12.42	13.28	12.58

See ANNEX B for test graphs.

Conclusion: PASS



A.2 Peak Power Spectral Density

Measurement Limit:

Standard	Limit
FCC CRF Part 15.247(d)	< 8 dBm/3 kHz

Measurement Results:

802.11b/g mode

Mode	Channel	Peak Power Spectral Density(dBm)		Conclusion
802.11b	1	Fig.1	-8.47	P
	6	Fig.2	-5.59	P
	11	Fig.3	-8.56	P
802.11g	1	Fig.4	-11.43	P
	6	Fig.5	-6.55	P
	11	Fig.6	-11.68	P

802.11n-20MHz mode

Mode	Channel	Peak Power Spectral Density(dBm)		Conclusion
802.11n (20MHz)	1	Fig.7	-11.82	P
	6	Fig.8	-7.61	P
	11	Fig.9	-10.60	P

See ANNEX B for test graphs.

Conclusion: PASS

A.3 Occupied 6dB Bandwidth

Measurement Limit:

Standard	Limit (kHz)
FCC 47 CFR Part 15.247 (a)	≥ 500

Measurement Result:

802.11b/g mode

Mode	Channel	Test Results (kHz)		conclusion
802.11b	1	Fig.10	8500	P
	6	Fig.11	8550	P
	11	Fig.12	8550	P
802.11g	1	Fig.13	16400	P
	6	Fig.14	16400	P
	11	Fig.15	16300	P

802.11n-20MHz mode

Mode	Channel	Test Results (kHz)		conclusion
802.11n (20MHz)	1	Fig.16	17300	P
	6	Fig.17	17600	P
	11	Fig.18	17350	P

See ANNEX B for test graphs.

Conclusion: PASS

A.4 Band Edges Compliance

Measurement Limit:

Standard	Limit (dBc)
FCC 47 CFR Part 15.247 (d)	> 20

Measurement Result:

802.11b/g mode

Mode	Channel	Test Results	Conclusion
802.11b	1	Fig.19	P
	11	Fig.20	P
802.11g	1	Fig.21	P
	11	Fig.22	P

802.11n-20MHz mode

Mode	Channel	Test Results	Conclusion
802.11n (20MHz)	1	Fig.23	P
	11	Fig.24	P

See ANNEX B for test graphs.

Conclusion: PASS

A.5 Transmitter Spurious Emission

A.5.1 Transmitter Spurious Emission - Conducted

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247 (d)	20dB below peak output power in 100 kHz bandwidth

Measurement Results:

802.11b/g mode

MODE	Channel	Frequency Range	Test Results	Conclusion
802.11b	1	2.412 GHz	Fig.25	P
		30 MHz-1 GHz	Fig.26	P
		1GHz-10GHz	Fig.27	P
	6	2.437 GHz	Fig.28	P
		30 MHz-1 GHz	Fig.29	P
		1GHz-10GHz	Fig.30	P
	11	2.462 GHz	Fig.31	P
		30 MHz-1 GHz	Fig.32	P
		1GHz-10GHz	Fig.33	P
802.11g	1	2.412 GHz	Fig.34	P
		30 MHz-1 GHz	Fig.35	P
		1GHz-10GHz	Fig.36	P
	6	2.437 GHz	Fig.37	P
		30 MHz-1 GHz	Fig.38	P
		1GHz-10GHz	Fig.39	P
	11	2.462 GHz	Fig.40	P
		30 MHz-1 GHz	Fig.41	P
		1GHz-10GHz	Fig.42	P

802.11n-20MHz mode

802.11n (20MHz)	1	2.412 GHz	Fig.43	P
		30 MHz-1 GHz	Fig.44	P
		1GHz-10GHz	Fig.45	P
	6	2.437 GHz	Fig.46	P
		30 MHz-1 GHz	Fig.47	P
		1GHz-10GHz	Fig.48	P
	11	2.462 GHz	Fig.49	P
		30 MHz-1 GHz	Fig.50	P
		1GHz-10GHz	Fig.51	P
/	All channels	10GHz-26GHz	Fig.52	P

See ANNEX B for test graphs.

Conclusion: PASS

A.5.2 Transmitter Spurious Emission - Radiated

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247, 15.205, 15.209	20dB below peak output power

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Limit in restricted band:

Frequency of emission (MHz)	Field strength(μ V/m)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Test Condition:

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

Frequency of emission (MHz)	RBW/VBW	Sweep Time(s)
30-1000	120kHz/300kHz	5
1000-4000	1MHz/3MHz	15
4000-18000	1MHz/3MHz	40
18000-26500	1MHz/3MHz	20

Note:

According to the performance evaluation, the radiated emission margin of EUT is over 20dB in the band below 30MHz. Therefore, the measurement starts from 30MHz to tenth harmonic. The measurement results include the horizontal polarization and vertical polarization measurements.

Measurement Results:

802.11b/g mode

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11b	1	1 GHz ~18 GHz	Fig.53	P
	6	9 kHz ~30 MHz	Fig.54	P
		30 MHz ~1 GHz	Fig.55	P
		1 GHz ~18 GHz	Fig.56	P
		18 GHz ~26.5 GHz	Fig.57	P
	11	1 GHz ~18 GHz	Fig.58	P
	Power(CH1)	2.38 GHz ~ 2.45 GHz	Fig.59	P
	Power(CH11)	2.45 GHz ~ 2.5 GHz	Fig.60	P
802.11g	1	1 GHz ~18 GHz	Fig.61	P
	6	9 kHz ~30 MHz	Fig.62	P
		30 MHz ~1 GHz	Fig.63	P
		1 GHz ~18 GHz	Fig.64	P
		18 GHz ~26.5 GHz	Fig.65	P
	11	1 GHz ~18 GHz	Fig.66	P
	Power(CH1)	2.38 GHz ~ 2.45 GHz	Fig.67	P
	Power(CH11)	2.45 GHz ~ 2.5 GHz	Fig.68	P

802.11n-20MHz mode

802.11n-20 MHz	1	1 GHz ~18 GHz	Fig.69	P
	6	9 kHz ~30 MHz	Fig.70	P
		30 MHz ~1 GHz	Fig.71	P
		1 GHz ~18 GHz	Fig.72	P
		18 GHz ~26.5 GHz	Fig.73	P
	11	1 GHz ~18 GHz	Fig.74	P
	Power(CH1)	2.38 GHz ~ 2.45 GHz	Fig.75	P
	Power(CH11)	2.45 GHz ~ 2.5 GHz	Fig.76	P

802.11b CH1 (1-18GHz)

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Corr. (dB)	Pol
14047.000000	55.07	74.00	18.93	10.9	V
14770.500000	55.90	74.00	18.10	11.9	H
15798.000000	57.19	74.00	16.81	12.8	V
16280.000000	57.62	74.00	16.38	13.3	H
16733.000000	59.62	74.00	14.38	13.8	H
17553.500000	57.97	74.00	16.03	14.0	H

Frequency (MHz)	Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Corr. (dB)	Pol
14546.000000	43.66	54.00	10.34	11.9	H
15147.500000	44.51	54.00	9.49	12.1	H
15778.500000	45.78	54.00	8.22	12.8	V
16216.000000	46.36	54.00	7.64	13.1	H
16734.500000	46.90	54.00	7.10	13.8	V
17293.500000	46.56	54.00	7.44	13.9	V

802.11b CH 6(1-18GHz)

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Corr. (dB)	Pol
13616.500000	53.55	74.00	20.45	11.1	V
15163.500000	55.90	74.00	18.10	12.1	H
15618.000000	56.56	74.00	17.44	12.5	H
16278.500000	57.21	74.00	16.79	13.3	V
16732.000000	57.21	74.00	16.79	13.8	H
17261.500000	57.03	74.00	16.97	13.9	H

Frequency (MHz)	Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Corr. (dB)	Pol
14551.500000	43.63	54.00	10.37	11.9	V
15159.000000	44.21	54.00	9.79	12.1	V
15748.500000	45.41	54.00	8.59	12.8	H
16190.500000	45.47	54.00	8.53	13.1	H
16847.000000	45.97	54.00	8.03	13.9	H
17271.500000	45.60	54.00	8.40	13.9	H

802.11b CH 11(1GHz-18GHz)

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Corr. (dB)	Pol
14115.000000	55.06	74.00	18.94	11.1	V
15101.000000	56.14	74.00	17.86	12.1	H
15748.500000	56.94	74.00	17.06	12.8	H
16224.000000	56.82	74.00	17.18	13.1	H
16688.000000	57.91	74.00	16.09	13.8	V
17354.000000	56.91	74.00	17.09	14.0	V

Frequency (MHz)	Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Corr. (dB)	Pol
14533.000000	43.54	54.00	10.46	11.9	V
15157.500000	44.24	54.00	9.76	12.1	H
15776.000000	45.35	54.00	8.65	12.8	H
16198.500000	45.54	54.00	8.46	13.1	H
16748.500000	46.24	54.00	7.76	13.9	H
17400.000000	45.47	54.00	8.53	14.0	H

802.11g CH1 (1G-18GHz)

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Corr. (dB)	Pol
12679.500000	52.40	74.00	21.60	10.7	H
13698.500000	54.25	74.00	19.75	11.2	V
15168.000000	56.64	74.00	17.36	12.1	H
16179.500000	57.59	74.00	16.41	13.1	H
16784.500000	58.20	74.00	15.80	13.9	V
17376.500000	58.16	74.00	15.84	14.0	H

Frequency (MHz)	Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Corr. (dB)	Pol
13183.500000	40.45	54.00	13.55	11.2	H
13941.000000	42.26	54.00	11.74	10.8	V
15691.500000	45.58	54.00	8.42	12.7	H
16209.500000	46.05	54.00	7.95	13.1	H
16793.000000	46.65	54.00	7.35	13.9	V
17266.000000	46.15	54.00	7.85	13.9	V

802.11g CH6 (1GHz-18GHz)

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Corr. (dB)	Pol
4869.000000	57.70	74.00	16.30	5.7	H
14912.500000	55.01	74.00	18.99	11.9	V
15777.000000	56.81	74.00	17.19	12.8	V
16343.500000	56.86	74.00	17.14	13.4	V
16789.000000	58.20	74.00	15.80	13.9	V
17434.000000	57.10	74.00	16.90	14.0	H

Frequency (MHz)	Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Corr. (dB)	Pol
4874.250000	44.70	54.00	9.30	5.7	H
15176.500000	43.33	54.00	10.67	12.1	H
15743.000000	45.39	54.00	8.61	12.8	V
16228.000000	45.70	54.00	8.30	13.1	H
16794.500000	46.62	54.00	7.38	13.9	V
17362.500000	45.84	54.00	8.16	14.0	H

802.11g CH11 (1GHz-18GHz)

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Corr. (dB)	Pol
4919.750000	59.16	74.00	14.84	5.7	H
15171.500000	55.88	74.00	18.12	12.1	H
15769.500000	57.37	74.00	16.63	12.8	H
16199.500000	57.28	74.00	16.72	13.1	H
16763.500000	58.13	74.00	15.87	13.9	V
17448.500000	58.15	74.00	15.85	14.0	V

Frequency (MHz)	Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Corr. (dB)	Pol
4924.125000	48.25	54.00	5.75	5.7	H
14533.500000	42.93	54.00	11.07	11.9	V
15166.000000	43.93	54.00	10.07	12.1	V
16216.000000	45.83	54.00	8.17	13.1	V
16768.500000	46.39	54.00	7.61	13.9	H
17282.000000	45.89	54.00	8.11	13.9	V

802.11n-20MHz CH1 (1GHz-18GHz)

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Corr. (dB)	Pol
14550.000000	54.65	74.00	19.35	11.9	V
15070.000000	55.34	74.00	18.66	12.1	H
15625.500000	55.99	74.00	18.01	12.5	H
16122.500000	56.26	74.00	17.74	13.1	H
16732.500000	56.81	74.00	17.19	13.8	V
17433.500000	56.26	74.00	17.74	14.0	H

Frequency (MHz)	Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Corr. (dB)	Pol
14516.500000	43.26	54.00	10.74	11.8	V
15146.000000	43.75	54.00	10.25	12.1	H
15741.500000	44.84	54.00	9.16	12.8	H
16247.500000	44.85	54.00	9.16	13.2	H
16782.000000	45.40	54.00	8.60	13.9	H
17411.000000	44.81	54.00	9.19	14.0	H

802.11n-20MHz CH6 (1GHz-18GHz)

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Corr. (dB)	Pol
14533.000000	54.84	74.00	19.16	11.9	H
15141.500000	55.70	74.00	18.30	12.1	V
15640.500000	56.25	74.00	17.75	12.6	H
16169.000000	56.72	74.00	17.28	13.1	V
16833.000000	57.47	74.00	16.53	13.9	H
17333.000000	56.08	74.00	17.92	14.0	V

Frequency (MHz)	Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Corr. (dB)	Pol
4875.125000	41.64	54.00	12.36	5.7	H
15055.500000	44.12	54.00	9.88	12.1	H
15741.000000	44.90	54.00	9.10	12.8	H
16209.000000	44.90	54.00	9.10	13.1	H
16811.000000	45.45	54.00	8.55	13.9	H
17349.000000	44.94	54.00	9.06	14.0	H

802.11n-20MHz CH11 (1GHz-18GHz)

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Corr. (dB)	Pol
14517.500000	54.34	74.00	19.66	11.8	H
15008.500000	54.77	74.00	19.23	12.0	V
15717.000000	56.80	74.00	17.20	12.7	H
16284.500000	57.00	74.00	17.00	13.3	V
16748.000000	57.94	74.00	16.06	13.9	H
17416.500000	57.50	74.00	16.50	14.0	V

Frequency (MHz)	Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Corr. (dB)	Pol
14182.500000	42.60	54.00	11.40	11.2	H
15158.000000	43.21	54.00	10.79	12.1	H
15742.500000	45.19	54.00	8.81	12.8	H
16203.000000	45.61	54.00	8.39	13.1	H
16797.000000	46.41	54.00	7.59	13.9	H
17398.500000	45.84	54.00	8.16	14.0	V

See ANNEX B for test graphs.

Conclusion: PASS

Note:

A "reference path loss" is established and the A_{Rpl} is the attenuation of "reference path loss", and including the gain of receive antenna, the gain of the preamplifier, the cable loss. P_{Mea} is the field strength recorded from the instrument.

The measurement results are obtained as described below:

$$\text{Result} = P_{Mea} + A_{Rpl} = P_{Mea} + \text{Cable Loss} + \text{Antenna Factor}$$

A.6 AC Powerline Conducted Emission

Test Condition:

Voltage (V)	Frequency (Hz)
120	60

Measurement Result and limit:

WLAN (Quasi-peak Limit)-AE1

Frequency range (MHz)	Quasi-peak Limit (dB μ V)	Result (dB μ V)	Conclusion
		Traffic	
0.15 to 0.5	66 to 56	Fig.77	P
0.5 to 5	56		
5 to 30	60		

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

WLAN (Average Limit)-AE1

Frequency range (MHz)	Average-peak Limit (dB μ V)	Result (dB μ V)	Conclusion
		Traffic	
0.15 to 0.5	56 to 46	Fig.77	P
0.5 to 5	46		
5 to 30	50		

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

WLAN (Quasi-peak Limit)-AE1

Frequency range (MHz)	Quasi-peak Limit (dB μ V)	Result (dB μ V)	Conclusion
		Idle	
0.15 to 0.5	66 to 56	Fig.78	P
0.5 to 5	56		
5 to 30	60		

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

WLAN (Average Limit)-AE1

Frequency range (MHz)	Average-peak Limit (dB μ V)	Result (dB μ V)	Conclusion
		Idle	
0.15 to 0.5	56 to 46	Fig.78	P
0.5 to 5	46		
5 to 30	50		

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

WLAN (Quasi-peak Limit)-AE2

Frequency range (MHz)	Quasi-peak Limit (dB μ V)	Result (dB μ V)	Conclusion
		Traffic	
0.16 to 0.5	66 to 56	Fig.79	P
0.5 to 5	56		
5 to 30	60		

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

WLAN (Average Limit)-AE2

Frequency range (MHz)	Average-peak Limit (dB μ V)	Result (dB μ V)	Conclusion
		Traffic	
0.15 to 0.5	56 to 46	Fig.79	P
0.5 to 5	46		
5 to 30	50		

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

WLAN (Quasi-peak Limit)-AE2

Frequency range (MHz)	Quasi-peak Limit (dB μ V)	Result (dB μ V)	Conclusion
		Idle	
0.16 to 0.5	66 to 56	Fig.80	P
0.5 to 5	56		
5 to 30	60		

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

WLAN (Average Limit)-AE2

Frequency range (MHz)	Average-peak Limit (dB μ V)	Result (dB μ V)	Conclusion
		Idle	
0.15 to 0.5	56 to 46	Fig.80	P
0.5 to 5	46		
5 to 30	50		

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

WLAN (Quasi-peak Limit)-AE3

Frequency range (MHz)	Quasi-peak Limit (dB μ V)	Result (dB μ V)	Conclusion
		Traffic	
0.17 to 0.5	66 to 56	Fig.81	P
0.5 to 5	56		
5 to 30	60		

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

WLAN (Average Limit)-AE3

Frequency range (MHz)	Average-peak Limit (dB μ V)	Result (dB μ V)	Conclusion
		Traffic	
0.15 to 0.5	56 to 46	Fig.81	P
0.5 to 5	46		
5 to 30	50		

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

WLAN (Quasi-peak Limit)-AE3

Frequency range (MHz)	Quasi-peak Limit (dB μ V)	Result (dB μ V)	Conclusion
		Idle	
0.17 to 0.5	66 to 56	Fig.82	P
0.5 to 5	56		
5 to 30	60		

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

WLAN (Average Limit)-AE3

Frequency range (MHz)	Average-peak Limit (dB μ V)	Result (dB μ V)	Conclusion
		Idle	
0.15 to 0.5	56 to 46	Fig.82	P
0.5 to 5	46		
5 to 30	50		

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

Test Condition:

Voltage (V)	Frequency (Hz)
240	60

Measurement Result and limit:

WLAN (Quasi-peak Limit)-AE1

Frequency range (MHz)	Quasi-peak Limit (dB μ V)	Result (dB μ V)	Conclusion
		Traffic	
0.180 to 0.5	66 to 56	Fig.83	P
0.5 to 5	56		
5 to 30	60		

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

WLAN (Average Limit)-AE1

Frequency range (MHz)	Average-peak Limit (dB μ V)	Result (dB μ V)	Conclusion
		Traffic	
0.15 to 0.5	56 to 46	Fig.83	P
0.5 to 5	46		
5 to 30	50		

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

WLAN (Quasi-peak Limit)-AE1

Frequency range (MHz)	Quasi-peak Limit (dB μ V)	Result (dB μ V)	Conclusion
		Idle	
0.180 to 0.5	66 to 56	Fig.84	P
0.5 to 5	56		
5 to 30	60		

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

WLAN (Average Limit)-AE1

Frequency range (MHz)	Average-peak Limit (dB μ V)	Result (dB μ V)	Conclusion
		Idle	
0.15 to 0.5	56 to 46	Fig.84	P
0.5 to 5	46		
5 to 30	50		

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

WLAN (Quasi-peak Limit)-AE2

Frequency range (MHz)	Quasi-peak Limit (dB μ V)	Result (dB μ V)	Conclusion
		Traffic	
0.19 to 0.5	66 to 56	Fig.85	P
0.5 to 5	56		
5 to 30	60		

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

WLAN (Average Limit)-AE2

Frequency range (MHz)	Average-peak Limit (dB μ V)	Result (dB μ V)	Conclusion
		Traffic	
0.15 to 0.5	56 to 46	Fig.85	P
0.5 to 5	46		
5 to 30	50		

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

WLAN (Quasi-peak Limit)-AE2

Frequency range (MHz)	Quasi-peak Limit (dB μ V)	Result (dB μ V)	Conclusion
		Idle	
0.19 to 0.5	66 to 56	Fig.86	P
0.5 to 5	56		
5 to 30	60		

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

WLAN (Average Limit)-AE2

Frequency range (MHz)	Average-peak Limit (dB μ V)	Result (dB μ V)	Conclusion
		Idle	
0.15 to 0.5	56 to 46	Fig.86	P
0.5 to 5	46		
5 to 30	50		

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

WLAN (Quasi-peak Limit)-AE3

Frequency range (MHz)	Quasi-peak Limit (dB μ V)	Result (dB μ V)	Conclusion
		Traffic	
0.20o 0.5	66 to 56	Fig.87	P
0.5 to 5	56		
5 to 30	60		

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

WLAN (Average Limit)-AE3

Frequency range (MHz)	Average-peak Limit (dB μ V)	Result (dB μ V)	Conclusion
		Traffic	
0.15 to 0.5	56 to 46	Fig.87	P
0.5 to 5	46		
5 to 30	50		

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

WLAN (Quasi-peak Limit)-AE3

Frequency range (MHz)	Quasi-peak Limit (dB μ V)	Result (dB μ V)	Conclusion
		Idle	
0.20o 0.5	66 to 56	Fig.88	P
0.5 to 5	56		
5 to 30	60		

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

WLAN (Average Limit)-AE3

Frequency range (MHz)	Average-peak Limit (dB μ V)	Result (dB μ V)	Conclusion
		Idle	
0.15 to 0.5	56 to 46	Fig.88	P
0.5 to 5	46		
5 to 30	50		

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

See ANNEX B for test graphs.

Conclusion: PASS

ANNEX B: TEST LAYOUTS




Fig.1 Power Spectral Density (802.11b, Ch 1)




Fig.2 Power Spectral Density (802.11b, Ch 6)




Fig.3 Power Spectral Density (802.11b, Ch 11)




Fig.4 Power Spectral Density (802.11g, Ch 1)




Fig.5 Power Spectral Density (802.11g, Ch 6)




Fig.6 Power Spectral Density (802.11g, Ch 11)




Fig.7 Power Spectral Density (802.11n-20MHz, Ch 1)




Fig.8 Power Spectral Density (802.11n-20MHz, Ch 6)




Fig.9 Power Spectral Density (802.11n-20MHz, Ch 11)




Fig.10 Occupied 6dB Bandwidth (802.11b, Ch 1)




Fig.11 Occupied 6dB Bandwidth (802.11b, Ch 6)



Fig.12 Occupied 6dB Bandwidth (802.11b, Ch 11)




Fig.13 Occupied 6dB Bandwidth (802.11g, Ch 1)




Fig.14 Occupied 6dB Bandwidth (802.11g, Ch 6)




Fig.15 Occupied 6dB Bandwidth (802.11g, Ch 11)




Fig.16 Occupied 6dB Bandwidth (802.11 n-20MHz, Ch 1)




Fig.17 Occupied 6dB Bandwidth (802.11 n-20MHz, Ch 6)




Fig.18 Occupied 6dB Bandwidth (802.11 n-20MHz, Ch 11)




Fig.19 Band Edges (802.11b, Ch 1)




Fig.20 Band Edges (802.11b, Ch 11)




Fig.21 Band Edges (802.11g, Ch 1)




Fig.22 Band Edges (802.11g, Ch 11)




Fig.23 Band Edges (802.11 n-20MHz, Ch 1)




Fig.24 Band Edges (802.11 n-20MHz, Ch 11)




Fig.25 Conducted Spurious Emission (802.11b, Ch1, Center Frequency)




Fig.26 Conducted Spurious Emission (802.11b, Ch1, 30 MHz-1 GHz)




Fig.27 Conducted Spurious Emission (802.11b, Ch1, 1 GHz-10 GHz)




Fig.28 Conducted Spurious Emission (802.11b, Ch6, Center Frequency)




Fig.29 Conducted Spurious Emission (802.11b, Ch6, 30 MHz-1 GHz)




Fig.30 Conducted Spurious Emission (802.11b, Ch6, 1 GHz-10 GHz)




Fig.31 Conducted Spurious Emission (802.11b, Ch11, Center Frequency)




Fig.32 Conducted Spurious Emission (802.11b, Ch11, 30 MHz-1 GHz)




Fig.33 Conducted Spurious Emission (802.11b, Ch11, 1 GHz-10 GHz)




Fig.34 Conducted Spurious Emission (802.11g, Ch1, Center Frequency)