

Difference Declaration letter

1 Equipment Specification

LYA-L29, LYA-L09 is subscriber equipment in the GSM/WCDMA/LTE system. The GSM frequency band includes GSM850 and GSM900 and DCS1800 and PCS1900. The UMTS frequency band is B1 and B2 and B4 and B5 and B6 and B8 and B19. The LTE frequency band is B1 and B2 and B3 and B4 and B5 and B6 and B7 and B8 and B9 and B12 and B17 and B18 and B19 and B20 and B26 and B28 and B32 and B34 and B38 and B39 and B40 and B41. The Mobile Phone implements such functions as RF signal receiving/transmitting, LTE/HSPA/UMTS and GSM/GPRS/EDGE protocol processing, voice, video MMS service, GPS, Bluetooth, NFC, Wi-Fi and Wirelessly Charging etc. LYA-L29 is a dual SIM smart phone, and one of the SIM card interfaces could be used as HUAWEI Nano SD card interface. LYA-L09 provides one USIM card interface and one HUAWEI Nano SD card interface. Externally it provides type C USB charging port, and the port could be used as the earphone port or data-transfer port.

2 Change description:

Add downlink carrier aggregation: CA_4A-28A, CA_4A-5A, CA_2A-28A, CA_2A-5A, and CA_4A-7A;

Delete downlink carrier aggregation: CA_3A-26A, 1 CA_1A-3A-26A, CA_8A-39A CA_8A-40A, CA_8A-41A, and 39 CA_39A-41A, CA_39C-41A, CA_39A-41C, CA_39C-41C, CA_39A-41D.



Zhang Xinghai

EMC Laboratory Manager

Huawei Technologies Co., Ltd.



E-mail: zhangxinghai@huawei.com

Tel: 0086-0755-28970299

Fax: 0086-0755-89650226

华为信息资产
仅供CTC使用
严禁扩散