



EMC Test Report

Product Name: CDMA 1X Mobile Phone

Model Number: HUAWEI M570

Report No: SYBH(Z-EMC)099052012-2
FCC ID: QISM570

Reliability Laboratory of Huawei Technologies Co., Ltd.

Huawei Base, Bantian, Longgang District, Shenzhen 518129, P.R. China

Tel: +86 755 28780808 Fax: +86 755 89652518

Notice

1. The laboratory has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS), and accreditation number: L0310.
2. The laboratory has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements. The site recognition number is 97456.
3. The laboratory has been listed by industry Canada to perform electromagnetic emission measurement. The site recognition number is 6369A-2.
4. The test report is invalid if not marked with "exclusive stamp for the test report".
5. The test report is invalid if not marked with the stamps or the signatures of the persons responsible for performing, revising and approving the test report.
6. The test report is invalid if there is any evidence of erasure and/or falsification.
7. If there is any dissidence for the test report, please file objection to the test centre within 15 days from the date of receiving the test report.
8. Normally, the test report is only responsible for the samples that have undergone the test.
9. Context of the test report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of the laboratory.



Applicant: Huawei Technologies Co., Ltd.
Address: Huawei Base, Bantian, Longgang District, Shenzhen
518129, P.R. China
Date of Receipt Test Item: May.09, 2012
Start Date of Test: May.10, 2012
End Date of Test: May.25, 2012
Test Result: Pass

Approved By
(Lab Manager)

2012-05-31
Date

Liuchunlin
Name

Signature

Operator

2012-05-31
Date

Daniel
Name

Signature

TABLE OF CONTENT

1	General Information	5
1.1	EUT Description	5
1.2	Test Site Information	6
1.3	Applied Standards	6
2	Summary of Results	7
3	System Configuration during EMC Test	8
3.1	Test Mode	8
3.2	Test System Configuration	8
3.3	Cables Used during Test	11
3.4	Associated Equipment Used during Test	11
4	Electromagnetic Interference (EMI)	12
4.1	Radiated Disturbance 30MHz to 18GHz	12
4.2	Conducted Disturbance 0.15 MHz to 30MHz	14
5	Main Test Instruments	15
6	System Measurement Uncertainty	15
7	Test Graph and Data	16
7.1	Radiated Disturbance	16
7.2	Conducted Disturbance	18

1 General Information

1.1 EUT Description

EUT Description	
Product Name	CDMA 1X Mobile Phone
Model Number	HUAWEI M570
IMEI Number	W5P01A9242100078
TX Frequency	CDMA/EVDO 800: 824 MHz To 849MHz CDMA/EVDO 1900: 1850 MHz To 1910MHz CDMA/EVDO 1700: 1710 MHz To 1755MHz Bluetooth: 2400MHz To 2483.5MHz
RX Frequency	CDMA/EVDO 800: 869 MHz To 894MHz CDMA/EVDO 1900: 1930 MHz To 1990MHz CDMA/EVDO 1700: 2110 MHz To 2155MHz Bluetooth: 2400MHz To 2483.5MHz
HW Version	Ver.B
SW Version	M570 V100R001C45B107
EUT Accessory	
Data cable	Data Cable USB A Male to Micro USB, Black
Adapter	Manufacturer: Huawei Technologies Co., Ltd. Adapter Model: HS-050040U5 Input voltage: ~100-240V 50/60Hz 0.2A Output voltage: 5V  400mA Rated Power: 2W S/N: HKAC12670683 S/N: TPAC11248227
Rechargeable Li-ion	Manufacturer: Huawei Technologies Co., Ltd. Battery Model: HB5A2H Rated capacity: 1150 mAh Nominal Voltage:  +3.7V Charging Voltage:  +4.2V S/N: UNDC302X97700379 S/N: YACC301197702524

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



1.2 Test Site Information

Site 1:	RELIABILITY LABORATORY OF HUAWEI TECHNOLOGIES CO., LTD.
Test Site Location:	Bantian Longgang District Shenzhen, P.R. China

1.3 Applied Standards

APPLIED STANDARD

47 CFR FCC Part 15:2011, Subpart B



2 Summary of Results

Summary of Results				
Test Items	Test Mode	Performance Class & Required Performance Criteria	Result	Site
<u>Radiated Emissions</u> Enclosure Port	Mode1~ Mode2 Mode5 Mode7~ Mode8	CLASS B	Pass	Site1
<u>Conducted Emissions</u> ☒ DC Power Port ☒ AC Power Port ☐ Telecommunication Ports	Mode1~ Mode4	CLASS B	Pass	Site1
Note: 1, Measurement taken is within the measurement uncertainty of measurement system. 2, ☒ The item has been tested; ☐ The item has not been tested.				

Test environment condition:

Item	Required
Ambient temperature	15°C ~ 35°C
Relative humidity	25% ~ 75%
Atmospheric pressure	86kPa ~ 106kPa

3 System Configuration during EMC Test

3.1 Test Mode


Huawei has verified the construction and function in typical operation. All the test modes were carried out with the EUT in normal operation, which was in this test report and defined as:

Test Mode	
Mode 1:	Adapter + earphone + Camera On + Idle
Mode 2:	Adapter + earphone + MP3 + Idle
Mode 3:	Adapter + earphone +Traffic
Mode 4:	Adapter +Traffic
Mode 5:	USB charging+ earphone + Idle
Mode 6:	Traffic
Mode 7:	Camera On + earphone + Idle
Mode 8:	Earphone + MP3 + Idle

Remark: When the EUT have multiple adapters, need separate test with multiple adapters . All test modes are performed, only the worst cases are recorded in this report.

3.2 Test System Configuration


Connection Diagram (Mode 1~Mode 3)



Connection Diagram (Mode 4)




Connection Diagram (Mode 5)



Connection Diagram (Mode 6)



Connection Diagram (Mode 7~Mode 8)





3.3 Cables Used during Test

Cable	Quantity	Length	Type of Cable
USB	1	<3m	shielded
Earphone	1	<3m	Unshielded

3.4 Associated Equipment Used during Test

Name	Model	Manufacturer	S/N	Calibrated Deadline
Radio Communication Tester	CMU200	R&S	3608105673	2012-11-06
Notebook	T61	IBM	3108052508	N/A

4 Electromagnetic Interference (EMI)

4.1 Radiated Disturbance 30MHz to 18GHz



Test Procedure

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4dB according to the standards: ANSI C63.4-2009. The test distance was 3m. The set-up and test methods were according to ANSI C63.4-2009.

A preliminary scan and a final scan of the emissions were made from 30 MHz to 18 GHz by using test script of software; the emissions were measured using Quasi-Peak Detector (30MHz~1GHz) and AV/PK detector (above 1GHz). The maximal emission value was acquired by adjusting the antenna height, polarisation and turntable azimuth in accordance with the software setup. Normally, the height range of antenna was 1m to 4m; the azimuth range of turntable was 0° to 360°. The receiving antenna has two polarizations V and H.

EUT was configured in idle mode and the test performed at worst emission state.

Test setup



Test set-up of radiated disturbance(above 1GHz)



Test Results

The EUT has met the requirements for Radiated Emission of enclosure port.
The test data see section 7.1 of this report.

Test Limits				
Frequency of Emission (MHz)	Radiated Limit			
	Unit(μ V/m)		Unit(dB μ V/m)	
30-88	100		40	
88-216	150		43.5	
216-960	200		46	
Above 960	500		54	
Above 1000	AV	PK	AV	PK
	500	5000	54	74

4.2 Conducted Disturbance 0.15 MHz to 30MHz

Test Procedure


The Table-top EUT was placed upon a non-metallic table 0.8 m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm away from LISN. The set-up and test methods were according to ANSI C63.4-2009. Conducted Disturbance at AC Port measurements were undertaken on the L and N Lines. The emissions were measured using a Quasi-Peak Detector and Average Detector.

EUT was communicated with the simulator through Air interface, the simulator controls the EUT to transmitter the maximum power which defined in specification of product. The EUT operated on the typical channel.

Measurement bandwidth (RBW) for 150kHz to 30 MHz: 9 kHz;

The EUT was setup in the shielded chamber and operated under nominal conditions.

Test Setup



Test Set-up of conducted disturbance

Test Results

The EUT has met requirements for Conducted disturbance of power lines.
The test data see section 7.2 of this report.

Test Limit of AC Power Port		
Frequency range	150kHz ~ 30MHz	
Frequency	Voltage limits	
	QP	AV
0.15MHz~0.5MHz	66-56dBμV	56-46 dBμV
0.5MHz-5MHz	56dBμV	46 dBμV
5MHz~30MHz	60dBμV	50 dBμV

5 Main Test Instruments

Main Test Equipments					
Test item	Test Instrument	Model	S/N	Manufacturer	Calibrated Deadline
RE	EMI Test receiver	ESU26	100150	R&S	May.27, 2013
	Broadband Antenna	VULB 9163	9163-941	SCHWARZBECK	Jul.07, 2013
	Horn Antenna	HF906	100683	R&S	May.15, 2013
CE	EMI Test receiver	ESCI	101163	R&S	Mar. 05, 2013
	Artificial Mains Network	ENV216	100382	R&S	Mar.21, 2013
Software Information					
Test Item	Software Name	Manufacturer		Version	
RE	ES-K1	R&S		1.7.1	
CE	EMC32	R&S		8.52.0	

6 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:


System Measurement Uncertainty		
Items		Extended Uncertainty
RE(30MHz-1GHz)	Field strength (dB μ V/m)	U=4.1dB; k=2
RE(1GHz-18GHz)	Field strength (dB μ V/m)	U=5.1dB; k=2
CE	Disturbance Voltage (dB μ V)	U=2.6dB; k=2

7 Test Graph and Data

Only the worst test result was shown in this report.

7.1 Radiated Disturbance


30MHz~1GHz



MEASUREMENT RESULT: QP Detector

Frequency MHz	Level dBμV/m	Transducer dB	Limit dBμV/m	Margin dB	Height cm	Azimuth deg	Polarisation
34.080000	22.60	14.9	40.0	17.4	150.0	192.00	VERTICAL
88.320000	19.90	11.6	43.5	23.6	128.0	1.00	VERTICAL
101.520000	22.20	13.4	43.5	21.3	121.0	0.00	VERTICAL
233.400000	20.40	13.6	46.0	25.6	100.0	123.00	HORIZONTAL
512.700000	26.90	19.5	46.0	19.1	163.0	152.00	HORIZONTAL
890.100000	32.70	24.8	46.0	13.3	100.0	166.00	VERTICAL

1GHz~18GHz



MEASUREMENT RESULT: PK Detector


Frequency MHz	Level dBμV/m	Transducer dB	Limit dBμV/m	Margin dB	Height cm	Azimuth deg	Polarisation
3797.600000	38.10	-4.9	74.0	35.9	100.0	35.00	VERTICAL
6858.100000	42.20	2.2	74.0	31.8	187.0	149.00	VERTICAL
14353.200000	47.90	14.8	74.0	26.1	100.0	117.00	HORIZONTAL

MEASUREMENT RESULT: AV Detector

Frequency MHz	Level dBμV/m	Transducer dB	Limit dBμV/m	Margin dB	Height cm	Azimuth deg	Polarisation
3802.100000	25.00	-4.9	54.0	29.0	100.0	91.00	VERTICAL
6868.100000	28.50	2.2	54.0	25.5	100.0	35.00	VERTICAL
14350.200000	35.00	14.8	54.0	19.0	100.0	124.00	HORIZONTAL

7.2 Conducted Disturbance

AC Port Test Data



MEASUREMENT RESULT: QP Detector

Frequency MHz	Level dBμV	Transducer dB	Limit dBμV	Margin dB	Line	PE
0.167969	39.6	9.7	65.1	25.5	L1	FLO
0.325440	39.6	9.7	59.6	20.0	N	FLO
0.586522	40.1	9.7	56.0	15.9	N	FLO
1.035600	36.6	9.7	56.0	19.4	N	FLO
1.396612	36.6	9.7	56.0	19.4	N	FLO
2.076945	37.9	9.7	56.0	18.1	N	FLO

MEASUREMENT RESULT: AV Detector

Frequency MHz	Level dBμV	Transducer dB	Limit dBμV	Margin dB	Line	PE
0.150189	41.8	9.7	56.0	14.2	N	FLO
0.187132	39.9	9.7	54.2	14.3	N	FLO
0.264016	40.5	9.7	51.3	10.8	N	FLO
0.547788	32.8	9.7	46.0	13.2	N	FLO
0.958793	32.6	9.7	46.0	13.4	N	FLO
1.292786	32.1	9.7	46.0	13.9	N	FLO

-----END-----