



# Appendix A: 20dB Emission Bandwidth (EBW)




## 1 Result Table

EUT Conf.	EBW [MHz]	Verdict
TM1_DH5_Ch0	0.95	Pass
TM1_DH5_Ch39	0.95	Pass
TM1_DH5_Ch78	0.95	Pass
TM2_2DH5_Ch0	1.44	Pass
TM2_2DH5_Ch39	1.44	Pass
TM2_2DH5_Ch78	1.44	Pass
TM3_3DH5_Ch0	1.44	Pass
TM3_3DH5_Ch39	1.44	Pass
TM3_3DH5_Ch78	1.44	Pass



## 2 Test Plot

### 2.1 TM1\_DH5\_Ch0





2.2 TM1\_DH5\_Ch39




2.3 TM1\_DH5\_Ch78






### 2.4 TM2\_2DH5\_Ch0






2.5 TM2\_2DH5\_Ch39






2.6 TM2\_2DH5\_Ch78








2.7 TM3\_3DH5\_Ch0






2.8 TM3\_3DH5\_Ch39





### 2.9 TM3\_3DH5\_Ch78





# Appendix B: Carrier Frequency Separation




## 1 Result Table

EUT Conf.	Carrier Frequency Separation [MHz]	Verdict
TM1_DH5_Hop	0.95	Pass
TM2_2DH5_Hop	0.95	Pass
TM3_3DH5_Hop	1.15	Pass




## 2 Test Plot

### 2.1 TM1\_DH5\_Hop






### 2.2 TM2\_2DH5\_Hop





### 2.3 TM3\_3DH5\_Hop







# Appendix C: Number of Hopping Channel




## 1 Result Table

EUT Conf.	Number of Hopping Channel	Verdict
TM1_DH5_Hop	79	Pass
TM2_2DH5_Hop	79	Pass
TM3_3DH5_Hop	79	Pass




## 2 Test Plot

### 2.1 TM1\_DH5\_Hop






## 2.2 TM2\_2DH5\_Hop





### 2.3 TM3\_3DH5\_Hop





# Appendix D: Time of Occupancy (Dwell Time)

## 1 Result Table

The Dwell Time = Burst Width \* Total Hops. The detailed calculations are showed as follows:

- The duration for dwell time calculation:  $0.4 \text{ [s]} * \text{hopping number} = 0.4 \text{ [s]} * 79 \text{ [ch]} = 31.6 \text{ [s*ch]}$ ;
- The burst width [ms/hop/ch], which is directly measured, refers to the duration on one channel hop.
- The hops per second for all channels: The selected EUT Conf uses a slot type of 5-Tx&1-Rx and a hopping rate of 1600 [ch\*hop/s] for all channels. So the final hopping rate for all channels is  $1600 / 6 = 266.67 \text{ [ch*hop/s]}$ ;
- The hops per second on one channel:  $266.67 \text{ [ch*hop/s]} / 79 \text{ [ch]} = 3.38 \text{ [hop/s]}$ ;
- The total hops for all channels within the dwell time calculation duration:  $3.38 \text{ [hop/s]} * 31.6 \text{ [s*ch]} = 106.67 \text{ [hop*ch]}$ ;
- The dwell time for all channels hopping:  $106.67 \text{ [hop*ch]} * \text{Burst Width [ms/hop/ch]}$ .


EUT Conf.	Burst Width [s/hop/ch]	Total Hops [hop*ch]	Dwell Time [ms]	Verdict
TM1_DH5_Ch39	0.0029	106.67	0.309	Pass
TM2_2DH5_Ch39	0.0029	106.67	0.309	Pass
TM3_3DH5_Ch39	0.0029	106.67	0.309	Pass



## 2 Test Plot

NOTE: The test plots are only for Burst Width measurements.


### 2.1 TM1\_DH5\_Ch39








### 2.2 TM2\_2DH5\_Ch39





### 2.3 TM3\_3DH5\_Ch39





# Appendix E: Maximum Peak Conducted Output Power




## 1 Result Table

EUT Conf.	Max. Peak Power [dBm]	Verdict
TM1_DH5_Ch0	9.453	Pass
TM1_DH5_Ch39	9.813	Pass
TM1_DH5_Ch78	10.008	Pass
TM2_2DH5_Ch0	8.064	Pass
TM2_2DH5_Ch39	8.356	Pass
TM2_2DH5_Ch78	8.508	Pass
TM3_3DH5_Ch0	8.055	Pass
TM3_3DH5_Ch39	8.47	Pass
TM3_3DH5_Ch78	8.522	Pass




## 2 Test Plot

### 2.1 TM1\_DH5\_Ch0






## 2.2 TM1\_DH5\_Ch39





### 2.3 TM1\_DH5\_Ch78





### 2.4 TM2\_2DH5\_Ch0







### 2.5 TM2\_2DH5\_Ch39





### 2.6 TM2\_2DH5\_Ch78





### 2.7 TM3\_3DH5\_Ch0





### 2.8 TM3\_3DH5\_Ch39





### 2.9 TM3\_3DH5\_Ch78





# Appendix F: Band edge spurious emission



## 1 Result Table


EUT Conf.	Channel No.	Carrier Frequency [MHz]	Max. Spurious Level [dBm]	Frequency Hopping	Carrier Power [dBm]	Limit [dBm]	Result
TM1_DH5_Ch0	0	2402	-31.902	Off	9.491	-10.509	Pass
	-	-	-42.934	On	9.303	-10.697	Pass
TM1_DH5_Ch78	78	2480	-48.951	Off	10.092	-9.908	Pass
	-	-	-52.501	On	9.603	-10.397	Pass
TM2_2DH_5_Ch0	0	2402	-39.693	Off	6.968	-13.032	Pass
	-	-	-41.815	On	6.85	-13.15	Pass
TM2_2DH_5_Ch78	78	2480	-51.004	Off	7.464	-12.536	Pass
	-	-	-51.544	On	6.716	-13.284	Pass
TM3_3DH_5_Ch0	0	2402	-38.879	Off	6.655	-13.345	Pass
	-	-	-41.131	On	6.517	-13.483	Pass
TM3_3DH_5_Ch78	78	2480	-50.85	Off	7.454	-12.546	Pass
	-	-	-52.36	On	5.456	-14.544	Pass



## 2 Test Plot


### 2.1 TM1\_DH5\_Ch0

No hopping





With hopping






## 2.2 TM1\_DH5\_Ch78

No hopping




With hopping



2.3 TM2\_2DH5\_Ch0

No hopping



With hopping






2.4 TM2\_2DH5\_Ch78

No hopping



With hopping





2.5 TM3\_3DH5\_Ch0

No hopping







With hopping






### 2.6 TM3\_3DH5\_Ch78

No hopping





With hopping





# Appendix G: Conducted RF Spurious Emission

## 1 Result Table

In this Appendix, the “Pref” refers to the peak power level in any 100 kHz bandwidth within the fundamental emission which is used as the reference level, the “Puw” refers to the maximum emission power in 100 kHz band segments outside of the authorized frequency band.

Considering that the higher ratio of RBW to the span for the frequency ranges below 30 MHz makes the results determination be complicated, a narrower RBW other than 100 kHz is used for these ranges. The measured value should add a RBW correction factor (RBWCF) where  $RBWCF [dB] = 10 \times \lg(100 [kHz]/narrower\ RBW [kHz])$ . As to this Appendix, the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

In the result table, the “< Limit” denotes that “The Puw [dBm] is less than Pref [dBm] - 20 [dB], see test plots for detailed”.


EUT Conf.	Pref [dBm/100 kHz]	Puw [dBm/100 kHz]	Verdict
TM1_DH5_Ch0	9.338	< Limit	Pass
TM1_DH5_Ch39	9.7	< Limit	Pass
TM1_DH5_Ch78	9.909	< Limit	Pass
TM2_2DH5_Ch0	6.849	< Limit	Pass
TM2_2DH5_Ch39	7.149	< Limit	Pass
TM2_2DH5_Ch78	7.303	< Limit	Pass
TM3_3DH5_Ch0	6.855	< Limit	Pass
TM3_3DH5_Ch39	7.297	< Limit	Pass
TM3_3DH5_Ch78	7.307	< Limit	Pass



## 2 Test Plot


### 2.1 TM1\_DH5\_Ch0


#### 2.1.1 Pref







### 2.1.2 Puw





















## 2.2 TM1\_DH5\_Ch39


### 2.2.1 Pref







### 2.2.2 P<sub>uw</sub>




















### 2.3 TM1\_DH5\_Ch78


#### 2.3.1 Pref







### 2.3.2 Puw





















## 2.4 TM2\_2DH5\_Ch0


### 2.4.1 Pref








### 2.4.2 Puw



















## 2.5 TM2\_2DH5\_Ch39


### 2.5.1 Pref





### 2.5.2 Puw


















## 2.6 TM2\_2DH5\_Ch78


### 2.6.1 Pref








### 2.6.2 Puw














## 2.7 TM3\_3DH5\_Ch0


### 2.7.1 Pref











### 2.7.2 Puw

















## 2.8 TM3\_3DH5\_Ch39

### 2.8.1 Pref








### 2.8.2 P<sub>uw</sub>




















## 2.9 TM3\_3DH5\_Ch78


### 2.9.1 Pref







### 2.9.2 Puw



















# Appendix H: Radiated Emissions in the Restricted Bands



### 3 Result Table

The whole testing range is from “9KHz to 26.5 GHz (10th harmonics)” is divided into 5 parts according to the test site settings, which are:

- (Part 1): Test range of “9 KHz to 30 MHz”,
- (Part 2): Test range of “30 GHz to 1 GHz”,
- (Part 3): Test range of “1 GHz to 3 GHz”.
- (Part 4): Test range of “3 GHz to 18 GHz”,
- (Part 5): Test range of “18 GHz to 26.5 GHz”.

In this Appendix, only the test results and plots under the worst case can be reported. In the result table, the “< Limit” denotes that “Not found obvious spikes or see marked spikes on plots and listed emissions records”.

Test Range	EUT Conf.	Emissions	Verdict
30 MHz to 1 GHz	TM1_DH5_Ch0 (Worst Conf.)	< Limit	Pass
1 GHz to 3 GHz	TM1_DH5_Ch0 (Worst Conf.)	< Limit	Pass
	TM1_DH5_Ch78 (Worst Conf.)	< Limit	Pass
3 GHz to 18 GHz	TM1_DH5_Ch0 (Worse Conf.)	< Limit	Pass
18 GHz to 26.5 GHz	TM1_DH5_Ch0 (Worst Conf.)	< Limit	Pass

Note: We tested all modes, but the data presented below is the worst case.

## 4 Result Plot


### Part 1: Testing Range of “9 kHz to 30MHz”

Note 1: No peak found in the Test Range of “9 kHz to 30MHz”

### Part 2: Testing Range of “30 MHz to 1 GHz”

Note 1: The test results and plot for testing range of “30 MHz to 1 GHz” showed as below is the WORST case for all Test Modes and Channels. This range will not be presented for each Test Mode and each Channel.

Note 2: The emissions in this range are mainly from the Platform Device (Notepad PC and its ancillary components).



#### MEASUREMENT RESULT: QP Detector

Frequency (MHz)	Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Trans d. (dB)
38.051000	30.79	40.00	9.21	100.0	V	319.0	17.0
147.467000	29.22	43.50	14.28	100.0	V	263.0	12.8
190.486500	22.04	43.50	21.46	100.0	V	116.0	12.0
257.368000	21.52	46.00	24.48	100.0	H	171.0	14.3
313.967500	27.63	46.00	18.37	100.0	H	353.0	16.9



---

---

439.485500	28.00	46.00	14.00	100.0	V	42.0	19.2
------------	-------	-------	-------	-------	---	------	------

Note:

1, Level =Reading level by receiver + Transd (Antenna factor + cable loss – preamplifier gain)


The reading level is calculated by software which is not shown in the sheet.

2, Margin=Limit - Level




### Part 3: Testing Range of “1GHz to 3GHz”

- Note 1: The testing range of “1 GHz to 3 GHz” is for checking radiated emissions located in restricted bands near the EUT operating bands.
- Note 2: Two limits are required in the testing range above 1 GHz, that is Peak limit (74 dB $\mu$ V/m) and Average Limit (54 dB $\mu$ V/m).
- Note 3: The peak spike exceeds the limit line is EUT’s operating frequency.



**Channel 0**



MEASUREMENT RESULT: AV Detector

Frequency (MHz)	Level (dBμ V/m)	Limit (dBμ V/m)	Margin (dB)	Height (cm)	Pol	Azimuth h (deg)	Transd. (dB)
2390.0000	26.56	54.00	27.44	150.0	H	75.0	-8.5

MEASUREMENT RESULT: PK Detector

Frequency (MHz)	Level (dBμ V/m)	Limit (dBμ V/m)	Margin (dB)	Height (cm)	Pol	Azimuth h (deg)	Transd. (dB)
2390.0000	35.30	74.00	38.70	150.0	H	229.0	-8.5


Note:

1, Level =Reading level by receiver + Transd (Antenna factor + cable loss – preamplifier gain)

The reading level is calculated by software which is not shown in the sheet.

2, Margin=Limit - Level

**Channel 78**



**MEASUREMENT RESULT: AV Detector**

Frequency (MHz)	Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Height (cm)	Pol	Azimuth h (deg)	Transd. (dB)
2483.5000	32.03	54.00	21.97	150.0	H	214.0	-6.8

**MEASUREMENT RESULT: PK Detector**

Frequency (MHz)	Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Height (cm)	Pol	Azimuth h (deg)	Transd. (dB)
2483.5000	40.23	74.00	33.77	150.0	H	214.0	-6.8

Note:


1, Level = Reading level by receiver + Transd (Antenna factor + cable loss – preamplifier gain)

The reading level is calculated by software which is not shown in the sheet.

2, Margin = Limit - Level

#### Part 4: Testing Range of “3 GHz to 18 GHz”

- Note 1: The test results and plot for testing range of “3 GHz to 18 GHz” showed as below is the WORST case for all Test Modes and Channels. This range will not be presented for each Test Mode and each Channel.
- Note 2: The testing range of “3 GHz to 18 GHz” is for checking radiated emissions located in restricted bands faraway from the EUT operating bands.
- Note 3: Two limits are required in the testing range above 3 GHz, that is Peak limit (74 dB $\mu$ V/m) and Average Limit (54 dB $\mu$ V/m).





**Part 5: Testing Range of “18 GHz to 26.5 GHz”**


NOTE1: No peak found in the Test Range of “18 GHz to 26.5GHz”



# Appendix I: AC Power Line Conducted Emissions

Note: RBW =9 kHz, VBW = 30 kHz

## Channel 39



**MEASUREMENT RESULT: AV Detector**

Frequency (MHz)	Level (dBμ V)	Limit (dBμ V)	Transd. (dB)	Margin (dB)	Line	PE
0.152159	29.42	55.88	9.7	26.46	N	FLO
0.165488	27.75	55.18	9.7	27.43	L1	FLO
0.573867	30.57	46.00	9.7	15.43	N	FLO
1.162088	17.17	46.00	9.7	28.83	L1	FLO
1.728475	19.65	46.00	9.7	26.35	N	FLO
5.183011	20.98	50.00	9.8	29.02	L1	FLO

**MEASUREMENT RESULT: PK Detector**

Frequency (MHz)	Level (dB $\mu$ V)	Limit (dB $\mu$ V)	Transd. (dB)	Margin (dB)	Line	PE
0.153192	47.66	65.83	9.7	18.17	N	FLO
0.308458	33.33	60.01	9.7	26.68	L1	FLO
0.568452	36.69	56.00	9.7	19.31	N	FLO
0.958101	23.74	56.00	9.7	32.26	N	FLO
2.373022	26.09	56.00	9.7	29.91	N	FLO
5.217639	28.03	60.00	9.8	31.97	L1	FLO

Note:

1, Level = Reading level by receiver + Transd (Antenna factor + cable loss – preamplifier gain)

The reading level is calculated by software which is not shown in the sheet.

2, Margin = Limit - Level

END