



中国认可
国际互认
检测
TESTING
CNAS L0310



ACCREDITED
TESTING CERT #2174.01

FCC

RF Test Report

Product Name: Smart Phone

**Model Number: HUAWEI MLA-L12, MLA-L12, HUAWEI
MLA-L02, MLA-L02**

Report No: SYBH(Z-RF)017062016-2001

FCC ID: QISMLA-LX2

Reliability Laboratory of Huawei Technologies Co., Ltd.

(Global Compliance and Testing Center of Huawei Technologies Co., Ltd)

Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District,
Shenzhen, 518129, P.R.C
Tel: +86 755 28780808 Fax: +86 755 89652518



HUAWEI

RF Test Report of HUAWEI MLA-L12, MLA-L12, HUAWEI MLA-L02, MLA-L02

Notice

1. The laboratory has passed the accreditation by China National Accreditation Service for Conformity Assessment (CNAS). The accreditation number is L0310.
2. The laboratory has passed the accreditation by The American Association for Laboratory Accreditation (A2LA). The accreditation number is 2174.01 & 2174.02 & 2174.03.
3. The laboratory has been listed by the US Federal Communications Commission to perform electromagnetic emission measurements. The site recognition number is 97456.
4. The laboratory has been listed by Industry Canada to perform electromagnetic emission measurements. The recognition numbers of test site are 6369A-1.
5. The laboratory (Reliability Lab of Huawei Technologies Co., Ltd) is also named “Global Compliance and Testing Center of Huawei Technologies Co., Ltd”, the both names have coexisted since 2009.
6. The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
7. The test report is invalid if there is any evidence of erasure and/or falsification.
8. The test report is only valid for the test samples.
9. Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.



HUAWEI

RF Test Report of HUAWEI MLA-L12, MLA-L12, HUAWEI MLA-L02, MLA-L02

Applicant: Huawei Technologies Co., Ltd.
Address: Administration Building, Headquarters of Huawei Technologies Co., Ltd.,
Bantian, Longgang District, Shenzhen, 518129, P.R.C

Date of Receipt Sample: 2016-07-11

Start Date of Test: 2016-07-11

End Date of Test: 2016-07-25

Test Result: Pass

Approved by Senior 2016-07-25 Roger Zhang *Roger Zhang*
Engineer: Date Name Signature

Prepared by: 2016-07-25 zhoulingbo *zhoulingbo*
Date Name Signature



CONTENT

1	General Information	5
1.1	Applied Standard	5
1.2	Test Location	5
1.3	Test Environment Condition	5
2	Test Summary	6
2.1	Cellular Band (824-849 MHz paired with 869-894 MHz)	6
2.2	LTE BAND5 and WCDMA BAND5 (824-849 MHz paired with 869-894 MHz)	7
2.3	PCS Band (1850-1910 MHz paired with 1930-1990 MHz)	8
2.4	BRS&EBS Band7 (2500-2570 MHz paired with 2620-2690 MHz)	9
2.5	BRS&EBS Band38 (2570-2620 MHz paired with 2570-2620 MHz)	11
3	Description of the Equipment under Test (EUT)	12
3.1	General Description	12
3.2	EUT Identity	14
3.3	Technical Specification	15
4	General Test Conditions / Configurations	16
4.1	Test Modes	16
4.2	Test Environment	16
4.3	Test Frequency	17
4.4	DESCRIPTION OF TESTS	21
4.5	Test Setups	27
4.6	Test Conditions	30
5	Main Test Instruments	32
6	Measurement Uncertainty	34
7	Appendixes	34



HUAWEI

RF Test Report of HUAWEI MLA-L12, MLA-L12, HUAWEI MLA-L02, MLA-L02

1 General Information

1.1 Applied Standard

Applied Rules: 47 CFR FCC Part 02:2014
47 CFR FCC Part 22: 2014
47 CFR FCC Part 24: 2014
47 CFR FCC Part 27: 2014

Test Method: FCC KDB 971168 D01 Power Meas License Digital Systems v02r02

1.2 Test Location

Test Location : Reliability Laboratory of Huawei Technologies Co., Ltd.
Address: Administration Building, Headquarters of Huawei Technologies Co., Ltd.,
Bantian, Longgang District, Shenzhen, 518129, P.R.C

1.3 Test Environment Condition

Ambient Temperature: 19.5 to 25 °C
Ambient Relative Humidity: 40 to 55 %
Atmospheric Pressure: Not applicable



HUAWEI

RF Test Report of HUAWEI MLA-L12, MLA-L12, HUAWEI MLA-L02, MLA-L02

2 Test Summary

2.1 Cellular Band (824-849 MHz paired with 869-894 MHz)

Test Item	FCC Rule No.	Requirements	Test Result	Verdict (Note1)
Effective (Isotropic) Radiated Power Output Data	§2.1046, §22.913	FCC: ERP ≤ 7 W.	Appendix A	SYBH(Z-R F)0270520 16-2001
Peak-Average Ratio	---	---	---	SYBH(Z-R F)0270520 16-2001
Modulation Characteristics	§2.1047	Digital modulation	Appendix C	SYBH(Z-R F)0270520 16-2001
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	Appendix D	SYBH(Z-R F)0270520 16-2001
Band Edges Compliance	§2.1051, §22.917	≤ -13 dBm/1%*EBW, in 1 MHz bands immediately outside and adjacent to the frequency block.	Appendix E	SYBH(Z-R F)0270520 16-2001
Spurious Emission at Antenna Terminals	§2.1051, §22.917	FCC: ≤ -13 dBm/100 kHz, from 9 kHz to 10 th harmonics but outside authorized operating frequency ranges.	Appendix F	SYBH(Z-R F)0270520 16-2001
Field Strength of Spurious Radiation	§2.1053, §22.917	FCC: ≤ -13 dBm/100 kHz.	Appendix G	SYBH(Z-R F)0270520 16-2001
Frequency Stability	§2.1055, §22.355	≤ ±2.5ppm.	Appendix H	SYBH(Z-R F)0270520 16-2001

NOTE 1: For the verdict, the "N/A" denotes "not applicable", the "N/T" denotes "not tested".



HUAWEI

RF Test Report of HUAWEI MLA-L12, MLA-L12, HUAWEI MLA-L02, MLA-L02

2.2 LTE BAND5 and WCDMA BAND5 (824-849 MHz paired with 869-894 MHz)

Test Item	FCC Rule No.	Requirements	Test Result	Verdict (Note1)
Effective (Isotropic) Radiated Power Output Data	§2.1046, §22.913	FCC: ERP ≤ 7 W.	Appendix A	SYBH(Z-R F)0220620 16-2001
Peak-Average Ratio	---	---	---	SYBH(Z-R F)0220620 16-2001
Modulation Characteristics	§2.1047	Digital modulation	Appendix C	SYBH(Z-R F)0220620 16-2001
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	Appendix D	SYBH(Z-R F)0220620 16-2001
Band Edges Compliance	§2.1051, §22.917	≤ -13 dBm/1%*EBW, in 1 MHz bands immediately outside and adjacent to the frequency block.	Appendix E	SYBH(Z-R F)0220620 16-2001
Spurious Emission at Antenna Terminals	§2.1051, §22.917	FCC: ≤ -13 dBm/100 kHz, from 9 kHz to 10 th harmonics but outside authorized operating frequency ranges.	Appendix F	SYBH(Z-R F)0220620 16-2001
Field Strength of Spurious Radiation	§2.1053, §22.917	FCC: ≤ -13 dBm/100 kHz.	Appendix G	SYBH(Z-R F)0220620 16-2001
Frequency Stability	§2.1055, §22.355	≤ ±2.5ppm.	Appendix H	SYBH(Z-R F)0220620 16-2001

NOTE 1: For the verdict, the "N/A" denotes "not applicable", the "N/T" denotes "not tested".



HUAWEI

RF Test Report of HUAWEI MLA-L12, MLA-L12, HUAWEI MLA-L02, MLA-L02

2.3 PCS Band (1850-1910 MHz paired with 1930-1990 MHz)

Test Item	FCC Rule No.	Requirements	Test Result	Verdict (Note1)
Effective (Isotropic) Radiated Power Output Data	§2.1046, §24.232	EIRP ≤ 2 W	Appendix A	SYBH(Z-R F)0270520 16-2001
Peak-Average Ratio	§2.1046, §24.232	Limit≤13 dB	Appendix B	SYBH(Z-R F)0270520 16-2001
Modulation Characteristics	§2.1047	Digital modulation	Appendix C	SYBH(Z-R F)0270520 16-2001
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	Appendix D	SYBH(Z-R F)0270520 16-2001
Band Edges Compliance	§2.1051, §24.238	≤ -13 dBm/1%*EBW, in 1 MHz bands immediately outside and adjacent to the frequency block.	Appendix E	SYBH(Z-R F)0270520 16-2001
Spurious Emission at Antenna Terminals	§2.1051, §24.238	≤ -13 dBm/1 MHz, from 9 kHz to 10 th harmonics but outside authorized operating frequency ranges.	Appendix F	SYBH(Z-R F)0270520 16-2001
Field Strength of Spurious Radiation	§2.1053, §24.238	≤ -13 dBm/1 MHz.	Appendix G	SYBH(Z-R F)0270520 16-2001
Frequency Stability	§2.1055, §24.235	IC: ≤ ±2.5 ppm.	Appendix H	SYBH(Z-R F)0270520 16-2001

NOTE 1: For the verdict, the "N/A" denotes "not applicable", the "N/T" denotes "not tested".


2.4 BRS&EBS Band7 (2500-2570 MHz paired with 2620-2690 MHz)

Test Item	FCC Rule No.	Requirements	Test Result	Verdict (Note1)
Effective (Isotropic) Radiated Power Output Data	§2.1046, §27.50(h)	EIRP ≤ 2W	Appendix A	SYBH(Z-R F)027052 016-2001
Peak-Average Ratio	§27.50(a)	FCC: Limit ≤ 13 dB	Appendix B	SYBH(Z-R F)027052 016-2001
Modulation Characteristics	§2.1047	Digital modulation	Appendix C	SYBH(Z-R F)027052 016-2001
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	Appendix D	SYBH(Z-R F)027052 016-2001
Band Edges Compliance	§2.1051, §27.53(m4)	<p>FCC: IC:</p> <p>2%*EBW Channel Edge 2%*EBW</p> <p>-10 dBm -10 dBm -13 dBm</p> <p>5.5 MHz 4 MHz 1 MHz 1 MHz (X-4) MHz</p> <p>RBW ≥ 2%*EBW RBW ≥ 2%*EBW X=Max {6MHz, EBW}</p> <p>2%*EBW Channel Edge 2%*EBW</p> <p>-10 dBm -10 dBm -13 dBm</p> <p>5.5 MHz 4 MHz 1 MHz 1 MHz (X-4) MHz</p> <p>RBW ≥ 2%*EBW RBW ≥ 2%*EBW X=Max {6MHz, EBW}</p>	Appendix E	SYBH(Z-R F)027052 016-2001
Spurious Emission at Antenna Terminals	§2.1051, §27.53(m)	<p>-25 dBm/1 MHz</p> <p>9 kHz 9.5 MHz X MHz 10th harmonics</p> <p>X=Max {6MHz, EBW}</p>	Appendix F	SYBH(Z-R F)027052 016-2001



HUAWEI

RF Test Report of HUAWEI MLA-L12, MLA-L12, HUAWEI MLA-L02, MLA-L02

Test Item	FCC Rule No.	Requirements	Test Result	Verdict (Note1)
Field Strength of Spurious Radiation	§2.1053, §27.53(m)	 -25 dBm/ 1 MHz 9 kHz 9.5 MHz X MHz 10th harmonics X=Max [6MHz, EBW]	Appendix G	SYBH(Z-R F)027052 016-2001
Frequency Stability	§2.1055, §27.54	Within authorized bands of operation/frequency block.	Appendix H	SYBH(Z-R F)027052 016-2001

NOTE 1: For the verdict, the "N/A" denotes "not applicable", the "N/T" denotes "not tested".

2.5 BRS&EBS Band38 (2570-2620 MHz paired with 2570-2620 MHz)

Test Item	FCC Rule No.	Requirements	Test Result	Verdict (Note1)
Effective (Isotropic) Radiated Power Output Data	§2.1046, §27.50(h)	EIRP \leq 2W	Appendix A	pass
Peak-Average Ratio	§27.50(a)	FCC: Limit \leq 13 dB	Appendix B	pass
Modulation Characteristics	§2.1047	Digital modulation	Appendix C	pass
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	Appendix D	pass
Band Edges Compliance	§2.1051, §27.53(m4)	<p>FCC: IC:</p> <p>2%*EBW Channel Edge</p> <p>2%*EBW</p> <p>-10 dBm</p> <p>-13 dBm</p> <p>1m 1m 1m 1m</p> <p>5.5 MHz 4 MHz 1 MHz 1 MHz 4 MHz (X-4) MHz</p> <p>RBW \geq 2%*EBW</p> <p>X = Max {6MHz, EBW}</p>	Appendix E	pass
Spurious Emission at Antenna Terminals	§2.1051, §27.53(m)	<p>Channel Edge</p> <p>-25 dBm/1 MHz</p> <p>-25 dBm/1 MHz</p> <p>9 kHz 9.5 MHz X MHz 10th harmonics</p> <p>X = Max {6MHz, EBW}</p>	Appendix F	pass
Field Strength of Spurious Radiation	§2.1053, §27.53(m)	<p>Channel Edge</p> <p>-25 dBm/1 MHz</p> <p>-25 dBm/1 MHz</p> <p>9 kHz 9.5 MHz X MHz 10th harmonics</p> <p>X = Max {6MHz, EBW}</p>	Appendix G	pass
Frequency Stability	§2.1055, §27.54	Within authorized bands of operation/frequency block.	Appendix H	pass

NOTE 1: For the verdict, the "N/A" denotes "not applicable", the "N/T" denotes "not tested".

NOTE 1 : The Appendixes please see No.: SYBH(Z-RF)017062016-2001-A of Appendix for LTE Band38



3 Description of the Equipment under Test (EUT)

3.1 General Description

HUAWEI MLA-L12, MLA-L12, HUAWEI MLA-L02, MLA-L02 is subscriber equipment in the GSM/WCDMA/LTE system. The GSM frequency band includes GSM850 and GSM900 and DCS1800 and PCS1900. The UMTS frequency band is B1 and B5 and B8. The LTE frequency band is B1 and B3 and B5 and B7 and B8 and B28 and B38 and B40. The Mobile Phone implements such functions as RF signal receiving/transmitting, LTE/HSPA/UMTS and GSM/GPRS/EDGE protocol processing, voice, video MMS service, GPS, AGPS and WIFI etc. Externally it provides one micro SD card interface (it can also be used as SIM card interface), earphone port (to provide voice service) and one SIM card interface. HUAWEI MLA-L12, MLA-L12 is a dual SIM smart phone. It also provides Bluetooth module to synchronize data between a PC and the phone, or to use the built-in modem of the phone to access the Internet with a PC, or to exchange data with other Bluetooth devices.

Note: The only differences between the new model and the original model are:

- Model HUAWEI MLA-L12, MLA-L12 is a smart phone with dual SIM
- .- Model HUAWEI MLA-L02, MLA-L02 is a smart phone with single SIM.
- The difference of them is only for SIM CARD. HUAWEI MLA-L02, MLA-L02 delete one SIM by software.

Differences between MLA-L11 and MLA-L13 and MLA-L12

	MLA-L12	MLA-L13	MLA-L11
GSM four bands	B2/B3/B5/B8	B2/B3/B5/B8	B2/B3/B5/B8
WCDMA bands	B1/ B5/B8	B1/B2/B4/B5/B8	B1/B8
LTE bands	B1/B3/B5/B7/B8/B28/B38/B40	B2/B4/B5/B7/B12/B17/B28	B1/B3/B7/ B8/B20/B38
FCC bands	GSM850/1900 W850 LTE B5/B7/B38	GSM850/1900 W850/W1700/W1900 LTE B2/B4/B5/B7/B12/B17	GSM850/1900 LTE B7 /B38
SIM card	Two	Two	Two
External camera	the same	the same	the same
internal camera	the same	the same	the same
FLASH	the same	the same	the same
Mainboard	the same	the same	the same
PCB layout	the same	the same	the same
Appearance	the same	the same	the same
Bluetooth mode	the same	the same	the same



HUAWEI

RF Test Report of HUAWEI MLA-L12, MLA-L12, HUAWEI MLA-L02, MLA-L02

WLAN mode	the same	the same	the same
BT/ WLAN antenna	the same	the same	the same
GSM/ WCDMA /LTE antenna	the same	the same	the same
Adapter	the same	the same	the same
Battery	the same	the same	the same
Chipset	the same	the same	the same
Memory	the same	the same	the same
RF Parameter	The same RF Parameter in the same band	The same RF Parameter in the same band	The same RF Parameter in the same band
Dimension	the same	the same	the same
Main Frequency NV	The same NV in the same band	The same NV in the same band	The same NV in the same band

NOTE1:We do not test GSM850/900 AND LTE B7 data of MLA-L12 MLA-L02,all the test data refer to

SYBH(Z-RF)027052016-2001 of MLA-L11

NOTE1:We do not test LTE B5 and WCDMA850 data of MLA-L12 MLA-L02,all the test data refer to

SYBH(Z-RF)022062016-2001 of MLA-L13.



HUAWEI

RF Test Report of HUAWEI MLA-L12, MLA-L12, HUAWEI MLA-L02, MLA-L02

3.2 EUT Identity

NOTE: Unless otherwise noted in the report, the functional boards installed in the units shall be selected from the below list, but not means all the functional boards listed below shall be installed in one unit.

3.2.1 Board

Board		
Description	Hardware Version	Software Version
Main Board	HL1MLAL01M	MLA-L12C900B063 MLA-L02C900B063

3.2.2 Sub-Assembly

Sub-Assembly			
Sub-Assembly Name	Model	Manufacturer	Description
Adapter	HW-050200U01	Huawei Technologies Co., Ltd.	Input Voltage: ~100-240V 50/60Hz 0.5A Output Voltage: 5V 2A
Adapter	HW-050200E01	Huawei Technologies Co., Ltd.	Input Voltage: ~100-240V 50/60Hz 0.5A Output Voltage: 5V 2A
Adapter	HW-050200B01	Huawei Technologies Co., Ltd.	Input Voltage: ~100-240V 50/60Hz 0.5A Output Voltage: 5V 2A
Adapter	HW-050200A01	Huawei Technologies Co., Ltd.	Input Voltage: ~100-240V 50/60Hz 0.5A Output Voltage: 5V 2A
Battery	HB386483ECW+	Huawei Technologies Co., Ltd.	Rated capacity: 3270mAh Nominal Voltage: +3.82V Charging Voltage: +4.40V



HUAWEI

RF Test Report of HUAWEI MLA-L12, MLA-L12, HUAWEI MLA-L02, MLA-L02

3.3 Technical Specification

Characteristics	Description	
Radio System Type	<input checked="" type="checkbox"/> GSM <input checked="" type="checkbox"/> UMTS <input checked="" type="checkbox"/> LTE	
Supported Frequency Range	GSM850/ WCDMA850	Transmission (TX): 824 to 849 MHz
		Receiving (RX): 869 to 894 MHz
	GSM1900	Transmission (TX): 1850 to 1910 MHz
		Receiving (RX): 1930 to 1990 MHz
	LTE BAND5	Transmission (TX): 824 to 849 MHz
		Receiving (RX): 869 to 894 MHz
	LTE BAND7	Transmission (TX): 2500 to 2570 MHz
		Receiving (RX): 2620 to 2690 MHz
	LTE BAND38	Transmission (TX): 2570 to 2620 MHz
		Receiving (RX): 2570 to 2620 MHz
TX and RX Antenna Ports	TX & RX port:	2
	TX-only port:	0
	RX-only port:	1
Target TX Output Power	LTE 38: 22.5 dBm	
Supported Channel Bandwidth	GSM system:	<input checked="" type="checkbox"/> 200 kHz
	UMTS system:	<input checked="" type="checkbox"/> 5MHz,
	LTE band 5	<input checked="" type="checkbox"/> 1.4 MHz, <input checked="" type="checkbox"/> 3 MHz, <input checked="" type="checkbox"/> 5 MHz, <input checked="" type="checkbox"/> 10 MHz
	LTE band 7	<input checked="" type="checkbox"/> 5 MHz, <input checked="" type="checkbox"/> 10 MHz, <input checked="" type="checkbox"/> 15 MHz, <input checked="" type="checkbox"/> 20 MHz
	LTE band 38	<input checked="" type="checkbox"/> 5MHz, <input checked="" type="checkbox"/> 10MHz, <input checked="" type="checkbox"/> 15MHz, <input checked="" type="checkbox"/> 20MHz
Designation of Emissions (Note: the necessary bandwidth of which is the worst value from the measured occupied bandwidths for each type of channel bandwidth configuration.)	LTE BAND38:	4M51G7D (5 MHz QPSK modulation), 4M50W7D (5 MHz 16QAM modulation) 8M97G7D (10 MHz QPSK modulation), 8M96W7D (10 MHz 16QAM modulation) 13M5G7D (15 MHz QPSK modulation), 13M5W7D (15 MHz 16QAM modulation) 18M0G7D (20 MHz QPSK modulation), 18M0W7D (20 MHz 16QAM modulation)

4 General Test Conditions / Configurations

4.1 Test Modes

NOTE: The test mode(s) are selected according to relevant radio technology specifications.

Test Mode	Test Modes Description
GSM/TM1	GSM system, GSM/GPRS, GMSK modulation
GSM/TM2	GSM system, EDGE, 8PSK modulation
UMTS/TM1	WCDMA system, QPSK modulation
UMTS/TM2	HSDPA system, QPSK modulation
UMTS/TM3	HSUPA system, QPSK modulation
LTE/TM1	LTE system, QPSK modulation
LTE/TM2	LTE system, 16QAM modulation

4.2 Test Environment

Environment Parameter	Selected Values During Tests	
Relative Humidity	Ambient	
Temperature	TN	Ambient
Voltage	VL	3.6 V
	VN	3.8V
	VH	4.35V

NOTE: VL= lower extreme test voltage

VN= nominal voltage

VH= upper extreme test voltage

TN= normal temperature



4.3 Test Frequency

Test Mode	TX / RX	RF Channel		
		Low (L)	Middle (M)	High (H)
GSM850	TX	Channel 128	Channel 190	Channel 251
		824.2MHz	836.6MHz	848.8MHz
	RX	Channel 128	Channel 190	Channel 251
		869.2MHz	881.6MHz	893.8MHz
WCDMA850	TX	Channel 4132	Channel 4182	Channel 4233
		826.4MHz	836.4MHz	846.6MHz
	RX	Channel 4357	Channel 4407	Channel 4458
		871.4MHz	881.4MHz	891.6MHz
Test Mode	TX / RX	RF Channel		
		Low (L)	Middle (M)	High (H)
GSM1900	TX	Channel 512	Channel 661	Channel 810
		1850.2MHz	1880.0MHz	1909.8MHz
	RX	Channel 512	Channel 661	Channel 810
		1930.2 MHz	1960.0 MHz	1989.8 MHz

Test Mode	TX / RX	RF Channel		
		Low (B)	Middle (M)	High (T)
LTE Band 5	TX(1.4M)	Channel 20407	Channel 20525	Channel 20643
		824.7 MHz	836.5 MHz	848.3 MHz
	TX(3M)	Channel 20415	Channel 20525	Channel 20635
		825.5 MHz	836.5 MHz	847.5 MHz
	TX(5M)	Channel 20425	Channel 20525	Channel 20625



HUAWEI

RF Test Report of HUAWEI MLA-L12, MLA-L12, HUAWEI MLA-L02, MLA-L02

Test Mode	TX / RX	RF Channel		
		Low (B)	Middle (M)	High (T)
		826.5 MHz	836.5 MHz	846.5 MHz
TX(10M)	RX(1.4M)	Channel 20450	Channel 20525	Channel 20600
		829 MHz	836.5 MHz	844 MHz
RX(3M)	RX(5M)	Channel 2407	Channel 2525	Channel 2643
		869.7 MHz	881.5 MHz	893.3 MHz
RX (10M)	RX (10M)	Channel 2415	Channel 2525	Channel 2635
		870.5 MHz	881.5 MHz	892.5 MHz
RX(5M)	RX (10M)	Channel 2425	Channel 2525	Channel 2625
		871.5 MHz	881.5 MHz	891.5 MHz
RX (10M)	RX (10M)	Channel 2450	Channel 2525	Channel 2600
		874 MHz	881.5 MHz	889 MHz

Test Mode	TX / RX	RF Channel		
		Low (B)	Middle (M)	High (T)
LTE Band 7	TX (5M)	Channel 20775	Channel 21100	Channel 21425
		2502.5 MHz	2535 MHz	2567.5 MHz
	TX (10M)	Channel 20800	Channel 21100	Channel 21400
		2505 MHz	2535 MHz	2565 MHz
	TX (15M)	Channel 20825	Channel 21100	Channel 21375
		2507.5 MHz	2535 MHz	2562.5 MHz
	TX (20M)	Channel 20850	Channel 21100	Channel 21350
		2510 MHz	2535 MHz	2560 MHz
	RX (5M)	Channel 2775	Channel 3100	Channel 3425



HUAWEI

RF Test Report of HUAWEI MLA-L12, MLA-L12, HUAWEI MLA-L02, MLA-L02

Test Mode	TX / RX	RF Channel		
		Low (B)	Middle (M)	High (T)
		2622.5 MHz	2655 MHz	2687.5 MHz
	RX (10M)	Channel 2800	Channel 3100	Channel 3400
		2625 MHz	2655 MHz	2685 MHz
	RX (15M)	Channel 2825	Channel 3100	Channel 3375
		2627.5 MHz	2655 MHz	2682.5 MHz
	RX (20M)	Channel 2850	Channel 3100	Channel 3350
		2630 MHz	2655 MHz	2680 MHz

Test Mode	TX / RX	RF Channel		
		Low (B)	Middle (M)	High (T)
LTE Band 38	TX(5M)	Channel 37775	Channel 38000	Channel 38225
		2572.5 MHz	2595 MHz	2617.5 MHz
	TX(10M)	Channel 37800	Channel 38000	Channel 38200
		2575 MHz	2595 MHz	2615 MHz
	TX(15M)	Channel 37825	Channel 38000	Channel 38175
		2577.5 MHz	2595 MHz	2612.5 MHz
	TX(20M)	Channel 37850	Channel 38000	Channel 38150
		2580 MHz	2595 MHz	2610 MHz
	RX(5M)	Channel 37775	Channel 38000	Channel 38225
		2572.5 MHz	2595 MHz	2617.5 MHz
	RX(10M)	Channel 37800	Channel 38000	Channel 38200
		2575 MHz	2595 MHz	2615 MHz
	RX(15M)	Channel 37825	Channel 38000	Channel 38175
		2577.5 MHz	2595 MHz	2612.5 MHz



HUAWEI

RF Test Report of HUAWEI MLA-L12, MLA-L12, HUAWEI MLA-L02, MLA-L02

Test Mode	TX / RX	RF Channel		
		Low (B)	Middle (M)	High (T)
	RX(20M)	Channel 37850	Channel 38000	Channel 38150
		2580 MHz	2595 MHz	2610 MHz

4.4 DESCRIPTION OF TESTS

4.4.1 Radiated Power and Radiated Spurious Emissions

Radiated spurious emissions are investigated indoors in a semi-anechoic chamber to determine the frequencies producing the worst case emissions. Final measurements for radiated power and radiated spurious emissions are performed on the 3 meter OATS per the guidelines of ANSI/TIA-603-C-2004. The equipment under test was transmitting while connected to its integral antenna and is placed on a wooden turntable 80cm above the ground plane and 3 meters from the receive antenna. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer. Emissions are also investigated with the receive antenna horizontally and vertically polarized.

A portable or small unlicensed wireless device shall be placed on a non-metallic test fixture or other non-metallic support during testing. The supporting fixture shall permit orientation of the EUT in each of three orthogonal (x, y, z) axis positions such that emissions from the EUT are maximized. Measure the EUT maximum RF power and record the result.

A half-wave dipole is then substituted in place of the EUT. For emissions above 3 GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT.

The power of the emission is calculated using the following formula:

$$P_d \text{ [dBm]} = P_g \text{ [dBm]} - \text{cable loss [dB]} + \text{antenna gain [dBd/dBi]}$$

Where, P_d is the dipole equivalent power, P_g is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to P_g [dBm] – cable loss [dB].

The calculated P_d levels are then compared to the absolute spurious emission limit of -13dBm which is equivalent to the required minimum attenuation of $43 + 10\log_{10}(\text{Power [Watts]})$.

Test Procedures Used

KDB 971168 v02r02-Section 5.2.1 / KDB 971168 v02R02-Section 5.8

ANSI/TIA-603-C-2004-Section 2.2.17 / ANSI/TIA-603-C-2004-Section 2.2.12

Note: Reference test setup 3



HUAWEI

RF Test Report of HUAWEI MLA-L12, MLA-L12, HUAWEI MLA-L02, MLA-L02

4.4.2 Peak-Average Ratio

A peak to average ratio measurement is performed at the conducted port of the EUT. For WCDMA signals, the spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level. For GSM signals, an average and a peak trace are used on a spectrum analyzer to determine the largest deviation between the average and the peak power of the EUT in a bandwidth greater than the emission bandwidth. The traces are generated with the spectrum analyzer set to zero span mode.

Test Procedures Used

KDB 971168 v02r02-Section 5.7.1

Test Settings

1. The signal analyzer's CCDF measurement profile enabled
2. Frequency= carrier center frequency
3. Measurement BW > EBW of signal
4. for continuous transmissions, set to 1ms
5. Record the maximum PAPR level associated with a probability of 0.1%.

Note: Reference test setup 1

4.4.3 Occupied Bandwidth

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts. The resolution bandwidth shall be set to as close to 1 percent of the selected span as is possible without being below 1 percent. The video bandwidth shall be set to 3 times the resolution bandwidth. Video averaging is not permitted. Where practical, a sampling detector shall be used since a peak or, peak hold, may produce a wider bandwidth than actual. The trace data points are recovered and are directly summed in linear terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 percent of the total is reached and that frequency recorded. The process is repeated for the highest frequency data points. This frequency is recorded. The span between the two recorded frequencies is the occupied bandwidth.

Test Procedures Used

KDB 971168 v02r02-Section 4.2

Test Settings

- 1、SET RBW=1-5% of OBW
- 2、SET VBW \geq 3*RBW
- 3、Detector: Peak
- 4、Trace mode= max hold.
- 5、Sweep= auto couple
- 6、Steps 1-5 were repeated after it is stable

Note: Reference test setup 1.



HUAWEI

RF Test Report of HUAWEI MLA-L12, MLA-L12, HUAWEI MLA-L02, MLA-L02

4.4.4 Band Edge Compliance

the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission power must be attenuated below the transmitting power (P) by a factor of at least $43+10\log_{10}P$ dB.

Test Procedures Used

KDB 971168 v02r02-Section 6.0

Test Settings

- 1、SET RBW \geq 1% of Emission BW.
- 2、SET VBW about three times of RBW
- 3、Detector: RMS
- 4、Trace mode= max hold.
- 5、Span= 2MHz

Note: Reference test setup 1.



HUAWEI

RF Test Report of HUAWEI MLA-L12, MLA-L12, HUAWEI MLA-L02, MLA-L02

4.4.5 Spurious and Harmonic Emissions at Antenna Terminal

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB. Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

Test Procedures Used

KDB 971168 v02r02-Section 6.0

Test Settings

1、 9kHz~150kHz, RBW = 1KHz, VBW \geq 3×RBW,

150kHz~30MHz, RBW = 10KHz, VBW \geq 3×RBW,

30MHz~1GHz, RBW = 100 kHz, VBW = 300 kHz.

Above 1GHz, RBW = 1 MHz, VBW = 3 MHz.

2、 Detector: Peak

3、 Trace mode= max hold.

Note: Reference test setup 1.



HUAWEI

RF Test Report of HUAWEI MLA-L12, MLA-L12, HUAWEI MLA-L02, MLA-L02

4.4.6 Frequency Stability / Temperature Variation

Frequency stability testing is performed in accordance with the guidelines of ANSI/TIA-603-C-2004. The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

Specification – The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5 \text{ ppm}$) of the center frequency.

Time Period and Procedure:

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.


Test Procedures Used

ANSI/TIA-603-C-2004


Note: Reference test setup 2.

4.5 Test Setups

4.5.1 Test Setup 1




4.5.2 Test Setup 2




4.5.3 Test Setup 3

NOTE: Effective radiated power (ERP) and Equivalent Isotropic Radiated Power(EIRP) refers to the radiation power output of the EUT, assuming all emissions are radiated from half-wave dipole antennas.

4.5.3.1 Step 1: Pre-test



4.5.3.2 Step 2: Substitution method to verify the maximum ERP/EIRP





HUAWEI

4.6 Test Conditions

Test Case		Test Conditions		
Transmit Output Power Data	Average Power, Total	Test Env.	Ambient Climate & Rated Voltage	
		Test Setup	Test Setup 1	
		RF Channels (TX)	L, M, H (L= low channel, M= middle channel, H= high channel)	
		Test Mode	GSM/TM1,GSM/TM2,LTE/TM2	
	Average Power, Spectral Density (if required)	Test Env.	Ambient Climate & Rated Voltage	
		Test Setup	Test Setup 1	
		RF Channels (TX)	L, M, H (L= low channel, M= middle channel, H= high channel)	
		Test Mode	GSM/TM1,GSM/TM2,LTE/TM2	
Peak-to-Average Ratio (if required)		Test Env.	Ambient Climate & Rated Voltage	
		Test Setup	Test Setup 1	
		RF Channels (TX)	L, M, H (L= low channel, M= middle channel, H= high channel)	
		Test Mode	GSM/TM1,GSM/TM2,LTE/TM2	
Modulation Characteristics		Test Env.	Ambient Climate & Rated Voltage	
		Test Setup	Test Setup 1	
		RF Channels (TX)	M (L= low channel, M= middle channel, H= high channel)	
		Test Mode	GSM/TM1,GSM/TM2,LTE/TM2	
Bandwidth	Occupied Bandwidth	Test Env.	Ambient Climate & Rated Voltage	
		Test Setup	Test Setup 1	
		RF Channels (TX)	L, M, H (L= low channel, M= middle channel, H= high channel)	
		Test Mode	GSM/TM1,GSM/TM2,LTE/TM2	
	Emission Bandwidth (if required)	Test Env.	Ambient Climate & Rated Voltage	
		Test Setup	Test Setup 1	
		RF Channels (TX)	L, M, H (L= low channel, M= middle channel, H= high channel)	
		Test Mode	GSM/TM1,GSM/TM2,LTE/TM2	
Band Edges Compliance		Test Env.	Ambient Climate & Rated Voltage	
		Test Setup	Test Setup 1	
		RF Channels (TX)	L, H (L= low channel, M= middle channel, H= high channel)	
		Test Mode	GSM/TM1,GSM/TM2,LTE/TM2	
Spurious Emission at Antenna Terminals		Test Env.	Ambient Climate & Rated Voltage	
		Test Setup	Test Setup 1	
		RF Channels (TX)	L, M, H (L= low channel, M= middle channel, H= high channel)	



HUAWEI

RF Test Report of HUAWEI MLA-L12, MLA-L12, HUAWEI MLA-L02, MLA-L02

Test Case	Test Conditions	
	Test Mode	GSM/TM1,GSM/TM2,LTE/TM2
Field Strength of Spurious Radiation	Test Env.	Ambient Climate & Rated Voltage
	Test Setup	Test Setup 3
	Test Mode	GSM/TM1,GSM/TM2, LTE/TM1,LTE/TM2 NOTE: If applicable, the EUT conf. that has maximum power density (based on the equivalent power level) is selected.
	RF Channels (TX)	L, M, H (L= low channel, M= middle channel, H= high channel)
Frequency Stability	Test Env.	(1) -30 °C to +50 °C with step 10 °C at Rated Voltage; (2) VL, VN and VH of Rated Voltage at Ambient Climate.
	Test Setup	Test Setup 2
	RF Channels (TX)	L, M, H (L= low channel, M= middle channel, H= high channel)
	Test Mode	GSM/TM1,GSM/TM2,LTE/TM2



HUAWEI

RF Test Report of HUAWEI MLA-L12, MLA-L12, HUAWEI MLA-L02, MLA-L02

5 Main Test Instruments

Main Test Equipments					
Equipment Name	Manufacturer	Model	Serial Number	Cal Date	Cal- Due
Power supply	KEITHLEY	2303	1342889	2015/9/16	2017/9/15
Wireless Communication Test set	Agilent	N4010A	MY49081592	2015/10/30	2016/10/29
Universal Radio Communication Tester	R&S	CMU200	123299	2015/10/30	2016/10/29
Spectrum Analyzer	Agilent	N9020A	MY52090652	2016/6/29	2017/6/29
Universal Radio Communication Tester	R & S	CMW500	126854	2016/1/8	2017/1/7
Signal Analyzer	R&S	FSQ31	200021	2015/10/30	2016/10/29
Spectrum Analyzer	Agilent	N9030A	MY49431698	2015/10/30	2016/10/29
Temperature Chamber	WEISS	WKL64	5.6246E+13	2016/1/21	2017/1/20
Signal generator	Agilent	E8257D	MY49281095	2015/10/30	2016/10/29
Vector Signal Generator	R&S	SMU200A	104162	2015/10/30	2016/10/29
Test receiver	R&S	ESU26	100387	2016/6/21	2017/6/20
Test receiver	R&S	ESCI	101163	2015/11/11	2016/11/10
Spectrum analyzer	R&S	FSU3	200474	2016/5/24	2017/5/23
Spectrum analyzer	R&S	FSU43	100144	2015/6/2	2017/6/2
LOOP Antennas(9kHz-30MHz)	R&S	HFH2-Z2	100262	2015/4/30	2017/4/29
LOOP Antennas(9kHz-30MHz)	R&S	HFH2-Z2	100263	2015/4/30	2017/4/29
Trilog Broadband Antenna (30M~3GHz)	SCHWARZBECK	VULB 9163	9163-490	2015/4/30	2017/4/29
Trilog Broadband Antenna (30M~3GHz)	SCHWARZBECK	VULB 9163	9163-520	2015/4/30	2017/4/29
Double-Ridged Waveguide Horn Antenna (1G~18GHz)	R&S	HF907	100304	2015/4/30	2017/4/29
double ridged horn antenna (0.8G-18GHz)	R&S	HF907	100305	2015/4/30	2017/4/29



HUAWEI

RF Test Report of HUAWEI MLA-L12, MLA-L12, HUAWEI MLA-L02, MLA-L02

Pyramidal Horn Antenna(18GHz-26.5GHz)	ETS-Lindgren	Sep-60	5140299	2015/7/15	2017/7/14
Artificial Main Network	R&S	ENV4200	100134	2016/6/2	2017/6/1
Line Impedance Stabilization Network	R&S	ENV216	100382	2016/6/2	2017/6/1
Signal Generator	Agilent	E4438C	MY49071538	2016/3/1	2017/3/1
Software Information					
Test Item	Software Name	Manufacturer	Version		
RE	EMC32	R&S	V9.25.0		
CE	EMC32	R&S	V9.25.0		
RSE	EMC32	R&S	V8.40.0		



HUAWEI

RF Test Report of HUAWEI MLA-L12, MLA-L12, HUAWEI MLA-L02, MLA-L02

6 Measurement Uncertainty

For a 95% confidence level ($k = 2$), the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 as following:

Test Item		Extended Uncertainty
Transmit Output Power Data	Power [dBm]	$U = 0.42 \text{ dB}$
Bandwidth	Magnitude [%]	$U = 0.2\%$
Band Edge Compliance	Disturbance Power [dBm]	$U = 1.24 \text{ dB}$
Spurious Emissions, Conducted	Disturbance Power [dBm]	$U = 1.62 \text{ dB}$
Field Strength of Spurious Radiation	ERP [dBm]	For 3 m Chamber: $U = 4.9 \text{ dB}$ (30 MHz to 26.5GHz)
Frequency Stability	Frequency Accuracy [ppm]	$U = 0.017 \text{ ppm}$

7 Appendices

Appendix No.	Description
SYBH(Z-RF)017062016-2001-A	Appendix for LTE B38

END