



# **FCC RF Test Report**

**Product Name: Vodafone Mobile Wi-Fi**

**Model Number: R208**

**Report No: SYBH(Z-RF)001082012-2001  
FCC ID:QISR208**

**Reliability Laboratory of Huawei Technologies Co., Ltd.**

Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District,  
Shenzhen, 518129, P.R.C  
Tel: +86 755 28780808 Fax: +86 755 89652518

## Notice

1. The laboratory has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS), and accreditation number: L0310.
2. The laboratory has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements. The site recognition number is 97456.
3. The laboratory has been listed by industry Canada to perform electromagnetic emission measurement. The site recognition number is 6369A-2.
4. The test report is invalid if not marked with "exclusive stamp for the test report".
5. The test report is invalid if not marked with the stamps or the signatures of the persons responsible for performing, revising and approving the test report.
6. The test report is invalid if there is any evidence of erasure and/or falsification.
7. If there is any dissidence for the test report, please file objection to the test centre within 15 days from the date of receiving the test report.
8. Normally, the test report is only responsible for the samples that have undergone the test.
9. Context of the test report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of the laboratory.



Operated By Sep., 05, 2012 Huang Qiuliang Huang Qiuliang  
Date Name Signature

# Contents

|          |                                                        |           |
|----------|--------------------------------------------------------|-----------|
| <b>1</b> | <b><u>General Information</u></b>                      | <b>5</b>  |
| 1.1      | APPLIED STANDARD                                       | 5         |
| 1.2      | TEST LOCATION                                          | 5         |
| 1.3      | TEST ENVIRONMENTAL CONDITION                           | 5         |
| <b>2</b> | <b><u>Summary</u></b>                                  | <b>6</b>  |
| <b>3</b> | <b><u>Product Description</u></b>                      | <b>7</b>  |
| 3.1      | PRODUCT INFORMATION                                    | 7         |
| <b>4</b> | <b><u>Test Description</u></b>                         | <b>9</b>  |
| 4.1      | SUPPORTED FREQUENCY RANGE                              | 9         |
| 4.2      | TRANSMITTER / RECEIVER CHARACTERISTICS                 | 9         |
| 4.3      | ANTENNA GAIN                                           | 10        |
| 4.4      | POWER SUPPLY                                           | 10        |
| <b>5</b> | <b><u>General Test Conditions / Configurations</u></b> | <b>11</b> |
| 5.1      | RF CHANNELS UNDER TEST                                 | 11        |
| 5.2      | TEST MODES                                             | 11        |
| 5.3      | TEST ENVIRONMENT                                       | 11        |
| 5.4      | TEST SETUP                                             | 12        |
| 5.5      | TEST CONDITIONS                                        | 16        |
| <b>6</b> | <b><u>Main Test Instruments</u></b>                    | <b>18</b> |
| <b>7</b> | <b><u>Test Results</u></b>                             | <b>19</b> |
| <b>8</b> | <b><u>Measurement Uncertainty</u></b>                  | <b>19</b> |

# 1 General Information

|                                         |                                                                                                                             |
|-----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| <b>1.1 Applied Standard</b>             |                                                                                                                             |
|                                         |                                                                                                                             |
| Applied Rules:                          | 47 CFR FCC Part 2:2011, Subpart J<br>47 CFR FCC Part 22:2011, Subpart H<br>ANSI/TIA 603C:2004                               |
|                                         |                                                                                                                             |
| <b>1.2 Test Location</b>                |                                                                                                                             |
|                                         |                                                                                                                             |
| Test Location 1:                        | Reliability Laboratory of Huawei Technologies Co., Ltd.                                                                     |
| Address:                                | Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C |
|                                         |                                                                                                                             |
| <b>1.3 Test Environmental Condition</b> |                                                                                                                             |
|                                         |                                                                                                                             |
| Ambient Temperature:                    | 20 – 25 °C                                                                                                                  |
| Ambient Relative Humidity:              | 45 – 55 %                                                                                                                   |
| Atmospheric Pressure:                   | 101 kPa                                                                                                                     |
|                                         |                                                                                                                             |

## 2 Summary

Table 1 Summary of results

| Test Case                              | FCC Part No.    | Requirements                                                                                                                                    | Result |
|----------------------------------------|-----------------|-------------------------------------------------------------------------------------------------------------------------------------------------|--------|
| Cellular Band                          |                 |                                                                                                                                                 |        |
| Transmitter Output Power               | 2.1046 & 22.913 | ERP not exceed 7 W                                                                                                                              | Pass   |
| Modulation Characteristics             | 2.1047          | Digital modulation                                                                                                                              | Pass   |
| Occupied Bandwidth                     | 2.1049          | (Not specified)                                                                                                                                 | Pass   |
| Band Edges Compliance                  | 2.1051 & 917    | Below -13 dBm/1%*EBW, in 1 MHz range                                                                                                            | Pass   |
| Spurious Emission at Antenna Terminals | 2.1051 & 2.917  | Below -13 dBm/1 kHz, 9 kHz to 150 kHz<br>Below -13 dBm/10 kHz, 150 kHz to 30 MHz<br>Below -13 dBm/100 kHz, 30 MHz to 10 <sup>th</sup> harmonics | Pass   |
| Field Strength of Spurious Radiation   | 2.1053 & 22.917 | Below -13 dBm/100 kHz                                                                                                                           | Pass   |
| Frequency Stability                    | 2.1055 & 22.355 | Maintained within the tolerances of $\pm 2.5$ ppm                                                                                               | Pass   |

### 3 Product Description

#### 3.1 Product Information

##### 3.1.1 General Description

R208 DC-HSDPA/2100M/900M/850M/EDGE Quad Band is subscriber equipment in the UMTS/GSM system. R208 implement such functions as RF signal receiving/ transmitting, DC-HSDPA/WCDMA protocol processing, data service etc, and it can act as a Wi-Fi hotspot for user accessing to internet. Externally it provides USB interface (to connect to the notebook etc.), USIM card interface and Micro SD card interface. R208 has 3 internal antennas as default Wi-Fi , diversity, and main antenna.

##### 3.1.2 Board Information

Table 2 Board Information

| Vodafone Mobile Wi-Fi               |                  |     |
|-------------------------------------|------------------|-----|
| R208                                |                  |     |
| Board and Module                    |                  |     |
| Equipment Designation / Description | Hardware version | S/N |
| Main Board                          | CH1E5756SM       | --  |

##### 3.1.3 Adapter Technical Data

| Name    | Manufacture | Description                                                                                                           |
|---------|-------------|-----------------------------------------------------------------------------------------------------------------------|
| Adapter | HUAWEI      | Adapter,-10degC-45degC,100V, 240V, 5.0V/2.0A,CE 2PIN/DC USB 2.0,ERP V, GHOST/CE, HUAWEI LOGO,White,Terminal Dedicated |

### 3.1.4 Battery Technical Data

| Name           | Manufacture                   | Description                                                                                                                                                                                                                                                                   |
|----------------|-------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Li-ion Battery | Huawei Technologies Co., Ltd. | Battery Model: HB5P1H<br>Rated capacity: 3000mAh<br>Nominal Voltage:  +3.7V<br>Charging Voltage:  +4.2V |



## 4 Test Description

### 4.1 Supported Frequency Range

| Characteristics | Description    |
|-----------------|----------------|
| Downlink        | 869 to 894 MHz |
| Uplink          | 824 to 849 MHz |

### 4.2 Transmitter / Receiver Characteristics

| Characteristics                    | Description                                                                                 |
|------------------------------------|---------------------------------------------------------------------------------------------|
| System Type                        | GSM<br>UMTS                                                                                 |
| TX Output Power (per Antenna Port) | GSM system: Power class 4<br>UMTS system: Power class 3                                     |
| Channel Spacing(s) / Bandwidth(s)  | GSM system: 200 kHz<br>UMTS system: 5 MHz                                                   |
| Designation of Emissions           | GSM system: 255KGXW (GMSK modulation),<br>253KG7W (8PSK modulation)<br>UMTS system: 4M18F9W |

### 4.3 Antenna Gain

|                   |       |
|-------------------|-------|
| Antenna Gain(dBi) | 2.02  |
| Antenna Gain(dBd) | -0.13 |

### 4.4 Power Supply

| Specification           | Description                                                                           |
|-------------------------|---------------------------------------------------------------------------------------|
| Power Supply Type       | Directly Connected to DC /AC Power Supply                                             |
| Input to EUT (DC power) | DC Voltage Nominal: $\approx$ +3.7 V<br>DC Voltage Range: $\approx$ +3.6 V to + 4.2 V |
| Input to EUT (AC power) | AC Voltage Nominal: ~ 120 V (50/60 Hz)<br>AC Voltage Range: ~ 100 V to 240 V          |

## 5 General Test Conditions / Configurations

### 5.1 RF Channels under Test

| Test Mode   | TX / RX | RF Channel   |              |              |
|-------------|---------|--------------|--------------|--------------|
|             |         | Low (L)      | Middle (M)   | High (H)     |
| TM1/TM2     | TX      | Channel 128  | Channel 192  | Channel 251  |
|             |         | 824.2MHz     | 837.0MHz     | 848.8MHz     |
|             | RX      | Channel 128  | Channel 192  | Channel 251  |
|             |         | 869.2MHz     | 882.0MHz     | 893.8MHz     |
| TM3/TM4/TM5 | TX      | Channel 4132 | Channel 4182 | Channel 4233 |
|             |         | 826.4MHz     | 836.4MHz     | 846.6MHz     |
|             | RX      | Channel 4357 | Channel 4407 | Channel 4458 |
|             |         | 871.4MHz     | 881.4MHz     | 891.6MHz     |

### 5.2 Test Modes

| Test Mode | Test Modes Description    |
|-----------|---------------------------|
| TM1       | GSM/GPRS, GMSK modulation |
| TM2       | EDGE, 8PSK modulation     |
| TM3       | WCDMA, QPSK modulation    |
| TM4       | HSDPA, QPSK modulation    |
| TM5       | HSUPA, QPSK modulation    |

### 5.3 Test Environment

| Environment Parameter | Selected Values During Tests |         |
|-----------------------|------------------------------|---------|
| Relative Humidity     | Ambient                      |         |
| Temperature           | TN                           | Ambient |
| Voltage               | VL                           | 3.6V    |
|                       | VN                           | 3.7V    |
|                       | VH                           | 4.2V    |


NOTE: VL= lower extreme test voltage  
VN= nominal voltage  
VH= upper extreme test voltage  
TN= normal temperature

## 5.4 Test Setup


### 5.4.1 General Test Setup Configurations

| Configuration       | Description                                                                                                                                                                                                                                        |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Antenna Ports  | Until otherwise declared, all TX tests are ONLY performed at the main Transmitter antenna port (e.g. TRXA, TXA and so on) of the EUT, and all RX tests are ONLY performed at the main Receiver antenna port (e.g. TRXA, RXA and so on) of the EUT. |
| Multiple RF Sources | Other than the tested RF source of the EUT, other RF source(s) are disabled or shutdown during measurements.                                                                                                                                       |

### 5.4.2 Test Setup 1



### 5.4.3 Test Setup 2




#### 5.4.4 Test Setup 3

NOTE1: Effective radiated power (ERP) or Effective Isotropic radiated power (EIRP) refers to the EUT radiation power output, assuming all emissions are radiated from half-wave dipole antennas or horn antennas.

NOTE2: The EUT was set on insulator 80cm above the Ground Plane. The setup and test methods were according to ANSI-TIA-603C 2004. The measurements were carried through with a Rohde and Schwarz Test Receiver and control software.


#### Step 1: Pre-test to find the Maximum ERP or EIRP

1. Connect the test system according to the following figure. EUT is running for 30 minutes before test, and measurement instruments are warming-up for 30 minutes.
2. Set up communication link between Universal radio communication tester and EUT, set EUT working frequency, and control EUT to transmit at maximum power.
3. Set the center frequency of the signal analyzer or receiver to the EUT's operating frequency, the RBW is equal to the emission bandwidth of the signal. Set RMS detector for the test, and the span is equal to 2 times of emission bandwidth, the other settings should remain automatic. Normally, the height range of antenna was 1m to 4m, the azimuth range of turntable was 0° to 360°. The receiver antenna has two polarizations V and H. A portable or small unlicensed wireless device shall be placed on a non-metallic test fixture or other non-metallic support during testing. The supporting fixture shall permit orientation of the EUT in each of three orthogonal (x, y, z) axis positions such that emissions from the EUT are maximized. Measure the EUT maximum RF power and record the result.
4. Changing EUT working frequency and measuring the RF power at channel T, M, B respectively.  
Complete the test data.



## Step 2: Substitution method to verify the maximum ERP or EIRP

1. Measurement setup is according to the following figure. EUT was substituted by antenna, and the polarization is identical with the test antenna; the signal generator was connected to the substitution antenna.
2. The radiated output power, measured by signal analyzer set, is the same as recorded in above. Then this power level is matched by a signal from a calibrated signal generator which is substituted for EUT. The power supplied by the generator is then equal to the ERP or EIRP after corrected by the antenna gain and cable loss.



## 5.5 Test Conditions

| Test Case                              | Test Conditions    |                                                                                                                           |
|----------------------------------------|--------------------|---------------------------------------------------------------------------------------------------------------------------|
| Transmitter Output Power               | Test Configuration | Ambient Temperature & Rated Voltage                                                                                       |
|                                        | Test Setup         | Test Setup 1 & Test Setup 3                                                                                               |
|                                        | Detector           | RMS                                                                                                                       |
|                                        | RF Channels (TX)   | L, M, H                                                                                                                   |
|                                        | Test Mode          | TM1/TM2/TM3/TM4/TM5                                                                                                       |
| Modulation Characteristics             | Test Configuration | Ambient Temperature & Rated Voltage                                                                                       |
|                                        | Test Setup         | Test Setup 1                                                                                                              |
|                                        | RF Channels (TX)   | M                                                                                                                         |
|                                        | Test Mode          | TM1/TM2/TM3                                                                                                               |
| Occupied Bandwidth                     | Test Configuration | Ambient Temperature & Rated Voltage                                                                                       |
|                                        | Test Setup         | Test Setup 1                                                                                                              |
|                                        | Detector           | PK                                                                                                                        |
|                                        | RF Channels (TX)   | L, M, H                                                                                                                   |
|                                        | Test Mode          | TM1/TM2/TM3                                                                                                               |
| Band Edges Compliance                  | Test Configuration | Ambient Temperature & Rated Voltage                                                                                       |
|                                        | Test Setup         | Test Setup 1                                                                                                              |
|                                        | Detector           | RMS                                                                                                                       |
|                                        | RF Channels (TX)   | L, H                                                                                                                      |
|                                        | Test Mode          | TM1/TM2/TM3                                                                                                               |
| Spurious Emission at Antenna Terminals | Test Configuration | Ambient Temperature & Rated Voltage                                                                                       |
|                                        | Test Setup         | Test Setup 1                                                                                                              |
|                                        | Detector           | PK                                                                                                                        |
|                                        | RF Channels (TX)   | L, M, H                                                                                                                   |
|                                        | Test Mode          | TM1/TM2/TM3                                                                                                               |
| Field Strength of Spurious Radiation   | Test Configuration | Ambient Temperature & Rated Voltage                                                                                       |
|                                        | Test Setup         | Test Setup 3                                                                                                              |
|                                        | Detector           | PK                                                                                                                        |
|                                        | RF Channels (TX)   | M                                                                                                                         |
|                                        | Test Mode          | TM1/TM2/TM3/TM4/TM5                                                                                                       |
| Frequency Stability                    | Test Configuration | (1) -30 °C to +50 °C with step 10 °C at Rated Voltage;<br>(2) 85%, 100% and 115% of Rated Voltage at Ambient Temperature. |
|                                        | Test Setup         | Test Setup 2                                                                                                              |
|                                        | RF Channels (TX)   | M                                                                                                                         |





| Test Case | Test Conditions |             |
|-----------|-----------------|-------------|
|           | Test Mode       | TM1/TM2/TM3 |

## 6 Main Test Instruments

Table 3 Main Test Equipments

| Equipment Description                | Manufacturer | Model                   | Serial Number | Calibrated until |
|--------------------------------------|--------------|-------------------------|---------------|------------------|
| Power supply                         | KEITHLEY     | 2303                    | 1288003       | Sept., 27, 2012  |
| Universal Radio Communication Tester | R&S          | CMU200                  | 105822        | Oct., 24, 2012   |
| Wireless Communication Test set      | Agilent      | N4010A                  | MY49081592    | Dec., 14, 2012   |
| Universal Radio Communication Tester | Agilent      | E5515C                  | MY50260239    | Aug., 31, 2013   |
| Spectrum Analyzer                    | Agilent      | E4440A                  | MY49420179    | Apr., 20, 2013   |
| Signal Analyzer                      | R&S          | FSQ31                   | 200021        | Sept., 27, 2012  |
| Temperature Chamber                  | WEISS        | WKL64                   | 24600294      | Jan., 03, 2013   |
| Signal generator                     | Agilent      | E8257D                  | MY49281095    | Jul., 09, 2013   |
| Vector Signal Generator              | R&S          | SMU200A                 | 104162        | Sept., 07, 2012  |
| Test receiver                        | R&S          | ESU26                   | 100150        | May., 24, 2013   |
| Tunable Dipole                       | Schwarzbeck  | D69250-UHAP/D69250-VHAP | 919/1009      | Dec., 13, 2012   |
| Tunable Dipole                       | Schwarzbeck  | D69250-UHAP/D69250-VHAP | 979/917       | Dec., 13, 2012   |
| Horn Antenna                         | R & S        | HF906                   | 100683        | May., 16, 2013   |
| Horn Antenna                         | R & S        | HF906                   | 100684        | May., 16, 2013   |
| Broadband Antenna                    | Schwarzbeck  | VULB 9163               | 9163-357      | Sep., 15, 2012   |
| Broadband Antenna                    | Schwarzbeck  | VULB 9163               | 9163-356      | Sep., 15, 2012   |

NOTE: All the test equipment are calibrated once a year.

## 7 Test Results

| No. | Test Item                              | Test Result |
|-----|----------------------------------------|-------------|
| 1   | Transmitter Output Power               | Appendix A  |
| 2   | Modulation Characteristics             | Appendix B  |
| 3   | Occupied Bandwidth                     | Appendix C  |
| 4   | Band Edges Compliance                  | Appendix D  |
| 5   | Spurious Emission at Antenna Terminals | Appendix E  |
| 6   | Radiated spurious emission             | Appendix F  |
| 7   | Frequency Stability                    | Appendix G  |
| 8   | Photos of Radiated spurious emission   | Appendix H  |

NOTE: There is no test data in Appendix H, only Photos of Test Setup for Field Strength of Spurious Radiation.

## 8 Measurement Uncertainty

For a 95% confidence level ( $k=2$ ), the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 as following:

| Test Item                            |                          | Extended Uncertainty                               |
|--------------------------------------|--------------------------|----------------------------------------------------|
| Transmitter Output Power             | Power (dBm)              | U =0.39 dB                                         |
| Occupied Bandwidth                   | Magnitude (%)            | U=0.2%                                             |
| Band Edge Compliance                 | Disturbance Power (dBm)  | U=2.0 dB                                           |
| Conducted Spurious Emissions         | Disturbance Power (dBm)  | U=2.0 dB                                           |
| Field Strength of Spurious Radiation | ERP (dBm)                | U=4.6 dB (30 MHz – 1GHz)<br>U=3.0 dB (above 1 GHz) |
| Frequency Stability                  | Frequency Accuracy (ppm) | U=0.21 ppm                                         |

-----The END-----



## **Appendix A**

# Transmitter Output Power

According to FCC Part 2.1046 & Part 22.913



## Conducted Power of Transmitter

|                     |       | RF Output Power (Conducted) |       |                |       |                |       |
|---------------------|-------|-----------------------------|-------|----------------|-------|----------------|-------|
| TEST CONDITIONS     |       | Channel128(L)               |       | Channel192(M)  |       | Channel251(H)  |       |
|                     |       | 824.2MHz                    |       | 837.0MHz       |       | 848.8MHz       |       |
|                     |       | dBm                         |       | dBm            |       | dBm            |       |
| $T_{nom} / V_{nom}$ |       | Measured                    | Limit | Measured       | Limit | Measured       | Limit |
| TM1                 |       | 32.85                       | 38.5  | 32.92          | 38.5  | 32.92          | 38.5  |
| TM2                 |       | 26.16                       | 38.5  | 26.02          | 38.5  | 25.95          | 38.5  |
| TEST CONDITIONS     |       | Channel4132(L)              |       | Channel4182(M) |       | Channel4233(H) |       |
|                     |       | 826.4MHz                    |       | 836.4MHz       |       | 846.6MHz       |       |
|                     |       | dBm                         |       | dBm            |       | dBm            |       |
| $T_{nom} / V_{nom}$ |       | Measured                    | Limit | Measured       | Limit | Measured       | Limit |
| TM3                 |       | 22.67                       | 38.5  | 22.76          | 38.5  | 22.52          | 38.5  |
| TM4                 | Case1 | 22.69                       | 38.5  | 22.72          | 38.5  | 22.54          | 38.5  |
|                     | Case2 | 22.56                       | 38.5  | 22.64          | 38.5  | 22.55          | 38.5  |
|                     | Case3 | 22.24                       | 38.5  | 22.36          | 38.5  | 22.24          | 38.5  |
|                     | Case4 | 22.32                       | 38.5  | 22.29          | 38.5  | 22.18          | 38.5  |
| TM5                 | Case1 | 21.33                       | 38.5  | 21.29          | 38.5  | 21.24          | 38.5  |
|                     | Case2 | 20.47                       | 38.5  | 20.49          | 38.5  | 20.41          | 38.5  |
|                     | Case3 | 20.38                       | 38.5  | 20.40          | 38.5  | 20.29          | 38.5  |
|                     | Case4 | 20.20                       | 38.5  | 20.28          | 38.5  | 20.11          | 38.5  |
|                     | Case5 | 21.36                       | 38.5  | 21.40          | 38.5  | 21.27          | 38.5  |



## Effective Radiated Power of Transmitter (ERP)

| Test Mode | Freq. [MHz] | Meas. Level [dBm] | Substitution Antenna Type | SGP [dBm] | Substitution Gain [dBd] | Cable Loss [dB] | Substitution Level (ERP) | FCC limit [dBm] | Result |
|-----------|-------------|-------------------|---------------------------|-----------|-------------------------|-----------------|--------------------------|-----------------|--------|
|           |             |                   |                           |           |                         |                 | [dBm]                    |                 |        |
| TM1       | 824.2       | 32.72             | Dipole Ant.               | 36.10     | -2.75                   | 0.6             | 32.75                    | 38.5            | Pass   |
| TM1       | 837.0       | 32.79             | Dipole Ant.               | 36.25     | -2.87                   | 0.6             | 32.78                    | 38.5            | Pass   |
| TM1       | 848.8       | 32.79             | Dipole Ant.               | 36.21     | -2.85                   | 0.6             | 32.76                    | 38.5            | Pass   |
| TM2       | 824.2       | 26.03             | Dipole Ant.               | 29.40     | -2.75                   | 0.6             | 26.05                    | 38.5            | Pass   |
| TM2       | 837.0       | 25.89             | Dipole Ant.               | 29.35     | -2.87                   | 0.6             | 25.88                    | 38.5            | Pass   |
| TM2       | 848.8       | 25.82             | Dipole Ant.               | 29.31     | -2.85                   | 0.6             | 25.86                    | 38.5            | Pass   |
| TM3       | 826.4       | 22.54             | Dipole Ant.               | 25.86     | -2.75                   | 0.6             | 22.51                    | 38.5            | Pass   |
| TM3       | 836.4       | 22.63             | Dipole Ant.               | 26.07     | -2.87                   | 0.6             | 22.60                    | 38.5            | Pass   |
| TM3       | 846.6       | 22.39             | Dipole Ant.               | 25.83     | -2.85                   | 0.6             | 22.38                    | 38.5            | Pass   |

Note: a, For getting the ERP (Efficient Radiated Power) in substitution method, the following formula should be taken to calculate it,

$$\text{ERP [dBm]} = \text{SGP [dBm]} - \text{Cable Loss [dB]} + \text{Gain [dBd]}$$

b, SGP=Signal Generator Level

-----The END-----




## **Appendix B**

# Modulation Characteristics

According to FCC Part 2.1047 & Part22 Subpart H




## Channel 192 (TM1:GPRS/GSM)








## Channel 192 (TM2:EDGE)





## Channel 4182 (TM3: WCDMA)



-----The END-----



## Appendix C

### Occupied Bandwidth According to FCC Part 2.1049 & Part 22 Subpart H




## Result Table

Table 1 Measurement Results

| Test Mode | RF Channel | Occupied Bandwidth [kHz] | Verdict |
|-----------|------------|--------------------------|---------|
| TM1       | 128        | 254.81                   | Pass    |
|           | 192        | 251.60                   | Pass    |
|           | 251        | 245.19                   | Pass    |
| TM2       | 128        | 250.00                   | Pass    |
|           | 192        | 245.19                   | Pass    |
|           | 251        | 253.21                   | Pass    |
| Test Mode | RF Channel | Occupied Bandwidth [MHz] | Verdict |
| TM3       | 4132       | 4.18                     | Pass    |
|           | 4182       | 4.18                     | Pass    |
|           | 4233       | 4.15                     | Pass    |




## Channel 128 (TM1:GPRS/GSM)



Date: 2.AUG.2012 12:19:31




## Channel 128 (TM2:EDGE)



Date: 2.AUG.2012 12:26:06




## Channel 4132 (TM3: WCDMA)



Date: 2.AUG.2012 12:31:27



## Channel 192 (TM1:GPRS/GSM)




Date: 2.AUG.2012 12:19:45






## Channel 192 (TM2:EDGE)



Date: 2.AUG.2012 12:26:20




## Channel 4182 (TM3: WCDMA)



Date: 2.AUG.2012 12:31:41




## Channel 251 (TM1:GPRS/GSM)



Date: 2.AUG.2012 12:19:59




## Channel 251 (TM2:EDGE)



Date: 2.AUG.2012 12:26:34



## Channel 4233 (TM3: WCDMA)



Date: 2.AUG.2012 12:31:54

The END



## **Appendix D**

### **Band Edges Compliance**


According to FCC Part 2.1051 & Part 22 Subpart H



# TM1:GPRS/GSM

## Left Edge


### Channel 128



Date: 2.AUG.2012 15:04:47



## Right Edge Channel 251




Date: 2.AUG.2012 15:05:41






## TM2:EDGE Left Edge Channel 128



Date: 2.AUG.2012 12:25:39



## Right Edge Channel 251




Date: 2.AUG.2012 12:25:52



## TM3: WCDMA

### Left Edge


### Channel 4132



Date: 2.AUG.2012 12:32:09



## Right Edge Channel 4233



Date: 2.AUG.2012 12:32:22

The END




## **Appendix E**

# Spurious Emission at Antenna Terminal


According to FCC Part 2.1051 & Part 22 Subpart H




## TM1:GPRS/GSM Channel 128



Date: 2.AUG.2012 12:20:13




Date: 2.AUG.2012 12:20:57



Ref 35 dB Att 45 dB SWT 100 ms 825.897435897 MHz









Date: 2.AUG.2012 12:22:25




## Channel 192




Date: 2.AUG.2012 12:20:28



Date: 2.AUG.2012 12:21:12




Date: 2.AUG.2012 12:21:55




Date: 2.AUG.2012 12:22:39




## Channel 251



Date: 2.AUG.2012 12:20:42




Date: 2.AUG.2012 12:21:26



Date: 2.AUG.2012 12:22:10







Date: 2.AUG.2012 12:22:54




## TM2:EDGE Channel 128



Date: 2.AUG.2012 14:19:22




Date: 2.AUG.2012 14:20:07



Ref 35 dB Att 45 dB SWT 100 ms 825.897435897 MHz







Date: 2.AUG.2012 14:21:34




## Channel 192



Date: 2.AUG.2012 14:19:38



Date: 2.AUG.2012 14:20:21




Date: 2.AUG.2012 14:21:05





1 PK  
MAXH


\*RBW 1 MHz      Marker 1 [T1 ]  
\*VBW 3 MHz      -16.45 dBm  
SWT 70 ms      2.619391026 GHz




Date: 2.AUG.2012 14:21:49




## Channel 251




Date: 2.AUG.2012 14:19:52




Date: 2.AUG.2012 14:20:36



Ref 35 dB Att 45 dB SWT 100 ms 849.214743590 MHz







Date: 2.AUG.2012 14:22:03




## TM3: WCDMA Channel 4132



Date: 2.AUG.2012 12:32:37




Date: 2.AUG.2012 12:33:21



Date: 2.AUG.2012 12:34:04







Date: 2.AUG.2012 12:34:48




## Channel 4182



Date: 2.AUG.2012 12:32:51



Date: 2.AUG.2012 12:33:35



Date: 2.AUG.2012 12:34:19




Ref 35 dB Att 45 dB SWT 70 ms 2.770032051 GHz





## Channel 4233




Date: 2.AUG.2012 12:33:06




1 PK  
MAXH


\*RBW 10 kHz      Marker 1 [T1 ]  
\*VBW 30 kHz      -32.21 dBm  
SWT 300 ms      197.836538462 kHz




Date: 2.AUG.2012 12:33:49



Ref 35 dB Att 45 dB SWT 100 ms 846.105769231 MHz







Date: 2.AUG.2012 12:35:17

The END

## **Appendix F**


# Radiated spurious emission

According to FCC Part 2.1053 & Part22.917


Note: 1. Simultaneous transmission was investigated and no new emissions were found.  
2. RBW  $\geq$  1MHz, VBW  $>$  3 x RBW.

## GPRS 850


Traffic Mode (9kHz-30MHz)



Traffic Mode (30MHz-3GHz)




## Traffic Mode (3GHz-18GHz)




## EDGE 850


### Traffic Mode (9kHz-30MHz)



## Traffic Mode (30MHz-3GHz)




## Traffic Mode (3GHz-18GHz)




## WCDMA Band V


Traffic Mode (9kHz-30MHz)



Traffic Mode (30MHz-3GHz)




## Traffic Mode (3GHz-18GHz)




## HSDPA Band V

### Traffic Mode (9kHz-30MHz)






## Traffic Mode (30MHz-3GHz)




## Traffic Mode (3GHz-18GHz)




## HSUPA Band V


Traffic Mode (9kHz-30MHz)



Traffic Mode (30MHz-3GHz)



## Traffic Mode (3GHz-18GHz)



The END



## **Appendix G**

### **Frequency Stability**

According to FCC Part 2.1055 & Part 22.355



## Frequency Error vs. Temperature:

| Test Mode | RF Ch. | Volt. | Temp.  | Freq. Error [Hz] | Freq. vs. rated [ppm] | Freq. vs. 20 °C [ppm] | Limit [ppm] | Verdict |
|-----------|--------|-------|--------|------------------|-----------------------|-----------------------|-------------|---------|
| TM 1      | M      | VN    | -30 °C | 11               | 0.01314               | ---                   | ±2.5        | Pass    |
|           |        |       | -20 °C | -18              | -0.02151              | ---                   | ±2.5        | Pass    |
|           |        |       | -10 °C | -23              | -0.02748              | ---                   | ±2.5        | Pass    |
|           |        |       | 0 °C   | 13               | 0.01553               | ---                   | ±2.5        | Pass    |
|           |        |       | 10 °C  | -6               | -0.00717              | ---                   | ±2.5        | Pass    |
|           |        |       | 20 °C  | -17              | -0.02031              | ---                   | ±2.5        | Pass    |
|           |        |       | 30 °C  | -24              | -0.02867              | ---                   | ±2.5        | Pass    |
|           |        |       | 40 °C  | -23              | -0.02748              | ---                   | ±2.5        | Pass    |
|           |        |       | 50 °C  | 12               | 0.01434               | ---                   | ±2.5        | Pass    |
| TM 2      | M      | VN    | -30 °C | -9               | -0.01075              | ---                   | ±2.5        | Pass    |
|           |        |       | -20 °C | 19               | 0.02270               | ---                   | ±2.5        | Pass    |
|           |        |       | -10 °C | -23              | -0.02748              | ---                   | ±2.5        | Pass    |
|           |        |       | 0 °C   | -15              | -0.01792              | ---                   | ±2.5        | Pass    |
|           |        |       | 10 °C  | 29               | 0.03465               | ---                   | ±2.5        | Pass    |
|           |        |       | 20 °C  | -14              | -0.01673              | ---                   | ±2.5        | Pass    |
|           |        |       | 30 °C  | -18              | -0.02151              | ---                   | ±2.5        | Pass    |
|           |        |       | 40 °C  | 28               | 0.03345               | ---                   | ±2.5        | Pass    |
|           |        |       | 50 °C  | 15               | 0.01792               | ---                   | ±2.5        | Pass    |
| TM 3      | M      | VN    | -30 °C | 26               | 0.03106               | ---                   | ±2.5        | Pass    |
|           |        |       | -20 °C | -9               | -0.01075              | ---                   | ±2.5        | Pass    |
|           |        |       | -10 °C | -14              | -0.01673              | ---                   | ±2.5        | Pass    |
|           |        |       | 0 °C   | 21               | 0.02509               | ---                   | ±2.5        | Pass    |
|           |        |       | 10 °C  | -18              | -0.02151              | ---                   | ±2.5        | Pass    |
|           |        |       | 20 °C  | -11              | -0.01314              | ---                   | ±2.5        | Pass    |
|           |        |       | 30 °C  | -23              | -0.02748              | ---                   | ±2.5        | Pass    |
|           |        |       | 40 °C  | 11               | 0.01314               | ---                   | ±2.5        | Pass    |
|           |        |       | 50 °C  | -23              | -0.02748              | ---                   | ±2.5        | Pass    |



## Frequency Error vs. Voltage:

| Test Mode | RF Ch. | Temp. | Volt. | Freq. Error [Hz] | Freq. vs. rated [ppm] | Freq. vs. 20 °C [ppm] | Limit [ppm] | Verdict |
|-----------|--------|-------|-------|------------------|-----------------------|-----------------------|-------------|---------|
| TM 1      | M      | TN    | VL    | -24              | -0.02867              | ---                   | ±2.5        | Pass    |
|           |        |       | VN    | -17              | -0.02031              | ---                   | ±2.5        | Pass    |
|           |        |       | VH    | 27               | 0.03226               | ---                   | ±2.5        | Pass    |
| TM 2      | M      | TN    | VL    | -9               | -0.01075              | ---                   | ±2.5        | Pass    |
|           |        |       | VN    | -24              | -0.02867              | ---                   | ±2.5        | Pass    |
|           |        |       | VH    | 29               | 0.03465               | ---                   | ±2.5        | Pass    |
| TM 3      | M      | TN    | VL    | 23               | 0.02748               | ---                   | ±2.5        | Pass    |
|           |        |       | VN    | -18              | -0.02151              | ---                   | ±2.5        | Pass    |
|           |        |       | VH    | -14              | -0.01673              | ---                   | ±2.5        | Pass    |

-----The END-----  
---