



Appendix for Test report

Appendix A: DTS (6 dB) Bandwidth

In this document, the "DTS6dBBW" refers to the measured "DTS (6 dB) Bandwidth" value. In this Appendix, the "fc(DTS6dBBW)" refers to the centre of the measured "DTS6dBBW". The introduction of the "fc(DTS6dBBW)" is due to that other measurements use it as the spectrum analyzer setting.


For measurements on smart antenna systems (devices with multiple transmit chains), the test is performed at each chain, and used as respective results for each chain.

Part I - Test Results

Test Mode	Test Channel	Frequency[MHz]	Ant	DTS6dBBW[MHz]	Verdict
11B	L	2412	Ant 1	9.07	pass
11B	M	2437	Ant 1	8.36	pass
11B	H	2462	Ant 1	8.76	pass
11G	L	2412	Ant 1	16.56	pass
11G	M	2437	Ant 1	16.50	pass
11G	H	2462	Ant 1	16.53	pass
11N20	L	2412	Ant 1	17.75	pass
11N20	M	2437	Ant 1	17.73	pass
11N20	H	2462	Ant 1	17.74	pass


Part II - Test Plots

2.1 11B L






2.2 11B_M






2.3 11B_H




2.4 11G_L






2.5 11G_M







2.6 11G_H



2.7 11N20_L




2.8 11N20_M





2.9 11N20_H




Appendix B: Maximum Peak Conducted Output Power

Part I - Test Results

Test Mode	Test Channel	Frequency[MHz]	Meas. Level (Cond.) [dBm]	Verdict
11B	L	2412	20.24	pass
11B	M	2437	20.63	pass
11B	H	2462	20.83	pass
11G	L	2412	21.01	pass
11G	M	2437	21.68	pass
11G	H	2462	21.77	pass
11N20	L	2412	19.82	pass
11N20	M	2437	20.55	pass
11N20	H	2462	20.71	pass

Part II - Test Plots


2.1 11B_L



2.1 11B_M



* RBW 1 MHz
* VBW 3 MHz
* SWT 1 s




2.1


11B_H



1 PK
MAX



2.1 11G_L




2.1 11G_M




* RBW 1 MHz
* VBW 3 MHz
* SWT 1 s

1 PK
MAX




2.1 11G_H



2.1 11N20_L




1 PK
MAX




2.1 11N20_M



* RBW 1 MHz
* VBW 3 MHz
* SWT 1 s



2.1 1120_H




Appendix C: Maximum Power Spectral Density Level

Part I - Test Results


Test Mode	Test Channel	Frequency[MHz]	Ant	PD[MHz]	Verdict
11B	L	2412	Ant 1	-3.55	pass
11B	M	2437	Ant 1	-2.69	pass
11B	H	2462	Ant 1	-2.29	pass
11G	L	2412	Ant 1	-7.44	pass
11G	M	2437	Ant 1	-6.88	pass
11G	H	2462	Ant 1	-7.00	pass
11N20	L	2412	Ant 1	-7.67	pass
11N20	M	2437	Ant 1	-7.55	pass
11N20	H	2462	Ant 1	-7.49	pass

Part II - Test Plots


2.1 11B_L




2.3 11B_M




2.5 11B_H




2.7 11G_L




2.9 11G_M




2.11 11G_H



2.13 11N20_L




2.15 11N20_M





2.17 11N20_H




Appendix D: Band Edges Compliance

Part I - Test Results


Test Mode	Test Channel	Frequency[MHz]	Ant	Carrier Power[dBm]	Max.Spurious Level[dBm]	Verdict
11B	L	2412	Ant 1	4.23	-45.85	pass
11B	H	2462	Ant 1	5.96	-51.65	pass
11G	L	2412	Ant 1	.94	-38.28	pass
11G	H	2462	Ant 1	1.68	-41.78	pass
11N20	L	2412	Ant 1	-.15	-39.64	pass
11N20	H	2462	Ant 1	.60	-47.14	pass

Part II - Test Plots

2.1 11B_L




2.3 11B_H






2.5 11G_L






2.7 11G_H






2.9 11N20_L





2.11 11N20_H



Appendix E: Unwanted Emissions into Non-Restricted Frequency

Bands

In this Appendix, the "Pref", which is used as the reference level, refers to the peak power level in any 100 kHz bandwidth within the fundamental emission, the "Puw" refers to the maximum emission power in 100 kHz band segments outside of the authorized frequency band.

Considering that the higher ratio of RBW to the span for the frequency ranges below 30 MHz makes the results determination be complicated, a narrower RBW other than 100 kHz is used for these ranges. The measured value should add a RBW correction factor (RBWCF) where $RBWCF [dB] = 10 \times \lg(100 [kHz]/\text{narrower RBW [kHz]})$. As to this Appendix, the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

For measurements on smart antenna systems (devices with multiple transmit chains), the test is performed at each chain and used as respective results for each chain, due to the relative-limit requirement.

In the result table, the "< Limit" denotes that "The Puw [dBm] is less than Pref[dBm]-20[dBm], see test plots for detailed".


Part I - Test Results

Test Mode	Test Channel	Frequency[MHz]	Ant	Pref[dBm]	Puw[dBm]	Verdict
11B	L	2412	Ant 1	5.96	<limit	pass
11B	M	2437	Ant 1	5.79	<limit	pass
11B	H	2462	Ant 1	6.14	<limit	pass
11G	L	2412	Ant 1	1.06	<limit	pass
11G	M	2437	Ant 1	1.45	<limit	pass
11G	H	2462	Ant 1	1.78	<limit	pass
11N20	L	2412	Ant 1	0.00	<limit	pass
11N20	M	2437	Ant 1	0.43	<limit	pass
11N20	H	2462	Ant 1	0.72	<limit	pass

Part II - Test Plots


2.1 11B_L


Pref:








Puw:
















2.3 11B_M


Pref:








Puw:
















2.5 11B_H


Pref:








Puw:
















2.7 11G_L


Pref:








Puw:
















2.9 11G_M


Pref:








Puw:

















2.11 11G_H


Pref:





Puw:
















2.13 11N20_L


Pref:








Puw:
















2.15 11N20_M


Pref:








Puw:



















Pref:








Puw:














Appendix F: Radiated Spurious Emission & Spurious in Restricted Band

Note: Below 1GHz, RBW = 100 kHz, VBW = 300 kHz.


Above 1GHz, RBW = 1 MHz, VBW = 3 MHz.

The simultaneous transmission has been considered

Part 1: Testing Range of “30 MHz to 1 GHz”

Note 1: The test results and plot for testing range of “30 MHz to 1 GHz” showed as below is **the WORST case for all Test Modes and Channels**. This range will not be presented for each Test Mode and each Channel.


Note 2: **The emissions in this range are mainly from the Platform Device (Notepad PC and its ancillary components).**



Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Height cm	Azimuth deg	Plarization
32.020800	27.1	14.1	40.0	12.9	100.0	295.0	VERTICAL
53.569920	31.7	14.7	40.0	8.3	400.0	176.0	HORIZONTAL
94.384960	29.9	12.7	43.5	13.6	386.0	307.0	HORIZONTAL
160.014400	27.9	10.8	43.5	15.6	114.0	96.0	VERTICA
400.027200	34.1	18.0	46.0	11.9	400.0	258.0	VERTICA
500.039040	38.8	19.8	46.0	7.2	187.0	102.0	HORIZONTAL

Part 2: Testing Range of “18 GHz to 26.5 GHz”

Note: No peak found in pre- test.




Part 3: Testing Range of “2.3GHz to 2.5GHz”

- Note 1: The testing range of “2.3 GHz to 2.5 GHz” is for checking radiated emissions located in restricted bands near the EUT operating bands.
- Note 2: Two limits are required in the testing range above 1 GHz, that is Peak limit (74 dB μ V/m) and Average Limit (54 dB μ V/m).
- Note 3: The peak spike exceeds the limit line is EUT’s operating frequency.

Test Mode: 11b- 1M-ANT0-CH1

Channel 1



Note: The peak exceeds the limit line is carrier frequency.

MEASUREMENT RESULT: PK Detector


Frequency MHz	Level dB μ V/m	Transd dB	Limit dB μ V/m	Margin dB	Height cm	Azimuth deg	Polarization
2390.000000	66.3	38.3	74.0	7.7	127.0	-17.0	HORIZONTAL
2483.500000	58.8	40.9	74.0	15.2	100.0	230.0	VERTICA

MEASUREMENT RESULT: AV Detector

Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Height cm	Azimuth deg	Polarization
2390.000000	43.1	38.3	54.0	10.9	100.0	197.0	HORIZONTAL
2483.500000	45.1	40.9	54.0	8.9	100.0	190.0	VERTICA

Test Mode: 11b- 1M-ANT0-ch11

Channel 11



Note: The peak exceeds the limit line is carrier frequency.

MEASUREMENT RESULT: PK Detector

Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Height cm	Azimuth deg	Polarization
2390.000000	56.5	38.3	74.0	17.5	113.0	9.0	HORIZONTAL
2483.500000	58.0	40.4	74.0	16.0	100.0	273.0	VERTICA


MEASUREMENT RESULT: AV Detector

Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Height cm	Azimuth deg	Polarization
------------------	-----------------	--------------	-----------------	--------------	--------------	----------------	--------------

2390.000000	43.1	38.3	54.0	10.9	100.0	0.0	HORIZONTAL
2483.500000	45.2	40.4	54.0	8.8	100.0	0.0	HORIZONTAL

Test Mode: 11g 6M-ANT0-CH1

Channel 1



Note: The peak exceeds the limit line is carrier frequency.

MEASUREMENT RESULT: PK Detector


Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Height cm	Azimuth deg	Polarization
2390.000000	65.8	38.3	74.0	8.2	100.0	207.0	HORIZONTAL
2483.500000	58.5	40.6	74.0	15.5	100.0	-32.0	HORIZONTAL

MEASUREMENT RESULT: AV Detector

Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Height cm	Azimuth deg	Polarization
2390.000000	46.5	38.3	54.0	7.5	100.0	199.0	HORIZONTAL
2483.500000	45.0	40.6	54.0	9.0	100.0	158.0	VERTICA

Test Mode: 11g- 6M-ANT0-CH11

Channel 11



Note: The peak exceeds the limit line is carrier frequency.

MEASUREMENT RESULT: PK Detector

Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Height cm	Azimuth deg	Polarization
2390.000000	57.4	38.3	74.0	16.6	114.0	25.0	HORIZONTAL
2483.500000	65.9	40.6	74.0	8.1	113.0	55.0	HORIZONTAL


MEASUREMENT RESULT: AV Detector

Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Height cm	Azimuth deg	Polarization
------------------	-----------------	--------------	-----------------	--------------	--------------	----------------	--------------

2390.000000	43.2	38.3	54.0	10.8	100.0	70.0	HORIZONTAL
2483.500000	46.8	40.6	54.0	7.2	100.0	55.0	HORIZONTAL

Test Mode: 11N20-CH1-ANT0-MSC06.5M

Channel 1



Note: The peak exceeds the limit line is carrier frequency.

MEASUREMENT RESULT: PK Detector


Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Height cm	Azimuth deg	Polarization
2390.000000	63.7	38.3	74.0	10.3	100.0	178.0	HORIZONTAL
2483.500000	60.1	41.8	74.0	13.9	100.0	35.0	VERTICA

MEASUREMENT RESULT: AV Detector

Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Height cm	Azimuth deg	Polarization
2390.000000	45.1	38.3	54.0	8.9	100.0	170.0	HORIZONTAL
2483.500000	46.1	41.8	54.0	7.9	100.0	80.0	HORIZONTAL

Test Mode: 11N20-CH11-ANT0-MSC06.5M

Channel 11



Note: The peak exceeds the limit line is carrier frequency.

MEASUREMENT RESULT: PK Detector

Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Height cm	Azimuth deg	Polarization
2390.000000	57.0	38.3	74.0	17.0	113.0	33.0	HORIZONTAL
2483.500000	66.1	41.0	74.0	7.9	100.0	172.0	HORIZONTAL


MEASUREMENT RESULT: AV Detector

Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Height cm	Azimuth deg	Polarization
2390.000000	43.2	38.3	54.0	10.8	100.0	38.3	VERTICA
2483.500000	46.1	41.0	54.0	7.9	100.0	40.9	HORIZONTAL

Part 4: Testing Range of “1 GHz to 18 GHz”

- Note 1: The test results and plot for testing range of “1 GHz to 18 GHz” showed as below is **the WORST case for all Test Modes and Channels**. This range will not be presented for each Test Mode and each Channel.
- Note 2: The testing range of “1 GHz to 18 GHz” is for checking radiated emissions located in restricted bands faraway from the EUT operating bands.
- Note 3: Two limits are required in the testing range above 1 GHz, that is Peak limit (74 dB μ V/m) and Average Limit (54 dB μ V/m).


FCC CLASS B RE 1GHz-18GHz



Appendix G: Conducted Emission at Power Port

Note: RBW = 9 kHz, VBW = 30 kHz

Channel 6



MEASUREMENT RESULT: QP Detector

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.208479	38.9	9.7	63.3	24.4	N	FLO
0.570506	31.0	9.7	56.0	25.0	L1	FLO
1.435069	37.6	9.7	56.0	18.4	L1	FLO
3.602164	34.9	9.8	56.0	21.1	L1	FLO
5.358150	39.1	9.8	60.0	20.9	L1	FLO
15.970714	36.5	10.0	60.0	23.5	L1	FLO

MEASUREMENT RESULT: AV Detector

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.186219	34.7	9.7	54.2	19.5	L1	FLO
0.333322	31.0	9.7	49.4	18.4	L1	FLO
0.516547	39.0	9.7	46.0	7.0	L1	FLO
1.416199	34.3	9.7	46.0	11.7	L1	FLO
3.549622	30.6	9.8	46.0	15.4	L1	FLO
15.966975	39.6	10.0	50.0	10.4	L1	FLO

END