



# EMC Test Report

**Product Name: Smart Phone**

**Model Number: STK-LX3**

**Report No: SYBH(Z-EMC)20190309001001-2**

**FCC ID: QISSTK-LX3**

**Reliability Laboratory of Huawei Technologies Co., Ltd.**

**(Global Compliance and Testing Center of Huawei Technologies Co., Ltd)**

No.2, New City Avenue, Songshan Lake Sci. & Tech. Industry Park, Dongguan, 523808, P.R.C

Tel: +86 769 23830808 Fax: +86 769 23837628



## Notice

1. The laboratory has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS), and accreditation number: L0310.
2. The laboratory has passed the accreditation by The American Association for Laboratory Accreditation (A2LA). The accreditation number is 2174.01
3. The laboratory has been recognized by the Innovation, Science and Economic Development Canada (ISED) to test to Canadian radio equipment requirements. The CAB identifier is CN0003, and the ISED# is 21741.
4. The laboratory (Reliability Lab of Huawei Technologies Co., Ltd) is also named as “Global Compliance and Testing Center of Huawei Technologies Co., Ltd”, the both names have coexisted since 2009.
5. The laboratory has been recognized by the US Federal Communications Commission (FCC) to perform compliance testing subject to the Commission's Certification rules. The Designation Number is CN1173, and the Test Firm Registration Number is 294140.
6. The test report is invalid if not marked with the stamps or the signatures of the persons responsible for performing, revising and approving the test report.
7. The test report is invalid if there is any evidence of erasure and/or falsification.
8. If there is any dissidence for the test report, please file objection to the test centre within 15 days from the date of receiving the test report.
9. Normally, the test report is only responsible for the samples that have undergone the test.
10. Context of the test report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of the laboratory.
11. If any question about this report, please contact the laboratory(PublicGCTC@huawei.com).



**Applicant:** Huawei Technologies Co., Ltd.  
**Address:** No.2 New City Avenue Songshan Lake Sci. &Tech.  
Industry Park, Dongguan, Guangdong, P.R.C

**Date of Receipt Test Item:** 2019-03-20  
**Start Date of Test:** 2019-03-25  
**End Date of Test:** 2019-04-05

**Test Result:** Pass

**Approved By (Lab Manager)**      2019-04-08      He Hao      He Hao  
Date      Name      Signature

**Prepared by (Test Engineer)**      2019-04-07      Chang Lina      Chang Lina  
Date      Name      Signature



**Modification Record**

No.	Last Report No.	Modification Description
1	NA	First Report.




## TABLE OF CONTENT

1	General Information.....	6
1.1	EUT Description .....	6
1.2	Test Site Information.....	9
1.3	Applied Standards.....	9
2	Summary of Results .....	10
3	System Configuration during EMC Test .....	11
3.1	Test Mode .....	11
3.2	Test System Configuration .....	12
3.3	Cables Used during Test.....	14
3.4	Associated Equipment Used during Test .....	14
4	Electromagnetic Interference (EMI) .....	15
4.1	Radiated Disturbance 30MHz to 18GHz.....	15
4.2	Conducted Disturbance 0.15 MHz to 30MHz.....	17
5	Main Test Instruments .....	18
6	System Measurement Uncertainty .....	18
7	Test Data and Graph.....	19
7.1	Radiated Disturbance.....	19
7.2	Conducted Disturbance.....	21










## 1 General Information



### 1.1 EUT Description

EUT Description	
Product Name	Smart Phone
Model Number	STK-LX3
Input voltage	3.82V
TX Frequency	GSM 850: 824MHz to 849MHz PCS 1900:1850MHz to 1910MHz WCDMA Band II: 1850MHz to 1910MHz WCDMA Band IV: 1710MHz to 1755MHz WCDMA Band V: 824MHz to 849MHz LTE BAND 2: 1850MHz to 1910MHz LTE BAND 4: 1710MHz to 1755MHz LTE BAND 5: 824MHz to 849MHz LTE BAND 7: 2500MHz to 2570MHz Bluetooth: 2400MHz to 2483.5MHz 2.4G WIFI: 2412MHz to 2462MHz
RX Frequency	GSM 850: 869MHz to 894MHz PCS 1900:1930MHz to 1990MHz WCDMA Band II: 1930MHz to 1990MHz WCDMA Band IV: 2110MHz to 2115MHz WCDMA Band V: 869MHz to 894MHz LTE BAND 2: 1930MHz to 1990MHz LTE BAND 4: 2110MHz to 2155MHz LTE BAND 5: 869MHz to 894MHz LTE BAND 7: 2620MHz to 2690MHz Bluetooth: 2400MHz to 2483.5MHz 2.4G WIFI: 2412MHz to 2462MHz GPS: 1575.42MHz BDS: 1559.052MHz GLONASS:1597.55MHz FM: 87.5MHz to 108MHz
S/N	85L0119226000210
HW Version	HL1STKM
SW Version	9.0.1.6(C900E6R1P2)
EUT Accessory	
Data cable	Data Cable USB A Male to Type C ,Shield Manufacturer: NingBo Broad Telecommunication Co.,Ltd. LUXSHARE Precision Industry Co., Ltd. HONGFUJIN PRECISION INDUSTRIAL(SHENZHEN).LTD Freeport Resources Enterprises (Jiangxi) Co.,Ltd Dongguan Mingji Electronics Technology Group Co.,Ltd
Adapter	Manufacturer:Huawei Technologies Co.,Ltd. Model: HW-050200E02 Input voltage: 100-240V 50/60Hz ,0.5A Output voltage: 5V  2A Rated Power: 10W



	SN: B95432J5T00024;K95401J4S00143; H9541RJ4L00140;P95416J6C00106;
Adapter	Manufacturer:Huawei Technologies Co.,Ltd. Model: HW-050200U02 Input voltage: 100-240V 50/60Hz ,0.5A Output voltage: 5V  2A Rated Power: 10W SN: P95521J6200032;B95532J5T00018; H955KAJ4M00153;K95501J3N00026;
Adapter	Manufacturer:Huawei Technologies Co.,Ltd. Model: HW-050200A02 Input voltage: 100-240V 50/60Hz ,0.5A Output voltage: 5V  2A Rated Power: 10W SN: B95632J3B00021; K95601HAA00036;
Adapter	Manufacturer:Huawei Technologies Co.,Ltd. Model: HW-050200B02 Input voltage: 100-240V 50/60Hz ,0.5A Output voltage: 5V  2A Rated Power: 10W SN: H95316J4200029;P95316J4300009; B95332J3Y00059;K95301J3X00032;
Adapter	Manufacturer:Huawei Technologies Co.,Ltd. Model: HW-050200E01 Input voltage: 100-240V 50/60Hz ,0.5A Output voltage: 5V  2A Rated Power: 10W SN: B78714H7H00861;H787K8J5K00952; P78714J5255717;
Adapter	Manufacturer:Huawei Technologies Co.,Ltd. Model: HW-050200A01 Input voltage: 100-240V 50/60Hz ,0.5A Output voltage: 5V  2A Rated Power: 10W SN: P78911H6A04740; B78975GCD22322; H789K7HA502790
Adapter	Manufacturer:Huawei Technologies Co.,Ltd. Model: HW-050200B01 Input voltage: 100-240V 50/60Hz ,0.5A Output voltage: 5V  2A Rated Power: 10W SN: H788K7H4N00955;P78817H7D35407; B78830H7H01619
Adapter	Manufacturer:Huawei Technologies Co.,Ltd. Model: HW-050200U01 Input voltage: 100-240V 50/60Hz ,0.5A Output voltage: 5V  2A Rated Power: 10W SN: H786K9J4V01394;B78697J4J03533 P78621J4278130



Rechargeable Li-ion	Manufacturer: Huawei Technologies Co.,Ltd. Battery Model: HB446486ECW Rated capacity: 3900mAh Nominal Voltage:  +3.82V Charging Voltage:  +4.40V SN: 6QXHAYIC18X0004F; 6QXWGCJ110G0004C; 6QXPWCJ104G0002F; 6QXLS11C14X00100;
Earphone(22040322)	Manufacturer: Jiangxi Lianchuang Hongsheng Electronic Co. ,LTD. Boluo County Quancheng Electronic Co.,ltd. FOXCONN INTERCONNECT TECHNOLOGY LIMITED

Remark: The above EUT's information is declared by manufacturer. Please refer to the specifications or user's manual for more detailed information.





## 1.2 Test Site Information

Test Site 1:	Reliability Laboratory of Huawei Technologies Co., Ltd. Global Compliance and Testing Center of Huawei Technologies Co., Ltd.
Test Site Location:	No.2, New City Avenue, Songshan Lake Sci. & Tech. Industry Park, Dongguan, 523808, P.R.C

## 1.3 Applied Standards

### APPLIED STANDARD

**47 CFR FCC Part 15, Subpart B**



## 2 Summary of Results

Summary of Results				
Test Items	Test Mode	Performance Class & Required Performance Criteria	Result	Site
<u>Radiated Emissions</u> Enclosure Port	Mode 2~ Mode 5	CLASS B	Pass	Site1
<u>Conducted Emissions</u> <input type="checkbox"/> DC Power Port <input checked="" type="checkbox"/> AC Power Port <input type="checkbox"/> Telecommunication Ports	Mode 1~ Mode 5	CLASS B	Pass	Site1
Note: 1, Measurement taken is within the uncertainty of test system. 2, <input checked="" type="checkbox"/> The item has been tested; <input type="checkbox"/> The item has not been tested.				

During the measurement, the environmental conditions complied with the range listed as below.

Item	Required
Ambient temperature	15°C ~ 35°C
Relative humidity	25% ~ 75%
Atmospheric pressure	86kPa ~ 106kPa



### 3 System Configuration during EMC Test

#### 3.1 Test Mode

The EUT was configured, installed, arranged and operated in a manner consistent with typical application. The following mode(s) were applied during the compliance test.

Test Mode	
Mode 1:	Charging +traffic +WIFI+BT+GNSS On +Earphone
Mode 2:	Charging +Camera On +Earphone +idle
Mode 3:	Charging +Video Playing +Earphone +idle
Mode 4:	Charging +FM +Earphone +idle
Mode 5:	USB Copy(EUT with PC) +Earphone

Remark:

- 1) If there is one kind of accessories with different models, each one should be applied throughout the compliance test respectively, however, only the worst case will be recorded in this report.
- 2) If EUT has more than one typical operation, only the worst test mode will be recorded in this report.

Traffic Mode:



When the EUT state is switched on and with Radio Resource Control (RRC) connection established.


Idle Mode:

When the EUT state is switched on but without Radio Resource Control (RRC) connection.



### 3.2 Test System Configuration







### 3.3 Cables Used during Test

Cable	Quantity	Length	Type of Cable
USB	1	<3m	Shielded
Earphone	1	<3m	Unshielded

### 3.4 Associated Equipment Used during Test

Name	Model	Manufacturer	S/N	Calibrated Deadline	Cal interval
Radio Communication Tester	CMU200	R&S	3608082535	2019-05-07	12
Radio Communication Tester	MT8820C	Anritsu	A110518805	2019-05-08	12
Notebook	S3	ThinkPad	A140714638	/	/
Mouse	M-U0025-O	Lenovo	HS423HB22TB	/	/



## 4 Electromagnetic Interference (EMI)

### 4.1 Radiated Disturbance 30MHz to 18GHz

#### 4.1.1 Test Procedure

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4dB according to the standards: ANCI C63.4: 2014. The test distance was 3m. The set-up and test methods were according to ANCI C63.4: 2014.

A preliminary scan and a final scan of the emissions were made from 30 MHz to 18 GHz by using test script of software; The emissions were measured using Quasi-Peak Detector (30MHz~1GHz) and AV/PK detector (above 1GHz). The maximal emission value was acquired by adjusting the antenna height, polarisation and turntable azimuth in accordance with the software setup. Normally, the height range of antenna was 1m to 4m. The azimuth range of turntable was 0° to 360°. The receiving antenna has two polarizations V and H.

Measurement bandwidth (RBW) for 30MHz to 1000 MHz: 120 kHz;

Measurement bandwidth (RBW) for 1000MHz to 18000 MHz: 1MHz;

EUT was configured in idle mode and the test performed at worst emission state.

#### 4.1.2 Test setup




Figure 1. Test set-up of radiated disturbance(30MHz-1GHz)




Figure 2. Test set-up of radiated disturbance(above 1GHz)



### 4.1.3 Test Results

The EUT has met the requirements for Radiated Emission of enclosure port.  
Refer to the section 7.1.1 of this report for test data.

Test Limits (Class B)				
Frequency of Emission (MHz)	Radiated Limit			
	Unit( $\mu$ V/m)		Unit(dB $\mu$ V/m)	
30-88	100		40	
88-216	150		43.5	
216-960	200		46	
Above 960	500		54	
Above 1000	AV	PK	AV	PK
	500	5000	54	74





## 4.2 Conducted Disturbance 0.15 MHz to 30MHz

### 4.2.1 Test Procedure

The Table-top EUT was placed upon a non-metallic table 0.8 m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm away from LISN. The set-up and test methods were according to ANCI C63.4: 2014 Conducted Disturbance at AC Port measurements were undertaken on the L and N Lines. The emissions were measured using a Quasi-Peak Detector and Average Detector.

EUT was communicated with the simulator through Air interface, the simulator controls the EUT to transmitter the maximum power which defined in specification of product. The EUT operated on the typical channel.

Measurement bandwidth (RBW) for 150 kHz to 30 MHz: 9 kHz;

The EUT was set in the shielded chamber and operated under nominal conditions.

### 4.2.2 Test Setup




Figure 3. Test Set-up of conducted disturbance

### 4.2.3 Test Results

The EUT has met requirements for Conducted disturbance of power lines. Refer to the section 7.2.1 of this report for test data.

Test Limit of AC Power Port		
Frequency range	150kHz ~ 30MHz	
Frequency	Voltage limits	
	QP (dB $\mu$ V)	AV (dB $\mu$ V)
0.15MHz~0.5MHz	66-56	56-46
0.5MHz-5MHz	56	46
5MHz~30MHz	60	50



## 5 Main Test Instruments

Main Test Equipments						
Test item	Test Instrument	Model	S/N	Manufacturer	Calibrated Deadline	Cal interval
RE	EMI Test receiver	ESU26	100150	R&S	Jan. 14, 2020	12
	Broadband Antenna	VULB 9163	9163-491	SCHWARZBECK	Mar. 24, 2021	24
	Horn Antenna	HF906	100683	R&S	Mar. 24, 2021	24
CE	EMI Test receiver	ESCI	101163	R&S	Jan. 14, 2020	12
	Artificial Mains Network	ENV216	100382	R&S	May. 07, 2019	12
Software Information						
Test Item	Software Name	Manufacturer		Version		
RE	EMC32	R&S		V9.25.0		
CE	EMC32	R&S		V9.25.0		

## 6 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

System Measurement Uncertainty		
Items	Extended Uncertainty	
RE(30MHz-1GHz)	Field strength (dB $\mu$ V/m)	U=5.24dB; k=2
RE(1GHz-18GHz)	Field strength (dB $\mu$ V/m)	U=4.84dB; k=2
CE	Disturbance Voltage (dB $\mu$ V)	U=2.3dB; k=2




## 7 Test Data and Graph

Only the worst test results were shown

### 7.1 Radiated Disturbance

#### 7.1.1 30MHz~1GHz

Test Mode 3: Charging + Video Playing + Earphone + idle



#### MEASUREMENT RESULT: QP Detector

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Height cm	Azimuth deg	Polarisation
40.965760	33.18	14.5	40.00	6.82	100.0	22.0	V
53.784820	26.78	13.4	40.00	13.22	126.0	317.0	V
91.623220	25.06	12.9	43.50	18.44	100.0	262.0	V
171.320720	28.70	10.2	43.50	14.80	100.0	179.0	V
338.050200	22.91	15.6	46.00	23.09	102.0	285.0	H
678.444860	29.14	21.0	46.00	16.86	101.0	26.0	H

Note:


Level = Reading level by receiver + Transd (Antenna factor + cable loss - preamplifier gain)

The reading level is calculated by software which is not shown in the sheet.



### 7.1.2 1GHz~18GHz

Test Mode 3: Charging + Video Playing +Earphone +idle



#### MEASUREMENT RESULT: PK Detector

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Height cm	Azimuth deg	Polarisation
6940.942	46.80	3.4	74.00	27.20	100	1	V
11986.4933	52.06	11.0	74.00	21.94	106	169	V
16817.867	59.93	20.4	74.00	14.07	151	47	V

#### MEASUREMENT RESULT: AV Detector

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Height cm	Azimuth deg	Polarisation
8676.334	34.96	6.6	54.00	19.04	100	18	V
14798.28267	40.72	17.6	54.00	13.28	135	0	V
17924.67333	45.20	21.6	54.00	8.80	144	263	H

Note:


Level =Reading level by receiver + Transd (Antenna factor + cable loss - preamplifier gain)  
The reading level is calculated by software which is not shown in the sheet.



## 7.2 Conducted Disturbance

### 7.2.1 AC Port Test Data

Test Mode 3: Charging +Video Playing +Earphone +idle



#### MEASUREMENT RESULT: QP Detector

Frequency MHz	Level dBµV	Line	Transd dB	Margin dB	Limit dBµV	PE
0.192821	48.41	N	9.7	15.50	63.91	FLO
0.316415	36.74	N	9.7	23.06	59.80	FLO
0.464659	38.28	L1	9.7	18.33	56.61	FLO
1.58973	38.92	L1	9.7	17.08	56	FLO
5.569974	37.10	L1	9.8	22.9	60	FLO
23.21603	27.63	N	10.2	32.37	60	FLO

#### MEASUREMENT RESULT: AV Detector

Frequency MHz	Level dBµV	Line	Transd dB	Margin dB	Limit dBµV	PE
0.19061	25.55	9.7	N	28.46	54.01	FLO
0.287956	21.61	9.7	N	28.97	50.58	FLO
0.468718	21.90	9.7	N	24.64	46.54	FLO
1.565766	22.40	9.7	L1	23.6	46	FLO
5.503463	19.52	9.8	L1	30.48	50	FLO
21.783913	19.47	10.2	N	30.53	50	FLO

-----**END**-----