

TABLE

Label for 25KTL-NAM3



型号 Model: SUN2000-25KTL-NAM3
名称 Name: 太阳能光伏逆变器
SOLAR INVERTER

最大输入电压 d.c. Max. Input Voltage: 1000 Vd.c.
最大输入电流 d.c. Max. Input Current: 26 A/26 A/26 A/26 A
输入短路电流 Isc: 40 A/40 A/40 A/40 A
MPP电压范围 d.c. MPP Range: 200 - 1000 Vd.c.
输出电压 a.c. Output Nominal Voltage: 480 Va.c.; 3(N)~+⊕
输出频率 a.c. Nominal Operating Frequency: 60 Hz
额定输出功率 a.c. Output Rated Power: 25 kW
最大视在功率 a.c. Output Max.Apparent Power: 27.5 kVA
最大输出电流 a.c. Output Max. Current: 33 A
功率因数 Power Factor: 0.8(lagging) - 0.8(leading)
温度范围 Operating Temperature Range: - 25 - +80 °C
逆变器拓扑 Inverter Topology: Non-Isolation
防护等级 Enclosure: Type 4X
保护等级 Protection Class: I
过电压类别 Overvoltage Category: II(DC)/III(AC)
污染等级 Pollution Degree: III
海拔 Altitude: 4000 m
通讯方式 Communication: MBUS/RS485/WLAN
电弧故障保护 AFCI: TYPE I
This device complies with Part 15 of the FCC Rules.Operation is subject to the following two conditions: (1) this device may not cause harmful interference,and (2) this device must accept any interference received,including interference that may cause undesired operation.
FCC ID:QISSUN2000
IC:6369A-SUN2000



华为技术有限公司 HUAWEI TECHNOLOGIES CO., LTD. 中国制造 MADE IN CHINA
HQ of Huawei, Bantian, Longgang District, Shenzhen, 518129, P.R.C

Label for 30KTL-NAM3



型号 Model: SUN2000-30KTL-NAM3
名称 Name: 太阳能光伏逆变器
SOLAR INVERTER

最大输入电压 d.c. Max. Input Voltage: 1000 Vd.c.
最大输入电流 d.c. Max. Input Current: 26 A/26 A/26 A/26 A
输入短路电流 Isc: 40 A/40 A/40 A/40 A
MPP电压范围 d.c. MPP Range: 200 - 1000 Vd.c.
输出电压 a.c. Output Nominal Voltage: 480 Va.c.; 3(N)~+⊕
输出频率 a.c. Nominal Operating Frequency: 60 Hz
额定输出功率 a.c. Output Rated Power: 30 kW
最大视在功率 a.c. Output Max.Apparent Power: 33 kVA
最大输出电流 a.c. Output Max. Current: 40 A
功率因数 Power Factor: 0.8(lagging) - 0.8(leading)
温度范围 Operating Temperature Range: - 25 - +80 °C
逆变器拓扑 Inverter Topology: Non-Isolation
防护等级 Enclosure: Type 4X
保护等级 Protection Class: I
过电压类别 Overvoltage Category: II(DC)/III(AC)
污染等级 Pollution Degree: III
海拔 Altitude: 4000 m
通讯方式 Communication: MBUS/RS485/WLAN
电弧故障保护 AFCI: TYPE I
This device complies with Part 15 of the FCC Rules.Operation is subject to the following two conditions: (1) this device may not cause harmful interference,and (2) this device must accept any interference received,including interference that may cause undesired operation.
FCC ID:QISSUN2000
IC:6369A-SUN2000



华为技术有限公司 HUAWEI TECHNOLOGIES CO., LTD. 中国制造 MADE IN CHINA
HQ of Huawei, Bantian, Longgang District, Shenzhen, 518129, P.R.C

Label for 33KTL-NAM3



型号 Model: SUN2000-33KTL-NAM3
名称 Name: 太阳能光伏逆变器
SOLAR INVERTER

最大输入电压 d.c. Max. Input Voltage: 1000 Vd.c.
最大输入电流 d.c. Max. Input Current: 28 A/28 A/28 A/28 A
输入短路电流 Isc: 40 A/40 A/40 A/40 A
MPP电压范围 d.c. MPP Range: 200 ~ 1000 Vd.c.
输出电压 a.c. Output Nominal Voltage: 480 Va.c.; 3(N)~*+⊕
输出频率 a.c. Nominal Operating Frequency: 60 Hz
额定输出功率 a.c. Output Rated Power: 33.3 kW
最大视在功率 a.c. Output Max.Apparent Power: 36.6 kVA
最大输出电流 a.c. Output Max. Current: 44.1 A
功率因数 Power Factor: 0.8(lagging) ~ 0.8(leading)
温度范围 Operating Temperature Range: - 25 ~ +60 °C
逆变器拓扑 Inverter Topology: Non-Isolation
防护等级 Enclosure: Type 4X
保护等级 Protection Class: I
过电压类别 Overvoltage Category: II(DC)/III(AC)
污染等级 Pollution Degree: III
海拔 Altitude: 4000 m
通讯方式 Communication: MBUS/RS485/WLAN
电弧故障保护 AFCI: TYPE I
This device complies with Part 15 of the FCC Rules.Operation is subject to the following two conditions: (1) this device may not cause harmful interference,and (2) this device must accept any interference received,including interference that may cause undesired operation.
FCC ID:QISSUN2000
IC:6369A-SUN2000



华为技术有限公司 HUAWEI TECHNOLOGIES CO.,LTD. 中国制造 MADE IN CHINA
HQ of Huawei, Bantian, Longgang District, Shenzhen, 518129, P.R.C

Label for 36KTL-NAM3



型号 Model: SUN2000-36KTL-NAM3
名称 Name: 太阳能光伏逆变器
SOLAR INVERTER

最大输入电压 d.c. Max. Input Voltage: 1000 Vd.c.
最大输入电流 d.c. Max. Input Current: 28 A/28 A/28 A/28 A
输入短路电流 Isc: 40 A/40 A/40 A/40 A
MPP电压范围 d.c. MPP Range: 200 ~ 1000 Vd.c.
输出电压 a.c. Output Nominal Voltage: 480 Va.c.; 3(N)~*+⊕
输出频率 a.c. Nominal Operating Frequency: 60 Hz
额定输出功率 a.c. Output Rated Power: 36 kW
最大视在功率 a.c. Output Max.Apparent Power: 40 kVA
最大输出电流 a.c. Output Max. Current: 48.2 A
功率因数 Power Factor: 0.8(lagging) ~ 0.8(leading)
温度范围 Operating Temperature Range: - 25 ~ +60 °C
逆变器拓扑 Inverter Topology: Non-Isolation
防护等级 Enclosure: Type 4X
保护等级 Protection Class: I
过电压类别 Overvoltage Category: II(DC)/III(AC)
污染等级 Pollution Degree: III
海拔 Altitude: 4000 m
通讯方式 Communication: MBUS/RS485/WLAN
电弧故障保护 AFCI: TYPE I
This device complies with Part 15 of the FCC Rules.Operation is subject to the following two conditions: (1) this device may not cause harmful interference,and (2) this device must accept any interference received,including interference that may cause undesired operation.
FCC ID:QISSUN2000
IC:6369A-SUN2000



华为技术有限公司 HUAWEI TECHNOLOGIES CO.,LTD. 中国制造 MADE IN CHINA
HQ of Huawei, Bantian, Longgang District, Shenzhen, 518129, P.R.C

Label for 40KTL-NAM3



型号 Model: SUN2000-40KTL-NAM3
名称 Name: 太阳能光伏逆变器
SOLAR INVERTER

最大输入电压 d.c. Max. Input Voltage: 1000 Vd.c.
最大输入电流 d.c. Max. Input Current: 28 A/28 A/28 A/28 A
输入短路电流 Isc: 40 A/40 A/40 A/40 A
MPP电压范围 d.c. MPP Range: 200 ~ 1000 Vd.c.
输出电压 a.c. Output Nominal Voltage: 480 Va.c.; 3(N)~+⊕
输出频率 a.c. Nominal Operating Frequency: 60 Hz
额定输出功率 a.c. Output Rated Power: 40 kW
最大视在功率 a.c. Output Max.Apparent Power: 44 kVA
最大输出电流 a.c. Output Max. Current: 53 A
功率因数 Power Factor: 0.8(lagging) ~ 0.8(leading)
温度范围 Operating Temperature Range: - 25 ~ +80 °C
逆变器拓扑 Inverter Topology: Non-Isolation
防护等级 Enclosure: Type 4X
保护等级 Protection Class: I
过电压类别 Overvoltage Category: II(DC)/III(AC)
污染等级 Pollution Degree: III
海拔 Altitude: 4000 m
通讯方式 Communication: MBUS/RS485/WLAN
电涌故障保护 AFCI: TYPE I

This device complies with Part 15 of the FCC Rules.Operation is subject to the following two conditions: (1) this device may not cause harmful interference,and (2) this device must accept any interference received,including interference that may cause undesired operation.
FCC ID:QISSUN2000
IC:6369A-SUN2000



华为技术有限公司 HUAWEI TECHNOLOGIES CO., LTD. 中国制造 MADE IN CHINA
HQ of Huawei, Bantian, Longgang District, Shenzhen, 518128, P.R.C

Location of Label

