


FCC Radio Test Report


FCC ID: QIST1-821W


This report concerns (check one): Original Grant Class II Change

Project No. : 1409C098A
Equipment : HUAWEI MediaPad T1 8.0 Pro
Model Name : T1-821w; T1-821L
Applicant : Huawei Technologies Co.,Ltd.
Address : Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District Shenzhen China

Date of Receipt : Sep. 26, 2014
Date of Test : Sep. 26, 2014~Nov. 12, 2014
Issued Date : Nov. 13, 2014
Tested by : BTL Inc.

Testing Engineer : 
(David Mao)

Technical Manager : 
(Leo Hung)

Authorized Signatory : 
(Steven Lu)

B T L I N C .

No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, Guangdong, China.

TEL: +86-769-8318-3000 FAX: +86-769-8319-6000

Declaration

BTL represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with the standards traceable to National Measurement Laboratory (**NML**) of **R.O.C.**, or National Institute of Standards and Technology (**NIST**) of **U.S.A.**

BTL's reports apply only to the specific samples tested under conditions. It is manufacturer's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

BTL's reports must not be used by the client to claim product endorsement by the authorities or any agency of the Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and **BTL-self**, extracts from the test report shall not be reproduced except in full with **BTL**'s authorized written approval.

BTL's laboratory quality assurance procedures are in compliance with the **ISO Guide 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Table of Contents	Page
1 . CERTIFICATION	7
2 . SUMMARY OF TEST RESULTS	8
2.1 TEST FACILITY	9
2.2 MEASUREMENT UNCERTAINTY	9
3 . GENERAL INFORMATION	10
3.1 GENERAL DESCRIPTION OF EUT	10
3.2 DESCRIPTION OF TEST MODES	13
3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING	15
3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	16
3.5 DESCRIPTION OF SUPPORT UNITS	16
4 . EMC EMISSION TEST	17
4.1 CONDUCTED EMISSION MEASUREMENT	17
4.1.1 POWER LINE CONDUCTED EMISSION	17
4.1.2 TEST PROCEDURE	17
4.1.3 DEVIATION FROM TEST STANDARD	17
4.1.4 TEST SETUP	18
4.1.5 EUT OPERATING CONDITIONS	18
4.1.6 EUT TEST CONDITIONS	18
4.1.7 TEST RESULTS	18
4.2 RADIATED EMISSION MEASUREMENT	19
4.2.1 RADIATED EMISSION LIMITS	19
4.2.2 TEST PROCEDURE	20
4.2.3 DEVIATION FROM TEST STANDARD	20
4.2.4 TEST SETUP	20
4.2.5 EUT OPERATING CONDITIONS	21
4.2.6 EUT TEST CONDITIONS	21
4.2.7 TEST RESULTS (9K TO 30MHz)	22
4.2.8 TEST RESULTS (BETWEEN 30 TO 1000 MHz)	22
4.2.9 TEST RESULTS (ABOVE 1000 MHz)	22
5 . 26dB SPECTRUM BANDWIDTH	23
5.1 APPLIED PROCEDURES / LIMIT	23
5.1.1 TEST PROCEDURE	23
5.1.2 DEVIATION FROM STANDARD	23
5.1.3 TEST SETUP	23
5.1.4 EUT OPERATION CONDITIONS	23
5.1.5 EUT TEST CONDITIONS	24
5.1.6 TEST RESULTS	24
6 . MAXIMUM CONDUCTED OUTPUT POWER	25

Table of Contents	Page
6.1 APPLIED PROCEDURES / LIMIT	25
6.1.1 TEST PROCEDURE	25
6.1.2 DEVIATION FROM STANDARD	26
6.1.3 TEST SETUP	26
6.1.4 EUT OPERATION CONDITIONS	26
6.1.5 EUT TEST CONDITIONS	26
6.1.6 TEST RESULTS	26
7 . ANTENNA CONDUCTED SPURIOUS EMISSION	27
7.1 APPLIED PROCEDURES / LIMIT	27
7.1.1 TEST PROCEDURE	27
7.1.2 DEVIATION FROM STANDARD	27
7.1.3 TEST SETUP	27
7.1.4 EUT OPERATION CONDITIONS	27
7.1.5 EUT TEST CONDITIONS	27
7.1.6 TEST RESULTS	27
8 . POWER SPECTRAL DENSITY TEST	28
8.1 APPLIED PROCEDURES / LIMIT	28
8.1.1 TEST PROCEDURE	28
8.1.2 DEVIATION FROM STANDARD	29
8.1.3 TEST SETUP	29
8.1.4 EUT OPERATION CONDITIONS	29
8.1.5 EUT TEST CONDITIONS	29
8.1.6 TEST RESULTS	29
9 . FREQUENCY STABILITY MEASUREMENT	30
9.1 APPLIED PROCEDURES / LIMIT	30
9.1.1 TEST PROCEDURE	30
9.1.2 DEVIATION FROM STANDARD	30
9.1.3 TEST SETUP	31
9.1.4 EUT OPERATION CONDITIONS	31
9.1.5 EUT TEST CONDITIONS	31
9.1.6 TEST RESULTS	31
10 . MEASUREMENT INSTRUMENTS LIST	32
11 . EUT TEST PHOTOS	34
ATTACHMENT A - CONDUCTED EMISSION	38
ATTACHMENT B - RADIATED EMISSION (9KHZ TO 30MHZ)	41
ATTACHMENT C - RADIATED EMISSION (30MHZ TO 1000MHZ)	43
ATTACHMENT D - RADIATED EMISSION (ABOVE 1000MHZ)	68
ATTACHMENT E - BANDWIDTH	204

Table of Contents	Page
ATTACHMENT F - MAXIMUM OUTPUT POWER	229
ATTACHMENT G - ANTENNA CONDUCTED SPURIOUS EMISSION	234
ATTACHMENT H - POWER SPECTRAL DENSITY	247
ATTACHMENT I - FREQUENCY STABILITY	272

REPORT ISSUED HISTORY

Issued No.	Description	Issued Date
BTL-FCCP-1-1409C098A	Original Issue.	Nov. 13, 2014

1. CERTIFICATION

Equipment : HUAWEI MediaPad T1 8.0 Pro
Brand Name : HUAWEI
Model Name : T1-821w; T1-821L
Applicant : Huawei Technologies Co.,Ltd.
Manufacturer : Huawei Technologies Co.,Ltd.
Address : Administration Building, Huawei Base, Bantian, Longgang District ,Shenzhen 518129, P.R.China
Factory : Huawei Technologies Co.,Ltd.
Address : Administration Building, Huawei Base, Bantian, Longgang District ,Shenzhen 518129, P.R.China
Date of Test : Sep. 26, 2014~Nov. 12, 2014
Test Sample : ENGINEERING SAMPLE
Standard(s) : FCC Part15, Subpart E(15.407) / ANSI C63.4: 2009
Standard(s) : FCC KDB 789033 D02 General UNII Test Procedures New Rules v01.

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. BTL-FCCP-1-1409C098A) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of TAF according to the ISO-17025 quality assessment standard and technical standard(s).

2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

FCC Part15, Subpart E			
Standard(s) Section	Test Item	Judgment	Remark
FCC			
15.207	AC Power Line Conducted Emissions	PASS	
15.407(a)	26dB Spectrum Bandwidth	PASS	
15.407(a)	Maximum Conducted Output Power	PASS	
15.407(a)	Power Spectral Density	PASS	
15.407(a)	Radiated Emissions	PASS	
15.407(b)	Band Edge Emissions	PASS	
15.407(g)	Frequency Stability	PASS	
15.203	Antenna Requirements	PASS	

NOTE:

- (1)" N/A" denotes test is not applicable in this test report.
- (2) FCC KDB 789033 D02 General UNII Test Procedures New Rules v01.

2.1 TEST FACILITY

The test facilities used to collect the test data in this report is **DG-C02/DG-CB03** at the location of No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, Guangdong, China. 523792
BTL's test firm number for FCC: 319330

2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty **U** is based on a standard uncertainty multiplied by a coverage factor of **k=2**, providing a level of confidence of approximately **95%** .

A. Conducted Measurement:

Test Site	Method	Measurement Frequency Range	U, (dB)	NOTE
DG-C02	CISPR	150 KHz ~ 30MHz	1.94	

B. Radiated Measurement:

Test Site	Method	Measurement Frequency Range	Ant. H / V	U, (B)	NOTE
DG-CB03	CISPR	9KHz~30MHz	V	3.79	
		9KHz~30MHz	H	3.57	
		30MHz ~ 200MHz	V	3.82	
		30MHz ~ 200MHz	H	3.60	
		200MHz ~ 1,000MHz	V	3.86	
		200MHz ~ 1,000MHz	H	3.94	
		1GHz~18GHz	V	3.12	
		1GHz~18GHz	H	3.68	
		18GHz~40GHz	V	4.15	
		18GHz~40GHz	H	4.14	

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Equipment	HUAWEI MediaPad T1 8.0 Pro	
Brand Name	HUAWEI	
Model Name	T1-821w; T1-821L	
Mode Different	Only differ in model name.	
Product Description	Operation Frequency	UNII-1: 5150-5250MHz UNII-2A: 5250-5350MHz UNII-2C: 5470-5725MHz UNII-3: 5725-5850MHz
	Modulation Type	OFDM
	Bit Rate of Transmitter	150Mbps
	Output Power (Max.)for UNII-1	802.11a: 10.99dBm 802.11n (20M): 11.15dBm 802.11n (40M): 11.57dBm
	Output Power (Max.)for UNII-2A	802.11a: 11.51dBm 802.11n (20M): 11.36dBm 802.11n (40M): 11.68dBm
	Output Power (Max.)for UNII-2C	802.11a: 11.12dBm 802.11n (20M): 11.14dBm 802.11n (40M): 11.81dBm
	Output Power (Max.)for UNII-3	802.11a: 10.82dBm 802.11n (20M): 10.92dBm 802.11n (40M): 11.77dBm
Power Source	#1 DC voltage supplied from AC/DC adapter. 1) Brand / Model: BYD / HW-050200E3W (EU) 2) Brand / Model: BYD / HW-050200B3W (UK) 3) Brand / Model: Huntkey / HW-050200E3W (EU) 4) Brand / Model: Huntkey / HW-050200B3W (UK) 5) Brand / Model: BYD / HW-050100E2W (EU) 6) Brand / Model: BYD / HW-050100B2W (UK) 7) Brand / Model: Huntkey / HW-050100E2W (EU) 8) Brand / Model: Huntkey / HW-050100B2W (UK) #2 Supplied from battery.	
Power Rating	#1 1) ~ 4) I/P: 100-240V~50/60Hz,0.5A O/P: 5V/2A 5) ~ 8) I/P: 100-240V~50/60Hz,0.2A O/P: 5V/1A #2 DC 3.8V	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2. Channel List:

802.11a 802.11n 20MHz		802.11n 40MHz	
UNII-1		UNII-1	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	38	5190
40	5200	46	5230
44	5220		
48	5240		

802.11a 802.11n 20MHz		802.11n 40MHz	
UNII-2A		UNII-2A	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
52	5260	54	5270
56	5280	62	5310
60	5300		
64	5320		

802.11a 802.11n 20MHz		802.11n 40MHz	
UNII-2C		UNII-2C	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
100	5500	102	5510
104	5520	110	5550
108	5540	118	5590
112	5560	126	5630
116	5580	134	5670
132	5660		
136	5680		
140	5700		

802.11a 802.11n 20MHz		802.11n 40MHz	
UNII-3		UNII-3	
Channel	Frequency (MHz)	Chann I	Frequency (MHz)
149	5745	151	5755
153	5765	159	5795
157	5785		
161	5805		
165	5825		

3. Antenna Specification:

Ant.	Manufacturer	Model Name	Antenna Type	Connector	Gain (dBi)	Note
1	N/A	N/A	Internal	N/A	1.00	TX/RX

3.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Test Mode	Description
Mode 1	TX A Mode / CH36, CH40, CH48 (UNII-1)
Mode 2	TX N20 Mode / CH36, CH40, CH48 (UNII-1)
Mode 3	TX N40 Mode / CH38, CH46 (UNII-1)
Mode 4	TX A Mode / CH52, CH60, CH64 (UNII-2A)
Mode 5	TX N20 Mode / CH52, CH60, CH64 (UNII-2A)
Mode 6	TX N40 Mode / CH54, CH62 (UNII-2A)
Mode 7	TX A Mode / CH100, CH116, CH140 (UNII-2C)
Mode 8	TX N20 Mode / CH100, CH116, CH140 (UNII-2C)
Mode 9	TX N40 Mode / CH102, CH110, CH134 (UNII-2C)
Mode 10	TX A Mode / CH149,CH157,CH165 (UNII-3)
Mode 11	TX N20 Mode / CH149,CH157,CH165 (UNII-3)
Mode 12	TX N40 Mode / CH151,CH159 (UNII-3)
Mode 13	TX Mode

The EUT system operated these modes were found to be the worst case during the pre-scanning test as following:

For Conducted Test	
Final Test Mode	Description
Mode 13	TX Mode

For Radiated Test	
Final Test Mode	Description
Mode 1	TX A Mode / CH36, CH40, CH48 (UNII-1)
Mode 2	TX N20 Mode / CH36, CH40, CH48 (UNII-1)
Mode 3	TX N40 Mode / CH38, CH46 (UNII-1)
Mode 4	TX A Mode / CH52, CH60, CH64 (UNII-2A)
Mode 5	TX N20 Mode / CH52, CH60, CH64 (UNII-2A)
Mode 6	TX N40 Mode / CH54, CH62 (UNII-2A)
Mode 7	TX A Mode / CH100, CH116, CH140 (UNII-2C)
Mode 8	TX N20 Mode / CH100, CH116, CH140 (UNII-2C)
Mode 9	TX N40 Mode / CH102, CH110, CH134 (UNII-2C)
Mode 10	TX A Mode / CH149,CH157,CH165 (UNII-3)
Mode 11	TX N20 Mode / CH149,CH157,CH165 (UNII-3)
Mode 12	TX N40 Mode / CH151,CH159 (UNII-3)

Note:

- 1) For Radiated Below 1G test, the 802.11a mode is found to be the worst case and recorded.
- 2) Except conducted emission, both adapter and battery are evaluated, operated the battery is the worst and recorded as below test data.
- 3) The EUT is considered a general unit; it was pre-tested on the positioned of each 3 axis. The worst case was found positioned on X-pane. Therefore only the test data of this X-plane was used for radiated emission measurement test.

3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING


During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product

UNII-1			
Test Software Version	ART		
Frequency (MHz)	5180	5200	5240
A Mode	16	16	16
N20 Mode	17	16	16
Frequency (MHz)	5190	5230	
N40 Mode	19	19	

UNII-2A			
Test Software Version	ART		
Frequency (MHz)	5260	5300	5320
A Mode	15	15	15
N20 Mode	15	15	15
Frequency (MHz)	5270	5310	
N40 Mode	16	15	

UNII-2C			
Test Software Version	ART		
Frequency (MHz)	5500	5580	5700
A Mode	13	11	11
N20 Mode	13	11	11
Frequency (MHz)	5510	5550	5670
N40 Mode	14	13	12

UNII-3			
Test Software Version	ART		
Frequency (MHz)	5745	5785	5825
A Mode	12	12	13
N20 Mode	12	12	13
Frequency (MHz)	5755	5795	
N40 Mode	13	13	

3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED**3.5 DESCRIPTION OF SUPPORT UNITS**

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.	Note
-	-	-	-	-	-	

Item	Shielded Type	Ferrite Core	Length	Note
-	-	-	-	

4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 POWER LINE CONDUCTED EMISSION (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *
0.50 -5.0	73.00	60.00	56.00	46.00
5.0 -30.0	73.00	60.00	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


4.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP



4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

The EUT was programmed to be in continuously transmitting/TX Mode mode.

4.1.6 EUT TEST CONDITIONS

Temperature: 25°C Relative Humidity: 55% Test Voltage: AC 120V/60Hz

4.1.7 TEST RESULTS

Please refer to the Attachment A.

Remark:

- (1) All readings are QP Mode value unless otherwise stated AVG in column of **Note**. If the QP Mode Measured value compliance with the QP Limits and lower than AVG Limits, the EUT shall be deemed to meet both QP & AVG Limits and then only QP Mode was measured, but AVG Mode didn't perform. In this case, a “*” marked in AVG Mode column of Interference Voltage Measured.
- (2) Measuring frequency range from 150KHz to 30MHz.

4.2 RADIATED EMISSION MEASUREMENT

4.2.1 RADIATED EMISSION LIMITS

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.

LIMITS OF UNWANTED EMISSION OUT OF THE RESTRICTED BANDS

Frequencies (MHz)	EIRP Limit (dBm)	Equivalent Field Strength at 3m (dB μ V/m)
5150-5250	-27	68.3
5250-5350	-27	68.3
5470-5725	-27	68.3
5725-5850	-27 (beyond 10MHz of the band edge)	68.3
	-17 (within 10 MHz of band edge)	78.3

Note: The following formula is used to convert the equipment isotropic radiated power (eirp) to field

strength: $E = \frac{1000000\sqrt{30P}}{3}$ μ V/m, where P is the eirp (Watts)

4.2.2 TEST PROCEDURE


- a. The measuring distance of at 3m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.2.3 DEVIATION FROM TEST STANDARD


No deviation

4.2.4 TEST SETUP


(A) Radiated Emission Test Set-Up Frequency30 - 1000MHz



(B) Radiated Emission Test Set-Up Frequency Above 1 GHz



(C) Radiated emissions below 30MHz



4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 Unless otherwise a special operating condition is specified in the follows during the testing.

4.2.6 EUT TEST CONDITIONS

Temperature: 25°C Relative Humidity: 55% Test Voltage: DC 3.8V

4.2.7 TEST RESULTS (9K TO 30MHz)

Please refer to the Attachment B

Remark:

- (1) The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.
- (2) Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);
- (3) Limit line = specific limits (dBuV) + distance extrapolation factor.

4.2.8 TEST RESULTS (BETWEEN 30 TO 1000 MHz)

Please refer to the Attachment C.

Remark:

- (1) Reading in which marked as QP or Peak means measurements by using are Quasi-Peak Mode or Peak Mode with Detector BW=120KHz ; SPA setting in RBW=120KHz, VBW =120KHz, Swp. Time = 0.3 sec./MHz .
- (2) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform .
- (3) Measuring frequency range from 30MHz to 1000MHz .
- (4) If the peak scan value lower limit more than 20dB, then this signal data does not show in table .

4.2.9 TEST RESULTS (ABOVE 1000 MHz)

Please refer to the Attachment D.

Remark:

- (1) Spectrum Setting: 30MHz – 1000MHz , RBW= 100KHz, VBW=100KHz, Sweep time = 200 ms. 1GHz- 40GHz, RBW= 1MHz, VBW= 1MHz, Sweep time = Auto
- (2) All readings are Peak unless otherwise stated AV in column of 『Note』 . Peak denotes that the Peak reading compliance with the AV Limits and then AV Mode measurement didn't perform.
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission .
- (4) Data of measurement within this frequency range shown “ * ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axes:
“X” - denotes Laid on Table ; “Y” - denotes Vertical Stand ; “Z” - denotes Side Stand
- (7) During the measurements above 1GHz it is taken care of that the EUT is always within the 3dB cone of radiation BW of the used antenna.
- (8) No limit: This is fundamental signal, the judgment is not applicable.
For fundamental signal judgment was referred to Peak output test.

5. 26dB SPECTRUM BANDWIDTH

5.1 APPLIED PROCEDURES / LIMIT

FCC Part15, Subpart E			
Test Item	Limit	Frequency Range (MHz)	Result
Bandwidth	26 dB Bandwidth	5150-5250	PASS
		5250-5350	PASS
		5470-5725	PASS
	Minimum 500KHz 6dB Bandwidth	5725-5850	PASS

5.1.1 TEST PROCEDURE

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,

b.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 26dB Bandwidth
RBW	300 kHz
VBW	1000 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

c. Measured the spectrum width with power higher than 26dB below carrier

5.1.2 DEVIATION FROM STANDARD

No deviation.

5.1.3 TEST SETUP



5.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 Unless otherwise a special operating condition is specified in the follows during the testing.

5.1.5 EUT TEST CONDITIONS

Temperature: 25°C Relative Humidity: 55% Test Voltage: DC 3.8V

5.1.6 TEST RESULTS

Please refer to the Attachment E.

6. MAXIMUM CONDUCTED OUTPUT POWER

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15, Subpart E			
Test Item	Limit	Frequency Range (MHz)	Result
Conducted Output Power	Fixed:1 Watt (30dBm) Mobile and portable: 250mW (24dBm)	5150-5250	PASS
	250mW (24dBm)	5250-5350	PASS
		5470-5725	PASS
	1 Watt (30dBm)	5725-5850	PASS

6.1.1 TEST PROCEDURE

a. The EUT was directly connected to the power meter and antenna output port as show in the block diagram below,
b.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Encompass the entire emissions bandwidth (EBW) of the signal
RBW	= 1MHz.
VBW	$\geq 3\text{MHz}$.
Detector	RMS
Trace	Max Hold
Sweep Time	auto

c. Test was performed in accordance with method of KDB 789033 D02.

6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP



6.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 Unless otherwise a special operating condition is specified in the follows during the testing.

6.1.5 EUT TEST CONDITIONS

Temperature: 25°C Relative Humidity: 55% Test Voltage: DC 3.8V

6.1.6 TEST RESULTS

Please refer to the Attachment F.

7. ANTENNA CONDUCTED SPURIOUS EMISSION

7.1 APPLIED PROCEDURES / LIMIT

FCC Part15, Subpart E			
Test Item	Limit	Frequency Range (MHz)	Result
Antenna conducted Spurious Emission	-27dBm/MHz	5150-5250	PASS
		5250-5350	PASS
		5470-5725	PASS
	Below -17dBm/MHz within 10MHz of band edge, below -27dBm/MHz beyond 10MHz of the band edge	5725-5850	PASS

7.1.1 TEST PROCEDURE

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,

b.

Spectrum Parameter	Setting
Attenuation	Auto
RBW	1000kHz
VBW	1000kHz
Trace	Max Hold
Sweep Time	Auto

7.1.2 DEVIATION FROM STANDARD

No deviation.

7.1.3 TEST SETUP



7.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 Unless otherwise a special operating condition is specified in the follows during the testing.

7.1.5 EUT TEST CONDITIONS

Temperature: 25°C Relative Humidity: 55% Test Voltage: DC 3.8V

7.1.6 TEST RESULTS

Please refer to the Attachment G.

8. POWER SPECTRAL DENSITY TEST

8.1 APPLIED PROCEDURES / LIMIT

FCC Part15, Subpart E			
Test Item	Limit	Frequency Range (MHz)	Result
Power Spectral Density	Other then Mobile and portable:17dBm/MHz Mobile and portable:11dBm/MHz	5150-5250	PASS
	11dBm/MHz	5250-5350	PASS
		5470-5725	PASS
	30dBm/500KHz	5725-5850	PASS

8.1.1 TEST PROCEDURE

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Encompass the entire emissions bandwidth (EBW) of the signal
RBW	= 1MHz.
VBW	\geq 3MHz.
Detector	RMS
Trace	Max Hold
Sweep Time	Auto

Note:

1. For UNII-3, according to KDB publication 789033 D02 General UNII Test Procedures New Rules v01, section II.F.5., it is acceptable to set RBW at 1MHz and VBW at 3MHz if the spectrum analyzer does not have 500kHz RBW.
2. The value measured with RBW=1MHz is to be added with $10\log(500\text{kHz}/1\text{MHz})$ which is -3dB. For example, if the measured value is +10dBm using RBW=1MHz (that is +10dBm/MHz), then the converted value will be +7dBm/500kHz.

8.1.1 DEVIATION FROM STANDARD

No deviation.

8.1.2 TEST SETUP



8.1.3 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 Unless otherwise a special operating condition is specified in the follows during the testing.

8.1.4 EUT TEST CONDITIONS

Temperature: 25°C Relative Humidity: 55% Test Voltage: DC 3.8V

8.1.5 TEST RESULTS

Please refer to the Attachment H.

9. FREQUENCY STABILITY MEASUREMENT

9.1 APPLIED PROCEDURES / LIMIT

FCC Part15, Subpart E			
Test Item	Limit	Frequency Range (MHz)	Result
Frequency Stability	Specified in the user's manual	5150-5250	PASS
		5250-5350	PASS
		5470-5725	PASS
		5725-5850	PASS

9.1.1 TEST PROCEDURE

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,


Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Entire absence of modulation emissions bandwidth
RBW	10 kHz
VBW	10 kHz
Sweep Time	Auto

c. The test extreme voltage is to change the primary supply voltage from 85 to 115 percent of the nominal value.
d. User manual temperature is -20°C~55°C.

9.1.2 DEVIATION FROM STANDARD

No deviation.

9.1.3 TEST SETUP



9.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 Unless otherwise a special operating condition is specified in the follows during the testing.

9.1.5 EUT TEST CONDITIONS

Temperature: 25°C Relative Humidity: 55% Test Voltage: DC 3.8V

9.1.6 TEST RESULTS

Please refer to the Attachment I.

10. MEASUREMENT INSTRUMENTS LIST

Conducted Emission Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	LISN	EMCO	3816/2	00052765	Mar. 29, 2015
2	LISN	R&S	ENV216	100087	Mar. 29, 2015
3	Test Cable	N/A	C_17	N/A	Mar. 14, 2015
4	EMI TEST RECEIVER	R&S	ESCS30	826547/022	Mar. 29, 2015
5	50Ω Terminator	SHX	TF2-3G-A	08122902	Mar. 29, 2015
6	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A

Radiated Emission Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Antenna	Schwarbeck	VULB9160	9160-3232	Mar. 29, 2015
2	Amplifier	HP	8447D	2944A09673	Mar. 29, 2015
3	Receiver	AGILENT	N9038A	MY52130039	Sep. 30, 2015
4	Test Cable	N/A	C-01_CB03	N/A	Jul. 01, 2015
5	Controller	CT	SC100	N/A	N/A
6	Antenna	ETS	3115	00075789	Mar. 29, 2015
7	Amplifier	Agilent	8449B	3008A02274	Mar. 29, 2015
8	Receiver	AGILENT	N9038A	MY52130039	Sep. 30, 2015
9	Test Cable	HUBER+SUHNER	C-48	N/A	Apr. 30, 2015
10	Controller	CT	SC100	N/A	N/A
11	Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170319	Feb. 22, 2015
12	Microwave Preamplifier With Adaptor	EMC INSTRUMENT	EMC2654045	980039 & HA01	Feb. 22, 2015
13	Active Loop Antenna	R&S	HFH2-Z2	830749/020	Mar. 29, 2015
14	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A

Spectrum Bandwidth Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov. 02, 2015

Maximum Conducted Output Power Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	P-series Power meter	Agilent	N1911A	MY45100473	Mar. 29, 2015
2	Wireband Power sensor	Agilent	N1921A	MY51100041	Mar. 29, 2015

Antenna Conducted Spurious Emission Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov. 02, 2015

Power Spectral Density Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov. 02, 2015

Frequency Stability Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov. 02, 2015
2	Precision Oven Tester	HOLINK	H-T-1F-D	BA03101701	May. 24, 2015

Remark: "N/A" denotes no model name, serial no. or calibration specified.

All calibration period of equipment list is one year.


11. EUT TEST PHOTOS

Conducted Measurement Photos




Radiated Measurement Photos

9KHz to 30MHz





Radiated Measurement Photos

30MHz to 1000MHz



Radiated Measurement Photos


Above 1000MHz



ATTACHMENT A - CONDUCTED EMISSION

Test Mode: TX MODE

Line




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1		0.1500	46.10	9.52	55.62	66.00	-10.38	peak	
2		0.1500	34.15	9.52	43.67	56.00	-12.33	AVG	
3		0.1930	44.86	9.54	54.40	63.91	-9.51	peak	
4		0.1930	32.57	9.54	42.11	53.91	-11.80	AVG	
5		0.2633	37.27	9.58	46.85	61.33	-14.48	peak	
6		0.3336	34.39	9.61	44.00	59.36	-15.36	peak	
7	*	3.6250	37.71	9.80	47.51	56.00	-8.49	peak	
8		3.6250	25.30	9.80	35.10	46.00	-10.90	AVG	
9		18.3242	31.57	10.39	41.96	60.00	-18.04	peak	

Note : The test result has included the cable loss.

Test Mode: TX MODE

Neutral



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV	dB			
1		0.1500	46.96	9.63	56.59	66.00	-9.41	peak	
2		0.1500	36.30	9.63	45.93	56.00	-10.07	AVG	
3		0.1812	44.16	9.62	53.78	64.43	-10.65	peak	
4		0.1812	33.80	9.62	43.42	54.43	-11.01	AVG	
5		0.2477	36.62	9.61	46.23	61.83	-15.60	peak	
6	*	3.7148	37.54	9.82	47.36	56.00	-8.64	peak	
7		3.7148	25.30	9.82	35.12	46.00	-10.88	AVG	
8		5.0663	32.08	9.88	41.96	60.00	-18.04	peak	
9		18.1836	31.41	10.38	41.79	60.00	-18.21	peak	

Note : The test result has included the cable loss.

ATTACHMENT B - RADIATED EMISSION (9KHZ TO 30MHZ)

Test Mode: TX MODE

Freq. (MHz)	Ant. 0°/90°	Reading(RA) (dBuV)	Corr.Factor(CF) (dB)	Measured(FS) (dBuV/m)	Limits(QP) (dBuV/m)	Margin (dB)	Note
frequency(MHz)	Ant0°/90°	Read leveldBuV	Factor(dB)	asured(FS)(dBuV/m)	nit(QP)(dBuV/m)	Margin(dB)	Note
0.0094	0°	0.34	24.97	25.31	108.11	-82.80	AVG
0.0094	0°	2.45	24.97	27.42	128.11	-100.69	PEAK
0.0236	0°	0.58	24.07	24.65	100.15	-75.49	AVG
0.0236	0°	2.48	24.07	26.55	120.15	-93.59	PEAK
0.0316	0°	1.34	23.57	24.91	97.61	-72.71	AVG
0.0316	0°	4.37	23.57	27.94	117.61	-89.68	PEAK
0.0428	0°	0.47	22.86	23.33	94.98	-71.65	AVG
0.0428	0°	3.16	22.86	26.02	114.98	-88.96	PEAK
0.4914	0°	5.48	19.82	25.30	73.78	-48.47	QP
1.7153	0°	5.17	19.53	24.70	69.54	-44.84	QP

Freq. (MHz)	Ant. 0°/90°	Reading(RA) (dBuV)	Corr.Factor(CF) (dB)	Measured(FS) (dBuV/m)	Limits(QP) (dBuV/m)	Margin (dB)	Note
0.0094	90°	0.64	24.30	24.94	128.13	-103.19	AVG
0.0094	90°	2.97	24.30	27.27	148.13	-120.86	PEAK
0.0236	90°	1.37	24.07	25.44	120.15	-94.70	AVG
0.0236	90°	4.68	24.07	28.75	140.15	-111.39	PEAK
0.0317	90°	0.28	23.56	23.84	117.58	-93.74	AVG
0.0317	90°	3.56	23.56	27.12	137.58	-110.46	PEAK
0.0428	90°	0.96	22.86	23.82	114.98	-91.16	AVG
0.0428	90°	3.17	22.86	26.03	134.98	-108.95	PEAK
0.4913	90°	4.67	19.82	24.49	73.78	-49.29	QP
1.7157	90°	5.03	19.53	24.56	69.54	-44.98	QP

ATTACHMENT C - RADIATED EMISSION (30MHZ TO 1000MHZ)

Test Mode: UNII-1/TX A Mode 5180MHz

Vertical



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	*	74.6200	39.30	-16.57	22.73	40.00	-17.27	peak	
2		132.8200	31.33	-13.09	18.24	43.50	-25.26	peak	
3		297.7200	28.48	-11.03	17.45	46.00	-28.55	peak	
4		432.5500	29.78	-8.94	20.84	46.00	-25.16	peak	
5		671.1700	30.73	-5.06	25.67	46.00	-20.33	peak	
6		888.4500	29.26	-1.90	27.36	46.00	-18.64	peak	

Test Mode: UNII-1/TX A Mode 5180MHz

Horizontal



No. Mk.	Freq. MHz	Reading Level	Correct Factor	Measure- ment	Limit	Over	Detector	Comment
		dBuV	dB	dBuV/m	dB			
1	140.5800	31.26	-13.17	18.09	43.50	-25.41	peak	
2	290.9300	30.31	-11.16	19.15	46.00	-26.85	peak	
3	426.7300	30.10	-9.04	21.06	46.00	-24.94	peak	
4	635.2800	30.76	-5.96	24.80	46.00	-21.20	peak	
5	662.4400	31.98	-5.10	26.88	46.00	-19.12	peak	
6	* 860.3200	30.95	-2.82	28.13	46.00	-17.87	peak	

Test Mode: UNII-1/TX A Mode 5200MHz

Vertical



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	*	74.6200	39.80	-16.57	23.23	40.00	-16.77	peak	
2		138.6400	32.40	-13.15	19.25	43.50	-24.25	peak	
3		297.7200	30.48	-11.03	19.45	46.00	-26.55	peak	
4		432.5500	31.28	-8.94	22.34	46.00	-23.66	peak	
5		644.0100	30.01	-5.49	24.52	46.00	-21.48	peak	
6		802.1200	30.02	-2.90	27.12	46.00	-18.88	peak	


Test Mode: UNII-1/TX A Mode 5200MHz

Horizontal



No. Mk.	Freq. MHz	Reading Level	Correct Factor	Measure- ment	Limit	Over	Detector	Comment
		dBuV	dB	dBuV/m	dBuV/m	dB		
1	71.7100	37.03	-16.38	20.65	40.00	-19.35	peak	
2	182.2900	31.67	-13.31	18.36	43.50	-25.14	peak	
3	290.9300	30.31	-11.16	19.15	46.00	-26.85	peak	
4	426.7300	29.60	-9.04	20.56	46.00	-25.44	peak	
5	662.4400	31.48	-5.10	26.38	46.00	-19.62	peak	
6 *	802.1200	30.26	-2.90	27.36	46.00	-18.64	peak	

Test Mode: UNII-1/TX A Mode 5240MHz



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector Comment
1	*	74.6200	40.30	-16.57	23.73	40.00	-16.27	peak
2		132.8200	33.33	-13.09	20.24	43.50	-23.26	peak
3		297.7200	29.48	-11.03	18.45	46.00	-27.55	peak
4		480.0800	31.53	-9.76	21.77	46.00	-24.23	peak
5		660.5000	30.18	-5.10	25.08	46.00	-20.92	peak
6		802.1200	30.02	-2.90	27.12	46.00	-18.88	peak

Test Mode: UNII-1/TX A Mode 5240MHz

Horizontal



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		71.7100	36.03	-16.38	19.65	40.00	-20.35	peak	
2		182.2900	30.67	-13.31	17.36	43.50	-26.14	peak	
3		373.3800	30.22	-10.74	19.48	46.00	-26.52	peak	
4		529.5500	30.08	-8.99	21.09	46.00	-24.91	peak	
5		662.4400	31.48	-5.10	26.38	46.00	-19.62	peak	
6	*	802.1200	30.26	-2.90	27.36	46.00	-18.64	peak	

Test Mode: UNII-2A/TX A Mode 5260MHz


Vertical



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	*	74.6200	40.30	-16.57	23.73	40.00	-16.27	peak	
2		132.8200	33.33	-13.09	20.24	43.50	-23.26	peak	
3		285.1100	30.80	-11.73	19.07	46.00	-26.93	peak	
4		451.9500	30.40	-8.70	21.70	46.00	-24.30	peak	
5		590.6600	30.85	-7.91	22.94	46.00	-23.06	peak	
6		753.6200	30.64	-4.50	26.14	46.00	-19.86	peak	

Test Mode: UNII-2A/TX A Mode 5260MHz


Horizontal



No. Mk.	Freq. MHz	Reading Level	Correct Factor	Measure- ment	Limit	Over	Detector	Comment
		dBuV	dB	dBuV/m	dBuV/m	dB		
1 *	71.7100	37.03	-16.38	20.65	40.00	-19.35	peak	
2	182.2900	31.67	-13.31	18.36	43.50	-25.14	peak	
3	290.9300	31.31	-11.16	20.15	46.00	-25.85	peak	
4	447.1000	29.57	-8.67	20.90	46.00	-25.10	peak	
5	655.6500	31.45	-5.13	26.32	46.00	-19.68	peak	
6	754.5900	29.85	-4.47	25.38	46.00	-20.62	peak	

Test Mode: UNII-2A/TX A Mode 5300MHz

Vertical



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	*	74.6200	40.30	-16.57	23.73	40.00	-16.27	peak	
2		132.8200	33.33	-13.09	20.24	43.50	-23.26	peak	
3		259.8900	31.01	-13.79	17.22	46.00	-28.78	peak	
4		432.5500	30.78	-8.94	21.84	46.00	-24.16	peak	
5		590.6600	30.85	-7.91	22.94	46.00	-23.06	peak	
6		783.6900	30.52	-3.45	27.07	46.00	-18.93	peak	


Test Mode: UNII-2A/TX A Mode 5300MHz

Horizontal



No. Mk.	Freq. MHz	Reading Level	Correct Factor	Measure- ment	Limit	Over	Detector	Comment
		dBuV	dB	dBuV/m	dBuV/m	dB		
1	71.7100	36.03	-16.38	19.65	40.00	-20.35	peak	
2	182.2900	31.67	-13.31	18.36	43.50	-25.14	peak	
3	373.3800	30.22	-10.74	19.48	46.00	-26.52	peak	
4	560.5900	30.18	-7.92	22.26	46.00	-23.74	peak	
5	723.5500	30.83	-4.78	26.05	46.00	-19.95	peak	
6 *	920.4600	30.03	-0.99	29.04	46.00	-16.96	peak	

Test Mode: UNII-2A/TX A Mode 5320MHz



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	*	74.6200	40.30	-16.57	23.73	40.00	-16.27	peak	
2		132.8200	32.33	-13.09	19.24	43.50	-24.26	peak	
3		285.1100	29.80	-11.73	18.07	46.00	-27.93	peak	
4		432.5500	30.78	-8.94	21.84	46.00	-24.16	peak	
5		611.0300	31.06	-7.30	23.76	46.00	-22.24	peak	
6		770.1100	30.30	-3.93	26.37	46.00	-19.63	peak	

Test Mode: UNII-2A/TX A Mode 5320MHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBm	dB	dBm	dB	Detector	Comment
1		71.7100	35.53	-16.38	19.15	40.00	-20.85	peak
2		182.2900	31.67	-13.31	18.36	43.50	-25.14	peak
3		290.9300	31.31	-11.16	20.15	46.00	-25.85	peak
4		450.0100	29.97	-8.62	21.35	46.00	-24.65	peak
5		635.2800	31.26	-5.96	25.30	46.00	-20.70	peak
6	*	802.1200	30.76	-2.90	27.86	46.00	-18.14	peak

Test Mode: UNII-2C/TX A Mode 5500MHz

Vertical



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	*	74.6200	39.30	-16.57	22.73	40.00	-17.27	peak	
2		165.8000	32.03	-13.22	18.81	43.50	-24.69	peak	
3		355.9200	31.07	-11.53	19.54	46.00	-26.46	peak	
4		517.9100	31.58	-9.60	21.98	46.00	-24.02	peak	
5		699.3000	30.82	-4.93	25.89	46.00	-20.11	peak	
6		830.2500	28.79	-3.05	25.74	46.00	-20.26	peak	

Test Mode: UNII-2C/TX A Mode 5500MHz

Horizontal



No. Mk.	Freq. MHz	Reading Level	Correct Factor	Measure- ment	Limit	Over	Detector	Comment
		dBuV	dB	dBuV/m	dBuV/m	dB		
1	71.7100	37.03	-16.38	20.65	40.00	-19.35	peak	
2	182.2900	31.67	-13.31	18.36	43.50	-25.14	peak	
3	290.9300	31.31	-11.16	20.15	46.00	-25.85	peak	
4	447.1000	29.07	-8.67	20.40	46.00	-25.60	peak	
5	662.4400	30.98	-5.10	25.88	46.00	-20.12	peak	
6	* 802.1200	30.76	-2.90	27.86	46.00	-18.14	peak	

Test Mode: UNII-2C/TX A Mode 5580MHz

Vertical



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	*	74.6200	40.80	-16.57	24.23	40.00	-15.77	peak	
2		132.8200	34.33	-13.09	21.24	43.50	-22.26	peak	
3		283.1700	30.13	-11.94	18.19	46.00	-27.81	peak	
4		413.1500	30.28	-9.29	20.99	46.00	-25.01	peak	
5		559.6200	30.52	-7.93	22.59	46.00	-23.41	peak	
6		802.1200	29.52	-2.90	26.62	46.00	-19.38	peak	


Test Mode: UNII-2C/TX A Mode 5580MHz

Horizontal



No. Mk.	Freq. MHz	Reading Level	Correct Factor	Measure- ment	Limit	Over	Comment
		dBuV	dB	dBuV/m	dBuV/m	dB	
1	71.7100	36.03	-16.38	19.65	40.00	-20.35	peak
2	182.2900	31.67	-13.31	18.36	43.50	-25.14	peak
3	290.9300	30.31	-11.16	19.15	46.00	-26.85	peak
4	434.4900	30.33	-8.90	21.43	46.00	-24.57	peak
5	607.1500	31.71	-7.52	24.19	46.00	-21.81	peak
6 *	756.5300	30.32	-4.40	25.92	46.00	-20.08	peak

Test Mode: UNII-2C/TX A Mode 5700MHz



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	*	74.6200	39.80	-16.57	23.23	40.00	-16.77	peak	
2		132.8200	32.33	-13.09	19.24	43.50	-24.26	peak	
3		290.9300	29.76	-11.16	18.60	46.00	-27.40	peak	
4		413.1500	28.78	-9.29	19.49	46.00	-26.51	peak	
5		545.0700	30.01	-8.19	21.82	46.00	-24.18	peak	
6		699.3000	30.82	-4.93	25.89	46.00	-20.11	peak	

Test Mode: UNII-2C/TX A Mode 5700MHz

Horizontal



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		71.7100	37.03	-16.38	20.65	40.00	-19.35	peak	
2		182.2900	31.67	-13.31	18.36	43.50	-25.14	peak	
3		290.9300	31.31	-11.16	20.15	46.00	-25.85	peak	
4		411.2100	29.69	-9.33	20.36	46.00	-25.64	peak	
5		655.6500	30.95	-5.13	25.82	46.00	-20.18	peak	
6	*	802.1200	30.76	-2.90	27.86	46.00	-18.14	peak	

Test Mode: UNII-3/TX A Mode 5745MHz

Vertical



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	*	74.6200	39.80	-16.57	23.23	40.00	-16.77	peak	
2		132.8200	33.33	-13.09	20.24	43.50	-23.26	peak	
3		317.1200	30.50	-11.27	19.23	46.00	-26.77	peak	
4		432.5500	30.78	-8.94	21.84	46.00	-24.16	peak	
5		671.1700	31.73	-5.06	26.67	46.00	-19.33	peak	
6		830.2500	30.79	-3.05	27.74	46.00	-18.26	peak	

Test Mode: UNII-3/TX A Mode 5745MHz

Horizontal



No. Mk.	Freq. MHz	Reading Level	Correct Factor	Measure- ment	Limit	Over	Detector	Comment
		dBuV	dB	dBuV/m	dBuV/m	dB		
1	71.7100	37.03	-16.38	20.65	40.00	-19.35	peak	
2	131.8500	30.73	-13.08	17.65	43.50	-25.85	peak	
3	283.1700	30.53	-11.94	18.59	46.00	-27.41	peak	
4	411.2100	30.19	-9.33	20.86	46.00	-25.14	peak	
5	635.2800	30.26	-5.96	24.30	46.00	-21.70	peak	
6 *	756.5300	31.32	-4.40	26.92	46.00	-19.08	peak	

Test Mode: UNII-3/TX A Mode 5785MHz

Vertical



No. Mk.	Freq. MHz	Reading Level	Correct Factor	Measure- ment	Limit	Over	Detector	Comment
		dBuV	dB	dBuV/m	dBuV/m	dB		
1	74.6200	38.30	-16.57	21.73	40.00	-18.27	peak	
2	191.0200	33.57	-14.42	19.15	43.50	-24.35	peak	
3	304.5100	30.96	-11.07	19.89	46.00	-26.11	peak	
4	559.6200	31.52	-7.93	23.59	46.00	-22.41	peak	
5	671.1700	31.23	-5.06	26.17	46.00	-19.83	peak	
6 *	909.7900	30.30	-1.27	29.03	46.00	-16.97	peak	


Test Mode: UNII-3/TX A Mode 5785MHz

Horizontal



No. Mk.	Freq. MHz	Reading Level	Correct Factor	Measure- ment	Limit	Over	Detector	Comment
		dBuV	dB	dBuV/m	dBuV/m	dB		
1	71.7100	37.03	-16.38	20.65	40.00	-19.35	peak	
2	182.2900	31.67	-13.31	18.36	43.50	-25.14	peak	
3	396.6600	30.62	-9.68	20.94	46.00	-25.06	peak	
4	577.0800	30.19	-7.92	22.27	46.00	-23.73	peak	
5	662.4400	30.98	-5.10	25.88	46.00	-20.12	peak	
6 *	894.2700	31.09	-1.72	29.37	46.00	-16.63	peak	

Test Mode: UNII-3/TX A Mode 5825MHz



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	*	74.6200	40.30	-16.57	23.73	40.00	-16.27	peak	
2		132.8200	33.33	-13.09	20.24	43.50	-23.26	peak	
3		278.3200	29.25	-12.45	16.80	46.00	-29.20	peak	
4		432.5500	30.78	-8.94	21.84	46.00	-24.16	peak	
5		611.0300	30.56	-7.30	23.26	46.00	-22.74	peak	
6		753.6200	30.64	-4.50	26.14	46.00	-19.86	peak	

Test Mode: UNII-3/TX A Mode 5825MHz


Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		71.7100	36.03	-16.38	19.65	40.00	-20.35	peak	
2		182.2900	30.67	-13.31	17.36	43.50	-26.14	peak	
3		305.4800	29.78	-11.07	18.71	46.00	-27.29	peak	
4		529.5500	29.58	-8.99	20.59	46.00	-25.41	peak	
5		756.5300	31.32	-4.40	26.92	46.00	-19.08	peak	
6	*	894.2700	31.09	-1.72	29.37	46.00	-16.63	peak	


ATTACHMENT D - RADIATED EMISSION (ABOVE 1000MHZ)

Orthogonal Axis:	X
Test Mode:	UNII-1/ TX A Mode 5180MHz



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		5150.000	13.01	39.00	52.01	68.30	-16.29	peak	
2		5150.000	2.86	39.00	41.86	54.00	-12.14	AVG	
3	*	5185.000	50.01	39.12	89.13	54.00	35.13	AVG	No Limit
4	X	5186.000	59.77	39.12	98.89	68.30	30.59	peak	No Limit


Orthogonal Axis:	X
Test Mode:	UNII-1/ TX A Mode 5180MHz

Vertical

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Comment
			Level	Factor	ment			
1		10359.16	38.69	11.11	49.80	68.30	-18.50	peak
2	*	10360.32	28.15	11.10	39.25	54.00	-14.75	AVG


Orthogonal Axis:	X
Test Mode:	UNII-1/ TX A Mode 5180MHz

Horizontal



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		5150.000	11.97	39.00	50.97	68.30	-17.33	peak	
2		5150.000	1.73	39.00	40.73	54.00	-13.27	AVG	
3	X	5182.800	58.77	39.11	97.88	68.30	29.58	peak	No Limit
4	*	5185.000	49.60	39.12	88.72	54.00	34.72	AVG	No Limit


Orthogonal Axis:	X
Test Mode:	UNII-1/ TX A Mode 5180MHz

Horizontal

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Comment
			Level	Factor	ment			
1	*	10360.24	26.88	11.10	37.98	54.00	-16.02	AVG
2		10360.64	36.50	11.10	47.60	68.30	-20.70	peak


Orthogonal Axis:	X
Test Mode:	UNII-1/ TX A Mode 5200MHz

Vertical




No.	Mk.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
		Freq.	Level	Factor				
		MHz	dBuV	dB	dBuV/m	dB		
1	X	5195.800	58.79	39.15	97.94	68.30	29.64	peak No Limit
2	*	5205.000	49.97	39.18	89.15	54.00	35.15	AVG No Limit

Orthogonal Axis:	X
Test Mode:	UNII-1/ TX A Mode 5200MHz

Vertical

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
1	*	10399.72	28.84	11.05	39.89	54.00	-14.11	AVG	
2		10400.40	38.38	11.05	49.43	68.30	-18.87	peak	

Orthogonal Axis:	X
Test Mode:	UNII-1/ TX A Mode 5200MHz

Horizontal


No.	Mk.	Reading		Correct Factor	Measure- ment	Limit	Over	Comment
		MHz	Level	dBuV	dB	dBuV/m	dB	Detector
1	X	5194.300	59.13	39.15	98.28	68.30	29.98	peak No Limit
2	*	5207.400	50.44	39.19	89.63	54.00	35.63	AVG No Limit

Orthogonal Axis:	X
Test Mode:	UNII-1/ TX A Mode 5200MHz

Horizontal

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Comment
			Level	Factor	ment			
1	*	10400.24	26.78	11.05	37.83	54.00	-16.17	AVG
2		10400.36	36.97	11.05	48.02	68.30	-20.28	peak

Orthogonal Axis:	X
Test Mode:	UNII-1/ TX A Mode 5240MHz

Vertical


No.	Mk.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
		Freq.	Level	Factor				
		MHz	dBuV	dB	dBuV/m	dB		
1	*	5232.800	47.73	39.27	87.00	54.00	33.00	AVG No Limit
2	X	5241.500	56.54	39.30	95.84	68.30	27.54	peak No Limit

Orthogonal Axis:	X
Test Mode:	UNII-1/ TX A Mode 5240MHz

Vertical


No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Comment
			Level	Factor	ment			
1	*	10480.28	26.63	10.94	37.57	54.00	-16.43	AVG
2		10480.72	36.76	10.94	47.70	68.30	-20.60	peak

Orthogonal Axis:	X
Test Mode:	UNII-1/ TX A Mode 5240MHz

Horizontal

No.	Mk.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
		Freq.	Level	Factor				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1	*	5232.800	51.15	39.27	90.42	54.00	36.42	AVG No Limit
2	X	5246.700	59.93	39.32	99.25	68.30	30.95	peak No Limit


Orthogonal Axis:	X
Test Mode:	UNII-1/ TX A Mode 5240MHz

Horizontal

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Comment
			Level	Factor	ment			
1		10479.40	37.38	10.94	48.32	68.30	-19.98	peak
2	*	10479.56	26.50	10.94	37.44	54.00	-16.56	AVG

Orthogonal Axis:	X
Test Mode:	UNII-1/ TX N20 Mode 5180MHz

Vertical



No.	Mk.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
		Freq.	Level	Factor				
		MHz	dBuV	dB	dBuV/m	dB		
1		5150.000	15.98	39.00	54.98	68.30	-13.32	peak
2		5150.000	5.21	39.00	44.21	54.00	-9.79	AVG
3	X	5185.800	59.96	39.12	99.08	68.30	30.78	peak No Limit
4	*	5187.400	51.15	39.12	90.27	54.00	36.27	AVG No Limit


Orthogonal Axis:	X
Test Mode:	UNII-1/ TX N20 Mode 5180MHz

Vertical

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Comment
			Level	Factor	ment			
1	*	10360.18	28.65	11.10	39.75	54.00	-14.25	AVG
2		10361.58	40.26	11.10	51.36	68.30	-16.94	peak

Orthogonal Axis:	X
Test Mode:	UNII-1/ TX N20 Mode 5180MHz

Horizontal




No.	Mk.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
		Freq.	Level	Factor				
		MHz	dBuV	dB	dBuV/m	dB		
1		5150.000	14.94	39.00	53.94	68.30	-14.36	peak
2		5150.000	3.82	39.00	42.82	54.00	-11.18	AVG
3	*	5175.000	50.00	39.08	89.08	54.00	35.08	AVG
4	X	5186.200	59.47	39.12	98.59	68.30	30.29	peak
								No Limit

Orthogonal Axis:	X
Test Mode:	UNII-1/ TX N20 Mode 5180MHz

Horizontal


No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Comment
			Level	Factor	ment			
1	*	10359.56	26.52	11.10	37.62	54.00	-16.38	AVG
2		10360.20	36.99	11.10	48.09	68.30	-20.21	peak

Orthogonal Axis:	X
Test Mode:	UNII-1/ TX N20 Mode 5200MHz

Vertical


No.	Mk.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
		Freq.	Level	Factor				
		MHz	dBuV	dB	dBuV/m	dB		
1	X	5205.000	60.15	39.18	99.33	68.30	31.03	peak No Limit
2	*	5207.400	50.57	39.19	89.76	54.00	35.76	AVG No Limit

Orthogonal Axis:	X
Test Mode:	UNII-1/ TX N20 Mode 5200MHz

Vertical


No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Comment
			Level	Factor	ment			
1		10399.36	37.33	11.05	48.38	68.30	-19.92	peak
2	*	10400.18	26.63	11.05	37.68	54.00	-16.32	AVG

Orthogonal Axis:	X
Test Mode:	UNII-1/ TX N20 Mode 5200MHz

Horizontal


No.	Mk.	Reading		Correct Factor	Measure- ment	Limit	Over	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	Detector	Comment
1	X	5204.200	58.10	39.18	97.28	68.30	28.98	peak No Limit
2	*	5207.600	49.44	39.19	88.63	54.00	34.63	AVG No Limit

Orthogonal Axis:	X
Test Mode:	UNII-1/ TX N20 Mode 5200MHz

Horizontal


No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Comment
			Level	Factor	ment			
1		10400.02	36.91	11.05	47.96	68.30	-20.34	peak
2	*	10400.28	26.77	11.05	37.82	54.00	-16.18	AVG

Orthogonal Axis:	X
Test Mode:	UNII-1/ TX N20 Mode 5240MHz

Vertical


No.	Mk.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
		Freq.	Level	Factor				
		MHz	dBuV	dB	dBuV/m	dB		
1	*	5245.000	50.76	39.31	90.07	54.00	36.07	AVG No Limit
2	X	5246.400	60.49	39.32	99.81	68.30	31.51	peak No Limit

Orthogonal Axis:	X
Test Mode:	UNII-1/ TX N20 Mode 5240MHz

Vertical


No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Comment
			Level	Factor	ment			
1		10479.18	36.51	10.94	47.45	68.30	-20.85	peak
2	*	10480.38	26.46	10.94	37.40	54.00	-16.60	AVG

Orthogonal Axis:	X
Test Mode:	UNII-1/ TX N20 Mode 5240MHz

Horizontal

No.	Mk.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
		Freq.	Level	Factor				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1	X	5244.300	57.45	39.31	96.76	68.30	28.46	peak No Limit
2	*	5245.000	48.66	39.31	87.97	54.00	33.97	AVG No Limit


Orthogonal Axis:	X
Test Mode:	UNII-1/ TX N20 Mode 5240MHz

Horizontal

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Comment
			Level	Factor	ment			
1		10479.26	36.65	10.94	47.59	68.30	-20.71	peak
2	*	10480.34	26.64	10.94	37.58	54.00	-16.42	AVG

Orthogonal Axis:	X
Test Mode:	UNII-1/ TX N40 Mode 5190MHz

Vertical



No.	Mk.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
		Freq.	Level	Factor				
		MHz	dBuV	dB	dBuV/m	dB		
1		5150.000	22.56	39.00	61.56	68.30	-6.74	peak
2		5150.000	10.61	39.00	49.61	54.00	-4.39	AVG
3	X	5173.600	53.62	39.07	92.69	68.30	24.39	peak No Limit
4	*	5202.600	43.58	39.17	82.75	54.00	28.75	AVG No Limit


Orthogonal Axis:	X
Test Mode:	UNII-1/ TX N40 Mode 5190MHz

Vertical

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Comment
			Level	Factor	ment			
1		10378.15	36.49	11.08	47.57	68.30	-20.73	peak
2	*	10380.52	26.45	11.08	37.53	54.00	-16.47	AVG

Orthogonal Axis:	X
Test Mode:	UNII-1/ TX N40 Mode 5190MHz

Horizontal




No.	Mk.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
		Freq.	Level	Factor				
		MHz	dBuV	dB	dBuV/m	dB		
1		5150.000	25.09	39.00	64.89	68.30	-4.21	peak
2		5150.000	10.28	39.00	49.28	54.00	-4.72	AVG
3	X	5186.600	55.05	39.12	94.17	68.30	25.87	peak No Limit
4	*	5187.600	45.28	39.13	84.41	54.00	30.41	AVG No Limit

Orthogonal Axis:	X
Test Mode:	UNII-1/ TX N40 Mode 5190MHz

Horizontal

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
1	*	10379.64	27.51	11.08	38.59	54.00	-15.41	AVG	
2		10380.52	38.62	11.08	49.70	68.30	-18.60	peak	

Orthogonal Axis:	X
Test Mode:	UNII-1/ TX N40 Mode 5230MHz

Vertical


No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Comment
			Level	Factor	ment			
		MHz	dBuV	dB	dBuV/m	dB	Detector	
1	X	5217.400	60.01	39.22	99.23	68.30	30.93	peak No Limit
2	*	5218.800	50.16	39.23	89.39	54.00	35.39	AVG No Limit

Orthogonal Axis:	X
Test Mode:	UNII-1/ TX N40 Mode 5230MHz

Vertical


No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Comment
			Level	Factor	ment			
1	*	10459.70	26.20	10.96	37.16	54.00	-16.84	AVG
2		10459.90	36.40	10.96	47.36	68.30	-20.94	peak

Orthogonal Axis:	X
Test Mode:	UNII-1/ TX N40 Mode 5230MHz

Horizontal


No.	Mk.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
		Freq.	Level	Factor				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1	*	5218.600	47.80	39.23	87.03	54.00	33.03	AVG No Limit
2	X	5240.000	57.48	39.29	96.77	68.30	28.47	peak No Limit

Orthogonal Axis:	X
Test Mode:	UNII-1/ TX N40 Mode 5230MHz

Horizontal


No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Comment
			Level	Factor	ment			
1		10459.78	36.63	10.96	47.59	68.30	-20.71	peak
2	*	10459.78	26.35	10.96	37.31	54.00	-16.69	AVG

Orthogonal Axis :	X
Test Mode :	UNII-2A/ TX A Mode 5260MHz

Vertical

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
			MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1	*	5255.200	47.30	39.35	86.65	54.00	32.65	AVG	No Limit
2	X	5256.700	55.67	39.35	95.02	68.30	26.72	peak	No Limit


Orthogonal Axis :	X
Test Mode :	UNII-2A/ TX A Mode 5260MHz

Vertical

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Comment
			Level	Factor	ment			
1		10519.40	38.75	10.92	49.67	68.30	-18.63	peak
2	*	10520.15	26.98	10.92	37.90	54.00	-16.10	AVG


Orthogonal Axis : X

Test Mode : UNII-2A/ TX A Mode 5260MHz

Horizontal

No.	Mk.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
		Freq.	Level	Factor				
			MHz	dBuV	dB	dBuV/m	dB	
1	X	5252.800	58.50	39.34	97.84	68.30	29.54	peak No Limit
2	*	5255.000	48.86	39.35	88.21	54.00	34.21	AVG No Limit


Orthogonal Axis :	X
Test Mode :	UNII-2A/ TX A Mode 5260MHz

Horizontal

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Comment
			Level	Factor	ment			
1		10519.00	37.75	10.92	48.67	68.30	-19.63	peak
2	*	10519.85	27.02	10.92	37.94	54.00	-16.06	AVG


Orthogonal Axis : X

Test Mode : UNII-2A/ TX A Mode 5300MHz

Vertical


No.	Mk.	Reading		Correct Factor	Measure- ment	Limit	Over	Detector	Comment
		Freq.	Level						
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	X	5302.900	55.04	39.51	94.55	68.30	26.25	peak	No Limit
2	*	5307.500	46.54	39.52	86.06	54.00	32.06	AVG	No Limit

Orthogonal Axis :	X
Test Mode :	UNII-2A/ TX A Mode 5300MHz

Vertical

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Comment
			Level	Factor	ment			
1		10598.15	38.53	11.00	49.53	68.30	-18.77	peak
2	*	10598.75	26.65	11.00	37.65	54.00	-16.35	AVG

Orthogonal Axis :	X
Test Mode :	UNII-2A/ TX A Mode 5300MHz

Horizontal

No.	Mk.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
		Freq.	Level	Factor				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1	*	5296.100	50.21	39.49	89.70	54.00	35.70	AVG No Limit
2	X	5300.800	59.33	39.50	98.83	68.30	30.53	peak No Limit

Orthogonal Axis :	X
Test Mode :	UNII-2A/ TX A Mode 5300MHz


Horizontal

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
1	*	10600.55	26.73	11.00	37.73	54.00	-16.27	AVG	
2		10600.70	37.40	11.00	48.40	68.30	-19.90	peak	

Orthogonal Axis : X


Test Mode : UNII-2A/ TX A Mode 5320MHz

Vertical



No.	Mk.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
		Freq.	Level	Factor				
		MHz	dBuV	dB	dBuV/m	dB		
1	*	5312.800	48.45	39.54	87.99	54.00	33.99	AVG No Limit
2	X	5318.400	57.50	39.56	97.06	68.30	28.76	peak No Limit
3		5350.000	13.94	39.66	53.60	68.30	-14.70	peak
4		5350.000	2.20	39.66	41.86	54.00	-12.14	AVG


Orthogonal Axis :	X
Test Mode :	UNII-2A/ TX A Mode 5320MHz

Vertical

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Comment
			Level	Factor	ment			
1		10638.70	37.59	11.04	48.63	68.30	-19.67	peak
2	*	10639.35	26.95	11.04	37.99	54.00	-16.01	AVG

Orthogonal Axis : X

Test Mode : UNII-2A/ TX A Mode 5320MHz

Horizontal

No.	Mk.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
		Freq.	Level	Factor				
		MHz	dBuV	dB	dBuV/m	dB		
1	*	5312.700	51.03	39.54	90.57	54.00	36.57	AVG No Limit
2	X	5326.300	60.03	39.58	99.61	68.30	31.31	peak No Limit
3		5350.000	17.78	39.66	57.44	68.30	-10.86	peak
4		5350.000	5.61	39.66	45.27	54.00	-8.73	AVG


Orthogonal Axis :	X
Test Mode :	UNII-2A/ TX A Mode 5320MHz

Horizontal

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Comment
			Level	Factor	ment			
1		10639.15	39.22	11.04	50.26	68.30	-18.04	peak
2	*	10639.30	26.85	11.04	37.89	54.00	-16.11	AVG


Orthogonal Axis : X

Test Mode : UNII-2A/ TX N20 Mode 5260MHz

Vertical

No.	Mk.	Reading Level	Correct Factor	Measure- ment	Limit	Over		
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	*	5252.500	49.20	39.34	88.54	54.00	34.54	AVG No Limit
2	X	5264.500	58.24	39.38	97.62	68.30	29.32	peak No Limit


Orthogonal Axis :	X
Test Mode :	UNII-2A/ TX N20 Mode 5260MHz

Vertical

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Comment
			Level	Factor	ment			
1		10518.57	36.75	10.92	47.67	68.30	-20.63	peak
2	*	10519.82	26.02	10.92	36.94	54.00	-17.06	AVG

Orthogonal Axis : X

Test Mode : UNII-2A/ TX N20 Mode 5260MHz

Horizontal

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	X	5265.500	59.03	39.39	98.42	68.30	30.12	peak	No Limit
2	*	5267.400	48.75	39.39	88.14	54.00	34.14	AVG	No Limit

Orthogonal Axis : X


Test Mode : UNII-2A/ TX N20 Mode 5260MHz

Horizontal

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Comment
			Level	Factor	ment			
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		10519.57	39.75	10.92	50.67	68.30	-17.63	peak
2	*	10520.63	27.97	10.93	38.90	54.00	-15.10	AVG


Orthogonal Axis : X

Test Mode : UNII-2A/ TX A Mode 5300MHz

Vertical

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Comment
			Level	Factor	ment			
		MHz	dBuV	dB	dBuV/m	dB	Detector	
1	X	5304.700	57.15	39.51	96.66	68.30	28.36	peak No Limit
2	*	5304.800	48.11	39.51	87.62	54.00	33.62	AVG No Limit


Orthogonal Axis :	X
Test Mode :	UNII-2A/ TX A Mode 5300MHz

Vertical

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Comment
			Level	Factor	ment			
1	*	10601.52	28.72	11.01	39.73	54.00	-14.27	AVG
2		10602.60	39.39	11.01	50.40	68.30	-17.90	peak


Orthogonal Axis : X

Test Mode : UNII-2A/ TX A Mode 5300MHz

Horizontal

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Comment
			Level	Factor	ment			
		MHz	dBuV	dB	dBuV/m	dB	Detector	
1	X	5300.000	60.17	39.50	99.67	68.30	31.37	peak No Limit
2	*	5303.800	50.56	39.50	90.06	54.00	36.06	AVG No Limit


Orthogonal Axis :	X
Test Mode :	UNII-2A/ TX A Mode 5300MHz

Horizontal

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	
			Level	Factor	ment			
		MHz	dBuV	dB	dBuV/m	dB	Detector	Comment
1	*	10598.38	28.65	11.00	39.65	54.00	-14.35	AVG
2		10598.46	36.53	11.00	47.53	68.30	-20.77	peak


Orthogonal Axis : X

Test Mode : UNII-2A/ TX N20 Mode 5320MHz

Vertical

No.	Mk.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
		Freq.	Level	Factor				
		MHz	dBuV	dB	dBuV/m	dB		
1	*	5315.300	48.16	39.55	87.71	54.00	33.71	AVG No Limit
2	X	5315.800	58.18	39.55	97.73	68.30	29.43	peak No Limit
3		5350.000	16.26	39.66	55.92	68.30	-12.38	peak
4		5350.000	4.31	39.66	43.97	54.00	-10.03	AVG


Orthogonal Axis :	X
Test Mode :	UNII-2A/ TX N20 Mode 5320MHz

Vertical

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Comment
			Level	Factor	ment			
1		10639.54	37.22	11.04	48.26	68.30	-20.04	peak
2	*	10639.87	26.17	11.04	37.21	54.00	-16.79	AVG

Orthogonal Axis : X

Test Mode : UNII-2A/ TX N20 Mode 5320MHz

Horizontal

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dB			
1	X	5324.900	60.07	39.58	99.65	68.30	31.35	peak	No Limit
2	*	5327.600	51.02	39.59	90.61	54.00	36.61	AVG	No Limit
3		5350.000	20.32	39.66	59.98	68.30	-8.32	peak	
4		5350.000	6.45	39.66	46.11	54.00	-7.89	AVG	


Orthogonal Axis :	X
Test Mode :	UNII-2A/ TX N20 Mode 5320MHz

Horizontal

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Comment
			Level	Factor	ment			
1	*	10637.63	28.17	11.04	39.21	54.00	-14.79	AVG
2		10638.46	38.48	11.04	49.52	68.30	-18.78	peak

Orthogonal Axis : X

Test Mode : UNII-2A/ TX N40 Mode 5270MHz

Vertical

No.	Mk.	Reading		Correct Factor	Measure- ment	Limit	Over	Detector	Comment
		Freq.	Level						
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	X	5278.400	56.77	39.42	96.19	68.30	27.89	peak	No Limit
2	*	5278.800	46.04	39.42	85.46	54.00	31.46	AVG	No Limit


Orthogonal Axis :	X
Test Mode :	UNII-2A/ TX N40 Mode 5270MHz

Vertical

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Comment
			Level	Factor	ment			
1	*	10540.00	26.19	10.95	37.14	54.00	-16.86	AVG
2		10540.08	36.49	10.95	47.44	68.30	-20.86	peak


Orthogonal Axis : X

Test Mode : UNII-2A/ TX N40 Mode 5270MHz

Horizontal

No.	Mk.	Reading		Correct Factor	Measure-ment		Limit	Over
		Freq.	Level		dB	dBuV/m		
		MHz	dBuV			Detector	Comment	
1	X	5277.000	55.15	39.42	94.57	68.30	26.27	peak No Limit
2	*	5281.200	45.13	39.43	84.56	54.00	30.56	AVG No Limit


Orthogonal Axis :	X
Test Mode :	UNII-2A/ TX N40 Mode 5270MHz

Horizontal

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Comment
			Level	Factor	ment			
1	*	10540.78	25.91	10.95	36.86	54.00	-17.14	AVG
2		10541.16	34.80	10.95	45.75	68.30	-22.55	peak


Orthogonal Axis : X

Test Mode : UNII-2A/ TX N40 Mode 5310MHz

Vertical

No.	Mk.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
		Freq.	Level	Factor				
		MHz	dBuV	dB	dBuV/m	dB		
1	*	5298.800	43.11	39.50	82.61	54.00	28.61	AVG No Limit
2	X	5305.800	54.60	39.51	94.11	68.30	25.81	peak No Limit
3		5350.000	20.02	39.66	59.68	68.30	-8.62	peak
4		5350.000	8.81	39.66	48.47	54.00	-5.53	AVG


Orthogonal Axis :	X
Test Mode :	UNII-2A/ TX N40 Mode 5310MHz

Vertical

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
1	*	10619.80	26.86	11.02	37.88	54.00	-16.12	AVG	
2		10620.16	37.59	11.02	48.61	68.30	-19.69	peak	


Orthogonal Axis : X

Test Mode : UNII-2A/ TX N40 Mode 5310MHz

Horizontal

No.	Mk.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
		Freq.	Level	Factor				
		MHz	dBuV	dB	dBuV/m	dB		
1	*	5298.800	45.98	39.50	85.48	54.00	31.48	AVG No Limit
2	X	5323.200	55.98	39.57	95.55	68.30	27.25	peak No Limit
3		5350.000	24.49	39.66	64.15	68.30	-4.15	peak
4		5350.000	9.88	39.66	49.54	54.00	-4.46	AVG

Orthogonal Axis :	X
Test Mode :	UNII-2A/ TX N40 Mode 5310MHz


Horizontal

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Comment
			Level	Factor	ment			
1		10619.10	38.51	11.02	49.53	68.30	-18.77	peak
2	*	10619.60	26.93	11.02	37.95	54.00	-16.05	AVG

Orthogonal Axis : X

Test Mode : UNII-2C/ TX A Mode 5500MHz

Vertical



No.	Mk.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
		Freq.	Level	Factor				
		MHz	dBuV	dB	dBuV/m	dB		
1		5460.000	5.51	40.03	45.54	68.30	-22.76	peak
2		5460.000	-3.21	40.03	36.82	54.00	-17.18	AVG
3		5470.000	5.49	40.06	45.55	68.30	-22.75	peak
4		5470.000	-2.33	40.06	37.73	54.00	-16.27	AVG
5	X	5497.200	53.85	40.15	94.00	68.30	25.70	peak No Limit
6	*	5504.700	44.26	40.18	84.44	54.00	30.44	AVG No Limit

Orthogonal Axis :	X
Test Mode :	UNII-2C/ TX A Mode 5500MHz

Vertical

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Comment
			Level	Factor	ment			
1		11000.85	39.37	11.38	50.75	68.30	-17.55	peak
2	*	11000.85	27.16	11.38	38.54	54.00	-15.46	AVG