

# TEST REPORT

## 1. Applicant

Name : HIMS International Corporation  
Brand Name : E-bot ADV  
Address : 174, Gajeong-ro, Yuseong-gu, Daejeon, KOREA 305-350  
FCC ID : QJCEB100A

## 2. Products

Name : Electronic Magnifier (E-bot ADV)  
Model No. : EB100A  
Variant Model No. : EB100  
Manufacturer : HIMS International Corporation  
Address : 174, Gajeong-ro, Yuseong-gu, Daejeon, KOREA 305-350

3. Test Standard : 47 CFR Part 15, Subpart C

4. Test Method : ANSI C63.10-2009

5. Test Result : PASS

6. Dates of Test : March 01, 2014 to March 10, 2014

7. Date of Issue : March 18, 2014

8. Test Laboratory : Korea Standard Quality Laboratories  
FCC Designation Number : 100384


Tested by



KwangMin, Lee

Test Engineer:

Approved by



SooWook, Chae

Compliance Engineer:

*This report may not be reproduced without the full written consent of Korea Standard Quality Laboratories.*

## 1. Test Summary

Test	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10 2009	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 2009	PASS
Conducted Peak Output Power	47 CFR Part 15, Subpart C Section 15.247 (b)(3)	KDB558074 D01	PASS
6dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.247 (a)(2)	KDB558074 D01	PASS
Power Spectral Density	47 CFR Part 15, Subpart C Section 15.247 (e)	KDB558074 D01	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	KDB558074 D01	PASS
RF Conducted Spurious Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	KDB558074 D01	PASS
Radiated Spurious Emissions	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2009	PASS
Band Edge (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2009	PASS

## 2. TABLE OF CONTENTS

<b>1. Test Summary.....</b>	<b>2</b>
<b>2. Table of Contents.....</b>	<b>3</b>
<b>3. General Information.....</b>	<b>4</b>
3.1 Client Information.....	4
3.2 General Description of E.U.T.....	4
3.3 Details of E.U.T.....	4
3.4 Operation Frequency each of channel.....	5
3.5 Description of Support Units .....	5
3.6 Abnormalities from Standard Conditions.....	5
3.7 Other Information Requested by the Customer.....	5
3.8 Test Location.....	5
<b>4. Equipment Used during Test.....</b>	<b>6</b>
<b>5. Test Results and Measurement Data.....</b>	<b>7</b>
5.1 Antenna Requirement.....	7
5.2 Conducted Peak Output Power.....	8
5.3 6dB Occupy Bandwidth.....	17
5.4 Power Spectral Density.....	25
5.5 Band-edge for RF Conducted Emissions.....	33
5.6 RF Conducted Spurious Emissions.....	37
5.7 Radiated Spurious Emissions.....	44
5.7.1 Harmonic and other spurious emissions.....	48
5.7.1.1 Test at Lowest Channel in transmitting status(b mode).....	48
5.7.1.2 Test at middle Channel in transmitting status(b mode).....	51
5.7.1.3 Test at Highest Channel in transmitting status(b mode).....	54
5.7.1.4 Test at Lowest Channel in transmitting status(g mode).....	57
5.7.1.5 Test at Lowest Channel in transmitting status(g mode).....	60
5.7.1.6 Test at Lowest Channel in transmitting status(g mode).....	63
5.7.1.7 Test at Lowest Channel in transmitting status(n-20MHz mode).....	66
5.7.1.8 Test at middle Channel in transmitting status(n-20MHz mode).....	69
5.7.1.9 Test at Highest Channel in transmitting status(n-20MHz mode).....	72
5.8 Band Edge (Radiated Emission).....	75
5.9 Conducted Emissions at Mains Terminals 150 kHz to 30 MHz.....	84
5.9.1 Measurement Data.....	86
5.10 Radio Frequency Exposure Procedures.....	88
<b>** APPENDIX.....</b>	<b>90</b>

### 3. General Information

#### 3.1. Client Information

Applicant : HIMS International Corporation  
Address of Applicant : 174, Gajeong-ro, Yuseong-gu, Daejeon, KOREA 305-350

#### 3.2. General Description of E.U.T.

Product Name : Electronic Magnifier (E-bot ADV)  
Model No. : EB100A

#### 3.3. Details of E.U.T.

Operation Frequency:	802.11b/g/n(20MHz): 2412MHz to 2462MHz
Channel Numbers:	802.11b/g/n(20MHz): 11 Channels
Channel Separation:	5MHz
Type of Modulation:	802.11b: DSSS 802.11g/n(20MHz) : OFDM
Transfer Spacing:	802.11b: 11 / 5.5 / 2 / 1 Mbps 802.11g: 54 / 48 / 36 / 24 / 18 / 12 / 9 / 6 Mbps 802.11n(20MHz): MCS0-7, up to 65 Mbps
Antenna Type:	Integral antenna
Antenna Gain:	2.0dBi
Power Supply:	Adapter: AC 120V/60Hz, DC 12V Battery: DC 7.2V 5200mAh (Lithium Ion Battery)
Test Voltage:	DC 7.2V Battery fully charged Adapter: AC 120V/60Hz (Power Line Conducted Emission)

### 3.4. Operation Frequency each of channel

Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	5	2432MHz	9	2452MHz
2	2417MHz	6	2437MHz	10	2457MHz
3	2422MHz	7	2442MHz	11	2462MHz
4	2427MHz	8	2447MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The Lowest channel	2412MHz
The Middle channel	2437MHz
The Highest channel	2462MHz

### 3.5. Description of Support Units

The EUT has been tested with corresponding accessories as below:

Supplied by KSQ:

Description	Manufacturer	Model No.	Serial No.
NoteBook	SAMSUNG	NT-Q310-AS220	DP4193CQA00148F
USB Cable	-	-	-
Power Supply	ALINCO	DM-340MW	F001015
AC Adapter	DVE	DSA-36W-12 1 36	-

### 3.6. Abnormalities from Standard Conditions

None.

### 3.7. Other Information Requested by the Customer

None.

### 3.8. Test Location

#102, Jangduk Dong, Hwasung City, Kyunggi Do, South Korea

(FCC Designation Number : 100384)

This test site is in compliance with ISO/IEC 17025 for general requirements for the competence of testing and calibration laboratories.

#### 4. Equipment Used during Test

No.	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Next Cal. Data	Used equipment
1	EMI Test Receiver	LIG Nex1	LSA-265	L07098033	2013.12.20	2014.12.20	■
2	Bi-log Antenna	Schwarzbeck	VULB9160	3311	2013.10.16	2015.10.16	■
3	Turn Table	KEI	KEI-TURN	9210	N/A	N/A	■
4	Turn Table	KEI	KEI-TURN	N/A	N/A	N/A	■
5	Loop ANT.	Com-Power	AL-130	121010	2013.04.26	2015.04.25	■
6	Spectrum Analyzer	Agilent	E4440A	MY45304715	2014.02.14	2015.02.14	■
7	Function Generator	Agilent	33120A	US36026465	2013.06.08	2014.06.08	□
8	Frequency Counter	HP	5350B	3049A05530	2013.06.08	2014.06.08	■
9	Modulation Analyzer	Agilent	8901B	3438A05099	2013.06.08	2014.06.08	□
10	Audio Analyser	Agilent	8903B	3729A18576	2013.06.08	2014.06.08	□
11	Attenuator	Agilent	8494B	MY41110204	2013.06.08	2014.06.08	□
12	Attenuator	Agilent	8496B	US40152183	2013.06.08	2014.06.08	□
13	Attenuator	Agilent	8495B	3308A17660	2013.06.08	2014.06.08	□
14	Attenuator	TAE SUNG	SMA-2	N/A	2013.06.08	2014.06.08	□
15	Power Meter	Agilent	E4418B	GB43312894	2013.06.08	2014.06.08	□
16	Power Sensor	HP	8485A	3316A14708	2013.06.08	2014.06.08	□
17	Vibration Tester	Gana	GNV-400		2013.06.21	2014.06.21	□
18	Temp & Humidity Chamber	Seoksan Tech	SE-CT-02	S7400JD5340618	2013.06.08	2014.06.08	□
19	Signal Generator	Leader Electronics	3220	0137231	2013.06.08	2014.06.08	■
20	Oscilloscope	Tektronix	TDS-350	B031902	2013.06.08	2014.06.08	□
21	Drop Tester	Self-made	KSQ-01	N/A	N/A	N/A	□
22	Pre Amplifier	GTC	GA-1825A	GT0929/003	2013.06.08	2014.06.08	■
23	Continuous operation tester	GTC	CT-100	GT0929/001	N/A	N/A	□
24	CW Generator	HP	83711B	US34490158	2013.06.08	2014.06.08	■
25	POWER DIVIDER	Agilent	11636B	54381	2013.06.08	2014.06.08	□
26	Power Sensor	Agilent	8482B	N/A	2013.06.08	2014.06.08	□
27	Attenuator	Winswell	53-30-33	N/A	2013.06.08	2014.06.08	□
28	DC Power Supply	Hanil	HPS-505A	0606123	2013.06.08	2014.06.08	□
29	Slidacs	Hanchang	5KV	N/A	2013.06.08	2014.06.08	□
30	Termination	Kwang Yeok	KYTE-NJ-150W	2040004	2013.06.08	2014.06.08	□
31	Band-limited filter	MITECH	KSQ-02	N/A	2013.06.08	2014.06.08	□
32	Horn ANT.	SCHWARZBECK	BBHA 9120D	9120D-679	2012.07.12	2014.07.12	■
33	Horn ANT.	A.H. SYSTEMS	SAS-572	100284	2013.09.07	2015.09.07	■
34	DC Power Supply	ALINCO	DM-340MW	F001015	2013.06.08	2014.06.08	■
35	LISN	Electro Metrics	ANS-25/2	2535	2014.04.20	2015.05.20	■
36	LISN	Kyoritsu	KNW-407	8-1010-14	2013.06.08	2014.06.08	□
37	Pulse Limiter	LIG Nex1	EPL-30	N/A	2013.06.08	2014.06.08	■

## 5. Test Results and Measurement Data

### 5.1. Antenna Requirement

**Standard requirement: 47 CFR Part 15C Section 15.203 /247(c)**

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

**EUT Antenna**

**PASS**


The transmitter has an Integrated PCB antenna. The directional gain of the antenna is 2.0 dBi.  
please refer to the EUT internal photos.

## 5.2. Conducted Peak Output Power

Test Requirement: 47 CFR Part 15C Section 15.247 (b)(3)

Test Method: KDB558074 D01

### Test Configuration:



Test Instruments: Refer to section 4.10 for details

Exploratory Test Mode: Transmitting mode

Final Test Mode: Through Pre-scan, find the 11Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g ; 6.5Mbps of rate is the worst case of 802.11n(20MHz).

Limit: 30dBm

Test Results: Pass



Pre-scan under all rate at lowest channel 1								
Mode	802.11b							
Data Rate	1Mbps	2Mbps	5.5Mbps	11Mbps				
Power (dBm)	<b>15.13</b>	14.81	14.94	14.99				
Mode	802.11g							
Data Rate	6Mbps	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps
Power (dBm)	<b>15.89</b>	15.84	15.80	15.83	15.69	15.48	14.64	14.23
Mode	802.11n(20MHz)							
Data Rate	6.5Mbps	13Mbps	19.5Mbps	26Mbps	39Mbps	52Mbps	58.5Mbps	65Mbps
Power (dBm)	<b>15.73</b>	15.68	15.63	15.62	14.72	13.65	10.94	9.32
Through Pre-scan, 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(20MHz).								


## Measurement Data

802.11b mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	15.13	30.0	Pass
Middle	14.81	30.0	Pass
Highest	15.04	30.0	Pass
802.11g mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	15.89	30.0	Pass
Middle	15.11	30.0	Pass
Highest	15.13	30.0	Pass
802.11n(20MHz)mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	15.73	30.0	Pass
Middle	15.50	30.0	Pass
Highest	15.39	30.0	Pass


Result plot as follows:

Test mode: 802.11.b


Lowest Channel:



Middle Channel:




Highest Channel:




Result plot as follows:

Test mode: 802.11.g


Lowest Channel:



Middle Channel:




Highest Channel:




Result plot as follows:

Test mode: 802.11.n(20MHz)


Lowest Channel:



Middle Channel:



Highest Channel:






### 5.3. 6dB Occupy Bandwidth

Test Requirement: 47 CFR Part 15C Section 15.247 (a)(2)

Test Method: KDB558074 D01

**Test Configuration:**



Instruments Used: Refer to section 4.10 for details

Exploratory Test Mode: Transmitting mode

Final Test Mode: Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g ; 6.5Mbps of rate is the worst case of 802.11n(20MHz)

Limit:  $\geq 500$  kHz

Test Results: Pass


## Measurement Data

802.11b mode			
Test channel	6dB Occupy Bandwidth (kHz)	Limit (kHz)	Result
Lowest	10064	≥500	Pass
Middle	9539	≥500	Pass
Highest	9990	≥500	Pass
802.11g mode			
Test channel	6dB Occupy Bandwidth (kHz)	Limit (kHz)	Result
Lowest	16312	≥500	Pass
Middle	16194	≥500	Pass
Highest	16308	≥500	Pass
802.11n(20MHz)mode			
Test channel	6dB Occupy Bandwidth (kHz)	Limit (kHz)	Result
Lowest	17323	≥500	Pass
Middle	17329	≥500	Pass
Highest	17053	≥500	Pass


Result plot as follows:

Test mode: 802.11.b


Lowest Channel:



Middle Channel:




Highest Channel:




Result plot as follows:

Test mode: 802.11.g


Lowest Channel:



Middle Channel:




Highest Channel:




Result plot as follows:

Test mode: 802.11.n(20MHz)


Lowest Channel:



Middle Channel:



Highest Channel:






## 5.4. Power Spectral Density

Test Requirement: 47 CFR Part 15C Section 15.247 (e)

Test Method: KDB558074 D01

### Test Configuration:



Test Instruments: Refer to section 4.10 for details

Exploratory Test Mode: Transmitting mode

Final Test Mode: Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g ; 6.5Mbps of rate is the worst case of 802.11n (20MHz)

Limit:  $\leq 8.00\text{dBm}$

Test Results: Pass


## Measurement Data

802.11b mode			
Test channel	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Lowest	-11.44	≤8.00	Pass
Middle	-11.75	≤8.00	Pass
Highest	-11.42	≤8.00	Pass
802.11g mode			
Test channel	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Lowest	-13.61	≤8.00	Pass
Middle	-14.87	≤8.00	Pass
Highest	-14.35	≤8.00	Pass
802.11n(20MHz)mode			
Test channel	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Lowest	-14.16	≤8.00	Pass
Middle	-14.93	≤8.00	Pass
Highest	-14.63	≤8.00	Pass


Result plot as follows:

Test mode: 802.11.b


Lowest Channel:



Middle Channel:




Highest Channel:




Result plot as follows:

Test mode: 802.11.g


Lowest Channel:



Middle Channel:




Highest Channel:




Result plot as follows:

Test mode: 802.11.n(20MHz)


Lowest Channel:



Middle Channel:



Highest Channel:






### 5.5. Band-edge for RF Conducted Emissions

Test Requirement: FCC Part15 C section 15.247

Test Method: KDB558074 D01

**Test Configuration:**



Exploratory Test Mode: Transmitting mode

Final Test Mode: Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g ; 6.5Mbps of rate is the worst case of 802.11n(20MHz)

Limit: In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.


Instruments Used: Refer to section 4.10 for details

Test Results: Pass


Result plot as follows:

Test mode: 802.11.b

Lowest Channel:




Highest Channel:




Result plot as follows:

Test mode: 802.11.g

Lowest Channel:




Highest Channel:




Result plot as follows:

Test mode: 802.11.n(20MHz)

Lowest Channel:



Highest Channel:




## 5.6. RF Conducted Spurious Emissions

Test Requirement: 47 CFR Part 15C Section 15.247 (d)

Test Method: KDB558074 D01

**Test Configuration:**



Exploratory Test Mode: Transmitting mode

Final Test Mode: Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g ; 6.5Mbps of rate is the worst case of 802.11n(20MHz)

Limit: In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.


Instruments Used: Refer to section 4.10 for details

Test Results: Pass


Result plot as follows:

Test mode: 802.11.b


Lowest Channel:



Middle Channel:




Highest Channel:




Result plot as follows:

Test mode: 802.11.g

Lowest Channel:




Middle Channel:






Highest Channel:




Result plot as follows:

Test mode: 802.11.n(20MHz)


Lowest Channel:



Middle Channel:



Highest Channel:




## 5.7. Radiated Spurious Emissions


Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205				
Test Method:	ANSI C63.10 2009				
Test Site:	Measurement Distance: 3m				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
	Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.				

**Test Configuration:**


**1) 9 kHz to 30 MHz emissions:**



**2) 30 MHz to 1 GHz emissions:**



3) 1 GHz to 25 GHz emissions:



Test Procedure:

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB

Test Procedure:	<p>margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</p> <p>g. Test the EUT in the lowest channel ,the middle channel ,the Highest channel</p> <p>h. The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, Only the test worst case mode is recorded in the report.</p> <p>i. Repeat above procedures until all frequencies measured was complete.</p>
Exploratory Test Mode:	Transmitting mode.
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(20MHz)
Instruments Used: Refer	Refer to section 4.10 for details
Test Results:	Pass

## 5.7.1. Harmonic and other spurious emissions

### 5.7.1.1. Test at Lowest Channel in transmitting status

9 kHz~30 MHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement

The measurements with active loop antenna were greater than 20dB below the limit, so the test data were not recorded in the test report.


30 MHz~1 GHz Spurious Emissions. Quasi-Peak Measurement

Test Mode: 802.11b

Test channel: Lowest

Vertical:

Level (dB $\mu$ V/m)




### Quasi-peak measurement

Frequency (MHz)	Detect Mode	Polarization (V/H)	Measured Value (dB $\mu$ V)	Antenna Factor + Cable Loss (dB/m)	Emission Level (dB $\mu$ N/m)	Limit (dB $\mu$ N/m)
71.80	QP	V	26.84	11.36	15.48	40.0
120.83	QP	V	30.75	8.64	22.11	43.5
212.84	QP	V	32.44	13.48	18.96	43.5
281.88	QP	V	30.75	17.07	13.68	46.0
371.76	QP	V	41.67	20.52	21.15	46.0
520.15	QP	V	34.15	24.35	9.80	46.0



Horizontal:

Level (dB $\mu$ V/m)



Quasi-peak measurement

Frequency (MHz)	Detect Mode	Polarization (V/H)	Measured Value (dB $\mu$ V)	Antenna Factor + Cable Loss (dB/m)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)
67.89	QP	H	24.01	11.54	12.47	40.0
145.69	QP	H	25.41	10.55	14.86	43.5
232.38	QP	H	30.09	15.12	14.97	46.0
297.51	QP	H	36.59	17.29	19.30	46.0
408.83	QP	H	39.99	21.98	18.01	46.0
965.53	QP	H	40.04	31.84	8.20	54.0

# 1~25 GHz Harmonics & Spurious Emissions. Peak & Average Measurement

## Peak Measurement:

Frequency (MHz)	Polarization (V/H)	Measured Value (dB $\mu$ V)	Correction Factor	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)
			Antenna+Cable-Amp. Gain		
4824.00	H	52.73	13.19	39.54	74
4824.00	V	49.13	13.19	35.94	74

## Average Measurement:

Frequency (MHz)	Polarization (V/H)	Measured Value (dB $\mu$ V)	Correction Factor	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)
			Antenna+Cable-Amp. Gain		
4824.00	H	50.63	13.19	37.44	54
4824.00	V	47.25	13.19	34.06	54

### 5.7.1.2. Test at middle Channel in transmitting status

9 kHz~30 MHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement

The measurements with active loop antenna were greater than 20dB below the limit, so the test data were not recorded in the test report.


30 MHz~1 GHz Spurious Emissions. Quasi-Peak Measurement

Test Mode: 802.11b

Test channel: Middle

Vertical:

Level (dBμV/m)




Quasi-peak measurement

Frequency (MHz)	Detect Mode	Polarization (V/H)	Measured Value (dBμV)	Antenna Factor + Cable Loss (dB/m)	Emission Level (dBμV/m)	Limit (dBμV/m)
71.80	QP	V	27.41	11.36	16.05	40.0
137.17	QP	V	29.98	9.53	20.45	43.5
233.68	QP	V	30.81	15.23	15.58	46.0
371.76	QP	V	38.26	20.52	17.74	46.0
520.15	QP	V	34.76	24.35	10.41	46.0

Horizontal:

Level (dB $\mu$ V/m)



Quasi-peak measurement

Frequency (MHz)	Detect Mode	Polarization (V/H)	Measured Value (dB $\mu$ V)	Antenna Factor + Cable Loss (dB/m)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)
69.19	QP	H	24.67	11.65	13.02	40.0
297.51	QP	H	40.96	17.29	23.67	46.0
408.83	QP	H	29.84	21.98	7.86	46.0
446.01	QP	H	36.86	22.82	14.04	46.0
520.15	QP	H	33.26	24.35	8.91	46.0
965.53	QP	H	38.87	31.84	7.03	54.0

# 1~25 GHz Harmonics & Spurious Emissions. Peak & Average Measurement

## Peak Measurement:

Frequency (MHz)	Polarization (V/H)	Measured Value (dB $\mu$ V)	Correction Factor	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)
			Antenna+Cable-Amp. Gain		
4874.00	H	53.83	13.63	40.20	74
4874.00	V	50.64	13.63	37.01	74

## Average Measurement:

Frequency (MHz)	Polarization (V/H)	Measured Value (dB $\mu$ V)	Correction Factor	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)
			Antenna+Cable-Amp. Gain		
4874.00	H	48.28	13.63	34.65	54
4874.00	V	45.37	13.63	31.74	54

### 5.7.1.3. Test at Highest Channel in transmitting status

9 kHz~30 MHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement

The measurements with active loop antenna were greater than 20dB below the limit, so the test data were not recorded in the test report.


30 MHz~1 GHz Spurious Emissions. Quasi-Peak Measurement

Test Mode: 802.11b

Test channel: Highest

Vertical:

Level (dB $\mu$ V/m)




Quasi-peak measurement

Frequency (MHz)	Detect Mode	Polarization (V/H)	Measured Value (dB $\mu$ V)	Antenna Factor + Cable Loss (dB/m)	Emission Level (dB $\mu$ N/m)	Limit (dB $\mu$ N/m)
71.80	QP	V	28.76	11.36	17.40	40.0
132.67	QP	V	29.44	9.28	20.16	43.5
232.38	QP	V	31.14	15.12	16.02	46.0
371.76	QP	V	37.09	20.52	16.57	46.0

Horizontal:

Level (dB $\mu$ V/m)



Quasi-peak measurement

Frequency (MHz)	Detect Mode	Polarization (V/H)	Measured Value (dB $\mu$ V)	Antenna Factor + Cable Loss (dB/m)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)
70.50	QP	H	25.17	11.62	13.55	40.0
297.51	QP	H	35.35	17.29	18.06	46.0
371.76	QP	H	37.11	20.52	16.59	46.0
483.08	QP	H	33.76	23.66	10.1	46.0
965.53	QP	H	39.17	31.84	7.33	46.0

# 1~25 GHz Harmonics & Spurious Emissions. Peak & Average Measurement

## Peak Measurement:

Frequency (MHz)	Polarization (V/H)	Measured Value (dB $\mu$ V)	Correction Factor	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)
			Antenna+Cable-Amp. Gain		
4924.00	H	48.21	13.66	34.55	74
4924.00	V	43.62	13.66	29.96	74

## Average Measurement:

Frequency (MHz)	Polarization (V/H)	Measured Value (dB $\mu$ V)	Correction Factor	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)
			Antenna+Cable-Amp. Gain		
4924.00	H	42.19	13.66	28.53	54
4924.00	V	40.44	13.66	26.78	54



#### 5.7.1.4. Test at Lowest Channel in transmitting status

9 kHz~30 MHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement

The measurements with active loop antenna were greater than 20dB below the limit, so the test data were not recorded in the test report.


30 MHz~1 GHz Spurious Emissions. Quasi-Peak Measurement

Test Mode: 802.11g

Test channel: Lowest

Vertical:

Level (dB $\mu$ V/m)




#### Quasi-peak measurement

Frequency (MHz)	Detect Mode	Polarization (V/H)	Measured Value (dB $\mu$ V)	Antenna Factor + Cable Loss (dB/m)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)
71.80	QP	V	26.81	11.36	15.45	40.0
117.63	QP	V	31.26	8.69	22.57	43.5
281.17	QP	V	31.01	17.06	13.95	46.0
371.76	QP	V	38.30	20.52	17.78	46.0
900.52	QP	V	36.98	30.58	6.40	46.0

Horizontal:

Level (dB $\mu$ V/m)



Quasi-peak measurement

Frequency (MHz)	Detect Mode	Polarization (V/H)	Measured Value (dB $\mu$ V)	Antenna Factor + Cable Loss (dB/m)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)
71.80	QP	H	25.35	11.36	13.99	40.0
233.09	QP	H	28.19	15.18	13.01	46.0
297.51	QP	H	35.10	17.29	17.81	46.0
371.76	QP	H	36.95	20.52	16.43	46.0
483.08	QP	H	32.86	23.66	9.20	46.0
965.53	QP	H	39.41	31.84	7.57	54.0

# 1~25 GHz Harmonics & Spurious Emissions. Peak & Average Measurement

## Peak Measurement:

Frequency (MHz)	Polarization (V/H)	Measured Value (dB $\mu$ V)	Correction Factor	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)
			Antenna+Cable-Amp. Gain		
4824.00	H	48.90	13.19	35.71	74
4824.00	V	46.22	13.19	33.03	74

## Average Measurement:

Frequency (MHz)	Polarization (V/H)	Measured Value (dB $\mu$ V)	Correction Factor	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)
			Antenna+Cable-Amp. Gain		
4824.00	H	43.50	13.19	30.31	54
4824.00	V	42.38	13.19	29.19	54

#### 5.7.1.5. Test at middle Channel in transmitting status

9 kHz~30 MHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement

The measurements with active loop antenna were greater than 20dB below the limit, so the test data were not recorded in the test report.


30 MHz~1 GHz Spurious Emissions. Quasi-Peak Measurement

Test Mode: 802.11g

Test channel: Middle

Vertical:

Level (dB $\mu$ V/m)




Quasi-peak measurement

Frequency (MHz)	Detect Mode	Polarization (V/H)	Measured Value (dB $\mu$ V)	Antenna Factor + Cable Loss (dB/m)	Emission Level (dB $\mu$ N/m)	Limit (dB $\mu$ N/m)
133.97	QP	V	30.66	9.35	21.31	43.5
233.68	QP	V	31.30	15.23	16.07	46.0
371.76	QP	V	37.79	20.52	17.27	46.0
425.76	QP	V	33.97	22.36	11.61	46.0
520.15	QP	V	34.26	24.35	9.91	46.0

Horizontal:

Level (dB $\mu$ V/m)



Quasi-peak measurement

Frequency (MHz)	Detect Mode	Polarization (V/H)	Measured Value (dB $\mu$ V)	Antenna Factor + Cable Loss (dB/m)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)
297.51	QP	H	34.66	17.29	17.37	46.0
371.76	QP	H	36.77	20.52	16.25	46.0
483.08	QP	H	32.48	23.66	8.82	46.0
965.53	QP	H	39.94	31.84	8.10	46.0

# 1~25 GHz Harmonics & Spurious Emissions. Peak & Average Measurement

## Peak Measurement:

Frequency (MHz)	Polarization (V/H)	Measured Value (dB $\mu$ V)	Correction Factor	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)
			Antenna+Cable-Amp. Gain		
4874.00	H	49.10	13.63	35.47	74
4874.00	V	47.31	13.63	33.68	74

## Average Measurement:

Frequency (MHz)	Polarization (V/H)	Measured Value (dB $\mu$ V)	Correction Factor	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)
			Antenna+Cable-Amp. Gain		
4874.00	H	42.71	13.63	29.08	54
4874.00	V	40.28	13.63	26.65	54

#### 5.7.1.6. Test at Highest Channel in transmitting status

9 kHz~30 MHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement

The measurements with active loop antenna were greater than 20dB below the limit, so the test data were not recorded in the test report.


30 MHz~1 GHz Spurious Emissions. Quasi-Peak Measurement

Test Mode: 802.11g

Test channel: Highest

Vertical:

Level (dB $\mu$ V/m)




Quasi-peak measurement

Frequency (MHz)	Detect Mode	Polarization (V/H)	Measured Value (dB $\mu$ V)	Antenna Factor + Cable Loss (dB/m)	Emission Level (dB $\mu$ N/m)	Limit (dB $\mu$ N/m)
143.09	QP	V	30.74	10.15	20.59	43.5
371.76	QP	V	43.53	20.52	23.01	46.0

Horizontal:

Level (dB $\mu$ V/m)



Quasi-peak measurement

Frequency (MHz)	Detect Mode	Polarization (V/H)	Measured Value (dB $\mu$ V)	Antenna Factor + Cable Loss (dB/m)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)
293.01	QP	H	29.18	17.23	11.95	46.0
297.51	QP	H	35.77	17.29	18.48	46.0
371.76	QP	H	37.75	20.52	17.23	46.0
483.08	QP	H	32.42	23.66	8.76	46.0
965.53	QP	H	37.93	31.84	6.09	54.0



# 1~25 GHz Harmonics & Spurious Emissions. Peak & Average Measurement

## Peak Measurement:

Frequency (MHz)	Polarization (V/H)	Measured Value (dB $\mu$ V)	Correction Factor	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)
			Antenna+Cable-Amp. Gain		
4924.00	H	47.38	13.66	33.72	74
4924.00	V	44.52	13.66	30.86	74

## Average Measurement:

Frequency (MHz)	Polarization (V/H)	Measured Value (dB $\mu$ V)	Correction Factor	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)
			Antenna+Cable-Amp. Gain		
4924.00	H	41.29	13.66	27.63	54
4924.00	V	40.77	13.66	27.11	54

#### 5.7.1.7. Test at Lowest Channel in transmitting status

9 kHz~30 MHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement

The measurements with active loop antenna were greater than 20dB below the limit, so the test data were not recorded in the test report.


30 MHz~1 GHz Spurious Emissions. Quasi-Peak Measurement

Test Mode: 802.11n(20MHz)

Test channel: Lowest

Vertical:

Level (dB $\mu$ V/m)




Quasi-peak measurement

Frequency (MHz)	Detect Mode	Polarization (V/H)	Measured Value (dB $\mu$ V)	Antenna Factor + Cable Loss (dB/m)	Emission Level (dB $\mu$ N/m)	Limit (dB $\mu$ N/m)
71.80	QP	V	27.11	11.36	15.75	40.0
139.77	QP	V	29.81	9.67	20.14	43.5
211.54	QP	V	32.16	13.37	18.79	46.0
371.76	QP	V	38.85	20.52	18.33	46.0
520.15	QP	V	34.11	24.35	9.76	46.0
965.53	QP	V	39.54	31.84	7.70	54.0

Horizontal:

Level (dB $\mu$ V/m)



Quasi-peak measurement

Frequency (MHz)	Detect Mode	Polarization (V/H)	Measured Value (dB $\mu$ V)	Antenna Factor + Cable Loss (dB/m)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)
297.51	QP	H	35.58	17.29	18.29	46.0
371.76	QP	H	37.55	20.52	17.03	46.0
483.08	QP	H	33.46	23.66	9.80	46.0
965.53	QP	H	39.65	31.84	7.81	46.0

# 1~25 GHz Harmonics & Spurious Emissions. Peak & Average Measurement

## Peak Measurement:

Frequency (MHz)	Polarization (V/H)	Measured Value (dB $\mu$ V)	Correction Factor	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)
			Antenna+Cable-Amp. Gain		
4824.00	H	46.21	13.19	33.02	74
4824.00	V	43.15	13.19	29.96	74

## Average Measurement:

Frequency (MHz)	Polarization (V/H)	Measured Value (dB $\mu$ V)	Correction Factor	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)
			Antenna+Cable-Amp. Gain		
4824.00	H	38.45	13.19	25.26	54
4824.00	V	35.63	13.19	22.44	54

#### 5.7.1.8. Test at middle Channel in transmitting status

9 kHz~30 MHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement

The measurements with active loop antenna were greater than 20dB below the limit, so the test data were not recorded in the test report.


30 MHz~1 GHz Spurious Emissions. Quasi-Peak Measurement

Test Mode: 802.11n(20MHz)

Test channel: Middle

Vertical:

Level (dB $\mu$ V/m)




Quasi-peak measurement

Frequency (MHz)	Detect Mode	Polarization (V/H)	Measured Value (dB $\mu$ V)	Antenna Factor + Cable Loss (dB/m)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)
70.50	QP	V	28.27	11.62	16.65	40.0
117.63	QP	V	31.07	8.69	22.38	43.5
297.51	QP	V	32.11	17.29	14.82	46.0
371.76	QP	V	39.27	20.52	18.75	46.0
965.53	QP	V	40.05	31.84	8.21	46.0

Horizontal:

Level (dB $\mu$ V/m)



Quasi-peak measurement

Frequency (MHz)	Detect Mode	Polarization (V/H)	Measured Value (dB $\mu$ V)	Antenna Factor + Cable Loss (dB/m)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)
297.51	QP	H	35.21	17.29	17.92	40.0
371.76	QP	H	37.53	20.52	17.01	40.0
965.53	QP	H	39.90	31.84	8.06	46.0

# 1~25 GHz Harmonics & Spurious Emissions. Peak & Average Measurement

## Peak Measurement:

Frequency (MHz)	Polarization (V/H)	Measured Value (dB $\mu$ V)	Correction Factor	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)
			Antenna+Cable-Amp. Gain		
4874.00	H	46.28	13.63	32.65	74
4874.00	V	43.19	13.63	29.56	74

## Average Measurement:

Frequency (MHz)	Polarization (V/H)	Measured Value (dB $\mu$ V)	Correction Factor	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)
			Antenna+Cable-Amp. Gain		
4874.00	H	41.74	13.63	28.11	54
4874.00	V	39.65	13.63	26.02	54

#### 5.7.1.9. Test at Highest Channel in transmitting status

9 kHz~30 MHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement

The measurements with active loop antenna were greater than 20dB below the limit, so the test data were not recorded in the test report.


30 MHz~1 GHz Spurious Emissions. Quasi-Peak Measurement

Test Mode: 802.11n(20MHz)

Test channel: Highest

Vertical:

Level (dBμV/m)




Quasi-peak measurement

Frequency (MHz)	Detect Mode	Polarization (V/H)	Measured Value (dBμV)	Antenna Factor + Cable Loss (dB/m)	Emission Level (dBμV/m)	Limit (dBμV/m)
118.22	QP	V	29.49	8.67	20.82	43.5
297.51	QP	V	35.44	17.29	18.15	46.0
371.76	QP	V	39.25	20.52	18.73	46.0
840.01	QP	V	40.01	29.86	10.15	46.0



Horizontal:

Level (dB $\mu$ V/m)



Quasi-peak measurement

Frequency (MHz)	Detect Mode	Polarization (V/H)	Measured Value (dB $\mu$ V)	Antenna Factor + Cable Loss (dB/m)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)
297.51	QP	H	35.58	17.29	18.29	46.0
371.76	QP	H	37.56	20.52	17.04	46.0
483.08	QP	H	34.22	23.66	10.56	46.0
965.53	QP	H	39.37	31.84	7.53	46.0

## 1~25 GHz Harmonics & Spurious Emissions. Peak & Average Measurement

### Peak Measurement:

Frequency (MHz)	Polarization (V/H)	Measured Value (dB $\mu$ V)	Correction Factor	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)
			Antenna+Cable-Amp. Gain		
4824.00	H	47.85	13.19	34.66	74
4824.00	V	45.38	13.19	32.19	74

### Average Measurement:

Frequency (MHz)	Polarization (V/H)	Measured Value (dB $\mu$ V)	Correction Factor	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)
			Antenna+Cable-Amp. Gain		
4824.00	H	40.22	13.19	27.03	54
4824.00	V	36.59	13.19	23.40	54

### Remark:

1). The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Emission = Measured Value + Antenna Factor + Cable Loss – Amplifier Gain.

2). As shown in Section, for frequencies above 1000 MHz, the above field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

3). The test only perform the EUT in transmitting status since the test frequencies were over 1GHz only required transmitting status.


## 5.8. Band Edge (Radiated Emission)

Test Requirement:	FCC Part15 C Section 15.247 (d) In addition, radiated emissions which fall in the restricted bands. as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).
Test Method:	ANSI C63.10: 2009
Measurement	3m (Semi-Anechoic Chamber)
Limit:	Section 15.209(a) 40.0 dB $\mu$ V/m between 30MHz & 88MHz; Quasi-peak Value 43.5 dB $\mu$ V/m between 88MHz & 216MHz; Quasi-peak Value 46.0 dB $\mu$ V/m between 216MHz & 960MHz; Quasi-peak Value 54.0 dB $\mu$ V/m between 960MHz.& 1GHz; Quasi-peak Value 54.0 dB $\mu$ V/m Above 1GHz; Average Value 74.0 dB $\mu$ V/m Above 1GHz; Peak Value
Test Procedure:	<p>a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.</p> <p>b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</p> <p>c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</p> <p>d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</p> <p>e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</p> <p>f. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel</p> <p>g. Test the EUT in the lowest channel , the Highest channel</p> <p>h. The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, only the test worst case mode is recorded in the report.</p> <p>i. Repeat above procedures until all frequencies measured was complete.</p>


Exploratory Test Mode:	Transmitting mode
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(20MHz)
Instruments Used:	Refer to section 4.10 for details
Test Results:	Pass

## Measurement Result:


### 802.11b- Lowest Channel , Horizontal , Peak/Average Detector




### 802.11b- High Channel , Horizontal , Peak/Average Detector




802.11b- Low Channel , Vertical , Peak/Average Detector




802.11b- High Channel , Vertical , Peak/Average Detector




802.11g- Lowest Channel , Horizontal , Peak/Average Detector




802.11g- High Channel , Horizontal , Peak/Average Detector



802.11g- Low Channel , Vertical , Peak/Average Detector




802.11g- High Channel , Vertical , Peak/Average Detector







802.11n(20MHz)- Lowest Channel , Horizontal , Peak/Average Detector




802.11n(20MHz)- High Channel , Horizontal , Peak/Average Detector



802.11n(20MHz)- Low Channel , Vertical , Peak/Average Detector



802.11n(20MHz)- High Channel , Vertical , Peak/Average Detector



Section 15.205 Restricted bands of operation.

(a) Except as shown in paragraph (d) of this section. only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	
13.36 - 13.41			

## 5.9. Conducted Emissions at Mains Terminals 150 kHz to 30 MHz

Test Requirement: FCC Part 15 C section 15.207  
 Test Method: ANSI C63.10: ANSI C63.10: 2009  
 Frequency Range: 150 kHz to 30 MHz  
 Detector: Peak for pre-scan (9 kHz Resolution Bandwidth)


Test Limit

**Limits for conducted disturbance at the mains ports of class B**

Frequency Range (MHz)	Class B Limit dB(μV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50
NOTE 1 The limit decreases linearly with the logarithm of the frequency in the range 0,15 MHz to 0,50 MHz.		

EUT Operation: Test in normal operating mode. For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage.

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

**Test Configuration:****Test procedure:**


1. The mains terminal disturbance voltage test was conducted in a shielded room.
2. The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a  $50/50\mu\text{H} + 5\text{linear}$  impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
3. The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, but separated from metallic contact with the ground reference plane by 0.1m of insulation.
4. The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0,4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0,8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0,8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2009 on conducted measurement.

### 5.9.1. Measurement Data


Pre-scan was performed with peak detected on all ports, Quasi-peak & average measurements were performed at the frequencies at which maximum peak emission level were detected.

Please see the attached Quasi-peak and Average test results.

Line – PE(Peak and Average detector used)



Neutral – PE(Peak and Average detector used)



Measurement data:

Frequency (MHz)	Correction Factor		Line	Quasi-Peak			Average		
	LISN	Cable		Limit [dBuV]	Reading [dBuV]	Result [dBuV]	Limit [dBuV]	Reading [dBuV]	Result [dBuV]
0.19	9.62	0.53	H	64.04	37.29	47.43	54.04	24.51	34.65
0.24	9.63	0.49	H	62.10	31.51	41.63	52.10	22.05	32.17
0.43	9.63	0.59	H	57.25	30.03	40.25	47.25	28.75	38.97
0.44	9.64	0.59	N	57.06	30.30	40.53	47.06	28.51	38.74
0.48	9.64	0.58	N	56.34	34.11	44.33	46.34	33.06	43.28
0.49	9.64	0.57	H	56.17	35.04	45.25	46.17	33.39	43.60
0.92	9.65	0.57	N	56.00	27.61	37.83	46.00	24.16	34.38
1.51	9.66	0.59	N	56.00	28.19	38.44	46.00	26.03	36.28
1.95	9.66	0.62	H	56.00	27.50	37.78	46.00	23.34	33.62
2.59	9.73	0.64	N	56.00	26.93	37.30	46.00	23.64	34.01
2.98	9.68	0.61	H	56.00	27.03	37.32	46.00	23.29	33.58
4.01	9.70	0.62	H	56.00	25.04	35.36	46.00	17.72	28.04
6.40	9.81	0.65	N	60.00	24.66	35.13	50.00	18.73	29.20

Margin (dB) = Limit – Reading

[Result = Reading + LISN+ Cable]

## 5.10. Radio Frequency Exposure Procedures

### Regulation

According to §15.247(i) and § 1.1307(b)(1) , systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines.

KDB 447498 D01: Approximate SAR test exclusion power thresholds at selected frequencies and test separation distances are illustrated in the following table:

MHz	5	10	15	20	25	mm
150	39	77	116	155	194	SAR Test Exclusion Threshold (mW)
300	27	55	82	110	137	
450	22	45	67	89	112	
835	16	33	49	66	82	
900	16	32	47	63	79	
1500	12	24	37	49	61	
1900	11	22	33	44	54	
2450	10	19	29	38	48	
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot$$

$$[\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.



**Maximum Measured Transmitter Power:**

Channel Frequency (MHz)	Maximum Peak Conducted Output Power		Max Antenna Gain (dBi)	Numeric antenna gain (mW)
	(dBm)	(mW)		
2412	15.89	38.81	2.00	1.584

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]

·  $[\sqrt{f(\text{GHz})}] = 38.81/25 \cdot \sqrt{2.412} = 2.41 \leq 3.0$

Threshold at which no SAR required is 48mW and  $\leq 3.0$  for 1-g SAR, Separation distance is 25mm.

**Conclusion : The SAR measurement is exempt.**

## APPENDIX

### 1. EUT photo

