

EMC TEST REPORT For FCC



Test Report No. : CTK4-F023

Date of Issue : April 30, 2004

FCC ID : QJCH-200

Model/Type No. : H-200 (HANSONE 2)

Kind of Product : Braille PDA

Applicant : HIMS Co., Ltd.

Applicant Address : High-Tech Venture Hall 5105, 53-3, Eoeun-dong,
Yuseong-ku, Daejeon, KOREA

Manufacturer : HIMS Co., Ltd.

Manufacturer Address : High-Tech Venture Hall 5105, 53-3, Eoeun-dong,
Yuseong-ku, Daejeon, KOREA

Contact Person : Kyeong-Seon, Choi

Telephone : +82-42-864-4460

Received Date : April 21, 2004

Test period : Start : April 21, 2004 End : April 22, 2004

Test Results : ☒ In Compliance ☐ Not in Compliance

The test results presented in this report relate only to the object tested.


CERTiTEK Standards Laboratory Co., Ltd. is accredited by Korea Laboratory Accreditation Scheme (KOLAS) which signed the International Laboratory Accreditation Cooperation (ILAC) Mutual Recognition Arrangement (MRA) for the above test item(s) and test method(s).

Tested by



Young-Joon, Park
EMC Test Engineer
Date: April 30, 2004

Reviewed by



James Hong
EMC Technical Manager
Date: April 30, 2004

REPORT REVISION HISTORY

Date	Revision	Page No
April 30, 2004	Issued (CTK04-F023)	All

This report shall not be reproduced except in full, without the written approval of CERTiTEK Standards Laboratory Co., Ltd. This document may be altered or revised by CERTiTEK Standards Laboratory Co., Ltd. Personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by CERTiTEK Standards Laboratory Co., Ltd. will constitute fraud and shall nullify the document.

TABLE OF CONTENTS

1.0 General Product Description	4
1.1 Model Differences	4
1.2 Device Modifications.....	4
1.3 EUT Configuration(s)	5
1.4 Test Software	5
1.5 EUT Operating Mode(s).....	5
1.6 Calibration Details of Equipment Used for Measurement	6
1.7 Test Facility	6
1.8 Measurement Procedure	6
1.9 Laboratory Accreditations and Listings	7
2.0 Emissions Test Regulations.....	8
2.1 Conducted Voltage Emissions	9
2.2 Radiated Electric Field Emissions.....	10
Configurations	11
APPENDIX A - TEST DATA.....	12
Conducted Voltage Emissions (Quasi-Peak reading)	12
Radiated Electric Field Emissions (Quasi-Peak reading).....	14

1.0 General Product Description

1.0.1 Tested Equipment

- ☒ Unless otherwise indicated, all tests were conducted on Model H-200 (HANSONE 2).
- ☐ Tests performed on Model _____ were considered to be representative of Model(s) _____.

1.0.2 Equipment Size, Mobility and Identification

Dimensions: 155(W) by 255(L) by 55(H) ☒ mm ☐ in
Mobility: ☐ Hand-Held ☒ Table-top ☐ Floor-standing
Serial No.: Prototype

1.0.3 Electrical Ratings

Adaptor	Input:	100-240Vac, 50/60Hz, 0.3A
	Output:	6Vdc, 2A
EUT	Input:	6Vdc
	Output:	-

1.0.4 Test Voltage & Frequency (Using the adaptor)

Unless indicated otherwise on the individual data sheet or test results, the test voltage and frequency was as indicated below.

Voltage: 120Vac
Frequency: 60Hz

1.0.5 Clock & Other Frequencies Utilized

3.686MHz, 32.768kHz, 30MHz, 50MHz,
36MHz, 20MHz, 14.31818MHz, 24.576MHz

1.1 Model Differences

Not applicable

1.2 Device Modifications

The following modifications were necessary for compliance:

Not applicable

1.3 EUT Configuration(s)

See Appendix A for individual test set-up configuration(s). The following peripheral devices and/or interface cables were connected during the measurement:

☒ Peripheral Devices

Device	Manufacturer	Model No.	Serial No.	FCC ID or DoC
Switching Adaptor	DVE	DSA-0131F-06 KA 12	-	-
Notebook PC	IBM CORPORATION	2611-43K	AA-DN8YC99/07	DoC
Adaptor	IBM CORPORATION	-	152914-001	DoC
Monitor	SAMSUNG	PG17HS	P0133H3NN703187	DoC
Printer	SEIKO EPSON CORP.	Stylus Color 460	BWCE136524	DoC
Mouse	SAMSUNG	OMS3CB	0303009888	DoC
Headphone	-	-	-	-
Microphone	-	-	-	-

☒ Cable Description

#	Description	Ferrite Core	Length (m)	Other Details
1	DC output cable, Unshielded	Yes	1.8	Between the EUT and Switching Adaptor
2	Monitor cable, Shielded	Yes	1.8	Between the EUT and Monitor
3	Printer cable, Shielded	No	1.8	Between the EUT and Printer
4	USB/M cable, Shielded	No	2.0	Between the EUT and Mouse
5	Headphone cable, Unshielded	No	2.5	Between the EUT and Headphone
6	Microphone cable, Unshielded	No	3.0	Between the EUT and Microphone
7	USB/S cable, Shielded	No	1.5	Between the EUT and Notebook PC
8	Serial cable, Shielded (RS232C)	No	2.5	Between the EUT and Notebook PC
9	LAN cable, Unshielded	No	20.0	Connect to HUB
10	DC output cable, Unshielded	No	1.5	Between Notebook PC and Adaptor
11	AC Power Cable, Unshielded	No	1.8	Connect to AC power
12	AC Power Cable, Unshielded	No	1.8	Connect to AC power
13	AC Power Cable, Unshielded	No	1.8	Connect to AC power

1.4 Test Software

- ☐ Ping
☒ Not applicable

1.5 EUT Operating Mode(s)

Equipment under test was operated during the measurement under the following conditions:

- ☐ Test program (H-Pattern) ☐ Test program (color bar)
☒ Ping ☐ Test program (customer specific)
☒ Practice operation –
Data was communicated between the EUT and notebook. (RS232C)
And Data was communicated between EUT and Hub. (Ethernet)

1.6 Calibration Details of Equipment Used for Measurement

Test equipment and test accessories are calibrated on regular basis. The maximum time between calibrations is one year or what is recommended by the manufacturer, whichever is less. All test equipment calibrations are traceable to the Korea Research Institute of Standards and Science (KRISS), therefore, all test data recorded in this report is traceable to KRISS.

1.7 Test Facility

The measurement facility is located at 386-1, Ho-Dong, Yongin-City, Kyungki-Do, Korea 449-100. The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

1.8 Measurement Procedure

Preliminary AC power line conducted emissions tests were performed shielded room. To find worst mode, several typical mode and typical cable position were tested. Final AC power line conducted emissions test was performed shielded room. (location is same as Preliminary test)






Based on the preliminary tests of the EUT, final test was proceeded worst case test mode and cable configuration.

Preliminary radiated emissions test were performed anechoic chamber (Distance of antenna and EUT was 3 m). To find worst mode, several typical mode and typical cable position were tested and peak level and frequency were recorded.

Final radiated emissions test was performed Open Area Test Site. Based on the preliminary tests of the EUT, final test was proceeded worst case test mode and cable configuration.

* Measurement procedures was In accordance with ANSI C63.4-2001 7.2.3, 7.2.4, 8.3.1.1, 8.3.1.2

1.9 Laboratory Accreditations and Listings

Country	Agency	Scope of Accreditation	Logo
USA	FCC	3 and 10 meter Open Area Test Sites to perform FCC Part 15/18 measurements.	 93250
JAPAN	VCCI	10 meter Open Area Test Site and one conducted site.	 R-948, C-986
KOREA	MIC	EMI (CE, RE) EMS (ESD, Burst, RS, Surge, CS, Power-Frequency Susceptibility, Voltage Dips and Short Interruptions)	 No. 51, KR0025
International	KOLAS	EMC	 NO. 119
Europe	GLAS	EMC EN 55011, EN 55022, EN 55024, EN 61326, EN 50130-4, EN 50081-1, EN 50081-2, EN 50082-1, EN 50082-2, EN 61000-6-2, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6, EN 61000-4-8, EN 61000-4-11, EN 61000-3-2, EN 61000-3-3	 No.13000796-02

2.0 Emissions Test Regulations

The emissions tests were performed according to following regulations:

- | | | |
|--|----------------------------------|---|
| <input type="checkbox"/> EN 50081-1:1992 | <input type="checkbox"/> Class A | <input type="checkbox"/> Class B |
| <input type="checkbox"/> EN 61000-6-3:2001 | <input type="checkbox"/> Class A | <input type="checkbox"/> Class B |
| <input type="checkbox"/> EN 50081-2:1993 | <input type="checkbox"/> Class A | <input type="checkbox"/> Class B |
| <input type="checkbox"/> EN 61000-6-4:2001 | <input type="checkbox"/> Class A | <input type="checkbox"/> Class B |
| <input type="checkbox"/> EN 50083-2:2001 | | |
| <input type="checkbox"/> EN 55011:1998 +A1:1999 | <input type="checkbox"/> Group 1 | <input type="checkbox"/> Group 2 |
| | <input type="checkbox"/> Class A | <input type="checkbox"/> Class B |
| <input type="checkbox"/> EN 55013:1990 +A12:1994 +A13:1996 +A14:1999 | | |
| <input type="checkbox"/> EN 55013:2001 | | |
| <input type="checkbox"/> EN 55014-1:2000 | | |
| <input type="checkbox"/> EN 55014-1:2000 +A1:2001 | | |
| <input type="checkbox"/> EN 55015:2000 | | |
| <input type="checkbox"/> EN 55015:2000 +A1:2001 | | |
| <input type="checkbox"/> EN 55022:1994 +A1:1995 +A2:1997 | <input type="checkbox"/> Class A | <input type="checkbox"/> Class B |
| <input type="checkbox"/> EN 55022:1998 | <input type="checkbox"/> Class A | <input type="checkbox"/> Class B |
| <input type="checkbox"/> EN 55022:1998 +A1:2000 | <input type="checkbox"/> Class A | <input type="checkbox"/> Class B |
| <input type="checkbox"/> EN 61000-3-2:1995 +A1:1998 +A2:1998 +A14:2000 | | |
| <input type="checkbox"/> EN 61000-3-2:2000 | | |
| <input type="checkbox"/> EN 61000-3-3:1995 | | |
| <input type="checkbox"/> EN 61000-3-3:1995 +A1:2001 | | |
| <input type="checkbox"/> VCCI V-3/2003.04 | <input type="checkbox"/> Class A | <input type="checkbox"/> Class B |
| <input type="checkbox"/> AS/NZS 3548:1995 +A1:1997 +A2:1997 | <input type="checkbox"/> Class A | <input type="checkbox"/> Class B |
| <input checked="" type="checkbox"/> FCC Part 15 Subpart B | <input type="checkbox"/> Class A | <input checked="" type="checkbox"/> Class B |
| <input checked="" type="checkbox"/> CISPR 22:1997 | <input type="checkbox"/> Class A | <input checked="" type="checkbox"/> Class B |
| The unit was tested to CISPR 22 and complied with the alternate methods allowed by FCC under paragraphs 15.107 and 15.109. | | |
| <input type="checkbox"/> CISPR 22:1997 +A1:2000 | <input type="checkbox"/> Class A | <input type="checkbox"/> Class B |

2.1 Conducted Voltage Emissions

Test Date

April 21, 2004

Test Location

EMI-CE: Shielded Room

Test Instruments

<input checked="" type="checkbox"/> Field Strength Meter	Rohde & Schwarz	ESHS30	828144/002
--	-----------------	--------	------------

Test Accessories

<input type="checkbox"/> LISN	EMCO	3825/2	9206-1971
<input checked="" type="checkbox"/> LISN	EMCO	3825/2	9409-2246
<input checked="" type="checkbox"/> LISN	EMCO	3825/2	9607-2574
<input checked="" type="checkbox"/> Control PC	HP	Vectra 500	SG72000192

Frequency Range of Measurement

<input checked="" type="checkbox"/> 150 kHz to 30 MHz
<input type="checkbox"/> 450 kHz to 30 MHz
<input type="checkbox"/> _____

Instrument Settings

IF Band Width: 9 kHz

Test Results

The requirements are:

<input checked="" type="checkbox"/> MET	minimum margin is 2.5 dBuV at 0.15 MHz
<input type="checkbox"/> NOT MET	limit exceeded by maximum of ____ dBuV at ____ MHz
<input type="checkbox"/> NOT APPLICABLE	

Remarks

See Appendix A for test data.

2.2 Radiated Electric Field Emissions

Test Date

April 21, 2004

Test Location

- ☒ EMI-OATS: Testing was performed at a test distance of 10 m
☐ EMI-OATS: Testing was performed at a test distance of 3 m

Test Instruments

☒ Field Strength Meter Rohde & Schwarz ESVS30 826638/008

Test Accessories

<input checked="" type="checkbox"/> ULTRA Broadband Antenna	Rohde & Schwarz	HL562	361324/014
<input type="checkbox"/> Biconical Antenna	Schwarzbeck	BBA9106	41-00201
<input type="checkbox"/> Biconical Antenna	EMCO	3110B	9607-2564
<input type="checkbox"/> Log-periodic Antenna	EMCO	3146	9607-4567

Frequency Range of Measurement

30 MHz to 1 GHz

Instrument Settings

IF Band Width: 120 kHz

Test Results


The requirements are:

- ☒ MET minimum margin is 6.9 dBuV/m at 301.08 MHz
☐ NOT MET limit exceeded by maximum of ____ dBuV/m at ____ MHz
☐ NOT APPLICABLE

Remarks

See Appendix A for test data



Configuration



APPENDIX A – TEST DATA

Conducted Voltage Emissions (Quasi-Peak reading)

Frequency [MHz]	Correction Factor		Line	Quasi-peak				Average			
	LISN	Cable		Limit [dBuV]	Reading [dBuV]	Result [dBuV]	Margin [dB]	Limit [dBuV]	Reading [dBuV]	Result [dBuV]	Margin [dB]
0.15	0.2	0.1	H	66.0	63.2	63.5	2.5	56.0	38.9	39.2	16.8
0.17	0.2	0.1	N	65.0	55.1	55.4	9.6	55.0	17.8	18.1	36.9
0.18	0.2	0.1	H	64.5	53.0	53.3	11.2	54.5	15.3	15.6	38.9
0.19	0.2	0.1	H	64.0	51.9	52.2	11.8	54.0	11.6	11.9	42.1
0.21	0.2	0.1	H	63.2	51.8	52.1	11.1	53.2	15.6	15.9	37.3
4.73	0.1	0.2	H	56.0	38.3	38.6	17.4	46.0	35.1	35.4	10.6



Radiated Electric Field Emissions (Quasi-Peak reading)

Frequency [MHz]	Reading [dBuV/m]	Pol.	Height [m]	Correction Factor		Limits [dBuV/m]	Result [dBuV/m]	Margin [dB]
				Antenna	Cable			
50.39	8.8	V	2.3	7.9	1.2	30.0	17.9	12.1
72.51	12.6	V	2.0	7.3	1.6	30.0	21.5	8.5
135.32	10.5	H	1.0	8.4	2.1	30.0	21.0	9.0
140.06	9.5	H	4.0	8.0	2.2	30.0	19.7	10.3
149.56	9.5	H	4.0	7.6	2.3	30.0	19.4	10.6
151.52	9.2	H	1.8	7.6	2.4	30.0	19.1	10.9
216.37	8.3	H	2.0	8.0	2.8	30.0	19.0	11.0
301.08	15.9	H	2.5	11.0	3.2	37.0	30.1	6.9
450.76	5.4	V	2.2	14.6	4.1	37.0	24.1	12.9