



CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea

Tel: +82-31-339-9970 Fax: +82-31-339-9855

www.e-ctk.com

RF EXPOSURE EVALUATION

Applicant	HIMS International Corporation
Applicant Address	KT Daejeon Satellite Center, 139-9, Gajung-dong, Yuseong-gu, Daejeon, KOREA, 305-350
Kind of Product	Braille Sense U2 QWERTY
Equipment model name	H432Q
RF Conducted Power	WLAN : 8.37 dBm BT : -9.442 dBm
Antenna type	Chip antenna
Frequency Range	WLAN : 2412 MHz – 2462 MHz BT : 2402 MHz - 2480 MHz
Antenna Gain	WLAN : -1 dBi BT : -1 dBi



CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-339-9855
www.e-ctk.com

** MPE Calculations **

No Evaluation Required if power is below this threshold. (60/f(GHz) mW)

Frequency (GHz)		mW
WLAN	2.462	24.37
BT	2.480	24.19

The MPE calculation for this exposure is shown below.

$EIRP = P + G$	Where, P = Conducted output power (dBm) G = Power gain of the antenna (dBi)
----------------	---

Mode	Output Power(dBm)	Antenna gain (dBi)	EIRP (dBm)	EIRP (mW)
WLAN	8.37	-1	7.37	5.46
BT	-9.442	-1	-10.442	0.09

Conclusion: No SAR evaluation required since Transmitter EIRP is below FCC threshold.