



CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-339-9855
www.e-ctk.com

TEST REPORT For FCC

Test Report No. : 2010070017
Date of Issue : July 01, 2010
FCC ID : QJCV400Q
Model/Type No. : V400Q
Kind of Product : Voice Sense QWERTY
Applicant : HIMS Co., Ltd.
Applicant Address : KT Daejeon Satellite Center, 139-9, Gajung-dong, Yuseong-gu, Daejeon, KOREA, 305-350
Manufacturer : HIMS Co., Ltd.
Manufacturer Address : KT Daejeon Satellite Center, 139-9, Gajung-dong, Yuseong-gu, Daejeon, KOREA, 305-350
Contact Person : Lee Chang Hui / Researcher
Telephone : +82-42-864-4460
Received Date : June 18, 2010
Test period : Start : June 18, 2010 End : July 01, 2010
Test Results : ☒ In Compliance ☐ Not in Compliance

The test results presented in this report relate only to the object tested.

Tested by

Y. T. Lee

Lee Young-taek
Test Engineer
Date: July 01, 2010

Reviewed by

Y. J. Park

Young-Joon, Park
Technical Manager
Date: July 01, 2010



CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea

Tel: +82-31-339-9970 Fax: +82-31-339-9855

www.e-ctk.com

REPORT REVISION HISTORY

Date	Revision	Page No
July 01, 2010	Issued (2010070017)	All

This report shall not be reproduced except in full, without the written approval of CTK Co., Ltd. This document may be altered or revised by CTK Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by CTK Co., Ltd. will constitute fraud and shall nullify the document.



CTK Co., Ltd.
The Prime Leader of Global Regulatory Compliance

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-339-9855
www.e-ctk.com

TABLE OF CONTENTS

REPORT REVISION HISTORY	2
1.0 General Product Description	4
1.1 Tested Frequency	4
1.2 Tested Mode	4
1.3 Model Differences	5
1.4 Device Modifications	5
1.5 Peripheral Devices	5
1.6 Calibration Details of Equipment Used for Measurement	5
1.7 Test Facility.....	5
1.8 Laboratory Accreditations and Listings	6
2.0 Summary of tests	7
2.1 Transmitter Requirements	8
2.1.1 Carrier Frequency Separation	8
2.1.2 Number of Hopping Frequencies	10
2.1.3 20 dB bandwidth	13
2.1.4 Time of Occupancy (Dwell Time)	19
2.1.5 Maximum peak Conducted Output Power.....	25
2.1.6 Band-edge.....	30
2.1.7 Field Strength of Emissions	38
2.1.8 AC Conducted Emissions.....	43
APPENDIX A – Test Equipment Used For Tests	46

1.0 General Product Description

Equipment model name : V400Q

Serial number : Prototype

EUT condition : Pre-production, not damaged

Antenna type : Chip antenna Gain -1.0 dBi

Frequency Range : 2402 ~ 2480 MHz

RF power : -4.42 dBm Peak Conducted (GFSK)
: -7.05 dBm Peak Conducted (8-DPSK)

Type of Modulation : Frequency Hopping Spread Spectrum

Number of channels : 79

Channel Spacing : 1MHz

Channel Access Protocol : Frequency Hopping

Type of Modulation : GFSK(1Mbps), DQPSK(2Mbps), 8-DPSK(3Mbps)

Power Source : Lithium Ion Rechargeable Battery(DC 3.7 V)

1.1 Tested Frequency

	LOW	MID	HIGH
Frequency (MHz)	2402	2441	2480

1.2 Tested Mode

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Tested Ch	Modulation Technology	Modulation Type	Packet Type
Low, Mid, High	FHSS	GFSK	DH 5
Low, Mid, High	FHSS	8-DPSK	3DH 5

1.3 Model Differences

Not applicable

1.4 Device Modifications

The following modifications were necessary for compliance:

Not applicable

1.5 Peripheral Devices

Device	Manufacturer	Model No.	Serial No.	FCC ID or DoC
Notebook PC	TOSHIBA	PSL48K-00L00K	Z7037782R	DoC
AC/DC ADAPTOR (for PC)	DELTA ELECTRONICS	ADP-75SB BB	T8W0746330531	-

1.6 Calibration Details of Equipment Used for Measurement

Test equipment and test accessories are calibrated on regular basis. The maximum time between calibrations is one year or what is recommended by the manufacturer, whichever is less. All test equipment calibrations are traceable to the Korea Research Institute of Standards and Science (KRISS), therefore, all test data recorded in this report is traceable to KRISS.

1.7 Test Facility

The measurement facility is located at 386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea.



CTK Co., Ltd.
The Prime Leader of Global Regulatory Compliance

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-339-9855
www.e-ctk.com

1.8 Laboratory Accreditations and Listings

Country	Agency	Scope of Accreditation	Logo
USA	FCC	3 & 10 meter Open Area Test Sites and one conducted site to perform FCC Part 15/18 measurements.	 805871
JAPAN	VCCI	10 meter Open Area Test Site and one conducted site.	 R-948, C-986
KOREA	KCC	EMI (10 meter Open Area Test Site and two conducted sites) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	 No. 51, KR0025
International	KOLAS	EMC	



CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-339-9855
www.e-ctk.com

2.0 Summary of tests

FCC Part Section(s)	Parameter	Limit	Test Condition	Status (note 1)
15.247(a)	Carrier Frequency Separation	> 25 kHz	Conducted	C
15.247(a)	Number of Hopping Frequencies	> 15 hops		C
15.247(a)	20 dB Bandwidth	NA		C
15.247	Dwell Time	< 0.4 seconds		C
15.247(b)	Transmitter Output Power	< 0.125 Watts		C
15.247(d)	Conducted Spurious emission	> 20 dBc		C
15.247(d)	Band Edge	> 20 dBc		C
15.249 /15.209	Field Strength of Harmonics	< 54 dBuV (at 3m)	Radiated	C
15.207 /15.107	AC Conducted Emissions	EN 55022	Line Conducted	C

Note 1: C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable

Note 2: The data in this test report are traceable to the national or international standards.

The sample was tested according to the following specification:
- FCC Part 15.247, ANSI C63.4-2003

2.1 Transmitter Requirements

2.1.1 Carrier Frequency Separation

Test Location

RF Test Room

Test Procedures

The carrier frequency separation was measured with a spectrum analyzer connected to the antenna terminal, while EUT has its hopping function enabled.

After the trace being stable, the reading value between the peaks of the adjacent channels using the marker-delta function was recorded as the measurement results.

The spectrum analyzer is set to:

Span = 3 MHz (wide enough to capture the peaks of two adjacent channels)

RBW = 30 kHz ($\geq 1\%$ of the span) Sweep = auto

VBW = 30 kHz ($\geq$ RBW) Detector function = peak

Trace = max hold




Figure 1 : Measurement setup for the carrier frequency separation

Limit

§15.247(a)(1) Frequency hopping system operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-third of 20dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Results

Test mode : GFSK, CFG PKT Packet Type : 15 Packet Size : 339(DH5)

Channel	Adjacent Hopping Channel Separation (kHz)	Two-third of 20dB bandwidth (kHz)	Minimum Bandwidth (kHz)	Result
2441MHz	996	635	25	Complies

Test mode : 8-DPSK, CFG PKT Packet Type : 31 Packet Size : 1021(3DH5)

Channel	Adjacent Hopping Channel Separation (kHz)	Two-third of 20dB bandwidth (kHz)	Minimum Bandwidth (kHz)	Result
2441MHz	996	843	25	Complies

See next pages for actual measured spectrum plots.




CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-339-9855
www.e-ctk.com


Carrier Frequency Separation

Data Rate : GFSK



Date: 30.JUN.2010 23:39:07

Data Rate : 8-DPSK



Date: 1.JUL.2010 12:27:50

2.1.2 Number of Hopping Frequencies

Test Location

RF Test Room


Test Procedures

The number of hopping frequencies was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

The spectrum analyzer is set to:

Frequency range 1: Start = 2389.5 MHz, Stop = 2439.5 MHz
 2: Start = 2439.5 MHz, Stop = 2489.5 MHz

Span = 50 MHz
RBW = 300 kHz ($\geq 1\%$ of the span)
VBW = 300 kHz ($\geq$ RBW)
Trace = max hold
Sweep = auto
Detector function = peak



Limit

§15.247(a)(1)(iii) For frequency hopping system operating in the 2400-2483.5 MHz band shall use at least 15 hopping frequencies.

Test Results

Test mode : GFSK, CFG PKT Packet Type : 15 Packet Size : 339(DH5)

Total number of Hopping Channels	Result
79	Complies

Test mode : 8-DPSK, CFG PKT Packet Type : 31 Packet Size : 1021(3DH5)

Total number of Hopping Channels	Result
79	Complies

See next pages for actual measured spectrum plots.



CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance


CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea


Tel: +82-31-339-9970 Fax: +82-31-339-9855

www.e-ctk.com

Number of Hopping Frequencies(GFSK)



Date: 30.JUN.2010 23:40:57



Date: 30.JUN.2010 23:41:57



CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance



CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea

Tel: +82-31-339-9970 Fax: +82-31-339-9855

www.e-ctk.com

Number of Hopping Frequencies(8-DPSK)



2.1.3 20 dB bandwidth

Test Location

RF Test Room

Test Procedures

The bandwidth at 20 dB below the highest inband spectral density was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels. After the trace being stable, Use the marker-to peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

Span = 2 MHz (approximately 2 or 3 times of the 20 dB bandwidth)


RBW = 30 kHz ($\geq 1\%$ of the span)

Sweep = auto

VBW = 30 kHz ($\geq$ RBW)

Detector function = peak

Trace = max hold



Limit

Limit : N/A



CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-339-9855
www.e-ctk.com

Test Results

Test mode : GFSK, CFG PKT Packet Type : 15 Packet Size : 339(DH5)

Frequency (MHz)	Channel Number.	Measured Bandwidth (MHz)	Result
2402	0	0.944	Complies
2441	39	0.948	Complies
2480	78	0.952	Complies

Test mode : 8-DPSK, CFG PKT Packet Type : 31 Packet Size : 1021(3DH5)

Frequency (MHz)	Channel Number.	Measured Bandwidth (MHz)	Result
2402	0	1.264	Complies
2441	39	1.264	Complies
2480	78	1.264	Complies

See next pages for actual measured spectrum plots.




CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance


CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-339-9855
www.e-ctk.com

20 dB Bandwidth - GFSK



Date: 30.JUN.2010 23:45:36




Date: 30.JUN.2010 23:46:46



CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-339-9855
www.e-ctk.com



Date: 30.JUN.2010 23:47:49




CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance


CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-339-9855
www.e-ctk.com

20 dB Bandwidth - 8-DPSK



Date: 1.JUL.2010 12:30:02



Date: 1.JUL.2010 12:31:22




CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea

Tel: +82-31-339-9970 Fax: +82-31-339-9855

www.e-ctk.com



Date: 1.JUL.2010 12:32:19

2.1.4 Time of Occupancy (Dwell Time)

Test Location

RF Test Room

Test Procedures

The dwell time was measured with a spectrum analyzer connected to the antenna terminal, while EUT has its hopping function enabled.

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in test setup without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Adjust the center frequency of spectrum analyzer on any frequency be measured and set spectrum analyzer to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
4. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
5. Repeat above procedures until all frequencies measured were complete.
6. The H318B has 3 type of payload, DH1, DH3, DH5. The hopping rate is 1600 per second.

The spectrum analyzer is set to:

Center frequency = the highest, middle, and the lowest channels

Span = zero


RBW = 1 MHz

Trace = max hold

VBW = 1 MHz ($\geq$ RBW)

Detector function = peak

Sweep = as necessary to capture the entire dwell time per hopping channel



Limit

§15.247(a)(1)(iii) For frequency hopping system operating in 2400-2483.5 MHz band, the average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

Test Results

Time of occupancy on the TX channel in 31.6 sec = time domain slot length × hop rate ÷
number of hop per channel × 31.6

Test mode : GFSK

Channel Frequency (MHz)	Packet Type	Dwell Time (ms)	Test Results	
			Time of occupancy on the TX channel in 31.6sec (ms)	Result
2441	DH 1	0.400	128.00	Complies
	DH 3	1.665	266.40	Complies
	DH 5	2.905	309.87	Complies

DH1 Dwell time = $0.400 \text{ ms} \times (1600 \div 2) \div 79 \times 31.6 = 128.00 \text{ ms}$

DH3 Dwell time = $1.665 \text{ ms} \times (1600 \div 4) \div 79 \times 31.6 = 266.40 \text{ ms}$

DH5 Dwell time = $2.905 \text{ ms} \times (1600 \div 6) \div 79 \times 31.6 = 309.87 \text{ ms}$

Test mode : 8-DPSK

Channel Frequency (MHz)	Packet Type	Dwell Time (ms)	Test Results	
			Time of occupancy on the TX channel in 31.6sec (ms)	Result
2441	3DH 1	0.413	132.16	Complies
	3DH 3	1.665	266.40	Complies
	3DH 5	2.925	312.00	Complies


3DH1 Dwell time = $0.413 \text{ ms} \times (1600 \div 2) \div 79 \times 31.6 = 132.16 \text{ ms}$

3DH3 Dwell time = $1.665 \text{ ms} \times (1600 \div 4) \div 79 \times 31.6 = 266.40 \text{ ms}$

3DH5 Dwell time = $2.925 \text{ ms} \times (1600 \div 6) \div 79 \times 31.6 = 312.00 \text{ ms}$


See next pages for actual measured spectrum plots.(Worst case)

Time of Occupancy for PACKET Type DH1(GFSK)



Date: 30.JUN.2010 23:52:38

Time of Occupancy for PACKET Type DH3(GFSK)



Date: 30.JUN.2010 23:51:30




CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance

CTK Co., Ltd.


386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-339-9855
www.e-ctk.com

Time of Occupancy for PACKET Type DH5(GFSK)




Date: 30.JUN.2010 23:50:33

Time of Occupancy for PACKET Type 3DH1(8-DPSK)



Date: 1.JUL.2010 12:35:20

Time of Occupancy for PACKET Type 3DH3(8-DPSK)



Date: 1.JUL.2010 12:34:24



CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance


CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea

Tel: +82-31-339-9970 Fax: +82-31-339-9855

www.e-ctk.com

Time of Occupancy for PACKET Type 3DH5(8-DPSK)



Date: 1.JUL.2010 12:33:40

2.1.5 Maximum peak Conducted Output Power

Test Location

RF Test Room

Test Procedures

The maximum peak conducted output power was measured with a spectrum analyzer connected to the antenna terminal, while EUT has its hopping function disabled at the highest, middle and the lowest available channels.

The spectrum analyzer is set to:

Center frequency = the highest, middle, and the lowest channels

Span = 5 MHz (approximately 5 times of the 20 dB bandwidth)


RBW = 1 MHz (greater than the 20 dB bandwidth of the emission being measured)

VBW = 1 MHz ($\geq$ RBW)

Detector function = peak

Trace = max hold

Sweep = auto



Limit

§5.247(b)(1) The Maximum Peak Output Power Measurement is 0.125 Watts for frequency hopping system operating in 2400-2483.5 MHz employing at least 15 Hopping channels.

Test Results

Test mode : GPSK, CFG PKT Packet Type : 15 Packet Size : 339(DH5)

Frequency (MHz)	Channel No.	Peak output power(dBm)	Peak output power(mW)	Result
2402	0	-4.42	0.36	Complies
2441	39	-4.45	0.36	Complies
2480	78	-5.09	0.31	Complies

Test mode : 8-DPSK, CFG PKT Packet Type : 31 Packet Size : 1021(3DH5)

Frequency (MHz)	Channel No.	Peak output power(dBm)	Peak output power(mW)	Result
2402	0	-7.05	0.20	Complies
2441	39	-7.07	0.20	Complies
2480	78	-7.75	0.17	Complies

See next pages for actual measured spectrum plots.




CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance


CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-339-9855
www.e-ctk.com

Maximum peak Conducted Output Power - GFSK



Date: 2.JUL.2010 12:33:09



Date: 2.JUL.2010 12:35:18




CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea

Tel: +82-31-339-9970 Fax: +82-31-339-9855

www.e-ctk.com



Date: 2.JUL.2010 12:36:40




CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance


CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-339-9855
www.e-ctk.com

Maximum peak Conducted Output Power - 8-DPSK



Date: 2.JUL.2010 12:41:15



Date: 2.JUL.2010 12:40:31




CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea

Tel: +82-31-339-9970 Fax: +82-31-339-9855

www.e-ctk.com



Date: 2.JUL.2010 12:39:13

2.1.6 Band-edge

Test Location

RF Test Room

Test Procedures

The bandwidth at 20 dB down from the highest inband spectral density was measured with a spectrum analyzer connected to the antenna terminal, while EUT has its hopping function disabled at the highest, middle and the lowest available channels.

The spectrum analyzer is set to:

Center frequency = the highest, middle, and the lowest channels

RBW = 100 kHz


VBW = 100 kHz ($\geq$ RBW)

Span = 100 MHz

Trace = max hold

Detector function = peak

Sweep = auto



Limit


> 20 dBc

Test Results


All conducted emission in any 100 kHz bandwidth outside of the spectrum band was at least 20 dB lower than the highest level of the inband spectral density. Therefore the applying equipment meets the requirement.

See next pages for actual measured spectrum plots.

Band – edge (with Hopping) - GFSK



Date: 30.JUN.2010 23:58:52



Date: 1.JUL.2010 00:00:10



www.e-ctk.com

Ref 0 dBm *Att 20 dB *REW 100 kHz Marker 1 [T1] -8.50 dBm
 VEW 100 kHz SWT 2.5 ms 2.402020000 GHz

0 Offset 1 dB

1 PK
 MAXH

D1 -28.5 dBm

Center 2.4 GHz 1 MHz/ Span 10 MHz

The screenshot displays a spectrum analyzer interface. The main plot shows a signal spectrum with a prominent peak at 2.47996 GHz, marked with a green dot and labeled '1'. The peak level is indicated as -10.92 dBm. The signal is centered at 2.4835 GHz with a 10 MHz span. The frequency axis ranges from 2.4735 GHz to 2.4935 GHz. The power axis ranges from -100 dBm to 0 dBm. A red horizontal line is drawn at -30 dBm, labeled 'D1 = -30.91 dBm'. The signal level drops sharply after the peak, reaching a noise floor around -70 dBm. The interface includes various settings: Ref 0 dBm, Att 20 dB, REW 100 kHz, VEW 100 kHz, SWT 2.5 ms, and Marker 1 [T1]. The status bar at the bottom shows 'Center 2.4835 GHz', '1 MHz/', and 'Span 10 MHz'.

Form No.: CTK-RF-EF-Part15 SubpartC(Rev.2)




CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-339-9855
www.e-ctk.com

Band - edge (without Hopping) - GFSK



Date: 30.JUN.2010 23:57:50



Date: 30.JUN.2010 23:57:01




CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance


CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-339-9855
www.e-ctk.com

Band - edge (without Hopping) - 8-DPSK




Date: 1.JUL.2010 12:40:16




Date: 1.JUL.2010 12:39:22

Band – edge (at 20 dB blow) – Low channel Frequency Range = 30 MHz ~ 10th harmonic (GFSK : Worst-Case)



Date: 1.JUL.2010 00:08:18



Date: 1.JUL.2010 00:09:07




CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance


CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-339-9855
www.e-ctk.com

Band – edge (at 20 dB blow) – Mid channel Frequency Range = 30 MHz ~ 10th harmonic (GFSK : Worst-Case)




Date: 1.JUL.2010 00:06:18




Date: 1.JUL.2010 00:07:01

Band – edge (at 20 dB blow) – High channel
Frequency Range = 30 MHz ~ 10th harmonic
(GFSK : Worst-Case)



Date: 1.JUL.2010 00:10:11



Date: 1.JUL.2010 00:10:39

2.1.7 Field Strength of Emissions

Test Location

☒ Testing was performed at a test distance of 3 meter Open Area Test Site

Test Procedures

The height of the measuring antenna was varied between 1 to 4 m and the table was rotated a full revolution in order to obtain maximum values of the electric field intensity. The measurement was made in both the vertical and horizontal polarization, and the maximum value is presented in the report.

The spectrum analyzer is set to:

Center frequency = the worst channel

Frequency Range = 30 MHz ~ 10th harmonic


RBW = 120 kHz (30 MHz ~ 1 GHz) VBW ≥ RBW

= 1 MHz (1 GHz ~ 10th harmonic)

Span = 100 MHz

Detector function = Quasi-peak

Trace = max hold



Limit

- 15.209(a)

Frequency(MHz)	Field Strength uV/m@3m	Field Strength dBuV/m@3m
30-88	100**	40
88-216	150**	43.5
216-960	200**	46
Above 960	500	54

** Except as provided in 15.209(g).fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72MHz, 76-88MHz, 174-216MHz, 470-806MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g.15.231 and 15.241.

Test Results

Test mode : Hopping(GFSK), CFG PKT Packet Type : 15 Packet Size : 339(DH5)

EUT	Voice Sense QWERTY	Measurement Detail	
Model	V400Q	Frequency Range	Below 1000MHz
Test mode	GFSK (Worst case)	Detector function	Quasi-Peak

The requirements are:

☒ Complies

Frequency (MHz)	Measured Data (dBuV/m)	Margin (dB)	Remark
678.52	42.9	3.1	Quasi-peak

Test Data

Frequency [MHz]	Reading [dBuV / m]	Pol.	Height [m]	Correction Factor			Limits [dBuV / m]	Result [dBuV / m]	Margin [dB]
				Antenna	Cable	Amp. Gain			
219.54	57.7	H	2.5	8.5	1.7	31.3	46.0	36.6	9.4
220.52	57.5	H	2.0	8.5	1.7	31.3	46.0	36.4	9.6
226.10	57.7	H	1.9	8.8	1.8	31.3	46.0	37.0	9.0
624.69	52.5	V	1.0	17.6	3.9	31.3	46.0	42.7	3.3
632.34	52.5	H	2.5	17.7	3.9	31.3	46.0	42.8	3.2
678.52	52.0	H	2.3	18.3	3.9	31.3	46.0	42.9	3.1

H : Horizontal, V : Vertical

Result = Reading + Antenna + Cable - Amp.Gain

Remark :

1. The field strength of spurious emission was measured in the following position: EUT stand-up position(Z axis), lie-down position(X,Y axis). The worst emission was found in stand-up position(Z axis) and the worst case was recorded.

Test Results

Test mode : GFSK, CFG PKT Packet Type : 15 Packet Size : 339(DH5)

EUT	Voice Sense QWERTY	Measurement Detail	
Model	V400Q	Frequency Range	1-25GHz
Channel	Channel 0	Detector function	Peak
Test Mode	GFSK (Worst case)		

Remarks

We have tested three mode (X, Y, Z). The worst mode (X axis) for final test.

The requirements are:

☒ Complies

Frequency (MHz)	Measured Data (dBuV/m)	Margin (dB)	Remark
4803.75	47.6 / 54.9	6.4 / 19.1	Average / Peak

Test Data

Frequency [MHz]	Reading [dBuV/m] AV / Peak	Pol.	Height [m]	Correction Factor			Limits [dBuV/m] AV / Peak	Result [dBuV/m] AV / Peak	Margin [dB] AV / Peak
				Antenna	Amp. Gain	Cable			
4803.75	38.4 / 45.7	V	1.0	32.7	34.9	11.4	54.0 / 74.0	47.6 / 54.9	6.4 / 19.1

Restricted band edge test data

Measured frequency range : 2310-2390 MHz, 2483.5-2500 MHz

Frequency [MHz]	Reading [dBuV / m]	Pol.	Height [m]	Correction Factor			Limits [dBuV / m]	Result [dBuV / m]	Margin [dB]
				Antenna	Amp. Gain	Cable			
No emissions were detected at a level greater than 20dB below limit.									

Test Results

Test mode : GFSK, CFG PKT Packet Type : 15 Packet Size : 339(DH5)

EUT	Voice Sense QWERTY	Measurement Detail	
Model	V400Q	Frequency Range	1-25GHz
Channel	Channel 39	Detector function	Peak
Test Mode	GFSK (Worst case)		

Remarks

We have tested three mode (X, Y, Z). The worst mode (X axis) for final test.

The requirements are:

☒ Complies

Frequency (MHz)	Measured Data (dBuV/m)	Margin (dB)	Remark
4882.00	48.6 / 53.6	5.4 / 20.4	Average / Peak

Test Data

Frequency [MHz]	Reading [dBuV/m] AV / Peak	Pol.	Height [m]	Correction Factor			Limits [dBuV/m] AV / Peak	Result [dBuV/m] AV / Peak	Margin [dB] AV / Peak
				Antenna	Amp. Gain	Cable			
4882.00	39.4 / 44.4	V	1.0	32.7	34.9	11.4	54.0 / 74.0	48.6 / 53.6	5.4 / 20.4

Restricted band edge test data

Measured frequency range : 2310-2390 MHz, 2483.5-2500 MHz

Frequency [MHz]	Reading [dBuV / m]	Pol.	Height [m]	Correction Factor			Limits [dBuV / m]	Result [dBuV / m]	Margin [dB]
				Antenna	Amp. Gain	Cable			
No emissions were detected at a level greater than 20dB below limit.									



CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-339-9855
www.e-ctk.com

Test Results

Test mode : GFSK, CFG PKT Packet Type : 15 Packet Size : 339(DH5)

EUT	Voice Sense QWERTY	Measurement Detail	
Model	V400Q	Frequency Range	1-25GHz
Channel	Channel 78	Detector function	Peak
Test Mode	GFSK (Worst case)		

Remarks

We have tested three mode (X, Y, Z). The worst mode (X axis) for final test.

The requirements are:

☒ Complies

Frequency (MHz)	Measured Data (dBuV/m)	Margin (dB)	Remark
4959.80	49.8 / 55.0	4.2 / 19.0	Average / Peak

Test Data

Frequency [MHz]	Reading [dBuV/m] AV / Peak	Pol.	Height [m]	Correction Factor			Limits [dBuV/m] AV / Peak	Result [dBuV/m] AV / Peak	Margin [dB] AV / Peak
				Antenna	Amp. Gain	Cable			
4959.80	40.6 / 45.8	V	1.1	32.7	34.9	11.4	54.0 / 74.0	49.8 / 55.0	4.2 / 19.0

Restricted band edge test data

Measured frequency range : 2310-2390 MHz, 2483.5-2500 MHz

Frequency [MHz]	Reading [dBuV / m]	Pol.	Height [m]	Correction Factor			Limits [dBuV / m]	Result [dBuV / m]	Margin [dB]
				Antenna	Amp. Gain	Cable			
No emissions were detected at a level greater than 20dB below limit.									



CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-339-9855
www.e-ctk.com

2.1.8 AC Conducted Emissions

Test Location

Shielded Room

Frequency Range of Measurement

150 kHz to 30 MHz

Instrument Settings

IF Band Width: 9 kHz

Test Procedures

The EUT was placed on a non-metallic table 0.8m above the metallic, grounded floor and 0.4m from the reference ground plane wall. The distance to other metallic surfaces was at least 0.8m.

Amplitude measurements were performed with a quasi-peak detector and an average detector.

Limit

- 15.207(a)

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56*	56 to 46*
0.5 ~ 5	56	46
5 ~ 30	60	50

* Decreases with the logarithm of the frequency.

Test Results

The requirements are:

☒ Complies

**Test mode : Hopping(GFSK), CFG PKT Packet Type : 15,
Packet Size : 339(DH5), Battery Charging mode**

Frequency (MHz)	Measured Data (dBuV/m)	Margin (dB)	Remark
0.54	49.9	6.1	Quasi-peak



CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea

Tel: +82-31-339-9970 Fax: +82-31-339-9855

www.e-ctk.com

Test Data

Frequency [MHz]	Correction Factor		Line	Quasi-peak				Average			
	LISN	Cable		Limit	Reading	Result	Margin	Limit	Reading	Result	Margin
				[dB μ V]	[dB μ V]	[dB μ V]	[dB]	[dB μ V]	[dB μ V]	[dB μ V]	[dB]
0.20	10.0	0.1	H	63.6	45.4	55.5	8.1	53.6	33.2	43.3	10.3
0.54	10.0	0.1	H	56.0	39.8	49.9	6.1	46.0	25.5	35.6	10.4
0.60	10.0	0.1	H	56.0	39.8	49.9	6.1	46.0	25.2	35.3	10.7
0.65	10.0	0.1	N	56.0	38.5	48.6	7.4	46.0	19.5	29.6	16.4
0.66	10.0	0.1	N	56.0	39.1	49.2	6.8	46.0	20.4	30.5	15.5
0.68	10.0	0.1	H	56.0	39.3	49.4	6.6	46.0	22.8	32.9	13.1

H : HOT, N : NEUTRAL



CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance

CTK Co., Ltd.


386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea

Tel: +82-31-339-9970


Fax: +82-31-339-9855

www.e-ctk.com

[Hot]



[NEUTRAL]





CTK Co., Ltd.
The Prime Leader of Global Regulatory Compliance

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea

Tel: +82-31-339-9970 Fax: +82-31-339-9855

www.e-ctk.com

APPENDIX A – Test Equipment Used For Tests

	Name of Equipment	Manufacturer	Model No.	Serial No.	Due Date
1	Signal Analyzer	Agilent	N9020A	MY48011598	2010-10-30
2	Spectrum Analyzer	Rohde & Schwarz	FSP-30	100994	2010-10-30
3	EMI Test Receiver	Rohde & Schwarz	ESVS30	826638/008	2010-08-10
4	ULTRA Broadband Antenna	Rohde & Schwarz	HL562	361324/014	2011-11-18
5	LOOP ANTENNA	EMCO	6502	9107-2652	2010-10-13
6	System Power Supply	HP	6032A	3440A-10521	2010-07-07
7	EPM Series Power Meter	HP	E4418A	GB38272734	2010-10-30
8	Power Sensor	HP	8487A	3318A03524	2010-07-09
9	Audio Analyzer	HP	8903B	2747A03432	2010-11-03
10	ESG-D Series Signal Generator	Agilent	E4432B	US40054094	2010-10-30
11	SYNTHESIZED SWEEPER	HP	8341B	2819A01563	2010-10-30
12	Modulation Analyzer	HP	8901B	3438A05228	2010-11-06
13	Attenuator	HP	8494A	3308A33351	2010-11-02
14	Temp&Humi Chamber	Kunpoong	KP-1000	2002KP050041	2011-01-25
15	DC POWER SUPPLY	Agilent	E3632A	MY40011638	2010-10-30
16	EMC Analyzer	Agilent	E7405A	MY45110859	2011-01-25
17	Horn Antenna	ETS-Lindgren	3115	00078894	2010-12-18
18	Horn Antenna	ETS-Lindgren	3115	00078895	2010-12-18
19	Dipole Antenna	SCHWARZBECK	VHA 9103	VHA91032557	2010-11-27
20	Dipole Antenna	SCHWARZBECK	UHA 9105	UHA91052417	2010-11-27
21	OPT H64 AMPLIFIER	HP	8447F	3113A06814	2011-03-31
22	PREAMPLIFIER	Agilent	8449B	3008A02307	2010-10-30
23	Radio Communication Tester	Rohde & Schwarz	CMU200	106765	2011-02-23
24	Band Reject Filter	Wainwright Instruments	WRCG824	-	2011-04-01
25	Band Reject Filter	Wainwright Instruments	WRCG1750	-	2011-04-01
26	Field Strength Meter	Rohde & Schwarz	ESHS30	862024/001	2011-03-08
27	LISN	Rohde & Schwarz	ESH3-Z5	100207	2010-12-15
28	LISN	EMCO	3825/2	9206-1971	2010-12-16
29	DC POWER SUPPLY	Agilent	E3632A	MY40011638	2010-10-30