

APPENDIX

Specifications

LCD viewable size	Type	• 15.0" viewable diagonal TFT type
	Pixel pitch	• 0.297(H) x 0.297(V)mm
	Glass surface	• Anti-Glare, Hard Coating
Viewable angle		• L/R : 65°/ 65°, U/D : 45°/ 65°
Contrast ratio		• 300:1 (typical)
Brightness		• 250 cd/m ² (typical)
Resolution		• 1024 x 768
Displayable color		• 16.7M(Full color)
Frame frequency (Refresh rate)		• Support range : 56 to 75Hz • Recommended : 60Hz
User controls		• Auto-Adjust, Brightness, Contrast, Position, Color, Language, OSD Adjust
Plug & play		• VESA DDC 1/2B
I/O Connectors		• DC Power in, VGA 15-pin D-sub
Power		• 100~240V
Power consumption (Max.)		• 40W
AC/DC Adapter		• Input : Universal AC100 ~ 240V • Output : DC 12V • TUV/GS, UL/cUL, CSA, CE,
Active area		• 304.1mm(H) x 228.1mm(V)
Dimensions (Physical)		• 380mm(W) x 410mm(H) x 150mm(D)
Weight		• 4.7Kg
Option		• Pivot software, Speaker