



Product Service

Choose certainty.
Add value.

Report On

FCC Testing of the
Cobham Tactical Communications Inca Repeater
In accordance with FCC CFR 47 Part 15B

COMMERCIAL-IN-CONFIDENCE

FCC ID: QKE-90136040

Document 75925939 Report 01 Issue 2

July 2014



Product Service

TÜV SÜD Product Service, Octagon House, Concorde Way, Segensworth North,
Fareham, Hampshire, United Kingdom, PO15 5RL
Tel: +44 (0) 1489 558100. Website: www.tuv-sud.co.uk

COMMERCIAL-IN-CONFIDENCE

REPORT ON

FCC Testing of the
Cobham Tactical Communications Inca Repeater
In accordance with FCC CFR 47 Part 15B

Document 75925939 Report 01 Issue 2

July 2014

PREPARED FOR

Cobham Tactical Communications
Skindbjergvej
Grenaa
8500
Denmark

PREPARED BY


Natalie Bennett
Senior Administrator, Technical Solutions

APPROVED BY


Ryan Henley
Authorised Signatory

DATED


14 May 2014

This report has been up-issued to Issue 2 to include the FCC ID.

ENGINEERING STATEMENT

The measurements shown in this report were made in accordance with the procedures described on test pages. All reported testing was carried out on a sample equipment to demonstrate limited compliance with FCC CFR 47 Part 15B. The sample tested was found to comply with the requirements defined in the applied rules.

Test Engineer(s):


Tony Guy


Paul Joynson





CONTENTS

Section		Page No
1	REPORT SUMMARY	3
1.1	Introduction	4
1.2	Brief Summary of Results	5
1.3	Application Form	6
1.4	Product Information	8
1.5	Test Conditions	8
1.6	Deviations from the Standard	8
1.7	Modification Record	8
2	TEST DETAILS	9
2.1	AC Line Conducted Emissions	10
2.2	Radiated Emissions	13
3	TEST EQUIPMENT USED	16
3.1	Test Equipment Used	17
3.2	Measurement Uncertainty	18
4	ACCREDITATION, DISCLAIMERS AND COPYRIGHT.....	19
4.1	Accreditation, Disclaimers and Copyright.....	20



Product Service

SECTION 1

REPORT SUMMARY

FCC Testing of the
Cobham Tactical Communications Inca Repeater
In accordance with FCC CFR 47 Part 15B



1.1 INTRODUCTION

The information contained in this report is intended to show verification of the FCC Testing of the Cobham Tactical Communications Inca Repeater to the requirements of FCC CFR 47 Part 15B.

Objective	To perform FCC Testing to determine the Equipment Under Test's (EUT's) compliance with the Test Specification, for the series of tests carried out.
Manufacturer	Cobham Tactical Communications
Model Number(s)	Inca Repeater
Serial Number(s)	891050
Number of Samples Tested	1
Test Specification/Issue/Date	FCC CFR 47 Part 15B (2013)
Incoming Release Date	Application Form 26 March 2014
Disposal Reference Number	Held Pending Disposal
Date	Not Applicable
Order Number	23561-3
Date	19 February 2014
Start of Test	14 March 2014
Finish of Test	21 March 2014
Name of Engineer(s)	P Joynson T Guy
Related Document(s)	ANSI C63.4 (2003)



1.2 BRIEF SUMMARY OF RESULTS

A brief summary of the tests carried out in accordance with FCC CFR 47 Part 15B is shown below.

Section	Spec Clause	Test Description	Result	Comments/Base Standard
Idle				
2.1	15.107	AC Line Conducted Emissions	Pass	ANSI C63.4 (2003)
2.2	15.109	Radiated Emissions	Pass	ANSI C63.4 (2003)



1.3 APPLICATION FORM

APPLICANT'S DETAILS			
COMPANY NAME :	Cobham Spectronic A/S		
ADDRESS :	Skindbjerg Vej 44..... DK- 8500 Grenaa..... Denmark.....		
NAME FOR CONTACT PURPOSES :	Lars Julsgaard.....		
TELEPHONE NO:	+45 87918122..... FAX NO: +45 87918181.....		
E-MAIL:	Lars.Julsgaard@cobham.com.....		
EQUIPMENT INFORMATION			
Model name/number	Inca Repeater...	Identification/Part number	90136041.....
Hardware Version0202.....	Software Version	...1.0.2.....
Manufacturer	Cobham Spectronic A/S	Country of Origin	Denmark.....
FCC ID	Industry Canada ID
Technical description (a brief description of the intended use and operation) Transmitter with repeater functionality operating in the VHF band – to be operated by professionals.			
<u>Supply Voltage:</u> <input type="checkbox"/> AC mains State AC voltage V and AC frequency Hz <input checked="" type="checkbox"/> DC (external) State DC voltage ...12 V and DC current 2,5 . A <input type="checkbox"/> DC (internal) State DC voltage V and Battery type			
<u>Frequency characteristics:</u> Transmitter Frequency range 150. MHz to ...174 MHz Channel spacing ...12,5kHz..... (if channelized) Receiver Frequency range to ... Channel spacing (if different) Designated test frequencies: Bottom:150..... MHz Middle:158 MHz Top:174 MHz Intermediate Frequencies : MHz Highest Internally Generated Frequency : MHz			
<u>Power characteristics:</u> Maximum transmitter power 5 W Minimum transmitter power 0,320 W <input checked="" type="checkbox"/> Continuous transmission <input type="checkbox"/> Intermittent transmission State duty cycle If intermittent, can transmitter be set to continuous transmit test mode? Y/N			
<u>Antenna characteristics:</u> <input type="checkbox"/> [BNC] Antenna connector State impedance 50 ohm <input type="checkbox"/> Temporary antenna connector State impedance ohm <input type="checkbox"/> Integral antenna Type State gain dBi <input type="checkbox"/> External Antenna Type State gain0... dBi			
<u>Modulation characteristics:</u> <input type="checkbox"/> Amplitude <input type="checkbox"/> Other <input checked="" type="checkbox"/> Frequency Details: ...FM..... <input type="checkbox"/> Phase (GMSK, QSPK etc) Can the transmitter operate un-modulated? Y ITU Class of emission:			
<u>Battery/Power Supply</u> Model name/number Identification/Part number Manufacturer Country of Origin			
<u>Ancillaries (if applicable)</u> Model name/number Identification/Part number Manufacturer Country of Origin			
<u>Extreme conditions:</u> Maximum temperature 55... °C Minimum temperature 0 °C Maximum supply voltage 15,6 V Minimum supply voltage 10,0 V			



Product Service

I hereby declare that I am entitled to sign on behalf of the applicant and that the information supplied is correct and complete.

Signature: A handwritten signature in blue ink, appearing to read "Lars Julsgaard".

Name : Lars Julsgaard

Position held : Engineering Manager - HW & Partnering

Date : 26-03-2014



1.4 PRODUCT INFORMATION

1.4.1 Technical Description

The Equipment Under Test (EUT) was a Cobham Tactical Communications Inca Repeater. A full technical description can be found in the manufacturer's documentation.

1.5 TEST CONDITIONS

For all tests the EUT was set up in accordance with the relevant test standard and to represent typical operating conditions. Tests were applied with the EUT situated in a shielded enclosure.

The EUT was powered from a 110 V AC supply.

FCC Measurement Facility Registration Number
90987 Octagon House, Fareham Test Laboratory

1.6 DEVIATIONS FROM THE STANDARD

No deviations from the applicable test standard were made during testing.

1.7 MODIFICATION RECORD

Modification State	Description of Modification still fitted to EUT	Modification Fitted By	Date Modification Fitted
Serial Number: IMEI 004401115077063			
0	As supplied by manufacturer.	N/A	N/A
1	Software only modification adding shutdown functionality to the RF bias circuitry. This included implementation of 1 pin on microprocessor board. See manufacturer's technical documentation for further details.	Lars Julsgaard	10 March 2014

The table above details modifications made to the EUT during the test programme. The modifications incorporated during each test are recorded on the appropriate test pages.



Product Service

SECTION 2

TEST DETAILS

FCC Testing of the
Cobham Tactical Communications Inca Repeater
In accordance with FCC CFR 47 Part 15B



2.1 AC LINE CONDUCTED EMISSIONS

2.1.1 Specification Reference

FCC CFR 47 Part 15B, Clause 15.107

2.1.2 Equipment Under Test and Modification State

Inca Repeater S/N: 891050 - Modification State 1

2.1.3 Date of Test

14 March 2014

2.1.4 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.1.5 Test Procedure

A test environment and testing arrangement meeting the specification of ANSI C63.4 was used during all testing. The Equipment Under Test (EUT) was set upon a non-conducting platform at an elevation of 80 cm above a horizontal reference ground plane. A vertical reference ground plane was situated 40 cm from the EUT and bonded to the horizontal reference ground plane.

The EUT was powered by a Line Impedance Stabilization Network (LISN), whereby emissions measurements of the current-carrying conductors were made through this LISN. The LISN was bonded to the horizontal reference ground plane with a separation distance greater than 80 cm from the EUT. A mains supply cable of 1 m length was used to supply mains power to the EUT from the LISN.

A preliminary emissions scan was conducted for each current-carrying conductor of the EUT, using a peak detector over a frequency range of 150 kHz to 30 MHz. At least six of the greatest peak emissions, frequency positions were selected from each preliminary emissions scan for further evaluation as final measuring points.

Final measurement points were measured using quasi-peak and average detectors. All final measurements were assessed against the Class B emission limits in Clause 15.107 of FCC CFR 47 FCC Part 15.


2.1.6 Environmental Conditions

Ambient Temperature	23°C
Relative Humidity	29%



2.1.7 Test Results


Live Line



Frequency (MHz)	QP Level (dBuV)	QP Limit (dBuV)	QP Margin (dBuV)	AV Level (dBuV)	AV Limit (dBuV)	AV Margin (dBuV)
0.210	32.8	63.2	-30.4	13.8	53.2	-39.4
0.270	28.4	61.1	-32.7	12.5	51.1	-38.6
0.392	18.2	58.0	-39.8	10.6	48.0	-37.5
1.046	15.5	56.0	-40.5	8.8	46.0	-37.2
3.284	13.3	56.0	-42.7	7.0	46.0	-39.0
25.720	11.1	60.0	-48.9	5.2	50.0	-44.8



Product Service

Neutral Line

Frequency (MHz)	QP Level (dBuV)	QP Limit (dBuV)	QP Margin (dBuV)	AV Level (dBuV)	AV Limit (dBuV)	AV Margin (dBuV)
0.156	24.8	65.7	-40.9	17.5	55.7	-38.2
0.201	31.6	63.6	-31.9	13.9	53.6	-39.6
0.419	19.6	57.5	-37.9	10.6	47.5	-36.9
0.478	21.5	56.4	-34.8	10.5	46.4	-35.8
2.526	13.1	56.0	-42.9	6.9	46.0	-39.1
23.386	10.8	60.0	-49.2	4.9	50.0	-45.1



2.2 RADIATED EMISSIONS

2.2.1 Specification Reference

FCC CFR 47 Part 15B, Clause 15.109

2.2.2 Equipment Under Test and Modification State

Inca Repeater S/N: 891050 - Modification State 1

2.2.3 Date of Test

21 March 2014

2.2.4 Test Equipment Used

The major items of test equipment used for the above tests are identified in Section 3.1.

2.2.5 Test Procedure

A test environment and testing arrangement meeting the specification of ANSI C63.4 was used during all testing. The Equipment Under Test (EUT) was set upon a non-conducting platform at an elevation of 80 cm above a horizontal reference ground plane.

The horizontal reference ground plane encompasses a turntable which is used to adjust the azimuth of the EUT. An antenna positioner is used to elevate the measuring antenna above the horizontal reference ground plane whereby the antenna elevation is adjustable between 1 m and 4 m.

At least six of the greatest peak emissions, frequency positions were selected from the exploratory radiated emissions measurements for further evaluation as final measuring points.

To ascertain the azimuth and measuring antenna polarization that yields the highest peak emission level, each final measurement frequency was investigated by continuous azimuth emissions searching with the measuring antenna in both vertical and horizontal polarizations. For each final measurement frequency, the respective peak emission azimuth and measuring antenna polarization was used during a measuring antenna elevation search from 1 m to 4 m. Each final measurement frequency was then measured with the EUT azimuth, measuring antenna height and polarization that yielded the greatest peak emission level.

Final measurement points over the frequency range of 30 MHz to 1 GHz were measured using a quasi-peak detector. Final measurement points over the frequency range of 1 GHz and 2 GHz were measured using peak and average methods. Peak measurements were made using a peak detector with 1 MHz resolution and video bandwidths. Average measurements were made using a resolution bandwidth of 1 MHz and a video bandwidth of 10 kHz.

All final measurements were assessed against the class B emission limits in Clause 15.109 of FCC CFR 47 FCC Part 15.




2.2.6 Environmental Conditions

Ambient Temperature 21.3°C
 Relative Humidity 33.5%

2.2.7 Test Results


30 MHz to 1 GHz



Frequency (MHz)	QP Level (dB μ V/m)	QP Level (μ V/m)	QP Limit (dB μ V/m)	QP Limit (μ V/m)	QP Margin (dB μ V/m)	QP Margin (μ V/m)	Angle (Deg)	Height (m)	Polarity
30.776	29.6	30.19	40.0	100	-10.4	-69.81	360	1.00	Horizontal
136.144	27.3	23.17	43.5	150	-16.2	-76.83	335	1.00	Vertical
142.560	21.9	12.45	43.5	150	-21.6	-87.55	0	1.20	Vertical
154.329	25.2	18.19	43.5	150	-18.3	-81.81	212	1.00	Vertical
163.742	30.0	31.62	43.5	150	-13.5	-68.38	217	1.15	Vertical
776.463	32.8	43.65	46.0	200	-13.2	-56.35	0	1.00	Horizontal
882.034	33.5	47.31	46.0	200	-12.5	-52.69	360	1.00	Vertical
901.394	33.6	47.86	46.0	200	-12.4	-52.14	260	2.59	Vertical



Product Service

1 GHz to 2 GHz

Date: 21.MAR.2014 15:18:48



Product Service

SECTION 3

TEST EQUIPMENT USED



3.1 TEST EQUIPMENT USED

List of absolute measuring and other principal items of test equipment.

Instrument	Manufacturer	Type No.	TE No.	Calibration Period (months)	Calibration Due
Section 2.1 - AC Line Conducted Emissions					
Transient Limiter	Hewlett Packard	11947A	15	12	10-Dec-2014
3 phase LISN	Rohde & Schwarz	ESH2-Z5	323	12	16-Jan-2015
Screened Room (5)	Rainford	Rainford	1545	24	10-Jan-2015
EMI Test Receiver	Rohde & Schwarz	ESU40	3506	12	22-Oct-2014
Section 2.2 - Radiated Emissions					
Antenna (Double Ridge Guide, 1GHz-18GHz)	EMCO	3115	234	12	3-Apr-2014
Load (50ohm/30W)	Weinschel	50T-054	285	12	12-Sep-2014
Turntable Controller	Inn-Co GmbH	CO 1000	1606	-	TU
Programmable Power Supply	Iso-tech	IPS 2010	2435	-	O/P Mon
Antenna (Bilog)	Chase	CBL6143	2904	24	10-Jun-2015
Termination (50ohm, 15W)	Diamond Antenna	DL-30N	3096	12	5-Mar-2015
Termination (50ohm, 15W)	Diamond Antenna	DL-30N	3098	12	27-Mar-2014
EMI Test Receiver	Rohde & Schwarz	ESU40	3506	12	22-Oct-2014
Tilt Antenna Mast	matureo GmbH	TAM 4.0-P	3916	-	TU
Mast Controller	matureo GmbH	NCD	3917	-	TU

TU – Traceability Unscheduled

O/P MON – Output Monitored with Calibrated Equipment



Product Service

3.2 MEASUREMENT UNCERTAINTY

For a 95% confidence level, the measurement uncertainties for defined systems are:-

Test Discipline	MU
Radiated Emissions	30MHz to 1GHz: ± 5.1 dB 1GHz to 40GHz: ± 6.3 dB
AC Line Conducted Emissions	± 3.2 dB



Product Service

SECTION 4

ACCREDITATION, DISCLAIMERS AND COPYRIGHT



Product Service

4.1 ACCREDITATION, DISCLAIMERS AND COPYRIGHT



This report relates only to the actual item/items tested.

Our UKAS Accreditation does not cover opinions and interpretations and any expressed are outside the scope of our UKAS Accreditation.

Results of tests not covered by our UKAS Accreditation Schedule are marked NUA
(Not UKAS Accredited).

This report must not be reproduced, except in its entirety, without the written permission of
TÜV SÜD Product Service

© 2014 TÜV SÜD Product Service