

# Analysis Report

Report No.: 13051480HKG-001

The Equipment Under Test (EUT) is a transmitter of a RC Car operating at 49.860 MHz as dictated by a crystal. The EUT is powered by a 3.0 V DC source (2 x 1.5V "AA" batteries). The EUT has 2 control buttons to control the RC car left, right, forward and backward.

After switching ON the EUT and the receiver of the RC Car, activating the control levers on the EUT can control the receiver moving forward, backward, left or right.

Antenna Type: External integral antenna

Antenna Gain: 0dBi

Nominal rated field strength: 51.2dB $\mu$ V/m at 3m

Maximum allowed field strength of production tolerance: +/- 3dB

According to the KDB 447498:

Based on the Maximum allowed field strength of production tolerance was 54.2dB $\mu$ V/m at 3m in frequency 49.860MHz, thus;

The EIRP = [(FS\*D) ^2\*1000 / 30] = 0.00079mW

Thus;

Conducted power = Radiated Power (EIRP) – Antenna Gain

So;

Conducted Power = 0.0079mW.

The SAR Exclusion Threshold Level for 49.860MHz when the minimum test separation distance is < 50mm:

$$= [474 * (1 + \log_{10}(f/\text{MHz}))]/2$$

$$= 308.6\text{mW}$$

Since the above conducted output power is well below the SAR Exclusion Threshold level, so the EUT is considered to comply with SAR requirement without testing.