

FCC NOTICE

SAFETY INFORMATION

NOTE: Areas with potentially explosive atmospheres are often, but not always, clearly marked. They include fueling areas such as below deck on boats; fuel or chemical transfer or storage facilities; areas where the air contains chemicals or particles, such as grain, dust, or metal powders; and any other area where you would normally be advised to turn off your vehicle engine.

Your wireless hand-held portable transceiver contains a low power transmitter. When the **TALK/CALL** button is pushed it sends out radio frequency (RF) signals. This device is authorized to operate at a duty factor not to exceed 50%.

In August 1996, The Federal Communications Commission (FCC) adopted RF exposure guidelines with safety levels for hand-held wireless devices.

IMPORTANT: To maintain compliance with the FCC's RF exposure guidelines, hold the transmitter and **ANTENNA** at least 2 inches (5 centimeters) from your face and speak in a normal voice, with the **ANTENNA** pointed away from the face.

Use only the supplied **ANTENNA**, **BELT CLIP** and **HEADSET**. Unauthorized antennas, modifications, or attachments could damage the transmitter and may violate FCC regulations.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

CARE AND MAINTENANCE

To clean your **COMMUNICATOR**, use a soft cloth dampened with water. Do not use cleaners or solvents; they can harm the body of the unit and leak inside, causing permanent damage. Use a dry, lint-free cloth to clean the battery contacts. Do not submerge the unit in water. If the unit gets wet, turn it off and remove the battery immediately. Dry the **BATTERY COMPARTMENT** with a soft cloth to minimize potential water damage. Leave the **BATTERY COMPARTMENT COVER** off overnight to ensure complete drying. Do not use the **COMMUNICATOR** until the unit is completely dry.