



Spectrum Research & Testing Lab., Inc.
No. 101-10, Ling 8,
Shan-Tong Li, Chung-Li
City, Taoyuan, Taiwan

TEST REPORT

Reference No.:A04080504
Report No.:FCCA04080504
Page:1 of 47
Date:Oct. 01, 2004

Product Name: Wireless Bluetooth Mouse
Model No.: GME225B
Applicant: IOGEAR, Inc.
23 Hubble, Irvine, Ca92618, USA
Date of Receipt: Aug. 05, 2004
Finished date of Test: Sep. 24, 2004
Applicable Standards: 47 CFR Part 15, Subpart C
ANSI C63.4:2003
DA 00-705

We, **Spectrum Research & Testing Laboratory Inc.**, hereby certify that one sample of the above was tested in our laboratory with positive results according to the above-mentioned standards. The records in the report are an accurate account of the results. Details of the results are given in the subsequent pages of this report.

Checked By :

Sunyou Chen , Date: 10/1/2004
(Sunyou Chen)

Approved By :

J Ho , Date: 10/1/2004
(Johnson Ho, Director)



Table of Contents

1. DOCUMENT POLICY AND TEST STATEMENT.....	4
1.1 DOCUMENT POLICY.....	4
1.2 TEST STATEMENT.....	4
1.3 EUT MODIFICATION.....	4
2. DESCRIPTION OF EUT AND TEST MODE.....	5
2.1 GENERAL DESCRIPTION OF EUT.....	5
2.2 DESCRIPTION OF EUT INTERNAL DEVICE.....	5
2.3 DESCRIPTION OF TEST MODE.....	6
2.4 DESCRIPTION OF SUPPORT UNIT.....	6
3. DESCRIPTION OF APPLIED STANDARDS.....	7
4.1 CONDUCTED EMISSION TEST.....	8
4.1.1 LIMIT.....	8
4.1.2 TEST EQUIPMENT.....	8
4.1.3 TEST SETUP.....	9
4.1.4 TEST PROCEDURE.....	9
4.1.5 EUT OPERATING CONDITION.....	9
4.1.6 TEST RESULT.....	10
4.2 CHANNEL SEPARATION TEST.....	11
4.2.1 LIMIT.....	11
4.2.2 TEST EQUIPMENT.....	11
4.2.3 TEST SET-UP.....	11
4.2.5 EUT OPERATING CONDITION.....	11
4.2.6 TEST RESULT.....	12
4.3 QUANTITY OF HOPPING CHANNEL TEST.....	15
4.3.1 LIMIT.....	15
4.3.2 TEST EQUIPMENT.....	15
4.3.3 TEST SET-UP.....	15
4.3.5 EUT OPERATING CONDITION.....	15
4.3.6 TEST RESULT.....	16
4.4 20DB BANDWIDTH.....	17
4.4.1 LIMIT.....	17
4.4.2 TEST EQUIPMENT.....	17
4.4.3 TEST SET-UP.....	17
4.4.4 TEST PROCEDURE.....	17
4.4.5 EUT OPERATING CONDITION.....	17
4.4.6 TEST RESULT.....	18
4.5 TIME OF OCCUPANCY (DWELL TIME).....	21
4.5.1 LIMIT.....	21
4.5.2 TEST EQUIPMENT.....	21
4.5.3 TEST SET-UP.....	21
4.5.5 EUT OPERATING CONDITION.....	21
4.5.6 TEST RESULT.....	22
4.6 PEAK POWER TEST.....	26



4.6.1 LIMIT	26
4.6.2 TEST EQUIPMENT.....	26
4.6.3 TEST SET-UP.....	26
4.6.5 EUT OPERATING CONDITION	27
4.6.6 TEST RESULT	27
4.7 BAND EDGE TEST	30
4.7.1 LIMIT	30
4.7.2 TEST EQUIPMENT.....	30
4.7.3 TEST SET-UP.....	31
4.7.5 EUT OPERATING CONDITION	32
4.7.6 TEST RESULT	32
4.8 SPURIOUS RADIATED EMISSION TEST	34
4.8.1 LIMIT	34
4.8.2 TEST EQUIPMENT.....	35
4.8.3 TEST SET-UP.....	36
4.8.4 TEST PROCEDURE.....	37
4.8.5 EUT OPERATING CONDITION	37
4.8.6 TEST RESULT	38
5. ANTENNA APPLICATION.....	43
5.1 ANTENNA REQUIREMENT	43
5.2 RESULT	43
6. PHOTOS OF TESTING	44
7. TERMS OF ABRIVATION.....	47



1. DOCUMENT POLICY AND TEST STATEMENT

1.1 DOCUMENT POLICY

- The report shall not be reproduced except in full, without the written approval of SRT Lab, Inc.

1.2 TEST STATEMENT

- The test results in the report apply only to the unit tested by SRT Lab.
- There was no deviation from the requirements of test standards during the test.
- AC power source, 120 VAC/60 Hz, was used during the test.

1.3 EUT MODIFICATION

- No modification in SRT Lab.



2. DESCRIPTION OF EUT AND TEST MODE

2.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Wireless Bluetooth Mouse
MODEL NO.	GME225B
POWER SUPPLY	DC 2.4V, 20mA from battery or PC USB port
CABLE	0.5m shielded USB cable (with one ferrite core)
I/O PORT	USB interface
FREQUENCY BAND	2400 ~ 2483.5MHz
CARRIER FREQUENCY	CH0: 2402MHz ~ CH78: 2480MHz
NUMBER OF CHANNEL	79
CHANNEL SPACING	1MHz
RATED RF OUTPUT POWER	0.001W
MODULATION TYPE	GFSK
BIT RATE OF TRANSMISSION	723Kbps
ANTENNA TYPE	Board antenna
ANTENNA GAIN	-1dBi

NOTE : For more detailed features, please refer to the manufacturer' s specification or User' s Manual of EUT.

2.2 DESCRIPTION OF EUT INTERNAL DEVICE

DEVICE	BRAND / MAKER	MODEL #	FCC ID/DOC	REMARK
N/A				



2.3 DESCRIPTION OF TEST MODE

The EUT was tested for emission measurement under the following situations:

Mode	Power Source	Operating
1	Battery	Link
2	PC USB port	Charge

The EUT was tested under the following channels during the Link mode:
79 channels are provided by EUT. The 3 channels of lower, medium and higher were chosen for test.

Channel	Frequency
0	2402
39	2441
78	2480

NOTE :

1. Below 1 GHz, the channel 0, 39, and 78 were pre-tested in chamber. The channel 78, worst case one, was chosen for conducted and radiated emission test.
2. Above 1 GHz, the channel 0, 39 and 78 were tested individually

2.4 DESCRIPTION OF SUPPORT UNIT

The EUT was configured by the requirement of ANSI C63.4:2003 and CISRP22:2003.
All interface ports were connected to the appropriate support units via specific cables.
The support units and cables are listed below.

NO	DEVICE	BRAND	MODEL #	FCC ID/DOC	CABLE
1	NOTEBOOK	DELL	C510/C610	DOC	1.5m unshielded power cord
2	PRINTER	EPSON	STYLUS C20SX	DOC	1.5m unshielded power cord 1.2m shielded data cable
3	MODEM	ACEEX	DM-1414	DOC	1.5m unshielded DC power cable 1.2m shielded data cable
4	BLUETOOTH DONGLE	CELLINK	BTA-3000	PQY-4710874200258	N/A

NOTE : For the actual test configuration, please refer to the photos of testing.



3. DESCRIPTION OF APPLIED STANDARDS

The EUT is a kind of wireless product and to be connected with a PC system for normal use. According to the specifications provided by the applicant, it must comply with the requirements of the following standards:

47 CFR Part 15, Subpart C

ANSI C63.4:2003

DA 00-705

All tests have been performed and recorded as the above standards.



4 TECHNICAL CHARACTERISTICS TEST

4.1 CONDUCTED EMISSION TEST

4.1.1 LIMIT

Frequency (MHz)	Class A (dB μ V)		Class B (dB μ V)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	79	66	66 - 56	56 - 46
0.50 - 5.0	73	60	56	46
5.0 - 30.0	73	60	60	50

NOTE :

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

4.1.2 TEST EQUIPMENT


The following test equipment was used for the test:

EQUIPMENT/ FACILITIES	SPECIFICATIONS	MANUFACTURER	MODEL#/ SERIAL#	DUE DATE OF CAL. & CAL. CENTER
EMI TEST RECEIVER	9 kHz TO 30 MHz	ROHDE & SCHWARZ	ESHS30/ 826003/008	AUG. 2005 ETC
LISN (for EUT)	50 μ H, 50 ohm	SOLAR ELECTRONICS	FCC-LISN-50-25-2 / 01018	NOV. 2004 ETC
LISN (for Peripheral)	50 μ H, 50 ohm	SOLAR ELECTRONICS	9252-50-R-24-BNC / 951318	JUN. 2005 ETC
50 ohm TERMINATOR	50 ohm	HP	11593A/ 2	MAR. 2005 ETC
COAXIAL CABLE	3m	SUNCITY	J400/ 3M	JUL. 2005 SRT
ISOLATION TRANSFORMER	N/A	APC	AFC-11015/ F102040016	N/A
FILTER	2 LINE, 30A	FIL.COIL	FC-943/ 771	N/A
GROUND PLANE	2.3M (H) x 2.4M (W)	SRT	N/A	N/A
GROUND PLANE	2.4M (H) x 2.4M (W)	SRT	N/A	N/A

NOTE: The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.



4.1.3 TEST SETUP



NOTE:

1. The EUT was put on a wooden table with 0.8m height above ground plane, and 0.4m away from reference ground plane (> 2mx2m).
2. For the actual test configuration, please refer to the photos of testing.
3. The serial no. of the LISN connected to EUT is 951318.
4. The serial no. of the LISN connected to support units is 924839.

4.1.4 TEST PROCEDURE

The EUT was tested according to the requirement of ANSI C63.4:2003 and CISRP22:2003. The frequency spectrum from 0.15 MHz to 30 MHz was investigated. The LISN used was 50 ohm/50 μ H as specified. All readings were quasi-peak and average values with 10 kHz resolution bandwidth of the test receiver. The EUT system was operated in all typical methods by users. Both lines of the power mains of EUT were measured and the cables connected to EUT and support units were moved to find the maximum emission levels for each frequency.

First, Find the margin or higher points at least 6 points by software, then use manual to find the maximum data. The procedure is referred on the test procedure of SRT LAB.

4.1.5 EUT OPERATING CONDITION

1. Set the EUT under transmission condition continuously at a specific channel frequency. (Link mode)
2. Under Windows XP ran "EMI TEST" programs, PC sent "H" pattern or accessed the following peripherals: (Charge mode)
 - RS232 (modem)
 - Printer
 - FDD
 - HDD



4.1.6 TEST RESULT

Temperature:	25 °C	Humidity:	58 %RH
Ferquency Range:	0.15 – 30 MHz	Tested Mode:	Charge
Receiver Detector:	Q.P. and AV.	Tested By:	Peter Tsai
Tested Result:	Pass	Tested Date:	Sep. 14, 2004

Power Line Measured : Line

Freq. (MHz)	Correct. Factor (dB)	Reading Value (dBmV)		Emission Level (dBmV)		Limit (dBmV)		Margin (dB)	
		Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
0.177	0.30	47.02	37.77	47.32	38.07	64.61	54.61	-17.29	-16.54
0.180	0.30	46.98	37.72	47.28	38.02	64.47	54.47	-17.19	-16.45
1.196	0.19	43.46	34.64	43.65	34.83	56.00	46.00	-12.35	-11.17
1.200	0.19	44.08	34.83	44.27	35.02	56.00	46.00	-11.73	-10.98
1.220	0.19	42.76	33.11	42.95	33.30	56.00	46.00	-13.05	-12.70
5.000	0.16	32.70	26.24	32.86	26.40	56.00	46.00	-23.14	-19.60

Power Line Measured : Neutral

Freq. (MHz)	Correct. Factor (dB)	Reading Value (dBmV)		Emission Level (dBmV)		Limit (dBmV)		Margin (dB)	
		Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
0.177	0.30	47.62	37.99	47.92	38.29	64.61	54.61	-16.69	-16.32
0.180	0.30	47.78	38.20	48.08	38.50	64.47	54.47	-16.39	-15.97
1.172	0.19	49.20	37.31	49.39	37.50	56.00	46.00	-6.61	-8.50
1.200	0.19	44.82	35.38	45.01	35.57	56.00	46.00	-10.99	-10.43
1.655	0.19	40.06	34.70	40.25	34.89	56.00	46.00	-15.75	-11.11
5.132	0.16	30.20	18.41	30.36	18.57	60.00	50.00	-29.64	-31.43

NOTE :

1. Measurement uncertainty is +/-1.32dB
2. Emission level = Reading value + Correction factor
3. Correction Factor = Cable loss + Insertion loss of LISN
4. Margin value = Emission level - Limit
5. The emission of other frequencies were very low against the limit.
6. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.



4.2 CHANNEL SEPARATION TEST

4.2.1 LIMIT

FCC Part15, Subpart C Section 15.247(a)(1). Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

FREQUENCY RANGE (MHz)	Limit(kHz)
902-928	>25kHz
2400-2483.5	>25kHz
5725-5850	>25kHz


4.2.2 TEST EQUIPMENT

The following test equipment was used during the radiated emission test:

EQUIPMENT/FACILITIES	SPECIFICATIONS	MANUFACTURER	MODEL#/SERIAL#	DUE DATE OF CAL. & CAL. CENTER
SPECTRUM	9kHz-7GHz	ROHDE & SCHWARZ	FSP7/ 839511/010	MAR. 2005 ETC

NOTE: The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.

4.2.3 TEST SET-UP



The EUT was connected to a spectrum through a 50 Ω RF cable.

4.2.4 TEST PROCEDURE

The EUT was operating in hopping mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.

4.2.5 EUT OPERATING CONDITION

Same as section 4.1.5 of this report.




4.2.6 TEST RESULT

Temperature:	<u>25°C</u>	Humidity:	<u>50%RH</u>
Spectrum Detector:	<u>PK.</u>	Tested Mode:	<u>Link</u>
Tested Result:	<u>Pass</u>	Tested By:	<u>Peter Tsai</u>

CHANNEL NUMBER	CHANNEL FREQUENCY (MHz)	SEPARATION READ VALUE (kHz)	SEPARATION LIMIT (kHz)
0	2402	1000	>25kHz
39	2441	1000	>25kHz
78	2480	1000	>25kHz


CH0:



Date: 10.SEP.2004 16:55:50



CH39:



Date: 10.SEP.2004 16:54:30




Spectrum Research & Testing Lab., Inc.
No. 101-10, Ling 8,
Shan-Tong Li, Chung-Li
City, Taoyuan, Taiwan

TEST REPORT

Reference No.:A04080504
Report No.:FCCA04080504
Page:14 of 47
Date:Oct. 01, 2004

CH78:



Date: 10.SEP.2004 16:53:19



4.3 QUANTITY OF HOPPING CHANNEL TEST

4.3.1 LIMIT

FCC Part15, Subpart C Section 15.247.

FREQUENCY RANGE (MHz)	Limit (Quantity of Hopping Channel)			
	20dB bandwidth <250kHz	20dB bandwidth >250kHz	20dB bandwidth <1MHz	20dB bandwidth >1MHz
902-928	50	25	NA	NA
2400-2483.5	NA	NA	75	15
5725-5850	NA	NA	75	NA


4.3.2 TEST EQUIPMENT

The following test equipment was used during the test:

EQUIPMENT/FACILITIES	SPECIFICATIONS	MANUFACTURER	MODEL#/SERIAL#	DUE DATE OF CAL. & CAL. CENTER
SPECTRUM	9kHz-7GHz	ROHDE & SCHWARZ	FSP7/ 839511/010	MAR. 2005 ETC

NOTE: The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.

4.3.3 TEST SET-UP



The EUT was connected to a spectrum through a 50 RF cable.

4.3.4 TEST PROCEDURE

The EUT was operating in hopping mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.

4.3.5 EUT OPERATING CONDITION

Same as section 4.1.5 of this report.




4.3.6 TEST RESULT

Temperature:	<u>25°C</u>	Humidity:	<u>50%RH</u>
Spectrum Detector:	<u>PK.</u>	Tested Mode:	<u>Link</u>
Tested Result:	<u>Pass</u>	Tested By:	<u>Peter Tsai</u>

HOPPING CHANNEL FREQUENCY RANGE	QUANTITY OF HOPPING CHANNEL READ VALUE	QUANTITY OF HOPPING CHANNEL LIMIT
2402~2480	79	75

CH0-CH78



Date: 10.SEP.2004 16:59:21



4.4 20dB BANDWIDTH

4.4.1 LIMIT

Frequency Range (MHz)	Quantity of Hopping Channel	Limit (kHz)			
		50	25	15	75
902-928		<250	>250	NA	NA
2400-2483.5		NA	NA	>1000	<1000


4.4.2 TEST EQUIPMENT

The following test equipment was used during the test:

EQUIPMENT/FACILITIES	SPECIFICATIONS	MANUFACTURER	MODEL#/SERIAL#	DUE DATE OF CAL. & CAL. CENTER
SPECTRUM	9kHz-7GHz	ROHDE & SCHWARZ	FSP7/ 839511/010	MAR. 2005 ETC

NOTE: The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.

4.4.3 TEST SET-UP



The EUT was connected to a spectrum through a 50 RF cable.

4.4.4 TEST PROCEDURE

The EUT was operating in hopping mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.

4.4.5 EUT OPERATING CONDITION

Same as section 4.1.5 of this report.




4.4.6 TEST RESULT

Temperature:	<u>26°C</u>	Humidity:	<u>55%RH</u>
Spectrum Detector:	<u>PK.</u>	Tested Mode:	<u>Link</u>
Tested Result:	<u>Pass</u>	Tested By:	<u>Peter Tsai</u>

CHANNEL NUMBER	CHANNEL FREQUENCY (MHz)	20dB DOWN BW (MHz)	MINIMUM LIMIT (MHz)
0	2402	0.780	1
39	2441	0.776	1
78	2480	0.764	1


CH0:



Date: 10.SEP.2004 16:45:14




CH39:



Date: 10.SEP.2004 16:43:30



CH78:



Date: 10.SEP.2004 16:41:13



4.5 TIME OF OCCUPANCY (DWELL TIME)

4.5.1 LIMIT

FCC Part15, Subpart C Section 15.247.

FREQUENCY RANGE (MHz)	LIMIT (ms)		
	20dB bandwidth <250kHz(50Channel)	20dB bandwidth >250kHz(25Channel)	20dB bandwidth <1MHz(75Channel)
902-928	400(20s)	400(10s)	NA
2400-2483.5	NA	NA	400(30s)
5725-5850	NA	NA	400(30s)

NOTE: The “()” is all channel’ s average time of occupancy.


4.5.2 TEST EQUIPMENT

The following test equipment was used during the test:

EQUIPMENT/ FACILITIES	SPECIFICATIONS	MANUFACTURER	MODEL#/ SERIAL#	DUE DATE OF CAL. & CAL. CENTER
SPECTRUM	9kHz-7GHz	ROHDE & SCHWARZ	FSP7/ 839511/010	MAR. 2005 ETC

NOTE: The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.

4.5.3 TEST SET-UP



The EUT was connected to a spectrum through a 50 RF cable.

4.5.4 TEST PROCEDURE

The EUT was operating in hopping mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.

4.5.5 EUT OPERATING CONDITION

Same as section 4.1.5 of this report.



4.5.6 TEST RESULT

Temperature: 25°C Humidity: 50%RH
Spectrum Detector: PK. Tested Mode: Link
Tested Result: Pass Tested By: Peter Tsai

Channel Number	CHANNEL FREQUENCY (MHz)	Pulse Time (i s)	Burts (in 1 sec.)	Time of occupancy (Dwell Time) (ms)	Average time of occupancy Limit (ms)
0	2402	420	10	132.72	400
39	2441	420	10	132.72	400
78	2480	420	10	132.72	400

Note:

Dwell Time:


CH0: $420 \times 10 \times 0.4 \times 792 = 132720(i\ s) = 132.72ms$

CH39: $420 \times 10 \times 0.4 \times 792 = 132720(i\ s) = 132.72ms$


CH78: $420 \times 10 \times 0.4 \times 792 = 132720(i\ s) = 132.72ms$



CH0:




Date: 10.SEP.2004 18:22:29




Date: 10.SEP.2004 17:19:14



CH39:




Date: 10.SEP.2004 18:23:22




Date: 10.SEP.2004 17:18:30



CH78:



Date: 10.SEP.2004 18:26:46



Date: 10.SEP.2004 17:16:35



4.6 PEAK POWER TEST

4.6.1 LIMIT

FCC Part15, Subpart C Section 15.247.

FREQUENCY RANGE (MHz)	Quantity of Hopping Channel	LIMIT (W)			
		50	25	15	75
902-928	1(30dBm)	0.125(21dBm)	NA	NA	NA
2400-2483.5	NA	NA	0.125(21dBm)	1(30dBm)	1(30dBm)
5725-5850	NA	NA	NA	NA	1(30dBm)


4.6.2 TEST EQUIPMENT

The following test equipment was used during the test:

EQUIPMENT/FACILITIES	SPECIFICATIONS	MANUFACTURER	MODEL#/SERIAL#	DUE DATE OF CAL. & CAL. CENTER
SPECTRUM	9kHz-7GHz	ROHDE & SCHWARZ	FSP7/ 839511/010	MAR. 2005 ETC
POWER METER	N/A	BOONTON	4232A/ 29001	MAY 2005 ETC

NOTE: The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.

4.6.3 TEST SET-UP



The EUT was connected to a spectrum through a 50 RF cable.



4.6.4 TEST PROCEDURE

The EUT was operating in hopping mode or could control its channel.
 Printed out the test result from the spectrum by hard copy function.
 Recorded the read value of the power meter.

4.6.5 EUT OPERATING CONDITION


Same as section 4.1.5 of this report.

4.6.6 TEST RESULT

Temperature:	<u>25°C</u>	Humidity:	<u>50%RH</u>
Spectrum Detector:	<u>PK.</u>	Tested Mode:	<u>Link</u>
Tested Result:	<u>Pass</u>	Tested By:	<u>Peter Tsai</u>


CHANNEL NUMBER	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)
0	2402	-1.40	30
39	2441	-2.67	30
78	2480	-3.85	30

CH0:






CH39:



Date: 10.SEP.2004 16:36:01



CH78:



Date: 10.SEP.2004 16:36:49



4.7 BAND EDGE TEST

4.7.1 LIMIT

FCC Part15, Subpart C Section 15.247. In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

OPERATING FREQUENCY RANGE (MHz)	SPURIOUS EMISSION FREQUENCY (MHz)	LIMIT	
		Peak power ration to emission(dBc)	Emission level(dBuV/m)
902-928	<902	>20	NA
	>928	>20	NA
	960-1240	NA	54
2400-2483.5	<2400	>20	NA
	>2483.5-2500	NA	54
5725-5850	<5350-5460	NA	54
	<5725	>20	NA
	>5850	>20	NA

4.7.2 TEST EQUIPMENT

The following test equipment was used during the test:


EQUIPMENT/ FACILITIES	SPECIFICATIONS	MANUFACTURER	MODEL#/ SERIAL#	DUE DATE OF CAL. & CAL. CENTER
SPECTRUM	9kHz-7GHz	ROHDE & SCHWARZ	FSP7/ 839511/010	MAR. 2005 ETC

NOTE: The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.




4.7.3 TEST SET-UP

FOR RF CONDUCTED TEST (dBc)



The EUT was connected to the spectrum through a 50 Ω RF cable.

FOR RADIATED EMISSION TEST



NOTE :

1. The EUT system was put on a wooden table with 0.8m heights above a ground plane.
2. For the actual test configuration, please refer to the photos of testing.



4.7.4 TEST PROCEDURE

1. The EUT was operating in hopping mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.
2. The EUT was tested according to the requirement of ANSI C63.4:2003 and CISPR 22:2003. The measurements were made at an open area test site with 10 meter measurement distance under 1 GHz and with 3m distance above 1GHz. The frequency spectrum measured started from 30 MHz. Under 1 GHz. All readings were quasi-peak values with 120 kHz resolution bandwidth of the test receiver. Above 1 GHz, the measurements were made at an open area test site with 3 meter measurement distance and all readings were peak and average values with 1 MHz resolution bandwidth of the test receiver. The EUT system was operated in all typical methods by users. The cables connected to EUT and support units were moved to find the maximum emission levels for each frequency.

4.7.5 EUT OPERATING CONDITION

Same as section 4.1.5 of this report.

4.7.6 TEST RESULT

Temperature:	<u>25° C</u>	Humidity:	<u>60%RH</u>
Spectrum Detector:	<u>PK. & AV.</u>	Tested Mode:	<u>Link</u>
Tested Result:	<u>Pass</u>	Tested By:	<u>Peter Tsai</u>

1. Conducted test

Frequency (MHz)	Peak Power Output (dBm)	Emission read Value(dBm)	Result of Band edge (dBc)	Band edge Limit (dBc)
<2400	-1.06	-35.86	34.80	>20dBc
>2483.5	-3.52	-49.23	45.71	>20dBc

2. Radiated emission test


Frequency (MHz)	Antenna polarization (H/V)	Peak Power Output (dBuV/m)	Emission read Value(dBuV/m)	Band edge Limit (dBuV/m)
<2400	V	42.6	*	54
>2483.5	H	47.6	*	54

NOTE :

1. “*”: The emission of the frequency was very low against the limit.




<2400MHz:



Date: 10.SEP.2004 16:50:00

>2483.5MHz



Date: 10.SEP.2004 16:51:27



4.8 SPURIOUS RADIATED EMISSION TEST

4.8.1 LIMIT

FCC Part15, Subpart C Section 15.209 limit of radiated emission for frequency below1000MHz. The emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

FREQUENCY (MHz)	DISTANCE (m)	FIELD STRENGTH (dBmV/m)
30 - 88	3	40.0
88 - 216	3	43.5
216 - 960	3	46.0
Above 960	3	54.0

NOTE :

1. In the emission tables above , the tighter limit applies at the band edges.
2. Distance refers to the distance between measuring instrument, antenna, and the closest point of any part of the device or system.

FCC Part 15, Section15.35(b) limit of radiated emission for frequency above 1000 MHz

FREQUENCY (MHz)	Class A (dBuV/m) (at 3m)		Class B (dBuV/m) (at 3m)	
	PEAK	AVERAGE	PEAK	AVERAGE
Above 1000	80.0	60.0	74.0	54.0

FCC Part 15, Subpart C Section 15.249. The field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

FUNDAMENTAL FREQUENCY (MHz)	FILED STRENGTH OF FUNDAMENTAL (dBuV/m) (at 3m)		FIELD STRENGTH OF HARMONICS (dBuV/m) (at 3m)	
	PEAK	AVERAGE	PEAK	AVERAGE
902 - 928	114	94	74.0	54.0
2400 - 2483.5	114	94	74.0	54.0
5725 - 5875	114	94	74.0	54.0
24000 - 24250	128	108	88.0	68.0



4.8.2 TEST EQUIPMENT


The following test equipment was used during the radiated emission test:

EQUIPMENT/ FACILITIES	SPECIFICATIONS	MANUFACTURER	MODEL#/ SERIAL#	DUE DATE OF CAL. & CAL. CENTER
EMI TEST RECEIVER	20 kHz TO 1 GHz	ROHDE & SCHWARZ	ESVS30/ 841977/003	SEP. 2005 ETC
BI-LOG ANTENNA	25 MHz TO 2 GHz	EMCO	3142/ 9701-1124	APR. 2005 SRT
SPECTRUM ANALYZER	9 KHz TO 26.5 GHz	HP	8593E/ 3710A03220	MAY 2005 ETC
PRE-AMPLIFIER	1 GHz TO 26.5 GHz	HP	8449B/ 3008A01019	DEC. 2004 ETC
HORN ANTENNA	1 GHz TO 18 GHz	EMCO	3115/ 9602-4681	JAN. 2005 ETC
HORN ANTENNA	18GHz TO 40GHz	ETS	3116/ 2567	OCT. 2004 ETC
OATS	3 – 10 M MEASUREMENT	SRT	SRT-1	APR. 2005 SRT
COAXIAL CABLE	25M	SUNCITY	J400/ 25M	AUG. 2005 SRT
FILTER	2 LINE, 30A	FIL.COIL	FC-943/ 869	N/A
FREQUENCY CONVERTER	N/A	APC	AFC-2KBB/ F100030031	AUG. 2005 SRT

NOTE:

1. The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.
2. The Open Area Test Site (SRT-1) is registered by FCC with No. 90957 and VCCI with No. R-1081.
3. The Open Area Test Site (SRT-2) is registered by FCC with No. 98458 and VCCI with No. R-1168.

4.8.3 TEST SET-UP



NOTE :

1. The EUT system was put on a wooden table with 0.8m heights above a ground plane.
2. For the actual test configuration, please refer to the photos of testing.



4.8.4 TEST PROCEDURE

The EUT was tested according to the requirement of ANSI C63.4:2003 and CISPR 22:2003. The measurements were made at an open area test site with 10 meter measurement distance under 1 GHz and with 3m distance above 1GHz. The frequency spectrum measured started from 30 MHz. Under 1 GHz, all readings were quasi-peak values with 120 kHz resolution bandwidth of the test receiver. Above 1 GHz, the measurements were made at an open area test site with 3 meter measurement distance and all readings were peak or average values with 1 MHz resolution bandwidth of the test receiver. The EUT system was operated in all typical methods by users. The cables connected to EUT and support units were moved to find the maximum emission levels for each frequency.

First, Find the margin or higher points at least 6 points by software, then use manual to find the maximum data. The procedure is referred on the test procedure of SRT LAB.

4.8.5 EUT OPERATING CONDITION

Same as section 4.1.5 of this report.



4.8.6 TEST RESULT

Temperature:	26 °C	Humidity:	62 %RH
Ferquency Range:	30 – 1000 MHz	Measured Distance:	3m
Receiver Detector:	Q.P.	Tested Mode:	Link
Tested By:	Peter Tsai	Tested Date:	Sep. 24, 2004

Antenna Polarization:Horizontal

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Reading Data (dBµV)	Emission Level (dBµV/m)	Limit (dBµV/m)	Margin (dB)	AZ(°)	EL(m)
166.7700	1.23	9.44	18.9	29.6	43.5	-13.9	158.0	3.41
232.7300	1.42	11.90	22.6	35.9	46.0	-10.1	248.0	2.98
265.7100	1.51	13.18	19.2	33.9	46.0	-12.1	348.0	3.15
332.6400	1.73	15.06	16.8	33.6	46.0	-12.4	164.0	2.15
452.9200	2.03	17.10	12.9	32.0	46.0	-14.0	68.0	1.98
666.3200	2.50	21.05	11.2	34.8	46.0	-11.2	249.0	2.06

Antenna Polarization:Vertical

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Reading Data (dBµV)	Emission Level (dBµV/m)	Limit (dBµV/m)	Margin (dB)	AZ(°)	EL(m)
91.1100	0.94	8.42	18.2	27.6	43.5	-15.9	114.0	2.94
165.8000	1.23	9.40	20.1	30.7	43.5	-12.8	160.0	3.31
232.7300	1.42	11.90	18.4	31.7	46.0	-14.3	246.0	3.02
339.4300	1.75	15.10	14.7	31.5	46.0	-14.5	161.0	2.58
452.9200	2.03	17.10	12.5	31.6	46.0	-14.4	71.0	2.15
666.3200	2.50	21.05	10.8	34.4	46.0	-11.6	251.0	2.21

NOTE :

1. Measurement uncertainty is +/-2dB.
2. "**": Measurement does not apply for this frequency.
3. Emission Level = Reading Value + Ant. Factor + Cable Loss.
4. The field strength of other emission frequencies were very low against the limit.



Temperature:	<u>26 °C</u>	Humidity:	<u>62 %RH</u>
Ferquency Range:	<u>30 – 1000 MHz</u>	Measured Distance:	<u>3m</u>
Receiver Detector:	<u>Q.P.</u>	Tested Mode:	<u>Charge</u>
Tested By:	<u>Peter Tsai</u>	Tested Date:	<u>Sep. 24, 2004</u>

Antenna Polarization:Horizontal

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Reading Data (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	AZ(°)	EL(m)
166.7600	1.23	9.44	18.8	29.5	43.5	-14.0	161.0	3.38
232.7300	1.42	11.90	21.5	34.8	46.0	-11.2	247.0	3.02
264.9800	1.50	13.14	20.0	34.6	46.0	-11.4	351.0	3.19
332.6300	1.73	15.06	16.7	33.5	46.0	-12.5	163.0	2.21
452.9200	2.03	17.10	13.0	32.1	46.0	-13.9	70.0	1.94
666.3200	2.50	21.05	11.3	34.9	46.0	-11.1	250.0	1.92

Antenna Polarization:Vertical

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Reading Data (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	AZ(°)	EL(m)
91.1200	0.94	8.42	18.1	27.5	43.5	-16.0	115.0	2.95
166.7700	1.23	9.44	19.8	30.5	43.5	-13.0	161.0	3.29
232.7200	1.42	11.90	18.5	31.8	46.0	-14.2	246.0	2.99
339.4200	1.75	15.10	15.0	31.8	46.0	-14.2	170.0	2.61
452.9200	2.03	17.10	12.4	31.5	46.0	-14.5	71.0	2.13
666.3200	2.50	21.05	11.0	34.6	46.0	-11.4	251.0	2.19

NOTE :

1. Measurement uncertainty is +/-2dB.
2. "": Measurement does not apply for this frequency.
3. Emission Level = Reading Value + Ant. Factor + Cable Loss.
4. The field strength of other emission frequencies were very low against the limit.



Temperature:	28 °C	Humidity:	60 %RH
Ferquency Range:	1 – 25 GHz	Measured Distance:	3m
Receiver Detector:	PK. or AV.	Tested Mode:	CH0: 2402MHz
Tested By:	Peter Tsai	Tested Date:	Sep. 24, 2004

Antenna Polarization : Horizontal

Frequency (MHz)	Correct Factor (dB)	Ant. Factor (dB/m)	Reading Data (dB μ V)		Emission Level (dB μ V/m)		Limit (dB μ V/m)		Margin (dB)		AZ (°)	EL (m)
			PK.	AV.	PK.	AV.	PK.	AV.	PK.	AV.		
2402.0000(F)	-32.16	28.00	76.6	46.6	72.4	42.4	N/A	N/A	N/A	N/A	258.0	1.12
2388.5000	-32.21	27.98	43.1	*	38.8	*	74.0	54.0	-35.2	*	246.0	1.10
2375.0000	-32.26	27.95	43.8	*	39.5	*	74.0	54.0	-34.5	*	261.0	1.15
2492.8000	-32.17	28.18	43.3	*	39.4	*	74.0	54.0	-34.6	*	255.0	1.16
4804.0000	-30.47	33.64	43.0	*	46.2	*	74.0	54.0	-27.8	*	231.0	1.2
7206.0000	-28.90	36.26	42.2	*	49.6	*	74.0	54.0	-24.4	*	242.0	1.21

Antenna Polarization : Vertical

Frequency (MHz)	Correct Factor (dB)	Ant. Factor (dB/m)	Reading Data (dB μ V)		Emission Level (dB μ V/m)		Limit (dB μ V/m)		Margin (dB)		AZ (°)	EL (m)
			PK.	AV.	PK.	AV.	PK.	AV.	PK.	AV.		
2402.0000(F)	-32.16	28.00	82.0	46.8	77.8	42.6	N/A	N/A	N/A	N/A	27.0	1.55
2390.0000	-32.20	27.98	43.3	*	39.1	*	74.0	54.0	-34.9	*	30.0	1.51
2371.3000	-32.27	27.94	43.6	*	39.3	*	74.0	54.0	-34.7	*	33.0	1.55
2499.1000	-32.16	28.20	43.2	*	39.2	*	74.0	54.0	-34.8	*	30.0	1.55
4804.0000	-30.47	33.64	44.2	*	47.3	*	74.0	54.0	-26.7	*	29.0	1.47
7206.00000	-28.90	36.26	41.8	*	49.1	*	74.0	54.0	-24.9	*	35.0	1.49

NOTE :

1. Measurement uncertainty is +/-2dB.
2. "*": The Peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. Emission Level = Reading Value + Ant. Factor + Correct Factor (incl.:Cable Loss and Pre-Amplifier Gain)
4. The field strength of other emission frequencies were very low against the limit.
5. (F):The field stregh of fundamental frequency.



Temperature:	<u>28 °C</u>	Humidity:	<u>60 %RH</u>
Ferquency Range:	<u>1 – 25 GHz</u>	Measured Distance:	<u>3m</u>
Receiver Detector:	<u>PK. or AV.</u>	Tested Mode:	<u>CH39: 2441MHz</u>
Tested By:	<u>Peter Tsai</u>	Tested Date:	<u>Sep. 24, 2004</u>

Antenna Polarization : Horizontal

Frequency (MHz)	Correct Factor (dB)	Ant. Factor (dB/m)	Reading Data (dB μ V)		Emission Level (dB μ V/m)		Limit (dB μ V/m)		Margin (dB)		AZ (°)	EL (m)
			PK.	AV.	PK.	AV.	PK.	AV.	PK.	AV.		
2441.0000(F)	-32.23	28.08	82.6	49.1	78.4	45.0	N/A	N/A	N/A	N/A	276.0	1.44
2380.0000	-32.24	27.96	43.4	*	39.1	*	74.0	54.0	-34.9	*	268.0	1.21
2391.0000	-32.19	27.98	43.0	*	38.8	*	74.0	54.0	-35.2	*	273.0	1.35
2486.5000	-32.18	28.17	43.2	*	39.1	*	74.0	54.0	-34.9	*	275.0	1.45
4882.0000	-30.26	33.71	42.2	*	45.7	*	74.0	54.0	-28.3	*	193.0	1.25
7323.0000	-29.04	36.36	41.9	*	49.2	*	74.0	54.0	-24.8	*	181.0	1.47

Antenna Polarization : Vertical

Frequency (MHz)	Correct Factor (dB)	Ant. Factor (dB/m)	Reading Data (dB μ V)		Emission Level (dB μ V/m)		Limit (dB μ V/m)		Margin (dB)		AZ (°)	EL (m)
			PK.	AV.	PK.	AV.	PK.	AV.	PK.	AV.		
2441.0000(F)	-32.23	28.08	80.7	45.0	76.5	40.9	N/A	N/A	N/A	N/A	123.0	1.17
2387.5000	-32.21	27.97	43.6	*	39.3	*	74.0	54.0	-34.7	*	118.0	1.21
2391.0000	-32.19	27.98	44.1	*	39.8	*	74.0	54.0	-34.2	*	154.0	1.25
2486.5000	-32.18	28.17	42.7	*	38.7	*	74.0	54.0	-35.3	*	214.0	1.33
4882.0000	-30.26	33.71	42.9	*	46.3	*	74.0	54.0	-27.7	*	168.0	1.32
7323.0000	-29.04	36.36	42.0	*	49.4	*	74.0	54.0	-24.6	*	232.0	1.27

NOTE :

1. Measurement uncertainty is +/-2dB.
2. "*": The Peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. Emission Level = Reading Value + Ant. Factor + Correct Factor (incl.:Cable Loss and Pre-Amplifier Gain)
4. The field strength of other emission frequencies were very low against the limit.
5. (F):The field stregh of fundamental frequency.



Temperature:	28 °C	Humidity:	60 %RH
Ferquency Range:	1 – 25 GHz	Measured Distance:	3m
Receiver Detector:	PK. or AV.	Tested Mode:	CH78: 2480MHz
Tested By:	Peter Tsai	Tested Date:	Sep. 24, 2004

Antenna Polarization : Horizontal

Frequency (MHz)	Correct Factor (dB)	Ant. Factor (dB/m)	Reading Data (dB μ V)		Emission Level (dB μ V/m)		Limit (dB μ V/m)		Margin (dB)		AZ (°)	EL (m)
			PK.	AV.	PK.	AV.	PK.	AV.	PK.	AV.		
2480.0000(F)	-32.19	28.16	81.9	51.6	77.8	47.6	N/A	N/A	N/A	N/A	33.0	1.84
2483.5000	-32.19	28.17	47.4	*	43.3	*	74.0	54.0	-30.7	*	33.0	1.84
2496.5000	-32.17	28.19	43.1	*	39.1	*	74.0	54.0	-34.9	*	186.0	1.32
2395.6000	-32.18	27.99	44.0	*	39.8	*	74.0	54.0	-34.2	*	151.0	1.51
4960.0000	-30.26	33.77	44.9	*	48.4	*	74.0	54.0	-25.6	*	96.0	1.19
7440.0000	-28.95	36.45	42.2	*	49.7	*	74.0	54.0	-24.3	*	232.0	1.22

Antenna Polarization : Vertical

Frequency (MHz)	Correct Factor (dB)	Ant. Factor (dB/m)	Reading Data (dB μ V)		Emission Level (dB μ V/m)		Limit (dB μ V/m)		Margin (dB)		AZ (°)	EL (m)
			PK.	AV.	PK.	AV.	PK.	AV.	PK.	AV.		
2480.0000(F)	-32.19	28.16	76.1	48.7	72.1	44.7	N/A	N/A	N/A	N/A	261.0	1.00
2483.5000	-32.19	28.17	43.9	*	39.8	*	74.0	54.0	-34.2	*	261.0	1.00
2496.5000	-32.17	28.19	42.1	*	38.1	*	74.0	54.0	-35.9	*	250.0	1.14
2393.8000	-32.19	27.99	43.6	*	39.4	*	74.0	54.0	-34.6	*	272.0	1.09
4960.0000	-30.26	33.77	40.5	*	44.0	*	74.0	54.0	-30.0	*	231.0	1.24
7440.0000	-28.95	36.45	40.0	*	47.5	*	74.0	54.0	-26.5	*	187.0	1.27

NOTE :

1. Measurement uncertainty is +/-2dB.
2. "*": The Peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. Emission Level = Reading Value + Ant. Factor + Correct Factor (incl.:Cable Loss and Pre-Amplifier Gain)
4. The field strength of other emission frequencies were very low against the limit.
5. (F):The field stregh of fundamental frequency.



5. Antenna application

5.1 Antenna requirement

The EUT' s antenna is met the requirement of FCC part15C section15.203 and 15.204.

FCC part15C section15.247 requirement:

Systems operating in the 2400-2483.5 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.


5.2 Result

The EUT' s antenna used a board antenna printed on PCB. The antenna' s gain is -1dBi and meets the requirement. The location of the antenna on the EUT as show in the attached EUT PHOTOS.




6. PHOTOS OF TESTING

- Conducted test (Charge mode)





- Radiated test (Link mode)





- Radiated test (Charge mode)





7. TERMS OF ABRIVATION

AV.	Average detection
AZ(°)	Turn table azimuth
Correct.	Correction
EL(m)	Antenna height (meter)
EUT	Equipment Under Test
Horiz.	Horizontal direction
LISN	Line Impedance Stabilization Network
NSA	Normalized Site Attenuation
Q.P.	Quasi-peak detection
SRT Lab	Spectrum Research & Testing Laboratory, Inc.
Vert.	Vertical direction