

FCC Part 15B Compliance Test Report

Test Report no.:	Tre_FCC_0711_03.doc	Date of Report:	30.3.2007
Number of pages:	14	Customer's Contact person:	Victoria Abadilla
Testing laboratory:	TCC Nokia Tampere Laboratory P.O. Box 68 Sinitaival 5 FIN-33720 TAMPERE, FINLAND Tel. +358 (0) 7180 46800 Fax. +358 (0) 7180 46880	Customer:	Nokia Corporation 12278 Scripps Summit Drive SAN DIEGO CA. 92131 USA Tel. +1 858 831 5000 Fax. +1 858 831 6500
FCC listing no.:	94436		
IC recognition no.:	3608		
Tested devices/ accessories:	GSM phone RM-164 / Battery BP-5M, AC charger AC-6, Data cable CA-101, Laptop IBM Thinkpad T22, AC adapter 02K6543, Printer HP deskjet 1600CC3540A, Digital camera FUJI DS-7, Serial cable for camera, Parallel cable for printer		
FCC ID:	QMNRM-164	IC:	661X-RM164
Supplement reports:	-		
Testing has been carried out in accordance with:	CFR 47, FCC rules Part 15 Subpart B, ANSI C63.4 (2003), ICES-003, CISPR 22 and IC standards RSS-132, RSS-133 and RSS-210. Deviations, modifications or clarifications (if any) to above mentioned documents are written in each section under "Test method and limit".		
Documentation:	The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 15 years at TCC Nokia.		
Test Results:	The EUT complies with the requirements in respect of all parameters subject to the test. The test results relate only to devices specified in this document.		
Date and signature for the contents:			

Jari Jantunen, System Manager

1. Summary for FCC Part 15B Compliance Test Report

Date of receipt	12.3.2007
Testing completed	22.2.2007
The customer's contact person	Victoria Abadilla
Test Plan referred to	\\EMC\\TESTPLAN\\
Notes	-
Document name	T:\\Projects\\RM-164\\EMC\\Results\\FCC\\Tre_FCC_0711_03.doc

1.1. EUT and Accessory Information

The EUT is a 4-band (GSM850/900/1800/1900) mobile phone with GPRS, EGPRS and Bluetooth. GSM bands are tested in idle mode. Bluetooth is tested with maximum rated TX power.

Product	Type	SN	HW	MV	SW	DUT
GSM phone	RM-164	004401010249601	3601	-	RM-164_03.31	40988
AC Charger	AC-6	-	0.5	-	-	40986
Battery	BP-5M	-	-	-	-	40990
Data cable	CA-101	-	1.2	1.1	-	40993
Laptop	IBM Thinkpad T22	555V2PT	-	-	-	40201
AC Adapter	02K6543	-	-	-	-	40202
Printer	HP deskjet 1600CC3540A	USB8302546	-	-	-	40077
Digital camera	FUJI DS-7	7102516	-	-	-	40076
Serial cable for camera	-	-	-	-	-	40088
Parallel cable for printer	-	-	-	-	-	40087

1.2. Summary of Test Results

GSM 850:

Section in CFR 47	Section in ICES-003 (RSS-132)	Name of the test	Result
15.107, a	5.3	AC powerline conducted emissions	PASSED
15.109, a	5.5 (6.6)	Radiated emissions	PASSED

GSM 1900:

Section in CFR 47	Section in ICES-003 (RSS-133)	Name of the test	Result
15.107, a	5.3	AC powerline conducted emissions	PASSED
15.109, a	5.5 (9)	Radiated emissions	PASSED

Bluetooth:

Section in CFR 47	Section in ICES-003	Name of the test	Result
15.107, a	5.3	AC powerline conducted emissions	PASSED
15.109, a	5.5	Radiated emissions	PASSED

PASSED

FAILED

NP

The EUT complies with the essential requirements in the standard.

The EUT does not comply with the essential requirements in the standard.

The test was not performed by the TCC Nokia Tampere Laboratory.


CONTENTS

1. Summary for FCC Part 15B Compliance Test Report.....	2
1.1. EUT and Accessory Information	2
1.2. Summary of Test Results.....	2
2. AC powerline conducted emissions (FCC §15.107, ICES-003 section 5.3).....	4
2.1. Test setup	4
2.2. Test method and limit.....	4
2.3. GSM 850 Test results	5
2.4. GSM 1900 Test results	6
2.5. Bluetooth Test results	7
3. Radiated emissions (FCC §15.109, ICES-003 section 5.5, RSS-132 6.6, RSS-133 9) 8	
3.1. Test setup	8
3.2. Test method and limit.....	8
3.3. GSM 850 Test results	9
3.4. GSM 1900 Test results	10
3.5. Bluetooth Test results	12
4. Test Equipment.....	14
4.1. Conducted measurements	14
4.2. Radiated measurements	14

2. AC powerline conducted emissions (FCC §15.107, ICES-003 section 5.3)

EUT with DUT number	RM-164 DUT 40988
Accessories with DUT numbers	BP-5M DUT 40990, AC-6 DUT 40986
Operation Voltage [V] / [Hz]	115 / 60
Result	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	19 / 49 / 101.6
Date of measurements	22.3.2007
Measured by	Jari Jantunen

2.1. Test setup



2.2. Test method and limit

The measurement is made according to ANSI C63.4-2003 as follows:

The EUT is placed on a wooden table 80 cm above the reference groundplane.

The EUT is connected via LISN to a test power supply.

The measurement results are obtained as described below:

$$U [dB\mu V] = U_{RX} + A_{TOT}$$


Where U_{RX} is receiver reading and A_{TOT} is total correction factor including cable and pulse limiter attenuations.

CISPR 22 Class B limits

Frequency range [MHz]	Quasi peak limit [dBμV]	Average limit [dBμV]
0.15 - 0.5	66 - 56	56 - 46
0.5 - 5	56	46
5 - 30	60	50

2.3. GSM 850 Test results

RX mode, channel 190 / 881.6 MHz



Quasi peak (RBW: 9 kHz)


Frequency [MHz]	U [dBμV]	Line	Result
0.190000	46.40	N	PASSED
0.195000	42.30	N	PASSED
0.320000	37.80	N	PASSED
0.445000	36.50	N	PASSED
4.240000	27.70	L1	PASSED

Average (RBW: 9 kHz)

Frequency [MHz]	U [dBμV]	Line	Result
0.190000	35.30	N	PASSED
0.430000	27.50	L1	PASSED
0.550000	24.30	L1	PASSED
4.240000	26.30	L1	PASSED

2.4. GSM 1900 Test results

RX mode, channel 661 / 1960.0 MHz



Quasi peak (RBW: 9 kHz)


Frequency [MHz]	U [dBμV]	Line	Result
0.180000	50.10	L1	PASSED
0.245000	45.00	N	PASSED
0.250000	42.70	N	PASSED
0.435000	36.50	N	PASSED
2.155000	26.10	L1	PASSED
4.240000	27.40	L1	PASSED

Average (RBW: 9 kHz)

Frequency [MHz]	U [dBμV]	Line	Result
0.185000	37.60	N	PASSED
0.240000	32.60	L1	PASSED
0.355000	28.40	L1	PASSED
0.535000	23.60	L1	PASSED
2.625000	21.10	L1	PASSED
4.240000	25.20	L1	PASSED

2.5. Bluetooth Test results

TX mode, channel 40 / 2442 MHz



Quasi peak (RBW: 9 kHz)

Frequency [MHz]	U [dBμV]	Line	Result
0.180000	43.40	L1	PASSED
0.245000	38.90	N	PASSED
0.360000	34.80	N	PASSED
0.440000	35.70	N	PASSED
4.240000	27.30	L1	PASSED

Average (RBW: 9 kHz)


Frequency [MHz]	U [dBμV]	Line	Result
0.185000	34.30	L1	PASSED
0.425000	27.30	L1	PASSED
0.605000	23.60	L1	PASSED
4.240000	25.50	L1	PASSED

3. Radiated emissions

(FCC §15.109, ICES-003 section 5.5, RSS-132 6.6, RSS-133 9)

EUT with DUT number	RM-164 DUT 40988
Accessories with DUT numbers	BP-5M DUT 40990, CA-101 DUT 40993, IBM Thinkpad T22 DUT 40201, 02K6543 DUT 40202, HP deskjet 1600CC3540A DUT 40077, FUJI DS-7 DUT 40076, Serial cable for camera DUT 40088, Parallel cable for printer DUT 40087
Operation Voltage [V] / [Hz]	115 / 60
Result	PASSED
Remarks	Continuous data transfer was active between the phone and the computer during the test.
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	25-26 / 41-42 / 101.0-101.4
Date of measurements	20-21.3.2007
Measured by	Jari Jantunen

3.1. Test setup



3.2. Test method and limit

The measurement is made according to ANSI C63.4-2003as follows:

The measurement is performed in the Semi-Anechoic Chamber with conducting metal floor.
The measurement distance is 3 m.

The EUT is placed on a nonconductive plate at 80 cm height.

For each suspected frequency, the turntable is rotated 360 degrees and antenna is scanned from 1 to 4 m. This is repeated for both horizontal and vertical receive antenna polarizations.

The emissions less than 20 dB below the permissible value are reported.

The measurement results are obtained as described below:

$$E [\mu\text{V/m}] = U_{RX} + A_{TOT}$$

Where U_{RX} is receiver reading and A_{TOT} is total correction factor including cable loss, antenna factor and preamplifier gain ($A_{TOT} = L_{CABLES} + AF - G_{PREAMP}$).

CISPR 22 and FCC Part 15 Class B limits (3 m measurement distance)

Frequency range [MHz]	Quasi peak limit [dBμV/m]	Average limit [dBμV/m]	Peak limit [dBμV/m]
30 – 230	40	-	-
230 – 1000	47	-	-
Above 1000	-	54	74

3.3. GSM 850 Test results

RX mode, channel 128 / 869.2 MHz

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
3476.800000	41.20	114.82	46.30	-5.1	HORIZONTAL	PASSED
6953.600000	44.90	175.79	44.00	0.9	VERTICAL	PASSED

Average (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
3476.800000	27.00	22.39	32.10	-5.1	HORIZONTAL	PASSED
6953.600000	30.30	32.73	29.40	0.9	VERTICAL	PASSED

RX mode, channel 190 / 881.6 MHz

Quasi peak (RBW: 120 kHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
99.839479	35.60	60.26	71.00	-35.40	HORIZONTAL	PASSED
149.619038	27.80	24.55	62.60	-34.80	HORIZONTAL	PASSED
348.596994	30.40	33.11	61.50	-31.10	HORIZONTAL	PASSED
645.790581	32.70	43.15	57.70	-25.00	VERTICAL	PASSED
677.152705	31.00	35.48	55.60	-24.60	VERTICAL	PASSED

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
1291.589178	53.00	446.68	71.00	-18.00	VERTICAL	PASSED
1296.087174	54.00	501.19	72.00	-18.00	VERTICAL	PASSED
3526.552104	40.70	108.39	45.50	-4.80	HORIZONTAL	PASSED
7052.800000	45.00	177.83	44.20	0.80	VERTICAL	PASSED

Average (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
1166.332665	34.60	53.70	53.90	-19.30	VERTICAL	PASSED
1234.966934	25.50	18.84	44.60	-19.10	VERTICAL	PASSED
1255.519038	26.20	20.42	44.90	-18.70	VERTICAL	PASSED
1294.587174	31.60	38.02	49.60	-18.00	VERTICAL	PASSED
1295.589178	31.10	35.89	49.10	-18.00	VERTICAL	PASSED
1297.599198	26.90	22.13	44.80	-17.90	VERTICAL	PASSED
1989.983968	33.60	47.86	45.60	-12.00	VERTICAL	PASSED
3526.552104	26.80	21.88	31.60	-4.80	HORIZONTAL	PASSED
7052.800000	30.20	32.36	29.40	0.80	VERTICAL	PASSED

RX mode, channel 251 / 893.8 MHz

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
3575.200000	40.30	103.51	44.90	-4.6	HORIZONTAL	PASSED
7150.400000	45.50	188.36	44.00	1.5	VERTICAL	PASSED

Average (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
3575.200000	26.60	21.38	31.20	-4.6	HORIZONTAL	PASSED
7150.400000	30.60	33.88	29.10	1.5	VERTICAL	PASSED

3.4. GSM 1900 Test results

RX mode, channel 512 / 1930.2 MHz

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
3860.000000	39.70	96.61	42.10	-2.4	VERTICAL	PASSED
7720.000000	41.70	121.62	39.00	2.7	VERTICAL	PASSED

Average (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
3860.000000	27.40	23.44	29.80	-2.4	HORIZONTAL	PASSED
7720.000000	29.40	29.51	26.70	2.7	HORIZONTAL	PASSED

RX mode, channel 661 / 1960.0 MHz

Quasi peak (RBW: 120 kHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
99.698998	41.40	117.49	76.80	-35.40	HORIZONTAL	PASSED
149.319038	33.70	48.42	68.50	-34.80	HORIZONTAL	PASSED
645.890581	32.10	40.27	57.10	-25.00	VERTICAL	PASSED
677.154709	31.50	37.58	56.10	-24.60	VERTICAL	PASSED
776.151102	30.30	32.73	53.50	-23.20	HORIZONTAL	PASSED
798.195190	30.90	35.08	54.00	-23.10	VERTICAL	PASSED

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
1959.919840	54.90	555.90	67.30	-12.40	VERTICAL	PASSED
3919.839679	45.80	194.98	48.20	-2.40	HORIZONTAL	PASSED
7840.179359	45.90	197.24	43.10	2.80	VERTICAL	PASSED

Average (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
1196.898798	23.80	15.49	43.10	-19.30	VERTICAL	PASSED
1256.019038	25.90	19.72	44.60	-18.70	VERTICAL	PASSED
1492.987976	31.20	36.31	47.90	-16.70	VERTICAL	PASSED
1991.483968	34.10	50.70	46.10	-12.00	HORIZONTAL	PASSED
2983.973948	32.10	40.27	36.50	-4.40	VERTICAL	PASSED
3919.839679	30.60	33.88	33.00	-2.40	HORIZONTAL	PASSED
7840.179359	31.40	37.15	28.60	2.80	VERTICAL	PASSED

RX mode, channel 810 / 1989.8 MHz

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
3980.000000	42.30	130.32	45.00	-2.7	VERTICAL	PASSED
7960.000000	42.80	138.04	39.70	3.1	VERTICAL	PASSED

Average (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
3980.000000	28.70	27.23	31.40	-2.7	VERTICAL	PASSED
7960.000000	29.80	30.90	26.70	3.1	VERTICAL	PASSED

3.5. Bluetooth Test results

TX mode, channel 0 / 2402 MHz

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4804.000000	39.60	95.50	41.30	-1.7	HORIZONTAL	PASSED
7206.000000	42.20	128.82	40.50	1.7	VERTICAL	PASSED

Average (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4804.000000	27.10	22.65	28.80	-1.7	HORIZONTAL	PASSED
7206.000000	28.40	26.30	26.70	1.7	VERTICAL	PASSED

TX mode, channel 40 / 2442 MHz

Quasi peak (RBW: 120 kHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
99.639479	40.70	108.39	76.10	-35.40	VERTICAL	PASSED
348.596994	26.70	21.63	57.80	-31.10	HORIZONTAL	PASSED
398.797194	33.00	44.67	62.90	-29.90	HORIZONTAL	PASSED
448.598196	28.40	26.30	57.40	-29.00	HORIZONTAL	PASSED
756.913026	33.30	46.24	56.70	-23.40	VERTICAL	PASSED
796.995190	32.90	44.16	55.90	-23.00	HORIZONTAL	PASSED

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4884.000000	40.00	100.00	41.60	-1.60	VERTICAL	PASSED
7326.000000	42.00	125.89	39.70	2.30	HORIZONTAL	PASSED

Average (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
1232.466934	26.70	21.63	45.80	-19.10	VERTICAL	PASSED
1256.519038	25.80	19.50	44.50	-18.70	VERTICAL	PASSED
1295.589178	30.40	33.11	48.40	-18.00	VERTICAL	PASSED
1495.487976	30.90	35.08	47.60	-16.70	VERTICAL	PASSED
1989.983968	33.50	47.32	45.50	-12.00	VERTICAL	PASSED
4884.000000	27.00	22.39	28.60	-1.60	HORIZONTAL	PASSED
7326.000000	29.40	29.51	27.10	2.30	VERTICAL	PASSED

TX mode, channel 78 / 2480 MHz

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dB μ V/m]	E [μ V/m]	U _{RX} [dB μ V]	A _{TOT} [dB]	Polarisation	Result
4960.000000	40.70	108.39	41.90	-1.2	VERTICAL	PASSED
7440.000000	42.70	136.46	40.00	2.7	VERTICAL	PASSED

Average (RBW: 1 MHz)

Frequency [MHz]	E [dB μ V/m]	E [μ V/m]	U _{RX} [dB μ V]	A _{TOT} [dB]	Polarisation	Result
4960.000000	27.00	22.39	28.20	-1.2	HORIZONTAL	PASSED
7440.000000	29.60	30.20	26.90	2.7	VERTICAL	PASSED

4. Test Equipment

4.1. Conducted measurements

Eq. No	Equipment	Type	Manufacturer	Used in
TM37610	Spectrum analyzer	FSU	R&S	22/24, 15C
TM37678	Radio communication tester	CMU-200	R&S	22/24, 15C
	Attenuator 10 dB	6251.17.A	Huber+Suhner AG	22/24, 15C
TM37499	Power splitter	11667A	Agilent	22/24, 15C
	Temperature chamber	VT4002	Vötsch	22/24, 15C
TM38112	DC power supply	6632A	Agilent	22/24, 15C
TM38111	Multimeter	34401A	Agilent	22/24, 15C
	EMI Test receiver	ESPC	R&S	15C, 15B
TM37773	Radio communication tester	CMU-200	R&S	15C, 15B
TM38631	Signal generator	83640L	Agilent	15C, 15B
TM38114	DC power supply	6632A	Agilent	15C, 15B
TM22835	Multimeter	87	Fluke	15C, 15B
TM30600	Pulse Limiter	ESH3-Z2	R&S	15C, 15B
TM26490	LISN 50 µH	ESH3-Z5/	R&S	15C, 15B
TM30636	LISN 50 µH	L2-16/	PMM	15C, 15B

4.2. Radiated measurements

Eq. No	Equipment	Type	Manufacturer	Used in
TM30599	3m semi-anechoic chamber		TDK	22/24, 15C, 15B
TM38845	EMI receiver	ESI 40	R&S	22/24, 15C, 15B
TM37498	Preamplifier	AMF-5D-020180-26-10P	MITEQ	22/24, 15C, 15B
TM37523	Preamplifier	AMF-4D-10M-3G-25-20P	MITEQ	22/24, 15C, 15B
TM37516	Biconilog antenna	HL562	R&S	22/24, 15C, 15B
TM26496	Double ridged waveguide antenna	3115	EMCO	22/24, 15C, 15B
TM39158	Horn antenna	3116	EMCO	22/24, 15C, 15B
TM26492	Reference dipole set	UHAP/VHAP	Schwarzbeck	22/24, 15C, 15B
TM37501	Dipole antenna	3125-870	EMCO	22/24
TM37502	Dipole antenna	3125-1880	EMCO	22/24
TM37773	Radio communication tester	CMU-200	R&S	22/24, 15C, 15B
TM38631	Signal generator	83640L	Agilent	22/24, 15C, 15B
TM38066	High pass filter	4HC3000/18000-3-KK	Trilithic	22/24, 15C, 15B
	High pass filter	WHK2010-10SS	Trilithic	22/24, 15C, 15B
	Low pass filter	WLK1750-10SS	Trilithic	22/24, 15C, 15B
TM26511	Tunable notch filter	WRCA870	Wainwright	22/24
TM38215	Tunable notch filter	WRCD1850/1910-0.2/40	Wainwright	22/24
TM38214	Band reject filter	WRCT 2402/2480-2400/2483.5-30	Wainwright	15C
TM30642	Turntable controller	HD-100	Deisel	22/24, 15C, 15B
TM26500	Turntable	DS412	Deisel	22/24, 15C, 15B
TM38842	Antenna mast controller	2090	EMCO	22/24, 15C, 15B
TM38843	Antenna mast	2075	EMCO	22/24, 15C, 15B
TM38114	DC power supply	6632A	Agilent	22/24, 15C, 15B
TM22835	Multimeter	87	Fluke	22/24, 15C, 15B