



Compliance Test Report

For FCC Part 22 & 24 Certification

Product Name : Cellular/PCS CDMA Phone with Bluetooth
(BT2.0+EDR)
Model No. : RM-339
FCC ID. : QMNRM-339
Max. Output Power : 0.26W(24.20Bm) ERP Cellular CDMA
0.61W(27.82dBm) EIRP PCS CDMA
Tx Frequency : CDMA2000 Cellular:824.70~848.31MHz
Range : CDMA2000 PCS:1851.25~1908.75MHz
FCC Rule Part(s) : FCC CFR Title 47 Part 2 ; 22(H) ; 24(E)
FCC Classification : PCS Licensed Transmitter Held to Ear (PCE)
Filing Type : Certification
Emission Designator : Cellular CDMA: 1M27F9W
PCS CDMA: 1M27F9W
Test Procedure : ANSI/TIA/EIA-603-C-2004

Applicant : Nokia Inc.
Address : 12278 Scripps Summit Dr. San Diego CA
92131 USA

Date of Receipt : Jun. 16, 2008
Issued Date : Jul. 31, 2008
Report No. : 087318R-HPUSP08V01
Report Version : V1.2

The Test Results relate only to the samples tested.

The test report shall not be reproduced except in full without the written approval of Quie Tek Corporation.

This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government

Test Report Certification

Issued Date : Jul. 31, 2008

Report No.: 087318R-HPUSP08V01



Accredited by NIST (NVLAP)

NVLAP Lab Code: 200533-0


Product Name : Cellular/PCS CDMA Phone with Bluetooth (BT2.0+EDR)
Applicant : Nokia Inc.
Address : 12278 Scripps Summit Dr. San Diego CA 92131 USA
Manufacturer : Foxconn International Holdings Limited
Manufacturer Address : No.2, 2nd Donghuan Road, 10th Yousong Industrial District,
Longhua, Baoan, Shenzhen, China
Model No. : RM-339
Rated Voltage : AC 100-240V/50-60 Hz
EUT Voltage : BL-4B: DC 3.7V
Trade Name : Nokia
Applicable Standards : FCC CFR Title 47 Part 2; 22(H); 24(E)
ANSI/TIA/EIA-603-C-2004
Test Result : Complied



Test results relate only to the samples tested.

The test report shall not be reproduced except in full without the written approval of Quie Tek Corporation.

This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government

Documented By : 
(Engineering Adm.
Assistant /
Nicole Huang)



Tested By : 
(Engineer / Paddy Chen)



Approved By : 
(Deputy Manager
/ Vincent Lin)

History of Test Report

Date	Version	Description
Jul. 22, 2008	V1.0	The First Version
Jul. 25 2008	V1.1	Revised rule parts for occupied bandwidth. Modified statements of test procedure for spurious emissions. Add descriptions of section 6.
Jul. 31 2008	V1.2	Show test data of Conducted Power

TABLE OF CONTENTS

Description	Page
1. GENERAL INFORMATION.....	5
1.1. EUT Description	5
1.2. Operational Description.....	5
1.3. Configuration of tested System	6
1.4. EUT Setup Procedures	6
1.5. Test Facility.....	7
1.6. EMI Reduction Method During Compliance Testing	8
1.7. Summary of Test Results.....	9
2. RF Power Output.....	10
2.1. Test Equipment.....	10
2.2. Test Setup	11
2.3. Limits... ..	12
2.4. Test Procedure	12
2.5. Uncertainty.....	13
2.6. Test Results of Peak Power Output	16
3. Occupied Bandwidth.....	22
3.1. Test Equipment.....	22
3.2. Test Setup	22
3.3. Test Procedure	23
3.4. Uncertainty.....	23
3.5. Test Results of Occupied Bandwidth	24
4. Band Edge Compliance	29
4.1. Test Equipment.....	29
4.2. Test Setup	29
4.3. Limits... ..	30
4.4. Test Procedure	30
4.5. Uncertainty.....	30
4.6. Band Edge Compliance	31
5. Spurious Emission	33
5.1. Test Equipment.....	33
5.2. Test Setup	34
5.3. Limits... ..	35
5.4. Test Procedure	36
5.5. Uncertainty.....	36
5.6. Test Results of Spurious Emission	37
6. Frequency Stability Under Temperature & Voltage Variations	60
6.1. Test Equipment.....	60
6.2. Test Setup	60
6.3. Limits... ..	60
6.4. Test Procedure	61
6.5. Uncertainty.....	61
6.6. Test Result of Frequency Stability Under Temperature Variations.....	62
Appendix A: Photographs of Test Setup.....	64

1. GENERAL INFORMATION

1.1. EUT Description

Product Name	Cellular/PCS CDMA Phone with Bluetooth (BT2.0+EDR)
Model No.	RM-339
MEID	A00000011E5869
TX Frequency	Cellular CDMA : 824.7 ~ 848.31MHz PCS CDMA : 1851.25 ~ 1908.75MHz
Rx Frequency	Cellular CDMA : 869.7 ~ 893.31MHz PCS CDMA : 1931.25 ~ 1988.75MHz
Maximum Output Power	24.20dBm / 0.26W(Cellular), 27.82dBm / 0.61W(PCS)
Type of Emission	Cellular CDMA: 1M27F9W PCS CDMA: 1M27F9W
Antenna Type	Fixed Internal
Hardware version	6000
Software version	KN_3600T6_VZW
Battery Pack	BL-4B: DC 3.7V

1.2. Operational Description

The information contained within this report is intended to show compliance of the Cellular and PCS CDMA phone to the requirements of 47CFR2, 22 and 24.

For Part 22 and 24, all of CDMA measurements were conducted with Agilent 8960 as a base station simulator. The base station simulator establishes a CDMA link with the test device.

Quie Tek has verified the construction and function in typical operation. All the test modes were carried out with the EUT in normal operation, which was shown in this test report and defined as:

Test Mode:	Mode 1: CDMA2000 1xRTT Cellular 850
	Mode 2: CDMA2000 1xRTT PCS 1900

1.3. Configuration of tested System




Fig. 1-1 Configuration of (a) Radiated (b) Conducted Emission measurement.

1.4. EUT Setup Procedures

- (1) Setup the EUT and simulators as shown on Fig. 1-1.
- (2) Turn on the power of all equipments.
- (3) The EUT was tested while the base station simulator, Agilent 8960, established a CDMA link with it (The EUT was set to transmit on maximum power).
- (4) To justify on the selection of applicable modes, the EUT was pre-test under all R.C.s and S.O.s operation modes to find the worst case.

1.5. Test Facility

Ambient conditions in the laboratory:

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	20-35
Humidity (%RH)	25-75	50-65
Barometric pressure (mbar)	860-1060	950-1000

Site Description: File on

Federal Communications Commission
FCC Engineering Laboratory
7435 Oakland Mills Road
Columbia, MD 21046
FCC Registration Number :92195



Certification and Engineering Bureau
3701 Carling Ave., Building 94
P.O. Box 11490, Station "H"
Ottawa, Ontario K2H 8S2
IC Recognized No. : 4075A



Accreditation on NVLAP
NVLAP Lab Code: 200533-0



Site Name: Quietek Corporation

Site Address: No. 5-22, Ruei-Shu Valley, Ruei-Ping Tsuen,
Lin Kou Shiang, Taipei 244 Taiwan, R.O.C.
TEL : 886-2-8601-3788 / FAX : 886-2-8601-3789
E-Mail : service@quietek.com



1.6. EMI Reduction Method During Compliance Testing

No modification was made during testing

1.7. Summary of Test Results

Product Name : Cellular/PCS CDMA Phone with Bluetooth (BT2.0+EDR)
 Model No. : RM-339
 MEID : A00000011E5869
 FCC ID : QMNRM-339
 FCC Classification : PCS Licensed Transmitter Held to Ear (PCE)
 Type of Emission : Cellular CDMA: 1M27F9W
 PCS CDMA: 1M27F9W

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
2.1046, 22.913(a)(2), 24.232(c)	RF Output Power (ERP/EIRP)	< 7Watts Max. ERP < 2Watts Max. EIRP	Radiated	Pass	Section 2.6
2.1049, 22.917(a), 24.238(a)	Occupied Bandwidth	N/A	Conducted	Pass	Section 3.6
2.1051, 22.917(a). 24.238(a)	Band Edge	< 43 + 10 log(P) at Band Edge	Conducted	Pass	Section 4.6
2.1051, 22.917(a), 24.238(a)	Conducted Spurious Emission	< 43 + 10 log(P) for all out-of-band emission	Conducted	Pass	Section 5.6.1
2.1053, 22.917(a), 24.238(a)	Radiated Undesirable Emission	< 43 + 10 log(P) for all out-of-band emission	Radiated	Pass	Section 5.6.2
2.1055, 22.355, 24.235	Frequency Stability	< 2.5 ppm	Conducted	Pass	Section 6.6

2. RF Power Output

2.1. Test Equipment


The following test equipments are used during the radiated emission test:

Item	Equipment	Manufacturer	Type No./ Serial No	Calibration Date	Calibration Due
1	Power Meter	Anritsu	ML2495A/ 6K00003357	May 17, 2008	May 16, 2009
2	Power Sensor	Anritsu	MA2491A/034457	May 17, 2008	May 16, 2009
3	Dual Directional couple	Agilent	778D-012/50550	Aug 10, 2007	Aug 09, 2008
4	Directional coupler	Agilent	87300C/ MY44300353	Aug 18, 2007	Aug 17, 2008
5	Bilog Antenna	Schaffner Chase	CBL6112B/2921	Aug 10, 2007	Aug 09, 2008
6	Broadband Horn Antenna	Schwarzbeck	BBHA9170/497	Sep 07, 2007	Sep 06, 2008
7	EMI Test Receiver	R&S	ESCS 30/100123	May 07, 2008	May 06, 2009
8	Horn Antenna	Schwarzbeck	BBHA9120D/305	Sep 06, 2007	Sep 05, 2008
9	Pre-Amplifier	QTK	N/A	N/A	
10	Microwave Amplifier (0.5GHZ-26.5GHZ)	Agilent	83017A/ MY39500682	Aug 10, 2007	Aug 09, 2008
11	Spectrum Analyzer	Advantest	R3162/01700040	Nov 13, 2007	Nov 12, 2008
12	Spectrum Analyzer (9K-40GHz)	R&S	FSP40/100339	Nov 06, 2007	Nov 05, 2008
13	Universal Radio Communication Tester	Agilent	8960 / GB47390315	May 02, 2008	May 01, 2009

2.2. Test Setup


Radiated Power Measurement

Under 1GHz Test Setup



(a)

Above 1GHz Test Setup



(b)

Fig. 2-1(a) (b) Test setup of Radiated Power Measurement

Conducted Power Measurement




Fig. 2-2 Test Setup of Conducted Power Measurement

2.3. Limits

FCC Part 22.913(a) Limits(ERP)	
Cellular 850	< 7W

FCC Part 24.232(c) Limits(EIRP)	
PCS1900	< 2W or +33dBm

2.4. Test Procedure

RF Out Power (Radiated)

The Spectrum Analyzer was tuned to the test frequency. The device was put into Transmit mode then rotated through 360 degrees until the highest power level was observed in both horizontal and vertical polarization. The device was then replaced with a substitution antenna, which input signal was adjusted until the received level matched that of the previously detected emission. For CDMA signals, a peak detector is used, with RBW=VBW=3MHz.

RF Out Power (Conducted)

Using a Power meter, the output power of the EUT was measured at the antenna terminals.

Reference standards: Part 2.1046, 22.913(a)(2), 24.232(c).

2.5. Uncertainty

The measurement uncertainty of conducted power output is evaluated as ± 1.036 dB.

Contributions		Probability Distribution	Standard Uncertainty u_i (dB)
Mismatch : Reference level Measurement	U01	U-shaped	0.04
Mismatch : direct attenuation measurement	U02	U-shaped	0.089
Attenuation measurement reading	U03	Normal	0.29
Attenuator: influence of the ambient temperature	U04	Normal	0
Attenuator: influence of setting the power supply	U05	Normal	0.017
EUT: influence of the ambient temperature	U06	Normal	0.1
EUT: influence of setting the power supply	U07	Normal	0.026
Mismatch on EUT	U08	U-shaped	0.391
Random: System Repeatability	U09	Standard Deviation	0.103
Combined Standard Uncertainty, U			0.518
Expanded Uncertainty (for a 95 % confidence level, k=2)			1.036

The measurement uncertainty of radiated output power is evaluated as ± 4.22 dB (30 – 1000MHz).

Contributions		Probability Distribution	Standard Uncertainty u_i (dB)
Mismatch: receiving part	U_{01}	U-shaped	0.182
Insertion loss: Measurement Antenna cable	U_{02}	Normal	0.50
Gain of the Pre-Amplifier	U_{03}	Rectangular	0.29
Receiving device: absolute level	U_{04}	Rectangular	0.58
EUT: influence of setting the power supply	U_{05}	Normal	0.03
Position of the phase centre: within the EUT volume	U_{06}	Rectangular	0.12
Positioning of the phase centre: within the EUT over the axis of rotation of the turntable	U_{07}	Rectangular	0.08
EUT: influence of the ambient temperature	U_{08}	Normal	0.10
Correction: measurement distance	U_{09}	Normal	0.30
Antenna: gain of the Measurement Antenna	U_{10}	Normal	0.60
Reflectivity of absorbing material: EUT to the test antenna	U_{11}	Normal	0.50
Correction: off bore sight angle in the elevation plane	U_{12}	Normal	0.50
EUT: mutual coupling to the power leads	U_{13}	Normal	0.50
Mutual coupling: amplitude effect of the test antenna on the EUT	U_{14}	Normal	0.50
Mutual coupling: EUT to its images in the absorbing material	U_{15}	Normal	0.50
Mutual coupling: EUT to its image in the ground plane	U_{16}	Normal	1.15
Mutual coupling: measuring antenna to its image in the absorbing material	U_{17}	Normal	0.50
Mutual coupling: measuring antenna to its image in the ground plane	U_{18}	Normal	0.58
Mutual coupling: interpolation of mutual coupling and mismatch loss correction factors	U_{19}	Normal	0.17
Random: System Repeatability	U_{20}	Standard Deviation	0.30
Combined Standard Uncertainty, U			2.11
Expanded Uncertainty (for a 95 % confidence level, k=2)			4.22

The measurement uncertainty is evaluated as ± 4.06 dB from 1 GHz to 20 GHz.

Contributions		Probability Distribution	Standard Uncertainty u_i (dB)
Mismatch: receiving part	U_{01}	U-shaped	0.182
Insertion loss: Measurement Antenna cable	U_{02}	Normal	0.50
Gain of the Pre-Amplifier	U_{03}	Rectangular	0.29
Receiving device: absolute level	U_{04}	Rectangular	0.58
EUT: influence of setting the power supply	U_{05}	Normal	0.03
Position of the phase centre: within the EUT volume	U_{06}	Rectangular	0.12
Positioning of the phase centre: within the EUT over the axis of rotation of the turntable	U_{07}	Rectangular	0.08
EUT: influence of the ambient temperature	U_{08}	Normal	0.10
Correction: measurement distance	U_{09}	Normal	1.26
Antenna: gain of the Measurement Antenna	U_{10}	Normal	0.60
Reflectivity of absorbing material: EUT to the test antenna	U_{11}	Normal	0.50
Correction: off bore sight angle in the elevation plane	U_{12}	Normal	0.50
EUT: mutual coupling to the power leads	U_{13}	Normal	0.50
Mutual coupling: amplitude effect of the test antenna on the EUT	U_{14}	Normal	0.50
Mutual coupling: EUT to its images in the absorbing material	U_{15}	Normal	0.50
Mutual coupling: EUT to its image in the ground plane	U_{16}	Normal	0.15
Mutual coupling: measuring antenna to its image in the absorbing material	U_{17}	Normal	0.50
Mutual coupling: measuring antenna to its image in the ground plane	U_{18}	Normal	0.15
Mutual coupling: interpolation of mutual coupling and mismatch loss correction factors	U_{19}	Normal	0.00
Random: System Repeatability	U_{20}	Standard Deviation	0.40
Combined Standard Uncertainty, U			2.03
Expanded Uncertainty (for a 95 % confidence level, k=2)			4.06

2.6. Test Results of Peak Power Output

2.6.1 RF Out Power (Conducted)-Phone Open

Product	Cellular/PCS CDMA Phone with Bluetooth (BT2.0+EDR)		
Test Condition	RF Output Power (Conducted)	Battery Type	Standard
Date of Test	2008/06/16	Test Site	CB5

Mode	Bands	Test Status	Channel	Frequency (MHz)	Conducted Power. (dBm)	Conducted Power (Watts)	Battery Type
CDMA 1xRTT	Cellular 850	RC1, SO2	1013	824.7	24.23	0.26	Standard
			384	836.52	24.56	0.29	Standard
			777	848.31	24.31	0.27	Standard
		RC1, SO55	1013	824.7	24.08	0.26	Standard
			384	836.52	24.56	0.29	Standard
			777	848.31	24.37	0.27	Standard
		RC2, SO9	1013	824.7	24.23	0.26	Standard
			384	836.52	24.51	0.28	Standard
			777	848.31	24.37	0.27	Standard
		RC2, SO55	1013	824.7	24.13	0.26	Standard
			384	836.52	24.56	0.29	Standard
			777	848.31	24.37	0.27	Standard
		RC3, SO9	1013	824.7	24.26	0.27	Standard
			384	836.52	24.53	0.28	Standard
			777	848.31	24.43	0.28	Standard
		RC3, SO55	1013	824.7	24.17	0.26	Standard
			384	836.52	24.56	0.29	Standard
			777	848.31	24.36	0.27	Standard
		RC4, SO2	1013	824.7	24.29	0.27	Standard
			384	836.52	24.58	0.29	Standard
			777	848.31	24.45	0.28	Standard
		RC4, SO55	1013	824.7	24.2	0.26	Standard
			384	836.52	24.58	0.29	Standard
			777	848.31	24.36	0.27	Standard
		RC5, SO9	1013	824.7	24.3	0.27	Standard
			384	836.52	24.55	0.29	Standard
			777	848.31	24.45	0.28	Standard
		RC5, SO55	1013	824.7	24.21	0.26	Standard
			384	836.52	24.59	0.29	Standard
			777	848.31	24.38	0.27	Standard

Mode	Bands	Test Status	Channel	Frequency (MHz)	Conducted Power. (dBm)	Conducted Power (Watts)	Battery Type
CDMA 1xRTT	Cellular 1900	RC1, SO2	25	1851.25	23.82	0.24	Standard
			600	1880.00	23.45	0.22	Standard
			1175	1908.75	23.29	0.21	Standard
		RC1, SO55	25	1851.25	23.82	0.24	Standard
			600	1880.00	23.39	0.22	Standard
			1175	1908.75	23.34	0.22	Standard
		RC2, SO9	25	1851.25	23.79	0.24	Standard
			600	1880.00	23.34	0.22	Standard
			1175	1908.75	23.28	0.21	Standard
		RC2, SO55	25	1851.25	23.84	0.24	Standard
			600	1880.00	23.37	0.22	Standard
			1175	1908.75	23.39	0.22	Standard
		RC3, SO9	25	1851.25	23.87	0.24	Standard
			600	1880.00	23.36	0.22	Standard
			1175	1908.75	23.33	0.22	Standard
		RC3, SO55	25	1851.25	23.80	0.24	Standard
			600	1880.00	23.31	0.21	Standard
			1175	1908.75	23.22	0.21	Standard
		RC4, SO2	25	1851.25	23.87	0.24	Standard
			600	1880.00	23.39	0.22	Standard
			1175	1908.75	23.31	0.21	Standard
		RC4, SO55	25	1851.25	23.79	0.24	Standard
			600	1880.00	23.29	0.21	Standard
			1175	1908.75	23.24	0.21	Standard
		RC5, SO9	25	1851.25	23.99	0.25	Standard
			600	1880.00	23.44	0.22	Standard
			1175	1908.75	23.35	0.22	Standard
		RC5, SO55	25	1851.25	23.83	0.24	Standard
			600	1880.00	23.30	0.21	Standard
			1175	1908.75	23.21	0.21	Standard

2.6.2 RF Out Power (Conducted)-Phone Close

Product	Cellular/PCS CDMA Phone with Bluetooth (BT2.0+EDR)		
Test Condition	RF Output Power (Conducted)	Battery Type	Standard
Date of Test	2008/06/16	Test Site	CB5

Mode	Bands	Test Status	Channel	Frequency (MHz)	Conducted Power. (dBm)	Conducted Power (Watts)	Battery Type
CDMA 1xRTT	Cellular 850	RC1, SO2	1013	824.7	24.38	0.27	Standard
			384	836.52	24.64	0.29	Standard
			777	848.31	24.45	0.28	Standard
		RC1, SO55	1013	824.7	24.45	0.28	Standard
			384	836.52	24.83	0.30	Standard
			777	848.31	24.60	0.29	Standard
		RC2, SO9	1013	824.7	24.40	0.28	Standard
			384	836.52	24.69	0.29	Standard
			777	848.31	24.54	0.28	Standard
		RC2, SO55	1013	824.7	24.38	0.27	Standard
			384	836.52	24.64	0.29	Standard
			777	848.31	24.63	0.29	Standard
		RC3, SO9	1013	824.7	24.50	0.28	Standard
			384	836.52	24.79	0.30	Standard
			777	848.31	24.64	0.29	Standard
		RC3, SO55	1013	824.7	24.44	0.28	Standard
			384	836.52	24.74	0.30	Standard
			777	848.31	24.55	0.29	Standard
		RC4, SO2	1013	824.7	24.49	0.28	Standard
			384	836.52	24.79	0.30	Standard
			777	848.31	24.71	0.30	Standard
		RC4, SO55	1013	824.7	24.45	0.28	Standard
			384	836.52	24.76	0.30	Standard
			777	848.31	24.56	0.29	Standard
		RC5, SO9	1013	824.7	24.53	0.28	Standard
			384	836.52	24.79	0.30	Standard
			777	848.31	24.66	0.29	Standard
		RC5, SO55	1013	824.7	24.50	0.28	Standard
			384	836.52	24.78	0.30	Standard
			777	848.31	24.54	0.28	Standard

Mode	Bands	Test Status	Channel	Frequency (MHz)	Conducted Power. (dBm)	Conducted Power (Watts)	Battery Type
CDMA 1xRTT	Cellular 1900	RC1, SO2	25	1851.25	24.61	0.29	Standard
			600	1880.00	24.03	0.25	Standard
			1175	1908.75	24.02	0.25	Standard
		RC1, SO55	25	1851.25	24.51	0.28	Standard
			600	1880.00	23.99	0.25	Standard
			1175	1908.75	23.86	0.24	Standard
		RC2, SO9	25	1851.25	24.63	0.29	Standard
			600	1880.00	24.18	0.26	Standard
			1175	1908.75	24.02	0.25	Standard
		RC2, SO55	25	1851.25	24.49	0.28	Standard
			600	1880.00	23.91	0.25	Standard
			1175	1908.75	23.79	0.24	Standard
		RC3, SO9	25	1851.25	24.56	0.29	Standard
			600	1880.00	24.15	0.26	Standard
			1175	1908.75	24.01	0.25	Standard
		RC3, SO55	25	1851.25	24.49	0.28	Standard
			600	1880.00	24.02	0.25	Standard
			1175	1908.75	23.86	0.24	Standard
		RC4, SO2	25	1851.25	24.44	0.28	Standard
			600	1880.00	24.06	0.25	Standard
			1175	1908.75	23.87	0.24	Standard
		RC4, SO55	25	1851.25	24.47	0.28	Standard
			600	1880.00	24.01	0.25	Standard
			1175	1908.75	23.86	0.24	Standard
		RC5, SO9	25	1851.25	24.45	0.28	Standard
			600	1880.00	24.07	0.26	Standard
			1175	1908.75	23.82	0.24	Standard
		RC5, SO55	25	1851.25	24.48	0.28	Standard
			600	1880.00	23.99	0.25	Standard
			1175	1908.75	23.85	0.24	Standard

2.6.3 RF Output Power (Radiated)

Product	Cellular/PCS CDMA Phone with Bluetooth (BT2.0+EDR)		
Test Mode	Mode 1: CDMA2000 1xRTT Cellular 850	Battery Type	Standard
Date of Test	2008/06/20	Test Site	OATS 3

Frequency (MHz)	Reading Level (dBm)	Substitution Level (dBm)	Substitution Antenna Gain (dBd)	Cable Loss (dB)	Result ERP (dBm)	Result ERP (W)	Polarization (V/H)
824.7	17.41	20.26	4.45	0.51	24.20	0.26	Horizontal
836.52	17.15	20.00	4.45	0.51	23.94	0.25	Horizontal
848.31	17.16	20.01	4.45	0.51	23.95	0.25	Horizontal

Note:

1. The EUT meets the requirements of FCC CFR 47: Part 22, Section 22.913(a)(2) for Effective Radiated Power.
2. Receiver setting (Peak Detector) : RBW:3MHz; VBW:3MHz.
3. Result ERP = Substitution Level + Substitution Antenna Gain - Cable Loss.

Product	Cellular/PCS CDMA Phone with Bluetooth (BT2.0+EDR)		
Test Mode	Mode 2: CDMA2000 1xRTT PCS 1900	Battery Type	Standard
Date of Test	2008/06/20	Test Site	OATS 3

Frequency (MHz)	Reading Level (dBm)	Substitution Level (dBm)	Substitution Antenna Gain (dBi)	Cable Loss (dB)	Result EIRP (dBm)	Result EIRP (W)	Polarization (V/H)
1851.25	16.76	18.44	10.4	1.02	27.82	0.61	Horizontal
1880.00	15.32	16.95	10.4	1.02	26.33	0.43	Horizontal
1908.75	14.34	15.93	10.4	1.02	25.31	0.34	Horizontal

Note:

1. The EUT meets the requirements of FCC CFR 47: Part 24, Section 24.232(c) for Equivalent Isotropic Radiated Power.
2. Receiver setting (Peak Detector) : RBW:3MHz; VBW:3MHz.
3. Result EIRP = Substitution Level + Substitution Antenna Gain - Cable Loss.

3. Occupied Bandwidth

3.1. Test Equipment

The following test equipments are used during the occupied bandwidth tests:

Item	Equipment	Manufacturer	Model No./ Serial No.	Calibration Date	Calbration Due
1	Spectrum Analyzer	Agilent	E4407B / US39440758	Jun 02, 2008	Jun 01, 2009
2	Universal Radio Communication Tester	Agilent	8960 / GB47390315	May 02, 2008	May 01, 2009
3	Dual Directional couple	Agilent	778D-012/ 50550	Aug 10, 2007	Aug 09, 2008
4	Directional coupler	Agilent	87300C/ MY44300353	Aug 18, 2007	Aug 17, 2008

3.2. Test Setup




Fig. 3-1 Test setup.

3.3. Test Procedure

The EUT was set to transmit on maximum power.

Using a resolution bandwidth of 30kHz and a video bandwidth of 100kHz, the -26dBc points were established and the emission bandwidth determined.

The plots below show the results display from the Spectrum Analyser.

Reference standards: Part 2.1049, 22.917(a), 24.238(a)

3.4. Uncertainty

The measurement uncertainty is evaluated as ± 24.30 kHz.

Contributions		Probability Distribution	Standard Uncertainty u_i (Hz)
Frequency Error	U_{01}	Rectangular	139.2
Frequency readout accuracy	U_{02}	Normal	12149
Combined Standard Uncertainty, U			12150
Expanded Uncertainty (for a 95 % confidence level, k=2)			24.30 kHz

3.5. Test Results of Occupied Bandwidth

Product	Cellular/PCS CDMA Phone with Bluetooth (BT2.0+EDR)
Test Condition	Occupied Bandwidth
Battery Type	Standard

Test Mode	Channel & TX Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB bandwidth (MHz)	Required Limit (MHz)	Result	Battery Type
Mode 1: CDMA2000 1xRTT Cellular 850	1013(824.7)	1.2786	1.435	N/A	Pass	Standard
	384(836.52)	1.2771	1.435	N/A	Pass	Standard
	777(848.31)	1.2753	1.435	N/A	Pass	Standard
Mode 2: CDMA2000 1xRTT PCS 1900	25(1851.25)	1.2783	1.423	N/A	Pass	Standard
	600(1880)	1.2724	1.430	N/A	Pass	Standard
	1175(1908.75)	1.2799	1.430	N/A	Pass	Standard

Product	Cellular/PCS CDMA Phone with Bluetooth (BT2.0+EDR)		
Test Mode	Mode 1: CDMA2000 1xRTT Cellular 850	Battery Type	Standard
Date of Test	2008/07/22	Test Site	CB5




Fig. 3-2 Occupied Bandwidth for mode 1(Ch. 1013).




Fig. 3-3 Occupied Bandwidth for mode 1(Ch. 384).




Fig. 3-4 Occupied Bandwidth for mode 1(Ch. 777).

Product	Cellular/PCS CDMA Phone with Bluetooth (BT2.0+EDR)		
Test Mode	Mode 2: CDMA2000 1xRTT PCS 1900	Battery Type	Standard
Date of Test	2008/07/18	Test Site	CB5




Fig. 3-5 Occupied Bandwidth for mode 2(Ch. 25).




Fig. 3-6 Occupied Bandwidth for mode 2(Ch. 600).




Fig. 3-7 Occupied Bandwidth for mode 2(Ch. 1175).

4. Band Edge Compliance

4.1. Test Equipment

The following test equipments are used during the band edge compliance test :

Item	Equipment	Manufacturer	Model No./ Serial No.	Calibration Date	Calbration Due
1	Spectrum Analyzer	Agilent	E4407B / US39440758	Jun 02, 2008	Jun 01, 2009
2	Universal Radio Communication Tester	Agilent	8960 / GB47390315	May 02, 2008	May 01, 2009
3	Dual Directional couple	Agilent	778D-012/ 50550	Aug 10, 2007	Aug 09, 2008
4	Directional coupler	Agilent	87300C/ MY44300353	Aug 18, 2007	Aug 17, 2008

4.2. Test Setup




Fig. 4-1 Test setup.

4.3. Limits

FCC Part 2.1051 & 22.917(a) & 24.238(a)	
Limit	<-13dBm (Below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB, where P is the power in Watts).

4.4. Test Procedure

In accordance with Part 22.917 and 24.238, at least 1% of the emission bandwidth was used for the resolution and video bandwidths up to 1MHz away from the Block Edge. At greater than 1MHz, the resolution and video bandwidth were increased to 1MHz.

The reference power and path losses of all channels used for testing in each frequency block were measured.

Reference standards: Part 2.1051, 22.917(a), 24.238(a).

4.5. Uncertainty

The measurement uncertainty is evaluated as ± 24.30 kHz.

Contributions		Probability Distribution	Standard Uncertainty u_i (Hz)
Frequency Error	U_{01}	Rectangular	38.88
Frequency readout accuracy	U_{02}	Normal	19406
Combined Standard Uncertainty, U			19.406kHz
Expanded Uncertainty (for a 95 % confidence level, k=2)			38.81 kHz

4.6. Band Edge Compliance

Product	Cellular/PCS CDMA Phone with Bluetooth (BT2.0+EDR)		
Test Mode	Mode 1: CDMA2000 1xRTT Cellular 850	Battery Type	Standard
Date of Test	2008/07/18	Test Site	CB5




Fig. 4-2 Band edge measurements for mode 1(Ch. 1013).




Fig. 4-3 Band edge measurements for mode 1(Ch. 777).

Product	Cellular/PCS CDMA Phone with Bluetooth (BT2.0+EDR)		
Test Mode	Mode 2: CDMA2000 1xRTT PCS 1900	Battery Type	Standard
Date of Test	2008/07/18	Test Site	CB5




Fig. 4-4 Band edge measurements for mode 2(Ch. 25).




Fig. 4-5 Band edge measurements for mode 2(Ch. 1175).

5. Spurious Emission

5.1. Test Equipment

The following test equipments are used during the spurious emission test:

Item	Equipment	Manufacturer	Type No./Serial No	Calibration Date	Calibration Due
1	Spectrum Analyzer	Agilent	E4407B / US39440758	Jun 02, 2008	Jun 01, 2009
2	Dual Directional couple	Agilent	778D-012/50550	Aug 10, 2007	Aug 09, 2008
3	Directional coupler	Agilent	87300C/ MY44300353	Aug 18, 2007	Aug 17, 2008
4	Bilog Antenna	Schaffner Chase	CBL6112B/2921	Aug 10, 2007	Aug 09, 2008
5	Broadband Horn Antenna	Schwarzbeck	BBHA9170/497	Sep 07, 2007	Sep 06, 2008
6	EMI Test Receiver	R&S	ESCS 30/100123	May 06, 2008	May 05, 2009
7	Horn Antenna	Schwarzbeck	BBHA9120D/ 305	Sep 06, 2007	Sep 05, 2008
8	Pre-Amplifier	QTK	N/A	N/A	
9	Microwave Amplifier (0.5GHZ-26.5GHZ)	Agilent	83017A/ MY39500682	Aug 10, 2007	Aug 09, 2008
10	Spectrum Analyzer	Advantest	R3162/01700040	Nov 13, 2007	Nov 12, 2008
11	Spectrum Analyzer (9K-40GHz)	R&S	FSP40/100339	Nov 06, 2007	Nov 05, 2008
12	Universal Radio Communication Tester	Agilent	8960 / GB47390315	May 02, 2008	May 01, 2009

5.2. Test Setup

Spurious emissions at antenna terminals.





Fig. 5-1 Test setup for conducted spurious measurements.


(a) Field strength of spurious radiation.

Under 1GHz Test Setup



(a)

Above 1GHz Test Setup



(b)

Fig. 5-2 (a) (b) Test setup for radiated spurious measurements.

5.3. Limits

FCC Part 2.1051 & 2.1053 & 22.917(a) & 24.238(a)	
Limit	<-13dBm Below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB, where P is the power in Watts

5.4. Test Procedure

Spurious emissions (Conducted)

In accordance with Part 2.1051, the spurious emissions from the antenna terminal were measured. The test setup figure was shown on Fig. 5-1 and the frequency spectrum was investigated from 30MHz up to the 10th harmonic of the fundamental in Cellular band and PCS band. The EUT was tested on low, middle and top channels with “All UP” power control bits.

Spurious emissions (Radiated)

Radiated emission measurements below 1GHz are made using broadband Bilog antenna and above 1GHz are made using Horn Antennas. The EUT was tested on low, middle and top channels with “All UP” power control bits in Cellular band and PCS band. The resolution and video bandwidth was set to 3MHz and 3MHz respectively. The spectrum analyzer detector was set to Max Hold. In addition, measurements were made from 30MHz up to the 10th harmonic of the fundamental.

The EUT is placed on a turn table which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level.

Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to TIA/EIA 603-C on radiated measurement.

Reference Standards: Part 2.1051, 2.1053, 22.917(a), 24.238(a).

5.5. Uncertainty

The measurement uncertainty of radiated output power is evaluated as ± 4.22 dB (30 – 1000 MHz).

The measurement uncertainty is evaluated as ± 4.06 dB from 1 GHz to 20 GHz.

The detail evaluations of each contribution are shown on the tables in Sec. 2.5.

5.6. Test Results of Spurious Emission

5.6.1 Conducted Spurious Emission

Product	Cellular/PCS CDMA Phone with Bluetooth (BT2.0+EDR)		
Test Condition	Conducted Spurious Emission	Battery Type	Standard
Test Mode	Mode 1: CDMA2000 1xRTT Cellular 850	Test Site	CB5
Date of Test	2008/07/18	Test Range	30MHz~10GHz

CH. 1013(824.7 MHz)			CH.384 (836.52 MHz)			CH. 777(848.31 MHz)		
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Frequency (MHz)	Emission Level (dBm)	Limit (dBm)
1649.4	-61.78	-13	1673.04	-62.58	-13	1696.62	-61.32	-13
2474.1	-58.08	-13	2509.56	-56.48	-13	2544.93	-53.16	-13
3298.8	-46.54	-13	3346.08	-40.69	-13	3393.24	-37.51	-13
4123.5	-45.49	-13	4182.6	-40.65	-13	4241.55	-39.04	-13
4948.2	-56.90	-13	5019.12	-51.31	-13	5089.86	-47.37	-13
5772.9	-58.90	-13	5855.64	-60.24	-13	5938.17	-57.59	-13
6597.6	-61.78	-13	6692.16	-61.05	-13	6786.48	-56.99	-13
7422.3	-60.93	-13	7528.68	-61.37	-13	7634.79	-59.83	-13
8247.0	-58.03	-13	8365.2	-57.48	-13	8483.1	-60.38	-13




Fig. 5-3(a) Conducted spurious emission for mode 1(Ch. 1013).




Fig. 5-3(b) Conducted spurious emission for mode 1(Ch. 1013).




Fig. 5-3(c) Conducted spurious emission for mode 1(Ch. 1013).




Fig. 5-3(d) Conducted spurious emission for mode 1(Ch. 1013).




Fig. 5-4(a) Conducted spurious emission for mode 1(Ch. 384).




Fig. 5-4(b) Conducted spurious emission for mode 1(Ch. 384).




Fig. 5-4(c) Conducted spurious emission for mode 1(Ch. 384).




Fig. 5-4(d) Conducted spurious emission for mode 1(Ch. 384).




Fig. 5-5(a) Conducted spurious emission for mode 1(Ch. 777).




Fig. 5-5(b) Conducted spurious emission for mode 1(Ch. 777).




Fig. 5-5(c) Conducted spurious emission for mode 1(Ch. 777).




Fig. 5-5(d) Conducted spurious emission for mode 1(Ch. 777).

Product	Cellular/PCS CDMA Phone with Bluetooth (BT2.0+EDR)		
Test Condition	Conducted Spurious Emission	Battery Type	Standard
Test Mode	Mode 2: CDMA2000 1xRTT PCS 1900	Test Site	CB5
Date of Test	2008/07/18	Test Range	30MHz~20GHz

CH. 25(1851.25 MHz)			CH.600 (1880.00 MHz)			CH. 1175(1908.75 MHz)		
Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Frequency (MHz)	Emission Level (dBm)	Limit (dBm)	Frequency (MHz)	Emission Level (dBm)	Limit (dBm)
3702.4	-34.76	-13	3760	-43.32	-13	3817.5	-18.44	-13
5553.6	-47.84	-13	5640	-42.18	-13	5726.25	-41.39	-13
7404.8	-48.35	-13	7520	-44.35	-13	7635	-51.17	-13
9256	-61.17	-13	9400	-60.82	-13	9543.75	-60.52	-13
11107.2	-61.92	-13	11280	-61.05	-13	11452.5	-61.82	-13
12958.4	-60.92	-13	13160	-59.83	-13	13361.25	-58.84	-13
14809.6	-58.44	-13	15040	-58.83	-13	15270	-58.22	-13
16660.8	-58.23	-13	16920	-58.54	-13	17178.75	-58.93	-13
18512	-58.63	-13	18800	-59.42	-13	19087.5	-58.00	-13




Fig. 5-6(a) Conducted spurious emission for mode 2(Ch. 25).




Fig. 5-6(b) Conducted spurious emission for mode 2(Ch. 25).




Fig. 5-6(c) Conducted spurious emission for mode 2(Ch. 25).




Fig. 5-6(d) Conducted spurious emission for mode 2(Ch. 25).




Fig. 5-6(e) Conducted spurious emission for mode 2(Ch. 25).




Fig. 5-7(a) Conducted spurious emission for mode 2(Ch. 600).




Fig. 5-7(b) Conducted spurious emission for mode 2(Ch. 600).




Fig. 5-7(c) Conducted spurious emission for mode 2(Ch. 600).




Fig. 5-7(d) Conducted spurious emission for mode 2(Ch. 600).




Fig. 5-7(e) Conducted spurious emission for mode 2(Ch. 600).




Fig. 5-8(a) Conducted spurious emission for mode 2(Ch. 1175).




Fig. 5-8(b) Conducted spurious emission for mode 2(Ch. 1175).




Fig. 5-8(c) Conducted spurious emission for mode 2(Ch. 1175).




Fig. 5-8(d) Conducted spurious emission for mode 2(Ch. 1175).




Fig. 5-8(e) Conducted spurious emission for mode 2(Ch. 1175).

5.6.2 Radiated Spurious Emission

Product	Cellular/PCS CDMA Phone with Bluetooth (BT2.0+EDR)		
Test Condition	Radiated Spurious Emission	Battery Type	Standard
Test Mode	Mode 1: CDMA2000 1xRTT Cellular 850	Test Site	OATS 3
Date of Test	2008/06/25	Test Range	30MHz~10GHz
TX Channel	CH. 1013(824.7MHz)		

Frequency	Reading Level	Signal Generator Level	Cable Loss	Antenna Gain	ERP Value	Limit
(MHz)	(dBm)	(dBm)	(dB)	(dBd)	(dBm)	(dBm)
Horizontal Emissions						
1649.4	-56.40	-61.35	1.41	7.65	-55.11	-13
2474.1	-58.75	-60.65	1.56	8.45	-53.76	-13
3298.8	-55.49	-53.78	2.01	10.15	-45.64	-13
4123.5	-58.99	-56.31	2.74	10.45	-48.6	-13
4948.2	-60.59	-55.98	2.64	10.55	-48.07	-13
5772.9	-61.56	-57.09	2.36	10.85	-48.6	-13
6597.6	-62.05	-56.19	3.16	9.95	-49.4	-13
7422.3	-61.36	-50.36	3.3	9.35	-44.31	-13
8247	-60.59	-49.05	3.16	9.35	-42.86	-13
Vertical Emissions						
1649.4	-57.29	-62.32	1.41	7.65	-56.08	-13
2474.1	-58.10	-59.76	1.56	8.45	-52.87	-13
3298.8	-59.16	-60.38	2.01	10.15	-52.24	-13
4117.5	-59.04	-56.97	2.74	10.45	-49.26	-13
4948.2	-60.16	-55.20	2.64	10.55	-47.29	-13
5736.9	-61.53	-56.57	2.36	10.85	-48.08	-13
6597.6	-61.94	-60.18	3.16	9.95	-53.39	-13
7422.3	-61.03	-52.05	3.3	9.35	-46	-13
8247	-60.44	-49.11	3.16	9.35	-42.92	-13

Note:

1. Receiver setting (Peak Detector) : RBW:3MHz; VBW:3MHz
2. ERP Value = Signal Generator Level + Antenna Gain - Cable Loss

Product	Cellular/PCS CDMA Phone with Bluetooth (BT2.0+EDR)		
Test Condition	Radiated Spurious Emission	Battery Type	Standard
Test Mode	Mode 1: CDMA2000 1xRTT Cellular 850	Test Site	OATS 3
Date of Test	2008/06/25	Test Range	30MHz~10GHz
TX Channel	CH. 384(836.52MHz)		

Frequency	Reading Level	Signal Generator Level	Cable Loss	Antenna Gain	ERP Value	Limit
(MHz)	(dBm)	(dBm)	(dB)	(dBd)	(dBm)	(dBm)
Horizontal Emissions						
1673.04	-58.52	-65	1.41	7.65	-58.76	-13
2509.56	-59.18	-61.21	1.56	8.45	-54.32	-13
3346.08	-57.48	-57.09	2.01	10.15	-48.95	-13
4182.6	-58.42	-55.08	2.74	10.45	-47.37	-13
5019.12	-60.57	-55.95	2.64	10.55	-48.04	-13
5857.64	-61.51	-56.97	2.36	10.85	-48.48	-13
6692.16	-60.31	-52.4	3.16	9.95	-45.61	-13
7528.68	-61.41	-50.47	3.3	9.35	-44.42	-13
8365.2	-60.49	-48.85	3.16	9.35	-42.66	-13
Vertical Emissions						
1673.04	-59.72	-64.79	1.41	7.65	-58.55	-13
2509.56	-58.32	-60.07	1.56	8.45	-53.18	-13
3346.08	-56.69	-56.13	2.01	10.15	-47.99	-13
4182.6	-60.04	-58.87	2.74	10.45	-51.16	-13
5019.12	-61.05	-57.31	2.64	10.55	-49.4	-13
5885.64	-61.58	-56.73	2.36	10.85	-48.24	-13
6692.16	-60.82	-56.48	3.16	9.95	-49.69	-13
7528.68	-61.26	-52.58	3.3	9.35	-46.53	-13
8365.2	-60.24	-48.79	3.16	9.35	-42.6	-13

Note:

1. Receiver setting (Peak Detector) : RBW:3 MHz; VBW:3MHz
2. ERP Value = Signal Generator Level + Antenna Gain - Cable Loss

Product	Cellular/PCS CDMA Phone with Bluetooth (BT2.0+EDR)		
Test Condition	Radiated Spurious Emission	Battery Type	Standard
Test Mode	Mode 1: CDMA2000 1xRTT Cellular 850	Test Site	OATS 3
Date of Test	2008/06/25	Test Range	30MHz~10GHz
TX Channel	CH. 777(848.31MHz)		

Frequency	Reading Level	Signal Generator Level	Cable Loss	Antenna Gain	ERP Value	Limit
(MHz)	(dBm)	(dBm)	(dB)	(dBd)	(dBm)	(dBm)
Horizontal Emissions						
1696.62	-56.50	-61.55	1.41	7.65	-51.19	-13
2544.99	-54.73	-53.89	1.56	8.45	-52.98	-13
3393.24	-47.72	-43.32	2.01	10.15	-41.16	-13
4241.55	-56.09	-51.38	2.74	10.45	-43.67	-13
5089.86	-59.95	-54.75	2.64	10.55	-46.84	-13
5938.17	-61.75	-57.52	2.36	10.85	-49.03	-13
6786.48	-61.04	-53.77	3.16	9.95	-46.98	-13
7634.79	-61.16	-49.92	3.3	9.35	-43.87	-13
8483.1	-60.23	-48.34	3.16	9.35	-42.15	-13
Vertical Emissions						
1696.62	-57.85	-63.22	1.41	7.65	-56.98	-13
2544.93	-58.02	-59.62	1.56	8.45	-52.73	-13
3393.24	-59.08	-60.29	2.01	10.15	-52.15	-13
4241.55	-55.16	-50.85	2.74	10.45	-43.14	-13
5089.86	-59.44	-53.71	2.64	10.55	-45.8	-13
5938.17	-61.62	-56.85	2.36	10.85	-48.36	-13
6786.48	-61.10	-57.48	3.16	9.95	-50.69	-13
7634.79	-61.24	-52.53	3.3	9.35	-46.48	-13
8483.10	-60.31	-48.90	3.16	9.35	-42.71	-13

Note:

1. Receiver setting (Peak Detector) : RBW:3MHz; VBW:3MHz
2. ERP Value = Signal Generator Level + Antenna Gain - Cable Loss

Product	Cellular/PCS CDMA Phone with Bluetooth (BT2.0+EDR)		
Test Condition	Radiated Spurious Emission	Battery Type	Standard
Test Mode	Mode 2: CDMA2000 1xRTT PCS 1900	Test Site	OATS 3
Date of Test	2008/07/18	Test Range	30MHz~20GHz
TX Channel	CH. 25(1851.25 MHz)		

Frequency	Reading Level	Signal Generator Level	Cable Loss	Antenna Gain	EIRP Value	Limit
(MHz)	(dBm)	(dBm)	(dB)	(dBi)	(dBm)	(dBm)
Horizontal Emissions						
3702.5	-53.79	-49.26	1.41	9.8	-38.07	-13
5553.75	-57.17	-46.32	1.56	10.6	-34.78	-13
7405	-60.05	-46.98	2.01	12.3	-37.49	-13
9256.25	-59.72	-44.62	2.74	12.6	-35.36	-13
11107.5	-60.34	-45.83	2.64	12.7	-36.47	-13
12958.75	-58.98	-39.75	2.36	13	-28.81	-13
Vertical Emissions						
3702.5	-58.07	-55.77	1.41	9.8	-44.58	-13
5553.75	-58.00	-48.67	1.56	10.6	-37.13	-13
7405	-60.29	-47.56	2.01	12.3	-38.07	-13
9256.25	-59.60	-43.57	2.74	12.6	-34.31	-13
11107.5	-60.97	-45.78	2.64	12.7	-36.42	-13
12958.75	-59.36	-39.38	2.36	13	-28.44	-13

Note:

1. Receiver setting (Peak Detector) : RBW:3MHz; VBW:3MHz
2. EIRP Value = Signal Generator Level + Antenna Gain - Cable Loss
3. Spurious emissions past 14 GHz are not shown, due to the magnitude of spurious emissions attenuated more than 20 dB below the limit.

Product	Cellular/PCS CDMA Phone with Bluetooth (BT2.0+EDR)		
Test Condition	Radiated Spurious Emission	Battery Type	Standard
Test Mode	Mode 2: CDMA2000 1xRTT PCS 1900	Test Site	OATS 3
Date of Test	2008/07/18	Test Range	30MHz~20GHz
TX Channel	CH. 600(1880 MHz)		

Frequency	Reading Level	Signal Generator Level	Cable Loss	Antenna Gain	EIRP Value	Limit
(MHz)	(dBm)	(dBm)	(dB)	(dBi)	(dBm)	(dBm)
Horizontal Emissions						
3760	-58.35	-56.37	1.41	9.8	-45.18	-13
5640	-58.79	-49.00	1.56	10.6	-37.46	-13
7520	-60.52	-48.15	2.01	12.3	-38.66	-13
9400	-58.56	-42.65	2.74	12.6	-33.39	-13
11280	-59.23	-42.72	2.64	12.7	-33.36	-13
13160	-60.04	-42.43	2.36	13	-31.49	-13
Vertical Emissions						
3760	-58.70	-56.98	1.41	9.8	-45.79	-13
5640	-57.74	-48.26	1.56	10.6	-36.72	-13
7520	-59.62	-46.12	2.01	12.3	-36.63	-13
9400	-59.88	-44.08	2.74	12.6	-34.82	-13
11280	-58.95	-40.69	2.64	12.7	-31.33	-13
13160	-60.08	-41.21	2.36	13	-30.27	-13

Note:

1. Receiver setting (Peak Detector) : RBW:3MHz; VBW:3MHz
2. EIRP Value = Signal Generator Level + Antenna Gain - Cable Loss
3. Spurious emissions past 14 GHz are not shown, due to the magnitude of spurious emissions attenuated more than 20 dB below the limit.

Product	Cellular/PCS CDMA Phone with Bluetooth (BT2.0+EDR)		
Test Condition	Radiated Spurious Emission	Battery Type	Standard
Test Mode	Mode 2: CDMA2000 1xRTT PCS 1900	Test Site	OATS 3
Date of Test	2008/07/18	Test Range	30MHz~20GHz
TX Channel	CH. 1175(1908.75 MHz)		

Frequency	Reading Level	Signal Generator Level	Cable Loss	Antenna Gain	EIRP Value	Limit
(MHz)	(dBm)	(dBm)	(dB)	(dBi)	(dBm)	(dBm)
Horizontal Emissions						
3817.5	-52.52	-47.68	1.41	9.8	-36.49	-13
5726.25	-56.66	-45.48	1.56	10.6	-33.94	-13
7635	-59.31	-45.13	2.01	12.3	-35.64	-13
9543.75	-59.04	-43.46	2.74	12.6	-34.20	-13
11452.5	-58.65	-41.36	2.64	12.7	-32.00	-13
13361.25	-59.16	-40.16	2.36	13	-29.22	-13
Vertical Emissions						
3817.5	-56.67	-53.83	1.41	9.8	-42.64	-13
5726.25	-58.04	-48.73	1.56	10.6	-37.19	-13
7635	-59.27	-45.36	2.01	12.3	-35.87	-13
9543.75	-59.88	-44.08	2.74	12.6	-34.82	-13
11452.5	-59.47	-41.93	2.64	12.7	-32.57	-13
13361.25	-59.93	-40.71	2.36	13	-29.77	-13

Note:

1. Receiver setting (Peak Detector) : RBW:3MHz; VBW:3MHz
2. EIRP Value = Signal Generator Level + Antenna Gain - Cable Loss
3. Spurious emissions past 14 GHz are not shown, due to the magnitude of spurious emissions attenuated more than 20 dB below the limit.


6. Frequency Stability Under Temperature & Voltage Variations

6.1. Test Equipment

The following test equipments are used during the frequency stability test:

Item	Equipment	Manufacturer	Type No./Serial No	Calibration Date	Calibration Due
1	Universal Radio Communication Tester	Agilent	8960 / GB47390315	May 02, 2008	May 01, 2009
2	Standard Temperature & Humidity Chamber	WIT	TH-1S-B / 108210	Aug 16, 2007	Aug 15, 2008
3	DC Power Supply	Agilent	E3610A / MY40009845	Apr 28, 2008	Apr 27, 2009

6.2. Test Setup



6.3. Limits

FCC Part 2.1055 & 22.355 & 24.235	
Limit	±2.5 ppm

6.4. Test Procedure

The frequency stability of transmitter is measured by:

- (a) **Temperature:** The temperature is varied from -30°C to 50°C in 10°C increment using a standard temperature & Humidity chamber.
- (b) **Primary Supply Voltage:** The primary supply voltage is varied 85% to 115% of the nominal value for non hand-carried equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating endpoint which shall be specified by the manufacturer.

Reference Standards: Part 2.1055 & 22.355 & 24.235

6.5. Uncertainty

The measurement uncertainty is evaluated as Hz.

Contributions		Probability Distribution	Standard Uncertainty $u_i(\text{Hz})$
Time base uncertainty	U_{01}	Rectangular	33.08
Counter uncertainty	U_{02}	Rectangular	2.9
Ambient temperature uncertainty	U_{03}	Normal	20.21
Combined Standard Uncertainty, U			38.87
Expanded Uncertainty (for a 95 % confidence level, k=2)			77.74

6.6. Test Result of Frequency Stability Under Temperature Variations

Product	Cellular/PCS CDMA Phone with Bluetooth (BT2.0+EDR)		
Test Condition	Frequency Stability Under Temperature Variations & Voltage Variations		
Test Mode	Mode 1: CDMA2000 1xRTT Cellular 850	Test Site	CTR
Date of Test	2008/07/18	Test Range	-30°C~+50°C, 85%~115% DC Voltage
TX Channel	CH. 384(836.52 MHz)		

Temperature Interval(°C)	DC Voltage (V)	Test Frequency (GHz)	Deviation (Hz)	Limit (KHz)
-30	3.7	0.836	-17	±2.0913
-20		0.836	14	±2.0913
-10		0.836	-12	±2.0913
0		0.836	16	±2.0913
10		0.836	-14	±2.0913
20		0.836	-15	±2.0913
30		0.836	-12	±2.0913
40		0.836	14	±2.0913
50		0.836	19	±2.0913

DC Voltage (V)	Temperature Interval(°C)	Test Frequency (GHz)	Deviation (Hz)	Limit (KHz)
3.3	20	0.836	19	±2.0913
3.7		0.836	-17	±2.0913
4.2		0.836	-21	±2.0913

Product	Cellular/PCS CDMA Phone with Bluetooth (BT2.0+EDR)		
Test Condition	Frequency Stability Under Temperature Variations & Voltage Variations		
Test Mode	Mode 2: CDMA2000 1xRTT PCS 1900	Test Site	CTR
Date of Test	2008/07/18	Test Range	-30°C~+50°C, 85%~115% DC Voltage
TX Channel	CH. 600(1880 MHz)		

Temperature Interval(°C)	DC Voltage (V)	Test Frequency (GHz)	Deviation (Hz)	Limit (KHz)
-30	3.7	1.88	-48	±4.7
-20		1.88	41	±4.7
-10		1.88	-32	±4.7
0		1.88	22	±4.7
10		1.88	-22	±4.7
20		1.88	-28	±4.7
30		1.88	-35	±4.7
40		1.88	-32	±4.7
50		1.88	36	±4.7

DC Voltage (V)	Temperature Interval(°C)	Test Frequency (GHz)	Deviation (Hz)	Limit (KHz)
3.3	20	1.88	-28	±4.7
3.7		1.88	-26	±4.7
4.2		1.88	-29	±4.7