

SAR Compliance Test Report

Test report no.:	SD_SAR_0913_01	Date of report:	2009-03-25
Template version:	11.0	Number of pages:	58
Testing laboratory:	TCC Nokia San Diego Laboratory 12278 Scripps Summit Drive SAN DIEGO CA. 92131 USA Tel. +1 858 831 5000 Fax. +1 858 831 6500	Client:	Nokia Corporation 12278 Scripps Summit Drive SAN DIEGO CA. 92131 USA Tel. +1 858 831 5000 Fax. +1 858 831 6500
Responsible test engineer:	Jose Gomez	Product contact person:	Mary Washington
Measurements made by:	Jose Gomez, Julian Kim		
Tested device:	RM-526		
FCC ID:	QMNRM-526	IC:	661X-RM526
Supplement reports:	SD_SAR_0913_02		
Testing has been carried out in accordance with:	47CFR §2.1093 Radiofrequency Radiation Exposure Evaluation: Portable Devices FCC OET Bulletin 65 (Edition 97-01), Supplement C (Edition 01-01) Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields RSS-102 Evaluation Procedure for Mobile and Portable Radio Transmitters with Respect to Health Canada's Safety Code 6 for Exposure of Humans to Radio Frequency Fields IEEE 1528 - 2003 IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Technique		
Documentation:	The documentation of the testing performed on the tested devices is archived for 15 years at TCC San Diego.		
Test results:	The tested device complies with the requirements in respect of all parameters subject to the test. The test results and statements relate only to the items tested. The test report shall not be reproduced except in full, without written approval of the laboratory.		

Date and signatures:



For the contents:

Jose Gomez
Certification Test Engineer

2009-04-03

CONTENTS

1. SUMMARY OF SAR TEST REPORT	4
1.1 TEST DETAILS.....	4
1.2 MAXIMUM RESULTS.....	4
1.2.1 Head Configuration.....	4
1.2.2 Body Worn Configuration	4
1.2.3 Maximum Drift	5
1.2.4 Measurement Uncertainty.....	5
2. DESCRIPTION OF THE DEVICE UNDER TEST	5
2.1 DESCRIPTION OF THE ANTENNA.....	5
3. TEST CONDITIONS	5
3.1 TEMPERATURE AND HUMIDITY.....	5
3.2 TEST SIGNAL, FREQUENCIES AND OUTPUT POWER.....	5
4. DESCRIPTION OF THE TEST EQUIPMENT	6
4.1 MEASUREMENT SYSTEM AND COMPONENTS	6
4.1.1 Isotropic E-field Probe Type ET3DV6	7
4.2 PHANTOMS	7
4.3 TISSUE SIMULANTS.....	7
4.3.1 Tissue Simulant Recipes.....	8
4.3.2 System Checking	8
4.3.3 Tissue Simulants used in the Measurements.....	9
5. DESCRIPTION OF THE TEST PROCEDURE	11
5.1 DEVICE HOLDER.....	11
5.2 TEST POSITIONS.....	11
5.2.1 Against Phantom Head.....	11
5.2.2 Body Worn Configuration	11
5.3 SCAN PROCEDURES.....	12
5.4 SAR AVERAGING METHODS.....	12
6. MEASUREMENT UNCERTAINTY	13
7. RESULTS.....	14
APPENDIX A: SYSTEM CHECKING SCANS.....	16
APPENDIX B: MEASUREMENT SCANS.....	23
APPENDIX C: CONDUCTED POWER MEASUREMENTS FOR SUPPORTED TRANSMISSION MODES	44
APPENDIX D: CONDUCTED POWER SETUP FOR TESTING.....	48
APPENDIX E: RELEVANT PAGES FROM PROBE CALIBRATION REPORT(S)	49

APPENDIX F: RELEVANT PAGES FROM DIPOLE VALIDATION KIT REPORT(S)	52
--	-----------

1. SUMMARY OF SAR TEST REPORT

1.1 Test Details

Period of test	2009-03-11 to 2009-03-24
SN, HW and SW numbers of tested device	SN: A00000016703A7, HW: 3000, SW: VN_2040T13_VZW_108, DUT: 79995
Batteries used in testing	BL-4C, DUT: 79994, 79993 BL-10C, DUT: 79992, 79991
Headsets used in testing	HS-49, DUT: 79990
Other accessories used in testing	-
State of sample	Prototype unit
Notes	-

1.2 Maximum Results

The maximum measured SAR values for Head configuration and Body Worn configuration are given in section 1.2.1 and 1.2.2 respectively. The device conforms to the requirements of the standard(s) when the maximum measured SAR value is less than or equal to the limit.

1.2.1 Head Configuration

Mode	Ch / f (MHz)	Conducted power	Position	Measured SAR value (1g avg)	Scaled* SAR value (1g avg)	SAR limit (1g avg)	Result
CDMA800	777/848.31	24.31dBm	Left, Cheek	0.901W/kg	1.01W/kg	1.6 W/kg	PASSED
CDMA1900	1175/1908.75	24.32dBm	Left, Cheek	1.00W/kg	1.12W/kg	1.6 W/kg	PASSED

1.2.2 Body Worn Configuration

Mode	Ch / f (MHz)	Conducted power	Separation distance	Measured SAR value (1g avg)	Scaled* SAR value (1g avg)	SAR limit (1g avg)	Result
CDMA800	777/848.31	24.31dBm	2.2cm	0.545W/kg	0.61W/kg	1.6 W/kg	PASSED
CDMA1900	600/1880.0	24.51dBm	2.2cm	0.229W/kg	0.26W/kg	1.6 W/kg	PASSED

* SAR values are scaled up by 12% to cover measurement drift. As a consequence of this upwards correction of the SAR values, the contribution of measurement drift to the overall measurement uncertainty (Section 6) is reduced to zero.

1.2.3 Maximum Drift

Maximum drift covered by 12% scaling up of the SAR values	Maximum drift during measurements
0.5dB	0.39dB

1.2.4 Measurement Uncertainty

Expanded Uncertainty (k=2) 95%	± 25.8%
--------------------------------	---------

2. DESCRIPTION OF THE DEVICE UNDER TEST

Device category	Portable
Exposure environment	General population / uncontrolled

Modes of Operation	Bands	Modulation Mode	Duty Cycle	Transmitter Frequency Range (MHz)
CDMA	800 1900	QPSK	1	824 – 849 1850 – 1910
BT	2450	GFSK	1	2402 – 2480

This is a 1 x RTT and Ev-Do Rev0 device.

2.1 Description of the Antenna

The device has an internal antenna. It is located at the bottom of the device underneath the back surface.

3. TEST CONDITIONS

3.1 Temperature and Humidity

Ambient temperature (°C):	20.3 to 22.1
Ambient humidity (RH %):	44 to 67

3.2 Test Signal, Frequencies and Output Power

The device was put into operation by using a call tester. Communication between the device and the call tester was established by air link.

The device output power was set to maximum power level for all tests; a fully charged battery was used for every test sequence.

In all operating bands the measurements were performed on lowest, middle and highest channels.

4. DESCRIPTION OF THE TEST EQUIPMENT

4.1 Measurement System and Components

The measurements were performed using an automated near-field scanning system, DASY4, manufactured by Schmid & Partner Engineering AG (SPEAG) in Switzerland. The SAR extrapolation algorithm used in all measurements was the 'advanced extrapolation' algorithm.

The following table lists calibration dates of SPEAG components:

Test Equipment	Serial Number	Calibration interval	Calibration expiry
DAE 4	860	12 months	2009-06
E-field Probe ET3DV6	1516	12 months	2009-10
Dipole Validation Kit, D835V2	486	24 months	2010-10
Dipole Validation Kit, D1900V2	509	24 months	2010-06
DASY Software	Version 4.7	-	-

Additional test equipment used in testing:

Test Equipment	Model	Serial Number	Calibration interval	Calibration expiry
Signal Generator	HP E4432B	US 40053677	24 months	2009-10
Signal Generator	HP E4432B	US 40052231	24 months	2010-06
Amplifier	Milmega AS0822-8L	1004832	-	-
Amplifier	Milmega AS0822-20L	1009777	-	-
Power Meter	Agilent E4417A	GB41290918	12 months	2010-01
Power Sensor	Agilent E9301A	US39211902	12 months	2009-07
Call Tester	Agilent 8960	GB44350217	-	-
Vector Network Analyzer	Agilent 8753ES	US39174327	12 months	2009-05
Dielectric Probe Kit	Agilent 85070D	US01440165	-	-

4.1.1 Isotropic E-field Probe Type ET3DV6

Construction	Symmetrical design with triangular core Built-in optical fiber for surface detection system Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., butyl diglycol)
Calibration	Calibration certificate in Appendix C
Frequency	10 MHz to 3 GHz (dosimetry); Linearity: ± 0.2 dB (30 MHz to 3 GHz)
Optical Surface Detection	± 0.2 mm repeatability in air and clear liquids over diffuse reflecting surfaces
Directivity	± 0.2 dB in HSL (rotation around probe axis) ± 0.4 dB in HSL (rotation normal to probe axis)
Dynamic Range	5 μ W/g to > 100 mW/g; Linearity: ± 0.2 dB
Dimensions	Overall length: 330 mm Tip length: 16 mm Body diameter: 12 mm Tip diameter: 6.8 mm Distance from probe tip to dipole centers: 2.7 mm
Application	General dosimetry up to 3 GHz Compliance tests of mobile phones Fast automatic scanning in arbitrary phantoms

4.2 Phantoms

The phantom used for all tests i.e. for both system checks and device testing, was the twin-headed "SAM Phantom", manufactured by SPEAG. The phantom conforms to the requirements of IEEE 1528 - 2003.

System checking was performed using the flat section, whilst Head SAR tests used the left and right head profile sections. Body SAR testing also used the flat section between the head profiles.

The SPEAG device holder (see Section 5.1) was used to position the device in all tests whilst a tripod was used to position the validation dipoles against the flat section of phantom.

4.3 Tissue Simulants

Recommended values for the dielectric parameters of the tissue simulants are given in IEEE 1528 - 2003 and FCC Supplement C to OET Bulletin 65. All tests were carried out using simulants whose dielectric parameters were within $\pm 5\%$ of the recommended values. All tests were carried out within 24 hours of measuring the dielectric parameters.

The depth of the tissue simulant was 15.0 ± 0.5 cm measured from the ear reference point during system checking and device measurements.

4.3.1 Tissue Simulant Recipes

The following recipe(s) were used for Head and Body tissue simulant(s):

800MHz band

Ingredient	Head (% by weight)	Body (% by weight)
Deionised Water	51.50	69.25
Tween 20	47.35	30.00
Salt	1.15	0.75

1900MHz band

Ingredient	Head (% by weight)	Body (% by weight)
Deionised Water	54.88	69.02
Butyl Diglycol	44.91	30.76
Salt	0.21	0.22

4.3.2 System Checking

The manufacturer calibrates the probes annually. Dielectric parameters of the tissue simulants were measured every day using the dielectric probe kit and the network analyser. A system check measurement was made following the determination of the dielectric parameters of the simulant, using the dipole validation kit. A power level of 250 mW was supplied to the dipole antenna, which was placed under the flat section of the twin SAM phantom. The system checking results (dielectric parameters and SAR values) are given in the table below.

System checking, head tissue simulant

f [MHz]	Description	SAR [W/kg], 1g	Dielectric Parameters		Temp [°C]
			ϵ_r	σ [S/m]	
835	Reference result	2.39	40.5	0.90	
	± 10% window	2.15 - 2.63			
	2009-03-11	2.33	41.4	0.91	22.1
	2009-03-23	2.17	40.4	0.91	21.2
1900	Reference result	9.96	39.1	1.48	
	± 10% window	8.96 - 10.96			
	2009-03-16	10.7	37.9	1.42	21.3
	2009-03-17	10.8	38.0	1.43	20.3

System checking, body tissue simulant

f [MHz]	Description	SAR [W/kg], 1g	Dielectric Parameters		Temp [°C]
			ϵ_r	σ [S/m]	
835	Reference result	2.42	53.4	1.00	
	± 10% window	2.18 - 2.66			
	2009-03-24	2.40	52.0	0.98	21.0
1900	Reference result	9.77	52.4	1.58	
	± 10% window	8.79 - 10.75			
	2009-03-17	9.64	52.3	1.55	20.4

Plots of the system checking scans are given in Appendix A.

4.3.3 Tissue Simulants used in the Measurements

Head tissue simulant measurements

f [MHz]	Description	Dielectric Parameters		Temp [°C]
		ϵ_r	σ [S/m]	
836	Recommended value	41.5	0.90	
	± 5% window	39.4 - 43.6	0.86 - 0.95	
	2009-03-11	41.4	0.91	22.1
	2009-03-23	40.4	0.91	21.2
1880	Recommended value	40.0	1.40	
	± 5% window	38.0 - 42.0	1.33 - 1.47	
	2009-03-16	38.2	1.41	21.3
	2009-03-17	38.1	1.41	20.3

Body tissue simulant measurements

f [MHz]	Description	Dielectric Parameters		Temp [°C]
		ϵ_r	σ [S/m]	
836	Recommended value	55.2	0.97	
	$\pm 5\%$ window	52.4 – 58.0	0.92 – 1.02	
	2009-03-24	52.0	0.98	21.0
1880	Recommended value	53.3	1.52	
	$\pm 5\%$ window	50.6 – 56.0	1.44 – 1.60	
	2009-03-17	52.5	1.54	20.4

5. DESCRIPTION OF THE TEST PROCEDURE

5.1 Device Holder

The device was placed in the device holder (illustrated below) that is supplied by SPEAG as an integral part of the Dasy system.



Device holder supplied by SPEAG

A Nokia designed spacer (illustrated below) was used to position the device within the SPEAG holder. The spacer positions the device so that the holder has minimal effect on the test results but still holds the device securely. The spacer was removed before the tests.



Nokia spacer

5.2 Test Positions

5.2.1 Against Phantom Head

Measurements were made in “cheek” and “tilt” positions on both the left hand and right hand sides of the phantom.

The positions used in the measurements were according to IEEE 1528 - 2003 "IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques".

5.2.2 Body Worn Configuration

The device was placed in the SPEAG holder using the Nokia spacer and placed below the flat section of the phantom. The distance between the device and the phantom was kept at the

separation distance indicated in Section 1.2.2 using a separate flat spacer that was removed before the start of the measurements. The device was oriented with both sides facing the phantom to find the highest results.

5.3 Scan Procedures

First, area scans were used for determination of the field distribution. Next, a zoom scan, a minimum of 5x5x7 points covering a volume of at least 30x30x30mm, was performed around the highest E-field value to determine the averaged SAR value. Drift was determined by measuring the same point at the start of the area scan and again at the end of the zoom scan.

5.4 SAR Averaging Methods

The maximum SAR value was averaged over a cube of tissue using interpolation and extrapolation.

The interpolation, extrapolation and maximum search routines within Dasy4 are all based on the modified Quadratic Shepard's method (Robert J. Renka, "Multivariate Interpolation Of Large Sets Of Scattered Data", University of North Texas ACM Transactions on Mathematical Software, vol. 14, no. 2, June 1988, pp. 139-148).

The interpolation scheme combines a least-square fitted function method with a weighted average method. A trivariate 3-D / bivariate 2-D quadratic function is computed for each measurement point and fitted to neighbouring points by a least-square method. For the zoom scan, inverse distance weighting is incorporated to fit distant points more accurately. The interpolating function is finally calculated as a weighted average of the quadratics.

In the zoom scan, the interpolation function is used to extrapolate the Peak SAR from the deepest measurement points to the inner surface of the phantom.

6. MEASUREMENT UNCERTAINTY

Table 6.1 – Measurement uncertainty evaluation

Uncertainty Component	Section in IEEE 1528	Tol. (%)	Prob Dist	Div	C_i	$C_i \cdot U_i$ (%)	v_i
Measurement System							
Probe Calibration	E2.1	±5.9	N	1	1	±5.9	∞
Axial Isotropy	E2.2	±4.7	R	√3	$(1-c_p)^{1/2}$	±1.9	∞
Hemispherical Isotropy	E2.2	±9.6	R	√3	$(c_p)^{1/2}$	±3.9	∞
Boundary Effect	E2.3	±1.0	R	√3	1	±0.6	∞
Linearity	E2.4	±4.7	R	√3	1	±2.7	∞
System Detection Limits	E2.5	±1.0	R	√3	1	±0.6	∞
Readout Electronics	E2.6	±1.0	N	1	1	±1.0	∞
Response Time	E2.7	±0.8	R	√3	1	±0.5	∞
Integration Time	E2.8	±2.6	R	√3	1	±1.5	∞
RF Ambient Conditions - Noise	E6.1	±3.0	R	√3	1	±1.7	∞
RF Ambient Conditions - Reflections	E6.1	±3.0	R	√3	1	±1.7	∞
Probe Positioner Mechanical Tolerance	E6.2	±0.4	R	√3	1	±0.2	∞
Probe Positioning with respect to Phantom Shell	E6.3	±2.9	R	√3	1	±1.7	∞
Extrapolation, interpolation and Integration Algorithms for Max. SAR Evaluation	E5	±3.9	R	√3	1	±2.3	∞
Test sample Related							
Test Sample Positioning	E4.2	±6.0	N	1	1	±6.0	11
Device Holder Uncertainty	E4.1	±5.0	N	1	1	±5.0	7
Output Power Variation - SAR drift measurement	6.6.3	±0.0	R	√3	1	±0.0	∞
Phantom and Tissue Parameters							
Phantom Uncertainty (shape and thickness tolerances)	E3.1	±4.0	R	√3	1	±2.3	∞
Conductivity Target - tolerance	E3.2	±5.0	R	√3	0.64	±1.8	∞
Conductivity - measurement uncertainty	E3.3	±5.5	N	1	0.64	±3.5	5
Permittivity Target - tolerance	E3.2	±5.0	R	√3	0.6	±1.7	∞
Permittivity - measurement uncertainty	E3.3	±2.9	N	1	0.6	±1.7	5
Combined Standard Uncertainty			RSS			±12.9	116
Coverage Factor for 95%			k=2				
Expanded Uncertainty						±25.8	

7. RESULTS

The measured Head SAR values for the test device are tabulated below:

800MHz Head SAR results

Battery used	Option used	Test configuration		SAR, averaged over 1g (W/kg)		
				Ch 1013 824.70MHz	Ch 384 836.52MHz	Ch 777 848.31MHz
RC3/S05		Power		24.42 dBm	24.42 dBm	24.31 dBm
BL-4C	Swivel open	Left	Cheek	0.621	0.768	0.901
			Tilt	-	0.324	-
		Right	Cheek	-	0.699	-
			Tilt	-	0.305	-
BL-10C	Swivel open	Left Cheek		0.521	0.511	0.646

1900MHz Head SAR results

Battery used	Option used	Test configuration		SAR, averaged over 1g (W/kg)		
				Ch 25 1851.25MHz	Ch 600 1880.00MHz	Ch1175 1908.75MHz
RC3/S05		Power		24.32 dBm	24.51 dBm	24.32 dBm
BL-4C	Swivel open	Left	Cheek	0.724	0.930	1.00
			Tilt	-	0.338	-
		Right	Cheek	-	0.653	-
			Tilt	-	0.350	-
BL-10C	Swivel open	Left Cheek		0.588	0.867	0.945

The measured Body SAR values for the test device are tabulated below:

800MHz Body SAR results

Battery used	Option used	Device orientation	Test configuration	SAR, averaged over 1g (W/kg)		
				Ch 1013 824.70MHz	Ch 384 836.52MHz	Ch 777 848.31MHz
RC3/S055			Power	24.42 dBm	24.42 dBm	24.31 dBm
BL-4C	Swivel closed	Display facing phantom	Without headset	-	0.354	-
			Headset HS-49	-	0.371	-
		Back facing phantom	Without headset	0.476	0.541	0.545
			Headset HS-49	-	0.386	-
BL-10C	Swivel closed	Back facing phantom	Without headset	0.280	0.286	0.323

1900MHz Body SAR results

Battery used	Option used	Device orientation	Test configuration	SAR, averaged over 1g (W/kg)		
				Ch 25 1851.25MHz	Ch 600 1880.00MHz	Ch1175 1908.75MHz
RC3/S055			Power	24.42 dBm	24.42 dBm	24.31 dBm
BL-4C	Swivel closed	Display facing phantom	Without headset	-	0.159	-
			Headset HS-49	-	0.156	-
		Back facing phantom	Without headset	0.193	0.229	0.183
			Headset HS-49	-	0.204	-
BL-10C	Swivel closed	Back facing phantom	Without headset	0.132	0.132	0.142

Plots of the Measurement scans are given in Appendix B.

APPENDIX A: SYSTEM CHECKING SCANS

Date/Time: 2009-03-11 9:44:44

Test Laboratory: TCC Nokia

Type: D835V2; Serial: 486

Communication System: CW835

Frequency: 835 MHz; Duty Cycle: 1:1

Medium: HSL850; Medium Notes: Liquid temperature= 22.1 C

Medium parameters used: $f = 835$ MHz; $\sigma = 0.911$ mho/m; $\epsilon_r = 41.4$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1516; Probe Notes:
- ConvF(6.26, 6.26, 6.26); Calibrated: 2008-10-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn860; Calibrated: 2008-06-12
- Phantom: SAM1; Type: Twin Phantom; Serial: TP-1035
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 172

System Check/Area Scan (61x61x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 2.53 mW/g

System Check/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 56.1 V/m


Peak SAR (extrapolated) = 3.11 W/kg

SAR(1 g) = 2.33 mW/g

SAR(10 g) = 1.56 mW/g

Power Drift = 0.000 dB

Maximum value of SAR (measured) = 2.52 mW/g



Date/Time: 2009-03-23 11:20:17

Test Laboratory: TCC Nokia

Type: D835V2; Serial: 486

Communication System: CW835

Frequency: 835 MHz; Duty Cycle: 1:1

Medium: HSL850; Medium Notes: Liquid temperature= 21.2 C

Medium parameters used: $f = 835$ MHz; $\sigma = 0.907$ mho/m; $\epsilon_r = 40.4$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1516; Probe Notes:
- ConvF(6.26, 6.26, 6.26); Calibrated: 2008-10-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn860; Calibrated: 2008-06-12
- Phantom: SAM1; Type: Twin Phantom; Serial: TP-1035
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

System Check/Area Scan (61x61x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 2.35 mW/g

System Check/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 54.3 V/m


Peak SAR (extrapolated) = 2.87 W/kg

SAR(1 g) = 2.17 mW/g

SAR(10 g) = 1.45 mW/g

Power Drift = 0.037 dB

Maximum value of SAR (measured) = 2.35 mW/g



Date/Time: 2009-03-16 13:44:45

Test Laboratory: TCC Nokia

Type: D1900V2; Serial: 509

Communication System: CW1900

Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: HSL1900; Medium Notes: Liquid temperature= 21.3 C

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.42$ mho/m; $\epsilon_r = 37.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1516; Probe Notes:
- ConvF(5.1, 5.1, 5.1); Calibrated: 2008-10-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn860; Calibrated: 2008-06-12
- Phantom: SAM2; Type: Twin Phantom; Serial: TP-1279
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 172

System Check/Area Scan (61x61x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 13.2 mW/g

System Check/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 97.5 V/m


Peak SAR (extrapolated) = 19.6 W/kg

SAR(1 g) = 10.7 mW/g

SAR(10 g) = 5.57 mW/g

Power Drift = -0.035 dB

Maximum value of SAR (measured) = 12.2 mW/g



Date/Time: 2009-03-17 11:00:26

Test Laboratory: TCC Nokia

Type: D1900V2; Serial: 509

Communication System: CW1900

Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: HSL1900; Medium Notes: Liquid temperature= 20.3 C

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.43$ mho/m; $\epsilon_r = 38$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1516; Probe Notes:
- ConvF(5.1, 5.1, 5.1); Calibrated: 2008-10-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn860; Calibrated: 2008-06-12
- Phantom: SAM2; Type: Twin Phantom; Serial: TP-1279
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 172

System Check/Area Scan (61x61x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 13.1 mW/g

System Check/Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 97.0 V/m


Peak SAR (extrapolated) = 19.6 W/kg

SAR(1 g) = 10.8 mW/g

SAR(10 g) = 5.6 mW/g

Power Drift = 0.015 dB

Maximum value of SAR (measured) = 12.2 mW/g



Date/Time: 2009-03-24 10:17:34

Test Laboratory: TCC Nokia

Type: D835V2; Serial: 486

Communication System: CW835

Frequency: 835 MHz; Duty Cycle: 1:1

Medium: MSL850; Medium Notes: Liquid temperature= 21.0

Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.982 \text{ mho/m}$; $\epsilon_r = 52$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1516; Probe Notes:
- ConvF(6.01, 6.01, 6.01); Calibrated: 2008-10-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn860; Calibrated: 2008-06-12
- Phantom: SAM2; Type: Twin Phantom; Serial: TP-1279
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 172

System Check/Area Scan (61x61x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 2.70 mW/g

System Check/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 54.6 V/m


Peak SAR (extrapolated) = 3.26 W/kg

SAR(1 g) = 2.4 mW/g

SAR(10 g) = 1.6 mW/g

Power Drift = -0.008 dB

Maximum value of SAR (measured) = 2.63 mW/g



Date/Time: 2009-03-17 9:33:49

Test Laboratory: TCC Nokia

Type: D1900V2; Serial: 509

Communication System: CW1900

Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: Body 1900MHz; Medium Notes: Temperature: 20.4 C

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.55$ mho/m; $\epsilon_r = 52.3$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1516; Probe Notes:
- ConvF(6.01, 6.01, 6.01); Calibrated: 2008-10-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn860; Calibrated: 2008-06-12
- Phantom: SAM2; Type: Twin Phantom; Serial: TP-1279
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 172

System Check/Area Scan (71x71x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 11.8 mW/g

System Check/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 90.1 V/m


Peak SAR (extrapolated) = 16.4 W/kg

SAR(1 g) = 9.64 mW/g

SAR(10 g) = 5.12 mW/g

Power Drift = -0.006 dB

Maximum value of SAR (measured) = 10.8 mW/g



APPENDIX B: MEASUREMENT SCANS

Date/Time: 2009-03-11 11:22:18

Test Laboratory: TCC Nokia

Type: RM-526; Serial: A00000016703A7

Communication System: CDMA800

Frequency: 848.31 MHz; Duty Cycle: 1:1

Medium: HSL850; Medium Notes: Liquid temperature= 22.1 C

Medium parameters used (interpolated): $f = 848.31$ MHz; $\sigma = 0.915$ mho/m; $\epsilon_r = 41.3$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1516; Probe Notes:
- ConvF(6.26, 6.26, 6.26); Calibrated: 2008-10-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn860; Calibrated: 2008-06-12
- Phantom: SAM1; Type: Twin Phantom; Serial: TP-1035
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 172

Cheek, High, Swivel open, BL-4C battery/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.925 mW/g

Cheek, High, Swivel open, BL-4C battery/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.1 V/m


Peak SAR (extrapolated) = 1.13 W/kg

SAR(1 g) = 0.901 mW/g

SAR(10 g) = 0.628 mW/g

Power Drift = 0.219 dB

Maximum value of SAR (measured) = 0.953 mW/g



SAR Report

SD_SAR_0913_01

Applicant: Nokia Corporation

Type: RM-526

Copyright © 2009 TCC Nokia

Date/Time: 2009-03-11 13:36:38

Test Laboratory: TCC Nokia

Type: RM-526; Serial: A00000016703A7

Communication System: CDMA800

Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: HSL850; Medium Notes: Liquid temperature= 22.1 C

Medium parameters used: $f = 837$ MHz; $\sigma = 0.912$ mho/m; $\epsilon_r = 41.4$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1516; Probe Notes:
- ConvF(6.26, 6.26, 6.26); Calibrated: 2008-10-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn860; Calibrated: 2008-06-12
- Phantom: SAM1; Type: Twin Phantom; Serial: TP-1035
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 172

Tilt, Middle, Swivel open, BL-4C battery/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.345 mW/g

Tilt, Middle, Swivel open, BL-4C battery/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 15.0 V/m


Peak SAR (extrapolated) = 0.352 W/kg

SAR(1 g) = 0.324 mW/g

SAR(10 g) = 0.254 mW/g

Power Drift = 0.062 dB

Maximum value of SAR (measured) = 0.339 mW/g



SAR Report

SD_SAR_0913_01

Applicant: Nokia Corporation

Type: RM-526

Copyright © 2009 TCC Nokia

Date/Time: 2009-03-11 15:30:46

Test Laboratory: The name of your organization

Type: RM-515; Serial: A00000016703A7

Communication System: CDMA800

Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: HSL850; Medium Notes: Liquid temperature= 22.1 C

Medium parameters used: $f = 837$ MHz; $\sigma = 0.912$ mho/m; $\epsilon_r = 41.4$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1516; Probe Notes:
- ConvF(6.26, 6.26, 6.26); Calibrated: 2008-10-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn860; Calibrated: 2008-06-12
- Phantom: SAM1; Type: SAM; Serial: TP-1035
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 172

Cheek, Middle, Swivel open, BL-4C battery/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.727 mW/g

Cheek, Middle, Swivel open, BL-4C battery/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.3 V/m


Peak SAR (extrapolated) = 0.794 W/kg

SAR(1 g) = 0.699 mW/g

SAR(10 g) = 0.518 mW/g

Power Drift = -0.143 dB

Maximum value of SAR (measured) = 0.738 mW/g



Date/Time: 2009-03-11 16:05:05

Test Laboratory: TCC Nokia

Type: RM-526; Serial: A00000016703A7

Communication System: CDMA800

Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: HSL850; Medium Notes: Liquid temperature= 22.1 C

Medium parameters used: $f = 837$ MHz; $\sigma = 0.912$ mho/m; $\epsilon_r = 41.4$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1516; Probe Notes:
- ConvF(6.26, 6.26, 6.26); Calibrated: 2008-10-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn860; Calibrated: 2008-06-12
- Phantom: SAM1; Type: Twin Phantom; Serial: TP-1035
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 172

Tilt, Middle, Swivel open, BL-4C battery/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.317 mW/g

Tilt, Middle, Swivel open, BL-4C battery/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 14.5 V/m


Peak SAR (extrapolated) = 0.336 W/kg

SAR(1 g) = 0.305 mW/g

SAR(10 g) = 0.241 mW/g

Power Drift = 0.056 dB

Maximum value of SAR (measured) = 0.320 mW/g



Date/Time: 2009-03-23 12:13:49

Test Laboratory: TCC Nokia

Type: RM-526; Serial: A00000016703A7

Communication System: CDMA800

Frequency: 848.31 MHz; Duty Cycle: 1:1

Medium: HSL850; Medium Notes: Liquid temperature= 21.2C

Medium parameters used (interpolated): $f = 848.31$ MHz; $\sigma = 0.917$ mho/m; $\epsilon_r = 40.3$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1516; Probe Notes:
- ConvF(6.26, 6.26, 6.26); Calibrated: 2008-10-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn860; Calibrated: 2008-06-12
- Phantom: SAM1; Type: Twin Phantom; Serial: TP-1035
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Cheek, High, Swivel open, BL-10C battery/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.681 mW/g

Cheek, High, Swivel open, BL-10C battery/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.10 V/m


Peak SAR (extrapolated) = 0.815 W/kg

SAR(1 g) = 0.646 mW/g

SAR(10 g) = 0.448 mW/g

Power Drift = -0.036 dB

Maximum value of SAR (measured) = 0.688 mW/g



Date/Time: 2009-03-16 14:23:35

Test Laboratory: TCC Nokia

Type: RM-526; Serial: A00000016703A7

Communication System: CDMA1900

Frequency: 1908.75 MHz; Duty Cycle: 1:1

Medium: HSL1900; Medium Notes: Liquid temperature= 21.3 C

Medium parameters used: $f = 1909$ MHz; $\sigma = 1.43$ mho/m; $\epsilon_r = 37.8$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1516; Probe Notes:
- ConvF(5.1, 5.1, 5.1); Calibrated: 2008-10-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn860; Calibrated: 2008-06-12
- Phantom: SAM2; Type: Twin Phantom; Serial: TP-1279
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 172

Cheek, High, Swivel open, BL-4C battery/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.14 mW/g

Cheek, High, Swivel open, BL-4C battery/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.2 V/m


Peak SAR (extrapolated) = 1.54 W/kg

SAR(1 g) = 1 mW/g

SAR(10 g) = 0.618 mW/g

Power Drift = -0.030 dB

Maximum value of SAR (measured) = 1.08 mW/g



SAR Report

SD_SAR_0913_01

Applicant: Nokia Corporation

Type: RM-526

Copyright © 2009 TCC Nokia

Date/Time: 2009-03-16 14:55:16

Test Laboratory: TCC Nokia

Type: RM-526; Serial: A00000016703A7

Communication System: CDMA1900

Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: HSL1900; Medium Notes: Liquid temperature= 21.3 C

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.41$ mho/m; $\epsilon_r = 38.2$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1516; Probe Notes:
- ConvF(5.1, 5.1, 5.1); Calibrated: 2008-10-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn860; Calibrated: 2008-06-12
- Phantom: SAM2; Type: Twin Phantom; Serial: TP-1279
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 172

Tilt, Middle, Swivel open, BL-4C battery/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.417 mW/g

Tilt, Middle, Swivel open, BL-4C battery/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 15.4 V/m


Peak SAR (extrapolated) = 0.489 W/kg

SAR(1 g) = 0.338 mW/g

SAR(10 g) = 0.215 mW/g

Power Drift = 0.028 dB

Maximum value of SAR (measured) = 0.360 mW/g



SAR Report

SD_SAR_0913_01

Applicant: Nokia Corporation

Type: RM-526

Copyright © 2009 TCC Nokia

Date/Time: 2009-03-16 16:09:21

Test Laboratory: TCC Nokia

Type: RM-526; Serial: A00000016703A7

Communication System: CDMA1900

Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: HSL1900; Medium Notes: Liquid temperature= 21.3 C

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.41$ mho/m; $\epsilon_r = 38.2$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1516; Probe Notes:
- ConvF(5.1, 5.1, 5.1); Calibrated: 2008-10-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn860; Calibrated: 2008-06-12
- Phantom: SAM2; Type: Twin Phantom; Serial: TP-1279
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 172

Cheek position, Middle, Swivel open, BL-4C battery/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.694 mW/g

Cheek position, Middle, Swivel open, BL-4C battery/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.7 V/m

Peak SAR (extrapolated) = 0.978 W/kg


SAR(1 g) = 0.653 mW/g

SAR(10 g) = 0.410 mW/g

Power Drift = 0.002 dB

Warning: Maximum averaged SAR over 10 g is located on the boundary of the measurement cube. This cube might not incorporate the absolute averaged SAR. Please consider a refinement of the Area Scan measurement.

Maximum value of SAR (measured) = 0.698 mW/g



Date/Time: 2009-03-16 15:45:44

Test Laboratory: TCC Nokia

Type: RM-526; Serial: A00000016703A7

Communication System: CDMA1900

Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: HSL1900; Medium Notes: Liquid temperature= 21.3 C

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.41$ mho/m; $\epsilon_r = 38.2$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1516; Probe Notes:
- ConvF(5.1, 5.1, 5.1); Calibrated: 2008-10-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn860; Calibrated: 2008-06-12
- Phantom: SAM2; Type: Twin Phantom; Serial: TP-1279
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 172

Tilt, Middle, Swivel open, BL-4C battery/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.396 mW/g

Tilt, Middle, Swivel open, BL-4C battery/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 16.5 V/m


Peak SAR (extrapolated) = 0.517 W/kg

SAR(1 g) = 0.350 mW/g

SAR(10 g) = 0.214 mW/g

Power Drift = 0.020 dB

Maximum value of SAR (measured) = 0.374 mW/g



Date/Time: 2009-03-17 12:57:47

Test Laboratory: TCC Nokia

Type: RM-526; Serial: A00000016703A7

Communication System: CDMA1900

Frequency: 1908.75 MHz; Duty Cycle: 1:1

Medium: HSL1900; Medium Notes: Liquid temperature= 20.3C

Medium parameters used: $f = 1909$ MHz; $\sigma = 1.43$ mho/m; $\epsilon_r = 37.9$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1516; Probe Notes:
- ConvF(5.1, 5.1, 5.1); Calibrated: 2008-10-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn860; Calibrated: 2008-06-12
- Phantom: SAM2; Type: Twin Phantom; Serial: TP-1279
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 172

Cheek, High, Swivel open, BL-10C battery/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.06 mW/g

Cheek, High, Swivel open, BL-10C battery/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.9 V/m

Peak SAR (extrapolated) = 1.45 W/kg

SAR(1 g) = 0.945 mW/g

SAR(10 g) = 0.582 mW/g

Power Drift = 0.068 dB

Maximum value of SAR (measured) = 1.02 mW/g

Cheek, High, Swivel open, BL-10C battery/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.9 V/m


Peak SAR (extrapolated) = 0.996 W/kg

SAR(1 g) = 0.607 mW/g

SAR(10 g) = 0.350 mW/g

Power Drift = 0.068 dB

Maximum value of SAR (measured) = 0.655 mW/g



Date/Time: 2009-03-24 12:32:02

Test Laboratory: TCC Nokia

Type: RM-526; Serial: A00000016703A7

Communication System: CDMA800

Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: HSL850; Medium Notes: Liquid temperature= 21.0C

Medium parameters used: $f = 837$ MHz; $\sigma = 0.984$ mho/m; $\epsilon_r = 52$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1516; Probe Notes:
- ConvF(6.01, 6.01, 6.01); Calibrated: 2008-10-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn860; Calibrated: 2008-06-12
- Phantom: SAM2; Type: Twin Phantom; Serial: TP-1279
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 172

Body, Middle, Swivel closed, No accessory, BL-4C battery, Display facing phantom/Area Scan (51x81x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.387 mW/g

Body, Middle, Swivel closed, No accessory, BL-4C battery, Display facing phantom/Zoom Scan (5x5x7)/Cube 0:

Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.8 V/m


Peak SAR (extrapolated) = 0.429 W/kg

SAR(1 g) = 0.354 mW/g

SAR(10 g) = 0.262 mW/g

Power Drift = -0.106 dB

Maximum value of SAR (measured) = 0.373 mW/g



Date/Time: 2009-03-24 12:20:33

Test Laboratory: TCC Nokia

Type: RM-526; Serial: A00000016703A7

Communication System: CDMA800

Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: HSL850; Medium Notes: Liquid temperature= 21.0C

Medium parameters used: $f = 837$ MHz; $\sigma = 0.984$ mho/m; $\epsilon_r = 52$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1516; Probe Notes:
- ConvF(6.01, 6.01, 6.01); Calibrated: 2008-10-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn860; Calibrated: 2008-06-12
- Phantom: SAM2; Type: Twin Phantom; Serial: TP-1279
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 172

Body, Middle, Swivel closed, HS-49, BL-4C battery, Display facing phantom/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.387 mW/g

Body, Middle, Swivel closed, HS-49, BL-4C battery, Display facing phantom/Zoom Scan (5x5x7)/Cube 0:

Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.3 V/m


Peak SAR (extrapolated) = 0.454 W/kg

SAR(1 g) = 0.371 mW/g

SAR(10 g) = 0.270 mW/g

Power Drift = 0.048 dB

Maximum value of SAR (measured) = 0.398 mW/g



Date/Time: 2009-03-24 13:43:03

Test Laboratory: TCC Nokia

Type: RM-526; Serial: A00000016703A7

Communication System: CDMA800

Frequency: 848.31 MHz; Duty Cycle: 1:1

Medium: HSL850; Medium Notes: Liquid temperature= 21.0C

Medium parameters used (interpolated): $f = 848.31$ MHz; $\sigma = 0.989$ mho/m; $\epsilon_r = 51.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1516; Probe Notes:
- ConvF(6.01, 6.01, 6.01); Calibrated: 2008-10-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn860; Calibrated: 2008-06-12
- Phantom: SAM2; Type: Twin Phantom; Serial: TP-1279
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 172

Body, High, Swivel closed, No accessory, BL-4C battery, Back facing phantom/Area Scan (51x81x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.567 mW/g

Body, High, Swivel closed, No accessory, BL-4C battery, Back facing phantom/Zoom Scan (6x6x7)/Cube 0:

Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 13.1 V/m


Peak SAR (extrapolated) = 0.686 W/kg

SAR(1 g) = 0.545 mW/g

SAR(10 g) = 0.388 mW/g

Power Drift = 0.044 dB

Maximum value of SAR (measured) = 0.575 mW/g



Date/Time: 2009-03-24 12:44:38

Test Laboratory: TCC Nokia

Type: RM-526; Serial: A00000016703A7

Communication System: CDMA800

Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: HSL850; Medium Notes: Liquid temperature= 21.0C

Medium parameters used: $f = 837$ MHz; $\sigma = 0.984$ mho/m; $\epsilon_r = 52$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1516; Probe Notes:
- ConvF(6.01, 6.01, 6.01); Calibrated: 2008-10-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn860; Calibrated: 2008-06-12
- Phantom: SAM2; Type: Twin Phantom; Serial: TP-1279
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 172

Body, Middle, Swivel closed, HS-49, BL-4C battery, Back facing phantom/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.413 mW/g

Body, Middle, Swivel closed, HS-49, BL-4C battery, Back facing phantom/Zoom Scan (5x5x7)/Cube 0:

Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.5 V/m

Peak SAR (extrapolated) = 0.489 W/kg


SAR(1 g) = 0.386 mW/g

SAR(10 g) = 0.275 mW/g

Power Drift = 0.068 dB

Warning: Maximum averaged SAR over 10 g is located on the boundary of the measurement cube. This cube might not incorporate the absolute averaged SAR. Please consider a refinement of the Area Scan measurement.

Maximum value of SAR (measured) = 0.409 mW/g



Date/Time: 2009-03-24 14:03:15

Test Laboratory: TCC Nokia

Type: RM-526; Serial: A00000016703A7

Communication System: CDMA800

Frequency: 848.31 MHz; Duty Cycle: 1:1

Medium: HSL850; Medium Notes: Liquid temperature= 21.0C

Medium parameters used (interpolated): $f = 848.31$ MHz; $\sigma = 0.989$ mho/m; $\epsilon_r = 51.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1516; Probe Notes:
- ConvF(6.01, 6.01, 6.01); Calibrated: 2008-10-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn860; Calibrated: 2008-06-12
- Phantom: SAM2; Type: Twin Phantom; Serial: TP-1279
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 172

Body, High, Swivel closed, No accessory, BL-10C battery, Back facing phantom/Area Scan (51x81x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.337 mW/g

Body, High, Swivel closed, No accessory, BL-10C battery, Back facing phantom/Zoom Scan (6x6x7)/Cube 0:

Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.3 V/m


Peak SAR (extrapolated) = 0.398 W/kg

SAR(1 g) = 0.323 mW/g

SAR(10 g) = 0.232 mW/g

Power Drift = -0.119 dB

Maximum value of SAR (measured) = 0.346 mW/g



Date/Time: 2009-03-17 14:56:11

Test Laboratory: TCC Nokia

Type: RM-526; Serial: A00000016703A7

Communication System: CDMA1900

Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: Body 1900MHz; Medium Notes: Temperature: 20.4 C

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.54$ mho/m; $\epsilon_r = 52.5$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1516; Probe Notes:
- ConvF(4.76, 4.76, 4.76); Calibrated: 2008-10-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn860; Calibrated: 2008-06-12
- Phantom: SAM1; Type: Twin Phantom; Serial: TP-1035
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Body, Middle, Swivel closed, No accessory, BL-4C battery, Display facing phantom/Area Scan (51x81x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.172 mW/g

Body, Middle, Swivel closed, No accessory, BL4C battery, Display facing phantom/Zoom Scan (5x5x7)/Cube 0:

Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.27 V/m


Peak SAR (extrapolated) = 0.247 W/kg

SAR(1 g) = 0.159 mW/g

SAR(10 g) = 0.102 mW/g

Power Drift = 0.042 dB

Maximum value of SAR (measured) = 0.172 mW/g



Date/Time: 2009-03-17 14:45:04

Test Laboratory: TCC Nokia

Type: RM-526; Serial: A00000016703A7

Communication System: CDMA1900

Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: Body 1900MHz; Medium Notes: Temperature: 20.4 C

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.54$ mho/m; $\epsilon_r = 52.5$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1516; Probe Notes:
- ConvF(4.76, 4.76, 4.76); Calibrated: 2008-10-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn860; Calibrated: 2008-06-12
- Phantom: SAM1; Type: Twin Phantom; Serial: TP-1035
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Body, Middle, Swivel closed, HS-49, BL-4C battery, Display facing phantom/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.172 mW/g

Body, Middle, Swivel closed, HS-49, BL-4C battery, Display facing phantom/Zoom Scan (5x5x7)/Cube 0:

Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.30 V/m


Peak SAR (extrapolated) = 0.245 W/kg

SAR(1 g) = 0.156 mW/g

SAR(10 g) = 0.100 mW/g

Power Drift = -0.156 dB

Maximum value of SAR (measured) = 0.167 mW/g



Date/Time: 2009-03-17 14:06:42

Test Laboratory: TCC Nokia

Type: RM-526; Serial: A00000016703A7

Communication System: CDMA1900

Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: Body 1900MHz; Medium Notes: Temperature: 20.4 C

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.54$ mho/m; $\epsilon_r = 52.5$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1516; Probe Notes:
- ConvF(4.76, 4.76, 4.76); Calibrated: 2008-10-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn860; Calibrated: 2008-06-12
- Phantom: SAM1; Type: Twin Phantom; Serial: TP-1035
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Body, Middle, Swivel closed, No accessory, BL-4C battery, Back facing phantom/Area Scan (51x81x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.254 mW/g

Body, Middle, Swivel closed, No accessory, BL-4C battery, Back facing phantom/Zoom Scan (5x5x7)/Cube 0:

Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.21 V/m


Peak SAR (extrapolated) = 0.343 W/kg

SAR(1 g) = 0.229 mW/g

SAR(10 g) = 0.151 mW/g

Power Drift = -0.035 dB

Maximum value of SAR (measured) = 0.243 mW/g



SAR Report

SD_SAR_0913_01

Applicant: Nokia Corporation

Type: RM-526

Copyright © 2009 TCC Nokia

Date/Time: 2009-03-17 14:23:32

Test Laboratory: TCC Nokia

Type: RM-526; Serial: A00000016703A7

Communication System: CDMA1900

Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: Body 1900MHz; Medium Notes: Temperature: 20.4 C

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.54$ mho/m; $\epsilon_r = 52.5$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1516; Probe Notes:
- ConvF(4.76, 4.76, 4.76); Calibrated: 2008-10-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn860; Calibrated: 2008-06-12
- Phantom: SAM1; Type: Twin Phantom; Serial: TP-1035
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Body, Middle, Swivel closed, HS-49, BL-4C battery, Back facing phantom/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.228 mW/g

Body, Middle, Swivel closed, HS-49, BL-4C battery, Back facing phantom/Zoom Scan (5x5x7)/Cube 0:

Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.82 V/m


Peak SAR (extrapolated) = 0.313 W/kg

SAR(1 g) = 0.204 mW/g

SAR(10 g) = 0.134 mW/g

Power Drift = -0.006 dB

Maximum value of SAR (measured) = 0.214 mW/g



Date/Time: 2009-03-17 16:45:50

Test Laboratory: TCC Nokia

Type: RM-526; Serial: A00000016703A7

Communication System: CDMA1900

Frequency: 1908.75 MHz; Duty Cycle: 1:1

Medium: Body 1900MHz; Medium Notes: Temperature: 20.4 C

Medium parameters used: $f = 1909$ MHz; $\sigma = 1.56$ mho/m; $\epsilon_r = 52.2$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1516; Probe Notes:
- ConvF(4.76, 4.76, 4.76); Calibrated: 2008-10-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn860; Calibrated: 2008-06-12
- Phantom: SAM1; Type: Twin Phantom; Serial: TP-1035
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Body, High, Swivel closed, No accessory, BL-10C battery, Display facing phantom/Area Scan (51x81x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.151 mW/g

Body, High, Swivel closed, No accessory, BL-10C battery, Display facing phantom/Zoom Scan (6x6x7)/Cube 0:

Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.10 V/m


Peak SAR (extrapolated) = 0.225 W/kg

SAR(1 g) = 0.142 mW/g

SAR(10 g) = 0.091 mW/g

Power Drift = -0.140 dB

Maximum value of SAR (measured) = 0.148 mW/g



APPENDIX C: CONDUCTED POWER MEASUREMENTS FOR SUPPORTED TRANSMISSION MODES

TYPE: RM-526; SERIAL NUMBER: A00000016703A7

CDMA800

Radio Configuration	Service Options and Channel Configurations	Supported	Ch 1013 824.70MHz	Ch 384 836.52MHz	Ch 777 848.31MHz
			Pavg dBm	Pavg dBm	Pavg dBm
RC1	S01	No	-	-	-
RC1	S02	Yes	24.51	24.51	24.32
RC1	S03	No	-	-	-
RC1	S055	Yes	24.42	24.51	24.34
RC2	S09	Yes	24.41	24.52	24.42
RC2	S017	No	-	-	-
RC2	S055	Yes	24.52	24.50	24.42
RC3	S01	No	-	-	-
RC3	S02	Yes	24.41	24.52	24.31
RC3	S03	No	-	-	-
RC3	S032 (no SCH1)	Yes	24.52	24.41	24.33
RC3	S032 (SCH1 9.6kbps)	No	-	-	-
RC3	S032 (SCH1 19.2kbps)	No	-	-	-
RC3	S032 (SCH1 38.4kbps)	No	-	-	-
RC3	S032 (SCH1 76.8kbps)	No	-	-	-
RC3	S032 (SCH1 153.6kbps)	No	-	-	-
RC3	S033 (SCH1 9.6kbps)	No	-	-	-
RC3	S033 (SCH1 19.2kbps)	No	-	-	-
RC3	S033 (SCH1 38.4kbps)	No	-	-	-
RC3	S033 (SCH1 76.8kbps)	No	-	-	-
RC3	S033 (SCH1 153.6kbps)	No	-	-	-
RC3	S055	Yes	24.42	24.42	24.31
RC4	S01	No	-	-	-
RC4	S02	Yes	24.32	24.50	24.33
RC4	S03	No	-	-	-
RC4	S032 (no SCH1)	Yes	24.40	24.42	24.33
RC4	S032 (SCH1 9.6kbps)	No	-	-	-
RC4	S032 (SCH1 19.2kbps)	No	-	-	-
RC4	S032 (SCH1 38.4kbps)	No	-	-	-
RC4	S032 (SCH1 76.8kbps)	No	-	-	-
RC4	S032 (SCH1 153.6kbps)	No	-	-	-
RC4	S033 (SCH1 9.6kbps)	No	-	-	-
RC4	S033 (SCH1 19.2kbps)	No	-	-	-
RC4	S033 (SCH1 38.4kbps)	No	-	-	-
RC4	S033 (SCH1 76.8kbps)	No	-	-	-
RC4	S033 (SCH1 153.6kbps)	No	-	-	-
RC4	S055	Yes	24.40	24.42	24.33

RC5	S09	Yes	24.41	24.52	24.42
RC5	S017	No	-	-	-
RC5	S033 (SCH1 9.6kbps)	No	-	-	-
RC5	S033 (SCH1 19.2kbps)	No	-	-	-
RC5	S033 (SCH1 38.4kbps)	No	-	-	-
RC5	S033 (SCH1 76.8kbps)	No	-	-	-
RC5	S033 (SCH1 153.6kbps)	No	-	-	-
RC5	S055	Yes	24.40	24.52	24.32

Application Configuration	Data Rate (kbps)	Supported	Ch 1013 824.70MHz	Ch 384 836.52MHz	Ch 777 848.31MHz
			Pavg dBm	Pavg dBm	Pavg dBm
RTAP	9.6	Yes	24.42	24.51	24.32
RTAP	19.2	Yes	24.51	24.62	24.22
RTAP	38.4	Yes	24.42	24.60	24.20
RTAP	76.8	Yes	24.43	24.62	24.33
RTAP	153.6	Yes	24.41	24.50	24.32

Note: FTAP set to 2-slots at 307kbps

CDMA1900

Radio Configuration	Service Options and Channel Configurations	Supported	Ch 25 1851.25MHz	Ch 600 1880.00MHz	Ch1175 1908.75MHz
			Pavg dBm	Pavg dBm	Pavg dBm
RC1	S01	No	-	-	-
RC1	S02	Yes	24.32	24.33	24.31
RC1	S03	No	-	-	-
RC1	S055	Yes	24.21	24.50	24.22
RC2	S09	Yes	24.42	24.43	24.33
RC2	S017	No	-	-	-
RC2	S055	Yes	24.41	24.51	24.33
RC3	S01	No	-	-	-
RC3	S02	Yes	24.32	24.52	24.22
RC3	S03	No	-	-	-
RC3	S032 (no SCH1)	Yes	24.22	24.14	24.22
RC3	S032 (SCH1 9.6kbps)	No	-	-	-
RC3	S032 (SCH1 19.2kbps)	No	-	-	-
RC3	S032 (SCH1 38.4kbps)	No	-	-	-
RC3	S032 (SCH1 76.8kbps)	No	-	-	-
RC3	S032 (SCH1 153.6kbps)	No	-	-	-
RC3	S033 (SCH1 9.6kbps)	No	-	-	-
RC3	S033 (SCH1 19.2kbps)	No	-	-	-
RC3	S033 (SCH1 38.4kbps)	No	-	-	-
RC3	S033 (SCH1 76.8kbps)	No	-	-	-
RC3	S033 (SCH1 153.6kbps)	No	-	-	-
RC3	S055	Yes	24.32	24.51	24.32
RC4	S01	No	-	-	-
RC4	S02	Yes	24.32	24.50	24.13
RC4	S03	No	-	-	-
RC4	S032 (no SCH1)	Yes	24.41	24.14	24.22
RC4	S032 (SCH1 9.6kbps)	No	-	-	-
RC4	S032 (SCH1 19.2kbps)	No	-	-	-
RC4	S032 (SCH1 38.4kbps)	No	-	-	-
RC4	S032 (SCH1 76.8kbps)	No	-	-	-
RC4	S032 (SCH1 153.6kbps)	No	-	-	-
RC4	S033 (SCH1 9.6kbps)	No	-	-	-
RC4	S033 (SCH1 19.2kbps)	No	-	-	-
RC4	S033 (SCH1 38.4kbps)	No	-	-	-
RC4	S033 (SCH1 76.8kbps)	No	-	-	-
RC4	S033 (SCH1 153.6kbps)	No	-	-	-
RC4	S055	Yes	24.20	24.42	24.14
RC5	S09	Yes	24.21	24.40	24.22
RC5	S017	No	-	-	-
RC5	S033 (SCH1 9.6kbps)	No	-	-	-
RC5	S033 (SCH1 19.2kbps)	No	-	-	-

RC5	S033 (SCH1 38.4kbps)	No	-	-	-
RC5	S033 (SCH1 76.8kbps)	No	-	-	-
RC5	S033 (SCH1 153.6kbps)	No	-	-	-
RC5	S055	Yes	24.22	24.32	24.21

Application Configuration	Data Rate (kbps)	Supported	Ch 25 1851.25MHz	Ch 600 1880.00MHz	Ch1175 1908.75MHz
			Pavg dBm	Pavg dBm	Pavg dBm
RTAP	9.6	Yes	24.32	24.43	24.14
RTAP	19.2	Yes	24.31	24.52	24.20
RTAP	38.4	Yes	24.30	24.50	24.22
RTAP	76.8	Yes	24.31	24.52	24.30
RTAP	153.6	Yes	24.30	24.50	24.24

Note: FTAP set to 2-slots at 307kbps

APPENDIX D: CONDUCTED POWER SETUP FOR TESTING

800MHz Band:

Target Power	
1 x RTT	Ev-Do
24.2 dBm	24.2 dBm

1900MHz Band:

Target Power	
1 x RTT	Ev-Do
24.2 dBm	24.2 dBm

APPENDIX E: RELEVANT PAGES FROM PROBE CALIBRATION REPORT(S)

**Calibration Laboratory of
Schmid & Partner
Engineering AG**
 Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
 The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **Nokia SD TCC**

Certificate No: **ET3-1516_Oct08**

CALIBRATION CERTIFICATE

Object **ET3DV6 - SN:1516**

Calibration procedure(s) **QA CAL-01.v6 and QA CAL-23.v3
 Calibration procedure for dosimetric E-field probes**

Calibration date: **October 21, 2008**

Condition of the calibrated item **In Tolerance**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^{\circ}\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	1-Apr-08 (No. 217-00788)	Apr-09
Power sensor E4412A	MY41495277	1-Apr-08 (No. 217-00788)	Apr-09
Power sensor E4412A	MY41498087	1-Apr-08 (No. 217-00788)	Apr-09
Reference 3 dB Attenuator	SN: S5054 (3c)	1-Jul-08 (No. 217-00865)	Jul-09
Reference 20 dB Attenuator	SN: S5086 (20b)	31-Mar-08 (No. 217-00787)	Apr-09
Reference 30 dB Attenuator	SN: S5129 (30b)	1-Jul-08 (No. 217-00866)	Jul-09
Reference Probe ES3DV2	SN: 3013	2-Jan-08 (No. ES3-3013_Jan08)	Jan-09
DAE4	SN: 660	9-Sep-08 (No. DAE4-660_Sep08)	Sep-09

Secondary Standards	ID #	Check Date (in house)	Scheduled Check
RF generator HP 8648C	US3642U01700	4-Aug-99 (in house check Oct-07)	In house check: Oct-09
Network Analyzer HP 8753E	US37390585	18-Oct-01 (in house check Oct-07)	In house check: Oct-08

	Name	Function	Signature
Calibrated by:	Marcel Fehr	Laboratory Technician	
Approved by:	Katja Pokovic	Technical Manager	

Issued: October 21, 2008

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: ET3-1516_Oct08



Page 1 of 9

SAR Report
 SD_SAR_0913_01
 Applicant: Nokia Corporation

Type: RM-526

Copyright © 2009 TCC Nokia

Conversion Factor Assessment



f [MHz]	Validity [MHz] ^c	TSL	Permittivity	Conductivity	Alpha	Depth	ConvF Uncertainty
900	± 50 / ± 100	Head	41.5 ± 5%	0.97 ± 5%	0.39	3.35	6.26 ± 11.0% (k=2)
1810	± 50 / ± 100	Head	40.0 ± 5%	1.40 ± 5%	0.55	2.34	5.10 ± 11.0% (k=2)
1950	± 50 / ± 100	Head	40.0 ± 5%	1.40 ± 5%	0.58	2.29	4.81 ± 11.0% (k=2)
2450	± 50 / ± 100	Head	39.2 ± 5%	1.80 ± 5%	0.90	1.80	4.29 ± 11.0% (k=2)
900	± 50 / ± 100	Body	55.0 ± 5%	1.05 ± 5%	0.63	2.67	6.01 ± 11.0% (k=2)
1810	± 50 / ± 100	Body	53.3 ± 5%	1.52 ± 5%	0.65	2.23	4.76 ± 11.0% (k=2)
1950	± 50 / ± 100	Body	53.3 ± 5%	1.52 ± 5%	0.65	2.24	4.66 ± 11.0% (k=2)
2450	± 50 / ± 100	Body	52.7 ± 5%	1.95 ± 5%	0.99	1.80	3.83 ± 11.0% (k=2)

^c The validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2). The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

APPENDIX F: RELEVANT PAGES FROM DIPOLE VALIDATION KIT REPORT(S)

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **Nokia SD TCC**

Certificate No: **D835V2-486_Oct08**

CALIBRATION CERTIFICATE

Object **D835V2 - SN: 486**

Calibration procedure(s) **QA CAL-05.v7**
Calibration procedure for dipole validation kits

Calibration date: **October 22, 2008**


Condition of the calibrated item **In Tolerance**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^{\circ}\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter EPM-442A	GB37480704	08-Oct-08 (No. 217-00898)	Oct-09
Power sensor HP 8481A	US37292783	08-Oct-08 (No. 217-00898)	Oct-09
Reference 20 dB Attenuator	SN: 5086 (20g)	01-Jul-08 (No. 217-00864)	Jul-09
Type-N mismatch combination	SN: 5047.2 / 06327	01-Jul-08 (No. 217-00867)	Jul-09
Reference Probe ES3DV2	SN: 3025	28-Apr-08 (No. ES3-3025_Apr08)	Apr-09
DAE4	SN: 601	14-Mar-08 (No. DAE4-601_Mar08)	Mar-09
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power sensor HP 8481A	MY41092317	18-Oct-02 (in house check Oct-07)	In house check: Oct-09
RF generator R&S SMT-06	100005	4-Aug-99 (in house check Oct-07)	In house check: Oct-09
Network Analyzer HP 8753E	US37390585 S4206	18-Oct-01 (in house check Oct-07)	In house check: Oct-08

	Name	Function	Signature
Calibrated by:	Jeton Kastrati	Laboratory Technician	
Approved by:	Katja Pokovic	Technical Manager	

Issued: October 22, 2008

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

DASY5 Validation Report for Head TSL

Date/Time: 22.10.2008 11:34:32

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN:486

Communication System: CW-835; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: HSL 900 MHz

Medium parameters used: $f = 835$ MHz; $\sigma = 0.9$ mho/m; $\epsilon_r = 40.5$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC)

DASY5 Configuration:

- Probe: ES3DV2 - SN3025; ConvF(5.97, 5.97, 5.97); Calibrated: 28.04.2008
- Sensor-Surface: 3.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 14.03.2008
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001
- Measurement SW: DASY5, V5.0 Build 120; SEMCAD X Version 13.4 Build 45


Pin=250mW; dip=15mm; dist=3.4mm/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 55.9 V/m; Power Drift = 0.020 dB

Peak SAR (extrapolated) = 3.52 W/kg

SAR(1 g) = 2.39 mW/g; SAR(10 g) = 1.57 mW/g

Maximum value of SAR (measured) = 2.7 mW/g



DASY5 Validation Report for Body TSL

Date/Time: 20.10.2008 10:14:40

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN:486

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: MSL900

Medium parameters used: $f = 835$ MHz; $\sigma = 1$ mho/m; $\epsilon_r = 53.4$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC)

DASY5 Configuration:

- Probe: ES3DV2 - SN3025; ConvF(5.9, 5.9, 5.9); Calibrated: 28.04.2008
- Sensor-Surface: 3.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 14.03.2008
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001
- Measurement SW: DASY5, V5.0 Build 120; SEMCAD X Version 13.4 Build 45


Pin = 250mW, d = 15mm/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 53.5 V/m; Power Drift = 0.015 dB

Peak SAR (extrapolated) = 3.51 W/kg

SAR(1 g) = 2.42 mW/g; SAR(10 g) = 1.6 mW/g

Maximum value of SAR (measured) = 2.74 mW/g



**Calibration Laboratory of
Schmid & Partner
Engineering AG**
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **Nokia SD TCC**

Certificate No: **D1900V2-509 Jun08**

CALIBRATION CERTIFICATE

Object **D1900V2 - SN: 509**

Calibration procedure(s) **QA CAL-05.v7
Calibration procedure for dipole validation kits**

Calibration date: **June 19, 2008**

Condition of the calibrated item **In Tolerance**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^{\circ}\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Calibrated by, Certificate No.)	Scheduled Calibration
Power meter EPM-442A	GB37480704	04-Oct-07 (No. 217-00736)	Oct-08
Power sensor HP 8461A	US37292783	04-Oct-07 (No. 217-00736)	Oct-08
Reference 20 dB Attenuator	SN: 5086 (20g)	07-Aug-07 (No. 217-00718)	Aug-08
Type-N mismatch combination	SN: 5047.2 / 06327	08-Aug-07 (No. 217-00721)	Aug-08
Reference Probe ES3DV2	SN: 3025	28-Apr-08 (No. ES3-3025_Apr08)	Apr-09
DAE4	SN: 601	14-Mar-08 (No. DAE4-601_Mar08)	Mar-09

Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power sensor HP 8461A	MY41092317	18-Oct-02 (in house check Oct-07)	In house check: Oct-08
RF generator R&S SMT-06	100005	4-Aug-98 (in house check Oct-07)	In house check: Oct-09
Network Analyzer HP 8753E	US37390585 S4206	18-Oct-01 (in house check Oct-07)	In house check: Oct-08

	Name	Function	Signature
Calibrated by:	Claudio Leubler	Laboratory Technician	

	Name	Function
Approved by:	Kajsa Pokovic	Technical Manager

Issued: June 23, 2008

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

DASY4 Validation Report for Head TSL

Date/Time: 18.06.2008 14:57:06

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN:509

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: HSL U10 BB;

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.48$ mho/m; $\epsilon_r = 39.1$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY4 (High Precision Assessment)

DASY4 Configuration:

- Probe: ES3DV2 - SN3025; ConvF(4.9, 4.9, 4.9); Calibrated: 28.04.2008
- Sensor-Surface: 3.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 14.03.2008
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; ;
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Pin = 250 mW; d = 10 mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 87.2 V/m; Power Drift = 0.060 dB

Peak SAR (extrapolated) = 18.5 W/kg

SAR(1 g) = 9.96 mW/g; SAR(10 g) = 5.12 mW/g

Maximum value of SAR (measured) = 12.0 mW/g



0 dB = 12.0mW/g

DASY4 Validation Report for Body TSL

Date/Time: 19.06.2008 15:04:52

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN:509

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: MSL U10 BB;

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.58$ mho/m; $\epsilon_r = 52.4$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY4 (High Precision Assessment)

DASY4 Configuration:

- Probe: ES3DV2 - SN3025; ConvF(4.5, 4.5, 4.5); Calibrated: 28.04.2008
- Sensor-Surface: 3.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 14.03.2008
- Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; ;
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 184

Pin = 250 mW; d = 10 mm/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 88.6 V/m; Power Drift = 0.001 dB

Peak SAR (extrapolated) = 17.3 W/kg

SAR(1 g) = 9.77 mW/g; SAR(10 g) = 5.11 mW/g

Maximum value of SAR (measured) = 11.6 mW/g

