

American Telecommunications Certification Body Inc.

6731 Whittier Ave, McLean, VA 22101

May 12, 2005

RE: FCC ID: QMNRM-61_ATCB002397 Attention: Louis Le / Nerina Walton

I have a few comments on this Application. Please note that further comments may arise in response to answers provided to the questions below.

- 1. Please note that the report gives no information on how ERP measurements were performed. Please provide the test method you used to measure ERP for the device.
- 2. Please note that the lowest resolution bandwidth that should be used when measuring occupied bandwidth is 1% of the 26dB bandwidth. Please note that the AMPS bandwidths as listed on the 731 is 40kHz. This means that the lowest res bandwidth should be is 400Hz. If 400Hz is not an available res bandwidth on the analyzer, then the next higher resolution bandwidth should be used. Please explain why a lower than 1% resolution bandwidth was used.

Dennis Ward

mailto:dward@AmericanTCB.com

Dennis Ward

The items indicated above must be submitted before processing can continue on the above referenced application. Failure to provide the requested information may result in application termination. Correspondence should be considered part of the permanent submission and may be viewed from the Internet after a Grant of Equipment Authorization is issued.

Please do not respond to this correspondence using the email reply button. In order for your response to be processed expeditiously, you must submit your documents through the AmericanTCB.com website. Also, please note that partial responses increase processing time and should not be submitted.

Any questions about the content of this correspondence should be directed to the sender.