

FCC Part 22/24/27 Compliance Test Report

Test Report no.:	FCC22&24&27_RM-878_27.docx	Date of Report:	30-Nov-2012
Number of pages:	9	Customer's Contact person:	Jerry Williams
Testing laboratory:	TCC Nokia San Diego Laboratory 16620 West Bernardo Drive San Diego, CA 92127 USA Tel. +1 858 831 5000 Fax. +1 858 831 6500	Customer:	Nokia, Inc. 16620 West Bernardo Drive San Diego, CA 92127 USA Tel. +1 858 831 5000 Fax. +1 858 385 1598
FCC listing no.:	586140		
IC recognition no.:	10162A-1		
Tested devices/ accessories:	Lumia 810 RM-878 / Battery BP-4W / WC Cover - / Charger AC-301U / Charging Pad DT-900		
FCC ID:	QMNRM-878	IC:	661X-RM878
Supplement reports:	-		
Testing has been carried out in accordance with:	CFR 47, FCC rules Parts 22/24/27 , TIA-603-C-2004 and IC standards, RSS-GEN (Issue 3, December 2010), RSS-132 (Issue 2, September 2005), RSS-133 (Issue 5, February 2009), RSS-139 (Issue 2, February 2009). Deviations, modifications or clarifications (if any) to above mentioned documents are written in each section under "Test method and limit".		
Documentation:	The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 15 years at TCC Nokia.		
Test Results:	The EUT complies with the requirements in respect of all parameters subject to the test. The test results relate only to devices specified in this document		
Date and signature for the contents:			

Feng You, Senior Specialist

1. Summary for FCC Part 22/24/27 Compliance Test Report

Date of receipt	23-Aug-2012
Testing completed	30-Nov-2012
The customer's contact person	Jerry Williams
Test Plan referred to	T:\Projects\RM-878\TestPlan\RS_testplan_RM-878_EMC_FCC_SAR.xlsm
Notes	-
Document name	T:\Projects\RM-878\EMC\FCC22&24&27_RM-878_27.docx

1.1. EUT and Accessory Information

The EUT is a mobile phone with following features:
GSM/WCDMA/WLAN/Bluetooth
The EUT is tested with maximum rated TX power.

Devices under tests

Product	Type	SN	HW	MV	SW	DUT
Lumia 810	RM-878	004402471182935	0205	-	1532.2105.9200.9903.12	30631
Battery	BP-4W	3932132274140101601;0670672	-	-	-	30588
WC Cover	-	-	-	-	-	30625
Charger	AC-301U	4090492255020200783; 0675641	NA	NA	NA	30639
Charging Pad	DT-900	067709123351TW00459	NA	NA	NA	30641

1.2. Summary of Test Results

GSM850:

Section in CFR 47	Section in RSS-GEN or RSS-132	Name of the test	Result
§2.1046(a), 22.913(a)	4.4	Conducted RF output power	NP
§22.913(a)	4.4	Radiated RF output power	NP
§2.1049(h)	4.6.1	99 % occupied bandwidth	NP
§22.917(a)	4.5	Band edge compliance	NP
§22.917(a), §2.1051	4.5	Spurious emissions at antenna terminals	NP
§22.917(a), §2.1053	4.5	Spurious radiated emissions	NP
§2.1055(a)	4.3	Frequency stability, temperature variation	NP
§2.1055(d)	4.3	Frequency stability, voltage variation	NP

WCDMA 850 (Band V):

Section in CFR 47	Section in RSS-GEN or RSS-132	Name of the test	Result
§2.1046(a), 22.913(a)	4.4	Conducted RF output power	NP
§22.913(a)	4.4	Radiated RF output power	NP
§2.1049(h)	4.6.1	99 % occupied bandwidth	NP
§22.917(a)	4.5	Band edge compliance	NP
§22.917(a), §2.1051	4.5	Spurious emissions at antenna terminals	NP
§22.917(a), §2.1053	4.5	Spurious radiated emissions	NP
§2.1055(a)	4.3	Frequency stability, temperature variation	NP
§2.1055(d)	4.3	Frequency stability, voltage variation	NP

GSM1900:

Section in CFR 47	Section in RSS-GEN or RSS-133	Name of the test	Result
§2.1046(a)	6.4	Conducted RF output power	NP
§24.232(b)	6.4	Radiated RF output power	NP

§2.1049(h)	4.6.1	99 % occupied bandwidth	NP
§24.238(a)	6.5	Band edge compliance	NP
§24.238(a), §2.1051	6.5	Spurious emissions at antenna terminals	NP
§24.238(a), §2.1053	6.5	Spurious radiated emissions	NP
§2.1055(a)	6.3	Frequency stability, temperature variation	NP
§2.1055(d)	6.3	Frequency stability, voltage variation	NP

WCDMA 1900 (Band II):

Section in CFR 47	Section in RSS-GEN or RSS-133	Name of the test	Result
§2.1046(a)	6.4	Conducted RF output power	NP
§24.232(b)	6.4	Radiated RF output power	NP
§2.1049(h)	4.6.1	99 % occupied bandwidth	NP
§24.238(a)	6.5	Band edge compliance	NP
§24.238(a), §2.1051	6.5	Spurious emissions at antenna terminals	NP
§24.238(a), §2.1053	6.5	Spurious radiated emissions	NP
§2.1055(a)	6.3	Frequency stability, temperature variation	NP
§2.1055(d)	6.3	Frequency stability, voltage variation	NP

WCDMA 1700 (Band IV):

Section in CFR 47	Section in RSS-GEN or RSS-139	Name of the test	Result
§2.1046(a)	6.4	Conducted RF output power	NP
§27.50(d)(2)	6.4	Radiated RF output power	NP
§2.1049(h)	4.6.1	99 % occupied bandwidth	NP
§27.53(g)	6.5	Band edge compliance	NP
§27.53(g), §2.1051	6.5	Spurious emissions at antenna terminals	NP
§24.238(a), §2.1053	6.5	Spurious radiated emissions	NP
§2.1055(a)	6.3	Frequency stability, temperature variation	NP
§2.1055(d)	6.3	Frequency stability, voltage variation	NP

LTE1700 (Band 4):

Section in CFR 47	Section in RSS-GEN or RSS-139	Name of the test	Result
§2.1046(a)	6.4	Conducted RF output power	NP
§27.50(d)(4)	6.4	Radiated RF output power	NP
§2.1049(h)	4.6.1	99 % occupied bandwidth	NP
§27.53(h)	6.5	Band edge compliance	NP
§27.53(h), §2.1051	6.5	Spurious emissions at antenna terminals	NP
§27.53(h), §2.1053	6.5	Spurious radiated emissions	PASSED
§2.1055(a)	6.3	Frequency stability, temperature variation	NP
§2.1055(d)	6.3	Frequency stability, voltage variation	NP

PASSED
FAILED
NP

The EUT complies with the essential requirements in the standard.
The EUT does not comply with the essential requirements in the standard.
The test was not performed by the TCC Nokia Laboratory.

CONTENTS


1. Summary for FCC Part 22/24/27 Compliance Test Report	2
1.1. EUT and Accessory Information.....	2
1.2. Summary of Test Results.....	2
2. Spurious radiated emissions (FCC §22.917(a), §2.1053, §24.238(a), §2.1053, §27.53(g), §2.1053, §27.53(h), RSS- 132 4.5, RSS-133 6.5).....	5
2.2. Test method and limit.....	5
2.3. LTE 1700 (Band IV) test results	7
3. Test Equipment.....	8
3.1. Conducted measurements	8
3.2. Radiated measurements	8

2. Spurious radiated emissions

(FCC §22.917(a), §2.1053, §24.238(a), §2.1053, §27.53(g), §2.1053, §27.53(h), RSS-132 4.5, RSS-133 6.5)

EUT with DUT number	RM-878, DUT 30631
Accessories with DUT numbers	BP-4W, DUT 30588 ; -, DUT 30625 ; AC-301U, DUT 30639 ; DT-900, DUT 30641
Operation Voltage [V] / [Hz]	115 V / 60 Hz
Results	PASSED
Remarks	
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	17.6 / 46.0%
Date of measurements	30-Nov-2012
Measured by	Feng You

2.1.1 Test setup



2.2. Test method and limit

The measurement is made according to TIA-603-C-2004 as follows:

The measurement is divided into the Preliminary Measurement and the Final Measurement.

The suspected frequencies are searched for in Preliminary Measurement with absorbers on the floor and measuring antenna at fixed height using 2-axis EUT position system.

The Final Measurement is performed in the Semi-Anechoic Chamber with conducting metal floor, if the Preliminary Measurement results are closer than 20 dB to the permissible value.

The EUT is placed at nonconductive plate at the turntable center.

For each suspected frequency, the turntable is rotated 360 degrees and antenna is scanned from 1 to 4 m. This is repeated for both horizontal and vertical receive antenna polarizations.

The emissions less than 20 dB below the permissible value are reported.

The substitution method is used.

The measurement results are obtained as described below:

$$P [dBm] = P_{SUBST\ TX} + G_{SUBST\ TX\ ANT} - L_{SUBST\ CABLE}$$

Where $P_{SUBST\ TX}$ is signal generator level, which produces the same receiver reading P_{MEAS} in dBm as EUT. $G_{SUBST\ TX\ ANT}$ is substitution antenna gain and $L_{SUBST\ CABLE}$ is the loss of the cable between the signal generator and the substitution antenna.

Limits for spurious radiated emissions measurements

Operation band	Frequency range [MHz]	Limit [dBm]
GSM850 / WCDMA850	30 - 8500	-13
WCDMA1700 / LTE1700 / / GSM1900 / WCDMA1900	30 - 18000	-13

2.3. LTE 1700 (Band IV) test results

Channel 20175 / 1732.5 MHz

FDD, CBW 5MHz, 16QAM, 1 RB, RMS detector

Frequency [MHz]	P [dBm]	P [μ W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarization	Results
3465.341	-56.77	0.0021	-65.42	8.65	VERTICAL	PASSED
5197.961	-58.59	0.00138	-70.1	11.51	HORIZONTAL	PASSED
6930.782	-55.77	0.00265	-68.59	12.82	HORIZONTAL	PASSED
8668.452	-58.63	0.00137	-74.96	16.33	VERTICAL	PASSED
10395.902	-57.12	0.00194	-74.26	17.14	HORIZONTAL	PASSED

3. Test Equipment

3.1. Conducted measurements

Eq. No	Equipment	Type	Manufacturer	Used in
4406	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
7602	Communication Tester	CMW500	R&S	22/24/27, 15C, 15B
7151	Bluetooth Tester	CBT	R&S	15B
-	GPS RX Antenna w/AMP	L1A-PM-NF	GPS Source	15C
-	GPS Inline amplifier	A11M-V-NF-NM	GPS Source	15C
-	GPS signal Splitter	S12-P110/5-NF	GPS Source	15C
-	GPS TX Antenna	L1P-PV-NF	GPS Source	15C
7912	Spectrum Analyzer	FSV-30	R&S	22/24/27, 15C
-	Thermal Chamber	VT-4002	Vötsch	22/24/27, 15C
-	Power splitter	11667B	Agilent	22/24/27, 15C
3396	EMC Analyzer	E7405A	HP	-
7451	EMI Receiver	ESU-26	R&S	22/24/27, 15C, 15B
4188	LISN 50 µH	ESH3-Z5	R&S	15C, 15B
6981	LISN 50 µH	ESH3-Z5	R&S	15C, 15B
-	Pulse Limiter	ESH3-Z2	R&S	15C, 15B
7582	Signal Generator	SMB100A	R&S	15C, 15B

3.2. Radiated measurements

Eq. No	Equipment	Type	Manufacturer	Used in
7591	Antenna	HL562	R&S	22/24/27, 15C, 15B
7572	Double Ridge Horn Antenna	3117	ETS-Lindgren	22/24/27, 15C
7607	Standard Gain Horn Antenna	SAS 586	A.H. System	22/24/27, 15C
7624	Standard Gain Horn Antenna	SAS 587	A.H. System	22/24/27, 15C
7561	Antenna	HFH2-Z2	R&S	15C, 15B
5715	Antenna	MBA-3030	EMC Automation	22/24/27, 15C
5712	Antenna	PLP3003	EMC Automation	22/24/27, 15C
7457	Relay Switch Unit	TS-RSP	R&S	22/24/27, 15C, 15B
7459	Relay Switch Unit	TS-RSP	R&S	22/24/27, 15C, 15B
5729	Relay Switch Unit	TS-RSP	R&S	22/24/27, 15C, 15B
5728	EMI Receiver	ESIB26	R&S	22/24/27, 15C, 15B
4406	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
7602	Communication Tester	CMW500	R&S	22/24/27, 15C, 15B
7151	Bluetooth Tester	CBT	R&S	15B
3406	Controller	Sc99V	Sunol	22/24/27, 15C, 15B
-	Controller	G-1000DXC	Yaesu	22/24/27, 15C, 15B
-	Computer Controller	GS-232B	Yaesu	22/24/27, 15C, 15B
7040	Preamplifier	TS-PR3	R&S	22/24/27, 15C, 15B
-	Preamplifier	AMF-6D-020180-29-20P	Miteq	22/24/27, 15C, 15B
-	Preamplifier	AMF-4D-01000800-30-29P	Miteq	22/24/27, 15C, 15B
-	Preamplifier	AMF-5F-18002650-25-10P	Miteq	22/24/27, 15C, 15B
-	High Pass Filter	4HC1700-1-KK	R&S	22
-	High Pass Filter	F-15041	RLC	22/24/27, 15C
-	Band Reject Filter	WRCA824/849-0.2-6SS	Wainwright	22
-	Band Reject Filter	WRCC1800/2000-0.2-10SS	Wainwright	24
-	Band Reject Filter	WRCG2400/2483-2390/2493-35/10SS	Wainwright	15C
-	Band Reject Filter	WRCG832/838-825/845-40/5SS	Wainwright	22
-	Band Reject Filter	WRCG1729.4/1735.4-1722.4/1742.4-40/6SS	Wainwright	27

Eq. No	Equipment	Type	Manufacturer	Used in
-	Band Reject Filter	WRCG1877/1883 - 1870/1890-40/6SS	Wainwright	24
-	Notch Filter	WRCD1880-1.1.25/50-10SS	Wainwright	22/24/27
-	Notch Filter	WRCT902.4-0.4/40-8SS	Wainwright	-
Planned	Notch Filter	WRCJV2531/2539-2523/2547-60/12SS	Wainwright	22/24/27
-	GPS RX Antenna w/AMP	L1A-PM-NF	GPS Source	15C
-	GPS Inline amplifier	A11M-V-NF-NM	GPS Source	15C
-	GPS signal Splitter	S12-P110/5-NF	GPS Source	15C
-	GPS TX Antenna	L1P-PV-NF	GPS Source	15C