

Standalone SAR test exclusion considerations:

Date: November 2, 2022

RF feature	Mode or Modulation	Transmitting Frequency(MHz)	Test separation distance (mm)	ANT Gain (dBi)	Max. power with tune-up tolerance (dBm) ^{Note1}	Max. power with tune-up tolerance (mW)	Power thresholds	SAR test exclusion thresholds
BLE	1Mbps	2480.00	5.0	-0.76	6.00	3.981	1.254	3.00

Note1. Please refer to the operation description for Max tune-up power.

KDB 447498 D01 clause 4.3.1 Step 1) SAR test exclusion thresholds for 100MHz to 6GHz at test separation distances \leq 50 mm

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1g SAR and } \leq 7.5 \text{ for 10g extremity SAR}$

Sample Calculation

$$= [(3.9811 \text{mW} / 5 \text{mm})] \times [\sqrt{2.48 \text{GHz}}] = 1.25$$

Note. The calculation result was rounded to two decimal place for comparison.

Conclusion : SAR evaluation for general population exposure conditions by measurement or numerical simulation is not required