

FCC ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT CERTIFICATION TO FCC PART 15 REQUIREMENTS

for

INTENTIONAL RADIATOR

of

Wireless Door/Window Transmitter

FCC ID Number : QNP-EVDW319

Trade Name : Evolution

Model Number : EV-DW319

Agency Series : N/A

Report Number : C30621401-RP

Date : July 1, 2003

Prepared for :

Secure Wireless, Inc.

1185 Park Center Dr Suite A/B

Vista, CA 92083, United States

Prepared by :

C&C LABORATORY CO., LTD.

No. 163-1, Chung Sheng Road, Hsin Tien City,

Taipei, Taiwan, R. O. C.

TEL: (02)2217-0894

FAX: (02)2217-1029



Lab. Code: 200617-0



**This report shall not be reproduced, except in full, without the written approval of
C&C Laboratory Co., Ltd.**

TABLE OF CONTENTS

1. VERIFICATION OF COMPLIANCE	3
2. PRODUCT DESCRIPTION.....	4
3. TEST FACILITY	4
4. MEASUREMENT STANDARDS	4
5. TEST METHODOLOGY	4
6. MEASUREMENT EQUIPMENT USED	5
7. POWERLINE RFI LIMIT.....	5
8. RADIATED EMISSION LIMITS	6
9. SYSTEM TEST CONFIGURATION	6
10. TEST PROCEDURE	7
11. EQUIPMENT MODIFICATIONS.....	8
12. TEST RESULT	9
12.1. MAXIMUM MODULATION PERCENTAGE(M%).....	9
12.2. THE EMISSIONS BANDWIDTH	9
 APPENDIX 1 PHOTOGRAPHS OF EUT	 10
APPENDIX 2 TEST DATA	17

1. VERIFICATION OF COMPLIANCE

COMPANY NAME : Secure Wireless, Inc.
1185 Park Center Dr Suite A/B
Vista, CA 92083, United States

CONTACT PERSON : Michael Lamb / Jeff Christensen

TELEPHONE NO. : 866-966-9473

EUT DESCRIPTION : Wireless Door/Window Transmitter

MODEL NAME/NUMBER : EV-DW319


FCC ID : QNP-EVDW319

DATE TESTED : June 17, 2003 & June 23, 2003

REPORT NUMBER : C30621401-RP

TYPE OF EQUIPMENT	SECURITY EQUIPMENT (INTENTIONAL RADIATOR)
EQUIPMENT TYPE	319.5 MHz Wireless Door/Window Transmitter
MEASUREMENT PROCEDURE	ANSI 63.4 / 1992
LIMIT TYPE	CERTIFICATION
FCC RULE	CFR 47, PART 15

The above equipment was tested by C&C Laboratory Co., Ltd. for compliance with the requirements set forth in the FCC CFR 47, PART 15. The results of testing in this report apply to the product/system which was tested only. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties. **Warning:** This document reports conditions under which testing was conducted and results of tests performed. This document may not be altered or revised in any way unless done so by Compliance Engineering Services, Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by C&C Laboratory Co., Ltd. will constitute fraud and shall nullify the document.



Vince Chiang / Supervisor
C&C Laboratory Co., Ltd.

2. PRODUCT DESCRIPTION

Fundamental Frequency	319.5 MHz
Power Source	3V Battery
Transmitting Time	Periodic \leq 5 seconds
Associated Receiver	Model: N/A

3. TEST FACILITY

The open area test sites and conducted measurement facilities used to collect the radiated data are located at No. 163-1, Chung Sheng Road, Hsin Tien City, Taipei, Taiwan R.O.C. The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

4. MEASUREMENT STANDARDS

The site is constructed and calibrated in conformance with the requirements of ANSI C63.4/1992.

5. TEST METHODOLOGY

For an intentional radiator, the spectrum shall be investigated from the lowest radio frequency signal generated in the device, without going below 9 KHz, up to at least the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower. (CFR 47 Section 15.33)

6. MEASUREMENT EQUIPMENT USED

Manufacturer	Model Number	Description	Cal Due Date
R&S	ESVS30	MEASURE RECEIVER	09/13/03
ADVANTEST	R3132	SPECTRUM ANALYZER	09/11/03
SCHAFFNER	CBL 6112B	ANTENNA	11/11/03
BELDEN	9913	CABLE	10/13/03
SCHAFFNER	CPA9231A	PRE-AMPLIFIER	10/30/03

7. POWERLINE RFI LIMIT

CONNECTED TO AC POWER LINE	SECTION 15.207
CARRIER CURRENT SYSTEM IN THE FREQUENCY RANGE OF 450 KHz TO 30 MHz	SECTION 15.205 AND SECTION 15.209, 15.221, 15.223, 15.225 OR 15.227, AS APPROPRIATE.
BATTERY POWER	NO REQUIRED.

8. RADIATED EMISSION LIMITS

GENERAL REQUIREMENTS	SECTION 15.209
RESTRICTED BANDS OF OPERATION	SECTION 15.205
PERIODIC OPERATION IN THE BAND 40.66 -40.70 MHz AND ABOVE 70 MHz.	SECTION 15.231

9. SYSTEM TEST CONFIGURATION

Use a block of foam and combined it with EUT wrapping rubber band around it. This way it can test X.Y, and Z axis. To activate continuous transmission, place a small plastic block between rubber band and EUT push button.



Radiated Open Site Test Set-up

10. TEST PROCEDURE

Radiated Emissions, 15.231(4)(b)




Fig. 1

1. The EUT was placed on a wooden table on the outdoor ground plane. The search antenna was placed 3-meters from the EUT.
2. The turntable was slowly rotated to locate the direction of maximum emission at each emission falling in the restricted bands of 15.205. The EUT was moved throughout the XY, XZ, and YZ planes to maximize emissions received by the search antenna.
3. Once maximum direction was determined, the search antenna was raised and lowered in both vertical and horizontal polarizations. The maximum readings so obtained are recorded in the data listed below.




Fig. 2

1. The EUT was placed on a wooden table on the outdoor ground plane. The search antenna was placed 1-meters from the EUT. The EUT antenna was mounted vertically as per normal installation.
2. The turntable was slowly rotated to locate the direction of maximum emission at each emission falling in the restricted bands of 15.205. The EUT was moved throughout the XY, XZ, and YZ planes to maximize emissions received by the search antenna.
3. Once maximum direction was determined, the search antenna was raised and lowered in both vertical and horizontal polarizations. The maximum readings so obtained are recorded in the data listed below.

11. Equipment Modifications

To achieve compliance to FCC Section 15.231 technical limits, the following change(s) were made during compliance testing:

NONE

12. TEST RESULT

Powerline RFI Class B	Eut	Radiated Emission Limits	Eut
SECTION 15.207		SECTION 15.209	X
SECTION 15.205, 15.209, 15.221, 15.223, x 15.225 OR 15.227		SECTION 15.205	
BATTERY POWER	X	SECTION 15.231 (b)	X
		SECTION 15.231 (e)	

12.1 Maximum Modulation Percentage (M%)

CALCULATION:

Average Reading = Peak Reading (dBuV/m)+ 20log (Duty Cycle)

In order to determine possible Maximum Modulation percentage, alternations are made to the EUT.
We measured:

WHERE 1 Period = 36.24 mS
Long pulse = 2.50 mS
Short pulse = 0.20 mS
No of Long pulse = 1
No of Short pulse = 24

Duty Cycle = (N1L1+N2L2+...+Nn-1Ln-1+NnLn)/36.24 or T
Duty Cycle = [(1x2.5)+(24x0.2)]/36.24 =0.2014 = 20.14 % or -13.919dB

12.2 The Emissions Bandwidth

The bandwidth of the emissions were investigated per 15.231(c)

Center Frequency	Measured	Limits
319.5 MHz	412.0 kHz < (refer to plot)	319.5MHzX0.25%=798.75 kHz

Tue 2003 Jun 17 10:49

REF 97.0 dB μ V

MK Δ 36.24 ms

10dB/

A_View


Posi

B_Blank

Posi

-0.11 dB

DELTA MKR
36.24 ms



CENTER 319.392000 MHz

SPAN 0.000 kHz

*RBW 100 kHz


*VBW 300 kHz

*SWP 80 ms

ATT 5 dB

Tue 2003 Jun 17 11:01
REF 97.0 dB μ V MK Δ 2.500 ns
10dB/ A_Write Posi B_Blank Posi 0.28 dB

DELTA MKR
2.500 ms



CENTER 319.392000 MHz SPAN 0.000 kHz
*RBW 100 kHz *VBW 300 kHz *SWP 10 ms ATT 5 dB

Tue 2003 Jun 17 11:05

REF 97.0 dB μ V


MK Δ 200.0 μ s

10dB/

A_Write Posi B_Blank Posi

0.04 dB

DELTA MKR
200.0 μ s



CENTER 319.392000 MHz

SPAN 0.000 kHz

*RBW 100 kHz

*VBW 300 kHz

*SWP 10 ns


ATT 5 dB

Tue 2003 Jun 17 10:56

REF 97.0 dB μ V

10dB/

A_Write Posi B_Blank Posi



CENTER 319.392000 MHz

SPAN 0.000 kHz

*RBW 100 kHz

*VBW 300 kHz

*SMP 40 ms

ATT 5 dB

Tue 2003 Jun 17 10:36

REF 97.0 dB μ V

DL 63.3 dB μ V

MK Δ 412 kHz


10dB/ A_Max

Posi B_Blank

Posi

0.29 dB

DELTA MKR
412 kHz



CENTER 319.392 MHz

SPAN 2.000 MHz

*RBW 100 kHz

*VBW 300 kHz

*SWP 20 ms

*ATT 0 dB

C&C Laboratory CO., LTD.

FCC, VCCI, CISPR, CE, AUSTEL, NZ
UL, CSA, TUV, BSMI, DHHS, NVLAP

No. 163-1, Chung Sheng Road,
Hsin Tien City, Taipei, Taiwan, R.O.C.
PHONE: 02-2217-0894 FAX: 02-2217-1029

Project #: C30621401
Report #: C30621401-RP
Date& Time: 2003/06/23
Test Engr: JIMMY CHEN

Company: Secure Wireless, Inc.
EUT Description: EV-DW319(Wireless Door/Window Transmitter)
Test Configuration : EUT ONLY
Type of Test: FCC 15.231(b)
Mode of Operation: NORMAL MODE

K-Site

$$M\% = ((t1+t2+t3+...)/T) * 100\% = 20.14 \%$$

$$Av \text{ Reading} = Pk \text{ Reading} + 20 * \log(M\%)$$

$$20 * \log(M\%) = -13.919$$

	Freq.	Pk Rdg	Av Rdg	AF/AT	Closs	Pre-amp	Level	Limit	Margin	Pol	Az	Height
	(MHz)	(dBuV)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	FCC_B	(dB)	(H/V)	(Deg)	(Meter)
X	Button #1:											
	319.39	69.40	55.48	25.85	2.58	47.42	36.48	75.88	-39.40	3mV	180	1.20
	638.79	44.97	31.05	30.09	4.30	45.70	19.75	55.88	-36.13	3mV	0	1.00
Y	958.00	35.33	21.41	29.24	6.21	43.25	13.61	55.88	-42.27	3mV	90	1.20
	319.39	80.38	66.46	25.85	2.58	47.42	47.46	75.88	-28.42	3mV	270	1.10
	638.77	46.63	46.63	30.09	4.30	45.70	35.33	55.88	-20.55	3mV	0	1.40
Z	958.37	38.99	25.07	29.24	6.21	43.25	17.27	55.88	-38.61	3mV	180	1.60
	319.39	79.21	65.29	25.85	2.58	47.42	46.29	75.88	-29.59	3mV	90	1.10
	638.78	54.70	40.78	30.09	4.30	45.70	29.48	55.88	-26.40	3mV	0	1.00
	958.65	37.95	24.03	29.24	6.21	43.25	16.23	55.88	-39.65	3mV	270	1.70
X	319.39	82.65	68.73	25.85	2.58	47.42	49.73	75.88	-26.15	3mH	180	1.10
	638.78	46.37	32.45	30.09	4.30	45.70	21.15	55.88	-34.73	3mH	0	1.20
	958.25	34.69	20.77	29.24	6.21	43.25	12.97	55.88	-42.91	3mH	90	1.50
Y	319.39	83.65	69.73	25.85	2.58	47.42	50.73	75.88	-25.15	3mH	270	1.20
	638.78	48.47	34.55	30.09	4.30	45.70	23.25	55.88	-32.63	3mH	90	1.50
	958.55	38.99	25.07	29.24	6.21	43.25	17.27	55.88	-38.61	3mH	0	1.20
Z	319.38	81.17	67.25	25.85	2.58	47.42	48.25	75.88	-27.63	3mH	180	1.00
	638.78	44.05	30.13	30.09	4.30	45.70	18.83	55.88	-37.05	3mH	0	1.40
	968.54	39.59	25.67	29.24	6.21	43.25	17.87	55.88	-38.01	3mH	90	1.80

AF/AT=AF+10dB(ATTENUATOR)

Peak: RBW= 100KHz

VBW= 300KHz

A(Average): Pk Reading - 13.919dB

Total Data #18

C&C Laboratory CO., LTD.

FCC, VCCI, CISPR, CE, AUSTEL, NZ
UL, CSA, TUV, BSMI, DHHS, NVLAP

No. 163-1, Chung Sheng Road,
Hsin Tien City, Taipei, Taiwan, R.O.C.
PHONE: 02-2217-0894 FAX: 02-2217-1029

Project #: C30621401
Report #: C30621401-RP
Date& Time: 2003/06/23
Test Engr: JIMMY CHEN

Company:
EUT Description:
Test Configuration :
Type of Test:
Mode of Operation:

Secure Wireless, Inc.

EV-DW319(Wireless Door/Window Transmitter)

EUT ONLY

FCC 15.231(b)

NORMAL MODE

☒ K-Site

Freq.	Pk Rdg	Av Rdg	AF	Closs	Pre-amp	Level	Limit	Margin	Pol	Az	Height	Mark
(MHz)	(dBuV)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	FCC_B	(dB)	(H/V)	(Deg)	(Meter)	(P/Q/A)
1278	56.15	42.23	25.14	4.70	31.99	40.08	55.88	-15.80	3mV	180	1.2	A
1597	51.92	38.00	25.97	5.33	32.57	36.73	54.00	-17.27	3mV	90	1.0	A
1917	44.61	30.69	27.03	5.92	33.00	30.64	55.88	-25.24	3mV	0	1.0	A
2236	45.31	31.39	27.93	6.32	33.17	32.47	54.00	-21.53	3mV	90	1.2	A
2555	46.18	32.26	28.78	6.70	33.19	34.55	55.88	-21.33	3mV	270	1.0	A
2874	49.10	35.18	29.66	7.19	33.07	38.96	54.00	-15.04	3mV	180	1.0	A
3194	41.48	27.56	30.46	7.70	33.00	32.72	55.88	-23.16	3mV	180	1.3	A
1278	47.88	33.96	25.14	4.70	31.99	31.81	55.88	-24.07	3mH	180	1.1	A
1597	55.38	41.46	25.97	5.33	32.57	40.19	54.00	-13.81	3mH	0	1.0	A
1917	44.80	30.88	27.03	5.92	33.00	30.83	55.88	-25.05	3mH	270	1.1	A
2236	44.62	30.70	27.93	6.32	33.17	31.78	54.00	-22.22	3mH	0	1.3	A
2555	47.34	33.42	28.78	6.70	33.19	35.71	55.88	-20.17	3mH	180	1.0	A
2876	44.50	30.58	29.66	7.19	33.07	34.36	54.00	-19.64	3mH	90	1.3	A
3195	40.41	26.49	30.46	7.70	33.00	31.65	55.88	-24.23	3mH	90	1.2	A

* No other emission were found within 20dB under the limits upto 3.2 GHz.

Total data #14
V.2d

P(Peak): RBW=VBW=1MHz
A(Average): Pk Reading -13.919dB