



849 NW State Road 45
Newberry, FL 32669 USA
Ph: 888.472.2424 or 352.472.5500
Fax: 352.472.2030
Email: info@timcoengr.com
Website: www.timcoengr.com

TEST REPORT PER

FCC PT 15.249 & IC RSS-210 FOR

UNLICENSED INTENTIONAL RADIATOR

Applicant	Golden Power Manufacturing Limited	
Address	Room 1-3, 10/F, Kwan Chart Tower, 6 Technology Road, Wanchai, Hong Kong	
FCC ID	FCC ID: QO8-ZWAVE0210	
IC Cert.No.	IC: 4714A-ZWAVE0210	
Model Number	RTZW-01	
Product Description	ZWave U-SNAP	
Date Sample Received	2/25/2010	
Date Tested	3/4/2010	
Tested By	Nam Nguyen	
Approved By	Mario de Aranzeta	
Report Number	425AUT10TestReport.pdf	
Test Results	<input checked="" type="checkbox"/> PASS	<input type="checkbox"/> FAIL

**THE ATTACHED REPORT SHALL NOT BE REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL OF TIMCO ENGINEERING, INC.**



Testing certificate # 0955-01



TABLE OF CONTENT

ATTESTATIONS	3
TESTING ENVIRONMENT AND TEST SETUP	4
TEST SUPPORTING EQUIPMENT.....	4
EMC EQUIPMENT LIST.....	5
TEST PROCEDURES.....	6
RADIATION INTERFERENCE	7
OCCUPIED BANDWIDTH	8
BAND EDGE COMPLIANCE	9
DUTY CYCLE	10
POWER LINE CONDUCTED INTERFERENCE	11
RECEIVER PORTION TEST DATA (FOR IC ONLY)	12



ATTESTATIONS

This equipment has been tested in accordance with the standards identified in this test report. To the best of my knowledge and belief, these tests were performed using the measurement procedures described in this report.

All instrumentation and accessories used to test products for compliance to the indicated standards are calibrated regularly in accordance with ISO 17025 requirements.



Certificate # 0955-01

I attest that the necessary measurements were made, under my supervision, at:

Timco Engineering Inc.
849 NW State Road 45
Newberry, FL 32669



Authorized Signatory Name:

Mario de Aranzeta C.E.T.
Compliance Engineer/ Lab. Supervisor

Date: March 8, 2010



DUT SPECIFICATION

Disclaimer	The test results relate only to the items tested.				
Applicable Standard	Part 15.249, IC RSS-210				
DUT Description	RADIO THERMOSTAT				
FCC ID	FCC ID: QO8-ZWAVE0210				
IC Cert No.	IC: 4714A-ZWAVE0210				
Model Number	RTZW-01				
Operating Frequency	TX: 908.42 MHz	RX: Same			
Modulations	FSK				
DUT Power Source	<input type="checkbox"/> 110–120Vac/50– 60Hz				
	<input type="checkbox"/> DC Power				
	<input checked="" type="checkbox"/> Battery Operated Exclusively				
Test Item	<input type="checkbox"/> Prototype	<input checked="" type="checkbox"/> Pre-Production	<input type="checkbox"/> Production		
Type of Equipment	<input checked="" type="checkbox"/> Fixed	<input type="checkbox"/> Mobile	<input type="checkbox"/> Portable		
Antenna Connector	FCC Rules require that the antenna connector be unique.				

TESTING ENVIRONMENT AND TEST SETUP

Test Facility	Timco Engineering Inc. located at 849 NW State Road 45 Newberry, FL 32669 USA.		
Test Conditions	Temperature: 26°C Relative humidity: 50%		
Test Exercise	The DUT was placed in continuous transmit mode of operation.		
Modifications			

TEST SUPPORTING EQUIPMENT

Supporting Device	Manufacturer	Model / FCC ID	Serial Number
N/A			

APPLICANT: Golden Power Manufacturing Limited

FCC ID: QO8-ZWAVE0210, IC: 4714A-ZWAVE0210

REPORT: G\Golden_QO8\425AUT10\425AUT10TestReport.doc Page 4 of 12



EMC EQUIPMENT LIST

Device	Manufacturer	Model	Serial Number	Cal/Char Date	Due Date
3/10-Meter OATS	TEI	N/A	N/A	Listed 3/20/07	3/19/10
3-Meter OATS	TEI	N/A	N/A	Listed 1/11/09	1/10/12
3-Meter Semi-Anechoic Chamber	Panashield	N/A	N/A	Listed 5/11/07	5/10/10
Analyzer Silver Tower Quasi-Peak Adapter	HP	85650A	3303A01844	CAL 10/30/08	10/30/10
Analyzer Silver Tower RF Preselector	HP	85685A	2620A00294	CAL 3/6/09	3/6/11
Analyzer Silver Tower Spectrum Analyzer	HP	8566B Opt 462	3552A22064 3638A08608	CAL 10/30/08	10/30/10
Analyzer Tan Tower Preamplifier	HP	8449B-H02	3008A00372	CAL 12/8/09	12/8/11
Analyzer Tan Tower Quasi-Peak Adapter	HP	85650A	3303A01690	CAL 12/8/09	12/8/11
Analyzer Tan Tower RF Preselector	HP	85685A	3221A01400	CAL 12/7/09	12/7/11
Analyzer Tan Tower Spectrum Analyzer	HP	8566B Opt 462	3138A07786 3144A20661	CAL 12/7/09	12/7/11
Antenna: Biconnical	Eaton	94455-1	1057	CAL 12/12/09	12/12/11
Antenna: Biconnical	Eaton	94455-1	1096	CAL 10/11/08	10/11/10
Antenna: Log-Periodic	Electro-Metrics	LPA-25	1122	CAL 12/1/08	12/1/10

APPLICANT: Golden Power Manufacturing Limited

FCC ID: QO8-ZWAVE0210, IC: 4714A-ZWAVE0210

REPORT: G\Golden_QO8\425AUT10\425AUT10TestReport.doc Page 5 of 12

TEST PROCEDURES

Radiation Interference: ANSI C63.4-2003 using a spectrum analyzer, a preselector, a quasi-peak adapter, and an appropriate antenna. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100 kHz with an appropriate sweep speed and the video bandwidth was 300 kHz up to 1 GHz and 1 MHz with a video BW of 3 MHz above 1 GHz. When an emission was found, the table was rotated to produce the maximum signal strength. The antenna was placed in both the horizontal and vertical planes and the worse case emissions were reported. The spectrum was searched to at least the tenth (10) harmonic of the fundamental.

Formula Of Conversion Factors: The field strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dB μ V) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the preselector was accounted for in the spectrum analyzer meter reading.

Example:

$$\begin{array}{llll}
 \text{Freq (MHz)} & \text{Meter Reading} & + \text{ACF} & + \text{CL} = \text{FS} \\
 33 & 20 \text{ dB}\mu\text{V} & + 10.36 \text{ dB} & + 0.5 = 30.86 \text{ dB}\mu\text{V/m} @ 3\text{m}
 \end{array}$$

Power Line Conducted Interference: The procedure used was ANSI C63.4-2003 using a 50uH LISN. Both lines were observed. The bandwidth of the spectrum analyzer was 10kHz with an appropriate sweep speed. The spectrum was scanned from 0.15 to 30 MHz.

Occupied Bandwidth: A small sample of the transmitter output was fed into the spectrum analyzer and the attached plot was printed. The vertical scale is set to -10 dBm per division.

ANSI C63.4-2003 10.1 Measurement Procedures: The DUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The DUT was placed in the center of the table (1.5m side). The table used for radiated measurements is capable of continuous rotation.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes. Emissions attenuated more than 20 dB below the permissible value are not reported.

RADIATION INTERFERENCE

Rules Part No.: 15.249, 15.209, IC RSS-210

Requirements:

Frequency	Limits
Part 15.209	
9 to 490 kHz	2400/F (kHz) μ V/m @ 300 meters
490 to 1705 kHz	24000/F (kHz) μ V/m @ 30 meters
1705 kHz to 30 MHz	29.54 dB μ V/m @ 30 meters
30 – 88	40.0 dB μ V/m @ 3 meters
80 – 216	43.5 dB μ V/m @ 3 meters
216 – 960	46.0 dB μ V/m @ 3 meters
Above 960	54.0 dB μ V/m @ 3 meters
Part 15.249	
Fundamental 902 – 928 MHz	94.0 dB μ V/m @ 3 meters
Fundamental 2.4 – 2.4835 MHz	94.0 dB μ V/m @ 3 meters
Harmonics	54.0 dB μ V/m @ 3 meters

Test Data:

Tuned Frequency MHz	Emission Frequency MHz	Meter Reading dB μ V	Ant. Polarity V/H	Coax Loss dB	Correction Factor dB/m	Field Strength dB μ V/m	Margin dB
908.4	908.42	62.5	V	1.96	22.62	87.08	6.92
908.4	908.42	68.6	H	1.96	23.38	93.94	0.06
908.4	1,816.84	15.6	V	2.75	30.03	48.38	5.62
908.4	1,816.84	16.1	H	2.75	30.03	48.88	5.12
908.4	908.42	62.5	V	1.96	22.62	87.08	6.92
908.4	2,725.26	8.9	V	3.41	32.55	44.86	9.14
908.4	2,725.26	11.5	H	3.41	32.55	47.46	6.54
908.4	3,633.68	7.2	V	4.17	33.01	44.38	9.62
908.4	3,633.68	7.6	H	4.17	33.01	44.78	9.22
908.4	4,542.10	7.4	V	4.77	34.10	46.27	7.73
908.4	4,542.10	7.9	H	4.77	34.10	46.77	7.23
908.4	5,450.52	6.1	H	5.14	34.64	45.88	8.12
908.4	5,450.52	6.7	V	5.14	34.64	46.48	7.52
908.4	6,358.94	6.8	H	5.41	35.69	47.90	6.10
908.4	6,358.94	7.5	V	5.41	35.69	48.60	5.40

APPLICANT: Golden Power Manufacturing Limited

FCC ID: QO8-ZWAVE0210, IC: 4714A-ZWAVE0210

REPORT: G\Golden_QO8\425AUT10\425AUT10TestReport.doc Page 7 of 12

OCCUPIED BANDWIDTH

Rules Part No.: 15.249 (d), IC RSS-210

Requirements: The field strength of any emissions appearing outside the bandedges and up to 10 kHz above and below the band edges shall be attenuated at least 50 dB below the level of the carrier or to the general limits of 15.249.

Test Data:



APPLICANT: Golden Power Manufacturing Limited

FCC ID: QO8-ZWAVE0210, IC: 4714A-ZWAVE0210

REPORT: G\Golden_QO8\425AUT10\425AUT10TestReport.doc Page 8 of 12



BAND EDGE COMPLIANCE

Rules Part No.: 15.249 (d), RSS-210

Requirements: 40 dBc or in the case of restricted bands 54 dB μ V/m.

Test Data: NA

Single channel device

APPLICANT: Golden Power Manufacturing Limited
FCC ID: QO8-ZWAVE0210, IC: 4714A-ZWAVE0210
REPORT: G\Golden_QO8\425AUT10\425AUT10TestReport.doc Page 9 of 12



DUTY CYCLE

Total # of pulses: 10 in 100 ms

Duration of pulse: 1.5 ms maximum duration of pulse according to manufacturer.

$20 \log ((10 \cdot 1.5) / 100) = 20 \log (0.15) = 16 \text{ dB}$



POWER LINE CONDUCTED INTERFERENCE

Rules Part No.: 15.207, IC RSS-210

Requirements:

Frequency (MHz)	Quasi Peak Limits (dB μ V)	Average Limits (dB μ V)
0.15 – 0.5	66 – 56	56 – 46
0.5 – 5.0	56	46
5.0 – 30	60	50

Test Data: The attached graphs represent the emissions read for power line conducted for this device. Both lines were observed.

N/A
Battery or vehicle powered DUT.



RECEIVER PORTION TEST DATA (FOR IC ONLY)

Rules Part No.: 15.109, RSS-210

Requirements:

Frequency MHz	Limits
30 – 88	40.0 dB μ V/m measured @ 3 meters
88 – 216	43.5 dB μ V/m measured @ 3 meters
216 – 960	46.0 dB μ V/m measured @ 3 meters
Above 960	54.0 dB μ V/m measured @ 3 meters

Test Data:

Tuned Frequency MHz	Emission Frequency MHz	Meter Reading dB μ V	Ant. Polarity V/H	Coax Loss dB	Correction Factor dB/m	Field Strength dB μ V/m	Margin dB
908.4	31.40	5.5	V	0.41	12.48	18.39	21.61
908.4	68.80	5.2	V	0.56	5.67	11.43	28.57
908.4	86.10	6.5	V	0.62	10.48	17.60	22.40
908.4	170.60	3.7	H	0.78	15.47	19.95	23.55
908.4	216.90	10.3	H	0.93	11.62	22.85	23.15
908.4	391.20	7.3	V	1.19	15.61	24.10	21.90
908.4	469.20	7.9	V	1.27	17.08	26.25	19.75
908.4	495.70	5.4	H	1.30	17.73	24.43	21.57
908.4	624.10	7.4	H	1.62	19.60	28.62	17.38
908.4	655.00	4.9	V	1.66	20.05	26.61	19.40
908.4	839.60	4.4	H	1.92	22.48	28.80	17.20

APPLICANT: Golden Power Manufacturing Limited

FCC ID: QO8-ZWAVE0210, IC: 4714A-ZWAVE0210

REPORT: G\Golden_QO8\425AUT10\425AUT10TestReport.doc Page 12 of 12