

RF EXPOSURE ANALYSIS

EQUIPMENT

Type of equipment:	WIFI Module
Brand name:	BlueGiga
Type / Model:	WF111-E
Manufacturer:	BlueGiga Technologies Oy
By request of:	Silicon Laboratories Finland Oy

FCC ID: QQQWF111

IC Number: 5123A-BGTWF111

Operating range: 2412 – 2462 MHz

REQUIREMENT

CFR 47 §1.1310
RSS-102 issue 5 (2014)

CALCULATIONS

Highest output power to antenna is +19.15 dBm
With +2.2 dBi antenna gain EIRP is +21.35 dBm or 136.5 mW

The manual recommends that the operator is not closer than (r) 20 cm to the transmitter's antenna.

A worst case calculation is as follows:

$$S = \frac{EIRP}{4 \times \pi \times r^2}$$

Maximum power density is

$$S = 0.1365 / (4 \times \pi \times 0,2^2) = 0.2716 \text{ W/m}^2 = 0.0272 \text{ mW/cm}^2$$

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Intertek Semko AB

Torshamnsgatan 43, Box 1103, SE-164 22 Kista, Sweden

Telephone +46 8 750 00 00, Fax +46 8 750 60 30

www.intertek.se

Registered in Sweden: No: SE556024059901, Registered office: As address

Limit:

CFR 47 §1.1310 (e) table 1 Limits for General Population/Uncontrolled Exposure: 1 mW/cm²

RSS-102 section 2.5.2: states that at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz;
Maximum EIRP 136.46 mW < 2,68 W at 2412 MHz.

The requirements are fulfilled.

Intertek Semko AB, Radio& EMC

Date of issue: 2015-09-22



Issued by: Daniel Nilsson

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Intertek Semko AB

Torshamnsgatan 43, Box 1103, SE-164 22 Kista, Sweden

Telephone +46 8 750 00 00, Fax +46 8 750 60 30

www.intertek.se

Registered in Sweden: No: SE556024059901, Registered office: As address