



FCC Test Report

FOR:
Crane Payment Innovations

Model Name:
CORA152-US

Product Description:
Vending machine cashless payment and system

FCC ID: QP8CORABTATT

Applied Rules and Standards:
47 CFR Part 15.247 (DTS)

REPORT #: EMC_MEIGR_010_20001_15.247_BT_DTS

DATE: 2020-06-10



A2LA Accredited

IC recognized #
3462B-2

CETECOM Inc.

411 Dixon Landing Road ♦ Milpitas, CA 95035 ♦ U.S.A.

Phone: + 1 (408) 586 6200 ♦ Fax: + 1 (408) 586 6299 ♦ E-mail: info@cetecom.com ♦ <http://www.cetecom.com>
CETECOM Inc. is a Delaware Corporation with Corporation number: 2905571

TABLE OF CONTENTS

1	ASSESSMENT	3
2	ADMINISTRATIVE DATA.....	4
2.1	IDENTIFICATION OF THE TESTING LABORATORY ISSUING THE EMC TEST REPORT.....	4
2.2	IDENTIFICATION OF THE CLIENT	4
2.3	IDENTIFICATION OF THE MANUFACTURER	4
3	EQUIPMENT UNDER TEST (EUT)	5
3.1	EUT SPECIFICATIONS	5
3.2	EUT SAMPLE DETAILS	5
3.3	SUPPORT EQUIPMENT	6
3.4	TEST SAMPLE CONFIGURATION.....	6
3.5	JUSTIFICATION FOR WORST CASE MODE OF OPERATION.....	7
4	SUBJECT OF INVESTIGATION	7
5	MEASUREMENT RESULTS SUMMARY	8
6	MEASUREMENT UNCERTAINTY	9
6.1	ENVIRONMENTAL CONDITIONS DURING TESTING:.....	9
6.2	DATES OF TESTING:	9
7	MEASUREMENT PROCEDURES.....	10
7.1	RADIATED MEASUREMENT	10
7.2	RF CONDUCTED MEASUREMENT PROCEDURE	12
8	TEST RESULT DATA.....	13
8.1	MAXIMUM PEAK CONDUCTED OUTPUT POWER	13
8.2	POWER SPECTRAL DENSITY	17
8.3	BAND EDGE COMPLIANCE.....	21
8.4	EMISSION BANDWIDTH 6dB AND 99% OCCUPIED BANDWIDTH	26
8.5	RADIATED TRANSMITTER SPURIOUS EMISSIONS AND RESTRICTED BANDS.....	33
9	TEST SETUP PHOTOS.....	47
10	TEST EQUIPMENT AND ANCILLARIES USED FOR TESTING	47
11	REVISION HISTORY	48



1 Assessment

The following device was evaluated against the applicable criteria specified in FCC rules Parts 15.247 of Title 47 of the Code of Federal Regulations.

No deviations were ascertained.

Company	Description	Model #
Crane Payment Innovations	Vending machine cashless payment and system	CORA152-US

Responsible for Testing Laboratory:

2020-06-10	Compliance	Cindy Li (Lab Manager)	
Date	Section	Name	Signature

Responsible for the Report:

2020-06-10	Compliance	Yuchan Lu (Test Engineer)	
Date	Section	Name	Signature

The test results of this test report relate exclusively to the test item specified in Section 3. CETECOM Inc. USA does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of CETECOM Inc. USA.

2 Administrative Data

2.1 Identification of the Testing Laboratory Issuing the EMC Test Report

Company Name:	CETECOM Inc.
Department:	Compliance
Street Address:	411 Dixon Landing Road
City/Zip Code	Milpitas, CA 95035
Country	USA
Telephone:	+1 (408) 586 6200
Fax:	+1 (408) 586 6299
EMC Lab Manager:	Cindy Li
Responsible Project Leader:	Rami Saman

2.2 Identification of the Client

Client's Name:	Crane Payment Innovations
Street Address:	3222 Phoenixville Pike, Suite 200
City/Zip Code:	Malvern, PA 19355
Country:	USA

2.3 Identification of the Manufacturer

Manufacturer's Name:	Same as Client
Manufacturers Address:	
City/Zip Code	
Country	

3 Equipment Under Test (EUT)

3.1 EUT Specifications

Model No:	CORA152-US
HW Version :	G1
SW Version :	9.20.1
FCC-ID:	QP8CORABTATT
HVIN:	CORA152-US
PMN:	CORA
Product Description:	Vending machine cashless payment and system
Frequency Range / number of channels:	Nominal band: 2400 MHz – 2483.5 MHz; Center to center: 2402 MHz (ch 0) – 2480 MHz (ch 39), 40 channels
Type(s) of Modulation:	Bluetooth Low Energy, using Dynamic Sequence Spread Spectrum with GFSK modulation.
Modes of Operation:	Bluetooth LE in both advertising and connected mode of operation
Antenna Information as declared:	¼ wave strip line PCB antenna, 1.8 dBi
Max. Peak Output Power:	Conducted Power 9.4 dBm
Power Supply/ Rated Operating Voltage Range:	Vmin: 20 VDC/ Vnom: 24 VDC / Vmax: 42 VDC
Operating Temperature Range:	-15 °C to 60 °C
Other Radios included in the device:	<ul style="list-style-type: none"> ❖ LTE <ul style="list-style-type: none"> • Module name: Telit • Module number: LE910B1-SA • FCC ID: RI7LE910B1SA
Sample Revision:	<input type="checkbox"/> Prototype Unit; <input checked="" type="checkbox"/> Production Unit; <input type="checkbox"/> Pre-Production

3.2 EUT Sample details

EUT #	PIN/SN	HW Version	SW Version	Notes/Comments
1	5742	G1	9.20.1	Radiated Sample
2	29890100010	G1	9.15	Conducted Sample

3.3 Support Equipment

SE #	Type	Model	Manufacturer	P/N
1	AC/DC Adapter	ETSA240270U	CUI INC	ETSA240270U-P5P-SZ
2	Vending Simulator /Power	-	-	-
3	PCB interface	-	-	-

3.4 Test Sample Configuration

EUT Set-up #	Combination of SE used for test set up	Comments
1	EUT#1+ SE#1+ SE#2+ SE#3	Special commands through command window used to configure the Bluetooth LE radio to low, mid and high channels provided by the client that will not be available to the end user. For radiated measurements, the internal antenna was connected.

3.5 Justification for Worst Case Mode of Operation

During the testing process, the EUT was tested with transmitter sets on BLE low, mid and high channels. Based on client declaration, the EUT was configured to the highest duty cycle and maximum output power.

For radiated measurements, all data in this report shows the worst case between horizontal and vertical antenna polarizations and for all orientations of the EUT.

Based on CETECOM Inc. evaluation of the TCF provided by the customer for QP8CORABT and QP8CORABTATT, the circuitry/power setting/schematics of the BT-LE part of EUT are identical with the device under FCC ID: QP8CORABT. Hence the conducted results are leveraged from CETECOM report "EMC_MEIGR_008_15.247_DTS".

4 Subject of Investigation

The objective of the measurements done by CETECOM Inc. was to assess the performance of the EUT according to the relevant requirements specified in FCC rules Part 15.247 of Title 47 of the Code of Federal Regulations.

Testing procedures are based on 558074 D01 DTS Meas Guidance v05r02 – "GUIDANCE FOR PERFORMING COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEMS (DTS) OPERATING UNDER SECTION 15.247" - April 5, 2017, by the Federal Communications Commission, Office of Engineering and Technology, Laboratory Division.

5 Measurement Results Summary

Test Specification	Test Case	Temperature and Voltage Conditions	Mode	Pass	NA	NP	Result
§15.247(a)(1)	Emission Bandwidth	Nominal	BTLE	■	□	□	Complies ¹
§15.247(e)	Power Spectral Density	Nominal	BTLE	■	□	□	Complies ¹
§15.247(b)(1)	Maximum Conducted Output Power and EIRP	Nominal	BTLE	■	□	□	Complies ¹
§15.247(d)	Band edge compliance Unrestricted Band Edges	Nominal	BTLE	■	□	□	Complies ¹
§15.247; 15.209; 15.205	Band edge compliance Restricted Band Edges	Nominal	BTLE	■	□	□	Complies ¹
§15.247(d); §15.209	TX Spurious emissions-Radiated	Nominal	BTLE	■	□	□	Complies
§15.207(a)	AC Conducted Emissions	Nominal	BTLE	□	■	□	Note2

Note1: Test result are leveraged from report "EMC_MEIGR_008_15.247_DTS". Refer to section 3.5 for justification

Note2: NA= Not Applicable; EUT is powered by 24VDC

6 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus, with 95% confidence interval (in dB delta to result), based on a coverage factor k=1.

Radiated measurement

9 kHz to 30 MHz	±2.5 dB (Magnetic Loop Antenna)
30 MHz to 1000 MHz	±2.0 dB (Biconilog Antenna)
1 GHz to 40 GHz	±2.3 dB (Horn Antenna)

Conducted measurement

150 kHz to 30 MHz	±0.7 dB (LISN)
-------------------	----------------

RF conducted measurement	±0.5 dB
--------------------------	---------

According to TR 102 273 a multiplicative propagation of error is assumed for RF measurement systems. For this reason the RMS method is applied to dB values and not to linear values as appropriate for additive propagation of error. Also used: <http://physics.nist.gov/cuu/Uncertainty/typeb.html>. The above calculated uncertainties apply to direct application of the Substitution method. The Substitution method is always used when the EUT comes closer than 3 dB to the limit.

6.1 Environmental Conditions During Testing:

The following environmental conditions were maintained during the course of testing:

- Ambient Temperature: 20-25° C
- Relative humidity: 40-60%

6.2 Dates of Testing:


03/10/2020 - 03/18/2020

7 Measurement Procedures


7.1 Radiated Measurement

The radiated measurement is performed according to ANSI C63.10 (2013)


- The exploratory measurement is accomplished by running a matrix of 16 sweeps over the required frequency range with R&S Test-SW EMC32 for 4 positions of the turntable, two orthogonal positions of the EUT and both antenna polarizations. This procedure exceeds the requirement of the above standards to cover the 3 orthogonal axis of the EUT. A max peak detector is utilized during the exploratory measurement. The Test-SW creates an overall maximum trace for all 12 sweeps and saves the settings for each point of this trace. The maximum trace is part of the test report.
- The 10 highest emissions are selected with an automatic algorithm of EMC32 searching for peaks in the noise floor and ensuring that broadband signals are not selected multiple times.
- The maxima are then put through the final measurement and again maximized in a 90deg range of the turntable, fine search in frequency domain and height scan between 1m and 4m.
- The above procedure is repeated for all possible ways of power supply to EUT and for all supported modulations.
- In case there are no emissions above noise floor level only the maximum trace is reported as described above.
- The results are split up into up to 4 frequency ranges due to antenna bandwidth restrictions. A magnetic loop is used from 9 kHz to 30 MHz, a Biconilog antenna is used from 30 MHz to 1 GHz, and two different horn antennas are used to cover frequencies up to 40 GHz.



Radiated Emissions Test Setup 30MHz-1GHz Measurements



Radiated Emissions Test Setup above 1GHz Measurements



7.1.1 Sample Calculations for Field Strength Measurements

Field Strength is calculated from the Spectrum Analyzer/ Receiver readings, taking into account the following parameters:

1. Measured reading in dB μ V
2. Cable Loss between the receiving antenna and SA in dB and
3. Antenna Factor in dB/m

All radiated measurement plots in this report are taken from a test SW that calculates the Field Strength based on the following equation:


$$FS \text{ (dB}\mu\text{V/m)} = \text{Measured Value on SA (dB}\mu\text{V)} + \text{Cable Loss (dB)} + \text{Antenna Factor (dB/m)}$$

Example:

Frequency (MHz)	Measured SA (dB μ V)	Cable Loss (dB)	Antenna Factor Correction (dB)	Field Strength Result (dB μ V/m)
1000	80.5	3.5	14	98.0

7.2 RF Conducted Measurement Procedure

Testing procedures are based on 558074 D01 DTS Meas Guidance v05r02 – “GUIDANCE FOR PERFORMING COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEMS (DTS) OPERATING UNDER SECTION 15.247” - April 5, 2017, by the Federal Communications Commission, Office of Engineering and Technology, Laboratory Division.



- Connect the equipment as shown in the above diagram.
- Adjust the settings of the SA (Rohde-Schwarz Spectrum Analyzer) to connect the EUT at the required mode of test.
- Measurements are to be performed with the EUT set to the low, middle and high channels and for worst case modulation schemes.
- Calculate the conducted power by taking into account attenuation of the cable and the attenuator

8 Test Result Data

8.1 Maximum Peak Conducted Output Power

8.1.1 Measurement according to FCC 558074 D01 DTS Meas Guidance v04

Spectrum Analyzer settings:

- RBW \geq DTS bandwidth
- VBW $\geq 3 \times$ RBW
- Span $\geq 3 \times$ RBW
- Sweep = Auto couple
- Detector function = Peak
- Trace = Max hold
- Use peak marker function to determine the peak amplitude level

8.1.2 Limits:

Maximum Peak Output Power:

- FCC §15.247 (b)(1): 1 W
- IC RSS-247: 1 W


8.1.3 Test conditions and setup:


Ambient Temperature	EUT Set-Up #	EUT operating mode	Power Input	Antenna Gain
22° C	1	GFSK continuous fixed channel	24 VDC	3.2 dBi


8.1.4 Measurement result:

Plot #	Frequency (MHz)	Maximum Peak Conducted Output Power (dBm)	EIRP (dBm)	Limit (dBm)	Result
1	2402	9.04	12.24	30 (Pk) / 36 (EIRP)	Pass
2	2440	9.38	12.58	30 (Pk) / 36 (EIRP)	Pass
3	2480	9.41	12.61	30 (Pk) / 36 (EIRP)	Pass

8.1.5 Measurement Plots:







8.2 Power Spectral Density

8.2.1 Measurement according to FCC 558074 D01 DTS Meas Guidance v04

Spectrum Analyzer settings for Peak PSD method:

- Set analyzer center frequency to DTS channel center frequency
- Set the span to 1.5 x DTS bandwidth
- Set RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
- Set the VBW $\geq 3 \times \text{RBW}$
- Detector = Peak
- Sweep time = Auto couple
- Trace mode = Max hold
- Allow trace to fully stabilize
- Use the peak marker function to determine the maximum amplitude level within the RBW
- If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat

8.2.2 Limits:

FCC§15.247(e) & RSS-247 5.2(2)

- For digitally modulated systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.


8.2.3 Test conditions and setup:


Ambient Temperature	EUT Set-Up #	EUT operating mode	Power Input	Antenna Gain
22° C	1	GFSK continuous fixed channel	24 VDC	3.2 dBi


8.2.4 Measurement result:

Plot #	Frequency (MHz)	Maximum Power Spectral Density (dBm/3 kHz)	PSD Adjusted for Antenna Gain (dBm/3 kHz)	Limit (dBm / 3 kHz)	Result
1	2402	-6.55	-3.35	8	Pass
2	2441	-6.67	-3.47	8	Pass
3	2480	-6.19	-2.99	8	Pass

8.2.5 Measurement Plots:







8.3 Band Edge Compliance

8.3.1 Measurement according to FCC 558074 D01 DTS Meas Guidance v04

Spectrum Analyzer settings for band edge:

- Set the center frequency and span to encompass frequency range to be measured
- RBW = 100 kHz
- VBW $\geq 3 \times$ RBW
- Sweep Time: Auto couple
- Detector = Peak
- Trace = Max hold
- Allow trace to fully stabilize
- Use the peak marker function to determine the maximum amplitude level
- Set the marker on the emission at the band edge, or on the highest modulation product outside of the band, if this level is greater than that at the band edge

8.3.2 Limits non restricted band:

FCC§15.247 (d)

- In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

RSS-247 5/5

- In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30dB instead of 20dB.

Spectrum Analyzer settings for restricted band:

- Peak measurements are made using a peak detector and RBW=1 MHz

8.3.3 Limits restricted band §15.247/15.209/15.205 and RSS-Gen 8.9/8.10

- *PEAK LIMIT= 74 dB μ V/m @3m =-21.23 dBm
- *AVG. LIMIT= 54 dB μ V/m @3m =-41.23 dBm
- Start frequency & stop frequency according to frequency range specified in the restricted band table in FCC section 15.205 & RSS-Gen 8.10
- Measurements with a peak detector were used to show compliance to average limits, thus showing compliance to both peak and average limits.

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

8.3.4 Test conditions and setup:


Ambient Temperature	EUT Set-Up #	EUT operating mode	Power Input	Antenna Gain
22° C	1	GFSK continuous fixed channel	24 VDC	3.2 dBi


8.3.5 Measurement result:


Plot #	EUT operating mode	Band Edge	Band Edge Delta (dBc)	Limit (dBc)	Result
1	GFSK continuous fixed channel	Lower, Non-restricted	-51.08	20	Pass

Plot #	EUT operating mode	Band Edge	Measured Peak Value (dBm)	Corrected by duty cycle	Corrected by Antenna Gain (dBm)	Limit (dBm)	Result
2	GFSK continuous fixed channel	Upper Restricted Peak	-31.82	NA due to peak detector, and trace max hold	-28.62	-21.23 Peak	Pass
3	GFSK continuous fixed channel	Upper Restricted AVG	-50.04	NA due to RMS detector, and trace average	-46.84	-41.23 AVG	Pass

8.3.6 Measurement Plots:







8.4 Emission Bandwidth 6dB and 99% Occupied Bandwidth

8.4.1 Measurement according to FCC 558074 D01 DTS Meas Guidance v04

Spectrum Analyzer settings:

- Set RBW = 100 kHz
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW
- Detector = Peak
- Trace mode = Max hold
- Sweep = Auto couple
- Allow the trace to stabilize
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

8.4.2 Limits:

FCC §15.247(a)(1) and RSS-247 5.2(1)

- Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

8.4.3 Test conditions and setup:


Ambient Temperature	EUT Set-Up #	EUT operating mode	Power Input
22° C	1	GFSK continuous fixed channel	24 VDC


8.4.4 Measurement result:


Plot #	Frequency (MHz)	6dB Emissions Bandwidth (MHz)	Limit (MHz)	Result
1	2402	0.687	> 0.5	Pass
2	2440	0.687	> 0.5	Pass
3	2480	0.687	> 0.5	Pass


Plot #	Frequency (MHz)	99% Occupied Bandwidth (MHz)	Limit (MHz)	Result
4	2402	1.043	> 0.5	Pass
5	2440	1.043	> 0.5	Pass
6	2480	1.043	> 0.5	Pass


8.4.5 Measurement Plots:














8.5 Radiated Transmitter Spurious Emissions and Restricted Bands

8.5.1 Measurement according to ANSI C63.10 (2013)

Spectrum Analyzer Settings:

- Frequency = 9 KHz – 30 MHz
- RBW = 9 KHz
- Detector: Peak

- Frequency = 30 MHz – 1 GHz
- Detector = Peak / Quasi-Peak
- RBW= 120 KHz (<1GHz)

- Frequency > 1 GHz
- Detector = Peak / Average
- RBW = 1 MHz

- Radiated spurious emissions shall be measured for the transmit frequencies, transmit power, and data rate for the lowest, middle and highest channel in each frequency band of operation and for the highest gain antenna for each antenna type, and using the appropriate parameters and test requirements.
- The highest (or worst-case) data rate shall be recorded for each measurement.
- For testing at distance other than the specified in the standard, the limit conversion is calculated by using 40 dB/decade extrapolation factor as follow: Conversion factor (CF) = $40 \log (D/d) = 40 \log (300m / 3m) = 80dB$

8.5.2 Limits:

FCC §15.247

- In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

FCC §15.209

- Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency of emission (MHz)	Field strength (µV/m)	Measurement Distance (m)	Field strength @ 3m (dBµV/m)
0.009-0.490	2400/F(kHz) / -----	300	-
0.490-1.705	24000/F(kHz) / -----	30	-
1.705-30.0	30 / (29.5)	30	-
30-88	100	3	40 dBµV/m
88-216	150	3	43.5 dBµV/m
216-960	200	3	46 dBµV/m
Above 960	500	3	54 dBµV/m

FCC §15.205

- Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

- Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
 *PEAK LIMIT= 74 dBµV/m
 *AVG. LIMIT= 54 dBµV/m


8.5.3 Test conditions and setup:


Ambient Temperature	EUT Set-Up #	EUT operating mode	Power Input
23° C	1	BTLE	24 VDC

8.5.4 Measurement result:

Plot #	Channel #	Scan Frequency	Limit	Result
1-3	Low	30 MHz – 18 GHz	See section 8.5.2	Pass
4-8	Mid	9 kHz – 26 GHz	See section 8.5.2	Pass
9-11	High	30 MHz – 18 GHz	See section 8.5.2	Pass

8.5.5 Measurement Plots:





Plot #3 Radiated Emissions: 3-18 GHz

Modulation: BT LE


Channel: Low

Final Result

Frequency (MHz)	MaxPeak (dBµV/m)	RMS (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (h)	Height (t)	Pol	Azimuth (h)	Corr. (dB/m)
4803.924	---	50.266	53.98	3.71	500.0	1000.000	100.0	H	245.0	-6.0
4803.924	53.085	---	73.99	20.90	500.0	1000.000	100.0	H	245.0	-6.0
7205.911	---	67.081	53.98	-13.10	500.0	1000.000	107.0	H	260.0	-2.8
7205.911	67.614	---	73.99	6.37	500.0	1000.000	107.0	H	260.0	-2.8

(continuation of the "Final_Result" table from column 16 ...)

Frequency (MHz)	Comment
4803.924	5:35:33 PM - 3/11/2020
4803.924	5:35:33 PM - 3/11/2020
7205.911	5:38:53 PM - 3/11/2020
7205.911	5:38:52 PM - 3/11/2020



— Preview Result 1-PK+ * Critical_Freqs PK+ — FCC 15C PK
- - - FCC 15C AVG ◆ Final_Result PK+ ◆ Final_Result RMS

Note: According to FCC15.35(c), a duty cycle correction factor is applied here. For BTLE advertising mode, maximum duty cycle will be 5%, which is 26 dB, Hence this margin could cover the highest spurious above.

Plot #4 Radiated Emissions: 9 KHz – 30 MHz

Modulation: BT LE


Channel: Mid

Final Result

Frequency (MHz)	QuasiPeak (dBµV/m)	RMS (dBµV/m)	Limit (dBµV/m)	Margin	Meas. Time (ms)	Bandwidth (h)	Height	Pol	Azimuth (h)	Corr. (dB/m)
0.948	67.221	---	68.08	0.86	500.0	9.000	116.0	H	204.0	18.4

(continuation of the "Final_Result" table from column 16 ...)

Frequency (MHz)	Comment
0.948	12:55:09 PM - 3/16/2020



- Preview Result 1-PK+
- FCC 15.9kHz converted to 3m
- ◆ Final_Result RMS
- * Critical_Freqs PK+
- ◆ Final_Result QPK

Plot #5 Radiated Emissions: 30 MHz – 1GHz

Modulation: BT LE


Channel: Mid

Final_Result


Frequency (MHz)	MaxPeak (dBµV/m)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin	Meas. Time (ms)	Bandwidth	Height	Pol	Azimuth	Corr. (dB/m)
330.001	---	42.486	46.00	3.51	500.0	120.000	125.0	H	321.0	-16.4
429.017	---	41.954	46.00	4.05	500.0	120.000	100.0	H	-7.0	-13.8
495.013	---	45.901	46.00	0.10	500.0	120.000	300.0	H	177.0	-12.5
792.021	---	41.670	46.00	4.33	500.0	120.000	100.0	V	182.0	-7.2
825.013	---	42.468	46.00	3.53	500.0	120.000	107.0	H	50.0	-7.1
891.035	---	42.854	46.00	3.15	500.0	120.000	100.0	H	81.0	-5.7

(continuation of the "Final_Result" table from column 16 ...)

Frequency (MHz)	Comment
330.001	2:18:12 PM - 3/13/2020
429.017	2:06:10 PM - 3/13/2020
495.013	2:14:57 PM - 3/13/2020
792.021	2:21:31 PM - 3/13/2020
825.013	2:09:09 PM - 3/13/2020
891.035	2:12:07 PM - 3/13/2020



◆ Preview Result 1-PK+ Final_Result PK+
 * Critical_Freqs PK+ Final_Result QPK
 — FCC 15C PK



Plot #7 Radiated Emissions: 3-18 GHz

Modulation: BT LE


Channel: Mid

Final Result

Frequency (MHz)	MaxPeak (dBµV/m)	RMS (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (h)	Height (t)	Pol	Azimuth (h)	Corr. (dB/m)
4882.034	---	54.528	53.98	-0.55	500.0	1000.000	100.0	H	239.0	-5.7
4882.034	56.115	---	73.99	17.87	500.0	1000.000	100.0	H	239.0	-5.7
7322.868	---	65.374	53.98	-11.40	500.0	1000.000	107.0	H	246.0	-2.7
7322.868	65.920	---	73.99	8.07	500.0	1000.000	107.0	H	246.0	-2.7


(continuation of the "Final_Result" table from column 16 ...)

Frequency (MHz)	Comment
4882.034	5:19:07 PM - 3/11/2020
4882.034	5:19:07 PM - 3/11/2020
7322.868	5:22:26 PM - 3/11/2020
7322.868	5:22:26 PM - 3/11/2020



— Preview Result 1-PK+ * Critical_Freqs PK+ — FCC 15C PK
- - - FCC 15C AVG ◆ Final_Result PK+ ◆ Final_Result RMS

Note: According to FCC15.35(c), a duty cycle correction factor is applied here. For BTLE advertising mode, maximum duty cycle will be 5%, which is 26 dB, Hence this margin could cover the highest spurious above.



Plot #9 Radiated Emissions: 30 MHz – 1GHz

Modulation: BT LE


Channel: High

Final Result


Frequency (MHz)	MaxPeak (dBµV/m)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin	Meas. Time (ms)	Bandwidth (Hz)	Height (dB)	Pol	Azimuth (deg)	Corr. (dB/m)
330.011	---	42.510	46.00	3.49	500.0	120.000	125.0	H	324.0	-16.4
429.008	---	42.136	46.00	3.86	500.0	120.000	100.0	H	-6.0	-13.8
495.017	---	43.858	46.00	2.14	500.0	120.000	116.0	V	77.0	-12.6
759.021	---	41.124	46.00	4.88	500.0	120.000	100.0	V	18.0	-7.6
825.012	---	41.941	46.00	4.06	500.0	120.000	100.0	H	47.0	-7.1
891.031	---	43.154	46.00	2.85	500.0	120.000	100.0	H	68.0	-5.7


(continuation of the "Final_Result" table from column 16 ...)

Frequency (MHz)	Comment
330.011	3:22:08 PM - 3/13/2020
429.008	3:12:58 PM - 3/13/2020
495.017	3:28:42 PM - 3/13/2020
759.021	3:25:38 PM - 3/13/2020
825.012	3:15:59 PM - 3/13/2020
891.031	3:19:00 PM - 3/13/2020



◆ Preview Result 1-PK+ Final_Result PK+
 * Critical_Freqs PK+ Final_Result QPK
 — FCC 15C PK







9 Test setup photos

Setup photos are included in supporting file name: "EMC_MEIGR_010_20001_Setup_Photos.pdf"

10 Test Equipment And Ancillaries Used For Testing

Equipment Type	Manufacturer	Model	Serial #	Calibration Cycle	Last Calibration Date
PASSIVE LOOP ANTENNA	ETS LINDGREN	6507	00161344	3 YEARS	10/26/2017
BILOG ANTENNA	TESEO	CBL 6141B	41106	3 YEARS	11/01/2017
HORN ANTENNA	EMCO	3115	00035114	3 YEARS	07/31/2017
HORN ANTENNA	ETS LINDGREN	3117	00169547	3 YEARS	08/08/2017
HORN ANTENNA	ETS LINDGREN	3116C	00169535	3 YEARS	09/24/2017
UNIVERSAL RADIO COMMUNICATION TESTER	R&S	CMU 200	101821	3 YEARS	07/06/2017
WIDEBAND RADIO COMMUNICATION	R&S	CMW500	127068	3 YEARS	07/01/2017
SIGNAL ANALYZER	R&S	FSV 40	101022	2 YEARS	07/15/2019
COMPACT DIGITAL BAROMETER	CONTROL COMPANY	35519-055	91119547	3 YEARS	06/20/2017
DIGITAL THRMOMETER	CONTROL COMPANY	36934-164	191871994	2 YEARS	01/10/2019

Note: Equipment used meets the measurement uncertainty requirements as required per applicable standards for 95% confidence levels. Calibration due dates, unless defined specifically, falls on the last day of the month. Items indicated "N/A" for cal status either do not specifically require calibration or is internally characterized before use.



11 Revision History

Date	Report Name	Changes to report	Report prepared by
2020-06-10	EMC_MEIGR_010_20001_15.247_BT_DTS	Initial version	Yuchan Lu

<<The End>>