



# EMC TEST REPORT

**Applicant**      MobiWire SAS

**FCC ID**          QPN-H6511

**Product**        4G Smart Phone

**Brand**            MobiWire; MobiWire; Vodafone

**Model**            MobiWire H6511; MBW Vodafone Smart  
T23; Vodafone Pro 4G

**Report No.**      R2209A0850-E1

**Issue Date**      November 23, 2022

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC Code CFR47 Part15B (2021)/ ANSI C63.4-2014**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

*Liu Wei*

*Prepared by: Liu Wei*

*Fan Guangchang*

*Approved by: Fan Guangchang*

**TA Technology (Shanghai) Co., Ltd.**

*Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China*

*TEL: +86-021-50791141/2/3*

*FAX: +86-021-50791141/2/3-8000*



## Table of Contents

1	Test Laboratory.....	4
1.1	Notes of the Test Report.....	4
1.2	Test facility.....	4
1.3	Testing Location.....	4
2	General Description of Equipment under Test.....	5
2.1	Applicant and Manufacturer Information.....	5
2.2	General information.....	5
2.3	Applied Standards.....	7
2.4	Test Mode.....	8
3	Test Case Results.....	9
3.1	Radiated Emission.....	9
3.2	Conducted Emission.....	14
4	Uncertainty Measurement.....	17
5	Main Test Instruments.....	18
	ANNEX A: The EUT Appearance.....	19
	ANNEX B: Test Setup Photos.....	20



### Summary of measurement results

Number	Test Case	Clause in FCC Rules	Conclusion
1	Radiated Emission	FCC Part15.109, ANSI C63.4-2014	PASS
2	Conducted Emission	FCC Part15.107, ANSI C63.4-2014	PASS
Date of Testing: September 19, 2022 ~ November 14, 2022			
Date of Sample Received: September 15, 2022			
Note: All indications of Pass/Fail in this report are opinions expressed by TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.			

## 1 Test Laboratory

### 1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **TA Technology (Shanghai) Co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

### 1.2 Test facility

#### **FCC (Designation number: CN1179, Test Firm Registration Number: 446626)**

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform measurements.

#### **A2LA (Certificate Number: 3857.01)**

TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform measurement.

### 1.3 Testing Location

Company: TA Technology (Shanghai) Co., Ltd.  
Address: Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China  
City: Shanghai  
Post code: 201201  
Country: P. R. China  
Contact: Fan Guangchang  
Telephone: +86-021-50791141/2/3  
Fax: +86-021-50791141/2/3-8000  
Website: <http://www.ta-shanghai.com>  
E-mail: [fanguangchang@ta-shanghai.com](mailto:fanguangchang@ta-shanghai.com)

## 2 General Description of Equipment under Test

### 2.1 Applicant and Manufacturer Information

<b>Applicant</b>	MobiWire SAS
<b>Applicant address</b>	107 Boulevard de la Mission Marchand, 92400 Courbevoie, France.
<b>Manufacturer</b>	MobiWire SAS
<b>Manufacturer address</b>	107 Boulevard de la Mission Marchand, 92400 Courbevoie, France.

### 2.2 General information

EUT Description			
Device Type	Portable Device		
Model	MobiWire H6511; MBW Vodafone Smart T23; Vodafone Pro 4G		
IMEI	356662530000196		
HW Version	V00		
SW Version	MobiWire_H6511M_V01		
Power Rating	DC 3.8V		
Connecting I/O Port(s)	Please refer to the User's Manual.		
Antenna Type	Internal Antenna		
Frequency	Band	Tx (MHz)	Rx (MHz)
	GSM 850	824 ~ 849	869 ~ 894
	GSM 1900	1850 ~ 1910	1930 ~ 1990
	LTE Band 4	1710 ~ 1755	2110 ~ 2155
	LTE Band 5	824 ~ 849	869 ~ 894
	LTE Band 7	2500 ~ 2570	2620 ~ 2690
	LTE Band 40	2300 ~ 2400	2300 ~ 2400
	Bluetooth	2400 ~ 2483.5	2400 ~ 2483.5
	Wi-Fi 2.4G	2400 ~ 2483.5	2400 ~ 2483.5
	Wi-Fi 5G(U-NII-1)	5150 ~ 5250	5150 ~ 5250
	Wi-Fi 5G(U-NII-2A)	5250 ~ 5350	5250 ~ 5350
	Wi-Fi 5G(U-NII-2C)	5470 ~ 5725	5470 ~ 5725
	Wi-Fi 5G(U-NII-3)	5725 ~ 5850	5725 ~ 5850
EUT Accessory			
Adapter 1	Manufacturer: Jiangxi Jian Aohai Technology Co., Ltd. Model: A103A-050100U-AU2		



	Input: 100-240V~50/60Hz 0.2A Output: 5.0V $\overline{\text{---}}$ 1.0A 5.0W
Adapter 2	Manufacturer: Dongguan Aohai Technology Co., Ltd. Model: A18A-050100U-US2 Input: 100-240V~50/60Hz 0.2A Output: 5.0V $\overline{\text{---}}$ 1.0A 5.0W
Battery	Manufacturer: Shenzhen Aerospace Electronic Co.,Ltd. Model: 178249224 DC 3.8V, 2950mAh, 11.21Wh
Earphone	Manufacturer: JIU JIANG JUWEI ELECTRONICS CO.,LTD Model: JWEP0957-M01R
USB Cable	Manufacturer: SHENZHEN FKY-QY HARDWARE ELECTRONIC CO.,LTD Model: AM/MICRO5P 100cm Cable, Shielded
Auxiliary test equipment	
PC	PC Manufacturer: Microsoft tablet Model: 1724 (SN: 032324771953)
<p>Note:</p> <ol style="list-style-type: none"> <li>The EUT is sent from the applicant to TA and the information of the EUT is declared by the applicant.</li> <li>Radio equipment in band 40 is only allowed to operate from 2305 MHz to 2315 MHz for Subset 1; 2350 MHz to 2360 MHz for Subset 2 for the transmitter and receiver.</li> <li>There are more than one Adapter, each one should be applied throughout the compliance test respectively, however, only the worst case (Adapter 2) will be recorded in this report.</li> </ol>	

Item	Configure 1	Configure 2
Components on PCB changes	/	add second flash
LCD changes	/	add second flash
Others	The same	The same
<p>Note: Customer declaration, two configures is the same, except for flash. There are more than one Configure, each one should be applied throughout the compliance test respectively, and however, only the worst case (Configure 1) will be recorded in this report.</p>		

Three models: MobiWire H6511; MBW Vodafone Smart T23; Vodafone Pro 4G

The difference:

MBW Vodafone Smart T23; Vodafone Pro 4G:

1: Battery cover silkscreen logo is different.

MobiWire H6511 is same as Vodafone Pro 4G, no difference. And only the data for MobiWire H6511 is recorded in this report.



## 2.3 Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

### Test standards

**FCC Code CFR47 Part15B (2021)**

**ANSI C63.4-2014**

## 2.4 Test Mode

Test Mode	
Mode 1	Adapter +USB cable+ earphone + Front camera On + GSM/LTE/Bluetooth/ WLAN receiver
Mode 2	Adapter +USB cable+ earphone + Rear camera On + GSM/LTE/Bluetooth/ WLAN receiver
Mode 3	Adapter +USB cable+ earphone + GSM/LTE/Bluetooth/ WLAN receiver
Mode 4	Adapter + USB cable + earphone + FM(98MHz)
Mode 5	Adapter + USB cable + earphone + Mp4
Mode 6	USB Copy (PC with EUT) + USB cable + earphone
Mode 7	USB Copy (EUT with PC) + USB cable + earphone
Mode 8	USB Copy (SD card with PC) + USB cable + earphone
Mode 9	USB Copy (SD card with PC) + USB cable + earphone
Mode 10	Front Camera On +earphone + GSM/LTE/Bluetooth/ WLAN receiver
Mode 11	Rear Camera On +earphone + GSM/LTE/Bluetooth/ WLAN receiver
Mode 12	Earphone + MP4
Mode 13	Earphone + FM(98MHz)
Mode 14	Earphone + GSM//LTE/Bluetooth/ WLAN receiver

During the test, the preliminary test was performed in all modes with all Adapters, mode 6 with Adapter 2 is selected as the worst condition. The test data of the worst-case condition was recorded in this report.



### 3 Test Case Results

#### 3.1 Radiated Emission

##### Ambient condition

Temperature	Relative humidity	Pressure
15°C~35°C	30%~60%	101.5kPa

##### Methods of Measurement

The EUT is placed on a non-metallic table 0.8m above the horizontal metal reference ground plane. The distance between EUT and receive antenna should be 3 meters. During the test, the EUT was operating in its typical mode. The test method is according to ANSI C63.4-2014. Sweep the whole frequency band through the range from 30MHz to the 5th harmonic of the carrier. During the test, the height of receive antenna shall be moved from 1 to 4 meters, and the antenna shall be performed under horizontal and vertical polarization. The turn table shall be rotated from 0 to 360 degrees for detecting the maximum of radiated signal level.

The data of cable loss and antenna factor has been calibrated in full testing frequency range before the testing. During the test, the EUT is worked at maximum output power.

Set the spectrum analyzer in the following:

Below 1GHz:

RBW=100 kHz / VBW=300 kHz / Sweep=AUTO

Above 1GHz:

(a) PEAK Detector: RBW=1MHz / VBW=3MHz / Sweep=AUTO


(b) AVERAGE Detector: RBW=1MHz / VBW=3MHz / Sweep=AUTO

The radiated emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis). The worst emission was found in lie-down position (X axis) and the worst case was recorded.


During the test, EUT is connected to a laptop via a USB cable in the case of Transfer Data mode. The EUT is used as the peripheral equipment of the PC. The data is transferred from EUT to PC; PC is connected to server via a long LAN cable.

**Test Setup**

**Below 1GHz**



**Above 1GHz**



Note: Area side: 2.4mX3.6m

Antenna Tower meets ANSI C63.4 requirements for measurements above 1 GHz by keeping the antenna aimed at the EUT during the antenna's ascent/ descent along the antenna mast.


**Limits****Class B**

Frequency (MHz)	Field Strength (dB $\mu$ V/m)	Detector
30 -88	40.0	Quasi-peak
88-216	43.5	Quasi-peak
216 – 960	46.0	Quasi-peak
960-1000	54.0	Quasi-peak
1000-5 <sup>th</sup> harmonic of the highest frequency or 40GHz, which is lower	54 74	Average Peak

**Test Results**

Sweep the whole frequency band through the range from 30MHz to the 5th harmonic of the carrier. The Emissions in the frequency band 18GHz – 26.5GHz is more than 20dB below the limit are not reported.

The following graphs display the maximum values of horizontal and vertical by software. For above 1GHz, Blue trace uses the peak detection, Green trace uses the average detection. A symbol (  $\text{dB } \mu\text{V/m}$  ) in the test plot below means (dB $\mu\text{V/m}$ )




Radiated Emission from 30MHz to 1GHz

Frequency (MHz)	Quasi-Peak (dB $\mu\text{V/m}$ )	Limit (dB $\mu\text{V/m}$ )	Margin (dB)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)
48.04	16.38	40.00	23.62	100.0	V	271.00	21
145.10	29.53	43.50	13.97	100.0	V	172.00	15
174.71	30.38	43.50	13.12	175.0	H	50.00	16
241.70	28.28	46.00	17.72	109.0	H	107.00	19
281.32	29.91	46.00	16.09	100.0	H	83.00	20
384.03	37.91	46.00	8.09	100.0	H	347.00	23

**Remark: 1. Correction Factor = Antenna factor + Insertion loss(cable loss+amplifier gain)**

**2. Margin = Limit – Quasi-Peak**



Radiated Emission from 1GHz to 18GHz

Frequency (MHz)	MaxPeak (dB $\mu$ V/m)	Average (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Meas. Time (ms)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1170.00	---	24.71	54.00	29.29	500.00	100.0	H	146.00	-18
1197.63	34.51	---	74.00	39.49	500.00	100.0	H	142.00	-17
1858.50	---	24.09	54.00	29.91	500.00	200.0	V	63.00	-14
1858.50	36.29	---	74.00	37.71	500.00	100.0	H	55.00	-14
2587.38	37.49	---	74.00	36.51	500.00	200.0	H	0.00	-10
2617.13	---	25.98	54.00	28.02	500.00	200.0	V	4.00	-10
4191.75	---	30.05	54.00	23.95	500.00	200.0	H	197.00	-4
4223.63	41.60	---	74.00	32.40	500.00	100.0	V	307.00	-4
5664.38	44.10	---	74.00	29.90	500.00	100.0	V	342.00	-1
6085.13	---	32.33	54.00	21.67	500.00	200.0	H	228.00	-1
9723.13	44.00	---	74.00	30.00	500.00	200.0	V	13.00	2
10037.63	---	32.75	54.00	21.25	500.00	200.0	V	103.00	2

Remark: 1. Correction Factor = Antenna factor + Insertion loss (cable loss + amplifier gain)

2. Peak Margin = Limit - MAX Peak/ Average

### 3.2 Conducted Emission

#### Ambient condition


Temperature	Relative humidity	Pressure
15°C~35°C	30%~60%	101.5kPa

#### Methods of Measurement

The EUT is placed on a non-metallic table of 80cm height above the horizontal metal reference ground plane. During the test, the EUT was operating in its typical mode. The test method is according to ANSI C63.4-2014. Connect the AC power line of the EUT to the L.I.S.N. Use EMI receiver to detect the average and Quasi-peak value. RBW is set to 9 kHz, VBW is set to 30kHz. The measurement result should include both L line and N line.

During the test, EUT is connected to a laptop via a USB cable in the case of Transfer Data mode. The EUT is used as the peripheral equipment of the PC. The data is transferred from EUT to PC; PC is connected to server via a long LAN cable.

#### Test Setup



Note: Power Supply is AC Power source and it is used to change the voltage 120V/60Hz.


#### Limits

Frequency (MHz)	Conducted Limits(dBμV)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56 *	56 to 46 *
0.5 - 5	56	46
5 - 30	60	50

\*: Decreases with the logarithm of the frequency.

**Test Results**

Following plots, Blue trace uses the peak detection; Green trace uses the average detection.




Frequency (MHz)	QuasiPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.181500	55.27	---	64.42	9.15	1000.0	9.000	L1	ON	20.7
0.183750	---	36.42	54.31	17.89	1000.0	9.000	L1	ON	20.7
0.435750	30.19	---	57.14	26.95	1000.0	9.000	L1	ON	20.4
0.667500	---	25.20	46.00	20.80	1000.0	9.000	L1	ON	20.2
2.094000	---	20.64	46.00	25.36	1000.0	9.000	L1	ON	19.5
2.118750	32.03	---	56.00	23.97	1000.0	9.000	L1	ON	19.5
4.985250	36.44	---	56.00	19.56	1000.0	9.000	L1	ON	19.5
4.996500	---	23.72	46.00	22.28	1000.0	9.000	L1	ON	19.5
5.284500	---	22.81	50.00	27.19	1000.0	9.000	L1	ON	19.5
5.295750	38.14	---	60.00	21.86	1000.0	9.000	L1	ON	19.5
16.059750	27.95	---	60.00	32.05	1000.0	9.000	L1	ON	19.8
16.523250	---	21.24	50.00	28.76	1000.0	9.000	L1	ON	19.8

**Remark: Correct factor=cable loss + LISN factor**

L line

Conducted Emission from 150 KHz to 30 MHz



Frequency (MHz)	QuasiPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.181500	57.37	---	64.42	7.05	1000.0	9.000	N	ON	20.7
0.183750	---	39.02	54.31	15.29	1000.0	9.000	N	ON	20.7
0.363750	37.29	---	58.64	21.35	1000.0	9.000	N	ON	20.5
0.696750	---	23.27	46.00	22.73	1000.0	9.000	N	ON	20.2
1.063500	---	20.28	46.00	25.73	1000.0	9.000	N	ON	19.9
2.109750	32.36	---	56.00	23.64	1000.0	9.000	N	ON	19.5
2.989500	---	25.22	46.00	20.78	1000.0	9.000	N	ON	19.5
4.978500	37.85	---	56.00	18.15	1000.0	9.000	N	ON	19.5
5.291250	---	23.67	50.00	26.33	1000.0	9.000	N	ON	19.5
5.388000	39.39	---	60.00	20.61	1000.0	9.000	N	ON	19.5
16.449000	---	19.67	50.00	30.33	1000.0	9.000	N	ON	19.7
16.833750	27.41	---	60.00	32.60	1000.0	9.000	N	ON	19.8

Remark: Correct factor=cable loss + LISN factor

N line

Conducted Emission from 150 KHz to 30 MHz



## 4 Uncertainty Measurement

Case	Uncertainty	Factor k
Radiated Emission 30MHz – 200MHz	4.17 dB	1.96
Radiated Emission 200MHz – 1GHz	4.84 dB	1.96
Radiated Emission 1GHz – 18GHz	4.35 dB	1.96
Radiated Emission 18GHz – 26.5GHz	5.90 dB	1.96
Conducted Emission	2.57 dB	2



## 5 Main Test Instruments

Name of Equipment	Manufacturer	Type/Model	Serial Number	Calibration Date	Expiration Time
Radiated Emission					
EMI Test Receiver	R&S	ESR	102389	2022-05-25	2023-05-24
Signal Analyzer	R&S	FSV40	100816	2021-12-12	2022-12-11
TRILOG Broadband Antenna	SCHWARZBECK	VULB 9163	1023	2020-05-05	2023-05-04
Horn Antenna	R&S	HF907	102723	2020-08-11	2023-08-10
Horn Antenna	ETS-Lindgren	3160-09	00102643	2021-10-10	2024-10-09
Software	R&S	EMC32	9.26.01	/	/
Conducted Emission					
Artificial main network	R&S	ENV216	102191	2020-12-13	2022-12-12
EMI Test Receiver	R&S	ESR	101667	2022-05-25	2023-05-24
Software	R&S	EMC32	10.35.10	/	/

\*\*\*\*\*END OF REPORT \*\*\*\*\*



## ANNEX A: The EUT Appearance

The EUT Appearance are submitted separately.



## **ANNEX B: Test Setup Photos**

**The Test Setup Photos are submitted separately.**