

品名： WAG-F-LAG0-00-047 工规

History List

[illegible]

WAG-F-LAG0-00-047 Specification

1. Explanation of part number :

WAG F LAG0 00 047
(1) (2) (3) (4) (5)

(1) Product Type : Wireless Antenna

(2) Material : FPC

(3) Frequency : 1575.42Mhz , 2400-2500Mhz, 5150~5825Mhz

(4) Coaxial Cable Type : 00

(5) Suffix : 047

2. Electrical Specification :

2-1. Frequency Band:

Frequency Band	MHz
GPS,WIFI	1575.42Mhz , 2400-2500Mhz,5150~5825Mhz

2-2. Impedance

50 ohm nominal

UNLESS OTHER SPECIFIED TOLERANCES ON:

X=±2 X.X=±0.1 X.XX=±0.05

ANGLES=± HOLEDIA=±



佳邦科技股份有限公司

INPAQ TECHNOLOGY CO., LTD.

SCALE:

UNIT: mm

DRAWN BY: 尹猛

CHECKED BY:

DESIGNED BY: 余超

APPROVED BY: 范东亚

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE: WAG-F-LAG0-00-047 Specification

DOCUMENT
NO.

PAGE REV.
A0

2-3. VSWR ,Efficiency , and Active Data :

2-3.1 VSWR:

Frequency Band	1575.42	2400	2500	
2-3-1. Typical Value:	≤ 2	≤ 3	≤ 3.5	
2-3-2Measuring Method	1. A 50 Ω coaxial cable is connected to the fpcb antenna. Then this cable is connected to a network analyzer to measure the VSWR. 2. Keeping this jig away from metal at least 20 cm.			
2-3-3Picture				

2-4. Measure and Chamber

UNLESS OTHER SPECIFIED TOLERANCES ON:

X=±2 X.X=±0.1 X.XX=±0.05

ANGLES=± HOLEDIA=±

SCALE: UNIT: mm

DRAWN BY: 尹猛 CHECKED BY:

DESIGNED BY: 余超 APPROVED BY: 范东亚

TITLE: WAG-F-LAG0-00-047 Specification



佳邦科技股份有限公司
INPAQ TECHNOLOGY CO., LTD.

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION


DOCUMENT
NO.

PAGE REV.
A0

2-4-1 Measure method

1. Using a low loss coaxial cable to link a standard handset jig
2. Fixed this handset jig on chamber's rotator plane
3. Linking jig into network analyzer port and using a probing horn antenna to collect data.
4. Using another standard gain horn antenna to calibrated those data

2-4-2 Chamber definition



1. An anechoic chamber (8mx4mx3.5m) which satisfied far-field condition was applied to avoid multi-path effect
2. The quiet room region is 40cmx40cmx40cm at the center of rotator
3. The distance between DUT and standard antenna is 4.38 m
4. Probing antenna (9120D horn antenna) and standard gain horn antenna (BBHA9120 LPF 700MHz ~6GHz)

UNLESS OTHER SPECIFIED TOLERANCES ON:

X=±2 X.X=±0.1 X.XX=±0.05

ANGLES=± HOLEDIA=±

SCALE:

UNIT: mm

DRAWN BY: 尹猛

CHECKED BY:

DESIGNED BY: 余超

APPROVED BY: 范东亚

TITLE: WAG-F-LAG0-00-047 Specification



佳邦科技股份有限公司
INPAQ TECHNOLOGY CO., LTD.

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

DOCUMENT
NO.

PAGE REV.
A0

2-4-3 TRP/TIS

			SPEC	测试值	GAP
802.11 b	TRP	1	12.5	11.4	-1.12
		6	12.5	12.8	0.34
		13	12.5	12.7	0.21
	TIS	1			
		6			
		13			
802.11 g	TRP	1	11	11.3	0.3
		6	11	13.0	1.97
		13	11	12.9	1.87
	TIS	1			
		6			
		13			
802.11 n	TRP	1	11	12.4	1.35
		6	11	14.5	3.48
		13	11	13.7	2.66
	TIS	1			
		6			
		13			
5GHz 802.11a TRP(6M)/TIS(54M)	TRP	44	8.5	8.3	-0.19
		60	8.5	9.4	0.93
		165	8.5	8.6	0.06
	TIS	44			
		60			
		165			

GPS	SPEC	测试值	GAP
TIS	-143	-145.06	2.06

UNLESS OTHER SPECIFIED TOLERANCES ON:

X=±2 X.X=±0.1 X.XX=±0.05

ANGLES=± HOLEDIA=±



佳邦科技股份有限公司

INPAQ TECHNOLOGY CO., LTD.

SCALE:

UNIT: mm

DRAWN BY: 尹猛

CHECKED BY:

DESIGNED BY: 余超

APPROVED BY: 范东亚

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE: WAG-F-LAG0-00-047 Specification

DOCUMENT
NO.

PAGE REV.

A0

2-4-4 Antenna Efficiency

Frequency (MHz)	Peak Gain (dB)	Average Gain (dB)	Efficiency (%)
1570	-0.55	-4.52	35.35
1571	-0.44	-4.40	36.32
1572	-0.40	-4.32	36.96
1573	-0.39	-4.32	36.99
1574	-0.38	-4.35	36.69
1575	-0.40	-4.38	36.45
1575.42	-0.47	-4.43	36.05
1576	-0.52	-4.47	35.71
1577	-0.62	-4.50	35.48
1578	-0.60	-4.48	35.63
1579	-0.52	-4.43	36.02
1580	-0.42	-4.38	36.50
2400	-1.19	-4.52	35.32
2410	-1.22	-4.26	37.52
2420	-1.33	-4.24	37.66
2430	-1.95	-4.20	38.01
2440	-2.09	-4.11	38.83
2450	-2.06	-4.03	39.50
2460	-1.71	-4.06	39.29
2470	-1.17	-3.90	40.77
2480	-0.60	-4.01	39.70
2490	-0.48	-4.15	38.42
2500	-0.24	-4.34	36.84

UNLESS OTHER SPECIFIED TOLERANCES ON:
X=±2 X.X=±0.1 X.XX=±0.05
ANGLES=± HOLEDIA=±



佳邦科技股份有限公司
INPAQ TECHNOLOGY CO., LTD.

SCALE: UNIT: mm
DRAWN BY: 尹猛 CHECKED BY:
DESIGNED BY: 余超 APPROVED BY: 范东亚

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE: WAG-F-LAG0-00-047 Specification



DOCUMENT
NO.

PAGE REV.
A0

Frequency (MHz)	Peak Gain (dB)	Average Gain (dB)	Efficiency (%)
5150	-2.36	-7.68	17.05
5200	-2.23	-7.28	18.71
5250	-2.16	-7.05	19.73
5300	-1.93	-6.34	23.25
5350	-1.86	-6.13	24.38
5400	-1.77	-5.85	25.97
5450	-1.79	-5.91	25.64
5500	-1.66	-5.51	28.13
5550	-1.75	-5.79	26.34
5600	-1.76	-5.82	26.17
5650	-1.83	-6.02	24.98
5700	-1.91	-6.28	23.57
5750	-1.96	-6.45	22.65
5800	-2.00	-6.58	22.00
5850	-2.07	-6.79	20.96

3. Antenna Dimensions:

UNLESS OTHER SPECIFIED TOLERANCES ON: $X=\pm 2$ $X.X=\pm 0.1$ $X.XX=\pm 0.05$ ANGLES= $\pm$ HOLEDIA= $\pm$		 佳邦科技股份有限公司 INPAQ TECHNOLOGY CO., LTD.	
SCALE:	UNIT: mm	THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION	
DRAWN BY: 尹猛	CHECKED BY:		
DESIGNED BY: 余超	APPROVED BY: 范东亚		
TITLE: <u>WAG-F-LAG0-00-047</u> Specification		DOCUMENT NO.	PAGE REV. A0



UNLESS OTHER SPECIFIED TOLERANCES ON:
 $X=\pm 2$ $X.X=\pm 0.1$ $X.XX=\pm 0.05$
 ANGLES= $\pm$ HOLEDIA= $\pm$



佳邦科技股份有限公司
 INPAQ TECHNOLOGY CO., LTD.

SCALE: UNIT: mm
 DRAWN BY: 尹猛 CHECKED BY:
 DESIGNED BY: 余超 APPROVED BY: 范东亚

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE: WAG-F-LAG0-00-047 Specification

DOCUMENT
NO.

PAGE REV.
A0