

*EMC Test Report*

*Application for Grant of Equipment Authorization*

*Industry Canada RSS-Gen Issue 3 / RSS 210 Issue 8  
FCC Part 15, Subpart E*

*Model: WS-AP3710e*

FCC ID: QQD10E  
IC CERTIFICATION #: 5248S-10E

APPLICANT: Flextronics  
21 Richardson Side Road  
Kanata, ON K2K 2C1, Canada

TEST SITE(S): NTS Silicon Valley  
41039 Boyce Road.  
Fremont, CA. 94538-2435

IC SITE REGISTRATION #: 2845B-4, 2845B-5, 2845B-7


REPORT DATE: March 12, 2013

RE-ISSUED DATE: March 20, 2013

FINAL TEST DATES: January 18, 23, 24, 28, 29, 30, February 5, 6 and  
7, 2013


TOTAL NUMBER OF PAGES: 122

PROGRAM MGR /  
TECHNICAL REVIEWER:



David W. Bare  
Chief Engineer

QUALITY ASSURANCE DELEGATE /  
FINAL REPORT PREPARER:



David Guidotti  
Senior Technical Writer



NTS Silicon Valley is accredited by the A2LA, certificate number 0214.26, to perform the test(s) listed in this report, except where noted otherwise. This report and the information contained herein represent the results of testing test articles identified and selected by the client performed to specifications and/or procedures selected by the client. National Technical Systems (NTS) makes no representations, expressed or implied, that such testing is adequate (or inadequate) to demonstrate efficiency, performance, reliability, or any other characteristic of the articles being tested, or similar products. This report should not be relied upon as an endorsement or certification by NTS of the equipment tested, nor does it represent any statement whatsoever as to its merchantability or fitness of the test article, or similar products, for a particular purpose. This report shall not be reproduced except in full

**REVISION HISTORY**

| Rev# | Date       | Comments  | Modified By |
|------|------------|---|-------------|
| -    | 03-12-2013 | Initial release   |             |
| 1    | 03-19-2013 | Added tabular data for 240 MHz emissions and additional plots for power showing compliance with 20dB BW at 5250 MHz | Dwb         |
| 2    | 03-20-2013 | Revised the tabular test data with the actual frequency instead of the transition frequency of 240 MHz              | DWB<br>DMG  |

**TABLE OF CONTENTS**

|  |            |
|--|------------|
| <b>REVISION HISTORY .....</b>  | <b>2</b>   |
| <b>TABLE OF CONTENTS .....</b>   | <b>3</b>   |
| <b>SCOPE.....</b>  | <b>4</b>   |
| <b>OBJECTIVE .....</b>   | <b>4</b>   |
| <b>STATEMENT OF COMPLIANCE.....</b>  | <b>5</b>   |
| <b>DEVIATIONS FROM THE STANDARDS.....</b>  | <b>5</b>   |
| <b>TEST RESULTS SUMMARY .....</b>  | <b>6</b>   |
| UNII / LELAN DEVICES .....   | 6          |
| GENERAL REQUIREMENTS APPLICABLE TO ALL BANDS.....                                  | 7          |
| MEASUREMENT UNCERTAINTIES.....   | 8          |
| <b>EQUIPMENT UNDER TEST (EUT) DETAILS.....</b>                                     | <b>9</b>   |
| GENERAL.....   | 9          |
| ANTENNA SYSTEM .....   | 9          |
| ENCLOSURE.....   | 9          |
| MODIFICATIONS.....   | 9          |
| SUPPORT EQUIPMENT.....   | 9          |
| EUT INTERFACE PORTS .....  | 10         |
| EUT OPERATION .....  | 10         |
| <b>TEST SITE.....</b>  | <b>11</b>  |
| GENERAL INFORMATION .....  | 11         |
| CONDUCTED EMISSIONS CONSIDERATIONS .....   | 11         |
| RADIATED EMISSIONS CONSIDERATIONS .....  | 11         |
| <b>MEASUREMENT INSTRUMENTATION .....</b>   | <b>12</b>  |
| RECEIVER SYSTEM .....  | 12         |
| INSTRUMENT CONTROL COMPUTER .....  | 12         |
| LINE IMPEDANCE STABILIZATION NETWORK (LISN).....                                   | 12         |
| FILTERS/ATTENUATORS .....  | 13         |
| ANTENNAS.....  | 13         |
| ANTENNA MAST AND EQUIPMENT TURNTABLE.....  | 13         |
| INSTRUMENT CALIBRATION.....  | 13         |
| <b>TEST PROCEDURES .....</b>   | <b>14</b>  |
| EUT AND CABLE PLACEMENT .....  | 14         |
| CONDUCTED EMISSIONS.....   | 14         |
| RADIATED EMISSIONS.....  | 15         |
| CONDUCTED EMISSIONS FROM ANTENNA PORT .....  | 17         |
| BANDWIDTH MEASUREMENTS .....   | 17         |
| SPECIFICATION LIMITS AND SAMPLE CALCULATIONS.....                                  | 18         |
| CONDUCTED EMISSIONS SPECIFICATION LIMITS: FCC 15.207; FCC 15.107(A), RSS GEN ..... | 18         |
| GENERAL TRANSMITTER RADIATED EMISSIONS SPECIFICATION LIMITS .....                  | 19         |
| RECEIVER RADIATED SPURIOUS EMISSIONS SPECIFICATION LIMITS .....                    | 19         |
| FCC 15.407 (A) OUTPUT POWER LIMITS .....   | 20         |
| OUTPUT POWER LIMITS –LELAN DEVICES.....  | 20         |
| SPURIOUS EMISSIONS LIMITS –UNII AND LELAN DEVICES .....                            | 21         |
| SAMPLE CALCULATIONS - CONDUCTED EMISSIONS .....                                    | 21         |
| SAMPLE CALCULATIONS - RADIATED EMISSIONS.....                                      | 21         |
| SAMPLE CALCULATIONS - FIELD STRENGTH TO EIRP CONVERSION.....                       | 22         |
| <b>APPENDIX A TEST EQUIPMENT CALIBRATION DATA .....</b>                            | <b>23</b>  |
| <b>APPENDIX B TEST DATA .....</b>  | <b>24</b>  |
| <b>END OF REPORT .....</b>   | <b>122</b> |

## SCOPE

An electromagnetic emissions test has been performed on the Flextronics model WS-AP3710e, pursuant to the following rules:

Industry Canada RSS-Gen Issue 3

RSS 210 Issue 8 "Low-power Licence-exempt Radiocommunication Devices (All Frequency Bands): Category I Equipment"

FCC Part 15, Subpart E requirements for UNII Devices (using FCC KDB 789033)

Conducted and radiated emissions data has been collected, reduced, and analyzed within this report in accordance with measurement guidelines set forth in the following reference standards and as outlined in NTS Silicon Valley test procedures:

ANSI C63.4:2003

FCC UNII test procedure KDB 789033

The intentional radiator above has been tested in a simulated typical installation to demonstrate compliance with the relevant Industry Canada performance and procedural standards.

Final system data was gathered in a mode that tended to maximize emissions by varying orientation of EUT, orientation of power and I/O cabling, antenna search height, and antenna polarization.

Every practical effort was made to perform an impartial test using appropriate test equipment of known calibration. All pertinent factors have been applied to reach the determination of compliance.

## OBJECTIVE

The primary objective of the manufacturer is compliance with the regulations outlined in the previous section.

Prior to marketing in the USA, all unlicensed transmitters and transceivers require certification. Receive-only devices operating between 30 MHz and 960 MHz are subject to either certification or a manufacturer's declaration of conformity, with all other receive-only devices exempt from the technical requirements.

Prior to marketing in Canada, Class I transmitters, receivers and transceivers require certification. Class II devices are required to meet the appropriate technical requirements but are exempt from certification requirements.

Certification is a procedure where the manufacturer submits test data and technical information to a certification body and receives a certificate or grant of equipment authorization upon successful completion of the certification body's review of the submitted documents. Once the equipment authorization has been obtained, the label indicating compliance must be attached to all identical units, which are subsequently manufactured.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product which may result in increased emissions should be checked to ensure compliance has been maintained (i.e., printed circuit board layout changes, different line filter, different power supply, harnessing or I/O cable changes, etc.).

#### **STATEMENT OF COMPLIANCE**

The tested sample of Flextronics model WS-AP3710e complied with the requirements of the following regulations:

RSS 210 Issue 8 "Low-power Licence-exempt Radiocommunication Devices (All Frequency Bands): Category I Equipment"

FCC Part 15, Subpart E requirements for UNII Devices

Maintenance of compliance is the responsibility of the manufacturer. Any modifications to the product should be assessed to determine their potential impact on the compliance status of the device with respect to the standards detailed in this test report.

The test results recorded herein are based on a single type test of Flextronics model WS-AP3710e and therefore apply only to the tested sample. The sample was selected and prepared by Georges Fares of Flextronics.

#### **DEVIATIONS FROM THE STANDARDS**

No deviations were made from the published requirements listed in the scope of this report.

**TEST RESULTS SUMMARY****UNII / LELAN DEVICES****Operation in the 5.15 – 5.25 GHz Band**

| FCC Rule Part   | RSS Rule Part       | Description            | Measured Value / Comments                              | Limit / Requirement  | Result   |
|---|---------------------|------------------------|--|--|----------|
| 15.407(e)   | A9.2(1)             | Indoor operation only  | Refer to user's manual                                 | N/A  | Complies |
| 15.407(a)(2)  |                     | Min. 26dB Bandwidth    | a: 23.2 MHz<br>n20: 24.2 MHz<br>n40: 47.8 MHz          | N/A – limits output power if < 20MHz                           | N/A      |
| 15.407 (a)(1)   |                     | Output Power           | 802.11a: 14.7 dBm<br>n20: 15.0 dBm<br>n40: 16.5 dBm    | a: 16.2dBm <sup>2</sup><br>n20: 17.0<br>n40: 17.0              | Complies |
|   | A9.2(1)             |                        | (Max eirp: 0.155 W) <sup>1</sup>                       | a: 15.5dBm <sup>3</sup><br>n20: 16.6 <sup>3</sup><br>n40: 17.0 | Complies |
| 15.407 (a)(1)   | -                   | Power Spectral Density | a: 3.1 dBm/MHz<br>n20: 2.9 dBm/MHz<br>n40: 1.6 dBm/MHz | 3.2 <sup>4</sup> dBm/MHz                                       | Complies |
| -   | A9.2 (1)<br>A9.4(2) |                        |  | 3.2 <sup>4</sup> dBm/MHz                                       | Complies |
| Note 1: EIRP calculated using antenna gain of 9.8 dBi (three 5 dBi antennas) for the highest EIRP system in legacy mode.  |                     |                        |  |  |          |
| Note 2: Limit reduced to 16.2 dBm from 17 dBm as effective antenna gain exceeded 6 dBi by 0.8 dBi for highest output legacy mode.   |                     |                        |  |  |          |
| Note 3: Limit reduced to 15.5/16.8 dBm from 17 dBm as effective antenna gain exceeded 6 dBi by 0.8 dBi for highest output legacy mode and the minimum 99% BW is 16.9/18.0 MHz for 20 MHz modes. |                     |                        |  |  |          |
| Note 4: Limit reduced to 3.2 dBm from 4 dBm as effective antenna gain exceeded 6 dBi by 0.8 dBi for the highest output.   |                     |                        |  |  |          |

**Requirements for all U-NII/LELAN bands**

| FCC Rule Part         | RSS Rule Part     | Description                   | Measured Value / Comments                                    | Limit / Requirement   | Result   |
|-----------------------|-------------------|-------------------------------|--|---|----------|
| 15.407                | A9.4(1)           | Modulation                    | System uses 802.11a/n techniques                             | Digital modulation is required  | Complies |
| 15.407(b)(5) / 15.209 | A9.2(1) / RSS-GEN | Spurious Emissions below 1GHz | 41.4 dBμV/m @ 110.77 MHz (-2.1 dB)                           | Refer to page 21  | Complies |
| 15.407(b)(5) / 15.209 | A9.2(1) / RSS-GEN | Spurious Emissions above 1GHz | 53.6 dBμV/m @ 5150.0 MHz (-0.4 dB)                           |   | Complies |
| 15.407(a)(6)          | -                 | Peak Excursion Ratio          | a: 9.0 dB<br>n20: 8.7 dB<br>n40: 8.9 dB                      | < 13dB  | Complies |
|                       | A9.4(3)           | Channel Selection             | Spurious emissions tested at outermost channels in each band | Device was tested on the top, bottom and center channels in each band | N/A      |
| 15                    |                   |                               | Measurements on three channels in each band                  |   |          |

| FCC Rule Part | RSS Rule Part | Description   | Measured Value / Comments   | Limit / Requirement  | Result   |
|---------------|---------------|---|---|--|----------|
| 15.407 (c)    | A9.4(4)       | Operation in the absence of information to transmit       | Operation is discontinued in the absence of information (See Operational Description)     | Device shall automatically discontinue operation in the absence of information to transmit | Complies |
| 15.407 (g)    |               | Frequency Stability                                       | Frequency stability is such that the signal remains in band (See Operational Description) | Signal shall remain within the allocated band  | Complies |
| 15.407 (h2)   | A9.3          | Dynamic frequency Selection (device with radar detection) | Device does not operate in either 5470 – 5725 or 5250 – 5350 MHz bands.                   |  | N/A      |
|               | A9.4(6) & (7) | User Manual information                                   | Refer to User Manual for details  | Warning regarding interference from Satellite Systems                                      | Complies |

**GENERAL REQUIREMENTS APPLICABLE TO ALL BANDS**

| FCC Rule Part                | RSS Rule part                                  | Description              | Measured Value / Comments  | Limit / Requirement                            | Result (margin) |
|------------------------------|--|--------------------------|--|--|-----------------|
| 15.203                       | -  | RF Connector             | Integral antenna   | Unique or integral antenna required            | Complies        |
| 15.207                       | RSS GEN Table 2                                | AC Conducted Emissions   | 36.1 dB $\mu$ V @ 0.377 MHz (-13.2 dB)                                     | Refer to page 18                               | Complies        |
| 15.247 (b) (5)<br>15.407 (f) | RSS 102  | RF Exposure Requirements | Refer to MPE calculations, RSS 102 declaration and User Manual statements. | Refer to OET 65, FCC Part 1 and RSS 102        | Complies        |
| -                            | RSP 100<br>RSS GEN 7.1.3                       | User Manual              | Refer to User Manual for details   | Statement required regarding non-interference  | Complies        |
| -                            | RSP 100<br>RSS GEN 7.1.2                       | User Manual              | Refer to User Manual for details   | Statement for products with detachable antenna | Complies        |
| -                            | RSP 100<br>RSS GEN 4.4.1<br>RSS-210<br>A9.2(1) | Max. 99% Bandwidth       | a: 16.9 MHz<br>n20: 18.1 MHz<br>n40: 36.5 MHz                              | Information only                               | N/A             |

**MEASUREMENT UNCERTAINTIES**

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level and were calculated in accordance with UKAS document LAB 34.

| Measurement Type                        | Measurement Unit | Frequency Range   | Expanded Uncertainty |
|---|------------------|-------------------|----------------------|
| RF power, conducted (power meter)       | dBm              | 25 to 7000 MHz    | $\pm 0.52$ dB        |
| RF power, conducted (Spectrum analyzer) | dBm              | 25 to 7000 MHz    | $\pm 0.7$ dB         |
| Conducted emission of transmitter       | dBm              | 25 to 26500 MHz   | $\pm 0.7$ dB         |
| Conducted emission of receiver          | dBm              | 25 to 26500 MHz   | $\pm 0.7$ dB         |
| Radiated emission (substitution method) | dBm              | 25 to 26500 MHz   | $\pm 2.5$ dB         |
| Radiated emission (field strength)      | dB $\mu$ V/m     | 25 to 1000 MHz    | $\pm 3.6$ dB         |
|   |                  | 1000 to 40000 MHz | $\pm 6.0$ dB         |
| Conducted Emissions (AC Power)          | dB $\mu$ V       | 0.15 to 30 MHz    | $\pm 2.4$ dB         |



**EQUIPMENT UNDER TEST (EUT) DETAILS****GENERAL**

The Flextronics model WS-AP3710e is a multiple radio access point, each radio operating in 3x3 MIMO and legacy modes. It incorporates both a 2.4 GHz band 802.11b/g/n and a 5.2 GHz band and 5.8 GHz band 802.11a/n radio in a single enclosure. Since the EUT could be placed in any position during operation, the EUT was treated as table-top equipment during testing to simulate the end-user environment. The electrical rating of the EUT is 48 Volts DC, 0.8 Amps.

The sample was received on January 15, 2013 and tested on January 18, 23, 24, 28, 29, 30, February 5, 6 and 7, 2013. The EUT consisted of the following component(s):

| Company     | Model      | Description  | Serial Number | FCC ID |
|-------------|------------|--------------|---------------|--------|
| Flextronics | WS-AP3710e | Access Point | None          | QQD10E |

**ANTENNA SYSTEM**

The antenna system consists of a 6 element Omni antenna (gain of 2.0dBi), two Sector antennas (gain of 5 dBi) or two 3 element Panel antennas (gain of 3 dBi in the 2.4 GHz band and 4 dBi in the 5.8 GHz band). When two antennas are used, they are the same for both radios.

| Model         | Application | Description             | Gain (dBi)         | Frequency (GHz)          | Connector type |
|---------------|-------------|-------------------------|--------------------|--------------------------|----------------|
| WS-AI-DX02360 | Indoor      | MIMO, Dual-band         | 2 dBi              | 2.4 – 2.5<br>5.15 – 5.85 | RSMA           |
| WS-AI-DT04360 | Indoor      | MIMO, Panel             | 3.0 dBi<br>4.0 dBi | 2.4 – 2.5<br>4.9 – 5.9   | RSMA           |
| WS-AI-DT05120 | Indoor      | MIMO, Sector, dual-band | 5 dBi              | 2.3 – 2.7<br>4.9 – 6.1   | RSMA           |

**ENCLOSURE**

The EUT enclosure measures approximately 20 by 18.5 by 3 centimeters. It is constructed of uncoated plastic and cast metal.

**MODIFICATIONS**

No modifications were made to the EUT during the time the product was at NTS Silicon Valley.

**SUPPORT EQUIPMENT**

The following equipment was used as remote support equipment for emissions testing:

| Company    | Model         | Description     | Serial Number      | FCC ID |
|------------|---------------|-----------------|--------------------|--------|
| PowerDsine | 9001G-40/SP   | POE adapter     | N11456519001846A01 | -      |
| Dell       | Latitude D610 | Laptop Computer | 26895386773        | -      |

**EUT INTERFACE PORTS**

The I/O cabling configuration during testing was as follows:

| Port                      | Connected To                 | Description | Cable(s)               |           |
|---------------------------|------------------------------|-------------|------------------------|-----------|
|                           |                              |             | Shielded or Unshielded | Length(m) |
| Ethernet/POE              | Remote POE adapter or switch | Cat 5       | Unshielded             | 10        |
| Remote POE Data or switch | Laptop                       | Cat 5       | Unshielded             | 2         |

The console port was not connected during testing as this is used only during configuration of the radio.

**EUT OPERATION**

During testing, the EUT was configured to transmit a continuous modulated signal at the selected frequency and power level on all three chains of both radios.

## TEST SITE

### GENERAL INFORMATION

Final test measurements were taken at the test sites listed below. Pursuant to section 2.948 of the FCC's Rules and section 3.3 of RSP-100, construction, calibration, and equipment data has been filed with the Commission and with industry Canada.

| Site      | Registration Numbers |         | Location                                   |
|-----------|----------------------|---------|--|
|           | FCC                  | Canada  |  |
| Chamber 7 | A2LA accreditation   | 2845B-7 | 41039 Boyce Road<br>Fremont, CA 94538-2435 |

ANSI C63.4:2003 recommends that ambient noise at the test site be at least 6 dB below the allowable limits. Ambient levels are below this requirement. The test site(s) contain separate areas for radiated and conducted emissions testing. Considerable engineering effort has been expended to ensure that the facilities conform to all pertinent requirements of ANSI C63.4:2003.

### CONDUCTED EMISSIONS CONSIDERATIONS

Conducted emissions testing is performed in conformance with ANSI C63.4:2003. Measurements are made with the EUT connected to the public power network through a nominal, standardized RF impedance, which is provided by a line impedance stabilization network, known as a LISN. A LISN is inserted in series with each current-carrying conductor in the EUT power cord.

### RADIATED EMISSIONS CONSIDERATIONS

The FCC has determined that radiation measurements made in a shielded enclosure are not suitable for determining levels of radiated emissions. Radiated measurements are performed in an open field environment or in a semi-anechoic chamber. The test sites are maintained free of conductive objects within the CISPR defined elliptical area incorporated in ANSI C63.4:2003 guidelines and meet the Normalized Site Attenuation (NSA) requirements of ANSI C63.4:2003.

## **MEASUREMENT INSTRUMENTATION**

### **RECEIVER SYSTEM**

An EMI receiver as specified in CISPR 16-1-1 is used for emissions measurements. The receivers used can measure over the frequency range of 9 kHz up to 2000 MHz. These receivers allow both ease of measurement and high accuracy to be achieved. The receivers have Peak, Average, and CISPR (Quasi-peak) detectors built into their design so no external adapters are necessary. The receiver automatically sets the required bandwidth for the CISPR detector used during measurements. If the repetition frequency of the signal being measured is below 20Hz, peak measurements are made in lieu of Quasi-Peak measurements.

For measurements above the frequency range of the receivers, a spectrum analyzer is utilized because it provides visibility of the entire spectrum along with the precision and versatility required to support engineering analysis. Average measurements above 1000MHz are performed on the spectrum analyzer using the linear-average method with a resolution bandwidth of 1 MHz and a video bandwidth of 10 Hz, unless the signal is pulsed in which case the average (or video) bandwidth of the measuring instrument is reduced to onset of pulse desensitization and then increased.

### **INSTRUMENT CONTROL COMPUTER**

The receivers utilize either a Rohde & Schwarz EZM Spectrum Monitor/Controller or contain an internal Spectrum Monitor/Controller to view and convert the receiver measurements to the field strength at an antenna or voltage developed at the LISN measurement port, which is then compared directly with the appropriate specification limit. This provides faster, more accurate readings by performing the conversions described under Sample Calculations within the Test Procedures section of this report. Results are printed in a graphic and/or tabular format, as appropriate. A personal computer is used to record all measurements made with the receivers.

The Spectrum Monitor provides a visual display of the signal being measured. In addition, the controller or a personal computer run automated data collection programs which control the receivers. This provides added accuracy since all site correction factors, such as cable loss and antenna factors are added automatically.

### **LINE IMPEDANCE STABILIZATION NETWORK (LISN)**

Line conducted measurements utilize a fifty microhenry Line Impedance Stabilization Network as the monitoring point. The LISN used also contains a 250 uH CISPR adapter. This network provides for calibrated radio frequency noise measurements by the design of the internal low pass and high pass filters on the EUT and measurement ports, respectively.

### ***FILTERS/ATTENUATORS***

External filters and precision attenuators are often connected between the receiving antenna or LISN and the receiver. This eliminates saturation effects and non-linear operation due to high amplitude transient events.

### ***ANTENNAS***

A loop antenna is used below 30 MHz. For the measurement range 30 MHz to 1000 MHz either a combination of a biconical antenna and a log periodic or a bi-log antenna is used. Above 1000 MHz, horn antennas are used. The antenna calibration factors to convert the received voltage to an electric field strength are included with appropriate cable loss and amplifier gain factors to determine an overall site factor, which is then programmed into the test receivers or incorporated into the test software.

### ***ANTENNA MAST AND EQUIPMENT TURNTABLE***

The antennas used to measure the radiated electric field strength are mounted on a non-conductive antenna mast equipped with a motor-drive to vary the antenna height. Measurements below 30 MHz are made with the loop antenna at a fixed height of 1m above the ground plane.

ANSI C63.4:2003 specifies that the test height above ground for table mounted devices shall be 80 centimeters. Floor mounted equipment shall be placed on the ground plane if the device is normally used on a conductive floor or separated from the ground plane by insulating material from 3 to 12 mm if the device is normally used on a non-conductive floor. During radiated measurements, the EUT is positioned on a motorized turntable in conformance with this requirement.

### ***INSTRUMENT CALIBRATION***

All test equipment is regularly checked to ensure that performance is maintained in accordance with the manufacturer's specifications. All antennas are calibrated at regular intervals with respect to tuned half-wave dipoles. An exhibit of this report contains the list of test equipment used and calibration information.


## TEST PROCEDURES

### EUT AND CABLE PLACEMENT

The regulations require that interconnecting cables be connected to the available ports of the unit and that the placement of the unit and the attached cables simulate the worst case orientation that can be expected from a typical installation, so far as practicable. To this end, the position of the unit and associated cabling is varied within the guidelines of ANSI C63.4:2003, and the worst-case orientation is used for final measurements.

### CONDUCTED EMISSIONS

Conducted emissions are measured at the plug end of the power cord supplied with the EUT. Excess power cord length is wrapped in a bundle between 30 and 40 centimeters in length near the center of the cord. Preliminary measurements are made to determine the highest amplitude emission relative to the specification limit for all the modes of operation. Placement of system components and varying of cable positions are performed in each mode. A final peak mode scan is then performed in the position and mode for which the highest emission was noted on all current carrying conductors of the power cord.



**Figure 1 Typical Conducted Emissions Test Configuration**


**RADIATED EMISSIONS**

A preliminary scan of the radiated emissions is performed in which all significant EUT frequencies are identified with the system in a nominal configuration. At least two scans are performed, one scan for each antenna polarization (horizontal and vertical; loop parallel and perpendicular to the EUT). During the preliminary scans, the EUT is rotated through 360°, the antenna height is varied (for measurements above 30 MHz) and cable positions are varied to determine the highest emission relative to the limit. Preliminary scans may be performed in a fully anechoic chamber for the purposes of identifying the frequencies of the highest emissions from the EUT.


A speaker is provided in the receiver to aid in discriminating between EUT and ambient emissions. Other methods used during the preliminary scan for EUT emissions involve scanning with near field magnetic loops, monitoring I/O cables with RF current clamps, and cycling power to the EUT.

Final maximization is a phase in which the highest amplitude emissions identified in the spectral search are viewed while the EUT azimuth angle is varied from 0 to 360 degrees relative to the receiving antenna. The azimuth, which results in the highest emission is then maintained while varying the antenna height from one to four meters (for measurements above 30 MHz, measurements below 30 MHz are made with the loop antenna at a fixed height of 1m). The result is the identification of the highest amplitude for each of the highest peaks. Each recorded level is corrected in the receiver using appropriate factors for cables, connectors, antennas, and preamplifier gain.

When testing above 18 GHz, the receive antenna is located at 1 meter from the EUT and the antenna height is restricted to a maximum of 2.5 meters.




Typical Test Configuration for Radiated Field Strength Measurements



The anechoic materials on the walls and ceiling ensure compliance with the normalized site attenuation requirements of CISPR 16 / CISPR 22 / ANSI C63.4 for an alternate test site at the measurement distances used.

Floor-standing equipment is placed on the floor with insulating supports between the unit and the ground plane.




Test Configuration for Radiated Field Strength Measurements  
Semi-Anechoic Chamber, Plan and Side Views



**CONDUCTED EMISSIONS FROM ANTENNA PORT**

Direct measurements of power, bandwidth and power spectral density are performed, where possible, with the antenna port of the EUT connected to either the power meter or spectrum analyzer via a suitable attenuator and/or filter. These are used to ensure that the front end of the measurement instrument is not overloaded by the fundamental transmission.

**Test Configuration for Antenna Port Measurements**

Measurement bandwidths (video and resolution) are set in accordance with the relevant standards and NTS Silicon Valley's test procedures for the type of radio being tested. When power measurements are made using a resolution bandwidth less than the signal bandwidth the power is calculated by summing the power across the signal bandwidth using either the analyzer channel power function or by capturing the trace data and calculating the power using software. In both cases the summed power is corrected to account for the equivalent noise bandwidth (ENBW) of the resolution bandwidth used.

If power averaging is used (typically for certain digital modulation techniques), the EUT is configured to transmit continuously. Power averaging is performed using either the built-in function of the analyzer or, if the analyzer does not feature power averaging, using external software. In both cases the average power is calculated over a number of sweeps (typically 100). When the EUT cannot be configured to continuously transmit then either the analyzer is configured to perform a gated sweep to ensure that the power is averaged over periods that the device is transmitting or power averaging is disabled and a max-hold feature is used.

If a power meter is used to make output power measurements the sensor head type (peak or average) is stated in the test data table.

**BANDWIDTH MEASUREMENTS**

The 6dB, 20dB and/or 26dB signal bandwidth is measured in using the bandwidths recommended by ANSI C63.4. When required, the 99% bandwidth is measured using the methods detailed in RSS GEN.

**SPECIFICATION LIMITS AND SAMPLE CALCULATIONS**

The limits for conducted emissions are given in units of microvolts, and the limits for radiated emissions are given in units of microvolts per meter at a specified test distance. Data is measured in the logarithmic form of decibels relative to one microvolt, or dB microvolts (dBuV). For radiated emissions, the measured data is converted to the field strength at the antenna in dB microvolts per meter (dBuV/m). The results are then converted to the linear forms of uV and uV/m for comparison to published specifications.

For reference, converting the specification limits from linear to decibel form is accomplished by taking the base ten logarithm, then multiplying by 20. These limits in both linear and logarithmic form are as follows:

**CONDUCTED EMISSIONS SPECIFICATION LIMITS: FCC 15.207; FCC 15.107(a), RSS GEN**

The table below shows the limits for the emissions on the AC power line from an intentional radiator and a receiver.

| Frequency<br>(MHz) | Average<br>Limit<br>(dBuV)   | Quasi Peak<br>Limit<br>(dBuV)  |
|--------------------|--|--|
| 0.150 to 0.500     | Linear decrease on<br>logarithmic frequency<br>axis<br>between 56.0 and 46.0 | Linear decrease on<br>logarithmic frequency<br>axis<br>between 66.0 and 56.0 |
| 0.500 to 5.000     | 46.0   | 56.0   |
| 5.000 to 30.000    | 50.0   | 60.0   |

**GENERAL TRANSMITTER RADIATED EMISSIONS SPECIFICATION LIMITS**

The table below shows the limits for the spurious emissions from transmitters that fall in restricted bands<sup>1</sup> (with the exception of transmitters operating under FCC Part 15 Subpart D and RSS 210 Annex 9), the limits for all emissions from a low power device operating under the general rules of RSS 310 (tables 3 and 4), RSS 210 (table 2) and FCC Part 15 Subpart C section 15.209.

| Frequency Range (MHz) | Limit (uV/m)                 | Limit (dBuV/m @ 3m)                                  |
|-----------------------|------------------------------|--|
| 0.009-0.490           | 2400/F <sub>KHz</sub> @ 300m | 67.6-20*log <sub>10</sub> (F <sub>KHz</sub> ) @ 300m |
| 0.490-1.705           | 24000/F <sub>KHz</sub> @ 30m | 87.6-20*log <sub>10</sub> (F <sub>KHz</sub> ) @ 30m  |
| 1.705 to 30           | 30 @ 30m                     | 29.5 @ 30m   |
| 30 to 88              | 100 @ 3m                     | 40 @ 3m  |
| 88 to 216             | 150 @ 3m                     | 43.5 @ 3m  |
| 216 to 960            | 200 @ 3m                     | 46.0 @ 3m  |
| Above 960             | 500 @ 3m                     | 54.0 @ 3m  |

**RECEIVER RADIATED SPURIOUS EMISSIONS SPECIFICATION LIMITS**

The table below shows the limits for the spurious emissions from receivers as detailed in FCC Part 15.109, RSS 210 Table 2, RSS GEN Table 1 and RSS 310 Table 3. Note that receivers operating outside of the frequency range 30 MHz – 960 MHz are exempt from the requirements of 15.109.

| Frequency Range (MHz) | Limit (uV/m @ 3m) | Limit (dBuV/m @ 3m) |
|-----------------------|-------------------|---------------------|
| 30 to 88              | 100               | 40                  |
| 88 to 216             | 150               | 43.5                |
| 216 to 960            | 200               | 46.0                |
| Above 960             | 500               | 54.0                |

<sup>1</sup> The restricted bands are detailed in FCC 15.203, RSS 210 Table 1 and RSS 310 Table 2

**FCC 15.407 (a) OUTPUT POWER LIMITS**

The table below shows the limits for output power and output power density. Where the signal bandwidth is less than 20 MHz the maximum output power is reduced to the power spectral density limit plus 10 times the log of the bandwidth (in MHz).

| Operating Frequency (MHz) | Output Power     | Power Spectral Density |
|---------------------------|------------------|------------------------|
| 5150 – 5250               | 50mW (17 dBm)    | 4 dBm/MHz              |
| 5250 – 5350               | 250 mW (24 dBm)  | 11 dBm/MHz             |
| 5725 – 5825               | 1 Watts (30 dBm) | 17 dBm/MHz             |

For system using antennas with gains exceeding 6dBi, the output power and power spectral density limits are reduced by 1dB for every dB the antenna gain exceeds 6dBi. Fixed point-to-point applications using the 5725 – 5825 MHz band may use antennas with gains of up to 23dBi without this limitation. If the gain exceeds 23dBi then the output power limit of 1 Watt is reduced by 1dB for every dB the gain exceeds 23dBi.

The peak excursion envelope is limited to 13dB.

**OUTPUT POWER LIMITS –LELAN DEVICES**

The table below shows the limits for output power and output power density defined by RSS 210. Where the signal bandwidth is less than 20 MHz the maximum output power is reduced to the power spectral density limit plus 10 times the log of the bandwidth (in MHz).

| Operating Frequency (MHz) | Output Power                                    | Power Spectral Density |
|---------------------------|---|------------------------|
| 5150 – 5250               | 200mW (23 dBm) eirp                             | 10 dBm/MHz eirp        |
| 5250 – 5350               | 250 mW (24 dBm) <sup>2</sup><br>1W (30dBm) eirp | 11 dBm/MHz             |
| 5470 – 5725               | 250 mW (24 dBm) <sup>3</sup><br>1W (30dBm) eirp | 11 dBm/MHz             |
| 5725 – 5825               | 1 Watts (30 dBm)<br>4W eirp                     | 17 dBm/MHz             |

In addition, the power spectral density limit shall be reduced by 1dB for every dB the highest power spectral density exceeds the “average” power spectral density ) by more than 3dB. The “average” power spectral density is determined by dividing the output power by  $10\log(\text{EBW})$  where EBW is the 99% power bandwidth.

Fixed point-to-point applications using the 5725 – 5825 MHz band may use antennas with gains of up to 23dBi without this limitation. If the gain exceeds 23dBi then the output power limit of 1 Watt is reduced by 1dB for every dB the gain exceeds 23dBi.

<sup>2</sup> If EIRP exceeds 500mW the device must employ TPC

<sup>3</sup> If EIRP exceeds 500mW the device must employ TPC

**SPURIOUS EMISSIONS LIMITS –UNII and LELAN DEVICES**

The spurious emissions limits for signals below 1GHz are the FCC/RSS-GEN general limits. For emissions above 1GHz, signals in restricted bands are subject to the FCC/RSS GEN general limits. All other signals have a limit of –27dBm/MHz, which is a field strength of 68.3dBuV/m/MHz at a distance of 3m. This is an average limit so the peak value of the emission may not exceed –7dBm/MHz (88.3dBuV/m/MHz at a distance of 3m). For devices operating in the 5725-5850Mhz bands under the LELAN/UNII rules, the limit within 10Mhz of the allocated band is increased to –17dBm/MHz.

**SAMPLE CALCULATIONS - CONDUCTED EMISSIONS**

Receiver readings are compared directly to the conducted emissions specification limit (decibel form) as follows:

$$R_r - S = M$$

where:

$R_r$  = Receiver Reading in dBuV

$S$  = Specification Limit in dBuV

$M$  = Margin to Specification in +/- dB

**SAMPLE CALCULATIONS - RADIATED EMISSIONS**

Receiver readings are compared directly to the specification limit (decibel form). The receiver internally corrects for cable loss, preamplifier gain, and antenna factor. The calculations are in the reverse direction of the actual signal flow, thus cable loss is added and the amplifier gain is subtracted. The Antenna Factor converts the voltage at the antenna coaxial connector to the field strength at the antenna elements.

A distance factor, when used for electric field measurements above 30MHz, is calculated by using the following formula:

$$F_d = 20 * \log_{10} (D_m/D_s)$$

where:

$F_d$  = Distance Factor in dB

$D_m$  = Measurement Distance in meters

$D_s$  = Specification Distance in meters

For electric field measurements below 30MHz the extrapolation factor is either determined by making measurements at multiple distances or a theoretical value is calculated using the formula:

$$F_d = 40 * \log_{10} (D_m/D_s)$$

Measurement Distance is the distance at which the measurements were taken and Specification Distance is the distance at which the specification limits are based. The antenna factor converts the voltage at the antenna coaxial connector to the field strength at the antenna elements.

The margin of a given emission peak relative to the limit is calculated as follows:

$$R_c = R_r + F_d$$

and

$$M = R_c - L_s$$

where:

$R_r$  = Receiver Reading in dBuV/m

$F_d$  = Distance Factor in dB

$R_c$  = Corrected Reading in dBuV/m

$L_s$  = Specification Limit in dBuV/m

$M$  = Margin in dB Relative to Spec

#### ***SAMPLE CALCULATIONS - FIELD STRENGTH TO EIRP CONVERSION***

Where the radiated electric field strength is expressed in terms of the equivalent isotropic radiated power (eirp), or where a field strength measurement of output power is made in lieu of a direct measurement, the following formula is used to convert between eirp and field strength at a distance of d (meters) from the equipment under test:

$$E = \frac{1000000 \sqrt{30 P}}{d} \quad \text{microvolts per meter}$$

where P is the eirp (Watts)

For a measurement at 3m the conversion from a logarithmic value for field strength (dBuV/m) to an eirp power (dBm) is -95.3dB.

**Appendix A Test Equipment Calibration Data****Radiated Emissions, 30 - 1,000 MHz, 18-Jan-13**

| <u>Manufacturer</u> | <u>Description</u>             | <u>Model</u> | <u>Asset #</u> | <u>Cal Due</u> |
|---------------------|--------------------------------|--------------|----------------|----------------|
| Sunol Sciences      | Biconilog, 30-3000 MHz         | JB3          | 1657           | 6/4/2014       |
| Rohde & Schwarz     | EMI Test Receiver, 20 Hz-7 GHz | ESIB7        | 1756           | 5/21/2013      |
| Com-Power Corp.     | Preamplifier, 30-1000 MHz      | PAM-103      | 2380           | 11/9/2013      |

**Conducted Emissions - AC Power Ports, 18-Jan-13**

| <u>Manufacturer</u> | <u>Description</u>             | <u>Model</u> | <u>Asset #</u> | <u>Cal Due</u> |
|---------------------|--------------------------------|--------------|----------------|----------------|
| Rohde & Schwarz     | Pulse Limiter                  | ESH3 Z2      | 1594           | 5/22/2013      |
| Rohde & Schwarz     | EMI Test Receiver, 20 Hz-7 GHz | ESIB7        | 1756           | 5/21/2013      |
| Com-Power           | LISN 9KHz-30MHz, 50uH          | LI-215A      | 2672           | 5/25/2013      |

**Radiated Emissions, 1,000 - 6,500 MHz, 20-Jan-13 to 24-Jan-13**

| <u>Manufacturer</u> | <u>Description</u>                | <u>Model</u> | <u>Asset #</u> | <u>Cal Due</u> |
|---------------------|-----------------------------------|--------------|----------------|----------------|
| EMCO                | Antenna, Horn, 1-18 GHz           | 3115         | 487            | 7/19/2014      |
| Rohde & Schwarz     | EMI Test Receiver, 20 Hz-7 GHz    | ESIB7        | 1756           | 5/21/2013      |
| Micro-Tronics       | Band Reject Filter, 2400-2500 MHz | BRM50702-02  | 2249           | 10/11/2013     |

**Radio Antenna Port (Power and Spurious Emissions), 25-Jan-13 to 30-Jan-13**

| <u>Manufacturer</u> | <u>Description</u>             | <u>Model</u>   | <u>Asset #</u> | <u>Cal Due</u> |
|---------------------|--------------------------------|----------------|----------------|----------------|
| Hewlett Packard     | SpecAn 9 kHz - 40 GHz          | 8564E (84125C) | 1393           | 5/1/2013       |
| Rohde & Schwarz     | EMI Test Receiver, 20 Hz-7 GHz | ESIB7          | 1756           | 5/21/2013      |
| Agilent             | PSA Spectrum Analyzer          | E4446A         | 2139           | 2/23/2013      |

**Radiated Emissions, 1,000 - 40,000 MHz, 30-Jan-13 to 7-Feb-13**

| <u>Manufacturer</u> | <u>Description</u>                        | <u>Model</u>       | <u>Asset #</u> | <u>Cal Due</u> |
|---------------------|---|--------------------|----------------|----------------|
| Hewlett Packard     | Microwave Preamp, 1-26.5GHz               | 8449B              | 263            | 3/29/2013      |
| EMCO                | Antenna, Horn, 1-18 GHz                   | 3115               | 487            | 7/19/2014      |
| Hewlett Packard     | Microwave Preamp, 1-26.5GHz               | 8449B              | 785            | 11/9/2013      |
| Hewlett Packard     | Microwave Preamp, 1-26.5GHz               | 8449B              | 870            | 2/23/2013      |
| EMCO                | Antenna, Horn, 1-18 GHz                   | 3115               | 1142           | 8/23/2014      |
| Hewlett Packard     | Head (Inc flex cable, 1143, 2198) Red     | 84125C             | 1145           | 7/5/2013       |
| Hewlett Packard     | SpecAn 30 Hz -40 GHz                      | 8564E (84125C)     | 1148           | 9/14/2013      |
| Hewlett Packard     | SpecAn 9 kHz - 40 GHz                     | 8564E (84125C)     | 1393           | 5/1/2013       |
| Hewlett Packard     | Head (Inc flex cable, (1742,1743) Blue)   | 84125C             | 1620           | 5/17/2013      |
| Micro-Tronics       | Band Reject Filter, 5725-5875 MHz         | BRC50705-02        | 1682           | 3/23/2013      |
| Micro-Tronics       | Band Reject Filter, 2400-2500 MHz         | BRM50702-02        | 1683           | 8/2/2013       |
| Hewlett Packard     | HF Amplifier, 45 MHz -50 GHz              | 83051A (84125C)    | 1742           | 5/17/2013      |
| Hewlett Packard     | HF Amplifier, 45 MHz -50 GHz              | 83051A (84125C)    | 1743           | 5/17/2013      |
| Hewlett Packard     | High Pass filter, 8.2 GHz (Purple System) | P/N 84300-80039    | 1767           | 12/5/2013      |
| Agilent             | PSA Spectrum Analyzer                     | E4446A             | 2139           | 2/23/2013      |
| A.H. Systems        | Red System Horn, 18-40GHz                 | SAS-574, p/n: 2581 | 2161           | 3/20/2013      |
| A.H. Systems        | Spare System Horn, 18-40GHz               | SAS-574, p/n: 2581 | 2162           | 5/8/2013       |
| Micro-Tronics       | Band Reject Filter, 5725-5875 MHz         | BRC50705-02        | 2241           | 10/4/2013      |
| Micro-Tronics       | Band Reject Filter, 2400-2500 MHz         | BRM50702-02        | 2249           | 10/11/2013     |

## *Appendix B Test Data*

T89830 Pages 25 - 121



|                        |                         |                  |                   |
|------------------------|-------------------------|------------------|-------------------|
| Client:                | Flextronics             | Job Number:      | J89632            |
| Model:                 | WS-AP3710e              | T-Log Number:    | T89830            |
|                        |                         | Account Manager: | Christine Krebill |
| Contact:               | George Fares            |                  |                   |
| Emissions Standard(s): | 15.247, 15.407, RSS-210 | Class:           | -                 |
| Immunity Standard(s):  | -                       | Environment:     | Radio             |

## EMC Test Data

For The

### Flextronics

Model

WS-AP3710e

Date of Last Test: 3/20/2013

|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

## Radiated Emissions 30-1000 MHz, (FCC 15.247/RSS 210)

(Elliott Laboratories Fremont Facility, Semi-Anechoic Chamber)

### Test Specific Details

Objective: The objective of this test session is to perform final qualification testing of the EUT with respect to the specification listed above.

Date of Test: 1/18/2013  
 Test Engineer: Rafael Varelas  
 Test Location: FT Chamber #7

Config. Used: 1  
 Config Change: None  
 EUT Voltage: POE

### General Test Configuration

The EUT and any local support equipment were located on the turntable for radiated emissions testing.

The test distance and extrapolation factor (if applicable) are detailed under each run description.

Note, preliminary testing indicates that the emissions were maximized by orientation of the EUT and elevation of the measurement antenna. Maximized testing indicated that the emissions were maximized by orientation of the EUT, elevation of the measurement antenna, and manipulation of the EUT's interface cables.

### Ambient Conditions:

Temperature: 22 °C  
 Rel. Humidity: 40 %

### Summary of Results

| Run #  | Test Performed  | Limit                | Result | Margin                                |
|--|---|----------------------|--------|---------------------------------------|
| Initial scans to determine antenna configuration that results in highest amplitude emissions from the EUT. |   |                      |        |                                       |
| 1 - Ant2   | Radiated Emissions<br>30 - 1000 MHz<br>Radio1 5825MHz (TX)<br>Radio2 2437MHz (TX) | FCC 15.247 / RSS 210 | Pass   | 35.7 dBμV/m @ 37.76 MHz<br>(-4.3 dB)  |
| 2 - Ant3   | Radiated Emissions<br>30 - 1000 MHz<br>Radio1 5825MHz (TX)<br>Radio2 2437MHz (TX) | FCC 15.247 / RSS 210 | Pass   | 43.7 dBμV/m @ 333.33 MHz<br>(-2.3 dB) |
| 3 - Ant1   | Radiated Emissions<br>30 - 1000 MHz<br>Radio1 5825MHz (TX)<br>Radio2 2437MHz (TX) | FCC 15.247 / RSS 210 | Pass   | 36.0 dBμV/m @ 37.94 MHz<br>(-4.0 dB)  |

|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

| Run #  | Test Performed  | Limit                | Result | Margin                                |
|--|---|----------------------|--------|---------------------------------------|
| Scans to determine if changing channels or modes of operation affect emisissions below 1000 MHz. |   |                      |        |                                       |
| 4 - Ant3   | Radiated Emissions<br>30 - 1000 MHz<br>Radio1 5180MHz (TX)<br>Radio2 2412MHz (TX) | FCC 15.247 / RSS 210 | Pass   | 41.4 dBμV/m @ 110.77 MHz<br>(-2.1 dB) |
| 5 - Ant3   | Radiated Emissions<br>30 - 1000 MHz<br>Radio1 5240MHz (TX)<br>Radio2 2462MHz (TX) | FCC 15.247 / RSS 210 | Pass   | 43.5 dBμV/m @ 333.33 MHz<br>(-2.5 dB) |

Based on the results from Runs #4 and #5, additional tests on other combinations of frequencies and modes is unnecessary due to the similarity of the results from Runs #2, #4 and #5.

## Modifications Made During Testing

No modifications were made to the EUT during testing

## Deviations From The Standard

No deviations were made from the requirements of the standard.

## ART GUI (Singleradio test) Or Command Line Script (multiple radio test)

ART GUI Used: No  
 ART GUI Boot File: -  
 -  
 ART GUI Calibration file: -  
 -  
 Command Line Script: 3710e 2nd Pilot\_925942 boot and initialize all 3 radios to NART Command Line Interface - HIGH POWER

|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |


## Run #1: Preliminary Radiated Emissions, 30 - 1000 MHz

Configured Radio 1 to Tx, 802.11a 20dBm on each chain (settings 20) on channel 165, Radio 2 to Tx, 802.11b 21dBm on each chain (settings 21) on channel 6, Use Antenna 2

### Antenna:

| # | Model                   | Type   | Freq. Band (GHz) | Gain (dBi) | Ind/Out | Xpol?           | Pt to Pt? |
|---|-------------------------|--------|------------------|------------|---------|-----------------|-----------|
| 2 | Enterasys WS-AI-DT05120 | Sector | 2.4 & 5.8        | 5          | Indoor  | 2 Xpol / 1 Vert | No        |

| Frequency Range | Test Distance | Limit Distance | Extrapolation Factor |
|-----------------|---------------|----------------|----------------------|
| 30 - 1000 MHz   | 3             | 3              | 0.0                  |



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

## Preliminary peak readings captured during pre-scan

| Frequency | Level        | Pol | FCC 15.47 / RSS 210 |        | Detector  | Azimuth | Height | Comments |
|-----------|--------------|-----|---------------------|--------|-----------|---------|--------|----------|
| MHz       | dB $\mu$ V/m | v/h | Limit               | Margin | Pk/QP/Avg | degrees | meters |          |
| 37.760    | 41.8         | V   | 40.0                | 1.8    | Peak      | 47      | 1.0    |          |
| 162.090   | 39.0         | H   | 43.5                | -4.5   | Peak      | 297     | 1.5    |          |
| 241.485   | 42.8         | H   | 46.0                | -3.2   | Peak      | 313     | 1.0    |          |
| 274.959   | 36.5         | H   | 46.0                | -9.5   | Peak      | 333     | 1.0    |          |
| 250.000   | 39.6         | H   | 46.0                | -6.4   | Peak      | 153     | 1.0    |          |
| 999.988   | 32.0         | V   | 54.0                | -22.0  | Peak      | 343     | 1.5    |          |

## Maximized quasi-peak readings (includes manipulation of EUT interface cables)

| Frequency     | Level        | Pol | FCC 15.47 / RSS 210 |             | Detector  | Azimuth | Height | Comments   |
|---------------|--------------|-----|---------------------|-------------|-----------|---------|--------|------------|
| MHz           | dB $\mu$ V/m | v/h | Limit               | Margin      | Pk/QP/Avg | degrees | meters |            |
| <b>37.760</b> | <b>35.7</b>  | V   | 40.0                | <b>-4.3</b> | QP        | 60      | 1.0    | QP (1.00s) |
| 250.000       | 40.3         | H   | 46.0                | -5.7        | QP        | 144     | 1.2    | QP (1.00s) |
| 241.485       | 39.8         | H   | 46.0                | -6.2        | QP        | 320     | 1.0    | QP (1.00s) |
| 162.090       | 36.7         | H   | 43.5                | -6.8        | QP        | 280     | 1.9    | QP (1.00s) |
| 274.959       | 34.1         | H   | 46.0                | -11.9       | QP        | 347     | 1.0    | QP (1.00s) |
| 999.988       | 32.0         | V   | 54.0                | -22.0       | QP        | 349     | 1.0    | QP (1.00s) |

|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |


## Run #2: Preliminary Radiated Emissions, 30 - 1000 MHz

Configured Radio 1 to Tx, 802.11a 20dBm on each chain (settings 20) on channel 165, Radio 2 to Tx, 802.11b 21dBm on each chain (settings 21) on channel 6, Use Antenna 3

### Antenna:

| # | Model                   | Type  | Freq. Band (GHz) | Gain (dBi) | Ind/Out | Xpol? | Pt to Pt? |
|---|-------------------------|-------|------------------|------------|---------|-------|-----------|
| 3 | Enterasys WS-AI-DT04360 | Panel | 2.4              | 3          | Indoor  | No    | No        |
| 3 | Enterasys WS-AI-DT04360 | Panel | 5.8              | 4          | Indoor  | No    | No        |

| Frequency Range | Test Distance | Limit Distance | Extrapolation Factor |
|-----------------|---------------|----------------|----------------------|
| 30 - 1000 MHz   | 3             | 3              | 0.0                  |



### 2437MHz

|  |       |        |  |
|--|-------|--------|--|
| Fundamental emission level @ 3m in 100kHz RBW:   | 117.3 | dBμV/m |  |
| Limit for emissions outside of restricted bands: | 97.3  | dBμV/m | Limit is -20dBc (Peak power measurement) |
| Limit for emissions outside of restricted bands: | 87.3  | dBμV/m | Limit is -30dBc (UNII power measurement) |

### 5825MHz

|  |       |        |  |
|--|-------|--------|--|
| Fundamental emission level @ 3m in 100kHz RBW:   | 112.7 | dBμV/m |  |
| Limit for emissions outside of restricted bands: | 92.7  | dBμV/m | Limit is -20dBc (Peak power measurement) |
| Limit for emissions outside of restricted bands: | 82.7  | dBμV/m | Limit is -30dBc (UNII power measurement) |



## EMC Test Data

|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

### Preliminary peak readings captured during pre-scan

| Frequency | Level        | Pol | FCC 15.47 / RSS 210 |        | Detector  | Azimuth | Height | Comments |
|-----------|--------------|-----|---------------------|--------|-----------|---------|--------|----------|
| MHz       | dB $\mu$ V/m | v/h | Limit               | Margin | Pk/QP/Avg | degrees | meters |          |
| 37.890    | 45.0         | V   | 40.0                | 5.0    | Peak      | 38      | 1.0    |          |
| 110.871   | 41.6         | H   | 43.5                | -1.9   | Peak      | 123     | 1.5    |          |
| 166.595   | 38.3         | H   | 43.5                | -5.2   | Peak      | 357     | 2.0    |          |
| 274.680   | 38.1         | H   | 46.0                | -7.9   | Peak      | 7       | 1.0    |          |
| 333.328   | 42.8         | H   | 46.0                | -3.2   | Peak      | 27      | 1.0    |          |
| 1000.000  | 31.7         | H   | 54.0                | -22.3  | Peak      | 197     | 2.0    |          |

### Maximized quasi-peak readings (includes manipulation of EUT interface cables)

| Frequency | Level        | Pol | FCC 15.47 / RSS 210 |        | Detector  | Azimuth | Height | Comments   |
|-----------|--------------|-----|---------------------|--------|-----------|---------|--------|------------|
| MHz       | dB $\mu$ V/m | v/h | Limit               | Margin | Pk/QP/Avg | degrees | meters |            |
| 333.328   | 43.7         | H   | 46.0                | -2.3   | QP        | 11      | 1.0    | QP (1.00s) |
| 110.871   | 39.8         | H   | 43.5                | -3.7   | QP        | 130     | 1.5    | QP (1.00s) |
| 37.890    | 36.2         | V   | 40.0                | -3.8   | QP        | 57      | 1.0    | QP (1.00s) |
| 166.595   | 34.7         | H   | 43.5                | -8.8   | QP        | 360     | 1.7    | QP (1.00s) |
| 274.680   | 36.9         | H   | 46.0                | -9.1   | QP        | 1       | 1.0    | QP (1.00s) |
| 1000.000  | 32.3         | H   | 54.0                | -21.7  | QP        | 223     | 1.3    | QP (1.00s) |
| 237.996   | 50.0         | H   | 82.7                | -32.7  | PK        | 320     | 1.0    |            |

|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |


## Run #3: Preliminary Radiated Emissions, 30 - 1000 MHz

Configured Radio 1 to Tx , 802.11a 20dBm on each chain (settings 20) on channel 165, Radio 2 to Tx, 802.11b 21dBm on each chain (settings 21) on channel 6, Use Antenna 1

### Antenna:

| # | Model                   | Type | Freq. Band (GHz) | Gain (dBi) | Ind/Out | Xpol? | Pt to Pt? |
|---|-------------------------|------|------------------|------------|---------|-------|-----------|
| 1 | Enterasys WS-AI-DX02360 | Omni | 2.4 & 5.8        | 2          | Indoor  | No    | No        |

| Frequency Range | Test Distance | Limit Distance | Extrapolation Factor |
|-----------------|---------------|----------------|----------------------|
| 30 - 1000 MHz   | 3             | 3              | 0.0                  |





|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

## Preliminary peak readings captured during pre-scan

| Frequency | Level        | Pol | FCC 15.47 / RSS 210 |        | Detector  | Azimuth | Height | Comments |
|-----------|--------------|-----|---------------------|--------|-----------|---------|--------|----------|
| MHz       | dB $\mu$ V/m | v/h | Limit               | Margin | Pk/QP/Avg | degrees | meters |          |
| 37.942    | 42.8         | V   | 40.0                | 2.8    | Peak      | 58      | 1.5    |          |
| 166.549   | 40.1         | H   | 43.5                | -3.4   | Peak      | 238     | 2.0    |          |
| 253.141   | 44.8         | H   | 46.0                | -1.2   | Peak      | 113     | 1.0    |          |
| 273.953   | 41.5         | H   | 46.0                | -4.5   | Peak      | 278     | 1.0    |          |
| 333.328   | 33.5         | H   | 46.0                | -12.5  | Peak      | 293     | 1.0    |          |
| 1000.000  | 33.2         | H   | 54.0                | -20.8  | Peak      | 342     | 1.5    |          |

## Maximized quasi-peak readings (includes manipulation of EUT interface cables)

| Frequency     | Level        | Pol | FCC 15.47 / RSS 210 |             | Detector  | Azimuth | Height | Comments   |
|---------------|--------------|-----|---------------------|-------------|-----------|---------|--------|------------|
| MHz           | dB $\mu$ V/m | v/h | Limit               | Margin      | Pk/QP/Avg | degrees | meters |            |
| <b>37.942</b> | <b>36.0</b>  | V   | 40.0                | <b>-4.0</b> | QP        | 54      | 1.0    | QP (1.00s) |
| 253.141       | 40.6         | H   | 46.0                | -5.4        | QP        | 107     | 1.0    | QP (1.00s) |
| 166.549       | 37.4         | H   | 43.5                | -6.1        | QP        | 233     | 1.7    | QP (1.00s) |
| 273.953       | 37.4         | H   | 46.0                | -8.6        | QP        | 280     | 1.0    | QP (1.00s) |
| 333.328       | 33.5         | H   | 46.0                | -12.5       | QP        | 286     | 1.0    | QP (1.00s) |
| 1000.000      | 33.1         | H   | 54.0                | -20.9       | QP        | 330     | 1.6    | QP (1.00s) |

|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |


## Run #4: Preliminary Radiated Emissions, 30 - 1000 MHz

Configured Radio 1 to Tx, 802.11a 18dBm on each chain (settings 18) on channel 36, Radio 2 to Tx, 802.11b 21dBm on each chain (settings 21) on channel 1, Use Antenna 3

### Antenna:

| # | Model                   | Type  | Freq. Band (GHz) | Gain (dBi) | Ind/Out | Xpol? | Pt to Pt? |
|---|-------------------------|-------|------------------|------------|---------|-------|-----------|
| 3 | Enterasys WS-AI-DT04360 | Panel | 2.4              | 3          | Indoor  | No    | No        |
| 3 | Enterasys WS-AI-DT04360 | Panel | 5.8              | 4          | Indoor  | No    | No        |

| Frequency Range | Test Distance | Limit Distance | Extrapolation Factor |
|-----------------|---------------|----------------|----------------------|
| 30 - 1000 MHz   | 3             | 3              | 0.0                  |



### 2412MHz

|  |       |              |  |
|--|-------|--------------|--|
| Fundamental emission level @ 3m in 100kHz RBW:   | 117.1 | dB $\mu$ V/m |  |
| Limit for emissions outside of restricted bands: | 97.1  | dB $\mu$ V/m | Limit is -20dBc (Peak power measurement) |
| Limit for emissions outside of restricted bands: | 87.1  | dB $\mu$ V/m | Limit is -30dBc (UNII power measurement) |

### 5180MHz

|  |      |              |
|--|------|--------------|
| Limit for emissions outside of restricted bands: | 68.3 | dB $\mu$ V/m |
|--|------|--------------|



## EMC Test Data

|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

### Preliminary peak readings captured during pre-scan

| Frequency | Level        | Pol | FCC 15.47 / RSS 210 |        | Detector  | Azimuth | Height | Comments |
|-----------|--------------|-----|---------------------|--------|-----------|---------|--------|----------|
| MHz       | dB $\mu$ V/m | v/h | Limit               | Margin | Pk/QP/Avg | degrees | meters |          |
| 37.955    | 45.9         | V   | 40.0                | 5.9    | Peak      | 88      | 1.0    |          |
| 110.774   | 42.5         | H   | 43.5                | -1.0   | Peak      | 132     | 2.0    |          |
| 162.317   | 38.4         | H   | 43.5                | -5.1   | Peak      | 353     | 1.5    |          |
| 280.954   | 38.4         | H   | 46.0                | -7.6   | Peak      | 360     | 1.0    |          |
| 333.328   | 43.1         | H   | 46.0                | -2.9   | Peak      | 27      | 1.0    |          |
| 1000.000  | 32.3         | H   | 54.0                | -21.7  | Peak      | 217     | 2.0    |          |

### Maximized quasi-peak readings (includes manipulation of EUT interface cables)

| Frequency | Level        | Pol | FCC 15.47 / RSS 210 |        | Detector  | Azimuth | Height | Comments   |
|-----------|--------------|-----|---------------------|--------|-----------|---------|--------|------------|
| MHz       | dB $\mu$ V/m | v/h | Limit               | Margin | Pk/QP/Avg | degrees | meters |            |
| 110.774   | 41.4         | H   | 43.5                | -2.1   | QP        | 155     | 2.0    | QP (1.00s) |
| 37.955    | 37.9         | V   | 40.0                | -2.1   | QP        | 79      | 1.0    | QP (1.00s) |
| 333.328   | 43.4         | H   | 46.0                | -2.6   | QP        | 8       | 1.0    | QP (1.00s) |
| 162.317   | 35.6         | H   | 43.5                | -7.9   | QP        | 349     | 1.9    | QP (1.00s) |
| 280.954   | 36.7         | H   | 46.0                | -9.3   | QP        | 360     | 1.0    | QP (1.00s) |
| 1000.000  | 32.7         | H   | 54.0                | -21.3  | QP        | 221     | 1.3    | QP (1.00s) |
| 237.996   | 52.0         | H   | 68.3                | -16.3  | PK        | 320     | 1.0    |            |

|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |


## Run #5: Preliminary Radiated Emissions, 30 - 1000 MHz

Configured Radio 1 to Tx, 802.11n20 18dBm on each chain (settings 18) on channel 48, Radio 2 to Tx, 802.11n20 19dBm on each chain (settings 19) on channel 11, Use Antenna 3

### Antenna:

| # | Model                   | Type  | Freq. Band (GHz) | Gain (dBi) | Ind/Out | Xpol? | Pt to Pt? |
|---|-------------------------|-------|------------------|------------|---------|-------|-----------|
| 3 | Enterasys WS-AI-DT04360 | Panel | 2.4              | 3          | Indoor  | No    | No        |
| 3 | Enterasys WS-AI-DT04360 | Panel | 5.8              | 4          | Indoor  | No    | No        |

| Frequency Range | Test Distance | Limit Distance | Extrapolation Factor |
|-----------------|---------------|----------------|----------------------|
| 30 - 1000 MHz   | 3             | 3              | 0.0                  |



### 2462MHz

|  |       |              |  |
|--|-------|--------------|--|
| Fundamental emission level @ 3m in 100kHz RBW:   | 113.7 | dB $\mu$ V/m |  |
| Limit for emissions outside of restricted bands: | 93.7  | dB $\mu$ V/m | Limit is -20dBc (Peak power measurement) |
| Limit for emissions outside of restricted bands: | 83.7  | dB $\mu$ V/m | Limit is -30dBc (UNII power measurement) |

### 5240MHz

|  |      |              |  |
|--|------|--------------|--|
| Limit for emissions outside of restricted bands: | 68.3 | dB $\mu$ V/m | Limit is -20dBc (Peak power measurement) |
|--|------|--------------|--|

|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

## Preliminary peak readings captured during pre-scan

| Frequency | Level        | Pol | FCC 15.47 / RSS 210 |        | Detector  | Azimuth | Height | Comments |
|-----------|--------------|-----|---------------------|--------|-----------|---------|--------|----------|
| MHz       | dB $\mu$ V/m | v/h | Limit               | Margin | Pk/QP/Avg | degrees | meters |          |
| 38.045    | 43.0         | V   | 40.0                | 3.0    | Peak      | 103     | 1.5    |          |
| 110.916   | 42.5         | H   | 43.5                | -1.0   | Peak      | 128     | 2.0    |          |
| 167.166   | 38.4         | H   | 43.5                | -5.1   | Peak      | 187     | 1.5    |          |
| 276.494   | 38.0         | H   | 46.0                | -8.0   | Peak      | 233     | 1.0    |          |
| 333.328   | 43.8         | H   | 46.0                | -2.2   | Peak      | 3       | 1.0    |          |
| 999.988   | 31.1         | H   | 54.0                | -22.9  | Peak      | 222     | 1.5    |          |

## Maximized quasi-peak readings (includes manipulation of EUT interface cables)

| Frequency      | Level        | Pol | FCC 15.47 / RSS 210 |             | Detector  | Azimuth | Height | Comments   |
|----------------|--------------|-----|---------------------|-------------|-----------|---------|--------|------------|
| MHz            | dB $\mu$ V/m | v/h | Limit               | Margin      | Pk/QP/Avg | degrees | meters |            |
| <b>333.328</b> | <b>43.5</b>  | H   | 46.0                | <b>-2.5</b> | QP        | 11      | 1.0    | QP (1.00s) |
| 38.045         | 36.6         | V   | 40.0                | -3.4        | QP        | 71      | 1.0    | QP (1.00s) |
| 110.916        | 40.0         | H   | 43.5                | -3.5        | QP        | 140     | 1.6    | QP (1.00s) |
| 167.166        | 34.3         | H   | 43.5                | -9.2        | QP        | 172     | 1.5    | QP (1.00s) |
| 276.494        | 34.8         | H   | 46.0                | -11.2       | QP        | 235     | 1.0    | QP (1.00s) |
| 999.988        | 34.0         | H   | 54.0                | -20.0       | QP        | 220     | 1.3    | QP (1.00s) |
| 237.996        | 50.0         | H   | 68.3                | -18.3       | PK        | 320     | 1.0    |            |

|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | -                 |

## Conducted Emissions

*(Elliott Laboratories Fremont Facility, Semi-Anechoic Chamber)*

### Test Specific Details

Objective: The objective of this test session is to perform final qualification testing of the EUT with respect to the specification listed above.

Date of Test: 1/18/2013  
 Test Engineer: Rafael Varelas  
 Test Location: Fremont Chamber #7

Config. Used: 1  
 Config Change: None  
 EUT Voltage: 120V/60Hz

### General Test Configuration

For tabletop equipment, the EUT was located on a wooden table inside the semi-anechoic chamber, 40 cm from a vertical coupling plane and 80cm from the LISN. Remote support equipment was located outside of the semi-anechoic chamber. Any cables running to remote support equipment were routed through metal conduit and when possible passed through a ferrite clamp upon exiting the chamber.

**Ambient Conditions:**

|                |         |
|----------------|---------|
| Temperature:   | 20.9 °C |
| Rel. Humidity: | 36 %    |

### Summary of Results

| Run # | Test Performed          | Limit      | Result | Margin                           |
|-------|-------------------------|------------|--------|----------------------------------|
| 1     | CE, AC Power, 120V/60Hz | FCC 15.207 | Pass   | 36.1 dBµV @ 0.337 MHz (-13.2 dB) |

### Modifications Made During Testing

No modifications were made to the EUT during testing

### Deviations From The Standard

No deviations were made from the requirements of the standard.

|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | -                 |


## Run #1: AC Power Port Conducted Emissions, 0.15 - 30MHz, 120V/60Hz

### Antenna:


| # | Model                   | Type   | Freq. Band (GHz) | Gain (dBi) | Ind/Out | Xpol?           | Pt to Pt? |
|---|-------------------------|--------|------------------|------------|---------|-----------------|-----------|
| 2 | Enterasys WS-AI-DT05120 | Sector | 5.2              | 5          | Indoor  | 2 Xpol / 1 Vert | No        |

### Preliminary peak readings captured during pre-scan (peak readings vs. average limit)

| Frequency MHz | Level dBμV | AC Line | FCC 15.207 |        | Detector OP/Ave | Comments |
|---------------|------------|---------|------------|--------|-----------------|----------|
|               |            |         | Limit      | Margin |                 |          |
| 0.168         | 40.1       | Line 1  | 55.2       | -15.1  | Peak            |          |
| 0.337         | 41.8       | Line 1  | 49.3       | -7.5   | Peak            |          |
| 1.839         | 32.3       | Line 1  | 46.0       | -13.7  | Peak            |          |
| 7.275         | 40.8       | Line 1  | 50.0       | -9.2   | Peak            |          |
| 0.169         | 39.9       | Neutral | 55.0       | -15.1  | Peak            |          |
| 0.338         | 41.7       | Neutral | 49.2       | -7.5   | Peak            |          |
| 1.420         | 34.2       | Neutral | 46.0       | -11.8  | Peak            |          |
| 7.192         | 39.7       | Neutral | 50.0       | -10.3  | Peak            |          |



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | -                 |



## Final quasi-peak and average readings

| Frequency<br>MHz | Level<br>dB $\mu$ V | AC<br>Line | FCC 15.207 |        | Detector<br>QP/Ave | Comments    |
|------------------|---------------------|------------|------------|--------|--------------------|-------------|
|                  |                     |            | Limit      | Margin |                    |             |
| 0.337            | 36.1                | Line 1     | 49.3       | -13.2  | AVG                | AVG (0.10s) |
| 0.168            | 40.7                | Line 1     | 55.1       | -14.4  | AVG                | AVG (0.10s) |
| 0.338            | 34.0                | Neutral    | 49.3       | -15.3  | AVG                | AVG (0.10s) |
| 0.169            | 39.5                | Neutral    | 55.0       | -15.5  | AVG                | AVG (0.10s) |
| 1.420            | 28.7                | Neutral    | 46.0       | -17.3  | AVG                | AVG (0.10s) |
| 0.168            | 47.7                | Line 1     | 65.1       | -17.4  | QP                 | QP (1.00s)  |
| 1.839            | 28.3                | Line 1     | 46.0       | -17.7  | AVG                | AVG (0.10s) |
| 0.169            | 47.1                | Neutral    | 65.0       | -17.9  | QP                 | QP (1.00s)  |
| 0.337            | 40.7                | Line 1     | 59.3       | -18.6  | QP                 | QP (1.00s)  |
| 0.338            | 39.9                | Neutral    | 59.3       | -19.4  | QP                 | QP (1.00s)  |
| 7.275            | 39.4                | Line 1     | 60.0       | -20.6  | QP                 | QP (1.00s)  |
| 7.192            | 38.7                | Neutral    | 60.0       | -21.3  | QP                 | QP (1.00s)  |
| 7.275            | 26.4                | Line 1     | 50.0       | -23.6  | AVG                | AVG (0.10s) |
| 1.839            | 32.3                | Line 1     | 56.0       | -23.7  | QP                 | QP (1.00s)  |
| 7.192            | 26.2                | Neutral    | 50.0       | -23.8  | AVG                | AVG (0.10s) |
| 1.420            | 32.2                | Neutral    | 56.0       | -23.8  | QP                 | QP (1.00s)  |



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

## RSS-210 (LELAN) and FCC 15.407(UNII) Antenna Port Measurements Power, PSD, Peak Excursion, Bandwidth and Spurious Emissions

### Test Specific Details

Objective: The objective of this test session is to perform final qualification testing of the EUT with respect to the specification listed above.

Date of Test: 1/28/2013  
 Test Engineer: Rafael Varelas  
 Test Location: FT 4

Config. Used: 1  
 Config Change: None  
 EUT Voltage: POE

### General Test Configuration

When measuring the conducted emissions from the EUT's antenna port, the antenna port of the EUT was connected to the spectrum analyzer or power meter via a suitable attenuator to prevent overloading the measurement system. All measurements are corrected to allow for the external attenuators and cables used.

### Ambient Conditions:

Temperature: 20.7 °C  
 Rel. Humidity: 36 %

### Summary of Results

| Run # | Test Performed                              | Limit                   | Pass / Fail | Result / Margin                             |
|-------|---|-------------------------|-------------|---|
| 1     | Peak Excursion Envelope                     | 15.407(a) (6)<br>13dB   | Pass        | 9.0 dB                                      |
| 2     | Antenna Conducted - Out of Band<br>Spurious | 15.407(b)<br>-27dBm/MHz |             | All emissions below the<br>-27dBm/MHz limit |

### Modifications Made During Testing

No modifications were made to the EUT during testing

### Deviations From The Standard

No deviations were made from the requirements of the standard.

### Notes

All measurements performed at the antenna port

|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

## Run #1: Peak Excursion Measurement

20MHz: Device meets the requirement for the peak excursion

| 802.11a |                    |       | 802.11n |                    |       |
|---------|--------------------|-------|---------|--------------------|-------|
| Freq    | Peak Excursion(dB) |       | Freq    | Peak Excursion(dB) |       |
| (MHz)   | Value              | Limit | (MHz)   | Value              | Limit |
| 5180    | 8.5                | 13.0  | 5180    | 8.6                | 13.0  |
| 5200    | 9.0                | 13.0  | 5200    | 8.4                | 13.0  |
| 5240    | 8.3                | 13.0  | 5240    | 8.7                | 13.0  |

40MHz: Device meets the requirement for the peak excursion


| Freq  | Peak Excursion(dB) |       |
|-------|--------------------|-------|
| (MHz) | Value              | Limit |
| 5190  | 8.6                | 13.0  |
| 5230  | 8.9                | 13.0  |
|       |                    |       |

### Plots Showing Peak Excursion

Trace A: RBW = 1MHz, VBW = 3MHz, Peak hold

Trace B: Same settings as used for power/PSD measurements (RBW = 1 MHz, VBW = 3MHz, Integrated **average** power)

|                                   |                                    |
|-----------------------------------|------------------------------------|
| Client: Flextronics               | Job Number: J89632                 |
| Model: WS-AP3710e                 | T-Log Number: T89830               |
| Contact: George Fares             | Account Manager: Christine Krebill |
| Standard: 15.247, 15.407, RSS-210 | Class: N/A                         |



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

## RSS-210 (LELAN) and FCC 15.407(UNII) Antenna Port Measurements Power, PSD, Peak Excursion, Bandwidth and Spurious Emissions

### Test Specific Details

Objective: The objective of this test session is to perform final qualification testing of the EUT with respect to the specification listed above.

Date of Test: 1/28/ & 1/29/13 & 1/30/13  
 Test Engineer: Rafael Varelas & Jack Liu  
 Test Location: FT 4 & FT 7

Config. Used: 1  
 Config Change: None  
 EUT Voltage: POE

### General Test Configuration

When measuring the conducted emissions from the EUT's antenna port, the antenna port of the EUT was connected to the spectrum analyzer or power meter via a suitable attenuator to prevent overloading the measurement system. All measurements are corrected to allow for the external attenuators and cables used.

### Ambient Conditions:

Temperature: 20.7 °C  
 Rel. Humidity: 36 %

### Summary of Results

| Run # | Test Performed        | Limit                         | Pass / Fail | Result / Margin   |
|-------|-----------------------|-------------------------------|-------------|---|
| 1     | Power, 5150 - 5250MHz | 15.407(a) (1), (2)            | Pass        | 802.11a: 29.6 mW<br>802.11n 20MHz: 31.8 mW<br>802.11n n40MHz: 45.1 mW             |
| 1     | PSD, 5150 - 5250MHz   | 15.407(a) (1), (2)            | Pass        | 802.11a: 3.1 dBm/MHz<br>802.11n 20MHz: 2.9 dBm/MHz<br>802.11n n40MHz: 1.6 dBm/MHz |
| 1     | 26dB Bandwidth        | 15.407<br>(Information only)  | -           | > 20MHz for all modes   |
| 1     | 99% Bandwidth         | RSS 210<br>(Information only) | N/A         | 802.11a: 16.9 MHz<br>802.11n 20MHz: 18.1 MHz<br>802.11n n40MHz: 36.5 MHz          |

### Antenna:

| # | Model                   | Type  | Freq. Band (GHz) | Gain (dBi) | Ind/Out | Xpol? | Pt to Pt? |
|---|-------------------------|-------|------------------|------------|---------|-------|-----------|
| 1 | Enterasys WS-AI-DX02360 | Panel | 5.2              | 2          | Indoor  | No    | No        |

|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

## Modifications Made During Testing

No modifications were made to the EUT during testing

## Deviations From The Standard

No deviations were made from the requirements of the standard.

## Notes

All measurements performed at the antenna port

## Run #1: Bandwidth, Output Power and Power Spectral Density - MIMO Systems

### MIMO Device - 5150-5250 MHz Band

|                   |                     | Chain 1 | Chain 2 | Chain 3 | Coherent | Effective <sup>5</sup> | EIRP (mW) | EIRP (dBm) |
|-------------------|---------------------|---------|---------|---------|----------|------------------------|-----------|------------|
| Legacy MIMO Power | Antenna Gain (dBi): | 2       | 2       | 2       | Yes      | 6.8                    | 140.7     | 21.5       |
|                   | Antenna Gain (dBi): | 2       | 2       | 2       | No       | 2.0                    | 71.4      | 18.5       |

| Frequency<br>(MHz) | Software<br>Setting | 26dB BW<br>(MHz) | Measured Output Power <sup>1</sup> dBm |         |         | Total |      | Limit (dBm) | Max Power<br>(W) | Pass or<br>Fail |
|--------------------|---------------------|------------------|--|---------|---------|-------|------|-------------|------------------|-----------------|
|                    |                     |                  | Chain 1                                | Chain 2 | Chain 3 | mW    | dBm  |             |                  |                 |
| 20MHz a Mode       |                     |                  |  |         |         |       |      |             |                  |                 |
| 5180               | 10.5                | 23.2             | 8.7                                    | 10.3    | 9.7     | 27.5  | 14.4 | 16.2        | 0.030            | PASS            |
| 5200               | 10.5                | 23.7             | 9.1                                    | 10.5    | 10.1    | 29.6  | 14.7 | 16.2        |                  | PASS            |
| 5240               | 10.5                | 24.3             | 9.1                                    | 10.1    | 10.5    | 29.6  | 14.7 | 16.2        |                  | PASS            |
| 20MHz n Mode       |                     |                  |  |         |         |       |      |             |                  |                 |
| 5180               | 11.5                | 25.7             | 9.5                                    | 10.3    | 10.5    | 30.8  | 14.9 | 17.0        | 0.032            | PASS            |
| 5200               | 11.0                | 24.2             | 9.7                                    | 10.4    | 10.6    | 31.8  | 15.0 | 17.0        |                  | PASS            |
| 5240               | 11.0                | 25.7             | 9.3                                    | 10.3    | 10.6    | 30.7  | 14.9 | 17.0        |                  | PASS            |
| 40MHz n Mode       |                     |                  |  |         |         |       |      |             |                  |                 |
| 5190               | 10.5                | 48.9             | 9.6                                    | 10.8    | 10.3    | 31.9  | 15.0 | 17.0        | 0.045            | PASS            |
| 5230               | 12.0                | 47.8             | 11.0                                   | 12.4    | 11.9    | 45.1  | 16.5 | 17.0        |                  | PASS            |

## PSD

| Frequency (MHz)     | 99% <sup>4</sup> BW | Total Power | PSD <sup>2</sup> dBm/MHz |         |         | Total PSD |         | Limit |                      | Pass or Fail |
|---------------------|---------------------|-------------|--------------------------|---------|---------|-----------|---------|-------|----------------------|--------------|
|                     |                     |             | Chain 1                  | Chain 2 | Chain 3 | mW/MHz    | dBm/MHz | FCC   | RSS 210 <sup>3</sup> |              |
| <b>20MHz a Mode</b> |                     |             |                          |         |         |           |         |       |                      |              |
| 5180                | 16.9                | 14.4        | -3.4                     | -1.5    | -1.6    | 1.9       | 2.7     | 3.2   | 3.2                  | PASS         |
| 5200                | 16.9                | 14.7        | -2.9                     | -1.6    | -0.9    | 2.0       | 3.1     | 3.2   | 3.2                  | PASS         |
| 5240                | 16.9                | 14.7        | -2.9                     | -1.8    | -1.0    | 2.0       | 3.0     | 3.2   | 3.2                  | PASS         |
| <b>20MHz n Mode</b> |                     |             |                          |         |         |           |         |       |                      |              |
| 5180                | 18.1                | 14.9        | -2.6                     | -2.0    | -1.3    | 1.9       | 2.8     | 3.2   | 3.2                  | PASS         |
| 5200                | 18.1                | 15.0        | -2.5                     | -1.9    | -1.2    | 2.0       | 2.9     | 3.2   | 3.2                  | PASS         |
| 5240                | 18.1                | 14.9        | -2.9                     | -2.0    | -1.4    | 1.9       | 2.7     | 3.2   | 3.2                  | PASS         |
| <b>40MHz n Mode</b> |                     |             |                          |         |         |           |         |       |                      |              |
| 5190                | 36.5                | 15.0        | -5.8                     | -4.7    | -4.2    | 1.0       | -0.1    | 3.2   | 3.2                  | PASS         |
| 5230                | 36.5                | 16.5        | -4.1                     | -2.8    | -2.7    | 1.4       | 1.6     | 3.2   | 3.2                  | PASS         |

|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

## Power (RSS Limit)

| Frequency<br>(MHz) | Software<br>Setting | 99% BW<br>(MHz) | Measured Output Power <sup>1</sup> dBm |         |         | Total |      | Limit (dBm) | Max Power<br>(W) | Pass or<br>Fail |
|--------------------|---------------------|-----------------|--|---------|---------|-------|------|-------------|------------------|-----------------|
|                    |                     |                 | Chain 1                                | Chain 2 | Chain 3 | mW    | dBm  |             |                  |                 |
| 20MHz a Mode       |                     |                 |  |         |         |       |      |             |                  |                 |
| 5180               | 10.5                | 16.9            | 8.7                                    | 10.3    | 9.7     | 27.5  | 14.4 | 15.5        | 0.030            | PASS            |
| 5200               | 10.5                | 16.9            | 9.1                                    | 10.5    | 10.1    | 29.6  | 14.7 | 15.5        |                  | PASS            |
| 5240               | 10.5                | 16.9            | 9.1                                    | 10.1    | 10.5    | 29.6  | 14.7 | 15.5        |                  | PASS            |
| 20MHz n Mode       |                     |                 |  |         |         |       |      |             |                  |                 |
| 5180               | 11.5                | 18.1            | 9.5                                    | 10.3    | 10.5    | 30.8  | 14.9 | 16.6        | 0.032            | PASS            |
| 5200               | 11.0                | 18.1            | 9.7                                    | 10.4    | 10.6    | 31.8  | 15.0 | 16.6        |                  | PASS            |
| 5240               | 11.0                | 18.1            | 9.3                                    | 10.3    | 10.6    | 30.7  | 14.9 | 16.6        |                  | PASS            |
| 40MHz n Mode       |                     |                 |  |         |         |       |      |             |                  |                 |
| 5190               | 10.5                | 36.5            | 9.6                                    | 10.8    | 10.3    | 31.9  | 15.0 | 17.0        | 0.045            | PASS            |
| 5230               | 12.0                | 36.5            | 11.0                                   | 12.4    | 11.9    | 45.1  | 16.5 | 17.0        |                  | PASS            |

Note 1: Output power measured using a spectrum analyzer (see plots below). RBW=1MHz, VB=3 MHz, # of points in sweep  $\geq 2 \times \text{span/RBW}$ , **sample** detector, power averaging on (transmitted signal was continuous) and power integration over 50/80 MHz (method SA-1 of KDB 789033).



Note 2: Measured using the same analyzer settings used for output power.

Note 3: For RSS-210 the limit for the 5150 - 5250 MHz band accounts for the antenna gain as the maximum eirp allowed is 10dBm/MHz. The limits are also corrected for instances where the highest measured value of the PSD exceeds the average PSD (calculated from the measured power divided by the measured 99% bandwidth) by more than 3dB by the amount that the measured value exceeds the average by more than 3dB.

Note 4: 99% Bandwidth measured in accordance with RSS GEN - RB > 1% of span and VB  $\geq 3 \times \text{RB}$

Note 5: For MIMO systems the total output power and total PSD are calculated from the sum of the powers of the individual chains (in linear terms). The antenna gain used to determine the EIRP and limits for PSD/Output power depends on the operating mode of the MIMO device. If the signals are non-coherent between the transmit chains then the gain used to determine the limits is the highest gain of the individual chains and the EIRP is the sum of the products of gain and power on each chain. If the signals are coherent then the effective antenna gain is the sum (in linear terms) of the gains for each chain and the EIRP is the product of the effective gain and total power.

|                                   |                                    |
|-----------------------------------|------------------------------------|
| Client: Flextronics               | Job Number: J89632                 |
| Model: WS-AP3710e                 | T-Log Number: T89830               |
| Contact: George Fares             | Account Manager: Christine Krebill |
| Standard: 15.247, 15.407, RSS-210 | Class: N/A                         |



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

## RSS-210 (LELAN) and FCC 15.407(UNII) Antenna Port Measurements Power, PSD, Peak Excursion, Bandwidth and Spurious Emissions

### Test Specific Details

Objective: The objective of this test session is to perform final qualification testing of the EUT with respect to the specification listed above.

Date of Test: 1/30/2013  
 Test Engineer: Rafael Varelas & Jack Liu  
 Test Location: FT 7

Config. Used: 1  
 Config Change: None  
 EUT Voltage: POE

### General Test Configuration

When measuring the conducted emissions from the EUT's antenna port, the antenna port of the EUT was connected to the spectrum analyzer or power meter via a suitable attenuator to prevent overloading the measurement system. All measurements are corrected to allow for the external attenuators and cables used.

### Ambient Conditions:

Temperature: 20.5 °C  
 Rel. Humidity: 37 %

### Summary of Results

| Run # | Test Performed        | Limit                         | Pass / Fail | Result / Margin  |
|-------|-----------------------|-------------------------------|-------------|--|
| 1     | Power, 5150 - 5250MHz | 15.407(a) (1), (2)            | Pass        | 802.11a: 15.3 mW<br>802.11n 20MHz: 12.2 mW<br>802.11n n40MHz: 14.6 mW              |
| 1     | PSD, 5150 - 5250MHz   | 15.407(a) (1), (2)            | Pass        | 802.11a: 0.1 dBm/MHz<br>802.11n 20MHz: 0.2 dBm/MHz<br>802.11n n40MHz: -0.5 dBm/MHz |
| 1     | 26dB Bandwidth        | 15.407<br>(Information only)  | -           | > 20MHz for all modes  |
| 1     | 99% Bandwidth         | RSS 210<br>(Information only) | N/A         | 802.11a: 16.9 MHz<br>802.11n 20MHz: 18.1 MHz<br>802.11n n40MHz: 36.3 MHz           |

### Antenna:

| # | Model                   | Type   | Freq. Band (GHz) | Gain (dBi) | Ind/Out | Xpol?           | Pt to Pt? |
|---|-------------------------|--------|------------------|------------|---------|-----------------|-----------|
| 2 | Enterasys WS-AI-DT05120 | Sector | 5.2              | 5          | Indoor  | 2 Xpol / 1 Vert | No        |



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

## Modifications Made During Testing

No modifications were made to the EUT during testing

## Deviations From The Standard

No deviations were made from the requirements of the standard.

## Notes

All measurements performed at the antenna port

## Run #1: Bandwidth, Output Power and Power Spectral Density - MIMO Systems

### MIMO Device - 5150-5250 MHz Band

|                   |                     | Chain 1 | Chain 2 | Chain 3 | Coherent | Effective <sup>5</sup> | EIRP (mW) | EIRP (dBm) |
|-------------------|---------------------|---------|---------|---------|----------|------------------------|-----------|------------|
| Legacy MIMO Power | Antenna Gain (dBi): | 5       | 5       | 5       | Yes      | 9.8                    | 144.8     | 21.6       |
|                   | Antenna Gain (dBi): | 5       | 5       | 5       | No       | 5.0                    | 90.2      | 19.6       |

| Frequency<br>(MHz) | Software<br>Setting    | 26dB BW<br>(MHz) | Measured Output Power <sup>1</sup> dBm |         |         | Total     |         | Limit (dBm) | Max Power<br>(W)     | Pass or<br>Fail |
|--------------------|------------------------|------------------|--|---------|---------|-----------|---------|-------------|----------------------|-----------------|
|                    |                        |                  | Chain 1                                | Chain 2 | Chain 3 | mW        | dBm     |             |                      |                 |
| 20MHz a Mode       |                        |                  |  |         |         |           |         |             |                      |                 |
| 5180               | 7.0                    | 23.2             | 5.9                                    | 7.0     | 7.2     | 14.2      | 11.5    | 13.2        | 0.015                | PASS            |
| 5200               | 7.0                    | 23.7             | 6.1                                    | 7.3     | 6.7     | 14.1      | 11.5    | 13.2        |                      | PASS            |
| 5240               | 7.5                    | 24.3             | 6.3                                    | 7.5     | 7.3     | 15.3      | 11.8    | 13.2        |                      | PASS            |
| 20MHz n Mode       |                        |                  |  |         |         |           |         |             |                      |                 |
| 5180               | 8.0                    | 25.7             | 6.7                                    | 7.5     | 7.4     | 15.8      | 12.0    | 17.0        | 0.017                | PASS            |
| 5200               | 8.0                    | 24.2             | 7.0                                    | 7.9     | 7.3     | 16.5      | 12.2    | 17.0        |                      | PASS            |
| 5240               | 7.5                    | 25.7             | 6.4                                    | 7.7     | 7.1     | 15.3      | 11.8    | 17.0        |                      | PASS            |
| 40MHz n Mode       |                        |                  |  |         |         |           |         |             |                      |                 |
| 5190               | 9.0                    | 48.9             | 8.4                                    | 9.4     | 9.6     | 24.6      | 13.9    | 17.0        | 0.029                | PASS            |
| 5230               | 10.0                   | 47.8             | 9.1                                    | 10.2    | 10.0    | 28.5      | 14.6    | 17.0        |                      | PASS            |
| PSD                |                        |                  |  |         |         |           |         |             |                      |                 |
| Frequency<br>(MHz) | 99% <sup>4</sup><br>BW | Total<br>Power   | PSD <sup>2</sup> dBm/MHz               |         |         | Total PSD |         | Limit       |                      | Pass or<br>Fail |
|                    |                        |                  | Chain 1                                | Chain 2 | Chain 3 | mW/MHz    | dBm/MHz | FCC         | RSS 210 <sup>3</sup> |                 |
| 20MHz a Mode       |                        |                  |  |         |         |           |         |             |                      |                 |
| 5180               | 16.9                   | 11.5             | -5.7                                   | -5.0    | -4.5    | 0.9       | -0.2    | 0.2         | 0.2                  | PASS            |
| 5200               | 16.9                   | 11.5             | -5.9                                   | -4.4    | -5.0    | 0.9       | -0.3    | 0.2         | 0.2                  | PASS            |
| 5240               | 16.9                   | 11.8             | -5.7                                   | -4.4    | -4.2    | 1.0       | 0.1     | 0.2         | 0.2                  | PASS            |
| 20MHz n Mode       |                        |                  |  |         |         |           |         |             |                      |                 |
| 5180               | 18.0                   | 12.0             | -5.4                                   | -4.9    | -4.8    | 0.9       | -0.3    | 0.2         | 0.2                  | PASS            |
| 5200               | 18.0                   | 12.2             | -5.1                                   | -4.3    | -4.5    | 1.0       | 0.2     | 0.2         | 0.2                  | PASS            |
| 5240               | 18.1                   | 11.8             | -5.8                                   | -4.4    | -4.8    | 1.0       | -0.2    | 0.2         | 0.2                  | PASS            |
| 40MHz n Mode       |                        |                  |  |         |         |           |         |             |                      |                 |
| 5190               | 36.3                   | 13.9             | -6.6                                   | -5.8    | -4.7    | 0.8       | -0.9    | 0.2         | 0.2                  | PASS            |
| 5230               | 36.3                   | 14.6             | -6.6                                   | -4.8    | -4.8    | 0.9       | -0.5    | 0.2         | 0.2                  | PASS            |

|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

## Power (RSS Limit)

| Frequency<br>(MHz) | Software<br>Setting | 99% BW<br>(MHz) | Measured Output Power <sup>1</sup> dBm |         |         | Total |      | Limit (dBm) | Max Power<br>(W) | Pass or<br>Fail |
|--------------------|---------------------|-----------------|--|---------|---------|-------|------|-------------|------------------|-----------------|
|                    |                     |                 | Chain 1                                | Chain 2 | Chain 3 | mW    | dBm  |             |                  |                 |
| 20MHz a Mode       |                     |                 |  |         |         |       |      |             |                  |                 |
| 5180               | 7.0                 | 16.9            | 5.9                                    | 7.0     | 7.2     | 14.2  | 11.5 | 12.5        | 0.015            | PASS            |
| 5200               | 7.0                 | 16.9            | 6.1                                    | 7.3     | 6.7     | 14.1  | 11.5 | 12.5        |                  | PASS            |
| 5240               | 7.5                 | 16.9            | 6.3                                    | 7.5     | 7.3     | 15.3  | 11.8 | 12.5        |                  | PASS            |
| 20MHz n Mode       |                     |                 |  |         |         |       |      |             |                  |                 |
| 5180               | 8.0                 | 18.0            | 6.7                                    | 7.5     | 7.4     | 15.8  | 12.0 | 16.6        | 0.017            | PASS            |
| 5200               | 8.0                 | 18.0            | 7.0                                    | 7.9     | 7.3     | 16.5  | 12.2 | 16.6        |                  | PASS            |
| 5240               | 7.5                 | 18.1            | 6.4                                    | 7.7     | 7.1     | 15.3  | 11.8 | 16.6        |                  | PASS            |
| 40MHz n Mode       |                     |                 |  |         |         |       |      |             |                  |                 |
| 5190               | 9.0                 | 36.3            | 8.4                                    | 9.4     | 9.6     | 24.6  | 13.9 | 17.0        | 0.029            | PASS            |
| 5230               | 10.0                | 36.3            | 9.1                                    | 10.2    | 10.0    | 28.5  | 14.6 | 17.0        |                  | PASS            |

Note 1: Output power measured using a spectrum analyzer (see plots below). RBW=1MHz, VB=3 MHz, # of points in sweep  $\geq 2 \times \text{span/RBW}$ , **sample** detector, power averaging on (transmitted signal was continuous) and power integration over 50/80 MHz (method SA-1 of KDB 789033).



Note 2: Measured using the same analyzer settings used for output power.

Note 3: For RSS-210 the limit for the 5150 - 5250 MHz band accounts for the antenna gain as the maximum eirp allowed is 10dBm/MHz. The limits are also corrected for instances where the highest measured value of the PSD exceeds the average PSD (calculated from the measured power divided by the measured 99% bandwidth) by more than 3dB by the amount that the measured value exceeds the average by more than 3dB.

Note 4: 99% Bandwidth measured in accordance with RSS GEN - RB > 1% of span and VB  $\geq 3 \times \text{RB}$

Note 5: For MIMO systems the total output power and total PSD are calculated from the sum of the powers of the individual chains (in linear terms). The antenna gain used to determine the EIRP and limits for PSD/Output power depends on the operating mode of the MIMO device. If the signals on the non-coherent between the transmit chains then the gain used to determine the limits is the highest gain of the individual chains and the EIRP is the sum of the products of gain and power on each chain. If the signals are coherent then the effective antenna gain is the sum (in linear terms) of the gains for each chain and the EIRP is the product of the effective gain and total power.

|                                   |                                    |
|-----------------------------------|------------------------------------|
| Client: Flextronics               | Job Number: J89632                 |
| Model: WS-AP3710e                 | T-Log Number: T89830               |
| Contact: George Fares             | Account Manager: Christine Krebill |
| Standard: 15.247, 15.407, RSS-210 | Class: N/A                         |



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

## RSS-210 (LELAN) and FCC 15.407(UNII) Antenna Port Measurements Power, PSD, Peak Excursion, Bandwidth and Spurious Emissions

### Test Specific Details

Objective: The objective of this test session is to perform final qualification testing of the EUT with respect to the specification listed above.

Date of Test: 1/30/2013  
 Test Engineer: Rafael Varelas & Jack Liu  
 Test Location: FT 7

Config. Used: 1  
 Config Change: None  
 EUT Voltage: POE

### General Test Configuration

When measuring the conducted emissions from the EUT's antenna port, the antenna port of the EUT was connected to the spectrum analyzer or power meter via a suitable attenuator to prevent overloading the measurement system. All measurements are corrected to allow for the external attenuators and cables used.

### Ambient Conditions:

Temperature: 20.5 °C  
 Rel. Humidity: 37 %

### Summary of Results

| Run # | Test Performed        | Limit                         | Pass / Fail | Result / Margin   |
|-------|-----------------------|-------------------------------|-------------|---|
| 1     | Power, 5150 - 5250MHz | 15.407(a) (1), (2)            | Pass        | 802.11a: 13.1 mW<br>802.11n 20MHz: 12.9 mW<br>802.11n n40MHz: 15.5 mW             |
| 1     | PSD, 5150 - 5250MHz   | 15.407(a) (1), (2)            | Pass        | 802.11a: 1.1 dBm/MHz<br>802.11n 20MHz: 1.0 dBm/MHz<br>802.11n n40MHz: 0.8 dBm/MHz |
| 1     | 26dB Bandwidth        | 15.407<br>(Information only)  | -           | > 20MHz for all modes   |
| 1     | 99% Bandwidth         | RSS 210<br>(Information only) | N/A         | 802.11a: 16.9 MHz<br>802.11n 20MHz: 18.2 MHz<br>802.11n n40MHz: 36.5 MHz          |

### Antenna:

| # | Model                   | Type  | Freq. Band (GHz) | Gain (dBi) | Ind/Out | Xpol? | Pt to Pt? |
|---|-------------------------|-------|------------------|------------|---------|-------|-----------|
| 3 | Enterasys WS-AI-DT04360 | Panel | 5.2              | 4          | Indoor  | No    | No        |

|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

## Modifications Made During Testing

No modifications were made to the EUT during testing

## Deviations From The Standard

No deviations were made from the requirements of the standard.

## Notes

All measurements performed at the antenna port

## Run #1: Bandwidth, Output Power and Power Spectral Density - MIMO Systems

### MIMO Device - 5150-5250 MHz Band

|                   |                     | Chain 1 | Chain 2 | Chain 3 | Coherent | Effective <sup>5</sup> | EIRP (mW) | EIRP (dBm) |
|-------------------|---------------------|---------|---------|---------|----------|------------------------|-----------|------------|
| Legacy MIMO Power | Antenna Gain (dBi): | 4       | 4       | 4       | Yes      | 8.8                    | 154.6     | 21.9       |
|                   | Antenna Gain (dBi): | 4       | 4       | 4       | No       | 4.0                    | 89.8      | 19.5       |

| Frequency (MHz) | Software Setting | 26dB BW (MHz) | Measured Output Power <sup>1</sup> dBm |         |         | Total |     | Limit (dBm) | Max Power (W) | Pass or Fail |
|-----------------|------------------|---------------|--|---------|---------|-------|-----|-------------|---------------|--------------|
|                 |                  |               | Chain 1                                | Chain 2 | Chain 3 | mW    | dBm |             |               |              |

### 20MHz a Mode

|      |     |      |     |     |     |      |      |      |       |      |
|------|-----|------|-----|-----|-----|------|------|------|-------|------|
| 5180 | 8.5 | 23.2 | 7.4 | 8.5 | 8.5 | 19.5 | 12.9 | 14.2 | 0.021 | PASS |
| 5200 | 8.5 | 23.7 | 7.8 | 8.8 | 8.4 | 20.5 | 13.1 | 14.2 |       | PASS |
| 5240 | 8.0 | 24.3 | 6.9 | 8.2 | 7.5 | 17.1 | 12.3 | 14.2 |       | PASS |

### 20MHz n Mode

|      |     |      |     |     |     |      |      |      |       |      |
|------|-----|------|-----|-----|-----|------|------|------|-------|------|
| 5180 | 8.5 | 25.7 | 7.4 | 8.3 | 8.5 | 19.3 | 12.9 | 17.0 | 0.020 | PASS |
| 5200 | 8.5 | 24.2 | 7.7 | 8.5 | 7.8 | 19.0 | 12.8 | 17.0 |       | PASS |
| 5240 | 8.5 | 25.7 | 7.4 | 8.7 | 8.3 | 19.7 | 12.9 | 17.0 |       | PASS |

### 40MHz n Mode

|      |      |      |     |      |      |      |      |      |       |      |
|------|------|------|-----|------|------|------|------|------|-------|------|
| 5190 | 9.0  | 48.9 | 8.4 | 9.4  | 9.6  | 24.6 | 13.9 | 17.0 | 0.036 | PASS |
| 5230 | 11.0 | 47.8 | 9.7 | 10.9 | 11.5 | 35.8 | 15.5 | 17.0 |       | PASS |

## PSD

| Frequency (MHz) | 99% <sup>4</sup> BW | Total Power | PSD <sup>2</sup> dBm/MHz |         |         | Total PSD |         | Limit |                      | Pass or Fail |
|-----------------|---------------------|-------------|--------------------------|---------|---------|-----------|---------|-------|----------------------|--------------|
|                 |                     |             | Chain 1                  | Chain 2 | Chain 3 | mW/MHz    | dBm/MHz | FCC   | RSS 210 <sup>3</sup> |              |

### 20MHz a Mode

|      |      |      |      |      |      |     |     |     |     |      |
|------|------|------|------|------|------|-----|-----|-----|-----|------|
| 5180 | 16.9 | 12.9 | -4.7 | -3.8 | -3.0 | 1.3 | 1.0 | 1.2 | 1.2 | PASS |
| 5200 | 16.9 | 13.1 | -4.6 | -3.5 | -3.2 | 1.3 | 1.1 | 1.2 | 1.2 | PASS |
| 5240 | 16.9 | 12.3 | -5.3 | -3.7 | -4.1 | 1.1 | 0.5 | 1.2 | 1.2 | PASS |

### 20MHz n Mode

|      |      |      |      |      |      |     |     |     |     |      |
|------|------|------|------|------|------|-----|-----|-----|-----|------|
| 5180 | 18.0 | 12.9 | -4.7 | -4.3 | -3.1 | 1.2 | 0.8 | 1.2 | 1.2 | PASS |
| 5200 | 18.2 | 12.8 | -4.8 | -3.5 | -4.3 | 1.2 | 0.6 | 1.2 | 1.2 | PASS |
| 5240 | 18.0 | 12.9 | -5.1 | -3.3 | -3.2 | 1.3 | 1.0 | 1.2 | 1.2 | PASS |

### 40MHz n Mode

|      |      |      |      |      |      |     |      |     |     |      |
|------|------|------|------|------|------|-----|------|-----|-----|------|
| 5190 | 36.3 | 13.9 | -6.6 | -5.8 | -4.7 | 0.8 | -0.9 | 1.2 | 1.2 | PASS |
| 5230 | 36.5 | 15.5 | -5.4 | -3.7 | -3.2 | 1.2 | 0.8  | 1.2 | 1.2 | PASS |

|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

## Power (RSS Limit)

| Frequency<br>(MHz) | Software<br>Setting | 99% BW<br>(MHz) | Measured Output Power <sup>1</sup> dBm |         |         | Total |      | Limit (dBm) | Max Power<br>(W) | Pass or<br>Fail |
|--------------------|---------------------|-----------------|--|---------|---------|-------|------|-------------|------------------|-----------------|
|                    |                     |                 | Chain 1                                | Chain 2 | Chain 3 | mW    | dBm  |             |                  |                 |
| 20MHz a Mode       |                     |                 |  |         |         |       |      |             |                  |                 |
| 5180               | 8.5                 | 16.9            | 7.4                                    | 8.5     | 8.5     | 19.5  | 12.9 | 13.5        | 0.021            | PASS            |
| 5200               | 8.5                 | 16.9            | 7.8                                    | 8.8     | 8.4     | 20.5  | 13.1 | 13.5        |                  | PASS            |
| 5240               | 8.0                 | 16.9            | 6.9                                    | 8.2     | 7.5     | 17.1  | 12.3 | 13.5        |                  | PASS            |
| 20MHz n Mode       |                     |                 |  |         |         |       |      |             |                  |                 |
| 5180               | 8.5                 | 18.0            | 7.4                                    | 8.3     | 8.5     | 19.3  | 12.9 | 16.6        | 0.020            | PASS            |
| 5200               | 8.5                 | 18.2            | 7.7                                    | 8.5     | 7.8     | 19.0  | 12.8 | 16.6        |                  | PASS            |
| 5240               | 8.5                 | 18.0            | 7.4                                    | 8.7     | 8.3     | 19.7  | 12.9 | 16.6        |                  | PASS            |
| 40MHz n Mode       |                     |                 |  |         |         |       |      |             |                  |                 |
| 5190               | 9.0                 | 36.3            | 8.4                                    | 9.4     | 9.6     | 24.6  | 13.9 | 17.0        | 0.036            | PASS            |
| 5230               | 11.0                | 36.5            | 9.7                                    | 10.9    | 11.5    | 35.8  | 15.5 | 17.0        |                  | PASS            |

Note 1: Output power measured using a spectrum analyzer (see plots below). RBW=1MHz, VB=3 MHz, # of points in sweep  $\geq 2 \times \text{span/RBW}$ , **sample** detector, power averaging on (transmitted signal was continuous) and power integration over 50/80 MHz (method SA-1 of KDB 789033).



Note 2: Measured using the same analyzer settings used for output power.

Note 3: For RSS-210 the limit for the 5150 - 5250 MHz band accounts for the antenna gain as the maximum eirp allowed is 10dBm/MHz. The limits are also corrected for instances where the highest measured value of the PSD exceeds the average PSD (calculated from the measured power divided by the measured 99% bandwidth) by more than 3dB by the amount that the measured value exceeds the average by more than 3dB.

Note 4: 99% Bandwidth measured in accordance with RSS GEN - RB > 1% of span and VB  $\geq 3 \times \text{RB}$

Note 5: For MIMO systems the total output power and total PSD are calculated from the sum of the powers of the individual chains (in linear terms). The antenna gain used to determine the EIRP and limits for PSD/Output power depends on the operating mode of the MIMO device. If the signals on the non-coherent between the transmit chains then the gain used to determine the limits is the highest gain of the individual chains and the EIRP is the sum of the products of gain and power on each chain. If the signals are coherent then the effective antenna gain is the sum (in linear terms) of the gains for each chain and the EIRP is the product of the effective gain and total power.

|                                   |                                    |
|-----------------------------------|------------------------------------|
| Client: Flextronics               | Job Number: J89632                 |
| Model: WS-AP3710e                 | T-Log Number: T89830               |
| Contact: George Fares             | Account Manager: Christine Krebill |
| Standard: 15.247, 15.407, RSS-210 | Class: N/A                         |





## EMC Test Data

|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

### RSS 210 and FCC 15.407 (NII) Radiated Spurious Emissions

#### Test Specific Details

Objective: The objective of this test session is to perform final qualification testing of the EUT with respect to the specification listed above.

#### General Test Configuration

The EUT and all local support equipment were located on the turntable for radiated spurious emissions testing. All remote support equipment was located approximately 30 meters from the EUT.

For radiated emissions testing the measurement antenna was located 3 meters from the EUT.

#### Ambient Conditions:

Temperature: 20.7 °C  
Rel. Humidity: 36 %

#### Summary of Results - Device Operating in the 5150-5250 MHz Band

| Run #   | Mode                  | Channel     | Power Setting | Measured Power | Test Performed                   | Limit  | Result / Margin                    |
|---------|-----------------------|-------------|---------------|----------------|----------------------------------|--------|------------------------------------|
| Run # 1 | 802.11a Chain A+B+C   | #36 5180MHz | 17.0          | -              | Restricted Band Edge at 5150 MHz | 15.209 | 49.0 dBµV/m @ 5147.6 MHz (-5.0 dB) |
|         |                       | #48 5240MHz | 17.0          | -              | Restricted Band Edge at 5350 MHz | 15.209 | 44.8 dBµV/m @ 5359.9 MHz (-9.2 dB) |
| Run # 2 | 802.11n20 Chain A+B+C | #36 5180MHz | 17.5          | -              | Restricted Band Edge at 5150 MHz | 15.209 | 53.6 dBµV/m @ 5150.0 MHz (-0.4 dB) |
|         |                       | #48 5240MHz | 18.0          | -              | Restricted Band Edge at 5350 MHz | 15.209 | 44.5 dBµV/m @ 5360.0 MHz (-9.5 dB) |
| Run # 3 | 802.11n40 Chain A+B+C | #38 5190MHz | 10.5          | -              | Restricted Band Edge at 5150 MHz | 15.209 | 53.1 dBµV/m @ 5150.0 MHz (-0.9 dB) |
|         |                       | #46 5230MHz | 17.0          | -              | Restricted Band Edge at 5350 MHz | 15.209 | 48.4 dBµV/m @ 5360.1 MHz (-5.6 dB) |

#### Antenna:

| # | Model                   | Type | Freq. Band (GHz) | Gain (dBi) | Ind/Out | Xpol? | Pt to Pt? |
|---|-------------------------|------|------------------|------------|---------|-------|-----------|
| 1 | Enterasys WS-AI-DX02360 | Omni | 5.2              | 2          | Indoor  | No    | No        |





## EMC Test Data

|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
|           |                         | Account Manager: | Christine Krebill |
| Contact:  | George Fares            |                  |                   |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

### Modifications Made During Testing

No modifications were made to the EUT during testing

### Deviations From The Standard

No deviations were made from the requirements of the standard.

### Notes

#### ART GUI (Singleradio test) Or Command Line Script (multiple radio test)

ART GUI Used: No

ART GUI Boot File: -

-

ART GUI Calibration file: -

-

Command Line Script: 3710e 2nd Pilot\_925942 boot and initialize all 3 radios to NART Command Line Interface - HIGH POWER

|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

## Run # 1, Band Edge Field Strength - 802.11a, Chain A+B+C

Date of Test: 1/24/2013

Test Location: FT7

Test Engineer: Rafael Varelas

Config Change: none


## Run # 1a, EUT on Channel #36 5180MHz - 802.11a, Chain A+B+C

| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5180 MHz | 17.0          |
| 2     | 2437 MHz | 21.0          |

## 5150 MHz Band Edge Signal Field Strength

| Frequency | Level  | Pol | 15.209 / 15.247 |        | Detector  | Azimuth | Height | Comments                 |
|-----------|--------|-----|-----------------|--------|-----------|---------|--------|--------------------------|
| MHz       | dBμV/m | v/h | Limit           | Margin | Pk/QP/Avg | degrees | meters |                          |
| 5147.600  | 49.0   | V   | 54.0            | -5.0   | AVG       | 10      | 1.0    | POS; RB 1 MHz; VB: 10 Hz |
| 5146.710  | 65.5   | V   | 74.0            | -8.5   | PK        | 10      | 1.0    | POS; RB 1 MHz; VB: 3 MHz |
| 5150.000  | 43.4   | H   | 54.0            | -10.6  | AVG       | 37      | 1.2    | POS; RB 1 MHz; VB: 10 Hz |
| 5149.440  | 54.9   | H   | 74.0            | -19.1  | PK        | 37      | 1.2    | POS; RB 1 MHz; VB: 3 MHz |

RB 1 MHz; VB 10 Hz Avg=Black Trace; RB1MHz VB3MHz PK=Blue Trace; V



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |


Run # 1b, EUT on Channel #48 5240MHz - 802.11a, Chain A+B+C

| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5240 MHz | 17.0          |
| 2     | 2437 MHz | 21.0          |

## 5350 MHz Band Edge Signal Radiated Field Strength

| Frequency | Level  | Pol | 15.209 / 15.247 |        | Detector  | Azimuth | Height | Comments                 |
|-----------|--------|-----|-----------------|--------|-----------|---------|--------|--------------------------|
| MHz       | dBμV/m | v/h | Limit           | Margin | Pk/QP/Avg | degrees | meters |                          |
| 5359.940  | 44.8   | V   | 54.0            | -9.2   | AVG       | 258     | 1.0    | POS; RB 1 MHz; VB: 10 Hz |
| 5377.250  | 55.6   | V   | 74.0            | -18.4  | PK        | 258     | 1.0    | POS; RB 1 MHz; VB: 3 MHz |
| 5360.020  | 41.4   | H   | 54.0            | -12.6  | AVG       | 332     | 1.0    | POS; RB 1 MHz; VB: 10 Hz |
| 5353.610  | 52.0   | H   | 74.0            | -22.0  | PK        | 332     | 1.0    | POS; RB 1 MHz; VB: 3 MHz |

RB 1 MHz; VB 10 Hz Avg=Black Trace; RB1MHz VB3MHz PK=Blue Trace; V



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

## Run # 2, Band Edge Field Strength - 802.11n20, Chain A+B+C

Date of Test: 1/24/2013

Test Location: FT7

Test Engineer: Rafael Varelas

Config Change: none


## Run # 2a, EUT on Channel #36 5180MHz - 802.11n20, Chain A+B+C

| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5180 MHz | 17.5          |
| 2     | 2437 MHz | 21.0          |

## 5150 MHz Band Edge Signal Field Strength

| Frequency | Level  | Pol | 15.209 / 15.247 |        | Detector  | Azimuth | Height | Comments                 |
|-----------|--------|-----|-----------------|--------|-----------|---------|--------|--------------------------|
| MHz       | dBμV/m | v/h | Limit           | Margin | Pk/QP/Avg | degrees | meters |                          |
| 5150.000  | 53.6   | V   | 54.0            | -0.4   | AVG       | 32      | 1.0    | POS; RB 1 MHz; VB: 10 Hz |
| 5149.280  | 69.8   | V   | 74.0            | -4.2   | PK        | 32      | 1.0    | POS; RB 1 MHz; VB: 3 MHz |
| 5150.000  | 46.5   | H   | 54.0            | -7.5   | AVG       | 30      | 1.4    | POS; RB 1 MHz; VB: 10 Hz |
| 5148.640  | 59.9   | H   | 74.0            | -14.1  | PK        | 30      | 1.4    | POS; RB 1 MHz; VB: 3 MHz |

RB 1 MHz; VB 10 Hz Avg=Black Trace; RB1MHz VB3MHz PK=Blue Trace; V



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |


Run # 2b, EUT on Channel #48 5240MHz - 802.11n20, Chain A+B+C

| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5240 MHz | 18.0          |
| 2     | 2437 MHz | 21.0          |

## 5350 MHz Band Edge Signal Radiated Field Strength

| Frequency | Level  | Pol | 15.209 / 15.247 |        | Detector  | Azimuth | Height | Comments                 |
|-----------|--------|-----|-----------------|--------|-----------|---------|--------|--------------------------|
| MHz       | dBμV/m | v/h | Limit           | Margin | PK/QP/Avg | degrees | meters |                          |
| 5360.020  | 44.5   | V   | 54.0            | -9.5   | AVG       | 280     | 1.0    | POS; RB 1 MHz; VB: 10 Hz |
| 5356.250  | 54.3   | V   | 74.0            | -19.7  | PK        | 280     | 1.0    | POS; RB 1 MHz; VB: 3 MHz |
| 5360.020  | 41.0   | H   | 54.0            | -13.0  | AVG       | 53      | 1.5    | POS; RB 1 MHz; VB: 10 Hz |
| 5388.480  | 51.5   | H   | 74.0            | -22.5  | PK        | 53      | 1.5    | POS; RB 1 MHz; VB: 3 MHz |

RB 1 MHz; VB 10 Hz Avg=Black Trace; RB1MHz VB3MHz PK=Blue Trace; V



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

## Run #3, Band Edge Field Strength - 802.11n40, Chain A+B+C

Date of Test: 1/24/2013

Test Location: FT7

Test Engineer: Rafael Varelas

Config Change: none


## Run #3a, EUT on Channel #38 5190MHz - 802.11n40, Chain A+B+C

| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5190 MHz | 10.5          |
| 2     | 2437 MHz | 21.0          |

## 5150 MHz Band Edge Signal Field Strength

| Frequency | Level  | Pol | 15.209 / 15.247 |        | Detector  | Azimuth | Height | Comments                 |
|-----------|--------|-----|-----------------|--------|-----------|---------|--------|--------------------------|
| MHz       | dBμV/m | v/h | Limit           | Margin | Pk/QP/Avg | degrees | meters |                          |
| 5149.990  | 53.1   | V   | 54.0            | -0.9   | AVG       | 4       | 1.0    | POS; RB 1 MHz; VB: 10 Hz |
| 5148.710  | 69.1   | V   | 74.0            | -4.9   | PK        | 4       | 1.0    | POS; RB 1 MHz; VB: 3 MHz |
| 5149.920  | 42.0   | H   | 54.0            | -12.0  | AVG       | 168     | 1.0    | POS; RB 1 MHz; VB: 10 Hz |
| 5148.400  | 56.0   | H   | 74.0            | -18.0  | PK        | 168     | 1.0    | POS; RB 1 MHz; VB: 3 MHz |

RB 1 MHz; VB 10 Hz Avg=Black Trace; RB1MHz VB3MHz PK=Blue Trace; V



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |


Run #3b, EUT on Channel #46 5230MHz - 802.11n40, Chain A+B+C

| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5230 MHz | 17.0          |
| 2     | 2437 MHz | 21.0          |

## 5350 MHz Band Edge Signal Radiated Field Strength

| Frequency | Level  | Pol | 15.209 / 15.247 |        | Detector  | Azimuth | Height | Comments                 |
|-----------|--------|-----|-----------------|--------|-----------|---------|--------|--------------------------|
| MHz       | dBμV/m | v/h | Limit           | Margin | Pk/QP/Avg | degrees | meters |                          |
| 5360.100  | 48.4   | V   | 54.0            | -5.6   | AVG       | 250     | 1.0    | POS; RB 1 MHz; VB: 10 Hz |
| 5359.860  | 54.9   | V   | 74.0            | -19.1  | PK        | 250     | 1.0    | POS; RB 1 MHz; VB: 3 MHz |
| 5350.990  | 39.6   | H   | 54.0            | -14.4  | AVG       | 330     | 1.0    | POS; RB 1 MHz; VB: 10 Hz |
| 5351.620  | 51.4   | H   | 74.0            | -22.6  | PK        | 330     | 1.0    | POS; RB 1 MHz; VB: 3 MHz |

RB 1 MHz; VB 10 Hz Avg=Black Trace; RB1MHz VB3MHz PK=Blue Trace; V





## EMC Test Data

|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

### RSS 210 and FCC 15.407 (NII) Radiated Spurious Emissions

#### Test Specific Details

Objective: The objective of this test session is to perform final qualification testing of the EUT with respect to the specification listed above.

#### General Test Configuration

The EUT and all local support equipment were located on the turntable for radiated spurious emissions testing. All remote support equipment was located approximately 30 meters from the EUT.

For radiated emissions testing the measurement antenna was located 3 meters from the EUT.

#### Ambient Conditions:

Temperature: 20.5 °C  
Rel. Humidity: 37 %

#### Summary of Results - Device Operating in the 5150-5250 MHz Band

| Run #   | Mode                  | Channel     | Power Setting | Measured Power | Test Performed                   | Limit  | Result / Margin                    |
|---------|-----------------------|-------------|---------------|----------------|----------------------------------|--------|------------------------------------|
| Run # 1 | 802.11a Chain A+B+C   | #36 5180MHz | 14.0          | -              | Restricted Band Edge at 5150 MHz | 15.209 | 46.9 dBµV/m @ 5149.7 MHz (-7.1 dB) |
|         |                       | #48 5240MHz | 14.0          | -              | Restricted Band Edge at 5350 MHz | 15.209 | 48.4 dBµV/m @ 5360.0 MHz (-5.6 dB) |
| Run # 2 | 802.11n20 Chain A+B+C | #36 5180MHz | 15.0          | -              | Restricted Band Edge at 5150 MHz | 15.209 | 50.1 dBµV/m @ 5150.0 MHz (-3.9 dB) |
|         |                       | #48 5240MHz | 15.0          | -              | Restricted Band Edge at 5350 MHz | 15.209 | 50.6 dBµV/m @ 5360.0 MHz (-3.4 dB) |
| Run # 3 | 802.11n40 Chain A+B+C | #38 5190MHz | 9.0           | -              | Restricted Band Edge at 5150 MHz | 15.209 | 52.8 dBµV/m @ 5150.0 MHz (-1.2 dB) |
|         |                       | #46 5230MHz | 14.0          | -              | Restricted Band Edge at 5350 MHz | 15.209 | 52.1 dBµV/m @ 5360.0 MHz (-1.9 dB) |

#### Antenna:

| # | Model                   | Type   | Freq. Band (GHz) | Gain (dBi) | Ind/Out | Xpol?           | Pt to Pt? |
|---|-------------------------|--------|------------------|------------|---------|-----------------|-----------|
| 2 | Enterasys WS-AI-DT05120 | Sector | 5.2              | 5          | Indoor  | 2 Xpol / 1 Vert | No        |





## EMC Test Data

|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
|           |                         | Account Manager: | Christine Krebill |
| Contact:  | George Fares            |                  |                   |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

### Modifications Made During Testing

No modifications were made to the EUT during testing

### Deviations From The Standard

No deviations were made from the requirements of the standard.

### Notes

#### ART GUI (Singleradio test) Or Command Line Script (multiple radio test)

ART GUI Used: No

ART GUI Boot File: -

-

ART GUI Calibration file: -

-

Command Line Script: 3710e 2nd Pilot\_925942 boot and initialize all 3 radios to NART Command Line Interface - HIGH POWER

|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

## Run # 1, Band Edge Field Strength - 802.11a, Chain A+B+C

Date of Test: 1/23/2013

Test Location: FT7

Test Engineer: Rafael Varelas

Config Change: none


## Run # 1a, EUT on Channel #36 5180MHz - 802.11a, Chain A+B+C

| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5180 MHz | 14.0          |
| 2     | 2437 MHz | 21.0          |

## 5150 MHz Band Edge Signal Field Strength

| Frequency | Level  | Pol | 15.209 / 15.247 |        | Detector  | Azimuth | Height | Comments                 |
|-----------|--------|-----|-----------------|--------|-----------|---------|--------|--------------------------|
| MHz       | dBμV/m | v/h | Limit           | Margin | Pk/QP/Avg | degrees | meters |                          |
| 5149.680  | 46.9   | V   | 54.0            | -7.1   | AVG       | 26      | 1.0    | POS; RB 1 MHz; VB: 10 Hz |
| 5149.920  | 63.3   | V   | 74.0            | -10.7  | PK        | 26      | 1.0    | POS; RB 1 MHz; VB: 3 MHz |
| 5147.270  | 43.3   | H   | 54.0            | -10.7  | AVG       | 360     | 1.0    | POS; RB 1 MHz; VB: 10 Hz |
| 5147.920  | 55.8   | H   | 74.0            | -18.2  | PK        | 360     | 1.0    | POS; RB 1 MHz; VB: 3 MHz |

RB 1 MHz; VB 10 Hz Avg=Black Trace; RB1MHz VB3MHz Pk= Blue Trace; V



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |


Run # 1b, EUT on Channel #48 5240MHz - 802.11a, Chain A+B+C

| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5240 MHz | 14.0          |
| 2     | 2437 MHz | 21.0          |

## 5350 MHz Band Edge Signal Radiated Field Strength

| Frequency | Level        | Pol | 15.209 / 15.247 |        | Detector  | Azimuth | Height | Comments                 |
|-----------|--------------|-----|-----------------|--------|-----------|---------|--------|--------------------------|
| MHz       | dB $\mu$ V/m | v/h | Limit           | Margin | Pk/QP/Avg | degrees | meters |                          |
| 5360.020  | 48.4         | V   | 54.0            | -5.6   | AVG       | 20      | 1.0    | POS; RB 1 MHz; VB: 10 Hz |
| 5359.860  | 56.7         | V   | 74.0            | -17.3  | PK        | 20      | 1.0    | POS; RB 1 MHz; VB: 3 MHz |
| 5359.940  | 44.6         | H   | 54.0            | -9.4   | AVG       | 17      | 1.0    | POS; RB 1 MHz; VB: 10 Hz |
| 5355.050  | 55.5         | H   | 74.0            | -18.5  | PK        | 17      | 1.0    | POS; RB 1 MHz; VB: 3 MHz |

RB 1 MHz; VB 10 Hz Avg=Black Trace; RB1MHz VB3MHz Pk= Blue Trace; V



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

## Run # 2, Band Edge Field Strength - 802.11n20, Chain A+B+C

Date of Test: 1/23/2013

Test Location: FT7

Test Engineer: Rafael Varelas

Config Change: none


## Run # 2a, EUT on Channel #36 5180MHz - 802.11n20, Chain A+B+C

| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5180 MHz | 15.0          |
| 2     | 2437 MHz | 21.0          |

## 5150 MHz Band Edge Signal Field Strength

| Frequency | Level  | Pol | 15.209 / 15.247 |        | Detector  | Azimuth | Height | Comments                 |
|-----------|--------|-----|-----------------|--------|-----------|---------|--------|--------------------------|
| MHz       | dBuV/m | v/h | Limit           | Margin | Pk/QP/Avg | degrees | meters |                          |
| 5150.000  | 50.1   | V   | 54.0            | -3.9   | AVG       | 0       | 1.0    | POS; RB 1 MHz; VB: 10 Hz |
| 5150.000  | 68.1   | V   | 74.0            | -5.9   | PK        | 0       | 1.0    | POS; RB 1 MHz; VB: 3 MHz |
| 5150.000  | 47.8   | H   | 54.0            | -6.2   | AVG       | 351     | 1.0    | POS; RB 1 MHz; VB: 10 Hz |
| 5149.520  | 62.4   | H   | 74.0            | -11.6  | PK        | 351     | 1.0    | POS; RB 1 MHz; VB: 3 MHz |

RB 1 MHz; VB 10 Hz Avg=Black Trace; RB1MHz VB3MHz Pk= Blue Trace; V



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |


Run # 2b, EUT on Channel #48 5240MHz - 802.11n20, Chain A+B+C

| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5240 MHz | 15.0          |
| 2     | 2437 MHz | 21.0          |

## 5350 MHz Band Edge Signal Radiated Field Strength

| Frequency | Level  | Pol | 15.209 / 15.247 |        | Detector  | Azimuth | Height | Comments                 |
|-----------|--------|-----|-----------------|--------|-----------|---------|--------|--------------------------|
| MHz       | dBμV/m | v/h | Limit           | Margin | Pk/QP/Avg | degrees | meters |                          |
| 5360.020  | 50.6   | V   | 54.0            | -3.4   | AVG       | 28      | 1.0    | POS; RB 1 MHz; VB: 10 Hz |
| 5360.020  | 57.7   | V   | 74.0            | -16.3  | PK        | 28      | 1.0    | POS; RB 1 MHz; VB: 3 MHz |
| 5360.020  | 48.0   | H   | 54.0            | -6.0   | AVG       | 24      | 1.0    | POS; RB 1 MHz; VB: 10 Hz |
| 5359.940  | 55.4   | H   | 74.0            | -18.6  | PK        | 24      | 1.0    | POS; RB 1 MHz; VB: 3 MHz |

RB 1 MHz; VB 10 Hz Avg=Black Trace; RB1MHz VB3MHz Pk= Blue Trace; V



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

## Run #3, Band Edge Field Strength - 802.11n40, Chain A+B+C

Date of Test: 1/23/2013

Test Location: FT7

Test Engineer: Rafael Varelas

Config Change: none


## Run #3a, EUT on Channel #38 5190MHz - 802.11n40, Chain A+B+C

| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5190 MHz | 9.0           |
| 2     | 2437 MHz | 21.0          |

## 5150 MHz Band Edge Signal Field Strength

| Frequency | Level        | Pol | 15.209 / 15.247 |        | Detector  | Azimuth | Height | Comments                 |
|-----------|--------------|-----|-----------------|--------|-----------|---------|--------|--------------------------|
| MHz       | dB $\mu$ V/m | v/h | Limit           | Margin | Pk/QP/Avg | degrees | meters |                          |
| 5150.000  | 52.8         | V   | 54.0            | -1.2   | AVG       | 15      | 1.0    | POS; RB 1 MHz; VB: 10 Hz |
| 5150.000  | 70.0         | V   | 74.0            | -4.0   | PK        | 15      | 1.0    | POS; RB 1 MHz; VB: 3 MHz |
| 5148.960  | 47.2         | H   | 54.0            | -6.8   | AVG       | 358     | 1.0    | POS; RB 1 MHz; VB: 10 Hz |
| 5147.600  | 59.9         | H   | 74.0            | -14.1  | PK        | 358     | 1.0    | POS; RB 1 MHz; VB: 3 MHz |

RB 1 MHz; VB 10 Hz Avg=Black Trace; RB1MHz VB3MHz Pk= Blue Trace; V



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |


Run #3b, EUT on Channel #46 5230MHz - 802.11n40, Chain A+B+C

| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5230 MHz | 14.0          |
| 2     | 2437 MHz | 21.0          |

## 5350 MHz Band Edge Signal Radiated Field Strength

| Frequency | Level  | Pol | 15.209 / 15.247 |        | Detector  | Azimuth | Height | Comments                 |
|-----------|--------|-----|-----------------|--------|-----------|---------|--------|--------------------------|
| MHz       | dBμV/m | v/h | Limit           | Margin | Pk/QP/Avg | degrees | meters |                          |
| 5360.020  | 52.1   | V   | 54.0            | -1.9   | AVG       | 24      | 1.0    | POS; RB 1 MHz; VB: 10 Hz |
| 5372.120  | 62.2   | V   | 74.0            | -11.8  | PK        | 24      | 1.0    | POS; RB 1 MHz; VB: 3 MHz |
| 5360.020  | 45.5   | H   | 54.0            | -8.5   | AVG       | 36      | 1.0    | POS; RB 1 MHz; VB: 10 Hz |
| 5359.620  | 54.1   | H   | 74.0            | -19.9  | PK        | 36      | 1.0    | POS; RB 1 MHz; VB: 3 MHz |

RB 1 MHz; VB 10 Hz Avg=Black Trace; RB1MHz VB3MHz Pk= Blue Trace; V



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

## RSS 210 and FCC 15.407 (NII) Radiated Spurious Emissions

### Test Specific Details

Objective: The objective of this test session is to perform final qualification testing of the EUT with respect to the specification listed above.

### General Test Configuration

The EUT and all local support equipment were located on the turntable for radiated spurious emissions testing. All remote support equipment was located approximately 30 meters from the EUT.

For radiated emissions testing the measurement antenna was located 3 meters from the EUT.

### Ambient Conditions:

Temperature: 20.7 °C  
 Rel. Humidity: 36 %

### Summary of Results - Device Operating in the 5150-5250 MHz Band

| Run #   | Mode                  | Channel     | Power Setting | Measured Power | Test Performed                   | Limit  | Result / Margin                    |
|---------|-----------------------|-------------|---------------|----------------|----------------------------------|--------|------------------------------------|
| Run # 1 | 802.11a Chain A+B+C   | #36 5180MHz | 15.0          | -              | Restricted Band Edge at 5150 MHz | 15.209 | 50.7 dBµV/m @ 5150.0 MHz (-3.3 dB) |
|         |                       | #48 5240MHz | 15.0          | -              | Restricted Band Edge at 5350 MHz | 15.209 | 47.7 dBµV/m @ 5360.2 MHz (-6.3 dB) |
| Run # 2 | 802.11n20 Chain A+B+C | #36 5180MHz | 15.5          | -              | Restricted Band Edge at 5150 MHz | 15.209 | 52.9 dBµV/m @ 5149.9 MHz (-1.1 dB) |
|         |                       | #48 5240MHz | 16.0          | -              | Restricted Band Edge at 5350 MHz | 15.209 | 50.5 dBµV/m @ 5360.1 MHz (-3.5 dB) |
| Run # 3 | 802.11n40 Chain A+B+C | #38 5190MHz | 9.0           | -              | Restricted Band Edge at 5150 MHz | 15.209 | 53.0 dBµV/m @ 5150.0 MHz (-1.0 dB) |
|         |                       | #46 5230MHz | 15.0          | -              | Restricted Band Edge at 5350 MHz | 15.209 | 51.0 dBµV/m @ 5360.0 MHz (-3.0 dB) |

### Antenna:

| # | Model                   | Type  | Freq. Band (GHz) | Gain (dBi) | Ind/Out | Xpol? | Pt to Pt? |
|---|-------------------------|-------|------------------|------------|---------|-------|-----------|
| 3 | Enterasys WS-AI-DT04360 | Panel | 5.2              | 4          | Indoor  | No    | No        |





## EMC Test Data

|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
|           |                         | Account Manager: | Christine Krebill |
| Contact:  | George Fares            |                  |                   |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

### Modifications Made During Testing

No modifications were made to the EUT during testing

### Deviations From The Standard

No deviations were made from the requirements of the standard.

### Notes

#### ART GUI (Singleradio test) Or Command Line Script (multiple radio test)

ART GUI Used: No

ART GUI Boot File: -

-

ART GUI Calibration file: -

-

Command Line Script: 3710e 2nd Pilot\_925942 boot and initialize all 3 radios to NART Command Line Interface - HIGH POWER

|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

## Run # 1, Band Edge Field Strength - 802.11a, Chain A+B+C

Date of Test: 1/24/2013

Test Location: FT7

Test Engineer: Rafael Varelas


Config Change: none

## Run # 1a, EUT on Channel #36 5180MHz - 802.11a, Chain A+B+C

| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5180 MHz | 15.0          |
| 2     | 2437 MHz | 21.0          |

## 5150 MHz Band Edge Signal Field Strength

| Frequency | Level  | Pol | 15.209 / 15.247 |        | Detector  | Azimuth | Height | Comments                 |
|-----------|--------|-----|-----------------|--------|-----------|---------|--------|--------------------------|
| MHz       | dBμV/m | v/h | Limit           | Margin | Pk/QP/Avg | degrees | meters |                          |
| 5150.000  | 50.7   | H   | 54.0            | -3.3   | AVG       | 47      | 1.0    | POS; RB 1 MHz; VB: 10 Hz |
| 5148.000  | 67.4   | H   | 74.0            | -6.6   | PK        | 47      | 1.0    | POS; RB 1 MHz; VB: 3 MHz |
| 5150.000  | 43.2   | V   | 54.0            | -10.8  | AVG       | 226     | 1.3    | POS; RB 1 MHz; VB: 10 Hz |
| 5149.360  | 58.0   | V   | 74.0            | -16.0  | PK        | 226     | 1.3    | POS; RB 1 MHz; VB: 3 MHz |




|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

Run # 1b, EUT on Channel #48 5240MHz - 802.11a, Chain A+B+C

| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5240 MHz | 15.0          |
| 2     | 2437 MHz | 21.0          |

## 5350 MHz Band Edge Signal Radiated Field Strength

| Frequency | Level  | Pol | 15.209 / 15.247 |        | Detector  | Azimuth | Height | Comments                 |
|-----------|--------|-----|-----------------|--------|-----------|---------|--------|--------------------------|
| MHz       | dBμV/m | v/h | Limit           | Margin | Pk/QP/Avg | degrees | meters |                          |
| 5360.180  | 47.7   | H   | 54.0            | -6.3   | AVG       | 44      | 1.0    | POS; RB 1 MHz; VB: 10 Hz |
| 5359.540  | 55.7   | H   | 74.0            | -18.3  | PK        | 44      | 1.0    | POS; RB 1 MHz; VB: 3 MHz |
| 5351.920  | 41.3   | V   | 54.0            | -12.7  | AVG       | 28      | 1.4    | POS; RB 1 MHz; VB: 10 Hz |
| 5350.140  | 53.2   | V   | 74.0            | -20.8  | PK        | 28      | 1.4    | POS; RB 1 MHz; VB: 3 MHz |



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

## Run # 2, Band Edge Field Strength - 802.11n20, Chain A+B+C

Date of Test: 1/24/2013

Test Location: FT7

Test Engineer: Rafael Varelas


Config Change: none

## Run # 2a, EUT on Channel #36 5180MHz - 802.11n20, Chain A+B+C

| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5180 MHz | 15.5          |
| 2     | 2437 MHz | 21.0          |

## 5150 MHz Band Edge Signal Field Strength

| Frequency | Level  | Pol | 15.209 / 15.247 |        | Detector  | Azimuth | Height | Comments                 |
|-----------|--------|-----|-----------------|--------|-----------|---------|--------|--------------------------|
| MHz       | dBμV/m | v/h | Limit           | Margin | Pk/QP/Avg | degrees | meters |                          |
| 5149.870  | 52.9   | H   | 54.0            | -1.1   | AVG       | 82      | 1.0    | POS; RB 1 MHz; VB: 10 Hz |
| 5149.940  | 72.9   | H   | 74.0            | -1.1   | PK        | 82      | 1.0    | POS; RB 1 MHz; VB: 3 MHz |
| 5147.840  | 46.2   | V   | 54.0            | -7.8   | AVG       | 346     | 1.3    | POS; RB 1 MHz; VB: 10 Hz |
| 5146.150  | 61.9   | V   | 74.0            | -12.1  | PK        | 346     | 1.3    | POS; RB 1 MHz; VB: 3 MHz |




|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

Run # 2b, EUT on Channel #48 5240MHz - 802.11n20, Chain A+B+C

| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5240 MHz | 16.0          |
| 2     | 2437 MHz | 21.0          |

## 5350 MHz Band Edge Signal Radiated Field Strength

| Frequency | Level  | Pol | 15.209 / 15.247 |        | Detector  | Azimuth | Height | Comments                 |
|-----------|--------|-----|-----------------|--------|-----------|---------|--------|--------------------------|
| MHz       | dBμV/m | v/h | Limit           | Margin | Pk/QP/Avg | degrees | meters |                          |
| 5360.100  | 50.5   | H   | 54.0            | -3.5   | AVG       | 57      | 1.1    | POS; RB 1 MHz; VB: 10 Hz |
| 5359.940  | 59.5   | H   | 74.0            | -14.5  | PK        | 57      | 1.1    | POS; RB 1 MHz; VB: 3 MHz |
| 5360.100  | 45.6   | V   | 54.0            | -8.4   | AVG       | 36      | 1.4    | POS; RB 1 MHz; VB: 10 Hz |
| 5383.110  | 52.5   | V   | 74.0            | -21.5  | PK        | 36      | 1.4    | POS; RB 1 MHz; VB: 3 MHz |



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

## Run #3, Band Edge Field Strength - 802.11n40, Chain A+B+C

Date of Test: 1/24/2013

Test Location: FT7

Test Engineer: Rafael Varelas


Config Change: none

## Run #3a, EUT on Channel #38 5190MHz - 802.11n40, Chain A+B+C

| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5190 MHz | 9.0           |
| 2     | 2437 MHz | 21.0          |

## 5150 MHz Band Edge Signal Field Strength

| Frequency | Level  | Pol | 15.209 / 15.247 |        | Detector  | Azimuth | Height | Comments                 |
|-----------|--------|-----|-----------------|--------|-----------|---------|--------|--------------------------|
| MHz       | dBuV/m | v/h | Limit           | Margin | Pk/QP/Avg | degrees | meters |                          |
| 5150.000  | 53.0   | H   | 54.0            | -1.0   | AVG       | 53      | 1.0    | POS; RB 1 MHz; VB: 10 Hz |
| 5149.750  | 69.2   | H   | 74.0            | -4.8   | PK        | 53      | 1.0    | POS; RB 1 MHz; VB: 3 MHz |
| 5149.840  | 48.0   | V   | 54.0            | -6.0   | AVG       | 37      | 1.6    | POS; RB 1 MHz; VB: 10 Hz |
| 5147.350  | 62.0   | V   | 74.0            | -12.0  | PK        | 37      | 1.6    | POS; RB 1 MHz; VB: 3 MHz |




|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

Run #3b, EUT on Channel #46 5230MHz - 802.11n40, Chain A+B+C

| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5230 MHz | 15.0          |
| 2     | 2437 MHz | 21.0          |

## 5350 MHz Band Edge Signal Radiated Field Strength

| Frequency | Level  | Pol | 15.209 / 15.247 |        | Detector  | Azimuth | Height | Comments                 |
|-----------|--------|-----|-----------------|--------|-----------|---------|--------|--------------------------|
| MHz       | dBμV/m | v/h | Limit           | Margin | Pk/QP/Avg | degrees | meters |                          |
| 5360.020  | 51.0   | H   | 54.0            | -3.0   | AVG       | 59      | 1.1    | POS; RB 1 MHz; VB: 10 Hz |
| 5366.190  | 58.6   | H   | 74.0            | -15.4  | PK        | 59      | 1.1    | POS; RB 1 MHz; VB: 3 MHz |
| 5359.940  | 43.3   | V   | 54.0            | -10.7  | AVG       | 0       | 1.4    | POS; RB 1 MHz; VB: 10 Hz |
| 5358.100  | 53.2   | V   | 74.0            | -20.8  | PK        | 0       | 1.4    | POS; RB 1 MHz; VB: 3 MHz |



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

## RSS 210 and FCC 15.247 (DTS) Radiated Spurious Emissions

### Test Specific Details

Objective: The objective of this test session is to perform final qualification testing of the EUT with respect to the specification listed above.

### General Test Configuration

The EUT and all local support equipment were located on the turntable for radiated spurious emissions testing. All remote support equipment was located approximately 30 meters from the EUT.

For radiated emissions testing the measurement antenna was located 3 meters from the EUT.

### Ambient Conditions:

Temperature: 20.4 °C  
 Rel. Humidity: 36 %

### Summary of Results - Device Operating in the DTS Bands

| Run #   | Mode        | Channel  | Power Setting | Measured Power | Test Performed                    | Limit               | Result / Margin                     |
|---------|-------------|----------|---------------|----------------|-----------------------------------|---------------------|-------------------------------------|
| Run #1  | 802.11b     | 2412 MHz | 19            | -              | Radiated Emissions,<br>1 - 40 GHz | FCC 15.209 / 15.247 | 46.6 dBμV/m @ 5440.0 MHz (-7.4 dB)  |
|         | 802.11a     | 5180 MHz | 11            | -              |                                   |                     | 44.0 dBμV/m @ 1666.7 MHz (-10.0 dB) |
|         |             | 2437 MHz | 19            | -              |                                   |                     | 44.0 dBμV/m @ 1666.7 MHz (-10.0 dB) |
|         | Chain A+B+C | 5200 MHz | 11            | -              |                                   |                     | 44.0 dBμV/m @ 1666.7 MHz (-10.0 dB) |
| Run # 2 | 802.11g     | 2412 MHz | 19            | -              | Radiated Emissions,<br>1 - 40 GHz | FCC 15.209 / 15.247 | 44.0 dBμV/m @ 1666.8 MHz (-10.0 dB) |
|         | 802.11a     | 5180 MHz | 11            | -              |                                   |                     | 49.3 dBμV/m @ 5453.3 MHz (-4.7 dB)  |
|         |             | 2437 MHz | 19            | -              |                                   |                     | 44.0 dBμV/m @ 1666.7 MHz (-10.0 dB) |
|         | Chain A+B+C | 5200 MHz | 11            | -              |                                   |                     | 44.0 dBμV/m @ 1666.7 MHz (-10.0 dB) |
| Run # 3 | 802.11n20   | 2412 MHz | 20            | -              | Radiated Emissions,<br>1 - 40 GHz | FCC 15.209 / 15.247 | 50.1 dBμV/m @ 5453.3 MHz (-3.9 dB)  |
|         | 802.11n20   | 5180 MHz | 12            | -              |                                   |                     | 44.0 dBμV/m @ 1666.7 MHz (-10.0 dB) |
|         |             | 2437 MHz | 20            | -              |                                   |                     | 44.0 dBμV/m @ 1666.7 MHz (-10.0 dB) |
|         | Chain A+B+C | 5200 MHz | 12            | -              |                                   |                     | 49.4 dBμV/m @ 5453.3 MHz (-4.6 dB)  |





## EMC Test Data

|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

| Run #   | Mode        | Channel  | Power Setting | Measured Power | Test Performed                    | Limit               | Result / Margin                    |
|---------|-------------|----------|---------------|----------------|-----------------------------------|---------------------|------------------------------------|
| Run # 4 | 802.11n40   | 2422 MHz | 16            | -              | Radiated Emissions,<br>1 - 40 GHz | FCC 15.209 / 15.247 | 49.6 dBμV/m @ 5455.0 MHz (-4.4 dB) |
|         |             | 5190 MHz | 12            | -              |                                   |                     |                                    |
|         | 802.11n40   | 2437 MHz | 16            | -              |                                   |                     | 48.7 dBμV/m @ 5453.8 MHz (-5.3 dB) |
|         |             | 5230 MHz | 12            | -              |                                   |                     |                                    |
|         | Chain A+B+C | 2452 MHz | 16            | -              |                                   |                     | 47.0 dBμV/m @ 5456.9 MHz (-7.0 dB) |
|         |             | 5230 MHz | 12            | -              |                                   |                     |                                    |

### Antenna:

| # | Model                   | Type | Freq. Band (GHz) | Gain (dBi) | Ind/Out | Xpol? | Pt to Pt? |
|---|-------------------------|------|------------------|------------|---------|-------|-----------|
| 1 | Enterasys WS-AI-DX02360 | Omni | 2.4 & 5.2        | 2          | Indoor  | No    | No        |

### Modifications Made During Testing

No modifications were made to the EUT during testing

### Deviations From The Standard

No deviations were made from the requirements of the standard.

### Notes

Antenna: antenna(s) connected  
Duty Cycle: 99.0%

#### ART GUI (Singleradio test) Or Command Line Script (multiple radio test)

ART GUI Used: No  
ART GUI Boot File: -  
-  
ART GUI Calibration file: -  
-  
Command Line Script: 3710e 2nd Pilot\_925942 boot and initialize all 3 radios to NART Command Line Interface - LOW POWER

|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

Run #1, Radiated Spurious Emissions, 1-40GHz, 802.11b/802.11a, Chain A+B+C

Run #1a, EUT on Channel #1 2412MHz - 802.11b and Channel #36 5180MHz - 802.11a - Chain A+B+C

Date of Test: 2/6/13 & 2/7/13  
 Test Engineer: Rafael Varelas/ Jack Liu

Test Location: FT7  
 Config Change: None


| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5180 MHz | 11.0          |
| 2     | 2412 MHz | 19.0          |

## Spurious Radiated Emissions:

| Frequency | Level  | Pol | 15.209/15.407 |        | Detector  | Azimuth | Height | Comments |
|-----------|--------|-----|---------------|--------|-----------|---------|--------|----------|
| MHz       | dBμV/m | v/h | Limit         | Margin | PK/QP/Avg | degrees | meters |          |
| 5440.040  | 46.6   | V   | 54.0          | -7.4   | AVG       | 20      | 1.0    |          |
| 5440.580  | 57.4   | V   | 74.0          | -16.6  | PK        | 20      | 1.0    |          |
| 3215.990  | 49.8   | V   | 68.3          | -18.5  | PK        | 47      | 1.0    | Note 1   |
| 1608.040  | 39.8   | V   | 54.0          | -14.2  | AVG       | 126     | 1.0    |          |
| 1607.990  | 44.6   | V   | 74.0          | -29.4  | PK        | 126     | 1.0    |          |
| 1666.700  | 44.6   | V   | 54.0          | -9.4   | AVG       | 235     | 1.0    |          |
| 1666.730  | 47.5   | V   | 74.0          | -26.5  | PK        | 235     | 1.0    |          |

Note 1:

For emissions in restricted bands, the limit of 15.209 was used. For all other emissions, the limit is -27dBm/MHz for peak measurements in a measurement bandwidth of 1MHz.



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |


Run #1b, EUT on Channel #6 2437MHz - 802.11b and Channel #40 5200MHz - 802.11a, Chain A+B+C

| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5200 MHz | 11.0          |
| 2     | 2437 MHz | 19.0          |

## Spurious Radiated Emissions:

| Frequency | Level  | Pol | 15.209/15.407 |        | Detector  | Azimuth | Height | Comments |
|-----------|--------|-----|---------------|--------|-----------|---------|--------|----------|
| MHz       | dBμV/m | v/h | Limit         | Margin | Pk/QP/Avg | degrees | meters |          |
| 1666.700  | 44.0   | V   | 54.0          | -10.0  | AVG       | 235     | 1.0    |          |
| 1666.780  | 46.9   | V   | 74.0          | -27.1  | PK        | 235     | 1.0    |          |
| 2111.800  | 50.8   | V   | 68.3          | -17.5  | PK        | 30      | 1.0    | Note 1   |
| 3249.370  | 48.2   | V   | 68.3          | -20.1  | PK        | 54      | 1.0    | Note 1   |
| 1624.670  | 37.8   | V   | 54.0          | -16.2  | AVG       | 149     | 1.4    |          |
| 1624.470  | 43.1   | V   | 74.0          | -30.9  | PK        | 149     | 1.4    |          |
| 6933.000  | 50.1   | V   | 68.3          | -18.2  | PK        | 138     | 1.9    | Note 1   |

|         |   |
|---------|---|
| Note 1: | For emissions in restricted bands, the limit of 15.209 was used. For all other emissions, the limit is -27dBm/MHz for peak measurements in a measurement bandwidth of 1MHz.                     |
| Note 2: | Scans made between 18 - 40GHz with the measurement antenna moved around the card and its antennas 20-50cm from the device indicated there were no significant emissions in this frequency range |



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |


Run #1c, EUT on Channel #11 2462MHz - 802.11b and Channel #48 5240MHz - 802.11a, Chain A+B+C

| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5240 MHz | 11.0          |
| 2     | 2462 MHz | 19.0          |

## Spurious Radiated Emissions:

| Frequency | Level        | Pol | 15.209/15.407 |        | Detector  | Azimuth | Height | Comments |
|-----------|--------------|-----|---------------|--------|-----------|---------|--------|----------|
| MHz       | dB $\mu$ V/m | v/h | Limit         | Margin | Pk/QP/Avg | degrees | meters |          |
| 1666.730  | 44.0         | H   | 54.0          | -10.0  | AVG       | 167     | 1.4    |          |
| 1666.960  | 47.3         | H   | 74.0          | -26.7  | PK        | 167     | 1.4    |          |
| 2112.000  | 50.2         | V   | 68.3          | -18.1  | PK        | 338     | 1.0    | Note 1   |
| 3282.610  | 49.3         | V   | 68.3          | -19.0  | PK        | 50      | 1.0    | Note 1   |

Note 1: For emissions in restricted bands, the limit of 15.209 was used. For all other emissions, the limit is -27dBm/MHz for peak measurements in a measurement bandwidth of 1MHz.





## EMC Test Data

|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

Run #2, Radiated Spurious Emissions, 1-40GHz, 802.11g/802.11a, Chain A+B+C

Run #2a, EUT on Channel #1 2412MHz - 802.11g and Channel #36 5180MHz - 802.11a - Chain A+B+C

Date of Test: 2/7/2013  
Test Engineer: Rafael Varelas/ Jack Liu

Test Location: FT7  
Config Change: None


| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5180 MHz | 11.0          |
| 2     | 2412 MHz | 19.0          |

### Spurious Radiated Emissions:

| Frequency | Level        | Pol | 15.209/15.407 |        | Detector  | Azimuth | Height | Comments |
|-----------|--------------|-----|---------------|--------|-----------|---------|--------|----------|
| MHz       | dB $\mu$ V/m | v/h | Limit         | Margin | Pk/QP/Avg | degrees | meters |          |
| 1666.760  | 44.0         | V   | 54.0          | -10.0  | AVG       | 237     | 1.0    |          |
| 1666.710  | 46.8         | V   | 74.0          | -27.2  | PK        | 237     | 1.0    |          |
| 5465.000  | 55.5         | V   | 68.3          | -12.8  | PK        | 30      | 1.0    | Note 1   |
| 3215.900  | 50.9         | V   | 68.3          | -17.4  | PK        | 52      | 1.0    | Note 1   |
| 4960.110  | 39.3         | V   | 54.0          | -14.7  | AVG       | 149     | 1.5    |          |
| 4960.380  | 49.0         | V   | 74.0          | -25.0  | PK        | 149     | 1.5    |          |
| 6907.030  | 50.2         | V   | 68.3          | -18.1  | PK        | 144     | 1.3    | Note 1   |
| 1608.060  | 41.6         | V   | 54.0          | -12.4  | AVG       | 337     | 1.0    |          |
| 1607.850  | 46.1         | V   | 74.0          | -27.9  | PK        | 337     | 1.0    |          |

Note 1:

For emissions in restricted bands, the limit of 15.209 was used. For all other emissions, the limit is -27dBm/MHz for peak measurements in a measurement bandwidth of 1MHz.



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |


Run #2b, EUT on Channel #6 2437MHz - 802.11g and Channel #40 5200MHz - 802.11a, Chain A+B+C

| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5200 MHz | 11.0          |
| 2     | 2437 MHz | 19.0          |

## Spurious Radiated Emissions:

| Frequency | Level  | Pol | 15.209/15.407 |        | Detector  | Azimuth | Height | Comments |
|-----------|--------|-----|---------------|--------|-----------|---------|--------|----------|
| MHz       | dBμV/m | v/h | Limit         | Margin | PK/QP/Avg | degrees | meters |          |
| 5453.330  | 49.3   | V   | 54.0          | -4.7   | AVG       | 276     | 1.3    |          |
| 5453.330  | 60.0   | V   | 74.0          | -14.0  | PK        | 276     | 1.3    |          |
| 3249.250  | 49.7   | V   | 68.3          | -18.6  | PK        | 52      | 1.0    | Note 1   |
| 6933.450  | 49.9   | V   | 68.3          | -18.4  | PK        | 138     | 1.9    | Note 1   |
| 1666.720  | 44.7   | V   | 54.0          | -9.3   | AVG       | 236     | 1.0    |          |
| 1666.750  | 47.6   | V   | 74.0          | -26.4  | PK        | 236     | 1.0    |          |
| 4960.100  | 37.3   | V   | 54.0          | -16.7  | AVG       | 317     | 1.0    |          |
| 4960.100  | 47.8   | V   | 74.0          | -26.2  | PK        | 317     | 1.0    |          |
| 5035.800  | 41.2   | V   | 54.0          | -12.8  | AVG       | 96      | 1.0    |          |
| 5026.340  | 52.2   | V   | 74.0          | -21.8  | PK        | 96      | 1.0    |          |
| 1624.730  | 38.8   | V   | 54.0          | -15.2  | AVG       | 340     | 1.0    |          |
| 1624.680  | 44.4   | V   | 74.0          | -29.6  | PK        | 340     | 1.0    |          |
| 2076.470  | 54.9   | V   | 68.3          | -13.4  | PK        | 339     | 1.1    | Note 1   |

|         |   |
|---------|---|
| Note 1: | For emissions in restricted bands, the limit of 15.209 was used. For all other emissions, the limit is -27dBm/MHz for peak measurements in a measurement bandwidth of 1MHz.                     |
| Note 2: | Scans made between 18 - 40GHz with the measurement antenna moved around the card and its antennas 20-50cm from the device indicated there were no significant emissions in this frequency range |



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |


Run #2c, EUT on Channel #11 2462MHz - 802.11g and Channel #48 5240MHz - 802.11a, Chain A+B+C

| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5240 MHz | 11.0          |
| 2     | 2462 MHz | 19.0          |

## Spurious Radiated Emissions:

| Frequency | Level  | Pol | 15.209/15.407 |        | Detector  | Azimuth | Height | Comments |
|-----------|--------|-----|---------------|--------|-----------|---------|--------|----------|
| MHz       | dBμV/m | v/h | Limit         | Margin | Pk/QP/Avg | degrees | meters |          |
| 1666.700  | 44.0   | V   | 54.0          | -10.0  | AVG       | 237     | 1.0    |          |
| 1666.700  | 47.1   | V   | 74.0          | -26.9  | PK        | 237     | 1.0    |          |
| 2112.660  | 52.5   | V   | 68.3          | -15.8  | PK        | 28      | 1.0    | Note 1   |
| 5456.130  | 43.7   | V   | 54.0          | -10.3  | AVG       | 33      | 1.3    |          |
| 5456.800  | 54.7   | V   | 74.0          | -19.3  | PK        | 33      | 1.3    |          |
| 3282.630  | 50.8   | V   | 68.3          | -17.5  | PK        | 50      | 1.0    | Note 1   |
| 5040.200  | 42.1   | V   | 54.0          | -11.9  | AVG       | 147     | 1.4    |          |
| 5041.870  | 52.2   | V   | 74.0          | -21.8  | PK        | 147     | 1.4    |          |

Note 1: For emissions in restricted bands, the limit of 15.209 was used. For all other emissions, the limit is -27dBm/MHz for peak measurements in a measurement bandwidth of 1MHz.



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

Run #3, Radiated Spurious Emissions, 1-40GHz, 802.11n20/802.11n20, Chain A+B+C

Run #3a, EUT on Channel #1 2412MHz - 802.11n20 and Channel #36 5180MHz - 802.11n20 - Chain A+B+C

Date of Test: 2/7/2013

Test Location: FT7

Test Engineer: Rafael Varelas/ Jack Liu

Config Change: None


| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5180 MHz | 12.0          |
| 2     | 2412 MHz | 20.0          |

## Spurious Radiated Emissions:

| Frequency | Level  | Pol | 15.209/15.407 |        | Detector  | Azimuth | Height | Comments |
|-----------|--------|-----|---------------|--------|-----------|---------|--------|----------|
| MHz       | dBuV/m | v/h | Limit         | Margin | Pk/QP/Avg | degrees | meters |          |
| 5453.330  | 50.1   | V   | 54.0          | -3.9   | AVG       | 136     | 1.3    |          |
| 5449.530  | 60.6   | V   | 74.0          | -13.4  | PK        | 136     | 1.3    |          |
| 3216.020  | 51.0   | V   | 68.3          | -17.3  | PK        | 48      | 1.0    | Note 1   |
| 2075.270  | 51.7   | V   | 68.3          | -16.6  | PK        | 79      | 1.0    | Note 1   |
| 4960.030  | 41.4   | V   | 54.0          | -12.6  | AVG       | 138     | 1.3    |          |
| 4960.250  | 49.4   | V   | 74.0          | -24.6  | PK        | 138     | 1.3    |          |
| 5040.170  | 42.8   | V   | 54.0          | -11.2  | AVG       | 318     | 1.0    |          |
| 5039.600  | 53.4   | V   | 74.0          | -20.6  | PK        | 318     | 1.0    |          |
| 1666.730  | 44.6   | V   | 54.0          | -9.4   | AVG       | 234     | 1.0    |          |
| 1666.630  | 47.6   | V   | 74.0          | -26.4  | PK        | 234     | 1.0    |          |
| 1607.930  | 41.3   | V   | 54.0          | -12.7  | AVG       | 340     | 1.0    |          |
| 1607.930  | 45.8   | V   | 74.0          | -28.2  | PK        | 340     | 1.0    |          |

Note 1:

For emissions in restricted bands, the limit of 15.209 was used. For all other emissions, the limit is -27dBm/MHz for peak measurements in a measurement bandwidth of 1MHz.





|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |


Run #3b, EUT on Channel #6 2437MHz - 802.11n20 and Channel #40 5200MHz - 802.11n20, Chain A+B+C

| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5200 MHz | 12.0          |
| 2     | 2437 MHz | 20.0          |

## Spurious Radiated Emissions:

| Frequency | Level  | Pol | 15.209/15.407 |        | Detector  | Azimuth | Height | Comments |
|-----------|--------|-----|---------------|--------|-----------|---------|--------|----------|
| MHz       | dBμV/m | v/h | Limit         | Margin | Pk/QP/Avg | degrees | meters |          |
| 1666.740  | 44.0   | V   | 54.0          | -10.0  | AVG       | 234     | 1.0    |          |
| 1666.540  | 46.8   | V   | 74.0          | -27.2  | PK        | 234     | 1.0    |          |
| 5480.000  | 56.0   | V   | 68.3          | -12.3  | PK        | 33      | 1.0    | Note 1   |
| 3249.430  | 48.9   | V   | 68.3          | -19.4  | PK        | 53      | 1.0    | Note 1   |
| 6933.480  | 49.7   | V   | 68.3          | -18.6  | PK        | 139     | 1.9    | Note 1   |
| 5040.200  | 42.0   | V   | 54.0          | -12.0  | AVG       | 145     | 1.2    |          |
| 5022.670  | 52.9   | V   | 74.0          | -21.1  | PK        | 145     | 1.2    |          |
| 4960.050  | 39.0   | V   | 54.0          | -15.0  | AVG       | 77      | 1.0    |          |
| 4960.030  | 48.1   | V   | 74.0          | -25.9  | PK        | 77      | 1.0    |          |
| 1624.630  | 38.7   | V   | 54.0          | -15.3  | AVG       | 336     | 1.0    |          |
| 1624.580  | 44.3   | V   | 74.0          | -29.7  | PK        | 336     | 1.0    |          |

|         |   |
|---------|---|
| Note 1: | For emissions in restricted bands, the limit of 15.209 was used. For all other emissions, the limit is -27dBm/MHz for peak measurements in a measurement bandwidth of 1MHz.                     |
| Note 2: | Scans made between 18 - 40GHz with the measurement antenna moved around the card and its antennas 20-50cm from the device indicated there were no significant emissions in this frequency range |



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |


Run #3c, EUT on Channel #11 2462MHz - 802.11n20 and Channel #48 5240MHz - 802.11n20, Chain A+B+C

| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5240 MHz | 12.0          |
| 2     | 2462 MHz | 20.0          |

## Spurious Radiated Emissions:

| Frequency | Level  | Pol | 15.209/15.407 |        | Detector  | Azimuth | Height | Comments |
|-----------|--------|-----|---------------|--------|-----------|---------|--------|----------|
| MHz       | dBμV/m | v/h | Limit         | Margin | Pk/QP/Avg | degrees | meters |          |
| 5453.260  | 49.4   | V   | 54.0          | -4.6   | AVG       | 277     | 1.3    |          |
| 5448.860  | 60.1   | V   | 74.0          | -13.9  | PK        | 277     | 1.3    |          |
| 3282.700  | 49.5   | V   | 68.3          | -18.8  | PK        | 45      | 1.0    | Note 1   |
| 5000.130  | 41.3   | V   | 54.0          | -12.7  | AVG       | 148     | 1.5    |          |
| 5000.050  | 49.9   | V   | 74.0          | -24.1  | PK        | 148     | 1.5    |          |
| 1666.670  | 42.9   | H   | 54.0          | -11.1  | AVG       | 168     | 1.3    |          |
| 1666.890  | 46.0   | H   | 74.0          | -28.0  | PK        | 168     | 1.3    |          |
| 2079.530  | 53.1   | V   | 68.3          | -15.2  | PK        | 271     | 1.8    | Note 1   |
| 1641.120  | 43.8   | V   | 68.3          | -24.5  | PK        | 336     | 1.0    | Note 1   |

Note 1: For emissions in restricted bands, the limit of 15.209 was used. For all other emissions, the limit is -27dBm/MHz for peak measurements in a measurement bandwidth of 1MHz.



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

Run #4, Radiated Spurious Emissions, 1-40GHz, 802.11n40/802.11n40, Chain A+B+C

Run #4a, EUT on Channel #3 2422MHz - 802.11n40 and Channel #38 5190MHz - 802.11n40 - Chain A+B+C

Date of Test: 2/7/2013  
 Test Engineer: Rafael Varelas/ Jack Liu

Test Location: FT7  
 Config Change: None


| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5190 MHz | 12.0          |
| 2     | 2422 MHz | 16.0          |

## Spurious Radiated Emissions:

| Frequency | Level  | Pol | 15.209/15.407 |        | Detector  | Azimuth | Height | Comments |
|-----------|--------|-----|---------------|--------|-----------|---------|--------|----------|
| MHz       | dBμV/m | v/h | Limit         | Margin | Pk/QP/Avg | degrees | meters |          |
| 5455.000  | 49.6   | V   | 54.0          | -4.4   | AVG       | 136     | 1.3    |          |
| 5454.510  | 61.8   | V   | 74.0          | -12.2  | PK        | 136     | 1.3    |          |
| 2112.130  | 52.1   | V   | 68.3          | -16.2  | PK        | 30      | 1.0    | Note 1   |
| 1666.720  | 44.3   | V   | 54.0          | -9.7   | AVG       | 233     | 1.0    |          |
| 1666.840  | 47.1   | V   | 74.0          | -26.9  | PK        | 233     | 1.0    |          |
| 1614.700  | 38.1   | V   | 54.0          | -15.9  | AVG       | 339     | 1.0    |          |
| 1614.850  | 43.8   | V   | 74.0          | -30.2  | PK        | 339     | 1.0    |          |
| 3229.350  | 50.3   | V   | 68.3          | -18.0  | PK        | 50      | 1.0    | Note 1   |
| 5000.080  | 42.7   | V   | 54.0          | -11.3  | AVG       | 147     | 1.9    |          |
| 4999.900  | 52.4   | V   | 74.0          | -21.6  | PK        | 147     | 1.9    |          |

Note 1:

For emissions in restricted bands, the limit of 15.209 was used. For all other emissions, the limit is -27dBm/MHz for peak measurements in a measurement bandwidth of 1MHz.



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

Run #4b, EUT on Channel #6 2437MHz - 802.11n40 and Channel #46 5230MHz - 802.11n40, Chain A+B+C


| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5230 MHz | 12.0          |
| 2     | 2437 MHz | 16.0          |

## Spurious Radiated Emissions:

| Frequency | Level  | Pol | 15.209/15.407 |        | Detector  | Azimuth | Height | Comments |
|-----------|--------|-----|---------------|--------|-----------|---------|--------|----------|
| MHz       | dBμV/m | v/h | Limit         | Margin | PK/QP/Avg | degrees | meters |          |
| 5453.750  | 48.7   | V   | 54.0          | -5.3   | AVG       | 296     | 1.1    |          |
| 5451.320  | 59.1   | V   | 74.0          | -14.9  | PK        | 296     | 1.1    |          |
| 1666.720  | 43.3   | H   | 54.0          | -10.7  | AVG       | 167     | 1.3    |          |
| 1666.890  | 46.3   | H   | 74.0          | -27.7  | PK        | 167     | 1.3    |          |
| 1624.680  | 36.8   | V   | 54.0          | -17.2  | AVG       | 342     | 1.0    |          |
| 1624.730  | 42.9   | V   | 74.0          | -31.1  | PK        | 342     | 1.0    |          |
| 2112.260  | 51.8   | V   | 68.3          | -16.5  | PK        | 28      | 1.0    | Note 1   |
| 3246.080  | 42.4   | V   | 68.3          | -25.9  | PK        | 52      | 1.0    | Note 1   |
| 5040.090  | 45.0   | V   | 54.0          | -9.0   | AVG       | 138     | 1.3    |          |
| 5040.450  | 54.6   | V   | 74.0          | -19.4  | PK        | 138     | 1.3    |          |
| 4960.110  | 41.3   | V   | 54.0          | -12.7  | AVG       | 148     | 1.6    |          |
| 4960.180  | 50.2   | V   | 74.0          | -23.8  | PK        | 148     | 1.6    |          |

Note 1: For emissions in restricted bands, the limit of 15.209 was used. For all other emissions, the limit is -27dBm/MHz for peak measurements in a measurement bandwidth of 1MHz.

Note 2: Scans made between 18 - 40GHz with the measurement antenna moved around the card and its antennas 20-50cm from the device indicated there were no significant emissions in this frequency range



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

Run #4c, EUT on Channel #9 2452MHz - 802.11n40 and Channel #46 5230MHz - 802.11n40, Chain A+B+C


| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5230 MHz | 12.0          |
| 2     | 2452 MHz | 16.0          |

## Spurious Radiated Emissions:

| Frequency | Level  | Pol | 15.209/15.407 |        | Detector  | Azimuth | Height | Comments |
|-----------|--------|-----|---------------|--------|-----------|---------|--------|----------|
| MHz       | dBμV/m | v/h | Limit         | Margin | Pk/QP/Avg | degrees | meters |          |
| 5456.870  | 47.0   | V   | 54.0          | -7.0   | AVG       | 28      | 1.0    |          |
| 5458.740  | 58.1   | V   | 74.0          | -15.9  | PK        | 28      | 1.0    |          |
| 1936.030  | 45.7   | V   | 68.3          | -22.6  | PK        | 37      | 1.1    | Note 1   |
| 3269.390  | 48.9   | V   | 68.3          | -19.4  | PK        | 51      | 1.0    | Note 1   |
| 4960.000  | 40.7   | V   | 54.0          | -13.3  | AVG       | 134     | 1.3    |          |
| 4959.960  | 49.3   | V   | 74.0          | -24.7  | PK        | 134     | 1.3    |          |
| 1666.750  | 44.5   | V   | 54.0          | -9.5   | AVG       | 229     | 1.0    |          |
| 1666.710  | 47.4   | V   | 74.0          | -26.6  | PK        | 229     | 1.0    |          |
| 5040.090  | 44.3   | V   | 54.0          | -9.7   | AVG       | 138     | 1.3    |          |
| 5040.070  | 52.7   | V   | 74.0          | -21.3  | PK        | 138     | 1.3    |          |
| 2112.330  | 52.1   | V   | 68.3          | -16.2  | PK        | 21      | 1.0    | Note 1   |
| 1634.980  | 41.9   | V   | 68.3          | -26.4  | PK        | 342     | 1.0    | Note 1   |

Note 1:

For emissions in restricted bands, the limit of 15.209 was used. For all other emissions, the limit is -27dBm/MHz for peak measurements in a measurement bandwidth of 1MHz.



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

## RSS 210 and FCC 15.247 (DTS) Radiated Spurious Emissions

### Test Specific Details

Objective: The objective of this test session is to perform final qualification testing of the EUT with respect to the specification listed above.

### General Test Configuration

The EUT and all local support equipment were located on the turntable for radiated spurious emissions testing. All remote support equipment was located approximately 30 meters from the EUT.

For radiated emissions testing the measurement antenna was located 3 meters from the EUT.

### Ambient Conditions:

Temperature: 20.4 °C  
 Rel. Humidity: 36 %

### Summary of Results - Device Operating in the DTS Bands

| Run #   | Mode        | Channel  | Power Setting | Measured Power | Test Performed                    | Limit               | Result / Margin                     |
|---------|-------------|----------|---------------|----------------|-----------------------------------|---------------------|-------------------------------------|
| Run #1  | 802.11b     | 2412 MHz | 19            | -              | Radiated Emissions,<br>1 - 40 GHz | FCC 15.209 / 15.247 | 45.6 dBμV/m @ 1666.7 MHz (-8.4 dB)  |
|         | 802.11a     | 5180 MHz | 8             | -              |                                   |                     | 43.4 dBμV/m @ 1666.7 MHz (-10.6 dB) |
|         |             | 2437 MHz | 19            | -              |                                   |                     | 51.2 dBμV/m @ 5453.2 MHz (-2.8 dB)  |
|         | Chain A+B+C | 5200 MHz | 8             | -              |                                   |                     | 51.2 dBμV/m @ 5453.2 MHz (-2.8 dB)  |
| Run # 2 | 802.11g     | 2412 MHz | 19            | -              | Radiated Emissions,<br>1 - 40 GHz | FCC 15.209 / 15.247 | 52.0 dBμV/m @ 5458.4 MHz (-2.0 dB)  |
|         | 802.11a     | 5180 MHz | 8             | -              |                                   |                     | 50.5 dBμV/m @ 5458.4 MHz (-3.5 dB)  |
|         |             | 2437 MHz | 19            | -              |                                   |                     | 49.1 dBμV/m @ 5440.1 MHz (-4.9 dB)  |
|         | Chain A+B+C | 5200 MHz | 8             | -              |                                   |                     | 49.1 dBμV/m @ 5440.1 MHz (-4.9 dB)  |
| Run # 3 | 802.11n20   | 2412 MHz | 20            | -              | Radiated Emissions,<br>1 - 40 GHz | FCC 15.209 / 15.247 | 51.4 dBμV/m @ 5438.4 MHz (-2.6 dB)  |
|         | 802.11n20   | 5180 MHz | 9             | -              |                                   |                     | 50.7 dBμV/m @ 5440.0 MHz (-3.3 dB)  |
|         |             | 2437 MHz | 20            | -              |                                   |                     | 50.3 dBμV/m @ 5440.0 MHz (-3.7 dB)  |
|         | Chain A+B+C | 5200 MHz | 9             | -              |                                   |                     | 50.3 dBμV/m @ 5440.0 MHz (-3.7 dB)  |



## EMC Test Data

|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

| Run #   | Mode        | Channel  | Power Setting | Measured Power | Test Performed                    | Limit               | Result / Margin                    |
|---------|-------------|----------|---------------|----------------|-----------------------------------|---------------------|------------------------------------|
| Run # 4 | 802.11n40   | 2422 MHz | 16            | -              | Radiated Emissions,<br>1 - 40 GHz | FCC 15.209 / 15.247 | 51.7 dBμV/m @ 5439.9 MHz (-2.3 dB) |
|         |             | 5190 MHz | 10            | -              |                                   |                     |                                    |
|         | 802.11n40   | 2437 MHz | 16            | -              |                                   |                     | 49.9 dBμV/m @ 5440.1 MHz (-4.1 dB) |
|         |             | 5230 MHz | 10            | -              |                                   |                     |                                    |
|         | Chain A+B+C | 2452 MHz | 16            | -              |                                   |                     | 51.3 dBμV/m @ 5439.8 MHz (-2.7 dB) |
|         |             | 5230 MHz | 10            | -              |                                   |                     |                                    |

### Antenna:

| # | Model                   | Type   | Freq. Band (GHz) | Gain (dBi) | Ind/Out | Xpol?           | Pt to Pt? |
|---|-------------------------|--------|------------------|------------|---------|-----------------|-----------|
| 2 | Enterasys WS-AI-DT05120 | Sector | 2.4 & 5.2        | 5          | Indoor  | 2 Xpol / 1 Vert | No        |

### Modifications Made During Testing

No modifications were made to the EUT during testing

### Deviations From The Standard

No deviations were made from the requirements of the standard.

### Notes

Antenna: antenna(s) connected  
Duty Cycle: 99.0%

#### ART GUI (Singleradio test) Or Command Line Script (multiple radio test)

ART GUI Used: No  
ART GUI Boot File: -  
-  
ART GUI Calibration file: -  
-  
Command Line Script: 3710e 2nd Pilot\_925942 boot and initialize all 3 radios to NART Command Line Interface - LOW POWER

|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

Run #1, Radiated Spurious Emissions, 1-40GHz, 802.11b/802.11a, Chain A+B+C

Run #1a, EUT on Channel #1 2412MHz - 802.11b and Channel #36 5180MHz - 802.11a - Chain A+B+C

Date of Test: 2/5/13 & 2/6/13  
 Test Engineer: Rafael Varelas/ Jack Liu

Test Location: FT7  
 Config Change: None


| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5180 MHz | 8.0           |
| 2     | 2412 MHz | 19.0          |

## Spurious Radiated Emissions:

| Frequency | Level  | Pol | 15.209/15.407 |        | Detector  | Azimuth | Height | Comments |
|-----------|--------|-----|---------------|--------|-----------|---------|--------|----------|
| MHz       | dBμV/m | v/h | Limit         | Margin | Pk/QP/Avg | degrees | meters |          |
| 1666.680  | 45.6   | V   | 54.0          | -8.4   | AVG       | 170     | 1.4    |          |
| 1666.780  | 47.6   | V   | 74.0          | -26.4  | PK        | 170     | 1.4    |          |
| 4823.950  | 41.3   | V   | 54.0          | -12.7  | AVG       | 2       | 1.4    |          |
| 4823.980  | 45.6   | V   | 74.0          | -28.4  | PK        | 2       | 1.4    |          |
| 4999.980  | 39.0   | V   | 54.0          | -15.0  | AVG       | 36      | 1.0    |          |
| 4999.500  | 46.2   | V   | 74.0          | -27.8  | PK        | 36      | 1.0    |          |
| 1608.030  | 40.1   | V   | 54.0          | -13.9  | AVG       | 52      | 1.1    |          |
| 1608.120  | 42.6   | V   | 74.0          | -31.4  | PK        | 52      | 1.1    |          |
| 6906.800  | 48.4   | V   | 68.3          | -19.9  | PK        | 10      | 1.1    | Note 1   |
| 3216.100  | 50.9   | H   | 68.3          | -17.4  | PK        | 8       | 1.0    | Note 1   |
| 2090.020  | 55.8   | V   | 68.3          | -12.5  | PK        | 25      | 1.0    | Note 1   |

Note 1:

For emissions in restricted bands, the limit of 15.209 was used. For all other emissions, the limit is -27dBm/MHz for peak measurements in a measurement bandwidth of 1MHz.





|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |


Run #1b, EUT on Channel #6 2437MHz - 802.11b and Channel #40 5200MHz - 802.11a, Chain A+B+C

| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5200 MHz | 8.0           |
| 2     | 2437 MHz | 19.0          |

## Spurious Radiated Emissions:

| Frequency | Level        | Pol | 15.209/15.407 |        | Detector  | Azimuth | Height | Comments |
|-----------|--------------|-----|---------------|--------|-----------|---------|--------|----------|
| MHz       | dB $\mu$ V/m | v/h | Limit         | Margin | Pk/QP/Avg | degrees | meters |          |
| 1666.650  | 43.4         | V   | 54.0          | -10.6  | AVG       | 230     | 1.3    |          |
| 1666.660  | 45.7         | V   | 74.0          | -28.3  | PK        | 230     | 1.3    |          |
| 4873.930  | 39.7         | V   | 54.0          | -14.3  | AVG       | 8       | 1.3    |          |
| 4874.050  | 45.2         | V   | 74.0          | -28.8  | PK        | 8       | 1.3    |          |
| 1624.650  | 42.2         | H   | 54.0          | -11.8  | AVG       | 28      | 1.1    |          |
| 1624.620  | 44.6         | H   | 74.0          | -29.4  | PK        | 28      | 1.1    |          |
| 3249.280  | 49.3         | H   | 68.3          | -19.0  | PK        | 10      | 1.0    | Note 1   |

|         |   |
|---------|---|
| Note 1: | For emissions in restricted bands, the limit of 15.209 was used. For all other emissions, the limit is -27dBm/MHz for peak measurements in a measurement bandwidth of 1MHz.                     |
| Note 2: | Scans made between 18 - 40GHz with the measurement antenna moved around the card and its antennas 20-50cm from the device indicated there were no significant emissions in this frequency range |



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |


Run #1c, EUT on Channel #11 2462MHz - 802.11b and Channel #48 5240MHz - 802.11a, Chain A+B+C

| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5240 MHz | 8.0           |
| 2     | 2462 MHz | 19.0          |

## Spurious Radiated Emissions:

| Frequency | Level  | Pol | 15.209/15.407 |        | Detector  | Azimuth | Height | Comments |
|-----------|--------|-----|---------------|--------|-----------|---------|--------|----------|
| MHz       | dBμV/m | v/h | Limit         | Margin | Pk/QP/Avg | degrees | meters |          |
| 5453.200  | 51.2   | V   | 54.0          | -2.8   | AVG       | 22      | 1.3    |          |
| 5452.930  | 62.2   | V   | 74.0          | -11.8  | PK        | 22      | 1.3    |          |
| 4999.870  | 42.5   | V   | 54.0          | -11.5  | AVG       | 42      | 1.1    |          |
| 4999.200  | 52.3   | V   | 74.0          | -21.7  | PK        | 42      | 1.1    |          |
| 1666.730  | 45.4   | V   | 54.0          | -8.6   | AVG       | 170     | 1.4    |          |
| 1666.830  | 48.0   | V   | 74.0          | -26.0  | PK        | 170     | 1.4    |          |
| 3282.650  | 52.1   | H   | 68.3          | -16.2  | PK        | 6       | 1.0    | Note 1   |
| 1641.350  | 47.3   | H   | 68.3          | -21.0  | PK        | 30      | 1.1    | Note 1   |
| 2090.440  | 57.6   | V   | 68.3          | -10.7  | PK        | 26      | 1.0    | Note 1   |

Note 1: For emissions in restricted bands, the limit of 15.209 was used. For all other emissions, the limit is -27dBm/MHz for peak measurements in a measurement bandwidth of 1MHz.



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

Run #2, Radiated Spurious Emissions, 1-40GHz, 802.11g/802.11a, Chain A+B+C

Run #2a, EUT on Channel #1 2412MHz - 802.11g and Channel #36 5180MHz - 802.11a - Chain A+B+C

Date of Test: 2/5/2013 & 2/6/13  
 Test Engineer: Rafael Varelas/ Jack Liu


Test Location: FT7  
 Config Change: None

| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5180 MHz | 8.0           |
| 2     | 2412 MHz | 19.0          |

## Spurious Radiated Emissions:

| Frequency | Level  | Pol | 15.209/15.407 |        | Detector  | Azimuth | Height | Comments |
|-----------|--------|-----|---------------|--------|-----------|---------|--------|----------|
| MHz       | dBμV/m | v/h | Limit         | Margin | Pk/QP/Avg | degrees | meters |          |
| 5458.400  | 52.0   | V   | 54.0          | -2.0   | AVG       | 18      | 1.1    |          |
| 5458.400  | 62.9   | V   | 74.0          | -11.1  | PK        | 18      | 1.1    |          |
| 1666.730  | 44.2   | V   | 54.0          | -9.8   | AVG       | 166     | 1.9    |          |
| 1666.680  | 46.9   | V   | 74.0          | -27.1  | PK        | 166     | 1.9    |          |
| 1608.080  | 39.8   | V   | 54.0          | -14.2  | AVG       | 347     | 1.0    |          |
| 1607.950  | 44.9   | V   | 74.0          | -29.1  | PK        | 347     | 1.0    |          |
| 3216.070  | 53.7   | H   | 68.3          | -14.6  | PK        | 14      | 1.0    | Note 1   |
| 2088.060  | 60.7   | V   | 68.3          | -7.6   | PK        | 28      | 1.0    | Note 1   |

Note 1: For emissions in restricted bands, the limit of 15.209 was used. For all other emissions, the limit is -27dBm/MHz for peak measurements in a measurement bandwidth of 1MHz.



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

Run #2b, EUT on Channel #6 2437MHz - 802.11g and Channel #40 5200MHz - 802.11a, Chain A+B+C


| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5200 MHz | 8.0           |
| 2     | 2437 MHz | 19.0          |

## Spurious Radiated Emissions:

| Frequency | Level  | Pol | 15.209/15.407 |        | Detector  | Azimuth | Height | Comments |
|-----------|--------|-----|---------------|--------|-----------|---------|--------|----------|
| MHz       | dBuV/m | v/h | Limit         | Margin | Pk/QP/Avg | degrees | meters |          |
| 5458.380  | 50.5   | V   | 54.0          | -3.5   | AVG       | 19      | 1.0    |          |
| 5458.380  | 60.3   | V   | 74.0          | -13.7  | PK        | 19      | 1.0    |          |
| 3249.330  | 54.3   | H   | 68.3          | -14.0  | PK        | 10      | 1.0    | Note 1   |
| 2090.660  | 61.2   | V   | 68.3          | -7.1   | PK        | 22      | 1.0    | Note 1   |
| 1666.690  | 44.1   | V   | 54.0          | -9.9   | AVG       | 139     | 1.0    |          |
| 1666.640  | 46.8   | V   | 74.0          | -27.2  | PK        | 139     | 1.0    |          |
| 5000.130  | 42.9   | V   | 54.0          | -11.1  | AVG       | 15      | 1.0    |          |
| 5000.400  | 50.6   | V   | 74.0          | -23.4  | PK        | 15      | 1.0    |          |
| 1624.700  | 42.7   | V   | 54.0          | -11.3  | AVG       | 347     | 1.0    |          |
| 1624.590  | 47.7   | V   | 74.0          | -26.3  | PK        | 347     | 1.0    |          |

Note 1: For emissions in restricted bands, the limit of 15.209 was used. For all other emissions, the limit is -27dBm/MHz for peak measurements in a measurement bandwidth of 1MHz.

Note 2: Scans made between 18 - 40GHz with the measurement antenna moved around the card and its antennas 20-50cm from the device indicated there were no significant emissions in this frequency range



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

Run #2c, EUT on Channel #11 2462MHz - 802.11g and Channel #48 5240MHz - 802.11a, Chain A+B+C


| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5240 MHz | 8.0           |
| 2     | 2462 MHz | 19.0          |

## Spurious Radiated Emissions:

| Frequency | Level  | Pol | 15.209/15.407 |        | Detector  | Azimuth | Height | Comments |
|-----------|--------|-----|---------------|--------|-----------|---------|--------|----------|
| MHz       | dBμV/m | v/h | Limit         | Margin | Pk/QP/Avg | degrees | meters |          |
| 5440.050  | 49.1   | V   | 54.0          | -4.9   | AVG       | 28      | 1.0    |          |
| 5440.080  | 60.6   | V   | 74.0          | -13.4  | PK        | 28      | 1.0    |          |
| 3282.660  | 54.4   | H   | 68.3          | -13.9  | PK        | 5       | 1.0    | Note 1   |
| 4999.650  | 41.8   | V   | 54.0          | -12.2  | AVG       | 10      | 1.0    |          |
| 4999.100  | 52.2   | V   | 74.0          | -21.8  | PK        | 10      | 1.0    |          |
| 2208.000  | 46.8   | V   | 54.0          | -7.2   | AVG       | 28      | 1.1    |          |
| 2210.800  | 60.1   | V   | 74.0          | -13.9  | PK        | 28      | 1.1    |          |
| 1666.700  | 41.2   | V   | 54.0          | -12.8  | AVG       | 177     | 1.3    |          |
| 1666.600  | 44.9   | V   | 74.0          | -29.1  | PK        | 177     | 1.3    |          |
| 1641.370  | 49.4   | V   | 68.3          | -18.9  | PK        | 340     | 1.0    | Note 1   |

Note 1:

For emissions in restricted bands, the limit of 15.209 was used. For all other emissions, the limit is -27dBm/MHz for peak measurements in a measurement bandwidth of 1MHz.



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

Run #3, Radiated Spurious Emissions, 1-40GHz, 802.11n20/802.11n20, Chain A+B+C

Run #3a, EUT on Channel #1 2412MHz - 802.11n20 and Channel #36 5180MHz - 802.11n20 - Chain A+B+C

Date of Test: 2/5/13 & 2/6/13  
 Test Engineer: Rafael Varelas/ Jack Liu

Test Location: FT7  
 Config Change: None


| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5180 MHz | 9.0           |
| 2     | 2412 MHz | 20.0          |

## Spurious Radiated Emissions:

| Frequency | Level        | Pol | 15.209/15.407 |        | Detector  | Azimuth | Height | Comments |
|-----------|--------------|-----|---------------|--------|-----------|---------|--------|----------|
| MHz       | dB $\mu$ V/m | v/h | Limit         | Margin | Pk/QP/Avg | degrees | meters |          |
| 5438.400  | 51.4         | V   | 54.0          | -2.6   | AVG       | 29      | 1.0    |          |
| 5438.040  | 62.1         | V   | 74.0          | -11.9  | PK        | 29      | 1.0    |          |
| 1608.010  | 40.0         | V   | 54.0          | -14.0  | AVG       | 349     | 1.0    |          |
| 1608.020  | 45.2         | V   | 74.0          | -28.8  | PK        | 349     | 1.0    |          |
| 1666.690  | 43.9         | V   | 54.0          | -10.1  | AVG       | 179     | 1.5    |          |
| 1666.680  | 46.9         | V   | 74.0          | -27.1  | PK        | 179     | 1.5    |          |
| 2232.050  | 47.5         | H   | 54.0          | -6.5   | AVG       | 26      | 1.0    |          |
| 2233.040  | 59.6         | H   | 74.0          | -14.4  | PK        | 26      | 1.0    |          |
| 4959.950  | 44.4         | V   | 54.0          | -9.6   | AVG       | 44      | 1.0    |          |
| 4960.290  | 52.0         | V   | 74.0          | -22.0  | PK        | 44      | 1.0    |          |
| 3216.030  | 55.2         | H   | 68.3          | -13.1  | PK        | 10      | 1.0    | Note 1   |

Note 1:

For emissions in restricted bands, the limit of 15.209 was used. For all other emissions, the limit is -27dBm/MHz for peak measurements in a measurement bandwidth of 1MHz.



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |


Run #3b, EUT on Channel #6 2437MHz - 802.11n20 and Channel #40 5200MHz - 802.11n20, Chain A+B+C

| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5200 MHz | 9.0           |
| 2     | 2437 MHz | 20.0          |

## Spurious Radiated Emissions:

| Frequency | Level  | Pol | 15.209/15.407 |        | Detector  | Azimuth | Height | Comments |
|-----------|--------|-----|---------------|--------|-----------|---------|--------|----------|
| MHz       | dBμV/m | v/h | Limit         | Margin | Pk/QP/Avg | degrees | meters |          |
| 5440.020  | 50.7   | V   | 54.0          | -3.3   | AVG       | 15      | 1.0    |          |
| 5440.200  | 62.7   | V   | 74.0          | -11.3  | PK        | 15      | 1.0    |          |
| 3249.300  | 53.6   | H   | 68.3          | -14.7  | PK        | 12      | 1.0    | Note 1   |
| 5039.930  | 47.4   | V   | 54.0          | -6.6   | AVG       | 11      | 1.2    |          |
| 5052.430  | 57.5   | V   | 74.0          | -16.5  | PK        | 11      | 1.2    |          |
| 2222.950  | 45.9   | V   | 54.0          | -8.1   | AVG       | 21      | 1.2    |          |
| 2223.590  | 57.2   | V   | 74.0          | -16.8  | PK        | 21      | 1.2    |          |
| 1666.580  | 43.2   | V   | 54.0          | -10.8  | AVG       | 180     | 1.5    |          |
| 1666.650  | 46.2   | V   | 74.0          | -27.8  | PK        | 180     | 1.5    |          |
| 1624.660  | 42.0   | V   | 54.0          | -12.0  | AVG       | 341     | 1.0    |          |
| 1624.900  | 46.6   | V   | 74.0          | -27.4  | PK        | 341     | 1.0    |          |

|         |   |
|---------|---|
| Note 1: | For emissions in restricted bands, the limit of 15.209 was used. For all other emissions, the limit is -27dBm/MHz for peak measurements in a measurement bandwidth of 1MHz.                     |
| Note 2: | Scans made between 18 - 40GHz with the measurement antenna moved around the card and its antennas 20-50cm from the device indicated there were no significant emissions in this frequency range |



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

Run #3c, EUT on Channel #11 2462MHz - 802.11n20 and Channel #48 5240MHz - 802.11n20, Chain A+B+C


| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5240 MHz | 9.0           |
| 2     | 2462 MHz | 20.0          |

## Spurious Radiated Emissions:

| Frequency | Level  | Pol | 15.209/15.407 |        | Detector  | Azimuth | Height | Comments |
|-----------|--------|-----|---------------|--------|-----------|---------|--------|----------|
| MHz       | dBμV/m | v/h | Limit         | Margin | Pk/QP/Avg | degrees | meters |          |
| 5440.000  | 50.3   | V   | 54.0          | -3.7   | AVG       | 18      | 1.0    |          |
| 5440.310  | 62.0   | V   | 74.0          | -12.0  | PK        | 18      | 1.0    |          |
| 1641.310  | 49.2   | V   | 68.3          | -19.1  | PK        | 350     | 2.0    | Note 1   |
| 1666.690  | 43.6   | V   | 54.0          | -10.4  | AVG       | 180     | 1.5    |          |
| 1666.700  | 47.1   | V   | 74.0          | -26.9  | PK        | 180     | 1.5    |          |
| 2230.020  | 47.4   | H   | 54.0          | -6.6   | AVG       | 23      | 1.0    |          |
| 2230.600  | 59.5   | H   | 74.0          | -14.5  | PK        | 23      | 1.0    |          |
| 5048.190  | 44.9   | V   | 54.0          | -9.1   | AVG       | 8       | 1.0    |          |
| 5047.950  | 56.9   | V   | 74.0          | -17.1  | PK        | 8       | 1.0    |          |
| 3282.530  | 54.2   | H   | 68.3          | -14.1  | PK        | 2       | 1.0    | Note 1   |

Note 1:

For emissions in restricted bands, the limit of 15.209 was used. For all other emissions, the limit is -27dBm/MHz for peak measurements in a measurement bandwidth of 1MHz.





|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

Run #4, Radiated Spurious Emissions, 1-40GHz, 802.11n40/802.11n40, Chain A+B+C

Run #4a, EUT on Channel #3 2422MHz - 802.11n40 and Channel #38 5190MHz - 802.11n40 - Chain A+B+C

Date of Test: 2/5/2013 & 2/6/13  
 Test Engineer: Rafael Varelas/ Jack Liu

Test Location: FT7  
 Config Change: None


| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5190 MHz | 10.0          |
| 2     | 2422 MHz | 16.0          |

## Spurious Radiated Emissions:

| Frequency | Level  | Pol | 15.209/15.407 |        | Detector  | Azimuth | Height | Comments |
|-----------|--------|-----|---------------|--------|-----------|---------|--------|----------|
| MHz       | dBμV/m | v/h | Limit         | Margin | Pk/QP/Avg | degrees | meters |          |
| 5439.850  | 51.7   | V   | 54.0          | -2.3   | AVG       | 14      | 1.0    |          |
| 5439.890  | 63.8   | V   | 74.0          | -10.2  | PK        | 14      | 1.0    |          |
| 2232.500  | 45.7   | H   | 54.0          | -8.3   | AVG       | 19      | 1.0    |          |
| 2232.790  | 57.5   | H   | 74.0          | -16.5  | PK        | 19      | 1.0    |          |
| 5000.070  | 48.2   | V   | 54.0          | -5.8   | AVG       | 41      | 1.0    |          |
| 5000.610  | 57.9   | V   | 74.0          | -16.1  | PK        | 41      | 1.0    |          |
| 1666.710  | 43.8   | V   | 54.0          | -10.2  | AVG       | 178     | 1.3    |          |
| 1666.670  | 47.0   | V   | 74.0          | -27.0  | PK        | 178     | 1.3    |          |
| 3229.330  | 53.0   | V   | 68.3          | -15.3  | PK        | 348     | 1.0    | Note 1   |
| 1614.680  | 38.0   | V   | 54.0          | -16.0  | AVG       | 350     | 1.3    |          |
| 1614.830  | 43.0   | V   | 74.0          | -31.0  | PK        | 350     | 1.3    |          |

Note 1:

For emissions in restricted bands, the limit of 15.209 was used. For all other emissions, the limit is -27dBm/MHz for peak measurements in a measurement bandwidth of 1MHz.



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |


Run #4b, EUT on Channel #6 2437MHz - 802.11n40 and Channel #46 5230MHz - 802.11n40, Chain A+B+C

| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5230 MHz | 10.0          |
| 2     | 2437 MHz | 16.0          |

## Spurious Radiated Emissions:

| Frequency | Level  | Pol | 15.209/15.407 |        | Detector  | Azimuth | Height | Comments |
|-----------|--------|-----|---------------|--------|-----------|---------|--------|----------|
| MHz       | dBuV/m | v/h | Limit         | Margin | Pk/QP/Avg | degrees | meters |          |
| 5440.080  | 49.9   | V   | 54.0          | -4.1   | AVG       | 5       | 1.0    |          |
| 5441.450  | 60.8   | V   | 74.0          | -13.2  | PK        | 5       | 1.0    |          |
| 1624.670  | 39.6   | V   | 54.0          | -14.4  | AVG       | 341     | 1.3    |          |
| 1624.800  | 44.6   | V   | 74.0          | -29.4  | PK        | 341     | 1.3    |          |
| 1666.560  | 43.3   | V   | 54.0          | -10.7  | AVG       | 180     | 1.5    |          |
| 1666.580  | 46.6   | V   | 74.0          | -27.4  | PK        | 180     | 1.5    |          |
| 3249.200  | 51.6   | H   | 68.3          | -16.7  | PK        | 46      | 1.0    | Note 1   |
| 2228.830  | 44.9   | V   | 54.0          | -9.1   | AVG       | 25      | 1.1    |          |
| 2229.370  | 55.9   | V   | 74.0          | -18.1  | PK        | 25      | 1.1    |          |
| 5042.450  | 45.7   | V   | 54.0          | -8.3   | AVG       | 20      | 1.0    |          |
| 5043.720  | 58.2   | V   | 74.0          | -15.8  | PK        | 20      | 1.0    |          |

|         |   |
|---------|---|
| Note 1: | For emissions in restricted bands, the limit of 15.209 was used. For all other emissions, the limit is -27dBm/MHz for peak measurements in a measurement bandwidth of 1MHz.                     |
| Note 2: | Scans made between 18 - 40GHz with the measurement antenna moved around the card and its antennas 20-50cm from the device indicated there were no significant emissions in this frequency range |



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

Run #4c, EUT on Channel #9 2452MHz - 802.11n40 and Channel #46 5230MHz - 802.11n40, Chain A+B+C


| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5230 MHz | 10.0          |
| 2     | 2452 MHz | 16.0          |

## Spurious Radiated Emissions:

| Frequency | Level  | Pol | 15.209/15.407 |        | Detector  | Azimuth | Height | Comments |
|-----------|--------|-----|---------------|--------|-----------|---------|--------|----------|
| MHz       | dBμV/m | v/h | Limit         | Margin | Pk/QP/Avg | degrees | meters |          |
| 5439.840  | 51.3   | V   | 54.0          | -2.7   | AVG       | 14      | 1.0    |          |
| 5440.130  | 61.9   | V   | 74.0          | -12.1  | PK        | 14      | 1.0    |          |
| 1634.820  | 46.8   | H   | 68.3          | -21.5  | PK        | 9       | 1.1    | Note 1   |
| 2207.490  | 43.8   | H   | 54.0          | -10.2  | AVG       | 38      | 1.0    |          |
| 2207.260  | 56.2   | H   | 74.0          | -17.8  | PK        | 38      | 1.0    |          |
| 3269.320  | 52.0   | V   | 68.3          | -16.3  | PK        | 24      | 1.0    | Note 1   |
| 5051.780  | 45.5   | V   | 54.0          | -8.5   | AVG       | 34      | 1.0    |          |
| 5051.980  | 56.6   | V   | 74.0          | -17.4  | PK        | 34      | 1.0    |          |
| 1666.690  | 44.1   | H   | 54.0          | -9.9   | AVG       | 177     | 1.0    |          |
| 1666.600  | 47.4   | H   | 74.0          | -26.6  | PK        | 177     | 1.0    |          |

Note 1:

For emissions in restricted bands, the limit of 15.209 was used. For all other emissions, the limit is -27dBm/MHz for peak measurements in a measurement bandwidth of 1MHz.



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

## RSS 210 and FCC 15.247 (DTS) Radiated Spurious Emissions

### Test Specific Details

Objective: The objective of this test session is to perform final qualification testing of the EUT with respect to the specification listed above.

### General Test Configuration

The EUT and all local support equipment were located on the turntable for radiated spurious emissions testing. All remote support equipment was located approximately 30 meters from the EUT.

For radiated emissions testing the measurement antenna was located 3 meters from the EUT.

### Ambient Conditions:

Temperature: 20.4 °C  
 Rel. Humidity: 36 %

### Summary of Results - Device Operating in the DTS Bands

| Run #   | Mode        | Channel  | Power Setting | Measured Power | Test Performed                    | Limit               | Result / Margin                    |
|---------|-------------|----------|---------------|----------------|-----------------------------------|---------------------|------------------------------------|
| Run #1  | 802.11b     | 2412 MHz | 19            | -              | Radiated Emissions,<br>1 - 40 GHz | FCC 15.209 / 15.247 | 48.5 dBµV/m @ 5441.0 MHz (-5.5 dB) |
|         | 802.11a     | 5180 MHz | 9             | -              |                                   |                     | 48.6 dBµV/m @ 5440.2 MHz (-5.4 dB) |
|         |             | 2437 MHz | 19            | -              |                                   |                     | 48.0 dBµV/m @ 5440.1 MHz (-6.0 dB) |
|         | Chain A+B+C | 5200 MHz | 9             | -              |                                   |                     | 48.0 dBµV/m @ 5440.1 MHz (-6.0 dB) |
| Run # 2 | 802.11g     | 2412 MHz | 19            | -              | Radiated Emissions,<br>1 - 40 GHz | FCC 15.209 / 15.247 | 49.7 dBµV/m @ 5454.0 MHz (-4.3 dB) |
|         | 802.11a     | 5180 MHz | 9             | -              |                                   |                     | 48.6 dBµV/m @ 5440.0 MHz (-5.4 dB) |
|         |             | 2437 MHz | 19            | -              |                                   |                     | 48.2 dBµV/m @ 5439.9 MHz (-5.8 dB) |
|         | Chain A+B+C | 5200 MHz | 9             | -              |                                   |                     | 48.2 dBµV/m @ 5439.9 MHz (-5.8 dB) |
| Run # 3 | 802.11n20   | 2412 MHz | 20            | -              | Radiated Emissions,<br>1 - 40 GHz | FCC 15.209 / 15.247 | 49.4 dBµV/m @ 5440.1 MHz (-4.6 dB) |
|         | 802.11n20   | 5180 MHz | 9             | -              |                                   |                     | 50.1 dBµV/m @ 5440.0 MHz (-3.9 dB) |
|         |             | 2437 MHz | 20            | -              |                                   |                     | 48.0 dBµV/m @ 5437.1 MHz (-6.0 dB) |
|         | Chain A+B+C | 5200 MHz | 9             | -              |                                   |                     | 48.0 dBµV/m @ 5437.1 MHz (-6.0 dB) |



## EMC Test Data

|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

| Run #   | Mode        | Channel  | Power Setting | Measured Power | Test Performed                    | Limit               | Result / Margin                          |
|---------|-------------|----------|---------------|----------------|-----------------------------------|---------------------|--|
| Run # 4 | 802.11n40   | 2422 MHz | 16            | -              | Radiated Emissions,<br>1 - 40 GHz | FCC 15.209 / 15.247 | 51.3 dB $\mu$ V/m @ 5434.7 MHz (-2.7 dB) |
|         |             | 5190 MHz | 11            | -              |                                   |                     |  |
|         | 802.11n40   | 2437 MHz | 16            | -              |                                   |                     | 49.7 dB $\mu$ V/m @ 5456.8 MHz (-4.3 dB) |
|         |             | 5230 MHz | 11            | -              |                                   |                     |  |
|         | Chain A+B+C | 2452 MHz | 16            | -              |                                   |                     | 50.7 dB $\mu$ V/m @ 5456.8 MHz (-3.3 dB) |
|         |             | 5230 MHz | 11            | -              |                                   |                     |  |

### Antenna:

| # | Model                   | Type  | Freq. Band (GHz) | Gain (dBi) | Ind/Out | Xpol? | Pt to Pt? |
|---|-------------------------|-------|------------------|------------|---------|-------|-----------|
| 3 | Enterasys WS-AI-DT04360 | Panel | 2.4              | 3          | Indoor  | No    | No        |

### Modifications Made During Testing

No modifications were made to the EUT during testing

### Deviations From The Standard

No deviations were made from the requirements of the standard.

### Notes

Antenna: antenna(s) connected  
Duty Cycle: 99.0%

#### ART GUI (Singleradio test) Or Command Line Script (multiple radio test)

ART GUI Used: No  
ART GUI Boot File: -  
-  
ART GUI Calibration file: -  
-  
Command Line Script: 3710e 2nd Pilot\_925942 boot and initialize all 3 radios to NART Command Line Interface - LOW POWER

|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

Run #1, Radiated Spurious Emissions, 1-40GHz, 802.11b/802.11a, Chain A+B+C

Run #1a, EUT on Channel #1 2412MHz - 802.11b and Channel #36 5180MHz - 802.11a - Chain A+B+C

Date of Test: 2/6/2013  
 Test Engineer: Rafael Varelas/ Jack Liu

Test Location: FT7  
 Config Change: None


| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5180 MHz | 9.0           |
| 2     | 2412 MHz | 19.0          |

## Spurious Radiated Emissions:

| Frequency | Level  | Pol | 15.209/15.407 |        | Detector  | Azimuth | Height | Comments |
|-----------|--------|-----|---------------|--------|-----------|---------|--------|----------|
| MHz       | dBμV/m | v/h | Limit         | Margin | PK/QP/Avg | degrees | meters |          |
| 5441.030  | 48.5   | H   | 54.0          | -5.5   | AVG       | 89      | 1.0    |          |
| 5441.080  | 59.5   | H   | 74.0          | -14.5  | PK        | 89      | 1.0    |          |
| 6906.660  | 52.2   | H   | 68.3          | -16.1  | PK        | 360     | 1.0    | Note 1   |
| 3215.960  | 53.4   | H   | 68.3          | -14.9  | PK        | 346     | 1.0    | Note 1   |
| 2040.440  | 53.3   | H   | 68.3          | -15.0  | PK        | 355     | 1.0    | Note 1   |
| 1666.690  | 45.4   | H   | 54.0          | -8.6   | AVG       | 268     | 1.3    |          |
| 1666.750  | 48.1   | H   | 74.0          | -25.9  | PK        | 268     | 1.3    |          |
| 1608.060  | 51.4   | H   | 54.0          | -2.6   | AVG       | 98      | 1.0    |          |
| 1608.020  | 52.9   | H   | 74.0          | -21.1  | PK        | 98      | 1.0    |          |

Note 1:

For emissions in restricted bands, the limit of 15.209 was used. For all other emissions, the limit is -27dBm/MHz for peak measurements in a measurement bandwidth of 1MHz.



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

Run #1b, EUT on Channel #6 2437MHz - 802.11b and Channel #40 5200MHz - 802.11a, Chain A+B+C


| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5200 MHz | 9.0           |
| 2     | 2437 MHz | 19.0          |

## Spurious Radiated Emissions:

| Frequency | Level  | Pol | 15.209/15.407 |        | Detector  | Azimuth | Height | Comments |
|-----------|--------|-----|---------------|--------|-----------|---------|--------|----------|
| MHz       | dBuV/m | v/h | Limit         | Margin | Pk/QP/Avg | degrees | meters |          |
| 5440.230  | 48.6   | H   | 54.0          | -5.4   | AVG       | 84      | 1.0    |          |
| 5439.010  | 60.5   | H   | 74.0          | -13.5  | PK        | 84      | 1.0    |          |
| 2225.970  | 41.3   | H   | 54.0          | -12.7  | AVG       | 54      | 1.0    |          |
| 2227.400  | 52.8   | H   | 74.0          | -21.2  | PK        | 54      | 1.0    |          |
| 1624.710  | 47.4   | H   | 54.0          | -6.6   | AVG       | 96      | 1.0    |          |
| 1624.690  | 49.7   | H   | 74.0          | -24.3  | PK        | 96      | 1.0    |          |
| 1666.530  | 45.5   | H   | 54.0          | -8.5   | AVG       | 265     | 1.3    |          |
| 1666.640  | 48.4   | H   | 74.0          | -25.6  | PK        | 265     | 1.3    |          |
| 3249.360  | 52.7   | H   | 68.3          | -15.6  | PK        | 348     | 1.2    | Note 1   |
| 2040.110  | 53.8   | H   | 68.3          | -14.5  | PK        | 340     | 1.0    | Note 1   |

Note 1: For emissions in restricted bands, the limit of 15.209 was used. For all other emissions, the limit is -27dBm/MHz for peak measurements in a measurement bandwidth of 1MHz.

Note 2: Scans made between 18 - 40GHz with the measurement antenna moved around the card and its antennas 20-50cm from the device indicated there were no significant emissions in this frequency range



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |


Run #1c, EUT on Channel #11 2462MHz - 802.11b and Channel #48 5240MHz - 802.11a, Chain A+B+C

| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5240 MHz | 9.0           |
| 2     | 2462 MHz | 19.0          |

## Spurious Radiated Emissions:

| Frequency | Level  | Pol | 15.209/15.407 |        | Detector  | Azimuth | Height | Comments |
|-----------|--------|-----|---------------|--------|-----------|---------|--------|----------|
| MHz       | dBμV/m | v/h | Limit         | Margin | Pk/QP/Avg | degrees | meters |          |
| 5440.100  | 48.0   | H   | 54.0          | -6.0   | AVG       | 74      | 1.0    |          |
| 5439.770  | 58.7   | H   | 74.0          | -15.3  | PK        | 74      | 1.0    |          |
| 2039.960  | 54.4   | H   | 68.3          | -13.9  | PK        | 343     | 1.0    | Note 1   |
| 3282.510  | 52.9   | H   | 68.3          | -15.4  | PK        | 348     | 1.1    | Note 1   |
| 1666.670  | 45.3   | H   | 54.0          | -8.7   | AVG       | 265     | 1.3    |          |
| 1666.660  | 47.9   | H   | 74.0          | -26.1  | PK        | 265     | 1.3    |          |
| 1641.270  | 46.0   | H   | 68.3          | -22.3  | PK        | 98      | 1.0    | Note 1   |
| 2219.810  | 44.4   | H   | 54.0          | -9.6   | AVG       | 95      | 1.0    |          |
| 2220.740  | 55.5   | H   | 74.0          | -18.5  | PK        | 95      | 1.0    |          |

Note 1: For emissions in restricted bands, the limit of 15.209 was used. For all other emissions, the limit is -27dBm/MHz for peak measurements in a measurement bandwidth of 1MHz.





|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

Run #2, Radiated Spurious Emissions, 1-40GHz, 802.11g/802.11a, Chain A+B+C

Run #2a, EUT on Channel #1 2412MHz - 802.11g and Channel #36 5180MHz - 802.11a - Chain A+B+C

Date of Test: 2/6/2013  
 Test Engineer: Rafael Varelas/ Jack Liu  
 Test Location: FT7  
 Config Change: None


| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5180 MHz | 9.0           |
| 2     | 2412 MHz | 19.0          |

## Spurious Radiated Emissions:

| Frequency | Level        | Pol | 15.209/15.407 |        | Detector  | Azimuth | Height | Comments |
|-----------|--------------|-----|---------------|--------|-----------|---------|--------|----------|
| MHz       | dB $\mu$ V/m | v/h | Limit         | Margin | Pk/QP/Avg | degrees | meters |          |
| 5454.030  | 49.7         | H   | 54.0          | -4.3   | AVG       | 82      | 1.0    |          |
| 5452.540  | 60.3         | H   | 74.0          | -13.7  | PK        | 82      | 1.0    |          |
| 2215.170  | 45.1         | H   | 54.0          | -8.9   | AVG       | 91      | 1.0    |          |
| 2216.140  | 56.5         | H   | 74.0          | -17.5  | PK        | 91      | 1.0    |          |
| 1598.560  | 36.2         | H   | 54.0          | -17.8  | AVG       | 93      | 1.0    |          |
| 1598.350  | 49.1         | H   | 74.0          | -24.9  | PK        | 93      | 1.0    |          |
| 1666.700  | 44.7         | H   | 54.0          | -9.3   | AVG       | 266     | 1.3    |          |
| 1666.730  | 48.0         | H   | 74.0          | -26.0  | PK        | 266     | 1.3    |          |
| 2040.170  | 57.2         | H   | 68.3          | -11.1  | PK        | 331     | 1.0    | Note 1   |
| 3215.960  | 54.9         | H   | 68.3          | -13.4  | PK        | 348     | 1.0    | Note 1   |
| 6906.500  | 52.3         | H   | 68.3          | -16.0  | PK        | 360     | 1.2    | Note 1   |

Note 1:

For emissions in restricted bands, the limit of 15.209 was used. For all other emissions, the limit is -27dBm/MHz for peak measurements in a measurement bandwidth of 1MHz.



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |


Run #2b, EUT on Channel #6 2437MHz - 802.11g and Channel #40 5200MHz - 802.11a, Chain A+B+C

| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5200 MHz | 9.0           |
| 2     | 2437 MHz | 19.0          |

## Spurious Radiated Emissions:

| Frequency | Level  | Pol | 15.209/15.407 |        | Detector  | Azimuth | Height | Comments |
|-----------|--------|-----|---------------|--------|-----------|---------|--------|----------|
| MHz       | dBuV/m | v/h | Limit         | Margin | Pk/QP/Avg | degrees | meters |          |
| 5440.010  | 48.6   | H   | 54.0          | -5.4   | AVG       | 76      | 1.0    |          |
| 5439.120  | 59.7   | H   | 74.0          | -14.3  | PK        | 76      | 1.0    |          |
| 6933.410  | 51.8   | H   | 68.3          | -16.5  | PK        | 359     | 1.0    | Note 1   |
| 3249.370  | 54.4   | H   | 68.3          | -13.9  | PK        | 350     | 1.2    | Note 1   |
| 2039.800  | 57.5   | H   | 68.3          | -10.8  | PK        | 332     | 1.0    | Note 1   |
| 1666.750  | 45.2   | H   | 54.0          | -8.8   | AVG       | 268     | 1.3    |          |
| 1666.740  | 48.1   | H   | 74.0          | -25.9  | PK        | 268     | 1.3    |          |
| 1624.710  | 45.4   | H   | 54.0          | -8.6   | AVG       | 98      | 1.0    |          |
| 1624.640  | 51.1   | H   | 74.0          | -22.9  | PK        | 98      | 1.0    |          |
| 2222.400  | 44.5   | H   | 54.0          | -9.5   | AVG       | 98      | 1.0    |          |
| 2224.370  | 56.6   | H   | 74.0          | -17.4  | PK        | 98      | 1.0    |          |

|         |   |
|---------|---|
| Note 1: | For emissions in restricted bands, the limit of 15.209 was used. For all other emissions, the limit is -27dBm/MHz for peak measurements in a measurement bandwidth of 1MHz.                     |
| Note 2: | Scans made between 18 - 40GHz with the measurement antenna moved around the card and its antennas 20-50cm from the device indicated there were no significant emissions in this frequency range |



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

Run #2c, EUT on Channel #11 2462MHz - 802.11g and Channel #48 5240MHz - 802.11a, Chain A+B+C


| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5240 MHz | 9.0           |
| 2     | 2462 MHz | 19.0          |

## Spurious Radiated Emissions:

| Frequency | Level  | Pol | 15.209/15.407 |        | Detector  | Azimuth | Height | Comments |
|-----------|--------|-----|---------------|--------|-----------|---------|--------|----------|
| MHz       | dBμV/m | v/h | Limit         | Margin | Pk/QP/Avg | degrees | meters |          |
| 5439.900  | 48.2   | H   | 54.0          | -5.8   | AVG       | 74      | 1.0    |          |
| 5440.220  | 59.2   | H   | 74.0          | -14.8  | PK        | 74      | 1.0    |          |
| 2222.000  | 45.2   | H   | 54.0          | -8.8   | AVG       | 94      | 1.0    |          |
| 2220.160  | 57.5   | H   | 74.0          | -16.5  | PK        | 94      | 1.0    |          |
| 1641.440  | 49.6   | H   | 68.3          | -18.7  | PK        | 104     | 1.0    | Note 1   |
| 1666.730  | 44.7   | H   | 54.0          | -9.3   | AVG       | 265     | 1.3    |          |
| 1666.820  | 48.4   | H   | 74.0          | -25.6  | PK        | 265     | 1.3    |          |
| 3282.720  | 53.8   | H   | 68.3          | -14.5  | PK        | 347     | 1.2    | Note 1   |
| 2040.060  | 57.2   | H   | 68.3          | -11.1  | PK        | 332     | 1.0    | Note 1   |

Note 1:

For emissions in restricted bands, the limit of 15.209 was used. For all other emissions, the limit is -27dBm/MHz for peak measurements in a measurement bandwidth of 1MHz.



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

Run #3, Radiated Spurious Emissions, 1-40GHz, 802.11n20/802.11n20, Chain A+B+C

Run #3a, EUT on Channel #1 2412MHz - 802.11n20 and Channel #36 5180MHz - 802.11n20 - Chain A+B+C

Date of Test: 2/6/2013  
 Test Engineer: Rafael Varelas/ Jack Liu

Test Location: FT7  
 Config Change: None


| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5180 MHz | 9.0           |
| 2     | 2412 MHz | 20.0          |

## Spurious Radiated Emissions:

| Frequency | Level  | Pol | 15.209/15.407 |        | Detector  | Azimuth | Height | Comments |
|-----------|--------|-----|---------------|--------|-----------|---------|--------|----------|
| MHz       | dBμV/m | v/h | Limit         | Margin | Pk/QP/Avg | degrees | meters |          |
| 5440.130  | 49.4   | H   | 54.0          | -4.6   | AVG       | 83      | 1.0    |          |
| 5439.460  | 61.1   | H   | 74.0          | -12.9  | PK        | 83      | 1.0    |          |
| 6906.770  | 52.4   | H   | 68.3          | -15.9  | PK        | 359     | 1.0    | Note 1   |
| 2039.730  | 56.5   | H   | 68.3          | -11.8  | PK        | 345     | 1.0    | Note 1   |
| 3216.070  | 54.9   | H   | 68.3          | -13.4  | PK        | 350     | 1.0    | Note 1   |
| 1666.510  | 44.8   | H   | 54.0          | -9.2   | AVG       | 262     | 1.3    |          |
| 1666.740  | 47.9   | H   | 74.0          | -26.1  | PK        | 262     | 1.3    |          |
| 1608.030  | 46.5   | H   | 54.0          | -7.5   | AVG       | 95      | 1.0    |          |
| 1607.960  | 53.7   | H   | 74.0          | -20.3  | PK        | 95      | 1.0    |          |
| 2225.020  | 44.4   | H   | 54.0          | -9.6   | AVG       | 84      | 1.0    |          |
| 2226.610  | 56.6   | H   | 74.0          | -17.4  | PK        | 84      | 1.0    |          |

Note 1:

For emissions in restricted bands, the limit of 15.209 was used. For all other emissions, the limit is -27dBm/MHz for peak measurements in a measurement bandwidth of 1MHz.



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |


Run #3b, EUT on Channel #6 2437MHz - 802.11n20 and Channel #40 5200MHz - 802.11n20, Chain A+B+C

| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5200 MHz | 9.0           |
| 2     | 2437 MHz | 20.0          |

## Spurious Radiated Emissions:

| Frequency | Level  | Pol | 15.209/15.407 |        | Detector  | Azimuth | Height | Comments |
|-----------|--------|-----|---------------|--------|-----------|---------|--------|----------|
| MHz       | dBuV/m | v/h | Limit         | Margin | PK/QP/Avg | degrees | meters |          |
| 5439.950  | 50.1   | H   | 54.0          | -3.9   | AVG       | 78      | 1.0    |          |
| 5439.910  | 60.7   | H   | 74.0          | -13.3  | PK        | 78      | 1.0    |          |
| 2228.590  | 45.1   | H   | 54.0          | -8.9   | AVG       | 84      | 1.0    |          |
| 2228.110  | 57.3   | H   | 74.0          | -16.7  | PK        | 84      | 1.0    |          |
| 1624.690  | 45.1   | H   | 54.0          | -8.9   | AVG       | 103     | 1.0    |          |
| 1624.530  | 52.0   | H   | 74.0          | -22.0  | PK        | 103     | 1.0    |          |
| 1666.700  | 44.7   | H   | 54.0          | -9.3   | AVG       | 264     | 1.3    |          |
| 1666.820  | 48.1   | H   | 74.0          | -25.9  | PK        | 264     | 1.3    |          |
| 2039.760  | 57.6   | H   | 68.3          | -10.7  | PK        | 334     | 1.0    | Note 1   |
| 3249.240  | 53.5   | H   | 68.3          | -14.8  | PK        | 348     | 1.0    | Note 1   |
| 6933.330  | 52.0   | H   | 68.3          | -16.3  | PK        | 355     | 1.0    | Note 1   |

|         |   |
|---------|---|
| Note 1: | For emissions in restricted bands, the limit of 15.209 was used. For all other emissions, the limit is -27dBm/MHz for peak measurements in a measurement bandwidth of 1MHz.                     |
| Note 2: | Scans made between 18 - 40GHz with the measurement antenna moved around the card and its antennas 20-50cm from the device indicated there were no significant emissions in this frequency range |



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |


Run #3c, EUT on Channel #11 2462MHz - 802.11n20 and Channel #48 5240MHz - 802.11n20, Chain A+B+C

| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5240 MHz | 9.0           |
| 2     | 2462 MHz | 20.0          |

## Spurious Radiated Emissions:

| Frequency | Level  | Pol | 15.209/15.407 |        | Detector  | Azimuth | Height | Comments |
|-----------|--------|-----|---------------|--------|-----------|---------|--------|----------|
| MHz       | dBμV/m | v/h | Limit         | Margin | Pk/QP/Avg | degrees | meters |          |
| 5437.100  | 48.0   | H   | 54.0          | -6.0   | AVG       | 84      | 1.0    |          |
| 5436.360  | 59.9   | H   | 74.0          | -14.1  | PK        | 84      | 1.0    |          |
| 3282.760  | 54.2   | H   | 68.3          | -14.1  | PK        | 348     | 1.2    | Note 1   |
| 2040.590  | 57.4   | H   | 68.3          | -10.9  | PK        | 332     | 1.0    | Note 1   |
| 1666.850  | 43.9   | H   | 54.0          | -10.1  | AVG       | 266     | 1.4    |          |
| 1666.560  | 46.7   | H   | 74.0          | -27.3  | PK        | 266     | 1.4    |          |
| 1641.280  | 49.9   | H   | 68.3          | -18.4  | PK        | 97      | 1.0    | Note 1   |
| 2227.930  | 46.4   | H   | 54.0          | -7.6   | AVG       | 92      | 1.0    |          |
| 2229.550  | 57.9   | H   | 74.0          | -16.1  | PK        | 92      | 1.0    |          |

Note 1: For emissions in restricted bands, the limit of 15.209 was used. For all other emissions, the limit is -27dBm/MHz for peak measurements in a measurement bandwidth of 1MHz.



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

Run #4, Radiated Spurious Emissions, 1-40GHz, 802.11n40/802.11n40, Chain A+B+C

Run #4a, EUT on Channel #3 2422MHz - 802.11n40 and Channel #38 5190MHz - 802.11n40 - Chain A+B+C

Date of Test: 2/6/2013  
 Test Engineer: Rafael Varelas/ Jack Liu

Test Location: FT7  
 Config Change: None


| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5190 MHz | 11.0          |
| 2     | 2422 MHz | 16.0          |

## Spurious Radiated Emissions:

| Frequency | Level  | Pol | 15.209/15.407 |        | Detector  | Azimuth | Height | Comments |
|-----------|--------|-----|---------------|--------|-----------|---------|--------|----------|
| MHz       | dBμV/m | v/h | Limit         | Margin | Pk/QP/Avg | degrees | meters |          |
| 5434.650  | 51.3   | H   | 54.0          | -2.7   | AVG       | 82      | 1.0    |          |
| 5433.740  | 63.4   | H   | 74.0          | -10.6  | PK        | 82      | 1.0    |          |
| 2225.110  | 42.3   | H   | 54.0          | -11.7  | AVG       | 53      | 1.0    |          |
| 2226.860  | 53.6   | H   | 74.0          | -20.4  | PK        | 53      | 1.0    |          |
| 2100.410  | 52.8   | H   | 68.3          | -15.5  | PK        | 50      | 1.0    | Note 1   |
| 1614.730  | 44.8   | H   | 54.0          | -9.2   | AVG       | 92      | 1.0    |          |
| 1614.770  | 48.8   | H   | 74.0          | -25.2  | PK        | 92      | 1.0    |          |
| 1666.880  | 44.9   | H   | 54.0          | -9.1   | AVG       | 265     | 1.3    |          |
| 1666.840  | 48.3   | H   | 74.0          | -25.7  | PK        | 265     | 1.3    |          |
| 3229.400  | 54.7   | H   | 68.3          | -13.6  | PK        | 344     | 1.2    | Note 1   |
| 6919.810  | 54.3   | H   | 68.3          | -14.0  | PK        | 354     | 1.0    | Note 1   |

Note 1:

For emissions in restricted bands, the limit of 15.209 was used. For all other emissions, the limit is -27dBm/MHz for peak measurements in a measurement bandwidth of 1MHz.



|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

Run #4b, EUT on Channel #6 2437MHz - 802.11n40 and Channel #46 5230MHz - 802.11n40, Chain A+B+C


| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5230 MHz | 11.0          |
| 2     | 2437 MHz | 16.0          |

## Spurious Radiated Emissions:

| Frequency | Level  | Pol | 15.209/15.407 |        | Detector  | Azimuth | Height | Comments |
|-----------|--------|-----|---------------|--------|-----------|---------|--------|----------|
| MHz       | dBμV/m | v/h | Limit         | Margin | Pk/QP/Avg | degrees | meters |          |
| 5456.780  | 49.7   | H   | 54.0          | -4.3   | AVG       | 82      | 1.0    |          |
| 5455.000  | 60.8   | H   | 74.0          | -13.2  | PK        | 82      | 1.0    |          |
| 1624.720  | 43.6   | H   | 54.0          | -10.4  | AVG       | 95      | 1.0    |          |
| 1624.820  | 47.3   | H   | 74.0          | -26.7  | PK        | 95      | 1.0    |          |
| 1666.500  | 44.6   | H   | 54.0          | -9.4   | AVG       | 266     | 1.3    |          |
| 1666.610  | 47.3   | H   | 74.0          | -26.7  | PK        | 266     | 1.3    |          |
| 3249.130  | 52.8   | H   | 68.3          | -15.5  | PK        | 343     | 1.1    | Note 1   |
| 1935.860  | 52.1   | H   | 68.3          | -16.2  | PK        | 346     | 1.0    | Note 1   |
| 2036.330  | 54.5   | H   | 68.3          | -13.8  | PK        | 334     | 1.0    | Note 1   |
| 6973.400  | 52.8   | H   | 68.3          | -15.5  | PK        | 355     | 1.0    | Note 1   |

Note 1: For emissions in restricted bands, the limit of 15.209 was used. For all other emissions, the limit is -27dBm/MHz for peak measurements in a measurement bandwidth of 1MHz.

Note 2: Scans made between 18 - 40GHz with the measurement antenna moved around the card and its antennas 20-50cm from the device indicated there were no significant emissions in this frequency range





|           |                         |                  |                   |
|-----------|-------------------------|------------------|-------------------|
| Client:   | Flextronics             | Job Number:      | J89632            |
| Model:    | WS-AP3710e              | T-Log Number:    | T89830            |
| Contact:  | George Fares            | Account Manager: | Christine Krebill |
| Standard: | 15.247, 15.407, RSS-210 | Class:           | N/A               |

Run #4c, EUT on Channel #9 2452MHz - 802.11n40 and Channel #46 5230MHz - 802.11n40, Chain A+B+C


| Radio | Freq     | Power Setting |
|-------|----------|---------------|
| 1     | 5230 MHz | 11.0          |
| 2     | 2452 MHz | 16.0          |

## Spurious Radiated Emissions:

| Frequency | Level  | Pol | 15.209/15.407 |        | Detector  | Azimuth | Height | Comments |
|-----------|--------|-----|---------------|--------|-----------|---------|--------|----------|
| MHz       | dBμV/m | v/h | Limit         | Margin | Pk/QP/Avg | degrees | meters |          |
| 5456.840  | 50.7   | H   | 54.0          | -3.3   | AVG       | 82      | 1.0    |          |
| 5450.440  | 61.3   | H   | 74.0          | -12.7  | PK        | 82      | 1.0    |          |
| 4960.050  | 43.8   | H   | 54.0          | -10.2  | AVG       | 64      | 1.0    |          |
| 4959.980  | 50.9   | H   | 74.0          | -23.1  | PK        | 64      | 1.0    |          |
| 1666.720  | 44.6   | H   | 54.0          | -9.4   | AVG       | 265     | 1.3    |          |
| 1666.770  | 48.3   | H   | 74.0          | -25.7  | PK        | 265     | 1.3    |          |
| 5040.030  | 47.5   | H   | 54.0          | -6.5   | AVG       | 336     | 1.1    |          |
| 5040.050  | 55.2   | H   | 74.0          | -18.8  | PK        | 336     | 1.1    |          |
| 1634.960  | 46.9   | H   | 68.3          | -21.4  | PK        | 97      | 1.0    | Note 1   |
| 3269.340  | 53.4   | H   | 68.3          | -14.9  | PK        | 346     | 1.2    | Note 1   |
| 2039.980  | 54.6   | H   | 68.3          | -13.7  | PK        | 332     | 1.0    | Note 1   |
| 6973.470  | 53.0   | H   | 68.3          | -15.3  | PK        | 354     | 1.0    | Note 1   |

Note 1:

For emissions in restricted bands, the limit of 15.209 was used. For all other emissions, the limit is -27dBm/MHz for peak measurements in a measurement bandwidth of 1MHz.



*End of Report*

This page is intentionally blank and marks the last page of this test report.