

ETS Dr.GenZ Taiwan PS Co., LTD

FCC Registration No.: 930600

Industry Canada filed test laboratory Reg. No. IC 5679

Accredited Testing Laboratory



A2LA Cert.No.: 2300.01

PCTRB Accredited Type Certification Test House

FCC

TEST - REPORT

FCC RULES PART 15 / SUBPART C

FCC ID: QQGBT1022

Test report no.: W6M20603-6643-P-15

TABLE OF CONTENTS

1	GENERAL INFORMATION	3
1.1	Notes	3
1.2	Testing laboratory	4
1.2.1	Location	4
1.2.2	Details of accreditation status	4
1.3	Details of approval holder	4
1.4	Application details	5
1.5	General information of Test item	5
1.6	Test standards	6
2	TECHNICAL TEST	7
2.1	Summary of test results	7
2.2	Test environment	7
2.3	Test Equipment List	8
3	TEST RESULTS (ENCLOSURE)	14
3.1	Peak Output Power (transmitter)	15
3.2	Equivalent isotropic radiated power	17
3.2.1	Transmitter	17
3.3	RF Exposure Compliance Requirements	17
3.4	Out of Band Radiated Emissions	17
3.5	Transmitter Radiated Emissions in restricted Bands	18
3.6	Spurious emissions (tx)	19
3.7	Carrier Frequency Separation	22
3.8	Number of Hopping Frequencies	23
3.8.1	Pseudorandom Frequency Hopping Sequence	23
3.8.2	Coordination of hopping sequences to other transmitters	23
3.8.3	System Receiver Hopping Capability	23
3.9	Time of Occupancy (Dwell Time)	24
3.10	20dB Bandwidth	25
3.10.1	System Receiver Input Bandwidth	26
3.11	Band-edge Compliance of RF Emissions	26
3.12	Radiated Emissions from Receiver Section of Transceiver	28
3.13	Power Line Conducted Emission	31
	APPENDIX	33
	Appendix A	34
	Appendix B	35
	Appendix C	36
	Appendix D	37
	Appendix E	38
	Appendix F	39
	Appendix G	40
	Appendix H	41
	Appendix I	42
	Appendix J	43

Registration number: W6M20603-6643-P-15
FCC ID : QQGBT1022

1 General Information

1.1 Notes

The purpose of conformity testing is to increase the probability of adherence to the essential requirements or conformity specifications, as appropriate.

The complexity of the technical specifications, however, means that full and thorough testing is impractical for both technical and economic reasons.

Furthermore, there is no guarantee that a test sample which has Passed all the relevant tests conforms to a specification.

Neither is there any guarantee that such a test sample will interwork with other genuinely open systems.

The existence of the tests nevertheless provides the confidence that the test sample possesses the qualities as maintained and that its performance generally conforms to representative cases of communications equipment.

The test results of this test report relate exclusively to the item tested as specified in 1.5.

The test report may only be reproduced or published in full.

Reproduction or publication of extracts from the report requires the prior written approval of the ETS DR. GENZ TAIWAN PS CO., LTD.

Tester:

April 03, 2006

Jay Chaing



Date

ETS-Lab.


Name

Signature

Technical responsibility for area of testing:

April 03, 2006

Steven Chuang



Date

ETS

Name

Signature

Registration number: W6M20603-6643-P-15
FCC ID : QQGBT1022

1.2 Testing laboratory

1.2.1 Location

OATS
No.5-1, Shuang Sing Village,
LiShuei Rd., Wanli Township,
Taipei County 207, Taiwan (R.O.C.)

Company
ETS DR. GENZ TAIWAN PS CO., LTD.
6F, NO. 58, LANE 188, RUEY-KUANG RD.
NEIHU, TAIPEI 114, TAIWAN R.O.C.
Tel : 886-2-66068877
Fax : 886-2-66068879

1.2.2 Details of accreditation status

Accredited testing laboratory

A2LA-registration number: 2300.01

FCC filed test laboratory Reg. No. 930600

Industry Canada filed test laboratory Reg. No. IC 5679

PCTRB Accredited Type Certification Test House

1.3 Details of approval holder

Name	: J-Three International Holding Co., Ltd.
Street	: No.23-7, Dungshyh 12 Lirn Dungshyh Lii Pingchien City
Town	: Taoyuan Hsien 324
Country	: Taiwan, R.O.C.
Telephone	: +886-3-4606755
Fax	: +886-3-4606761
Contact	: Mr. David Wu
Telephone	: +886-3-4606755

Registration number: W6M20603-6643-P-15
FCC ID : QQGBT1022

1.4 Application details

Date of receipt of application : March 02, 2006
Date of receipt of test item : March 14, 2006
Date of test : from March 15, 2006 to March 30, 2006

1.5 General information of Test item

Type of test item : Bluetooth 2.0 ClassII Module
Model Number : BT1022
Hardware : V2.0
Software : V2.0
Serial number : without
Photos : see Annex

Technical data

Frequency band : 2.4 GHz – 2.4835 GHz
Frequency (ch A) : 2.402 GHz
Frequency (ch B) : 2.441 GHz
Frequency (ch C) : 2.480 GHz

Transmitter

Unom

Normal Mode

Power (ch A or **ch 0**) : **Conducted: -2.09 dBm**
Power (ch B or **ch 39**) : **Conducted: -1.51 dBm**
Power (ch C or **ch 78**) : **Conducted: -0.22 dBm**

EDR Mode

Power (ch A or **ch 0**) : **Conducted: -2.28 dBm**
Power (ch B or **ch 39**) : **Conducted: -0.66 dBm**
Power (ch C or **ch 78**) : **Conducted: -1.09 dBm**

Power supply : 120 VAC(power on pc)

Operation modes : duplex

Modulation Type : GFSK

Antenna Type : Chip Antenna

Antenna gain : -2.83 dBi

Registration number: W6M20603-6643-P-15
FCC ID : QQGBT1022

Host device : none

Classification :

Fixed Device	☒
Mobile Device (Human Body distance > 20cm)	☐
Portable Device (Human Body distance < 20cm)	☐

Manufacturer:
(if applicable)

Name : ./.
Street : ./.
Town : ./.
Country : ./.

Additional information : The test sample is designed as BT1022 device. Its pseudorandom hopping scheme, authentication, receiver parameters, synchronization procedure and other parameters are determined by BT1022 Specification.

1.6 Test standards

Technical standard : FCC RULES PART 15 / SUBPART C § 15.247

Registration number: W6M20603-6643-P-15
FCC ID : QQGBT1022

2 Technical test

2.1 Summary of test results

No deviations from the technical specification(s) were ascertained in the course of the tests performed.



or

The deviations as specified in 2.5 were ascertained in the course of the tests performed.



2.2 Test environment

Temperature	: 23 °C
Relative humidity content	: 20 ... 75 %
Air pressure	: 86 ... 103 kPa
Details of power supply	: 120 VAC(power on pc)
Extrem conditions parameters	: test voltage : -- extreme min :-- V max :-- V

Registration number: W6M20603-6643-P-15

FCC ID : QQGBT1022

2.3 Test Equipment List


No.	Test equipment	Type	Serial No.	Manufacturer	Cal. Date	Next Cal. Date
ETSTW-CE 001	EMI TEST RECEIVER	ESHS10	842121/013	R&S	2005/10/27	2006/10/26
ETSTW-CE 002	PREREULATOR MODE DC POWER SUPPLY	None	None			
ETSTW-CE 003	AC POWER SOURCE	APS-9102	D161137	GW		
ETSTW-CE 004	ZWEILEITER-V-NETZNACHBILDUNG TWO-LINE V-NETWORK	ESH3-Z5	840731/011	R&S	2005/10/25	2006/10/24
ETSTW-CE 005	Line-Impedance Stabilisation Network	NNBM 8126D	137	Schwarzbeck	2005/10/21	2006/10/20
ETSTW-CE 006	IMPULS-BEGRENZER PULSE LIMITER	ESH3-Z2	100226	R&S	2004/11/11	2006/11/10
ETSTW-CE 007	SPECTRUM ANALYZER 5GHz	FSB	849670/001	R&S		
ETSTW-CE 008	ABSORBING CLAMP	MDS 21	3469	ABSORPTIONS-MESSWANDLER-ZANGE	2005/10/24	2007/10/23
ETSTW-CE 009	TEMP.&HUMIDITY CHAMBER	GTH-225-40-1P-U	MAA0305-009	GIANT FORCE	2005/8/18	2006/8/17
ETSTW-CE 012	Dual-Phase-V-Network	NNB-2/16Z	03/10201	Telemeter	2005/4/12	2006/4/11
ETSTW-CS 001	SIGNAL GENERATOR	SMX	849254/003	R&S	2005/10/14	2006/10/13
ETSTW-CS 002	COUPLING AND DECOUPLING NETWORK	CDN S751	19263	SCHAFFNER	2005/10/14	2006/10/13
ETSTW-CS 003	COUPLING AND DECOUPLING NETWORK	CDN T400	19820	SCHAFFNER	2005/10/14	2006/10/13
ETSTW-CS 004	COUPLING AND DECOUPLING NETWORK	CDN M016	20053	SCHAFFNER	2005/10/27	2006/10/26
ETSTW-CS 005	RF Power Amplifier	100A250A	306547	AR	2005/10/14	2006/10/13
ETSTW-CS 004	6 dB Attenuator	HFP-5100-3/06 N M/F	2010876106			
ETSTW-RE 002	Function Generator	33220A	MY43004982	Agilent	2005/10/14	2007/10/13
ETSTW-RE 003	EMI TEST RECEIVER	ESI 26	831438/001	R&S	2005/10/24	2006/10/23
ETSTW-RE 004	EMI TEST RECEIVER	ESI 40	832427/004	R&S	2005/10/29	2006/10/30
ETSTW-RE 005	EMI TEST RECEIVER	ESVS10	843207/020	R&S	2005/10/16	2006/10/15
ETSTW-RE 010	PROGRAMMABLE LINEAR POWER SUPPLY	LPS-305	30503070181	MOTECH		
ETSTW-RE 011	PROGRAMMABLE LINEAR POWER SUPPLY	LPS-305	30503070165	MOTECH		
ETSTW-RE 012	TUNABLE BANDREJECT FILTER	D.C 0309	146	K&L		

Registration number: W6M20603-6643-P-15
FCC ID : QQGBT1022

ETSTW-RE 013	TUNABLE BANDREJECT FILTER	D.C 0036	397	K&L		
ETSTW-RE 015	ANTENNA	HK116	841489/003	R&S	2005/1/14	2007/1/11
ETSTW-RE 016	ANTENNA	HL223	848953/006	R&S	2005/1/14	2007/1/11
ETSTW-RE 017	ANTENNA	HL025	352886/001	R&S	2005/9/6	2007/9/3
ETSTW-RE 018	ANTENNA	AT4560	27212	AR	2004/11/8	2006/11/7
ETSTW-RE 019	ANTENNA , HORN	22240-25	121074	FM		
ETSTW-RE 020	MICROWAVE HORN ANTENNA	AT4002A	306915	AR		
ETSTW-RE 021	SWEEP GENERATOR	SWM05	835130/010	R&S	2005/10/14	2006/10/13
ETSTW-RE 022	AMPLIFIER	8447D	2944A09837	Brüel&Kjær	2005/10/14	2006/10/13
ETSTW-RE 027	Passive Loop Antenna	6512	34563	EMCO	2004/6/30	2006/6/29
ETSTW-RE 032	Millivoltmeter	URV 55	849086/013	R&S	2005/10/17	2006/10/16
ETSTW-RE 033	4CH 1GHz 5GS/s DSO	WAVERUNNER 6100A	LCRY0604P14508	LeCory	2005/8/11	2006/8/10
ETSTW-RE 034	Power Sensor	URV5-Z4	839313/006	R&S	2005/10/17	2006/10/16
ETSTW-RE 037	Log-Periodic DipoleArray Antenna	3148	00034546	EMCO	2004/11/18	2006/11/17
ETSTW-RE 038	Log-Periodic DipoleArray Antenna	3148	00034547	EMCO	2004/11/18	2006/11/17
ETSTW-RE 039	Biconical Antenna	3110B	41760	EMCO	2004/11/18	2006/11/17
ETSTW-RE 040	Biconical Antenna	3110B	41761	EMCO	2004/11/18	2006/11/17
ETSTW-RE 042	ANTENNA	HK116	100172	R&S	2005/1/14	2007/1/13
ETSTW-RE 043	ANTENNA	HL223	100166	R&S	2004/4/16	2006/4/15
ETSTW-RE 044	ANTENNA	HL050	100094	R&S		
ETSTW-RE 048	Triple Loop Antenna	HXYZ 9170	HXYZ 9170-134	Schwarzbeck	2005/3/22	2007/3/21
ETSTW-RE 049	TRILOG Super Broadband test Antenna	VULB 9160	9160-3185	Schwarzbeck	2005/5/19	2007/5/18
ETSTW-RE 055	SPECTRUM ANALYZER	FSU-26	200074	R&S	2005/9/6	2006/9/5
ETSTW-RE 056	Matching Pad (75W -> 50W)	57Z-3G	None			
ETSTW-RE 057	Matching Pad (75W -> 50W)	57Z-3G	None			
ETSTW-EMI 001	HARMONICS 1000	HAR1000-1P	93	EMC-PARTNER	2005/9/11	2006/11/10

Registration number: W6M20603-6643-P-15
FCC ID : QQGBT1022

ETSTW-EMS 001	Clamp BASELSTRASSE 160 CH-4242 LAUFEN	CN-EFT1000	354	EMC-PARTNER	2004/11/2	2006/11/1
ETSTW-EMS 003	EMC Immunity Test System	TRA2000IN6	579	EMC-PARTNER	2005/10/27	2006/10/26
ETSTW-EMS 004	ESD generator minizap	ESD2000	016	EMC-PARTNER	2005/10/27	2006/10/26
ETSTW-EMS 008	Safety Test Solutions	ELT-400	E-0039	Narda	2005/1/4	2007/1/3
ETSTW-EMS 009	Magnetic Field Antenna	MF1000-1	104	EMC-PARTNER	2004/12/3	2007/12/2
ETSTW-EMS 010	Coupling De-coupling Network	CDN-UTP8	014	EMC-PARTNER	2005/9/1	2008/8/31
ETSTW-EMS 012	EM Injection Clamp	F-2031-23MM	476	FCC	2005/8/11	2006/8/11
ETSTW-RS 001	14" COLOR VIDEO MONITOR	TP-1480HR	P009799	TOPICA		
ETSTW-RS 003	RF Power Amplifier	30S1G3	306933	AR		
ETSTW-RS 004	RF Power Amplifier	150W1000	307009	AR	2005/10/21	2006/10/20
ETSTW-RS 005	Electric Field Probe Type 8.3	EMR-20	BN 2244/20	Narda	2005/9/7	2006/9/6
ETSTW-RS 006	SIGNAL GENERATOR	SML03	101551	R&S	2005/10/21	2006/10/20
ETSTW-GSM 01	SIM Simulator	IT3	B2004-50106	ORGA	2005/9/15	2006/9/14
ETSTW-GSM 02	Universal Radio Communication Tester	CMU 200	103489	R&S	2005/11/15	2006/11/14
ETSTW-GSM 03	Agilent 8960 Test Set 1	E5515C	GB44052675	Agilent	2004/7/14	2006/7/13
ETSTW-GSM 04	Agilent 8960 Test Set 2	E5515C	GB44052665	Agilent	2004/7/14	2006/7/13
ETSTW-GSM 05	Agilent 8960 Test Set 3	E5515C	GB44052652	Agilent	2004/7/17	2006/7/16
ETSTW-GSM 06	Agilent 8960 Test Set 4	E5515C	GB44052684	Agilent	2004/7/16	2006/7/15
ETSTW-GSM 07	Agilent 8960 Test Set 5	E5515C	GB44052658	Agilent	2004/7/14	2006/7/13
ETSTW-GSM 08	Agilent 8960 Test Set 6	E5515C	GB44052666	Agilent	2004/7/16	2006/7/15
ETSTW-GSM 10	Combiner Wessex / Anite	B4605/100	053	Wessex / Anite	2004/7/14	2006/7/13
ETSTW-GSM 11	GSM 850,900,1800,1900 Test system	TS8950G		R&S	2005/11/1	2006/10/31
ETSTW-GSM 12	Acoustical Calibrator	4231	2463874	Brüel&Kjær	2005/10/31	2006/10/30
ETSTW-GSM 13	Conditioning Amplifier	2690--0S2	2437856	Brüel&Kjær		
ETSTW-GSM 14	Telephone Test Head	4602B	2465324	Brüel&Kjær		
ETSTW-GSM 15	Mouth Simulator	4227	2462516	Brüel&Kjær		



Registration number: W6M20603-6643-P-15
FCC ID : QQGBT1022

ETSTW-GSM 16	TEMP.&HUMIDITY CHAMBER	GTH-120-40-1P-U	MAA0501002	GIANT FORCE	2005/12/29	2006/12/28
ETSTW-GSM 17	ANTENNT COPLER	CMU-Z10	100988	R&S		
ETSTW-GSM 18	AUDIO ANALYZER	UPL16	100173	R&S	2005/10/29	2006/10/28
ETSTW-GSM 19	Band Reject Filter	WRCTF824/849-822/851-40 /12+9SS	3	WI		
ETSTW-GSM 20	Band Reject Filter	WRCD1747/1748-1743/1752-32/5SS	1	WI		
ETSTW-GSM 21	Band Reject Filter	WRCD1879.5/1880.5-1875.5/1884.5-32/5SS	3	WI		
ETSTW-GSM 22	Band Reject Filter	WRCT901.9/903.1-904.25-50/8SS	1	WI		
ETSTW-GSM 23	SPLITTER	4901.19.A	None	SUHNER		
ETSTW-GSM 24	Vibration Testing System	VS-100V	5494	Vibration	2005/12/20	2006/12/19

Registration number: W6M20603-6643-P-15
FCC ID : QQGBT1022

2.4 General Test Procedure

POWER LINE CONDUCTED INTERFERENCE: The procedure used was ANSI STANDARD C63.4-2003 using a 50 μ H LISN (if necessary). Both lines were observed. The bandwidth of the spectrum analyzer was 10 kHz with an appropriate sweep speed.

RADIATION INTERFERENCE: The test procedure used was according to ANSI STANDARD C63.4-2003 employing a spectrum analyzer. For investigated frequency is equal to or below 1GHz, the RBW and VBW of the spectrum analyzer was 100 kHz and 100kHz respectively with an appropriate sweep speed. For investigated frequency is above 1GHz, both of RBW and VBW of the spectrum analyzer were 1 MHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The ambient temperature of the UUT was 23°C with a humidity of 40 %.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dB μ V) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB.

Example:

Freq (MHz)	METER READING + ACF + CABLE LOSS (to the receiver) = FS
33	20 dB μ V + 10.36 dB + 6 dB = 36.36 dB μ V/m @3m

The UUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m (non metallic table) and arranged according to ANSI C63.4-2003 Section 13.1.2. The table used for radiated measurements is capable of continuous rotation. The spectrum was scanned from 30 MHz to the frequency specified as follows:

- (1) If the intentional radiator operates below 10 GHz: to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
- (2) If the intentional radiator operates at or above 10 GHz and below 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 100 GHz, whichever is lower.
- (3) If the intentional radiator operates at or above 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 200 GHz, whichever is lower, unless specified otherwise elsewhere in the rules.
- (4) If the intentional radiator contains a digital device, regardless of whether this digital device controls the functions of the intentional radiator or the digital device is used for additional control or function purposes other than to enable the operation of the intentional radiator, the frequency range shall be investigated up to the range specified in paragraphs (a)(1)-(a)(3) of this section or the range applicable to the digital device, as shown in paragraph (b)(1) of this Section, whichever is the higher frequency range of investigation.

For hand-held devices, a exploratory test was performed with three (3) orthogonal planes to determine the highest emissions.

Measurements were made by ETS Dr. Genz Taiwan PS Co., Ltd. at the registered open field test site located No.5-1, Shuang Sing Village, LiShuei Rd., Wanli Township, Taipei County 207, Taiwan (R.O.C.). The Registration Number: 930600.

Registration number: W6M20603-6643-P-15
FCC ID : QQGBT1022

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

When the radiated emission limits are expressed in terms of the average value of the emission, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.

The formula is as follows:

Average = Peak + Duty Factor

Duty Factor = $20 \log (\text{dwell time}/T)$

$T = 100\text{ms}$ when the pulse train period is over 100 ms or the period of the pulse train.

Modified Limits for peak according to 15.35 (b) = Max Permitted average Limits + 20dB

ANTENNA & GROUND:

This unit uses Chip Antenna.

Registration number: W6M20603-6643-P-15
FCC ID : QQGBT1022

3 Test results (enclosure)

TEST CASE	Para. Number	Required	Test passed	Test failed
Peak Output Power	15.247(b)	☒	☒	☐
Equivalent radiated Power	15.247(b)	☒	☒	☐
Spurious Emissions radiated – Transmitter operating	15.247(c)	☒	☒	☐
Spurious Emissions conducted – Transmitter operating	15.247	☐	☐	☐
Carrier Frequency Separation	15.247(a) (1)	☒	☒	☐
Number of Hopping Frequencies	15.247(a) (1)(i)	☒	☒	☐
Time of Occupancy (Dwell Time)	15.247(a) (1)(i)	☒	☒	☐
20 dB Bandwidth	15.247(a) (1)(i)	☒	☒	☐
Band-edge Compliance of RF Emission	15.247(c)	☒	☒	☐
Radiated Emission from Digital Part And Receiver L.O.	15.109	☒	☒	☐
Power Line Conducted Emission	15.207(a)	☒	☒	☐

The follows is intended to leave blank.

Registration number: W6M20603-6643-P-15
FCC ID : QQGBT1022

3.1 Peak Output Power (transmitter)

FCC Rule: 15.247

This measurement applies to equipment with an integral antenna and to equipment with an antenna connector and equipped with an antenna as declared by the applicant.

The power was measured with modulation (declared by the applicant).

(Normal Mode)

Test conditions		Conducted Power		
		Channel A [dBm]	Channel B [dBm]	Channel C [dBm]
$T_{nom} = 23^{\circ}\text{C}$	$V_{nom} = 120\text{ V}$	-2.09	-1.51	-0.22
Measurement uncertainty		< 3 dB		

(EDR Mode)

Test conditions		Conducted Power		
		Channel A [dBm]	Channel B [dBm]	Channel C [dBm]
$T_{nom} = 23^{\circ}\text{C}$	$V_{nom} = 120\text{ V}$	-2.28	-0.66	-1.09
Measurement uncertainty		< 3 dB		

Test conditions		Radiated Power		
		Channel A [dBm]	Channel B [dBm]	Channel C [dBm]
$T_{nom} = 23^{\circ}\text{C}$	$V_{nom} = 120\text{ V}$	--	--	--
Measurement uncertainty		< 3 dB		

Registration number: W6M20603-6643-P-15
FCC ID : QQGBT1022

Test conditions $T_{nom} = 23^{\circ}\text{C}$, $V_{nom} = 120\text{ V}$ Frequency[MHz]	Signal Field strength TX highest power mode dB $\mu\text{V/m}$
2402	91.32
Measurement uncertainty	< 3 dB

The diagrams for the field strength measurements are included in Appendix.

Maximum Peak Output Power

Limits:

Frequency MHz	Number of hopping channels			
	≥ 75	≥ 50	$49 \geq 25$	$74 \geq 15$
902-928		30 dBm	24 dBm	
2400-2483.5 MHz	30 dBm	-		21 dbm
5725-5850 MHz	30 dBm	-		

In case of employing transmitter antennas having antenna gain >dBi and using fixed poin-to point operation consider §15.247 (b)(4).

Test equipment used: ETSTW-RE 003, ETSTW-RE 012, ETSTW-RE 017, ETSTW-RE 024

Registration number: W6M20603-6643-P-15
FCC ID : QQGBT1022

3.2 Equivalent isotropic radiated power

FCC Rule: 15.239(b), 15.35

Because using an internal antenna there are no deviations from the radiated test results according 3.1.

3.2.1 Transmitter

Integral Antenna:

At the transmitter the measurement was transacted with the modulation declared by the manufacturer and the maximum available output power of the EUT.

In this arrangement the EUT fulfils the requirements of the FCC rules § 15.247, subpart C, section b. This unit uses an internal antenna. There is no provision for an external antenna (see photo).

3.3 RF Exposure Compliance Requirements

According to Supplement C, Edition 01-01 to OET Bulletin 65, Edition 97-01 this spread spectrum transmitter is categorically excluded from routine environmental evaluation because of the low power level, where there is a high likelihood of compliance with RF exposure standards.

The antenna used for this Bluetooth transceiver module must not be co-located or operating in conjunction with any other antenna or transmitter.

3.4 Out of Band Radiated Emissions

FCC Rule: 15.247(c) , 15.35

For out of band emissions that are close to or that exceed the 20 dB attenuation requirement described in the specification, radiated measurements were performed at a 3 m separation distance to determine whether these emissions complied with the general radiated emission requirement.

Limits:

For frequencies below 1GHz :

Max. reading – 20 dB

$91.32 \text{ dB}\mu\text{V/m} - 20 \text{ dB} = 71.32 \text{ dB}\mu\text{V/m}$

Guidance on Measurement of FHSS Systems:

“If the emission is pulsed, modify the unit for continuous operation , use the settings shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation.” Here the correction was added to the limit instead subtracted from the reading.

Duty Cycle correction = $20 \log (\text{dwell time}/100\text{ms})$

For frequencies above 1GHz (Peak measurements).

Limit = max. aver. reading-20dB +20dB(because Peak detector is used)

$71.32 \text{ dB}\mu\text{V/m}$

For frequencies above 1GHz (Average measurements).

Max. reading – 20 dB - duty cycle correction:

No duty cycle correction was added to the reading

$91.32 \text{ dB}\mu\text{V/m} - 20 \text{ dB} = 71.32 \text{ dB}\mu\text{V/m}$

Remarks: See attached diagrams.

Test equipment used: ETSTW-CE 003 , ETSTW-RE 003

Registration number: W6M20603-6643-P-15
FCC ID : QQGBT1022

3.5 Transmitter Radiated Emissions in restricted Bands

FCC Rules: 15.247 (c), 15.205, 15.209, 15.35

Radiated emission measurements were performed from 30 MHz to 26000 MHz.

For radiated emission tests, the analyzer setting was as followings:

RES BW VID BW

Frequency <1 GHz 100 kHz 100 kHz (Peak measurements)

Frequency >1 GHz 1 MHz 1 MHz (Peak measurements)

1 MHz 1 MHz (Average measurements)

Limits:

For frequencies below 1GHz :

Frequency of Emission (MHz)	Field strength (microvolts/meter)	Field Strength (dB microvolts/meter)
30 – 88	100	40.0
88 – 216	150	43.5
216 – 960	200	46.0
Above 960	500	54.0

For frequencies above 1GHz (Average measurements).

Guidance on Measurement of FHSS Systems:

“If the emission is pulsed, modify the unit for continues operation , use the settings shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation.” Here the correction was added to the limit instead subtracted from the reading.

Duty cycle correction = $20 \log (\text{dwell time}/100\text{ms})$

For frequencies above 1GHz (Average measurements).

Limit – duty cycle correction

No duty cycle correction was added to the reading.

54.0dB μ V/m

For frequencies above 1GHz (Peak measurements).

Limit + 20dB

54.0dB μ V/m + 20 dB= 74 dB μ V/m

Remarks: See attached diagrams.

Test equipment used: ETSTW-RE 003, ETSTW-RE 012, ETSTW-RE 015, ETSTW-RE 016,
ETSTW-RE 017, ETSTW-RE 024

3.6 Spurious emissions (tx)

Spurious emission was measured with modulation (declared by manufacturer).

In any 100 kHz bandwidth outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c))

SAMPLE CALCULATION OF LIMIT. All results will be updated by an automatic measuring system in accordance to point 2.3.

Calculation of test results:

Such factors like antenna correction, cable loss, external attenuation etc. are already included in the provided measurement results. This is done by using validated test software and calibrated test system according the accreditation requirements.

The peak and average spurious emission plots was measured with the average limits.

In the Table being listed the critical peak and average value an exhibit the compliance with the above calculated Limits.

If in the column's correction factor states a value then the max. Field strength in the same row is corrected by a value gained from the "Marker-Delta-Method" or the „Duty-Cycle Correction Factor“.

Summary table with radiated data of the test plots

Low Channel

Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBuV)	Correction Factor (dB)	Detector	Test Result (dBuV/m)	Compliance Limit (dBuV/m)	Margin (dB)	Table Azimuth (degree)
V	71.222445	27.56	11.27	PK	38.83	91.32	52.49	241
	432.464930	14.56	18.49	PK	33.05	91.32	58.27	177
	802.805611	14.01	25.16	PK	39.17	91.32	52.15	323
	1601.202405	49.36	-7.03	PK	42.33	54.0	31.67	169
	2400.0	60.05	2.06	PK	62.11	91.32	29.21	287
	4801.603206	46.27	4.44	PK	50.71	54.0	23.29	278

Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBuV)	Correction Factor (dB)	Detector	Test Result (dBuV/m)	Compliance Limit (dBuV/m)	Margin (dB)	Table Azimuth (degree)
H	82.124248	23.99	9.91	PK	33.90	91.32	57.42	233
	432.464930	20.57	18.49	PK	39.06	91.32	52.26	186
	802.805611	17.46	25.16	PK	42.62	91.32	48.70	328
	1603.206413	54.58	-7.04	PK	47.54	54.0	26.46	173
	2400.0	64.26	2.06	PK	66.32	91.32	25.0	289
	4803.60020	50.85	4.43	PK	55.28	74.0	18.72	243
	4803.60020	37.46	4.43	AV	41.89	54.0	12.11	243

Registration number: W6M20603-6643-P-15
FCC ID : QQGBT1022

Middle Channel


Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBuv)	Correction Factor (dB)	Detector	Test Result (dBuV/m)	Compliance Limit (dBuV/m)	Margin (dB)	Table Azimuth (degree)
V	71.222445	27.6	11.27	PK	38.87	91.32	52.45	260
	815.631263	15.04	25.43	PK	40.47	91.32	50.85	316
	1629.258517	48.21	-6.97	PK	41.24	91.32	50.08	149
	2377.555110	46.24	2.09	PK	48.33	54.0	25.67	291
	4881.763527	44.57	4.86	PK	49.43	54.0	24.57	288

Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBuv)	Correction Factor (dB)	Detector	Test Result (dBuV/m)	Compliance Limit (dBuV/m)	Margin (dB)	Table Azimuth (degree)
H	82.124248	27.74	9.91	PK	34.65	91.32	56.67	229
	814.028056	17.51	25.41	PK	42.92	91.32	48.4	310
	1627.254509	54.98	-6.96	PK	48.02	91.32	43.3	183
	2377.555110	48.76	2.09	PK	50.85	54.0	23.15	293
	4881.763527	45.72	4.86	PK	50.58	54.0	23.42	294

High Channel

Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBuv)	Correction Factor (dB)	Detector	Test Result (dBuV/m)	Compliance Limit (dBuV/m)	Margin (dB)	Table Azimuth (degree)
V	71.222445	27.81	11.27	PK	39.08	91.32	52.24	231
	828.456914	20.43	25.54	PK	45.97	91.32	45.35	319
	1653.306613	47.72	-6.75	PK	40.97	91.32	50.35	173
	2494.885772	46.44	-1.57	PK	44.87	54.0	29.13	296
	4953.907816	44.02	3.89	PK	47.91	54.0	26.09	399

Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBuv)	Correction Factor (dB)	Detector	Test Result (dBuV/m)	Compliance Limit (dBuV/m)	Margin (dB)	Table Azimuth (degree)
H	82.124248	25.09	9.91	PK	35.0	91.32	56.32	233
	828.456914	21.82	25.54	PK	47.36	91.32	43.96	324
	1653.306613	55.54	-6.75	PK	48.79	91.32	42.53	156
	2495.920842	52.06	-1.57	PK	50.49	54.0	23.51	297
	4953.907816	46.51	3.89	PK	50.40	54.0	23.6	292



Registration number: W6M20603-6643-P-15
FCC ID : QQGBT1022

All other not noted test plots do not contain significant test results in relation to the limits.

TEST RESULT (Transmitter): The unit DOES meet the FCC requirements.

Comment: see attached diagrams

Test equipment used: ETSTW-RE 003, ETSTW-RE 012, ETSTW-RE 015, ETSTW-RE 016,
ETSTW-RE 017, ETSTW-RE 024

Registration number: W6M20603-6643-P-15
FCC ID : QQGBT1022

3.7 Carrier Frequency Separation

Carrier Frequency Separation was measured with modulation (declared by manufacturer).

According to FCC rules part 15 subpart C §15.247 frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or 20 dB bandwidth of the hopping channel, whichever is greater.

Test conditions		Channel Separation	
		Channel B	Channel B+1
$T_{nom} = 23^{\circ}\text{C}$	$V_{nom} = 120\text{ V}$	1.00200401 MHz	
Measurement uncertainty		< 10 Hz	

Limits:

Frequency Range MHz	Limits	
	20 dB bandwidth < 25 kHz	20 dB bandwidth > 25 kHz
902-928	25 kHz	20 dB bandwidth
2400-2483.5 5725-5850.0	25 kHz	20 dB bandwidth

Test equipment used: ETSTW-CE 003, ETSTW-RE 003

Comment: see attached diagram

Registration number: W6M20603-6643-P-15
FCC ID : QQGBT1022

3.8 Number of Hopping Frequencies

According to FCC rules part 15 subpart C §15.247 frequency hopping systems operating in the 2400-2483.5 MHz band shall use at least 15 hopping frequencies. Frequency hopping systems in 5725-5850 MHz bands shall use least 75 hopping frequencies.

For frequency hopping systems operating in the 902-928 MHz band: if the 20dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies; if the 20dB bandwidth of the hopping channel 250 kHz or greater, the system shall use at least 25 hopping frequencies.

Test conditions		Operating Mode	Number of Channels
$T_{nom} = 23^{\circ}\text{C}$	$V_{nom} = 120\text{ V}$	normal transmitting	79
$T_{nom} = 23^{\circ}\text{C}$	$V_{nom} = 120\text{ V}$	Inquiry mode	32

Limits:

Frequency Range MHz	Limit			
	20dB Bandwidth		20dB Bandwidth < 250 kHz	20dB Bandwidth ≥ 250 kHz
	≤ 1MHz			
902-928 MHz			≥ 50	≥ 25
2400-2483.5	≥ 15	≥ 15		
5725-5850.0 MHz	≥ 75			

Test equipment used: ETSTW-CE 003 , ETSTW-RE 003

Comment: see attached diagrams

3.8.1 Pseudorandom Frequency Hopping Sequence

The generation of the hopping sequence is determined by the Bluetooth cord specification and complies with the FCC requirements.

3.8.2 Coordination of hopping sequences to other transmitters

According to the Bluetooth core specification V1.1 such a coordination is not possible. During scatternet function only one of the two hopping sequences will be used at a definite moment.

3.8.3 System Receiver Hopping Capability

According to the Bluetooth core specification. The system receivers shift frequencies in synchronization with the transmitted signals.

Registration number: W6M20603-6643-P-15
FCC ID : QQGBT1022

3.9 Time of Occupancy (Dwell Time)

Frequency hopping systems operating in the 5725-5850 MHz band shall use an average time of occupancy on any frequency not greater than 0.4 seconds within a 30 second period.

In 2400-2483,5 MHz band the average time of occupancy on any channel shall not be greater than 0,4 seconds multiplied by the number of hopping channels employed.

For frequency hopping systems operating in the 902-928 MHz band: if the 20dB bandwidth of the hopping channel is less than 250 kHz, the average time of occupancy on any frequency shall not greater than 0.4 seconds within a 20 second period; if the 20dB bandwidth of the hopping channel is 250 kHz or greater, the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period.

Test conditions	Operating mode	Measurement periode	Time of Occupancy
$T_{nom} = 23^{\circ}\text{C}$ $V_{nom} = 120\text{ V}$ Channel B	normal transmitting		141.8401635 ms
	inquiry mode		68.16 ms
Measurement uncertainty	< 1 μs		

Limits and measurement periods:

Frequency MHz	Number of channels	Measurement Periode	Limit
902 – 928	≥ 50	20 s	0,4 s
	$49 \geq 25$	10 s	0,4 s
2400 – 2483,5	≥ 15	0,4 s * number of used channels	0,4 s
5725- 5850	≥ 75	30 s	0,4s

Test equipment used: ETSTW-CE 003 , ETSTW-RE 003

Comment: See attached diagram, which show the On-time and the number of counted events during the measurement period

Registration number: W6M20603-6643-P-15

FCC ID : QQGBT1022

3.10 20dB Bandwidth

Frequency hopping systems operating in the 5725-5850 MHz bands shall use a maximum 20dB bandwidth of 1 MHz.

The 20dB bandwidth is measured on the lowest, middle and highest hopping channel.

For frequency hopping systems operating in the 902-928 MHz band the maximum 20dB bandwidth of the hopping channel is 500 kHz.

(Normal Mode)

Test conditions		20 dB Bandwidth		
		Channel A	Channel B	Channel C
$T_{\text{nom}} = 23^{\circ}\text{C}$	$V_{\text{nom}} = 120 \text{ V}$	969.93987976 kHz	961.92384770 kHz	961.92384770 kHz
Measurement uncertainty		< 10 Hz		

(EDR Mode)

Test conditions		20 dB Bandwidth		
		Channel A	Channel B	Channel C
$T_{\text{nom}} = 23^{\circ}\text{C}$	$V_{\text{nom}} = 120 \text{ V}$	1.307692308 MHz	1.314102564 MHz	1.314102564 MHz
Measurement uncertainty		< 10 Hz		

Limits:

Frequency Range / MHz	Number of channels	Limit
902-928	< 50	< 250 kHz
	$49 \geq 25$	$500 \text{ kHz} \geq 250 \text{ kHz}$
2400-2483.5	≥ 15	not determined
5725-5850	75	$\leq 1 \text{ MHz}$

Test equipment used: ETSTW-CE 003 , ETSTW-RE 003

Comment: see attached diagram

3.10.1 System Receiver Input Bandwidth

It is determined in the Bluetooth core specification. The value matches to the bandwidth of transmitter signal.

3.11 Band-edge Compliance of RF Emissions

According to FCC rules part 15 subpart C §15.247(c) in any 100 kHz bandwidth outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required.

In addition radiated emission which fall in the restricted bands, as defined in section 15.205(a), must also with the radiated emission limits.


(Normal Mode)

Test conditions		Attenuation at or outside band-edges	
		Single Frequency	
		Lower Band-edge	Upper Band-edge
$T_{nom} = 23^{\circ}\text{C}$	$V_{nom} = 120 \text{ V}$	--	--
Measurement uncertainty		< 100 Hz	

Test conditions		Attenuation at or outside band-edges	
		Hopping Frequency	
		Lower Band-edge	Upper Band-edge
$T_{nom} = 23^{\circ}\text{C}$	$V_{nom} = 120 \text{ V}$	38.35 dB	49.59 dB
Measurement uncertainty		< 100 Hz	

(EDR Mode)

Test conditions		Attenuation at or outside band-edges	
		Hopping Frequency	
		Lower Band-edge	Upper Band-edge
$T_{nom} = 23^{\circ}\text{C}$	$V_{nom} = 120 \text{ V}$	45.32 dB	44.30 dB
Measurement uncertainty		< 100 Hz	



Registration number: W6M20603-6643-P-15
FCC ID : QQGBT1022

Limits:

Frequency Range / MHz	Limit
902 –928	- 20 dB
2400 – 2483.5	
5725 - 5850	

Test equipment used: ETSTW-CE 003 , ETSTW-RE 003

Comment: see attached diagrams

3.12 Radiated Emissions from Receiver Section of Transceiver

FCC Rule: 15.109

Summary table with radiated data of the test plots

(RX)

Low Channel

Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBuv)	Correction Factor (dB)	Detector	Test Result (dBuV/m)	Compliance Limit (dBuV/m)	Margin (dB)	Table Azimuth (degree)
V	71.563126	26.41	12.09	PK	38.50	40	1.5	199
	432.464930	13.54	18.51	PK	32.05	46	13.95	190
	1601.202405	45.58	-7.03	PK	38.55	54	45.45	183
	2400.801603	33.31	2.06	PK	35.37	54	18.63	271

Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBuv)	Correction Factor (dB)	Detector	Test Result (dBuV/m)	Compliance Limit (dBuV/m)	Margin (dB)	Table Azimuth (degree)
H	82.464930	24.52	9.91	PK	34.43	40	5.57	197
	160.140281	16.50	15.46	PK	31.96	43.5	11.54	83
	432.464930	17.99	18.51	PK	36.50	46	9.5	181
	1601.202405	50.57	-7.03	PK	43.54	54	10.46	184
	2400.801603	38.85	2.06	PK	40.91	54	13.09	263

Middle Channel

Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBuv)	Correction Factor (dB)	Detector	Test Result (dBuV/m)	Compliance Limit (dBuV/m)	Margin (dB)	Table Azimuth (degree)
V	70.881764	26.28	12.11	PK	38.89	40	1.61	207
	432.464930	13.81	18.51	PK	32.32	46	13.68	200
	1625.250501	44.83	-6.95	PK	37.88	54	16.12	187

Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBuv)	Correction Factor (dB)	Detector	Test Result (dBuV/m)	Compliance Limit (dBuV/m)	Margin (dB)	Table Azimuth (degree)
H	82.464930	24.71	9.91	PK	34.62	40	5.38	203
	398.797595	18.47	17.76	PK	36.23	46	9.77	173
	1625.250501	50.03	-6.95	PK	43.08	54	10.92	191
	2436.873747	38.05	1.36	PK	39.41	54	14.59	241

Registration number: W6M20603-6643-P-15

FCC ID : QQGBT1022

High Channel

Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBuv)	Correction Factor (dB)	Detector	Test Result (dBuV/m)	Compliance Limit (dBuV/m)	Margin (dB)	Table Azimuth (degree)
V	70.541082	26.83	12.11	PK	38.49	40	1.51	223
	432.464930	14.26	18.51	PK	32.77	46	13.23	187
	1649.298597	43.61	-6.75	PK	36.86	54	17.14	184
	2478.957916	34.32	-0.23	PK	34.09	54	19.91	231

Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBuv)	Correction Factor (dB)	Detector	Test Result (dBuV/m)	Compliance Limit (dBuV/m)	Margin (dB)	Table Azimuth (degree)
H	82.464930	24.36	9.91	PK	34.27	40	5.73	213
	432.464930	18.78	18.51	PK	37.29	46	8.71	192
	1649.298579	46.05	-6.75	PK	39.30	54	14.7	192
	2478.957916	39.88	-0.23	PK	39.65	54	14.35	242

Registration number: W6M20603-6643-P-15
FCC ID : QQGBT1022

Summary table with radiated data of the test plots
(Digital)

Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBuv)	Correction Factor (dB)	Detector	Test Result (dBuV/m)	Compliance Limit (dBuV/m)	Margin (dB)	Table Azimuth (degree)	Antenna Height (cm)
V	70.95190381	20.85	12.11	QP	32.96	40	7.04	238	277
	432.464930	15.31	18351	PK	34.12	46	11.88	173	259
	802.805611	15.12	25.16	PK	40.28	46	5.72	292	299

Antenna Polarization	Frequency Marker (MHz)	Corrected Reading (dBuv)	Correction Factor (dB)	Detector	Test Result (dBuV/m)	Compliance Limit (dBuV/m)	Margin (dB)	Table Azimuth (degree)	Antenna Height (cm)
H	82.464930	25.87	9.91	PK	35.78	40	4.22	267	229
	192.164329	21.11	12.51	PK	33.62	43.5	9.88	83	123
	432.464930	15.61	18.51	PK	34.12	46	11.88	173	259
	802.80561	18.39	25.16	PK	43.55	46	2.45	296	307

Except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency of Emission (MHz)	Field Strength (microvolts/meter)	Field Strength (dBmicrovolts/meter)
30 – 88	100	40.0
88 – 216	150	43.5
216 – 960	200	46.0
Above 960	500	54.0

Test equipment used: ETSTW-RE 015, ETSTW-RE 016, ETSTW-RE 017, ETSTW-CS 001, ETSTW-RE 026, ETSTW-RE 003, ETSTW-RE 025

Comment: see attached diagram

3.13 Power Line Conducted Emission

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the table bellows with this provision shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminals.

This measurement was transact first with instrumentation using an average and peak detector and a 10 kHz bandwidth. If the peak detector achieves a calculated level, the measurement is repeated by an instrumentation using a quasi-peak detector.

Frequency	Level (dB μ V)	
	quasi-peak	average
150 kHz	lower limit line	Lower limit line

LISN Type	Frequency Marker (MHz)	Corrected Reading (dB μ V)	Correction Factor (dB)	Detector	Test Result (dB μ V)	Compliance Limit (dB μ V)	Margin
N	0.218	35.7	10.1	QP	45.8	62.8	17
	0.218	33.2	10.1	AV	43.3	52.8	9.8
	0.29	30.7	10.1	QP	40.8	60.52	19.72
	0.29	26.3	10.1	AV	36.4	50.52	14.12
	0.577	38.6	10.1	QP	48.7	56	7.3
	0.577	33.4	10.1	AV	43.5	46	2.5
	0.649	35.2	10.1	QP	45.3	56	10.7
	0.649	32.6	10.1	AV	42.7	46	3.3

LISN Type	Frequency Marker (MHz)	Corrected Reading (dB μ V)	Correction Factor (dB)	Detector	Test Result (dB μ V)	Compliance Limit (dB μ V)	Margin
L1	0.218	31.1	10.1	QP	41.2	62.8	21.6
	0.218	26.4	10.1	AV	36.5	52.8	16.3
	0.505	31.6	10.1	QP	41.7	56	14.3
	0.505	26.6	10.1	AV	36.7	46	9.3
	0.577	38.4	10.1	QP	48.5	56	7.5
	0.577	33.6	10.1	AV	43.7	46	2.3
	2.803	31.8	10.1	QP	41.9	56	14.1
	2.803	23.1	10.1	AV	33.2	46	12.8

Registration number: W6M20603-6643-P-15
FCC ID : QQGBT1022

Limits:

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi Peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

Test equipment used: ETSTW-CE 004, ETSTW-CE 001, ETSTW-RE 023

Comment: see attached diagram

Registration number: W6M20603-6643-P-15
FCC ID : QQGBT1022

Appendix

- A Peak Output Power
- B Spurious Emissions radiated
- C Carrier Frequency Separation
- D Number of Hopping Frequencies
- E Time of Occupancy (Dwell Time)
- F 20dB Bandwidth
- G Band-edge Compliance of RF Conducted Emissions
- H Radiated Emissions from Receiver Section of Transceiver
- I Power Line Conducted Emission
- J Pictures



Registration number: W6M20603-6643-P-15
FCC ID : QQGBT1022


Appendix A

Peak Output Power

The measurement diagram are wideband pre-scan results; only for reference.




Ref Lvl	Marker 1 [T1]	RBW	1 MHz	RF Att	10 dB
3.5 dBm	-2.09 dBm	VBW	1 MHz		
	2.40180361 GHz	SWT	200 ms	Unit	dBm



Title: MAX OUTPUT POWER CH 0
Date: 14.MAR.2006 15:50:04




Ref Lvl	Marker 1 [T1]	RBW	1 MHz	RF Att	10 dB
3.5 dBm	-1.51 dBm	VBW	1 MHz		
	2.44080361 GHz	SWT	200 ms	Unit	dBm



Title: MAX OUTPUT POWER CH39
Date: 14.MAR.2006 15:51:13



Ref Lvl	Marker 1 [T1]	RBW	1 MHz	RF Att	10 dB
3.5 dBm	-0.22 dBm	VBW	1 MHz		
	2.47985972 GHz	SWT	200 ms	Unit	dBm



Title: MAX OUTPUT POWER CH78
Date: 14.MAR.2006 15:52:20




*RBW 1 MHz
*VBW 1 MHz
*SWT 200 ms

Marker 1 [T1]
-2.28 dBm
2.401823718 GHz

Ref 10 dBm

*Att 5 dB

1 PK
MAXH



Center 2.402 GHz

1 MHz/

Span 10 MHz

MAX OUTPUT POWER CH0 EDR MODE

Date: 30.MAR.2006 06:36:51




*RBW 1 MHz
*VBW 1 MHz
*SWT 200 ms

Marker 1 [T1]
-0.66 dBm
2.440823718 GHz

Ref 10 dBm

*Att 5 dB

1 PK
MAXH



Center 2.441 GHz

1 MHz/

Span 10 MHz

MAX OUTPUT POWER CH39 EDR MODE

Date: 30.MAR.2006 06:37:57




*RBW 1 MHz
*VBW 1 MHz
*SWT 200 ms

Marker 1 [T1]
-1.09 dBm
2.479823718 GHz

Ref 10 dBm

*Att 5 dB

1 PK
MAXH



Center 2.48 GHz

1 MHz/

Span 10 MHz


MAX OUTPUT POWER CH78 EDR MODE

Date: 30.MAR.2006 06:41:14

Carrier power (Field Strength)

FCC RULES PART 15, SUBPART C


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 low channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL025
Freq: 2.402GHz, Emax: 86.51dBµV/m, RBW: 1MHz



Carrier power (Field Strength)

FCC RULES PART 15, SUBPART C


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 low channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL025
Freq: 2.402GHz, Emax: 91.32dBµV/m, RBW: 1MHz



Carrier power (Field Strength)

FCC RULES PART 15, SUBPART C


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 middle channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL025
Freq: 2.441GHz, Emax: 86.04dBµV/m, RBW: 1MHz



Carrier power (Field Strength)

FCC RULES PART 15, SUBPART C


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 middle channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL025
Freq: 2.441GHz, Emax: 89.69dBµV/m, RBW: 1MHz



Carrier power (Field Strength)

FCC RULES PART 15, SUBPART C


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 high channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL025
Freq: 2.480GHz, Emax: 84.17dBµV/m, RBW: 1MHz




Carrier power (Field Strength)

FCC RULES PART 15, SUBPART C

EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 high channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL025
Freq: 2.480GHz, Emax: 90.89dBµV/m, RBW: 1MHz





Registration number: W6M20603-6643-P-15
FCC ID : QQGBT1022

Appendix B


Spurious Emissions radiated

The measurement diagram are wideband pre-scan results; only for reference.

Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 low channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HK 116
Freq: 71.222MHz, Emax: 38.83dBμV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 low channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HK 116
Freq: 82.465MHz, Emax: 34.78dBμV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 low channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL 223,
Freq: 802.806MHz, Emax: 39.17dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 low channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL 223,
Freq: 802.806MHz, Emax: 42.62dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 low channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 2.400GHz, Emax: 62.11dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 low channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 2.400GHz, Emax: 66.32dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 low channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 7.743GHz, Emax: 52.24dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 low channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 4.802GHz, Emax: 55.07dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 low channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 12.000GHz, Emax: 48.06dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 low channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 11.615GHz, Emax: 48.36dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 low channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 17.844GHz, Emax: 52.24dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 low channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 17.844GHz, Emax: 52.75dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 low channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 24.354GHz, Emax: 50.96dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 low channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 26.432GHz, Emax: 51.35dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 middle channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HK 116
Freq: 71.222MHz, Emax: 38.87dBμV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 middle channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HK 116
Freq: 82.124MHz, Emax: 34.65dBμV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 middle channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL 223,
Freq: 815.631MHz, Emax: 40.47dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 middle channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL 223,
Freq: 814.028MHz, Emax: 42.92dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 middle channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 2.378GHz, Emax: 48.33dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 middle channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 2.378GHz, Emax: 50.85dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 middle channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 7.776GHz, Emax: 52.32dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 middle channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 7.383GHz, Emax: 52.29dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 middle channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 11.471GHz, Emax: 48.12dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 middle channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 11.735GHz, Emax: 48.38dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 middle channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 17.772GHz, Emax: 52.60dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 middle channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 17.880GHz, Emax: 52.29dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 middle channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 26.006GHz, Emax: 51.04dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 middle channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 26.415GHz, Emax: 51.85dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 high channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HK 116
Freq: 71.222MHz, Emax: 39.08dBμV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 high channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HK 116
Freq: 82.124MHz, Emax: 35.00dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 high channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL 223,
Freq: 828.457MHz, Emax: 45.97dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 high channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL 223,
Freq: 828.457MHz, Emax: 47.36dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 high channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 2.495GHz, Emax: 44.87dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 high channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 2.496GHz, Emax: 50.49dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 high channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 7.984GHz, Emax: 51.77dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 high channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 7.768GHz, Emax: 52.09dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 high channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 12.000GHz, Emax: 48.66dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 high channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 11.920GHz, Emax: 48.38dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 high channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 17.784GHz, Emax: 52.14dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 high channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 17.880GHz, Emax: 52.46dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 high channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 25.904GHz, Emax: 51.09dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C

EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 high channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 25.291GHz, Emax: 50.89dBμV/m, RBW: 1MHz






Registration number: W6M20603-6643-P-15
FCC ID : QQGBT1022

Appendix C

Carrier Frequency Separation



Title: FREQUENCY SPREADING BANDWIDTH CH38&CH39
Date: 14.MAR.2006 16:50:11



Registration number: W6M20603-6643-P-15
FCC ID : QQGBT1022


Appendix D

Number of Hopping Frequencies



Ref Lvl
3.5 dBm

RBW 300 kHz RF Att 10 dB
VBW 300 kHz
SWT 200 ms Unit dBm




Title: NUMBER OF HOPPING FREQUENCIES (CH:0-13)
Date: 14.MAR.2006 16:16:28



Ref Lvl
3.5 dBm

RBW 300 kHz RF Att 10 dB
VBW 300 kHz
SWT 200 ms Unit dBm




Title: NUMBER OF HOPPING FREQUENCIES (CH:14-38)
Date: 14.MAR.2006 16:18:28



Ref Lvl
3.5 dBm

RBW 300 kHz RF Att 10 dB
VBW 300 kHz
SWT 200 ms Unit dBm




Title: NUMBER OF HOPPING FREQUENCIES (CH:39-63)
Date: 14.MAR.2006 16:20:22



Ref Lvl
3.5 dBm

RBW 300 kHz RF Att 10 dB
VBW 300 kHz
SWT 200 ms Unit dBm




Title: NUMBER OF HOPPING FREQUENCIES (CH:64-78)
Date: 14.MAR.2006 16:22:13



Ref Lvl
3.5 dBm

RBW 300 kHz RF Att 10 dB
VBW 300 kHz
SWT 200 ms Unit dBm




Title: NUMBER OF HOPPING FREQUENCIES (MASTER INQUIRY MODE)
Date: 14.MAR.2006 16:26:22



Ref Lvl
3.5 dBm

RBW 300 kHz RF Att 10 dB
VBW 300 kHz
SWT 200 ms Unit dBm




Title: NUMBER OF HOPPING FREQUENCIES (MASTER INQUIRY MODE)
Date: 14.MAR.2006 16:27:32



Ref Lvl
3.5 dBm

RBW 300 kHz RF Att 10 dB
VBW 300 kHz
SWT 200 ms Unit dBm




Title: NUMBER OF HOPPING FREQUENCIES (MASTER INQUIRY MODE)
Date: 14.MAR.2006 16:58:05



Ref Lvl
3.5 dBm

RBW 300 kHz RF Att 10 dB
VBW 300 kHz
SWT 200 ms Unit dBm



Title: NUMBER OF HOPPING FREQUENCIES (MASTER INQUIRY MODE)
Date: 14.MAR.2006 16:45:06




Registration number: W6M20603-6643-P-15
FCC ID : QQGBT1022

Appendix E

Time of Occupancy (Dwell Time)



Ref Lvl 107 dBμV
Delta 1 [T1] 0.03 dB
382.318468 μs
RBW 1 MHz
VBW 1 MHz
SWT 480 μs
RF Att 10 dB
Unit dBμV




Center 2.441 GHz 48 μs/

Title: Time of occupancy (Hopping DH1) 371 events * 0.3823185 ms = 141.8401635 ms
Comment A: J-Three International Holding Co., Ltd.
Date: 15.Mar.2006 13:34:15



Ref Lvl 107 dBV
Delta 1 [T1] 0.36 dB
141.706200 μ s
RBW 1 MHz
VBW 1 MHz
SWT 480 μ s
RF Att 10 dB
Unit dBV



Center 2.441 GHz 48 μ s/

Title: Time of occupancy (Inquiry Mode) 141.706 μ s * 481 events = 68.16 ms
Comment A: J-Three International Holding Co., Ltd.
Date: 15.Mar.2006 13:40:47




Registration number: W6M20603-6643-P-15
FCC ID : QQGBT1022

Appendix F

20dB Bandwidth




Marker 1 [T1 ndB] RBW 50 kHz RF Att 10 dB
Ref Lvl ndB 20.00 dB VBW 100 kHz
3.5 dBm BW 969.93987976 kHz SWT 200 ms Unit dBm



Title: 20dB BANDWIDTH CH 0
Date: 14.MAR.2006 16:00:07




Ref Lvl	3.5 dBm	Marker 1 [T1 ndB]	ndB	20.00 dB	RBW	50 kHz	RF Att	10 dB
		BW	961.92384770 kHz		VBW	100 kHz	Unit	dBm
					SWT	200 ms		



Title: 20dB BANDWIDTH CH39
Date: 14.MAR.2006 16:00:38




Marker 1 [T1 ndB] RBW 50 kHz RF Att 10 dB
Ref Lvl ndB 20.00 dB VBW 100 kHz
3.5 dBm BW 961.92384770 kHz SWT 200 ms Unit dBm



Title: 20dB BANDWIDTH CH78
Date: 14.MAR.2006 16:01:19



1 PK
MAXH



20dB BANDWIDTH CH0 EDR MODE
Date: 30.MAR.2006 06:48:26




*RBW 50 kHz Marker 1 [T1]
*VBW 100 kHz -0.88 dBm
*SWT 200 ms 2.441006410 GHz

Ref 10 dBm

*Att 5 dB

1 PK
MAXH



Center 2.441 GHz

400 kHz/

Span 4 MHz

20dB BANDWIDTH CH39 EDR MODE

Date: 30.MAR.2006 06:47:43




*RBW 50 kHz Marker 1 [T1]
*VBW 100 kHz -1.37 dBm
*SWT 200 ms 2.480006410 GHz

Ref 10 dBm

*Att 5 dB

1 PK
MAXH



Center 2.48 GHz

400 kHz/

Span 4 MHz

20dB BANDWIDTH CH78 EDR MODE

Date: 30.MAR.2006 06:46:46




Registration number: W6M20603-6643-P-15
FCC ID : QQGBT1022

Appendix G

Band-edge Compliance of RF Conducted Emissions




Ref Lvl	Delta 1 [T1]	RBW	100 kHz	RF Att	10 dB
3.5 dBm	38.35 dB	VBW	100 kHz		
	1.99278557 MHz	SWT	200 ms	Unit	dBm



Title: BANEDGE COMPLIANCE CH 0 (CONDUCTY ,HOPPING MODE)
Date: 16.MAR.2006 16:10:50



Delta 1 [T1]	RBW	100 kHz	RF Att	10 dB
Ref Lvl	49.59 dB	VBW	100 kHz	
3.5 dBm	-3.49422846 MHz	SWT	200 ms	Unit dBm



Title: BANDEDGE COMPLIANCE CH78 (CONDUCTY ,HOPPING MODE)
Date: 16.MAR.2006 16:12:42




*RBW 100 kHz Marker 1 [T1]
*VBW 100 kHz -47.61 dBm
*SWT 200 ms 2.400000000 GHz

Ref 10 dBm

*Att 5 dB

1 PK
MAXH



Center 2.4 GHz

800 kHz/

Span 8 MHz

BANDEGE COMPLIANCE CH0 (CONDUCTY, HOPPING MODE) EDR MODE


Date: 30.MAR.2006 06:52:48



*RBW 100 kHz Marker 1 [T1]
*VBW 100 kHz -45.49 dBm
*SWT 200 ms 2.483500000 GHz

Ref 10 dBm

*Att 5 dB



Center 2.4819 GHz

800 kHz/

Span 8 MHz

BANDEDGE COMPLIANCE CH78 (CONDUCTY, HOPPING MODE) EDR MODE

Date: 30.MAR.2006 06:56:02



Registration number: W6M20603-6643-P-15
FCC ID : QQGBT1022

Appendix H


Radiated Emissions from Receiver Section of Transceiver

The measurement diagram are wideband pre-scan results; only for reference.

Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 low channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HK 116
Freq:71.563MHz Emax:38.50dBμV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 low channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HK 116
Freq:82.465MHz Emax:34.43dBμV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 low channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL 223, ampl.
Freq:972.745MHz Emax:35.06dBμV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 low channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL 223, ampl.
Freq:432.465MHz Emax:36.50dBμV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 low channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:1.601GHz Emax:38.55dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 low channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:1.601GHz Emax:43.54dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 low channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:7.431GHz Emax:46.29dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 low channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:7.976GHz Emax:46.97dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 low channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:11.928GHz Emax:51.30dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 low channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:11.928GHz Emax:51.25dBuV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 low channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:17.940GHz Emax:52.66dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 low channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:17.820GHz Emax:52.36dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 middle channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HK 116
Freq:70.882MHz Emax:38.39dBμV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 middle channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HK 116
Freq:82.465MHz Emax:34.62dBμV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 middle channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL 223, ampl.
Freq:972.745MHz Emax:35.32dBuV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 middle channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL 223, ampl.
Freq:432.465MHz Emax:36.41dBuV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 middle channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:1.625GHz Emax:37.88dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 middle channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:1.625GHz Emax:43.08dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 middle channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:7.992GHz Emax:46.07dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 middle channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:7.752GHz Emax:45.94dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 middle channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:11.992GHz Emax:50.82dBuV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 middle channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:11.735GHz Emax:51.50dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 middle channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:17.940GHz Emax:51.98dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 middle channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:17.796GHz Emax:52.51dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 high channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HK 116
Freq:70.541MHz Emax:38.49dBμV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 high channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HK 116
Freq:82.465MHz Emax:34.27dBμV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 high channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL 223, ampl.
Freq:918.236MHz Emax:35.57dBuV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 high channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL 223, ampl.
Freq:432.465MHz Emax:37.29dBuV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 high channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:1.649GHz Emax:37.34dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 high channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:2.479GHz Emax:39.65dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 high channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:7.703GHz Emax:46.27dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 high channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:7.776GHz Emax:46.05dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 high channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:11.912GHz Emax:51.31dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 high channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:11.976GHz Emax:51.32dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 high channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:17.760GHz Emax:52.38dBμV/m RBW: 1 MHz




Field Strength under normal conditions

FCC RULES PART 15, SUBPART B

EUT: Bluetooth 2.0 ClassII Module
MODEL NO.: BT1022 high channel
Approval Holder: J-Three International Holding Co., Ltd.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.4°C/ Unom.: 120 VAC(power on pc)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:17.820GHz Emax:52.50dBµV/m RBW: 1 MHz





Registration number: W6M20603-6643-P-15
FCC ID : QQGBT1022

Appendix I


Power Line Conducted Emission

The measurement diagram are wideband pre-scan results; only for reference.

EMI voltage test in the ac-mains according to FCC Part 15

Class B


EUT: Bluetooth 2.0 ClassII Module
Approval Holder: J-Three International Holding Co., Ltd.
Operating Condition: Unom: 120 VAC (Power on PC), Tnom: 25.6°C
Test Site: ETS
Operator: Orville
Test Specification: V-network: ESH3-Z5 N
Comment: model: BT1022 mode: active



EMI voltage test in the ac-mains according to FCC Part 15

Class B

EUT: Bluetooth 2.0 ClassII Module
Approval Holder: J-Three International Holding Co., Ltd.
Operating Condition: Unom: 120 VAC (Power on PC), Tnom: 25.6°C
Test Site: ETS
Operator: Orville
Test Specification: V-network: ESH3-Z5 L1
Comment: model: BT1022 mode: active





Registration number: W6M20603-6643-P-15
FCC ID : QQGBT1022

Appendix J

Pictures