

2.4GHz Wireless LAN PC Card

Model : SP-1001

Part 15.35(b)

Test Mode : Channel 1(11Mbps), peak detector.

Frequency (MHz)	Cable Loss(dB)	Antenna Factor(dB/m)	Polarity	Reading Level(dBuV)	Emission Level(dBuV/m)	Limit (dBuV/m)
4824.200	8.33	10.05	H	40.50	58.88	74.0
7236.600	10.8	12.11	H	41.50	64.11	74.0
9647.800	11.48	12.35	H	38.83	62.66	74.0
4824.200	8.33	10.05	V	40.33	58.71	74.0
7236.600	10.8	12.11	V	41.50	64.41	74.0
9648.400	11.48	12.35	V	42.33	66.16	74.0

Test Mode : Channel 6(11Mbps), peak detector.

Frequency (MHz)	Cable Loss(dB)	Antenna Factor(dB/m)	Polarity	Reading Level(dBuV)	Emission Level(dBuV/m)	Limit (dBuV/m)
4874.400	8.33	10.05	H	39.17	57.55	74.0
7310.700	10.8	12.11	H	40.33	63.24	74.0
9747.500	11.48	12.35	H	40.83	64.66	74.0
4874.400	8.33	10.05	V	39.00	57.38	74.0
7310.700	10.8	12.11	V	39.17	62.08	74.0
9747.500	11.48	12.35	V	41.50	65.33	74.0

Test Mode : Channel 11(11Mbps), peak detector.

Frequency (MHz)	Cable Loss(dB)	Antenna Factor(dB/m)	Polarity	Reading Level(dBuV)	Emission Level(dBuV/m)	Limit (dBuV/m)
4924.700	8.33	10.05	H	39.33	57.71	74.0
7385.730	10.8	12.11	H	42.00	64.91	74.0
9847.480	11.48	12.35	H	41.17	65.00	74.0
4924.600	8.33	10.05	V	39.00	57.38	74.0
7385.600	10.8	12.11	V	40.50	63.41	74.0
9847.820	11.48	12.35	V	41.33	65.16	74.0

Part 15.247(c)

Test Mode : Channel 11(11Mbps), peak detector.

Frequency (MHz)	Cable Loss(dB)	Antenna Factor(dB/m)	Polarity	Reading Level(dBuV)	Emission Level(dBuV/m)	Limit (dBuV/m)
2490.3	6.63	8.40	H	52.17	67.20	74.0
2483.7	6.63	8.40	V	48.67	63.0	74.0

Test Mode : Channel 11(11Mbps). Average detector.

Frequency (MHz)	Cable Loss(dB)	Antenna Factor(dB/m)	Polarity	Reading Level(dBuV)	Emission Level(dBuV/m)	Limit (dBuV/m)
2483.9	6.63	8.40	H	30.59	45.62	54.00
2490.0	6.63	8.40	V	33.63	48.66	54.00