



Operational Description

TR-6000, TR-SL2 Series
Wireless Network Adapter
Tranzeo Wireless Technologies Inc.

Date: January 19, 2007

Report No.: 190107.1

Lab: 19473 Fraser Way, Pitt Meadows, BC, Canada V3Y 2V4

A handwritten signature in black ink, appearing to read 'Cam Finnigan'.

Cam Finnigan
EMC Engineer

A handwritten signature in blue ink, appearing to read 'Sam Zahed'.

Sam Zahed
EMC Coordinator

A.1 Operational Description

The device is a wireless network bridge designed specifically for outdoor applications. The device provides a bridge between IEEE802.3 wired Ethernet LANs and IEEE802.11b/g compliant wireless networks. It uses an integrated antenna, or an external antenna in case of the TR-6000-N, coupled with an 802.11b/g transceiver to connect to remote wireless clients. The transceiver operates in the frequency band 2400-2483.5 MHz. The device transmits digital network data. The unit is mounted externally in fixed point-to-point installations. It is mounted on the exterior of a building typically for broadband internet access.

The type of RF modulation is DSSS and OFDM both used at 2.4 GHz. The device can transmit data at a bit rate of 11 Mbps in DSSS mode and 54 Mbps in OFDM mode or at a real-world data rate of approximately 4 and 27 Mbps respectively. A 128 bits Wired Equivalent Protection (WEP) algorithm is used for secure communications. The device's standard compliance ensures that it can communicate with any 802.11b/g network.

The firmware used with the device prevents the use of channels outside the specified frequency bands.

The product is used exclusively in a professionally installed, fixed point-to-point environment.